


FurseWELD

Cable to steel surface & pipe CS3 & CS7

Cable to steel surface & pipe CS3 - FurseWELD



Stranded/solid circular conductor size A (mm ²)	Mould part no.	Order code	Powder cartridge part no.	Handle clamp part no.
16 *	CS3-4-16	7TCA083910R2056	45P10	HCPK4
25	CS3-4-25	7TCA083910R2062	45P10	HCPK4
35	CS3-4-35	7TCA083910R2064	45P10	HCPK4
50	CS3-4-50	7TCA083910R2066	65P10	HCPK4
70	CS3-4-70	7TCA083910R2067	90P10	HCPK4
95	CS3-4-95	7TCA083910R2070	115P10	HCPK4
120	CS3-4-120	7TCA083910R2072	115P10	HCPK4
150	CS3-4-150	7TCA083910R2055	115P10	HCPK4
185	CS3-4-185	7TCA083910R2060	200P10	HCPK4
240	CS3-4-240	7TCA083910R2061	200P10	HCPK4
300	CS3-4-300	7TCA083910R2063	250P10	HCPK4

Special moulds for all FurseWELD products can be manufactured to meet specific customer applications on request

*1 x S103 Sleeve required when joining conductors 16 mm² or smaller


For order codes of powder cartridges and handle clamps, see page 49-50

FurseWELD moulds should only be used with FurseWELD powders, handle clamps and accessories. If moulds, powders, handle clamps and accessories from other manufacturers are utilized, we cannot guarantee the safe use or the integrity of the completed joint

FurseWELD moulds for use with stranded conductor are designed for use with non-compacted conductor to BS EN 60228. If a mould for compacted conductor is required, please contact your local representative

Conductors must be installed in the orientation shown to achieve the correct connection

Cable to steel surface & pipe CS7 - FurseWELD



Stranded/solid circular conductor size A (mm ²)	Mould part no.	Order code	Powder cartridge part no.	Handle clamp part no.
16 *	CS7-4-16	7TCA083910R2108	65P10	HCPK4
25	CS7-4-25	7TCA083910R2109	65P10	HCPK4
35	CS7-4-35	7TCA083910R2110	65P10	HCPK4
50	CS7-4-50	7TCA083910R2111	90P10	HCPK4
70	CS7-4-70	7TCA083910R2113	150P10	HCPK4
95	CS7-5-95	7TCA083910R2118	200P10	HCPK4
120	CS7-5-120	7TCA083910R2115	200P10	HCPK4
150	CS7-5-150	7TCA083910R2116	250P10	HCPK4
185	CS7-9-185	7TCA083910R2119	2 x 150P10	HCPK4
240	CS7-9-240	7TCA083910R2120	2 x 150P10	HCPK4
300	CS7-10-300	7TCA083910R3009	2 x 200P10	HCPK5

Special moulds for all FurseWELD products can be manufactured to meet specific customer applications on request

*1 x S103 Sleeve required when joining conductors 16 mm² or smaller

For order codes of powder cartridges and handle clamps, see pages 49-50

FurseWELD moulds should only be used with FurseWELD powders, handle clamps and accessories. If moulds, powders, handle clamps and accessories from other manufacturers are utilized, we cannot guarantee the safe use or the integrity of the completed joint

FurseWELD moulds for use with stranded conductor are designed for use with non-compacted conductor to BS EN 60228. If a mould for compacted conductor is required, please contact your local representative

Conductors must be installed in the orientation shown to achieve the correct connection