

- **PID controller with 'one shot' auto-tune**
 - single loop, heat/cool and ramp/soak as standard
- **Quick code, front face or PC configuration**
 - easy commissioning and operation using our Windows™-based software
- **Universal process input with transmitter power supply**
 - direct connection for any process signal
- **Hoseproof front panel and full noise immunity**
 - reliability in the harshest environments
- **RS485/Modbus serial communications**
 - SCADA, PLC and open systems integration



**C100 –
the easy-to use 1/8 DIN controller
with extensive capabilities**

C100

The C100 Universal Process controller is a highly versatile, **single loop controller** designed to be exceptionally easy to operate and set up.


Universal input and **integral transmitter power supply** ensure that the C100 has the capabilities to measure a wide range of process signals such as temperature, pressure, flow and level.


Analog, logic and relay control outputs are all fitted as standard, with the option to add further i/o capabilities such as additional relays, remote set point and digital input, to suit your application.

The **configuration** of the C100 is simply achieved by moving the security switch and entering a simple code from the front panel keys. No passwords, no input links, no complications.

With **hoseproof front panel protection** and superior RF immunity as standard the C100 has been designed to control reliably in the harshest of today's industrial environments.








PID Control


Simple PID control is available using any of the unit's three built-in outputs.

- 4 to 20mA analog
- Logic 18V time proportioning (to drive solid state relays)
- 5A relay for Time proportioning or On/Off control




Heat/Cool

Heat/Cool control strategies may be implemented on the standard C100, using a combination of the analog, logic and relay outputs.




Ramp/Soak Set Point Profiles

The ramp/soak facility available on every C100 provides for a single program, four-segment profile. This facility also includes guaranteed ramp/soak, repeat program, skip and reset.



Master/Slave and Cascade

Two or more C100s can be used in master/slave, or cascade, configuration with the addition of the remote set point option to the basic unit.



RS485/Modbus

Fitted with an optional RS485 serial communication board, the C100 can communicate with PLCs and SCADA systems using

Specification

Summary

P, PI, PID single loop controller
Autotune facility
Fully user configurable
Hoseproof front face

Operation

Display

High-intensity 7-segment, 2 x 4-digit LED display
Display range -999 to +9999
Display resolution ±1 digit
Display height 10mm (0.39 in.)

Configuration

User defined via front panel or PC Configurator

Standard Functions

Control types

Programmable for manual, on/off, time proportioning, current proportioning and heat/cool control.

Set points

Local
Remote
4 selectable fixed value
Ramping set point

Profile controller

Number 4 ramp/soak segments
Features Guaranteed ramp/soak, self seeking set point, program repeat
Controls Run, hold and stop from front panel switches
Run/hold or run/stop from digital input

Alarms

Number Two user-defined
Type High/low process
High/low deviation

...Specification

Analog Inputs

Number

- One as standard
- One optional (4 to 20mA remote set point input)

Input sampling rate

- 250ms per channel

Type

Universally configurable to provide (Channel 1 only):

- Thermocouple (THC)
- Resistance Thermometer (RTD)
- Millivolt
- Current
- DC voltage

Input impedance

- | | |
|-------|-------|
| mA | 100Ω |
| mV, V | >10MΩ |

Linearizer functions

- Programmable for standard inputs:
 - SqRoot, THC types B, E, J, K, N, R, S, T or Pt100

Broken sensor protection

- Upscale drive on THC and RTD
- Downscale drive on milliamps and voltage

Cold junction compensation

- Automatic CJC incorporated as standard
- Stability <0.05°C/°C change in ambient temperature

Input protection

- | | |
|-----------------------|---------------------------------------|
| Common mode isolation | >120dB at 50/60Hz with 300Ω imbalance |
| Series mode rejection | >60dB 50/60Hz |

Transmitter power supply

- 24V, 30mA max. powers one 2-wire transmitter

Standard Analog Input Ranges

Thermocouple	Maximum Range °C	Maximum Range °F	Accuracy (% of reading)
B	-18 to 1800	0 to 3270	0.25% or ±2°C (above 200°C)
E	-100 to 900	-140 to 1650	0.25% or ±0.5°C
J	-100 to 900	-140 to 1650	0.25% or ±0.5°C
K	-100 to 1300	-140 to 2350	0.25% or ±0.5°C
N	-200 to 1300	-325 to 2350	0.25% or ±0.5°C
R	-18 to 1700	0 to 3000	0.25% or ±1.0°C (above 300°C)
S	-18 to 1700	0 to 3000	0.25% or ±0.5°C (above 200°C)
T	-250 to 300	-400 to 550	0.25% or ±0.5°C

RTD	Maximum Range °C	Maximum Range °F	Accuracy (% of reading)
PT100	-200 to 600	-325 to 1100	0.25% or ±0.5°C

Linear Inputs	Range	Accuracy (% of reading)
Milliamps	0 to 20	0.25% or ±2µA
Milliamps	4 to 20	0.25% or ±2µA
Volts	0 to 5	0.25% or ±200µV
Volts	1 to 5	0.25% or ±200µV
Millivolts	0 to 50	0.25% or ±20µV

Square Root Input	Range	Accuracy (% of reading)
Milliamps	4 to 20	0.25% or ±2µA

Notes.

Performance accuracy is not guaranteed at extreme low end of thermocouple and sq. root ranges.
RTD, 3-wire platinum, 100Ω per DIN 43760 standard (IEC751), with range of 0 to 400Ω.

Min. span below zero Type T 70°C/126°F
 Type N 105°C/189°F

THC standards DIN 43710 IEC 584
 RTD standards DIN 43760 IEC 751

...Specification

Outputs

Control output/retransmission

Analog, configurable in the range of 4 to 20mA	
Max. load	15V (750Ω at 20mA)
Accuracy	≤0.25% of span
Dielectric	500V DC from I/P (not isolated from logic O/P)

Logic output

18V DC	at 20mA
Min. load	400Ω
Dielectric	500V DC from I/P (not isolated from control O/P)

Relay output

One relay as standard (SPDT) (5A @ 115/230V AC, 5A @ 24V DC)

Options

One option board can be installed from:

Type 1	One relay
Type 2	Two relays + one digital input + remote set point
Type 3	One relay + one digital input + remote set point + Modbus serial communications

Relay output

SPDT	5A @ 115/230V AC
------	------------------

Digital input

Type	Volt-free
Minimum pulse	250ms (not isolated from remote set point)

Modbus serial communications

Connections	RS422/485, 2 or 4-wire
Speed	2.4k or 9.6k baud rate
Protocol	Modbus RTU slave

Remote Set Point Input

4 to 20 mA DC, 100Ω nominal input impedance
Preset to process variable engineering units
(not isolated from digital inputs)

Physical

Size

48 wide x 96 high x 125mm
(1.89 in. wide x 3.78 in. high x 4.92 in.)

Weight

250g (0.5lb) approximate

Electrical

Voltage

85 to 265V AC (50/60Hz)
24V DC

Power consumption

< 6VA

Environmental

Operating limits

0 to 55°C (32 to 131°F)
5 to 95%RH non-condensing

Temperature stability

< 0.02% of reading or 2μV/°C (1μV/°F)

Front face

IP65 (NEMA3), case rear IP20

EMC

Emissions and Immunity

Meets requirements of IEC 61326 for an Industrial Environment


Design and manufacturing standards

CE Mark


Safety standards

EN61010 – 1
C22.2 No. 1010
UL 310 – 1
FM 3810


Dimensions



Electrical Connections




Thermocouple, Millivolts and Volts




Milliamps


(100 ohm shunt placed across Terminals 1 and 2)



3-Lead RTD




2-Lead RTD and Resistance



Milliamps using internal 2-wire transmitter power supply

(100Ω shunt placed across Terminals 1 and 2)



Ordering Guide

C100 1/8 DIN Process Controller		C100/	X	X	X	X	/	X	X	X	X	
Option Board	- None		0	0								
	- One additional relay		0	1								
	- Two additional relays + one digital input + remote set point 4 to 20mA		0	2								
	- One additional relay + one digital input + remote set point + RS485/Modbus		0	3								
Power Supply	85V to 265V AC		0									
	24V DC			1								
Build	Company Standard						0					
	CSA approval							1				
	UL approval								2			
	FM approval									4		
Progammng/Special Features	Configured to factory standard									S	T	D
	Configured to customer requirements									C	U	S
	Special features									S	P	X

Instrument Coding Example



ABB has Sales & Customer Support expertise in over 100 countries worldwide

www.abb.com

The Company's policy is one of continuous product improvement and the right is reserved to modify the information contained herein without notice.

Printed in UK (08.07)

© ABB 2007



ABB Limited
Howard Road, St. Neots
Cambridgeshire
PE19 8EU
UK
Tel: +44 (0)1480 475321
Fax: +44 (0)1480 217948

ABB Inc.
125 E. County Line Road
Warminster
PA 18974
USA
Tel: +1 215 674 6000
Fax: +1 215 674 7183