

CERTIFICATE OF COMPLIANCE

Certificate Number 20130926-E312527
Report Reference E312527-20130301
Issue Date 2013-SEPTEMBER-26

Issued to: ABB FRANCE
ACTIVITE PROTECTION ET CONTROL
3 RUE JEAN PERRIN
CS90009
69687 CHASSIEU CEDEX FRANCE


This is to certify that representative samples of MOTOR CONTROLLERS, MAGNETIC
SEE ADDENDUM PAGE

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.


Standard(s) for Safety: UL 60947-4-1A & CSA C22.2 NO 60947-4-1-07, Low-Voltage Switchgear and Controlgear – Part 4-1: Contactors and motor-starters – Electromechanical contactors and motor-starters

Additional Information: See the UL Online Certifications Directory at www.ul.com/database for additional information

Only those products bearing the UL Listing and Classification Marks should be considered as being covered by UL's Listing, Classification and Follow-Up Service.

The combined UL Listing and Classification Marks generally include the symbol UL in a circle:  with the word "LISTED"; a control number (may be alphanumeric) assigned by UL; and the product category name (product identifier) as indicated in the appropriate UL Directory and a statement "ALSO CLASSIFIED TO (extent of UL's evaluation of the product)".

Look for the UL Listing and Classification Mark on the product.



William R. Carney, Director, North American Certification Programs
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus



CERTIFICATE OF COMPLIANCE

Certificate Number 20130926-E312527
Report Reference E312527-20130301
Issue Date 2013-SEPTEMBER-26

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

USL, CNL, Magnetic motor controllers. Across-the-line reversing and non-reversing contactors for use in industrial applications, open type -


Cat. Nos. AF40, AF52, AF65, may be, followed by -30, may be followed by -00, -11, or -22, followed by 2 digits.

Cat. Nos. AF80, AF96, may be, followed by -30, may be followed by -00, -11, or -22, followed by 2 digits.

Cat. Nos. AF40R, AF52R, AF65R, AF80R, AF96R.

Cat. Nos. AF40M, AF52M, AF65M, AF80M, AF96M.

Cat. Nos. AF40N2, AF52N2, AF65N2, AF80N3, AF96N3.



William R. Carney, Director, North American Certification Programs
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus

