

# Automation Products

## AC500–S Safety PLC

### Product News: AI581-S Safety Analog Input Module

15.05.2013

#### AI581-S Safety analog input module

Ideal for applications like machinery safety, braking systems in hoists, position control in crane and selective shutdown in wind turbines involving safe control of

- Position
- Torque
- Pressure
- Temperature
- etc.



#### Key Features

- Supports SIL3 (IEC 61508, IEC 62061) and PL e (ISO 13849-1)
- High-speed dedicated analog current module with PROFINET/PROFIsafe functionality
- 4 safety current input channels up to SIL2 or PL d OR 2 safety current input channels up to SIL3 or PL e
- Could be configured for a range of 0 to 20 mA or 4 to 20 mA (1 or 2 channel mode)
- 14 bit A/D converter resolution with a LSB value of 2.03  $\mu$ A
- 0.33 ms for conversion cycle
- Extreme condition (XC) version for harsh environments
- Built-in over-voltage protection
- Input indication on LEDs (intensity change)
- Got approvals from CE, cUL, UL and C-Tick

Order Codes	Product Description
1SAP 282 000 R0001	Standard AI581-S module
1SAP 482 000 R0001	Extreme condition AI581-S-XC module

#### ABB Automation Products GmbH

Wallstadter Str. 59  
68526 Ladenburg,  
Germany  
Phone: +49 (0) 6221 701-1444  
Fax: +49 (0) 6221 701-1382  
Email: [plc.sales@de.abb.com](mailto:plc.sales@de.abb.com)  
[www.abb.com/plc](http://www.abb.com/plc)  
[www.abb.com/drives](http://www.abb.com/drives)

#### Note:

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB AG does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its contents – in whole or in parts – is forbidden without prior written consent of ABB AG.

Copyright© 2013 ABB - All rights reserved