

FUNCTIONAL OVERVIEW

## **EOW-i** Intelligent Extended Operator Workplace

Enhance operational efficiency and situational awareness with our patented solution<sup>1</sup>, designed to minimize downtime and optimize the operator environment.

01 EOW-i3 depicting the various customizable functions to suit the individual operator.

The operator's actions have a direct impact on uptime, production output, quality, and safety. EOW-i is designed to optimize operator efficiency by minimizing response time and supporting 24/7 operations.

The Extended Operator Workplace (EOW) offers unparalleled ergonomics, visualization and communication solutions for operators. The EOW-i ensures operator alertness, and when action is needed; keeps the essential functions at the operator's fingertips. In addition, the EOW-i supports the operator to work seamlessly and efficiently by having a smart keyboard that controls all three clients and screens.

## Effeciency and well-being in balance

02 Diagrams illustrating the functions of the EOW-i.

03 EOW-i3 with light grey topboard.

Everything is designed to support effective interaction and collaboration:

- · Plant visualization and information all in one view
- · Process overviews on close-by large interactive panels
- One fast-acting functional keyboard for controlling the complete operator environment.
- Supports the operators in working efficiently with process control system
- Enables better collaboration and optimization
- Improved work environment to appeal the next generation of operators.

The sets of monitors are mounted in a way that enable both a focused and a general view of operations.

Desk and monitor height, secondary monitors' angle, and depth of main monitors are motorized and adjustable, to ensure an ergonomic and customized operator environment. The personalized settings can be saved and automatically restored to fit each operator's preferences.

The EOW-i promotes proactive alertness, benefits the operator's health and ensures sustainability.



Large screen depth adjustability



Personal and public sound and lights



Save/Load multiple desk settings



Sturdy and durable, built for 24/7 operations



Desk settings, sound, and light touch controls



Integrated USB camera



Both Ultra Flex computers and KVM solutions available



Multi-client keyboard with touch screen



Optimized and ergonomic single operator environment



Other colors or specifications are available on request



04 EOW-i2 with birch topboard. EOW-i is available in two models: i2 and i3. Size and number of monitors are the main differences.

- Depth adjustable CLOV (Close Large OverView) with two/three 55<sup>"</sup> industrial LCD 4K-UHD 3840x2160 wide screens, with LED backlight
- Four/six 24" full HD monitors, with simultaneously adjustable monitor angle and depth
- Choose between: The KVM extender solution or integrated Ultra Flex computers
- All adjustable axes motorized, 100-240V 50-60Hz
- Adjustable "temperature" LED down-light
- Public Address (PA) sound speakers
- Personal sound shower
- Integrated USB camera
- Interchangable multi client keyboard with multiple languages available
- Separate power feed for desk motors, to ease connection via UPS feed
- USB fast charging station with a Type-A 12W port and a Type-C 60W port
- Cableport for additional cabling
- Personal settings that can be saved on an RFID tag
- Frame and columns in silver RAL 9006
- Level adjustable feet in grey RAL 7015
- High pressure laminate top board





abb.com new.abb.com/control-rooms All rights to other trademarks reside with their respective owners.

We reserve the right to make technical changes to the products or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not assume any responsibility for any errors or incomplete information in this document.

## EOW-i3


Total weight, including full sets of monitors: Approximately 850 kg






## EOW-i2

Total weight, including full sets of monitors: Approximately 750 kg





We reserve all rights to this document and the items and images it contains. The reproduction, disclosure to third parties or the use of the content of this document – including parts thereof – are prohibited without ABB's prior written permission.

Copyright© 2025 ABB All rights reserved