

CERTIFICATE OF COMPLIANCE

Certificate Number 20180302-E36588
Report Reference E36588-20000623
Issue Date 2018-MARCH-02

Issued to: ABB AB, CONTROL PRODUCTS
MOTORGRAND 20
SE-721 61 VASTERAS SWEDEN

This is to certify that representative samples of MOTOR CONTROLLERS, MAGNETIC
See Addendum Page.

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 60947-4-1 & CSA C22.2 NO 60947-4-1-14, Low-Voltage Switchgear and Controlgear – Part 4-1: Contactors and motor-starters– Electromechanical contactors and motor-starters

Additional Information: See the UL Online Certifications Directory at www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20180302-E36588
Report Reference E36588-20000623
Issue Date 2018-MARCH-02

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Open type, magnetic motor controllers and Type AF400, AF460, AFS400, AFS460, AF400F or AF460F, AF400W or AF460W followed by -30, followed by -00, -11, -22, -01, -10 may be followed by two additional suffixes. Type AF460N6, or AFS460N6, may be followed by -30, M or R, followed by -00, -11, -22, -01, -10 followed by two additional suffixes. Reversers, mechanical interlocked, open type, AF400 or AF460, followed by M or R, followed by -30, followed by -00, -11, -22, followed by additional suffixes indicating coil voltage.

USL, CNL - Accessories for AF400, AF460, AFS400, AFS460, AF460N6, AFS460N6 Contactors: Terminal shrouds Type Nos. LT460-AC, LT460-AL; Connection bars Type Nos. BEM460-30, BES460-30, BEA750/T6, BEA750/T5, BED400, BED460, LY460, LP460, LX460. Mechanical interlocks Type Nos. VM300/460H, VM300/460V, VM370/460 and VM750H. Terminal enlargement Type LW460.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/locations/>

