DATA SHEET

Date: 18.8.2015

Fusible heavy duty safety switch, single throw
EOH365RK

Electrical equipment should be installed, operated, serviced, and maintained only by qualified personnel. No responsibility is assumed by ABB for any consequences arising out of the use of this material.

Type	EOH365RK
Ordering number	1SCA132520R1001
EAN-code	6417019616353
Product Name	Fusible heavy duty safety switch, single throw
UL-file number	E314773
CSA-file number	58077
Country of Origin	Finland
Type of enclosure	NEMA Type 3R Rainproof
General purpose current rating 600V	400A
Number of poles	3
Net Weight	103.7lb / 47.029kg
Gross Weight	113.7lb / 51.571kg
Standards	UL98, UL50, UL4248-1, NEMA KS1, CSA
Instructions and manuals	34 EOH364-5-6JRS
Type of disconnect	OT400US30EOH
Switch operating torque	336.3lb.in / 38Nm
Min. Electrical endurance power factor 0.7 - 0.8	1500 op. cycles
Mechanical endurance	7500 op. cycles
Power loss / switch unit excluding fusegear	30W
Application ambient air temperature	-30°C/-22°F…40°C/104°F
Standard Power rating Three phase /240V	50HP / 37.3kW
Standard Power rating Three phase /480V	100HP / 74.6kW
Standard Power rating Three phase /600V	125HP / 93.25kW
Max. Power rating Three phase /240V	125HP / 93.25kW
Max. Power rating Three phase /480V	250HP / 186.5kW
Max. Power rating Three phase /600V	350HP / 261.1kW
Max. Power rating /250Vdc	50HP / 37.3kW
Max. motor FLA current Three phase /120-127V	260A
Max. motor FLA current Three phase /240V	312A
Max. motor FLA current Three phase /480V	302A
Max. motor FLA current Three phase /600V	336A
Maximum fuse size	400A
Fuse clips	Class H, K, RK1-5 to be equipped with field-installable rejection members, provision to relocate fuse base for class J, field-installable mounting kit for class T
Class RK fuses, short circuit rating 480Vac	200kA
Class J fuses, short circuit rating 480Vac	200kA
Class T fuses, short circuit rating 480Vac	200kA

Power and productivity for a better world™

© Copyright ABB

Fusible heavy duty safety switch, single throw
EOH365RK

Class RK fuses, short circuit rating 600Vac	100kA
Class J fuses, short circuit rating 600Vac	200kA
Class T fuses, short circuit rating 600Vac	200kA
Class H fuses, short circuit rating 600Vac	10kA
Class K fuses, short circuit rating 600Vac	50kA
Short circuit rating 250Vdc	100kA
Terminal lugs for line and load side terminals	Line side OZXA-800 / Load side OZXA-800E
Torque: Lug mounting line and load side terminals	480lb.in / 54.2Nm
Wire size 75°C Copper	2x500 kcmil
Wire size 75°C Copper Cross section	506mm²
Wire size 75°C Aluminium	2x500 kcmil
Wire size 75°C Aluminium Cross section	506mm²
Torque: line and load side wire tightening	500lb.in / 56.5Nm
Grounding terminal included in delivery	2xOZXG2
Grounding terminal wire range	250kcmil - AWG6
Torque: grounding wire tightening	275lb.in / 31.1Nm
Auxiliary contacts included	Field-installable auxiliary contacts mountable in switch mechanism are to be ordered separately.
Max. number of auxiliary contacts to be added	4no+4nc (early break)
Enclosure construction type	EOH5R Type 3R: Enclosures constructed for either indoor or outdoor use to provide a degree of protection to personnel against incidental contact with the enclosed equipment; to provide adegree of protection against falling dirt, rain, sleet, and snow; and that will be undamaged by the external formation of ice on the enclosure.
Cabling direction	TopBottom
Enclosure colour	ANSI 61 (light gray)
External Enclosure width/W	22.05in / 560mm
External Enclosure height/H	55.12in / 1400mm
External Enclosure depth/D	8.5in / 216mm
Cable outlets type	Concentric knockouts
Cable outlets / top (ølnch/mm)	3x(ø3.62/92+ø3/76.2+ø2.5/63.5+ø2/50.8+ø1.57/40)+2x(ø0.75/19.05+ø0.5/12.7)
Cable outlets / bottom (ølnch/mm)	3x(ø3.5/88.9+ø3/76.2+ø2.5/63.5+ø2/50.8+ø1.57/40)+2x(ø0.75/19.05+ø0.5/12.7)
Number of door hinges	3
Number of door locking latches	3
Enclosure material specification	Corrosion resistant steel, paint: polyester powder coating 70+/-10µm, material thickness: door 0.059in/1.5mm, enclosure 0.059in/1.5mm, fixing plates 0.118in/3mm, handle shield 0.059in/1.5mm.
Handle type	Side-operated, fully insulated
Handle color	Black grip with red position ON indicator
Handle material specification	Handle grip: metallic insert, glass reinforced polyamide (PA f1)/ Red handle indicator: polycarbonate (PC f1).
Type of packing	Environment friendly corrugated cardboard
Packingbox width	24.4in / 620mm
Packingbox heigth	59.1in / 1500mm
Packingbox depth	12in / 305mm
Additional information	Fusible heavy duty safety switch in painted steel sheet enclosure. Grounding bus is included. Padlockable in OFF-position with 3 padlocks of bail max. diameter 0.25in/6.4mm. Releasable door interlocking mechanism. Field-installable accessories and fuses are to be ordered separately. Factory mounted fuse base and clips for class H, K, RK1-5 fuses. Not for use as motor controller.
Description FI	Sulakkeellinen turvakytkin raskaaseen käyttöön
Description EN	Fusible heavy duty safety switch

Power and productivity for a better world™

Fusible heavy duty safety switch, single throw EOH365RK

Description FR	Interrupteur avec fusibles de sécurité pour service intensif
Description ES	Interruptor de seguridad de servicio pesado con fusibles

Technical information:
http://new.abb.com/low-voltage/launches/safetyswitches

UL Certificate of Compliance:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/762006113685b65fc1257d6200207c53/$file/UL%20certificate%20EOH.pdf

CSA Certificate of Compliance:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/8e61ba5de98778c9c1257d5e002e7422/$file/CSA%20Certificate%20EOH_%20EOHU_.pdf

Catalogue:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/fa1d5d4923ab6eddc1257da200370e6b/$file/1SCC340010C0201.pdf

Leaflet:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/c4e1234e4521d69ac1257c7b003240a2/$file/1SCC340007K0201.pdf

Instruction bulletin:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/32753b9528f44814c1257d230034a00e/$file/1SCC340032M1401.pdf

Drawing/PDF:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/2badd30f658b2eb4c1257c9800594efd/$file/Z13_EOH365JK.PDF

Drawing/IGES:
http://new.abb.com/low-voltage/launches/safetyswitches/fusible-safety-switches

Field-installable accessories:

Neutral assembly	EOHXSN56
Fuse mounting kits	EOHFBK5 for Class T 400A fuses
Fuse rejection member kits	EOHRM5R for Class RK1-5 fuses
Auxiliary contact NO type to be added	OA1G10
Auxiliary contact NC type to be added	OA3G01
Hubs	H050-TB, H125-TB, H150-TB, H200-TB, H250-TB, H300-TB
Condensation water outlet	YJTB3/M10

Replacement parts:

Terminal lugs for line and load side terminals	OZXA-800/3 Line side / OZXA-800E/3 Load side
Grounding terminal	OZXG2/2
Switch disconnect	OT400US30EOHR
Fuse base kits	EOHFBR5LU
Door locking mechanism	EOHLM4
Handle assembly	EOHH2

Technical and product support:
ABB OY Breakers and Switches
P.O.Box 622
FI-65101 Vaasa, Finland
Phone: +358 102211
e-Mail: switch.technicalservice@fi.abb.com

Sales in USA:
ABB Inc. / USA
16250 W Glendale Drive
New Berlin, WI 53151, USA
Phone: 888-385-1221
e-Mail: lvps.support@us.abb.com

Sales in Canada:
ABB Inc. / CANADA
2117, 32nd Avenue
Lachine, QC H8T 3J1, Canada
Phone: 514-420-3100
e-Mail: lvp.support@ca.abb.com

Power and productivity for a better world™

DATA SHEET

Date: 18.8.2015

Fusible heavy duty safety switch, single throw
EOH365RK

EOH365RK

A	57.48in	1460mm
B	20.16in	512mm
F	10.08in	256mm
O	5.2in	132mm
P	4.82in	122.5mm
G	1in	25.5mm
N	1.14in	29mm
K	0.55in	14mm
L	0.55in	14mm
M	0.98in	25mm
H	58.66in	1490mm
W	22.99in	584mm
W1	24.53in	623mm
D	8.5in	216mm
E	10.39in	264mm

EOH365RK KNOCKOUT INFORMATION
TOP ENDWALL OF ENCLOSURE

H horizontal	V vertical (see Note)	Ø Knockout hole diameter
7.05in/179mm	3.03in/77mm	0.5in/12.7mm 0.75in/19.1mm
11.77in/299mm	3.03in/77mm	0.5in/12.7mm 0.75in/19.1mm
4.69in/119mm	5.2in/132mm	1.75in/44.4mm 2in/50.8mm 2.46in/62.50mm 3.01in/76.5mm 3.62in/92mm
9.41in/239mm	5.2in/132mm	1.75in/44.4mm 2in/50.8mm 2.46in/62.50mm 3.01in/76.5mm 3.62in/92mm
14.13in/359mm	5.2in/132mm	1.75in/44.4mm 2in/50.8mm 2.46in/62.50mm 3.01in/76.5mm 3.62in/92mm

Note: Vertical dimension is from mounting surface.

EOH365RK KNOCKOUT INFORMATION
BOTTOM ENDWALL OF ENCLOSURE

H horizontal	V vertical (see Note)	Ø Knockout hole diameter
7.05in/179mm	3.03in/77mm	0.5in/12.7mm 0.75in/19.1mm
11.77in/299mm	3.03in/77mm	0.5in/12.7mm 0.75in/19.1mm
4.69in/119mm	5.2in/132mm	1.75in/44.4mm 2in/50.8mm 2.46in/62.50mm 3.01in/76.5mm 3.62in/92mm
9.41in/239mm	5.2in/132mm	1.75in/44.4mm 2in/50.8mm 2.46in/62.50mm 3.01in/76.5mm 3.62in/92mm
14.13in/359mm	5.2in/132mm	1.75in/44.4mm 2in/50.8mm 2.46in/62.50mm 3.01in/76.5mm 3.62in/92mm

Note: Vertical dimension is from mounting surface.

Power and productivity for a better world™

© Copyright ABB