DATA SHEET

Date: 18.8.2015

Fusible heavy duty safety switch, single throw
EOH367S

Electrical equipment should be installed, operated, serviced, and maintained only by qualified personnel. No responsibility is assumed by ABB for any consequences arising out of the use of this material.

Type	EOH367S
Ordering number	1SCA139039R1001
EAN-code	6417019670966
Product Name	Fusible heavy duty safety switch, single throw
UL-file number	E314773
CSA-file number	58077
Country of Origin	Finland
Type of enclosure	NEMA Type 4/4X Watertight
General purpose current rating 600V	800A
Number of poles	3
Net Weight	157.6lb / 71.475kg
Gross Weight	169.3lb / 76.778kg
Standards	UL98, UL50, UL4248-1, NEMA KS1, CSA
Instructions and manuals	34 EOH367-8JRS
Type of disconnect	OT800US30EOH
Switch operating torque	354lb.in / 40Nm
Min. Electrical endurance power factor 0.7 - 0.8	600 op. cycles
Mechanical endurance	3500 op. cycles
Power loss / switch unit excluding fusegear	36W
Application ambient air temperature	-30°C/-22°F…40°C/104°F
Standard Power rating Three phase /240V	100HP / 74.6kW
Standard Power rating Three phase /480V	200HP / 149.2kW
Standard Power rating Three phase /600V	250HP / 186.5kW
Max. Power rating Three phase /240V	250HP / 186.5kW
Max. Power rating Three phase /480V	500HP / 373kW
Max. Power rating Three phase /600V	500HP / 373kW
Max. Power rating /250Vdc	50HP / 37.3kW
Max. motor FLA current Three phase /240V	600A
Max. motor FLA current Three phase /480V	590A
Max. motor FLA current Three phase /600V	472A
Maximum fuse size	800A
Fuse clips	Class L
Class L fuses, short circuit rating 480Vac	200kA
Class L fuses, short circuit rating 600Vac	200kA
Short circuit rating 250Vdc	100kA
Terminal lugs for line and load side terminals	OZXA-1200
Torque: Lug mounting line and load side terminals	443lb.in / 50.1Nm
Wire size 75°C Copper	4x500 kcmil

Power and productivity for a better world™

© Copyright ABB

Fusible heavy duty safety switch, single throw
EOH367S

Wire size 75°C Copper Cross section	1012mm²
Wire size 75°C Aluminium	4x500 kcmil
Wire size 75°C Aluminium Cross section	1012mm²
Torque: line and load side wire tightening	500lb.in / 56.5Nm
Grounding terminal included in delivery	2xOZXG2
Grounding terminal wire range	250kcmil - AWG6
Torque: grounding wire tightening	275lb.in / 31.1Nm
Auxiliary contacts included	Field-installable auxiliary contacts mountable in switch mechanism are to be ordered separately.
Max. number of auxiliary contacts to be added	2no+2nc (early break)
Enclosure construction type	EOH7S Type 4/4X: Enclosures constructed for either indoor or outdoor use to provide a degree of protection to personnel against incidental contact with the enclosed equipment; to provide a degree of protection against falling dirt, rain, sleet, snow, windblown dust, splashing water, hose-directed water, and corrosion (4X); and that will be undamaged by the external formation of ice on the enclosure. Material AISI304.
Cabling direction	TopBottom
Enclosure colour	Unpainted stainless steel grade 304
External Enclosure width/W	22.05in / 560mm
External Enclosure height/H	62.68in / 1592mm
External Enclosure depth/D	8.54in / 217mm
Cable outlets type	Blank
Cable outlets / top (øInch/mm)	Blank
Cable outlets / bottom (øInch/mm)	Blank
Number of door hinges	3
Number of door locking latches	5
Enclosure material specification	Stainless steel AISI304 material thickness: door 0.079in/2mm, enclosure 0.079in/2mm, fixing plates 0.118in/3mm, handle shield 0.059in/1.5mm.
Handle type	Side-operated, fully insulated
Handle color	Black grip with red position ON indicator
Handle material specification	Handle grip: metallic insert, glass reinforced polyamide (PA f1)/ Red handle indicator: polycarbonate (PC f1).
Type of packing	Environment friendly corrugated cardboard
Packingbox width	24.4in / 620mm
Packingbox heigth	67.3in / 1710mm
Packingbox depth	12in / 305mm
Additional information	Fusible heavy duty safety switch in grade 304 unpainted stainless steel sheet enclosure. Grounding bus is included. Padlockable in OFF-position with 3 padlocks of bail max. diameter 0.25in/6.4mm. Releasable door interlocking mechanism. Factory-mounted fuse base and mounting screw kit for class L fuses are included. Field-installable accessories and fuses are to be ordered separately. Not for use as motor controller.
Description FI	Sulakkeellinen turvakytkin raskaaseen käyttöön
Description EN	Fusible heavy duty safety switch
Description FR	Interrupteur avec fusibles de sécurité pour service intensif
Description ES	Interruptor de seguridad de servicio pesado con fusibles

Power and productivity for a better world™ ABB

Fusible heavy duty safety switch, single throw EOH367S

Technical information:
http://new.abb.com/low-voltage/launches/safetyswitches

Catalogue:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/fa1d5d4923ab6eddc1257da200370e6b/$file/1SCC340010C0201.pdf

Leaflet:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/c4e1234e4521d69ac1257c7b003240a2/$file/1SCC340007K0201.pdf

Instruction bulletin:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/11915529ae2635d9c1257d230038db82/$file/1SCC340034M1401.pdf

Drawing/PDF:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/96ce81b465f62dd8c1257c9900204a98/$file/Z13_EOH367J.PDF

Drawing/IGES:
http://search-ext.abb.com/library/Download.aspx?DocumentID=EOH367J_R_S.igs&LanguageCode=en&DocumentPartId=&Action=Launch

Field-installable accessories:

Neutral assembly	EOHXSN78
Auxiliary contact NO type to be added	OA1G10
Auxiliary contact NC type to be added	OA3G01
Hubs	H075CP-TB, H100CP-TB, H125CP-TB, H200CP-TB, H250CP-TB, H300CP-TB, H350CP-TB, H400CP-TB

Replacement parts:

Terminal lugs for line and load side terminals	OZXA-1200/3
Grounding terminal	OZXG2/2
Switch disconnect	OT800US30EOHR
Fuse base kits	EOHFBL7
Door locking mechanism	EOHLM4
Handle assembly	EOHHS2

Technical and product support:
ABB OY Breakers and Switches
P.O.Box 622
FI-65101 Vaasa, Finland
Phone: +358 102211
e-Mail: switch.technicalservice@fi.abb.com

Sales in USA:
ABB Inc. / USA
16250 W Glendale Drive
New Berlin, WI 53151, USA
Phone: 888-385-1221
e-Mail: lvps.support@us.abb.com

Sales in Canada:
ABB Inc. / CANADA
2117, 32nd Avenue
Lachine, QC H8T 3J1, Canada
Phone: 514-420-3100
e-Mail: lvp.support@ca.abb.com

Power and productivity for a better world™

DATA SHEET

Date: 18.8.2015

Fusible heavy duty safety switch, single throw
EOH367S

EOH367S

A	65.43in	1662mm
B	20.16in	512mm
F	10.08in	256mm
O	5.2in	132mm
P	4.82in	122.5mm
G	1in	25.5mm
N	1.14in	29mm
K	0.55in	14mm
L	0.55in	14mm
M	0.98in	25mm
H	66.61in	1692mm
W	22.99in	584mm
W1	24.53in	623mm
D	8.5in	216mm
E	11.61in	295mm

EOH367S KNOCKOUT INFORMATION
TOP ENDWALL OF ENCLOSURE

No factory-made knockouts.
Drillings or cutting for purpose-made cabling accessories is allowed inside blank surface A:
Width: 17.08in / 434mm
Depth: 6.26in / 159mm
Note: Vertical dimension is from mounting surface.

EOH367S KNOCKOUT INFORMATION
BOTTOM ENDWALL OF ENCLOSURE

No factory-made knockouts.
Drillings or cutting for purpose-made cabling accessories is allowed inside blank surface B:
Width: 17.08in / 434mm
Depth: 6.26in / 159mm
Note: Vertical dimension is from mounting surface.

Power and productivity for a better world™ ABB

© Copyright ABB