DATA SHEET

Date: 18.8.2015

Non-fusible heavy duty safety switch, single throw
EOHU361S

Electrical equipment should be installed, operated, serviced, and maintained only by qualified personnel. No responsibility is assumed by ABB for any consequences arising out of the use of this material.

Type	EOHU361S
Ordering number	1SCA132025R1001
EAN-code	6417019611921
Product Name	Non-fusible heavy duty safety switch, single throw
UL-file number	E314773
CSA-file number	58077
Country of Origin	Finland
Type of enclosure	NEMA Type 4/4X Watertight
General purpose current rating 600V	30A
Number of poles	3
Net Weight	16.7lb / 7.59kg
Gross Weight	19.5lb / 8.865kg
Standards	UL98, UL50, NEMA KS1, CSA
Instructions and manuals	34 EOHU361-2-3JRS
Type of disconnect	OT30US30EOH
Switch operating torque	79.7lb.in / 9Nm
Min. Electrical endurance power factor 0.7 - 0.8	8000 op. cycles
Mechanical endurance	15000 op. cycles
Power loss / switch unit	0.3W
Application ambient air temperature	-30°C/-22°F…40°C/104°F
Max. Power rating Single phase /120-127V	2HP / 1.49kW
Max. Power rating Single phase /240V	3HP / 2.24kW
Max. Power rating Single phase /480V	7.5HP / 5.6kW
Max. Power rating Single phase /600V	10HP / 7.46kW
Max. Power rating Three phase /120-127V	3HP / 2.24kW
Max. Power rating Three phase /200-208V	2.24HP / 1.67kW
Max. Power rating Three phase /240V	10HP / 7.46kW
Max. Power rating Three phase /480V	20HP / 14.92kW
Max. Power rating Three phase /600V	30HP / 22.38kW
Max. Power rating /125Vdc	3HP / 2.2kW
Max. Power rating /250Vdc	5HP / 3.7kW
Max. motor FLA current Single phase /120-127V	24A
Max. motor FLA current Single phase /240V	17A
Max. motor FLA current Single phase /480V	21A
Max. motor FLA current Single phase /600V	20A
Max. motor FLA current Three phase /120-127V	19.2A
Max. motor FLA current Three phase /240V	22A
Max. motor FLA current Three phase /480V	21A

Power and productivity for a better world™

© Copyright ABB

Non-fusible heavy duty safety switch, single throw EOHU361S

Max. motor FLA current Three phase /600V	22A
Maximum fuse size	30A
Class RK fuses, short circuit rating 480Vac	200kA
Class J fuses, short circuit rating 480Vac	200kA
Class RK fuses, short circuit rating 600Vac	200kA
Class J fuses, short circuit rating 600Vac	200kA
Short circuit rating 250Vdc	100kA
Terminal lugs for line and load side terminals	OZXA-100
Torque: Lug mounting line and load side terminals	132lb.in / 14.9Nm
Wire size 60°C Copper	AWG8
Wire size 60°C Copper Cross section	8.4mm²
Wire size 60°C Aluminium	AWG8
Wire size 60°C Aluminium Cross section	8.4mm²
Wire size 75°C Copper	AWG8
Wire size 75°C Copper Cross section	8.4mm²
Wire size 75°C Aluminium	AWG8
Wire size 75°C Aluminium Cross section	8.4mm²
Torque: line and load side wire tightening	AWG8: 40 lb.in, AWG10-14: 35 lb.in / AWG8: 4.5 Nm, AWG10-14: 4 Nm
Grounding terminal included in delivery	2xOZXG1
Grounding terminal wire range	AWG2 - 14
Torque: grounding wire tightening	50lb.in / 5.6Nm
Auxiliary contacts included	Field-installable auxiliary contacts mountable in switch mechanism are to be ordered separately.
Max. number of auxiliary contacts to be added	2no+2nc (early break)
Enclosure construction type	EOHU1S Type 4/4X: Enclosures constructed for either indoor or outdoor use to provide a degree of protection to personnel against incidental contact with the enclosed equipment; to provide a degree of protection against falling dirt, rain, sleet, snow, windblown dust, splashing water, hose-directed water, and corrosion (4X); and that will be undamaged by the external formation of ice on the enclosure. Material AISI304.
Cabling direction	TopBottom
Enclosure colour	Unpainted stainless steel grade 304
External Enclosure width/W	12.09in / 307mm
External Enclosure height/H	9.17in / 233mm
External Enclosure depth/D	6.22in / 158mm
Cable outlets type	Blank
Cable outlets / top (øInch/mm)	Blank
Cable outlets / bottom (øInch/mm)	Blank
Number of door hinges	2
Number of door locking latches	2
Enclosure material specification	Stainless steel AISI304 material thickness: door 0.059in/1.5mm, enclosure 0.059in/1.5mm, fixing plates 0.118in/3mm, handle shield 0.059in/1.5mm.
Handle type	Side-operated, fully insulated
Handle color	Black grip with red position ON indicator
Handle material specification	Handle grip: glass reinforced polyamide (PA f1)/ Red handle indicator: polycarbonate (PC f1).
Type of packing	Environment friendly corrugated cardboard
Packingbox width	14.6in / 370mm
Packingbox heigth	13in / 330mm
Packingbox depth	9.3in / 235mm

Power and productivity for a better world™

© Copyright ABB

Non-fusible heavy duty safety switch, single throw EOHU361S

Additional information	Non-fusible heavy duty safety switch in grade 304 unpainted stainless steel sheet enclosure. Grounding bus is included. Padlockable in OFF-position with 3 padlocks of bail max. diameter 0.25in/6.4mm. Releasable door interlocking mechanism. Field-installable accessories are to be ordered separately.
Description FI	Sulakkeeton turvakytkin raskaaseen käyttöön
Description EN	Non-fusible heavy duty safety switch
Description FR	Interrupteur non fusibles de sécurité pour service intensif
Description ES	Interruptor de seguridad de Servicio Pesado sin fusibles

Technical information:
http://new.abb.com/low-voltage/launches/safetyswitches

Catalogue:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/fa1d5d4923ab6eddc1257da200370e6b/$file/1SCC340010C0201.pdf

Leaflet:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/c4e1234e4521d69ac1257c7b003240a2/$file/1SCC340007K0201.pdf

Drawing/IGES:
http://new.abb.com/low-voltage/launches/safetyswitches/fusible-safety-switches

Field-installable accessories:

Neutral assembly	EOHXSN13
Auxiliary contact NO type to be added	OA1G10
Auxiliary contact NC type to be added	OA3G01
Terminal cover Line side	OTS250G1S/3
Terminal cover Load side	OTS250G1S/3
Hubs	H075CP-TB, H100CP-TB, H125CP-TB, H200CP-TB, H250CP-TB

Replacement parts:

Terminal lugs for line and load side terminals	OZXA-100/3
Grounding terminal	OZXG1/2
Switch disconnect	OT30US30EOHR
Door locking mechanism	EOHLM2
Handle assembly	EOHHS1

Technical and product support:
ABB OY Breakers and Switches
P.O.Box 622
FI-65101 Vaasa, Finland
Phone: +358 102211
e-Mail: switch.technicalservice@fi.abb.com

Sales in USA:
ABB Inc. / USA
16250 W Glendale Drive
New Berlin, WI 53151, USA
Phone: 888-385-1221
e-Mail: lvps.support@us.abb.com

Sales in Canada:
ABB Inc. / CANADA
2117, 32nd Avenue
Lachine, QC H8T 3J1, Canada
Phone: 514-420-3100
e-Mail: lvp.support@ca.abb.com

Power and productivity for a better world™

DATA SHEET

Date: 18.8.2015

Non-fusible heavy duty safety switch, single throw
EOHU361S

EOHU361S

A	10.75in	273mm
B	10.59in	269mm
F	5.28in	134mm
G	1.1in	28mm
N	0.83in	21mm
K	0.35in	9mm
L	0.35in	9mm
M	0.75in	19mm
H	11.54in	293mm
H1	12.4in	315mm
W	12.8in	336mm
W1	14.49in	368mm
D	6.14in	160mm
E	8.7in	229mm

EOHU361S KNOCKOUT INFORMATION
TOP ENDWALL OF ENCLOSURE

No factory-made knockouts.

Drillings or cutting for purpose-made cabling accessories is allowed inside blank surface A:

Width: 7.12in / 181mm

Depth: 3.82in / 97mm

Note: Vertical dimension is from mounting surface.

EOHU361S KNOCKOUT INFORMATION
BOTTOM ENDWALL OF ENCLOSURE

No factory-made knockouts.

Drillings or cutting for purpose-made cabling accessories is allowed inside blank surface B:

Width: 7.12in / 181mm

Depth: 3.82in / 97mm

Note: Vertical dimension is from mounting surface.

Power and productivity for a better world™