DATA SHEET

Date: 18.8.2015

Non-fusible heavy duty safety switch, single throw
EOHU365S

Electrical equipment should be installed, operated, serviced, and maintained only by qualified personnel. No responsibility is assumed by ABB for any consequences arising out of the use of this material.

Type	EOHU365S
Ordering number	1SCA132029R1001
EAN-code	6417019611969
Product Name	Non-fusible heavy duty safety switch, single throw
UL-file number	E314773
CSA-file number	58077
Country of Origin	Finland
Type of enclosure	NEMA Type 4/4X Watertight
General purpose current rating 600V	400A
Number of poles	3
Net Weight	84.9lb / 38.5kg
Gross Weight	93.2lb / 42.294kg
Standards	UL98, UL50, NEMA KS1, CSA
Instructions and manuals	34 EOHU364-5-6JRS
Type of disconnect	OT400US30EOH
Switch operating torque	336.3lb.in / 38Nm
Min. Electrical endurance power factor 0.7 - 0.8	1500 op. cycles
Mechanical endurance	7500 op. cycles
Power loss / switch unit	30W
Application ambient air temperature	-30°C/-22°F…40°C/104°F
Max. Power rating Three phase /240V	125HP / 93.25kW
Max. Power rating Three phase /480V	250HP / 186.5kW
Max. Power rating Three phase /600V	350HP / 261.1kW
Max. Power rating /250Vdc	50HP / 37.3kW
Max. motor FLA current Three phase /120-127V	260A
Max. motor FLA current Three phase /240V	312A
Max. motor FLA current Three phase /480V	302A
Max. motor FLA current Three phase /600V	336A
Maximum fuse size	400A
Class RK fuses, short circuit rating 480Vac	200kA
Class J fuses, short circuit rating 480Vac	200kA
Class T fuses, short circuit rating 480Vac	200kA
Class RK fuses, short circuit rating 600Vac	100kA
Class J fuses, short circuit rating 600Vac	200kA
Class T fuses, short circuit rating 600Vac	200kA
Short circuit rating 250Vdc	100kA
Terminal lugs for line and load side terminals	Line side OZXA-800 / Load side OZXA-800E
Torque: Lug mounting line and load side terminals	480lb.in / 54.2Nm

Power and productivity for a better world™

© Copyright ABB

Non-fusible heavy duty safety switch, single throw EOHU365S

Wire size 75°C Copper	2x500 kcmil
Wire size 75°C Copper Cross section	506mm²
Wire size 75°C Aluminium	2x500 kcmil
Torque: line and load side wire tightening	500lb.in / 56.5Nm
Grounding terminal included in delivery	2xOZXG2
Grounding terminal wire range	250kcmil - AWG6
Torque: grounding wire tightening	275lb.in / 31.1Nm
Auxiliary contacts included	Field-installable auxiliary contacts mountable in switch mechanism are to be ordered separately.
Max. number of auxiliary contacts to be added	4no+4nc (early break)
Enclosure construction type	EOHU5S Type 4/4X: Enclosures constructed for either indoor or outdoor use to provide a degree of protection to personnel against incidental contact with the enclosed equipment; to provide a degree of protection against falling dirt, rain, sleet, snow, windblown dust, splashing water, hose-directed water, and corrosion (4X); and that will be undamaged by the external formation of ice on the enclosure. Material AISI304.
Cabling direction	TopBottom
Enclosure colour	Unpainted stainless steel grade 304
External Enclosure width/W	22.05in / 560mm
External Enclosure height/H	39.96in / 1015mm
External Enclosure depth/D	8.46in / 215mm
Cable outlets type	Blank
Cable outlets / top (øInch/mm)	Blank
Cable outlets / bottom (øInch/mm)	Blank
Number of door hinges	2
Number of door locking latches	2
Enclosure material specification	Stainless steel AISI304 material thickness: door 0.059in/1.5mm, enclosure 0.059in/1.5mm, fixing plates 0.118in/3mm, handle shield 0.059in/1.5mm.
Handle type	Side-operated, fully insulated
Handle color	Black grip with red position ON indicator
Handle material specification	Handle grip: metallic insert, glass reinforced polyamide (PA f1)/ Red handle indicator: polycarbonate (PC f1).
Type of packing	Environment friendly corrugated cardboard
Packingbox width	24.6in / 625mm
Packingbox heigth	43.9in / 1115mm
Packingbox depth	12in / 305mm
Additional information	Non-fusible heavy duty safety switch in grade 304 unpainted stainless steel sheet enclosure. Grounding bus is included. Padlockable in OFF-position with 3 padlocks of bail max. diameter 0.25in/6.4mm. Releasable door interlocking mechanism. Field-installable accessories are to be ordered separately. Not for use as motor controller.
Description FI	Sulakkeeton turvakytkin raskaaseen käyttöön
Description EN	Non-fusible heavy duty safety switch
Description FR	Interrupteur non fusibles de sécurité pour service intensif
Description ES	Interruptor de seguridad de Servicio Pesado sin fusibles

Power and productivity for a better world™

Non-fusible heavy duty safety switch, single throw EOHU365S

Technical information:
http://new.abb.com/low-voltage/launches/safetyswitches

Catalogue:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/fa1d5d4923ab6eddc1257da200370e6b/$file/1SCC340010C0201.pdf

Leaflet:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/c4e1234e4521d69ac1257c7b003240a2/$file/1SCC340007K0201.pdf

Drawing/IGES:
http://new.abb.com/low-voltage/launches/safetyswitches/fusible-safety-switches

Field-installable accessories:

Neutral assembly	EOHXSN56
Auxiliary contact NO type to be added	OA1G10
Auxiliary contact NC type to be added	OA3G01
Hubs	H075CP-TB, H100CP-TB, H125CP-TB, H200CP-TB, H250CP-TB, H300CP-TB, H350CP-TB, H400CP-TB

Replacement parts:

Terminal lugs for line and load side terminals	OZXA-800/3 Line side / OZXA-800E/3 Load side
Grounding terminal	OZXG2/2
Switch disconnect	OT400US30EOHR
Door locking mechanism	EOHLM4
Handle assembly	EOHHS2

Technical and product support:
ABB OY Breakers and Switches
P.O.Box 622
FI-65101 Vaasa, Finland
Phone: +358 102211
e-Mail: switch.technicalservice@fi.abb.com

Sales in USA:
ABB Inc. / USA
16250 W Glendale Drive
New Berlin, WI 53151, USA
Phone: 888-385-1221
e-Mail: lvps.support@us.abb.com

Sales in Canada:
ABB Inc. / CANADA
2117, 32nd Avenue
Lachine, QC H8T 3J1, Canada
Phone: 514-420-3100
e-Mail: lvp.support@ca.abb.com

Power and productivity for a better world™

DATA SHEET

Date: 18.8.2015

Non-fusible heavy duty safety switch, single throw
EOHU365S

EOHU365S

A	42.32in	1075mm
B	20.16in	512mm
F	10.08in	256mm
O	5.2in	132mm
P	4.88in	124mm
G	1in	25.5mm
N	1.14in	29mm
K	0.55in	14mm
L	0.55in	14mm
M	0.98in	25mm
H	42.72in	1085mm
W	23in	584mm
W1	24.53in	623mm
D	8.5in	216mm
E	11.61in	295mm

EOHU365S KNOCKOUT INFORMATION
TOP ENDWALL OF ENCLOSURE

No factory-made knockouts.
Drillings or cutting for purpose-made cabling accessories is allowed inside blank surface A:
Width: 17.08in / 434mm
Depth: 6.22in / 158mm
Note: Vertical dimension is from mounting surface.

EOHU365S KNOCKOUT INFORMATION
BOTTOM ENDWALL OF ENCLOSURE

No factory-made knockouts.
Drillings or cutting for purpose-made cabling accessories is allowed inside blank surface B:
Width: 17.08in / 434mm
Depth: 6.22in / 158mm
Note: Vertical dimension is from mounting surface.

Power and productivity for a better world™