DATA SHEET

Date: 18.8.2015

Fusible heavy duty safety switch with neutral, single throw EOH365NSS

Electrical equipment should be installed, operated, serviced, and maintained only by qualified personnel. No responsibility is assumed by ABB for any consequences arising out of the use of this material.

Type	EOH365NSS
Ordering number	1SCA139054R1001
EAN-code	6417019671116
Product Name	Fusible heavy duty safety switch with neutral, single throw
UL-file number	E314773
CSA-file number	58077
Country of Origin	Finland
Type of enclosure	NEMA Type 4/4X Watertight
General purpose current rating 600V	400A
Number of poles	3
Net Weight	105.9lb / 48.019kg
Gross Weight	115.9lb / 52.561kg
Standards	UL98, UL50, UL4248-1, NEMA KS1, CSA
Instructions and manuals	34 EOH364-5-6JRS
Type of disconnect	OT400US30EOH
Switch operating torque	336.3lb.in / 38Nm
Min. Electrical endurance power factor 0.7 - 0.8	1500 op. cycles
Mechanical endurance	7500 op. cycles
Power loss / switch unit excluding fusegear	30W
Application ambient air temperature	-30°C/-22°F…40°C/104°F
Standard Power rating Three phase /240V	50HP / 37.3kW
Standard Power rating Three phase /480V	100HP / 74.6kW
Standard Power rating Three phase /600V	125HP / 93.25kW
Max. Power rating Three phase /240V	125HP / 93.25kW
Max. Power rating Three phase /480V	250HP / 186.5kW
Max. Power rating Three phase /600V	350HP / 261.1kW
Max. Power rating /250Vdc	50HP / 37.3kW
Max. motor FLA current Three phase /120-127V	260A
Max. motor FLA current Three phase /240V	312A
Max. motor FLA current Three phase /480V	302A
Max. motor FLA current Three phase /600V	336A
Maximum fuse size	400A
Fuse clips	Class H, K, RK1-5 to be equipped with field-installable rejection members, provision to relocate fuse base for class J, field-installable mounting kit for class T
Class RK fuses, short circuit rating 480Vac	200kA
Class J fuses, short circuit rating 480Vac	200kA
Class T fuses, short circuit rating 480Vac	200kA

Power and productivity for a better world™

© Copyright ABB

Fusible heavy duty safety switch with neutral, single throw EOH365NSS

Class RK fuses, short circuit rating 600Vac	100kA
Class J fuses, short circuit rating 600Vac	200kA
Class T fuses, short circuit rating 600Vac	200kA
Class H fuses, short circuit rating 600Vac	10kA
Class K fuses, short circuit rating 600Vac	50kA
Short circuit rating 250Vdc	100kA
Terminal lugs for line and load side terminals	Line side OZXA-800 / Load side OZXA-800E
Torque: Lug mounting line and load side terminals	480lb.in / 54.2Nm
Wire size 75°C Copper	2x500 kcmil
Wire size 75°C Copper Cross section	506mm²
Wire size 75°C Aluminium	2x500 kcmil
Wire size 75°C Aluminium Cross section	506mm²
Torque: line and load side wire tightening	500lb.in / 56.5Nm
Grounding terminal included in delivery	2xOZXG2
Grounding terminal wire range	250kcmil - AWG6
Torque: grounding wire tightening	275lb.in / 31.1Nm
Neutral bus included	EOHXSN56
Auxiliary contacts included	Field-installable auxiliary contacts mountable in switch mechanism are to be ordered separately.
Max. number of auxiliary contacts to be added	4no+4nc (early break)
Enclosure construction type	EOH5SS Type 4/4X: Enclosures constructed for either indoor or outdoor use to provide a degree of protection to personnel against incidental contact with the enclosed equipment; to provide a degree of protection against falling dirt, rain, sleet, snow, windblown dust, splashing water, hose-directed water, and corrosion (4X); and that will be undamaged by the external formation of ice on the enclosure. Material AISI316.
Cabling direction	TopBottom
Enclosure colour	Unpainted stainless steel grade 316
External Enclosure width/W	22.05in / 560mm
External Enclosure height/H	55.12in / 1400mm
External Enclosure depth/D	8.5in / 216mm
Cable outlets type	Blank
Cable outlets / top (øInch/mm)	Blank
Cable outlets / bottom (øInch/mm)	Blank
Number of door hinges	3
Number of door locking latches	3
Enclosure material specification	Stainless steel AISI316 material thickness: door 0.059in/1.5mm, enclosure 0.059in/1.5mm, fixing plates 0.118in/3mm, handle shield 0.059in/1.5mm.
Handle type	Side-operated, fully insulated
Handle color	Black grip with red position ON indicator
Handle material specification	Handle grip: metallic insert, glass reinforced polyamide (PA f1)/ Red handle indicator: polycarbonate (PC f1).
Type of packing	Environment friendly corrugated cardboard
Packingbox width	24.4in / 620mm
Packingbox heigth	59.1in / 1500mm
Packingbox depth	12in / 305mm

Power and productivity for a better world™ ABB

Fusible heavy duty safety switch with neutral, single throw EOH365NSS

Additional information	Fusible heavy duty safety switch in grade 316 unpainted stainless steel sheet enclosure. Neutral assembly with bonding jumper is included. Suitable only for use as service equipment. Grounding bus is included. Padlockable in OFF-position with 3 padlocks of bail max. diameter 0.25in/6.4mm. Releasable door interlocking mechanism. Field-installable accessories and fuses are to be ordered separately. Factory mounted fuse base and clips for class H, K, RK1-5 fuses. Not for use as motor controller.
Description FI	Sulakkeellinen turvakytkin raskaaseen käyttöön
Description EN	Fusible heavy duty safety switch
Description FR	Interrupteur avec fusibles de sécurité pour service intensif
Description ES	Interruptor de seguridad de servicio pesado con fusibles

Technical information:
http://new.abb.com/low-voltage/launches/safetyswitches

Catalogue:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/fa1d5d4923ab6eddc1257da200370e6b/$file/1SCC340010C0201.pdf

Leaflet:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/c4e1234e4521d69ac1257c7b003240a2/$file/1SCC340007K0201.pdf

Instruction bulletin:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/32753b9528f44814c1257d230034a00e/$file/1SCC340032M1401.pdf

Drawing/PDF:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/3d231bd0c9359acfc1257c99001ffb8d/$file/Z13_EOH365S.PDF

Drawing/IGES:
http://new.abb.com/low-voltage/launches/safetyswitches/fusible-safety-switches

Field-installable accessories:

Fuse mounting kits	EOHFBK5 for Class T 400A fuses
Fuse rejection member kits	EOHRM5R for Class RK1-5 fuses
Auxiliary contact NO type to be added	OA1G10
Auxiliary contact NC type to be added	OA3G01
Hubs	H075CP-TB, H100CP-TB, H125CP-TB, H200CP-TB, H250CP-TB, H300CP-TB, H350CP-TB, H400CP-TB

Replacement parts:

Terminal lugs for line and load side terminals	OZXA-800/3 Line side / OZXA-800E/3 Load side
Grounding terminal	OZXG2/2
Switch disconnect	OT400US30EOHR
Fuse base kits	EOHFBR5LU
Door locking mechanism	EOHLM4
Handle assembly	EOHHSS2

Technical and product support:
ABB OY Breakers and Switches
P.O.Box 622
FI-65101 Vaasa, Finland
Phone: +358 102211
e-Mail: switch.technicalservice@fi.abb.com

Sales in USA:
ABB Inc. / USA
16250 W Glendale Drive
New Berlin, WI 53151, USA
Phone: 888-385-1221
e-Mail: lvps.support@us.abb.com

Sales in Canada:
ABB Inc. / CANADA
2117, 32nd Avenue
Lachine, QC H8T 3J1, Canada
Phone: 514-420-3100
e-Mail: lvp.support@ca.abb.com

Power and productivity for a better world™

DATA SHEET

Date: 18.8.2015

Fusible heavy duty safety switch with neutral, single throw EOH365NSS

EOH365NSS

A	57.48in	1460mm
B	20.16in	512mm
F	10.08in	256mm
O	5.2in	132mm
P	4.82in	122.5mm
G	1in	25.5mm
N	1.14in	29mm
K	0.55in	14mm
L	0.55in	14mm
M	0.98in	25mm
H	58.66in	1490mm
W	22.99in	584mm
W1	24.53in	623mm
D	8.5in	216mm
E	10.39in	264mm

EOH365NSS KNOCKOUT INFORMATION
TOP ENDWALL OF ENCLOSURE

No factory-made knockouts.
Drillings or cutting for purpose-made cabling accessories is allowed inside blank surface A:
Width: 17.08in / 434mm
Depth: 6.22in / 158mm
Note: Vertical dimension is from mounting surface.

EOH365NSS KNOCKOUT INFORMATION
BOTTOM ENDWALL OF ENCLOSURE

No factory-made knockouts.
Drillings or cutting for purpose-made cabling accessories is allowed inside blank surface B:
Width: 17.08in / 434mm
Depth: 6.22in / 158mm
Note: Vertical dimension is from mounting surface.

Power and productivity for a better world™ ABB