DATA SHEET

Date: 18.8.2015

Fusible heavy duty safety switch, single throw
EOH361S

Electrical equipment should be installed, operated, serviced, and maintained only by qualified personnel. No responsibility is assumed by ABB for any consequences arising out of the use of this material.

Type	EOH361S
Ordering number	1SCA132186R1001
EAN-code	6417019613253
Product Name	Fusible heavy duty safety switch, single throw
UL-file number	E314773
CSA-file number	58077
Country of Origin	Finland
Type of enclosure	NEMA Type 4/4X Watertight
General purpose current rating 600V	30A
Number of poles	3
Net Weight	23.8lb / 10.81kg
Gross Weight	30.2lb / 13.676kg
Standards	UL98, UL50, UL4248-1, NEMA KS1, CSA
Instructions and manuals	34 EOH361-2-3JRS
Type of disconnect	OT30US30EOH
Switch operating torque	79.7Ib.in / 9Nm
Min. Electrical endurance power factor 0.7 - 0.8	8000 op. cycles
Mechanical endurance	15000 op. cycles
Power loss / switch unit excluding fusegear	0.3W
Application ambient air temperature	-30°C/-22°F…40°C/104°F
Standard Power rating Single phase /120-127V	0.5HP / 0.37kW
Standard Power rating Single phase /240V	1.5HP / 1.12kW
Standard Power rating Single phase /480V	3HP / 2.24kW
Standard Power rating Single phase /600V	3HP / 2.24kW
Standard Power rating Three phase /120-127V	1.5HP / 1.12kW
Standard Power rating Three phase /240V	3HP / 2.24kW
Standard Power rating Three phase /480V	5HP / 3.73kW
Standard Power rating Three phase /600V	7.5HP / 5.6kW
Max. Power rating Single phase /120-127V	2HP / 1.49kW
Max. Power rating Single phase /240V	3HP / 2.24kW
Max. Power rating Single phase /480V	7.5HP / 5.6kW
Max. Power rating Single phase /600V	10HP / 7.46kW
Max. Power rating Three phase /120-127V	3HP / 2.24kW
Max. Power rating Three phase /200-208V	2.24HP / 1.67kW
Max. Power rating Three phase /240V	7.5HP / 5.6kW
Max. Power rating Three phase /480V	15HP / 11.19kW
Max. Power rating Three phase /600V	20HP / 14.92kW
Max. Power rating /125Vdc	3HP / 2.2kW

Power and productivity for a better world™

© Copyright ABB

Fusible heavy duty safety switch, single throw
EOH361S

Max. Power rating /250Vdc	5HP / 3.7kW
Max. motor FLA current Single phase /120-127V	24A
Max. motor FLA current Single phase /240V	17A
Max. motor FLA current Single phase /480V	21A
Max. motor FLA current Single phase /600V	20A
Max. motor FLA current Three phase /120-127V	19.2A
Max. motor FLA current Three phase /240V	22A
Max. motor FLA current Three phase /480V	21A
Max. motor FLA current Three phase /600V	22A
Maximum fuse size	30A
Fuse clips	Class H, K, RK1-5 to be equipped with field-installable rejection members, provision to relocate fuse base for class J
Class RK fuses, short circuit rating 480Vac	200kA
Class J fuses, short circuit rating 480Vac	200kA
Class RK fuses, short circuit rating 600Vac	200kA
Class J fuses, short circuit rating 600Vac	200kA
Class H fuses, short circuit rating 600Vac	10kA
Class K fuses, short circuit rating 600Vac	50kA
Short circuit rating 250Vdc	100kA
Terminal lugs for line and load side terminals	OZXA-100
Torque: Lug mounting line and load side terminals	132lb.in / 14.9Nm
Wire size 60°C Copper	AWG6
Wire size 60°C Copper Cross section	13.3mm²
Wire size 60°C Aluminium	AWG6
Wire size 60°C Aluminium Cross section	13.3mm²
Wire size 75°C Copper	AWG6
Wire size 75°C Copper Cross section	13.3mm²
Wire size 75°C Aluminium	AWG6
Wire size 75°C Aluminium Cross section	13.3mm²
Torque: line and load side wire tightening	AWG6: 45 lb.in, AWG8: 40 lb.in, AWG10-14: 35 lb.in / AWG6: 5.1 Nm, AWG8: 4.5 Nm, AWG10-14: 4 Nm
Grounding terminal included in delivery	2xOZXG1
Grounding terminal wire range	AWG2 - 14
Torque: grounding wire tightening	50lb.in / 5.6Nm
Auxiliary contacts included	Field-installable auxiliary contacts mountable in switch mechanism are to be ordered separately.
Max. number of auxiliary contacts to be added	2no+2nc (early break)
Enclosure construction type	EOH1S Type 4/4X: Enclosures constructed for either indoor or outdoor use to provide a degree of protection to personnel against incidental contact with the enclosed equipment; to provide a degree of protection against falling dirt, rain, sleet, snow, windblown dust, splashing water, hose-directed water, and corrosion (4X); and that will be undamaged by the external formation of ice on the enclosure. Material AISI304.
Cabling direction	TopBottom
Enclosure colour	Unpainted stainless steel grade 304
External Enclosure width/W	12.09in / 307mm
External Enclosure height/H	17.05in / 433mm
External Enclosure depth/D	6.22in / 158mm
Cable outlets type	Blank
Cable outlets / top (øInch/mm)	Blank
Cable outlets / bottom (øInch/mm)	Blank
Number of door hinges	2
Number of door locking latches	2

Power and productivity for a better world™

© Copyright ABB

Fusible heavy duty safety switch, single throw
EOH361S

Enclosure material specification	Stainless steel AISI304 material thickness: door 0.059in/1.5mm, enclosure 0.059in/1.5mm, fixing plates 0.118in/3mm, handle shield 0.059in/1.5mm.
Handle type	Side-operated, fully insulated
Handle color	Black grip with red position ON indicator
Handle material specification	Handle grip: glass reinforced polyamide (PA f1)/ Red handle indicator: polycarbonate (PC f1).
Type of packing	Environment friendly corrugated cardboard
Packingbox width	14.6in / 370mm
Packingbox heigth	20.9in / 530mm
Packingbox depth	9.3in / 235mm
Additional information	Fusible heavy duty safety switch in grade 304 unpainted stainless steel sheet enclosure. Grounding bus is included. Padlockable in OFF-position with 3 padlocks of bail max. diameter 0.25in/6.4mm. Releasable door interlocking mechanism. Field-installable accessories and fuses are to be ordered separately. Factory mounted fuse base and clips for class H, K, RK1-5 fuses.
Description FI	Sulakkeellinen turvakytkin raskaaseen käyttöön
Description EN	Fusible heavy duty safety switch
Description FR	Interrupteur avec fusibles de sécurité pour service intensif
Description ES	Interruptor de seguridad de servicio pesado con fusibles

Technical information:
http://new.abb.com/low-voltage/launches/safetyswitches

Catalogue:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/fa1d5d4923ab6eddc1257da200370e6b/$file/1SCC340010C0201.pdf

Leaflet:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/c4e1234e4521d69ac1257c7b003240a2/$file/1SCC340007K0201.pdf

Instruction bulletin:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/a8e65d4cbe016259c1257d230033a2c9/$file/1SCC340030M1401.pdf

Drawing/PDF:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/347b4990a1eb94cac1257c99001f67a3/$file/Z13_EOH361S.PDF

Drawing/IGES:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/a6beb805526394d2c1257c76001cf4d8/$file/EOH361S.igs

Field-installable accessories:

Neutral assembly	EOHXSN13
Fuse rejection member kits	EOHRM1R for Class RK1-5 fuses
Auxiliary contact NO type to be added	OA1G10
Auxiliary contact NC type to be added	OA3G01
Terminal cover Line side	OTS250G1S/3
Hubs	H075CP-TB, H100CP-TB, H125CP-TB, H200CP-TB, H250CP-TB

Replacement parts:

Terminal lugs for line and load side terminals	OZXA-100/3
Grounding terminal	OZXG1/2
Switch disconnect	OT30US30EOHR
Fuse base kits	EOHFBR1
Door locking mechanism	EOHLM2
Handle assembly	EOHHS1

Technical and product support:
ABB OY Breakers and Switches
P.O.Box 622
FI-65101 Vaasa, Finland
Phone: +358 102211
e-Mail: switch.technicalservice@fi.abb.com

Sales in USA:
ABB Inc. / USA
16250 W Glendale Drive
New Berlin, WI 53151, USA
Phone: 888-385-1221
e-Mail: lvps.support@us.abb.com

Sales in Canada:
ABB Inc. / CANADA
2117, 32nd Avenue
Lachine, QC H8T 3J1, Canada
Phone: 514-420-3100
e-Mail: lvp.support@ca.abb.com

Power and productivity for a better world™

DATA SHEET

Date: 18.8.2015

Fusible heavy duty safety switch, single throw
EOH361S

EOH361S

A	18.62in	473mm
B	10.59in	269mm
F	5.28in	134mm
G	1.1in	28mm
N	0.83in	21mm
K	0.35in	9mm
L	0.35in	9mm
M	0.75in	19mm
H	19.41in	493mm
W	13.23in	336mm
W1	14.49in	368mm
D	6.3in	160mm
E	9in	229mm

EOH361S KNOCKOUT INFORMATION
TOP ENDWALL OF ENCLOSURE

No factory-made knockouts.

Drillings or cutting for purpose-made cabling accessories is allowed inside blank surface A:

Width: 7.12in / 181mm

Depth: 3.82in / 97mm

Note: Vertical dimension is from mounting surface.

EOH361S KNOCKOUT INFORMATION
BOTTOM ENDWALL OF ENCLOSURE

No factory-made knockouts.

Drillings or cutting for purpose-made cabling accessories is allowed inside blank surface B:

Width: 7.12in / 181mm

Depth: 3.82in / 97mm

Note: Vertical dimension is from mounting surface.

Power and productivity for a better world™