DATA SHEET

Date: 18.8.2015

Fusible heavy duty safety switch, single throw
EOH364S

Electrical equipment should be installed, operated, serviced, and maintained only by qualified personnel. No responsibility is assumed by ABB for any consequences arising out of the use of this material.

Type	EOH364S
Ordering number	1SCA139031R1001
EAN-code	6417019670904
Product Name	Fusible heavy duty safety switch, single throw
UL-file number	E314773
CSA-file number	58077
Country of Origin	Finland
Type of enclosure	NEMA Type 4/4X Watertight
General purpose current rating 600V	200A
Number of poles	3
Net Weight	57.3lb / 26kg
Gross Weight	67.2lb / 30.5kg
Standards	UL98, UL50, UL4248-1, NEMA KS1, CSA
Instructions and manuals	34 EOH364-5-6JRS
Type of disconnect	OT200US30EOH
Switch operating torque	203.6Ib.in / 23Nm
Min. Electrical endurance power factor 0.7 - 0.8	6000 op. cycles
Mechanical endurance	12000 op. cycles
Power loss / switch unit excluding fusegear	7.5W
Application ambient air temperature	-30°C/-22°F…40°C/104°F
Standard Power rating Single phase /240V	15HP / 11.19kW
Standard Power rating Single phase /480V	25HP / 18.65kW
Standard Power rating Single phase /600V	30HP / 22.38kW
Standard Power rating Three phase /240V	25HP / 18.65kW
Standard Power rating Three phase /480V	50HP / 37.3kW
Standard Power rating Three phase /600V	60HP / 44.76kW
Max. Power rating Single phase /240V	15HP / 11.19kW
Max. Power rating Single phase /480V	50HP / 37.3kW
Max. Power rating Single phase /600V	50HP / 37.3kW
Max. Power rating Three phase /240V	60HP / 44.76kW
Max. Power rating Three phase /480V	125HP / 93.25kW
Max. Power rating Three phase /600V	150HP / 111.9kW
Max. Power rating /250Vdc	40HP / 29.8kW
Max. motor FLA current Single phase /120-127V	135A
Max. motor FLA current Single phase /240V	68A
Max. motor FLA current Single phase /480V	108A
Max. motor FLA current Single phase /600V	86A
Max. motor FLA current Three phase /120-127V	160A

Power and productivity for a better world™

© Copyright ABB

Fusible heavy duty safety switch, single throw
EOH364S

Max. motor FLA current Three phase /240V	164A
Max. motor FLA current Three phase /480V	156A
Max. motor FLA current Three phase /600V	144A
Maximum fuse size	200A
Fuse clips	Class H, K, RK1-5 to be equipped with field-installable rejection members, provision to relocate fuse base for class J, field-installable mounting kit for class T
Class RK fuses, short circuit rating 480Vac	200kA
Class J fuses, short circuit rating 480Vac	200kA
Class T fuses, short circuit rating 480Vac	200kA
Class RK fuses, short circuit rating 600Vac	200kA
Class J fuses, short circuit rating 600Vac	200kA
Class T fuses, short circuit rating 600Vac	200kA
Class H fuses, short circuit rating 600Vac	10kA
Class K fuses, short circuit rating 600Vac	50kA
Short circuit rating 250Vdc	100kA
Terminal lugs for line and load side terminals	OZXA-400
Torque: Lug mounting line and load side terminals	228Ib.in / 25.8Nm
Wire size 75°C Copper	250 kcmil
Wire size 75°C Copper Cross section	127mm²
Wire size 75°C Aluminium	250 kcmil
Wire size 75°C Aluminium Cross section	127mm²
Torque: line and load side wire tightening	375Ib.in / 42.4Nm
Grounding terminal included in delivery	2xOZXG1
Grounding terminal wire range	AWG2 - 14
Torque: grounding wire tightening	50Ib.in / 5.6Nm
Auxiliary contacts included	Field-installable auxiliary contacts mountable in switch mechanism are to be ordered separately.
Max. number of auxiliary contacts to be added	4no+4nc (early break)
Enclosure construction type	EOH4S Type 4/4X: Enclosures constructed for either indoor or outdoor use to provide a degree of protection to personnel against incidental contact with the enclosed equipment; to provide a degree of protection against falling dirt, rain, sleet, snow, windblown dust, splashing water, hose-directed water, and corrosion (4X); and that will be undamaged by the external formation of ice on the enclosure. Material AISI304.
Cabling direction	TopBottom
Enclosure colour	Unpainted stainless steel grade 304
External Enclosure width/W	16.14in / 410mm
External Enclosure height/H	37.44in / 951mm
External Enclosure depth/D	7.32in / 186mm
Cable outlets type	Blank
Cable outlets / top (øInch/mm)	Blank
Cable outlets / bottom (øInch/mm)	Blank
Number of door hinges	3
Number of door locking latches	3
Enclosure material specification	Stainless steel AISI304 material thickness: door 0.059in/1.5mm, enclosure 0.059in/1.5mm, fixing plates 0.118in/3mm, handle shield 0.059in/1.5mm.
Handle type	Side-operated, fully insulated
Handle color	Black grip with red position ON indicator
Handle material specification	Handle grip: metallic insert, glass reinforced polyamide (PA f1)/ Red handle indicator: polycarbonate (PC f1).
Type of packing	Environment friendly corrugated cardboard
Packingbox width	18.5in / 470mm
Packingbox heigth	41.3in / 1050mm

Power and productivity for a better world™

© Copyright ABB

Fusible heavy duty safety switch, single throw
EOH364S

Packingbox depth	10.8in / 275mm
Additional information	Fusible heavy duty safety switch in grade 304 unpainted stainless steel sheet enclosure. Grounding bus is included. Padlockable in OFF-position with 3 padlocks of bail max. diameter 0.25in/6.4mm. Releasable door interlocking mechanism. Field-installable accessories and fuses are to be ordered separately. Factory mounted fuse base and clips for class H, K, RK1-5 fuses. Not for use as motor controller.
Description FI	Sulakkeellinen turvakytkin raskaaseen käyttöön
Description EN	Fusible heavy duty safety switch
Description FR	Interrupteur avec fusibles de sécurité pour service intensif
Description ES	Interruptor de seguridad de servicio pesado con fusibles

Technical information:
http://new.abb.com/low-voltage/launches/safetyswitches

Catalogue:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/fa1d5d4923ab6eddc1257da200370e6b/$file/1SCC340010C0201.pdf

Leaflet:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/c4e1234e4521d69ac1257c7b003240a2/$file/1SCC340007K0201.pdf

Instruction bulletin:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/32753b9528f44814c1257d230034a00e/$file/1SCC340032M1401.pdf

Drawing/PDF:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/cec6074f0cd3d129c1257c99001fc7f5/$file/Z13_EOH364S.PDF

Drawing/IGES:
http://new.abb.com/low-voltage/launches/safetyswitches/fusible-safety-switches

Field-installable accessories:

Neutral assembly	EOHXSN4
Fuse mounting kits	EOHFBK4 for Class T 200A fuses
Fuse rejection member kits	EOHRM34R for Class RK1-5 fuses
Auxiliary contact NO type to be added	OA1G10
Auxiliary contact NC type to be added	OA3G01
Terminal cover Line side	OTS400G1L/3, OTS400G1S/3
Hubs	H075CP-TB, H100CP-TB, H125CP-TB, H200CP-TB, H250CP-TB

Replacement parts:

Terminal lugs for line and load side terminals	OZXA-400/3
Grounding terminal	OZXG1/2
Switch disconnect	OT200US30EOHR
Fuse base kits	EOHFBR4LU
Door locking mechanism	EOHLM3
Handle assembly	EOHHS2

Technical and product support:
ABB OY Breakers and Switches
P.O.Box 622
FI-65101 Vaasa, Finland
Phone: +358 102211
e-Mail: switch.technicalservice@fi.abb.com

Sales in USA:
ABB Inc. / USA
16250 W Glendale Drive
New Berlin, WI 53151, USA
Phone: 888-385-1221
e-Mail: lvps.support@us.abb.com

Sales in Canada:
ABB Inc. / CANADA
2117, 32nd Avenue
Lachine, QC H8T 3J1, Canada
Phone: 514-420-3100
e-Mail: lvp.support@ca.abb.com

Power and productivity for a better world™

DATA SHEET

Date: 18.8.2015

Fusible heavy duty safety switch, single throw
EOH364S

EOH364S

A	39.02in	991mm
B	14.65in	372mm
F	7.32in	186mm
G	1.18in	30mm
N	0.83in	21mm
K	0.35in	9mm
L	0.35in	9mm
M	0.75in	19mm
H	39.8in	1011mm
W	17.28in	439mm
W1	18.54in	471mm
D	7.36in	187mm
E	9.25in	235mm

EOH364S KNOCKOUT INFORMATION
TOP ENDWALL OF ENCLOSURE

No factory-made knockouts.
Drillings or cutting for purpose-made cabling accessories is allowed inside blank surface A:
Width: 11.18in / 284mm
Depth: 5in / 127mm
Note: Vertical dimension is from mounting surface.

EOH364S KNOCKOUT INFORMATION
BOTTOM ENDWALL OF ENCLOSURE

No factory-made knockouts.
Drillings or cutting for purpose-made cabling accessories is allowed inside blank surface B:
Width: 11.18in / 284mm
Depth: 5in / 127mm
Note: Vertical dimension is from mounting surface.

Power and productivity for a better world™