DATA SHEET

Date: 18.8.2015

Fusible heavy duty safety switch, single throw
EOH368R

Electrical equipment should be installed, operated, serviced, and maintained only by qualified personnel. No responsibility is assumed by ABB for any consequences arising out of the use of this material.

Type	EOH368R
Ordering number	1SCA132753R1001
EAN-code	6417019618364
Product Name	Fusible heavy duty safety switch, single throw
UL-file number	E314773
CSA-file number	58077
Country of Origin	Finland
Type of enclosure	NEMA Type 3R Rainproof
General purpose current rating 600V	1200A
Number of poles	3
Net Weight	415.6lb / 188.5kg
Gross Weight	586.4lb / 266kg
Standards	UL98, UL50, UL4248-1, NEMA KS1, CSA
Instructions and manuals	34 EOH367-8JRS
Type of disconnect	OT1200US30EOH
Switch operating torque	655lb.in / 74Nm
Min. Electrical endurance power factor 0.7 - 0.8	600 op. cycles
Mechanical endurance	2500 op. cycles
Power loss / switch unit excluding fusegear	81W
Application ambient air temperature	-30°C/-22°F…40°C/104°F
Standard Power rating Three phase /240V	100HP / 74.6kW
Standard Power rating Three phase /480V	200HP / 149.2kW
Standard Power rating Three phase /600V	250HP / 186.5kW
Max. Power rating Three phase /240V	250HP / 186.5kW
Max. Power rating Three phase /480V	500HP / 373kW
Max. Power rating Three phase /600V	500HP / 373kW
Max. Power rating /250Vdc	50HP / 37.3kW
Max. motor FLA current Three phase /240V	600A
Max. motor FLA current Three phase /480V	590A
Max. motor FLA current Three phase /600V	472A
Maximum fuse size	1200A
Fuse clips	Class L
Class L fuses, short circuit rating 480Vac	200kA
Class L fuses, short circuit rating 600Vac	200kA
Short circuit rating 250Vdc	100kA
Terminal lugs for line and load side terminals	Line side OZXA-1200E / Load side OZXA-1200
Torque: Lug mounting line and load side terminals	Line side 319 lb.in / Load side 443 lb.in / Line side 36 Nm / Load side 50.1 Nm

Power and productivity for a better world™

© Copyright ABB

Fusible heavy duty safety switch, single throw EOH368R

Wire size 75°C Copper	Line side 6x500 kcmil / Load side 4x500 kcmil
Wire size 75°C Copper Cross section	Line side 1518mm² / Load side1012mm²
Wire size 75°C Aluminium	Line side 6x500 kcmil / Load side 4x500 kcmil
Wire size 75°C Aluminium Cross section	Line side 1518 / Load side1012
Torque: line and load side wire tightening	Line side 620 lb.in / Load side 500 lb.in / Line side 70.1 Nm / Load side 56.5 Nm
Grounding terminal included in delivery	2xOZXG2
Grounding terminal wire range	250kcmil - AWG6
Torque: grounding wire tightening	275lb.in / 31.1Nm
Auxiliary contacts included	Field-installable auxiliary contacts mountable in switch mechanism are to be ordered separately.
Max. number of auxiliary contacts to be added	2no+2nc (early break)
Enclosure construction type	EOH8R Type 3R: Enclosures constructed for either indoor or outdoor use to provide a degree of protection to personnel against incidental contact with the enclosed equipment; to provide adegree of protection against falling dirt, rain, sleet, and snow; and that will be undamaged by the external formation of ice on the enclosure.
Cabling direction	TopBottom
Enclosure colour	ANSI 61 (light gray)
External Enclosure width/W	39.37in / 1000mm
External Enclosure height/H	68.9in / 1750mm
External Enclosure depth/D	12.44in / 316mm
Cable outlets type	Blank
Cable outlets / top (ølnch/mm)	Blank
Cable outlets / bottom (ølnch/mm)	Blank
Number of door hinges	4
Number of door locking latches	5
Enclosure material specification	Corrosion resistant steel, paint: polyester powder coating 70+/-10µm, material thickness: door 0.079in/2mm provided with welded horizonthal beams, enclosure 0.079in/2mm, ribbed enclosure bottom and fixing lugs 0.118in/3mm, handle shield 0.059in/1.5mm.
Handle type	Side-operated, fully insulated
Handle color	Black grip with red position ON indicator
Handle material specification	Handle grip: metallic insert, glass reinforced polyamide (PA f1)/ Red handle indicator: polycarbonate (PC f1).
Type of packing	Plywood container equipped with removable front cover and sledge runners
Packingbox width	46.5in / 1180mm
Packingbox heigth	72.8in / 1850mm
Packingbox depth	15.7in / 400mm
Additional information	Fusible heavy duty safety switch in painted steel sheet enclosure. Grounding bus is included. Padlockable in OFF-position with 3 padlocks of bail max. diameter 0.25in/6.4mm. Releasable door interlocking mechanism. Factory-mounted fuse base and mounting screw kit for class L fuses are included. Field-installable accessories and fuses are to be ordered separately. Not for use as motor controller.
Description FI	Sulakkeellinen turvakytkin raskaaseen käyttöön
Description EN	Fusible heavy duty safety switch
Description FR	Interrupteur avec fusibles de sécurité pour service intensif
Description ES	Interruptor de seguridad de servicio pesado con fusibles

Power and productivity for a better world™

© Copyright ABB

Fusible heavy duty safety switch, single throw EOH368R

Technical information:
http://new.abb.com/low-voltage/launches/safetyswitches

UL Certificate of Compliance:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/762006113685b65fc1257d6200207c53/$file/UL%20certificate%20EOH.pdf

CSA Certificate of Compliance:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/8e61ba5de98778c9c1257d5e002e7422/$file/CSA%20Certificate%20EOH_%20EOHU_.pdf

Catalogue:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/fa1d5d4923ab6eddc1257da200370e6b/$file/1SCC340010C0201.pdf

Leaflet:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/c4e1234e4521d69ac1257c7b003240a2/$file/1SCC340007K0201.pdf

Instruction bulletin:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/11915529ae2635d9c1257d230038db82/$file/1SCC340034M1401.pdf

Drawing/PDF:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/83a3622df06fabf0c1257c99002083ea/$file/Z13_EOH368.PDF

Drawing/IGES:
http://new.abb.com/low-voltage/launches/safetyswitches/fusible-safety-switches

Field-installable accessories:

Neutral assembly	EOHXSN78
Auxiliary contact NO type to be added	OA1G10
Auxiliary contact NC type to be added	OA3G01
Condensation water outlet	YJTB3/M10

Replacement parts:

Terminal lugs for line and load side terminals	OZXA-1200E/3 Line side / OZXA-1200/3 Load side
Grounding terminal	OZXG2/2
Switch disconnect	OT1200US30EOHR
Fuse base kits	EOHFBL8
Door locking mechanism	EOHLM5
Handle assembly	EOHH3

Technical and product support:
ABB OY Breakers and Switches
P.O.Box 622
FI-65101 Vaasa, Finland
Phone: +358 102211
e-Mail: switch.technicalservice@fi.abb.com

Sales in USA:
ABB Inc. / USA
16250 W Glendale Drive
New Berlin, WI 53151, USA
Phone: 888-385-1221
e-Mail: lvps.support@us.abb.com

Sales in Canada:
ABB Inc. / CANADA
2117, 32nd Avenue
Lachine, QC H8T 3J1, Canada
Phone: 514-420-3100
e-Mail: lvp.support@ca.abb.com

Power and productivity for a better world™

DATA SHEET

Date: 18.8.2015

Fusible heavy duty safety switch, single throw
EOH368R

EOH368R

A	60.95in	1548mm
B	41.14in	1045mm
F	30.47in	774mm
G	3.98in	101mm
N	1.18in	30mm
K	0.39in	10mm
H	68.9in	1750mm
W	39.96in	1015mm
W1	41.77in	1061mm
W2	43.11in	1095mm
D	12.6in	320mm
E	14.76in	375mm

EOH368R KNOCKOUT INFORMATION
TOP ENDWALL OF ENCLOSURE

No factory-made knockouts.
Drillings or cutting for purpose-made cabling accessories is allowed inside blank surface A:
Width: 34.4in / 874mm
Depth: 8.5in / 216mm
Note: Vertical dimension is from mounting surface.

EOH368R KNOCKOUT INFORMATION
BOTTOM ENDWALL OF ENCLOSURE

No factory-made knockouts.
Drillings or cutting for purpose-made cabling accessories is allowed inside blank surface B:
Width: 34.4in / 874mm
Depth: 8.5in / 216mm
Note: Vertical dimension is from mounting surface.

Power and productivity for a better world™ ABB