DATA SHEET

Date: 18.8.2015

Non-fusible heavy duty safety switch, single throw
EOHU364RK

Electrical equipment should be installed, operated, serviced, and maintained only by qualified personnel. No responsibility is assumed by ABB for any consequences arising out of the use of this material.

Type	EOHU364RK
Ordering number	1SCA131627R1001
EAN-code	6417019608723
Product Name	Non-fusible heavy duty safety switch, single throw
UL-file number	E314773
CSA-file number	58077
Country of Origin	Finland
Type of enclosure	NEMA Type 3R Rainproof
General purpose current rating 600V	200A
Number of poles	3
Net Weight	37.9lb / 17.2kg
Gross Weight	42.8lb / 19.425kg
Standards	UL98, UL50, NEMA KS1, CSA
Instructions and manuals	34 EOHU364-5-6JRS
Type of disconnect	OT200US30EOH
Switch operating torque	203.6Ib.in / 23Nm
Min. Electrical endurance power factor 0.7 - 0.8	6000 op. cycles
Mechanical endurance	12000 op. cycles
Power loss / switch unit	7.5W
Application ambient air temperature	-30°C/-22°F…40°C/104°F
Max. Power rating Single phase /240V	15HP / 11.19kW
Max. Power rating Single phase /480V	50HP / 37.3kW
Max. Power rating Single phase /600V	50HP / 37.3kW
Max. Power rating Three phase /240V	60HP / 44.76kW
Max. Power rating Three phase /480V	125HP / 93.25kW
Max. Power rating Three phase /600V	150HP / 111.9kW
Max. Power rating /250Vdc	40HP / 29.8kW
Max. motor FLA current Single phase /120-127V	135A
Max. motor FLA current Single phase /240V	68A
Max. motor FLA current Single phase /480V	108A
Max. motor FLA current Single phase /600V	86A
Max. motor FLA current Three phase /120-127V	160A
Max. motor FLA current Three phase /240V	164A
Max. motor FLA current Three phase /480V	156A
Max. motor FLA current Three phase /600V	144A
Maximum fuse size	200A
Class RK fuses, short circuit rating 480Vac	200kA
Class J fuses, short circuit rating 480Vac	200kA

Power and productivity for a better world™

© Copyright ABB

Non-fusible heavy duty safety switch, single throw EOHU364RK

Class T fuses, short circuit rating 480Vac	200kA
Class RK fuses, short circuit rating 600Vac	200kA
Class J fuses, short circuit rating 600Vac	200kA
Class T fuses, short circuit rating 600Vac	200kA
Short circuit rating 250Vdc	100kA
Terminal lugs for line and load side terminals	OZXA-400
Torque: Lug mounting line and load side terminals	228Ib.in / 25.8Nm
Wire size 75°C Copper	250 kcmil
Wire size 75°C Copper Cross section	127mm²
Wire size 75°C Aluminium	250 kcmil
Torque: line and load side wire tightening	375Ib.in / 42.4Nm
Grounding terminal included in delivery	2xOZXG1
Grounding terminal wire range	AWG2 - 14
Torque: grounding wire tightening	50Ib.in / 5.6Nm
Auxiliary contacts included	Field-installable auxiliary contacts mountable in switch mechanism are to be ordered separately.
Max. number of auxiliary contacts to be added	4no+4nc (early break)
Enclosure construction type	EOHU4R Type 3R: Enclosures constructed for either indoor or outdoor use to provide a degree of protection to personnel against incidental contact with the enclosed equipment; to provide adegree of protection against falling dirt, rain, sleet, and snow; and that will be undamaged by the external formation of ice on the enclosure.
Cabling direction	TopBottom
Enclosure colour	ANSI 61 (light gray)
External Enclosure width/W	16.14in / 410mm
External Enclosure height/H	24.41in / 620mm
External Enclosure depth/D	7.32in / 186mm
Cable outlets type	Concentric knockouts
Cable outlets / top (øInch/mm)	3x(ø2.5/63.5+ø2/50.8+ø1.5/38.1+ø1.25/31.75+ø0.79/20)+ø0.25/6.35+ø0.9/22.4
Cable outlets / bottom (øInch/mm)	3x(ø2.5/63.5+ø2/50.8+ø1.5/38.1+ø1.25/31.75+ø0.79/20)+ø0.25/6.35+ø0.9/22.4
Number of door hinges	2
Number of door locking latches	2
Enclosure material specification	Corrosion resistant steel, paint: polyester powder coating 70+/-10µm, material thickness: door 0.059in/1.5mm, enclosure 0.059in/1.5mm, fixing plates 0.118in/3mm, handle shield 0.059in/1.5mm.
Handle type	Side-operated, fully insulated
Handle color	Black grip with red position ON indicator
Handle material specification	Handle grip: metallic insert, glass reinforced polyamide (PA f1)/ Red handle indicator: polycarbonate (PC f1).
Type of packing	Environment friendly corrugated cardboard
Packingbox width	18.7in / 475mm
Packingbox heigth	28.3in / 720mm
Packingbox depth	10.8in / 275mm
Additional information	Non-fusible heavy duty safety switch in painted steel sheet enclosure. Grounding bus is included. Padlockable in OFF-position with 3 padlocks of bail max. diameter 0.25in/6.4mm. Releasable door interlocking mechanism. Field-installable accessories are to be ordered separately. Not for use as motor controller.
Description FI	Sulakkeeton turvakytkin raskaaseen käyttöön
Description EN	Non-fusible heavy duty safety switch
Description FR	Interrupteur non fusibles de sécurité pour service intensif
Description ES	Interruptor de seguridad de Servicio Pesado sin fusibles

Power and productivity for a better world™

© Copyright ABB

Non-fusible heavy duty safety switch, single throw EOHU364RK

Technical information:
http://new.abb.com/low-voltage/launches/safetyswitches

UL Certificate of Compliance:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/aec18f1adb9e499ec1257d620020cedf/$file/UL%20certificate%20EOHU.pdf

CSA Certificate of Compliance:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/8e61ba5de98778c9c1257d5e002e7422/$file/CSA%20Certificate%20EOH_%20EOHU_.pdf

Catalogue:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/fa1d5d4923ab6eddc1257da200370e6b/$file/1SCC340010C0201.pdf

Leaflet:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/c4e1234e4521d69ac1257c7b003240a2/$file/1SCC340007K0201.pdf

Drawing/IGES:
http://new.abb.com/low-voltage/launches/safetyswitches/fusible-safety-switches

Field-installable accessories:

Neutral assembly	EOHXSN4
Auxiliary contact NO type to be added	OA1G10
Auxiliary contact NC type to be added	OA3G01
Terminal cover Line side	OTS400G1L/3, OTS400G1S/3
Terminal cover Load side	OTS400G1L/3, OTS400G1S/3
Hubs	H050-TB, H075-TB, H100-TB, H150-TB, H200-TB
Condensation water outlet	YJTB3/M5

Replacement parts:

Terminal lugs for line and load side terminals	OZXA-400/3
Grounding terminal	OZXG1/2
Switch disconnect	OT200US30EOHR
Door locking mechanism	EOHLM3
Handle assembly	EOHH2

Technical and product support:
ABB OY Breakers and Switches
P.O.Box 622
FI-65101 Vaasa, Finland
Phone: +358 102211
e-Mail: switch.technicalservice@fi.abb.com

Sales in USA:
ABB Inc. / USA
16250 W Glendale Drive
New Berlin, WI 53151, USA
Phone: 888-385-1221
e-Mail: lvps.support@us.abb.com

Sales in Canada:
ABB Inc. / CANADA
2117, 32nd Avenue
Lachine, QC H8T 3J1, Canada
Phone: 514-420-3100
e-Mail: lvp.support@ca.abb.com

Power and productivity for a better world™

DATA SHEET

Date: 18.8.2015

Non-fusible heavy duty safety switch, single throw
EOHU364RK

EOHU364RK

A	25.98in	660mm
B	14.65in	372mm
F	7.32in	186mm
G	0.87in	22mm
N	0.83in	21mm
K	0.35in	9mm
L	0.35in	9mm
M	0.75in	19mm
H	26.77in	680mm
W	17.01in	432mm
W1	19.09in	485mm
D	7.36in	187mm
E	10.16in	258mm

EOHU364RK KNOCKOUT INFORMATION
TOP ENDWALL OF ENCLOSURE

H horizontal	V vertical (see Note)	Ø Knockout hole diameter
5.91in/150mm	2.72in/69mm	0.25in/6.35mm
3.74in/95mm	3.9in/99mm	0.63in/16mm 0.88in/22.4mm 1.11in/28.2mm 1.39in/35.2mm 2in/50.8mm 2.46in/62.50mm
8.07in/205mm	3.9in/99mm	0.63in/16mm 0.88in/22.4mm 1.11in/28.2mm 1.39in/35.2mm 2in/50.8mm 2.46in/62.50mm
12.4in/315mm	3.9in/99mm	0.63in/16mm 0.88in/22.4mm 1.11in/28.2mm 1.39in/35.2mm 2in/50.8mm 2.46in/62.50mm
5.91in/150mm	5.47in/139mm	0.79in/20mm

Note: Vertical dimension is from mounting surface.

EOHU364RK KNOCKOUT INFORMATION
BOTTOM ENDWALL OF ENCLOSURE

H horizontal	V vertical (see Note)	Ø Knockout hole diameter
5.91in/150mm	2.72in/69mm	0.25in/6.35mm
3.74in/95mm	3.9in/99mm	0.63in/16mm 0.88in/22.4mm 1.11in/28.2mm 1.39in/35.2mm 2in/50.8mm 2.46in/62.50mm
8.07in/205mm	3.9in/99mm	0.63in/16mm 0.88in/22.4mm 1.11in/28.2mm 1.39in/35.2mm 2in/50.8mm 2.46in/62.50mm
12.4in/315mm	3.9in/99mm	0.63in/16mm 0.88in/22.4mm 1.11in/28.2mm 1.39in/35.2mm 2in/50.8mm 2.46in/62.50mm
5.91in/150mm	5.47in/139mm	0.79in/20mm

Note: Vertical dimension is from mounting surface.

Power and productivity
for a better world™

© Copyright ABB