# DATA SHEET

Date: 18.8.2015

# Fusible heavy duty safety switch with neutral, single throw EOH364NSS

Electrical equipment should be installed, operated, serviced, and maintained only by qualified personnel. No responsibility is assumed by ABB for any consequences arising out of the use of this material.

| | |
|---|---|
| **Type** | EOH364NSS |
| **Ordering number** | 1SCA139052R1001 |
| **EAN-code** | 6417019671093 |
| **Product Name** | Fusible heavy duty safety switch with neutral, single throw |
| **UL-file number** | E314773 |
| **CSA-file number** | 58077 |
| **Country of Origin** | Finland |
| **Type of enclosure** | NEMA Type 4/4X Watertight |
| **General purpose current rating 600V** | 200A |
| **Number of poles** | 3 |
| **Net Weight** | 58.8lb / 26.685kg |
| **Gross Weight** | 68.7lb / 31.181kg |
| **Standards** | UL98, UL50, UL4248-1, NEMA KS1, CSA |
| **Instructions and manuals** | 34 EOH364-5-6JRS |
| **Type of disconnect** | OT200US30EOH |
| **Switch operating torque** | 203.6Ib.in / 23Nm |
| **Min. Electrical endurance power factor 0.7 - 0.8** | 6000 op. cycles |
| **Mechanical endurance** | 12000 op. cycles |
| **Power loss / switch unit excluding fusegear** | 7.5W |
| **Application ambient air temperature** | -30°C/-22°F…40°C/104°F |
| **Standard Power rating Single phase /240V** | 15HP / 11.19kW |
| **Standard Power rating Single phase /480V** | 25HP / 18.65kW |
| **Standard Power rating Single phase /600V** | 30HP / 22.38kW |
| **Standard Power rating Three phase /240V** | 25HP / 18.65kW |
| **Standard Power rating Three phase /480V** | 50HP / 37.3kW |
| **Standard Power rating Three phase /600V** | 60HP / 44.76kW |
| **Max. Power rating Single phase /240V** | 15HP / 11.19kW |
| **Max. Power rating Single phase /480V** | 50HP / 37.3kW |
| **Max. Power rating Single phase /600V** | 50HP / 37.3kW |
| **Max. Power rating Three phase /240V** | 60HP / 44.76kW |
| **Max. Power rating Three phase /480V** | 125HP / 93.25kW |
| **Max. Power rating Three phase /600V** | 150HP / 111.9kW |
| **Max. Power rating /250Vdc** | 40HP / 29.8kW |
| **Max. motor FLA current Single phase /120-127V** | 135A |
| **Max. motor FLA current Single phase /240V** | 68A |
| **Max. motor FLA current Single phase /480V** | 108A |
| **Max. motor FLA current Single phase /600V** | 86A |
| **Max. motor FLA current Three phase /120-127V** | 160A |

Power and productivity for a better world™

© Copyright ABB

# Fusible heavy duty safety switch with neutral, single throw EOH364NSS

| | |
|---|---|
| **Max. motor FLA current Three phase /240V** | 164A |
| **Max. motor FLA current Three phase /480V** | 156A |
| **Max. motor FLA current Three phase /600V** | 144A |
| **Maximum fuse size** | 200A |
| **Fuse clips** | Class H, K, RK1-5 to be equipped with field-installable rejection members, provision to relocate fuse base for class J, field-installable mounting kit for class T |
| **Class RK fuses, short circuit rating 480Vac** | 200kA |
| **Class J fuses, short circuit rating 480Vac** | 200kA |
| **Class T fuses, short circuit rating 480Vac** | 200kA |
| **Class RK fuses, short circuit rating 600Vac** | 200kA |
| **Class J fuses, short circuit rating 600Vac** | 200kA |
| **Class T fuses, short circuit rating 600Vac** | 200kA |
| **Class H fuses, short circuit rating 600Vac** | 10kA |
| **Class K fuses, short circuit rating 600Vac** | 50kA |
| **Short circuit rating 250Vdc** | 100kA |
| **Terminal lugs for line and load side terminals** | OZXA-400 |
| **Torque: Lug mounting line and load side terminals** | 228Ib.in / 25.8Nm |
| **Wire size 75°C Copper** | 250 kcmil |
| **Wire size 75°C Copper Cross section** | 127mm² |
| **Wire size 75°C Aluminium** | 250 kcmil |
| **Wire size 75°C Aluminium Cross section** | 127mm² |
| **Torque: line and load side wire tightening** | 375Ib.in / 42.4Nm |
| **Grounding terminal included in delivery** | 2xOZXG1 |
| **Grounding terminal wire range** | AWG2 - 14 |
| **Torque: grounding wire tightening** | 50Ib.in / 5.6Nm |
| **Neutral bus included** | EOHXSN4 |
| **Auxiliary contacts included** | Field-installable auxiliary contacts mountable in switch mechanism are to be ordered separately. |
| **Max. number of auxiliary contacts to be added** | 4no+4nc (early break) |
| **Enclosure construction type** | EOH4SS Type 4/4X: Enclosures constructed for either indoor or outdoor use to provide a degree of protection to personnel against incidental contact with the enclosed equipment; to provide a degree of protection against falling dirt, rain, sleet, snow, windblown dust, splashing water, hose-directed water, and corrosion (4X); and that will be undamaged by the external formation of ice on the enclosure. Material AISI316. |
| **Cabling direction** | TopBottom |
| **Enclosure colour** | Unpainted stainless steel grade 316 |
| **External Enclosure width/W** | 16.14in / 410mm |
| **External Enclosure height/H** | 37.44in / 951mm |
| **External Enclosure depth/D** | 7.32in / 186mm |
| **Cable outlets type** | Blank |
| **Cable outlets / top (øInch/mm)** | Blank |
| **Cable outlets / bottom (øInch/mm)** | Blank |
| **Number of door hinges** | 3 |
| **Number of door locking latches** | 3 |
| **Enclosure material specification** | Stainless steel AISI316 material thickness: door 0.059in/1.5mm, enclosure 0.059in/1.5mm, fixing plates 0.118in/3mm, handle shield 0.059in/1.5mm. |
| **Handle type** | Side-operated, fully insulated |
| **Handle color** | Black grip with red position ON indicator |
| **Handle material specification** | Handle grip: metallic insert, glass reinforced polyamide (PA f1)/ Red handle indicator: polycarbonate (PC f1). |
| **Type of packing** | Environment friendly corrugated cardboard |
| **Packingbox width** | 18.5in / 470mm |

Power and productivity for a better world™ ABB

# Fusible heavy duty safety switch with neutral, single throw EOH364NSS

| | |
|---|---|
| **Packingbox heigth** | 41.3in / 1050mm |
| **Packingbox depth** | 10.8in / 275mm |
| **Additional information** | Fusible heavy duty safety switch in grade 316 unpainted stainless steel sheet enclosure. Neutral assembly with bonding jumper is included. Suitable only for use as service equipment. Grounding bus is included. Padlockable in OFF-position with 3 padlocks of bail max. diameter 0.25in/6.4mm. Releasable door interlocking mechanism. Field-installable accessories and fuses are to be ordered separately. Factory mounted fuse base and clips for class H, K, RK1-5 fuses. Not for use as motor controller. |
| **Description FI** | Sulakkeellinen turvakytkin raskaaseen käyttöön |
| **Description EN** | Fusible heavy duty safety switch |
| **Description FR** | Interrupteur avec fusibles de sécurité pour service intensif |
| **Description ES** | Interruptor de seguridad de servicio pesado con fusibles |

## Technical information:
http://new.abb.com/low-voltage/launches/safetyswitches

## Catalogue:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/fa1d5d4923ab6eddc1257da200370e6b/$file/1SCC340010C0201.pdf

## Leaflet:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/c4e1234e4521d69ac1257c7b003240a2/$file/1SCC340007K0201.pdf

## Instruction bulletin:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/32753b9528f44814c1257d230034a00e/$file/1SCC340032M1401.pdf

## Drawing/PDF:
http://www05.abb.com/global/scot/scot209.nsf/veritydisplay/cec6074f0cd3d129c1257c99001fc7f5/$file/Z13_EOH364S.PDF

## Drawing/IGES:
http://new.abb.com/low-voltage/launches/safetyswitches/fusible-safety-switches

## Field-installable accessories:

| | |
|---|---|
| **Fuse mounting kits** | EOHFBK4 for Class T 200A fuses |
| **Fuse rejection member kits** | EOHRM34R for Class RK1-5 fuses |
| **Auxiliary contact NO type to be added** | OA1G10 |
| **Auxiliary contact NC type to be added** | OA3G01 |
| **Terminal cover Line side** | OTS400G1L/3, OTS400G1S/3 |
| **Hubs** | H075CP-TB, H100CP-TB, H125CP-TB, H200CP-TB, H250CP-TB |

## Replacement parts:

| | |
|---|---|
| **Terminal lugs for line and load side terminals** | OZXA-400/3 |
| **Grounding terminal** | OZXG1/2 |
| **Switch disconnect** | OT200US30EOHR |
| **Fuse base kits** | EOHFBR4LU |
| **Door locking mechanism** | EOHLM3 |
| **Handle assembly** | EOHHSS2 |

**Technical and product support**:
ABB OY Breakers and Switches
P.O.Box 622
FI-65101 Vaasa, Finland
Phone: +358 102211
e-Mail: switch.technicalservice@fi.abb.com

**Sales in USA**:
ABB Inc. / USA
16250 W Glendale Drive
New Berlin, WI 53151, USA
Phone: 888-385-1221
e-Mail: lvps.support@us.abb.com

**Sales in Canada**:
ABB Inc. / CANADA
2117, 32nd Avenue
Lachine, QC H8T 3J1, Canada
Phone: 514-420-3100
e-Mail: lvp.support@ca.abb.com

Power and productivity for a better world™

# DATA SHEET

Date: 18.8.2015

## Fusible heavy duty safety switch with neutral, single throw EOH364NSS

**EOH364NSS**

| | | |
|---|---|---|
| **A** | 39.02in | 991mm |
| **B** | 14.65in | 372mm |
| **F** | 7.32in | 186mm |
| **G** | 1.18in | 30mm |
| **N** | 0.83in | 21mm |
| **K** | 0.35in | 9mm |
| **L** | 0.35in | 9mm |
| **M** | 0.75in | 19mm |
| **H** | 39.8in | 1011mm |
| **W** | 17.28in | 439mm |
| **W1** | 18.54in | 471mm |
| **D** | 7.36in | 187mm |
| **E** | 9.25in | 235mm |

**EOH364NSS KNOCKOUT INFORMATION**
**TOP ENDWALL OF ENCLOSURE**

**No factory-made knockouts.**

Drillings or cutting for purpose-made cabling accessories is allowed inside blank surface A:

Width: 11.18in / 284mm

Depth: 5in / 127mm

Note: Vertical dimension is from mounting surface.

**EOH364NSS KNOCKOUT INFORMATION**
**BOTTOM ENDWALL OF ENCLOSURE**

**No factory-made knockouts.**

Drillings or cutting for purpose-made cabling accessories is allowed inside blank surface B:

Width: 11.18in / 284mm

Depth: 5in / 127mm

Note: Vertical dimension is from mounting surface.

Power and productivity for a better world™