



Declaration of Conformity (RoHS)

Page 1 of 2

We ABB Automation Products GmbH
Eppelheimer Strasse 82
D-69123 Heidelberg
Germany

declare that the products

Distributed Automation PLC, Distributed Automation I/O and Accessories for Programmable Logic Controllers PLCs
listed on page 2
manufactured after **1st June 2009**

to which this declaration relates, are following the provisions of EU Directive(s)

2002/95/EC applicable on Restriction of Hazardous Substances (RoHS)

The products are not in the product list of the RoHS directive. But in some case they are components of concerned equipments.

Nevertheless that the products are made RoHS compliant, the responsibility for the concerned equipment remains with the manufacturer of it.

This Declaration is subject to the provision of the respective delivery contract.

Heidelberg March 21st, 2013

ABB Automation Products GmbH

Head of PLC & Automation Germany

i.V. Gernot Gaub

Head of Quality & Laboratory

i.V. Roland Schmale

Document No. 1SAA960010-4406

ABB Automation Products GmbH

Postal address:
Postfach 10 16 80
69006 Heidelberg

Visiting address:
Eppelheimer Straße 82
69123 Heidelberg
Phone +49 6221 701 0
Telefax (Einkauf):+49 6203 717 240
Telefax: (Vertrieb):+49 6203 717 600
Internet: <http://www.abb.com/de>

Head Office:
Ladenburg
Registry Court:
Amtsgericht Mannheim
Commercial Register:
HRB 700229
USt-IdNr.: DE 115 300 097

Chairman of the Supervisory
Board:
Hans-Georg Krabbe
Managing Directors:
Till Schreiter (Chairman)
Daniel Huber

Bankers:
UniCredit Bank AG, Munich
Account: 654160252
Sorting Code: 700 202 70



Declaration of Conformity (RoHS)

Page 2 of 2

Type designator	Description
AI561	Analog input module, 4AI U/I
AI562	Analog input module, 2AI RTD
AI563	Analog input module, 4AI thermocouple
AO561	Analog output module, 2AO U/I
AX561	Analog input/output module, 4AI U/I / 2AO U/I
DC561	Digital input/output module, 16DC, Interfast
DI561	Digital input module, 8DI 24VDC
DI562	Digital input module, 16DI 24VDC
DI571	Digital input module, 8DI 100-240VAC
DO561	Digital output module, 8DO-transistor 24VDC 0.5A
DO571	Digital output module, 8DO-relay 120-240VAC 2A
DO572	Digital output module, 8DO-triac 100-240VAC 0.3A
DX561	Digital input/output module, 8DI 24VDC / 8DO-transistor 24VDC 0.5A
DX571	Digital input/output module, 8DI 24VDC / 8DO-relay 120/240VAC 2A
MC503	SD-Memory card adapter
PM554-R	CPU with 128kB user memory, digital I/O with relays, 24VDC supply
PM554-R-AC	CPU with 128kB user memory, digital I/O with relays, 100-240VAC supply
PM554-RP	CPU with 128kB user memory, digital I/O with relays, 24VDC supply
PM554-RP-AC	CPU with 128kB user memory, digital I/O with relays, 100-240VAC supply
PM554-T	CPU with 128kB user memory, digital I/O with transistor, 24VDC supply
PM554-T-ETH	CPU with 128kB user memory, Ethernet interface, digital I/O with transistor, 24VDC supply
PM554-TP	CPU with 128kB user memory, digital I/O with transistor, 24VDC supply
PM554-TP-ETH	CPU with 128kB user memory, Ethernet interface, digital I/O with transistor, 24VDC supply
PM556-TP-ETH	CPU with 512kB user memory, Ethernet interface, digital I/O with transistor, 24VDC supply
PM564-R	CPU with 128kB user memory, digital I/O with relays, analog I/O, 24VDC supply
PM564-R-AC	CPU with 128kB user memory, digital I/O with relays, analog I/O, 100-240VAC supply
PM564-R-ETH	CPU with 128kB user memory, Ethernet interface, digital I/O with relays, analog I/O, 24VDC supply
PM564-R-ETH-AC	CPU with 128kB user memory, Ethernet interface, digital I/O with relays, analog I/O, 100-240VAC supply
PM564-RP	CPU with 128kB user memory, digital I/O with relays, analog I/O, 24VDC supply
PM564-RP-AC	CPU with 128kB user memory, digital I/O with relays, analog I/O, 100-240VAC supply
PM564-RP-ETH	CPU with 128kB user memory, Ethernet interface, digital I/O with relays, analog I/O, 24VDC supply
PM564-RP-ETH-AC	CPU with 128kB user memory, Ethernet interface, digital I/O with relays, analog I/O, 100-240VAC supply
PM564-T	CPU with 128kB user memory, digital I/O with transistor, analog I/O, 24VDC supply
PM564-T-ETH	CPU with 128kB user memory, Ethernet interface, digital I/O with transistor, analog I/O, 24VDC supply
PM564-TP	CPU with 128kB user memory, digital I/O with transistor, analog I/O, 24VDC supply
PM564-TP-ETH	CPU with 128kB user memory, Ethernet interface, digital I/O with transistor, analog I/O, 24VDC supply
TA561-RTC	Option board with Real Time Clock
TA562-RS	Option board with RS485 serial interface
TA562-RS-RTC	Option board with Real Time Clock and RS485 serial interface
TA563-11	TA563-11/L444611:S500,Terminal block,F/S,11 scr.
TA563-9	TA563-9/L444609:S500,Terminal block,F/S,9 screw
TA564-11	TA564-11/L444411:S500,Terminal block,F/F,11 scr.
TA564-9	TA564-9/L444409:S500,Terminal block,F/F,9 screw
TA565-11	TA565-11/L444711:S500,Terminal block,F/F,11 spr.
TA565-9	TA565-9/L444709:S500,Terminal block,F/F,9 spring
TA571-SIM	AC500-eCo CPU input simulator
TK506	RS485 Isolator for COM1 of AC500-eCo CPU, D-Sub 9pole/Terminal 5pole

Document No. 1SAA960010-4406

ABB Automation Products GmbH

Postal address:
Postfach 10 16 80
69006 Heidelberg

Visiting address:
Eppelheimer Straße 82
69123 Heidelberg
Phone +49 6221 701 0
Telefax (Einkauf):+49 6203 717 240
Telefax: (Vertrieb):+49 6203 717 600
Internet: <http://www.abb.com/de>

Head Office:
Ladenburg
Registry Court:
Amtsgericht Mannheim
Commercial Register:
HRB 700229
USt-IdNr.: DE 115 300 097

Chairman of the Supervisory
Board:
Hans-Georg Krabbe
Managing Directors:
Till Schreiter (Chairman)
Daniel Huber

Bankers:
UniCredit Bank AG, Munich
Account: 654160252
Sorting Code: 700 202 70