

Stanilite®

Platinum exit LED Quickfit® DALI



Range

Platinum range

Product group

Exit LED Quickfit



Features

- LED technology 100,000 hours plus lamp life
- Low power consumption and LED light source for reduced operation and maintenance costs
- Advanced charging technology combined with Lithium iron phosphate battery for long life and low maintenance
- DALI lighting system
- Quickfit unique steel slide connect bracket for quick installation and easy maintenance
- Includes all pictograph diffuser options for single or double sided installation
- Universal wall/ceiling mounting, can also be rod or wire suspended
- Retrofit capability; fits into any existing Quickfit mounting bracket

Catalogue no.	Description
DALI products	
PQFDALEDP	Platinum exit LED Quickfit DALI pictograph
Accessories	
MQFCL	Cantilever bracket
QFWGCM	Wire guard - ceiling
QFWGWM	Wire guard - wall
PWQFKITPOLY	IP65 kit - polycarbonate for single or double sided installation
PWQFKITACRY	IP65 kit - acrylic for single or double sided installation
29-PIQFVERT	Quickfit pictograph vertical insert pack 4 piece set *
Note: * Refer to the installation manual for vertical installation requirements	
Spare parts	
03-01309PB	Battery LiFePO4 3.2V 3.2Ah
31-PQF	Diffuser Quickfit LED includes single sided pictograph decal
PQFDALEDP-LB	Platinum exit LED Quickfit less bracket DALI pictograph
PQFDALEDP-FR	Platinum exit LED Quickfit frame only DALI



Dimensions			
	Length	Width	Height (incl. bracket)
	379mm	72mm	214mm
Weight			
Model	Weight		
DALI	1.8kg		
Construction			
Part	Construction		
Body	FR ABS		
Diffuser	Opal acrylic		
Bracket	White powder coated zinc steel		

Light source		
Model	Light source	
DALI	Multiple LED 1.6W	

Power consumption		
Model	Power consumption	
DALI	3.2W	

Note: Preliminary results

Photometrics			
Model	Class	Classification	
DALI	C0	D3.2	
	C90	D3.2	

Note: Preliminary results

Note:

- Designed to comply with AS2293 and meet relevant Australian EMC standards