


FurseWELD

Cable to bar CB4

Cable to bar CB4 - FurseWELD



Stranded/solid conductor size A (mm ²)	Flat tape conductor size B (mm)	Mould part no.	Order code	Powder cartridge part no.	Handle clamp part no.
16 *	25 x 3	CB4-4-16253	7TCA083910R0800	45P10	HCPK4
25	25 x 3	CB4-4-25253	7TCA083910R0843	45P10	HCPK4
35	25 x 3	CB4-4-35253	7TCA083910R0851	45P10	HCPK4
50	25 x 3	CB4-4-50253	7TCA083910R0865	45P10	HCPK4
Ø 8	25 x 3	CB4-4-8SC253	7TCA083910R0908	45P10	HCPK4
70	25 x 3	CB4-4-70253	7TCA083910R0883	65P10	HCPK4
70	25 x 3	CB4-4-70253-IU	-	65P10	HCPK4
70	25 x 4	CB4-4-70254	7TCA083910R0884	65P10	HCPK4
70	25 x 4	CB4-4-70254-IU	-	65P10	HCPK4
70	25 x 6	CB4-4-70256	7TCA083910R0885	90P10	HCPK4
70	25 x 6	CB4-4-70404-IU	-	90P10	HCPK4
Ø 10	25 x 3	CB4-4-10SC253	7TCA083910R0759	65P10	HCPK4
Ø 10	25 x 4	CB4-4-10SC254	7TCA083910R0760	65P10	HCPK4
Ø 10	25 x 6	CB4-4-10SC256	7TCA083910R0761	90P10	HCPK4
95	25 x 4	CB4-4-95254	7TCA083910R0911	90P10	HCPK4
95	25 x 4	CB4-4-95254-IU	-	90P10	HCPK4
95	25 x 6	CB4-4-95256	7TCA083910R0912	115P10	HCPK4
120	25 x 6	CB4-4-120254-IU	-	115P10	HCPK4
120	25 x 6	CB4-4-120256	7TCA083910R0765	115P10	HCPK4
120	30 x 5	CB4-4-120305	7TCA083910R0769	115P10	HCPK4
150	25 x 6	CB4-4-150256	7TCA083910R0788	115P10	HCPK4
150	30 x 5	CB4-4-150305	7TCA083910R0789	115P10	HCPK4
150	40 x 5	CB4-4-150405	7TCA083910R0793	115P10	HCPK4
185	31 x 6	CB4-4-185316	7TCA083910R0810	150P10	HCPK4
185	40 x 5	CB4-4-185405	7TCA083910R0816	150P10	HCPK4
185	50 x 5	CB4-4-185505	7TCA083910R0820	150P10	HCPK4
240	50 x 5	CB4-4-240505	7TCA083910R0837	200P10	HCPK4
240	50 x 6	CB4-4-240506	7TCA083910R0838	250P10	HCPK4
240	50 x 6	CB4-4-240506-IU	-	250P10	HCPK4
300	50 x 6	CB4-5-300506	7TCA083910R0940	2 x 150P10	HCPK5

Special moulds for all FurseWELD products can be manufactured to meet specific customer applications on request

*1 x S103 Sleeve required when joining conductors 16 mm² or smaller

For order codes of powder cartridges and handle clamps, see pages 49-50

FurseWELD moulds should only be used with FurseWELD powders, handle clamps and accessories. If moulds, powders, handle clamps and accessories from other manufacturers are utilized, we cannot guarantee the safe use or the integrity of the completed joint

FurseWELD moulds for use with stranded conductor are designed for use with non-compacted conductor to BS EN 60228. If a mould for compacted conductor is required, please contact your local representative

Conductors must be installed in the orientation shown to achieve the correct connection