

Environmental Product Declaration

Protect^{IT} Protective Relays SPACOM 300 series



Company Information

ABB Oy, Distribution Automation in Finland is part of ABB's automation technology sector. The company is in charge of design, manufacturing and marketing of protection and automation equipment and systems for electrical networks, including services and software products.

Environmental management

The ISO 14001 environmental management system has been implemented and the Vaasa factory has been certified since 1997. Life cycle assessment (LCA) is continually applied to the products.

Application

A typical example of the SPACOM 300 series is the stabilized differential relay SPAD 346 C. The SPAD 346 C is designed for protecting two-winding power transformers and generator-transformer units against winding short-circuit, interterm fault, earth-fault and short-circuit, and generators and motors against interwinding short-circuit and pole short circuit.

Function

The relays incorporate a wide range of functions:

- Protection functions
- Measurement functions
- Control functions
- Communication
- Additional general functions
- Standard functions



ENVIRONMENTAL PERFORMANCE

Functional unit

The functional unit of our LCAs is an IED variant. The environmental impacts in the Life Cycle Assessment have been calculated for the most typical variant delivered of each product.

Manufacturing of the product

The manufacturing at ABB consists of assembling components manufactured and delivered to ABB by subcontractors, and calibration, testing and packing. The only negative impacts of the manufacturing phase are waste generation and some energy consumption. The amount of waste produced is minimized by waste sorting and reusable packaging.

Use of the product

The product can save equipment and resources when performing its function as a protection relay. The environmental impacts during the life cycle of the relays are caused by the electrical power consumption, not the operation itself.

Recycling of the product

It is recommended that the product is recycled by a company specialized in recycling of electronic equipment. ABB aims at continuously increasing the degree of recycling of the equipment manufactured. It is estimated that more than 70 weight percent can be recycled.

ENVIRONMENTAL IMPACT

Impact indicator values of a typical product variant of the SPACOM 300 series

Environmental impact categories	Manufacturing phase	Usage phase	Disposal phase	Total	Equivalent unit *
Acidification	96.81	212.19	-4.16	304.84	mol H ⁺
Global warming	442.68	1397.43	-25.36	1814.76	kg CO ₂
Eutrophication	17.31	16.63	-0.17	33.77	kg O ₂
Ozone depletion	0.00	0.00	0.00	0.00	kg CFC-11
Photochemical oxidant formation	0.24	0.27	0.00	0.50	kg Ethylene

* In order to illustrate the numbers above we can note that 1118 kg CO₂ is the amount-related operation of equipment consuming 8 W annually during 25 years. 170 mol H⁺ also corresponds to the above mentioned power consumption and emissions of SO₂ and NO_x. The eutrophication impact of 13 kg O₂ corresponds to the amount of phosphor needed to produce 50 kg grain using the fertilizer amount normal in the Nordic countries. The ozone depletion of 0.02 g is below 0.005% of the freon content of an old refrigerator. The photochemical oxidant formation can be compared to that of a medium-sized car used for approx. 1000 km.

Resource utilization during the life cycle of a typical product variant of the SPACOM 300 series

Use of non-renewable resources	Manufacturing phase	Usage phase	Disposal phase	Equivalent unit
Bauxite	7.74	0.11	-7.14	kg
Copper	0.52	0.02	0.00	kg
Crude oil	35.52	59.28	-2.56	kg
Hard coal	89.76	585.55	-6.54	kg
Iron in ore	3.94	4.02	-2.13	kg
Lignite	66.43	7.62	0.01	kg
Limestone	2.87	8.56	-0.43	kg
Natural gas	37.48	1.18	-0.48	kg
Uranium in ore	0.01	0.01	0.00	kg
Use of renewable resources				
Hydro energy	1450.37	1446.81	15.04	MJ
Wood	1.87	19.27	-0.04	kg

Energy consumption during the life cycle of a typical product variant of the SPACOM 300 series

Energy form	Manufacturing phase	Usage phase	Disposal phase**	Unit
World Electricity Mix	2195	2190	23	kWh
% of total	49.8	49.7	0.5	%

** In the assessment of the energy demanded for the disposal of the SPACOM 300 protection terminal, only the energy required for handling the steel scrap was taken into account. The energy demand of 9.35 MJ/kg of steel scrap is based on the information from the Methodology Report of the International Iron and Steel Institute.

Electricity World 1998 ETH-EPD

Generation of electricity with different power generating systems in the world during 1998. The percentage share of the Electricity World: Electricity biomass & waste 1.09%, Electricity coal 39.36%, Electricity gas 15.27%, Electricity geothermal 0.31%, Electricity hydro 18.35%, Electricity nuclear 16.97%, Electricity oil 8.52%.

Data have been adapted to the demands of the EPD (Environmental Product Declaration) guidelines in Sweden.

SUMMARY

The most significant environmental impact (Global Warming Potential indicator) is the power use during the product lifetime (10 W). The second biggest impact is coming from the production process of printed circuit boards.

The five environmental impact values

Acidification AP

Acidification originates from the emissions of sulphur dioxide and oxides of nitrogen. In the atmosphere, these oxides react with water vapour and form acids which subsequently fall down to the earth in form of rain or snow, or as dry depositions. Acidification potential translates the quantity of emission of substances into a common measure to compare their contributions to the capacity to release hydrogen ions.

Eutrophication NP

Nutrients (mainly nitrogen and phosphorus) from sewage outfalls and fertilised farmland accelerate the growth of algae and other vegetation in water. The degradation of organic material consumes oxygen resulting in oxygen deficiency and fish kill.

Global Warming Potential GWP

The index used to translate the level of emission of various gases into a common measure to compare their contributions to the absorption by the atmosphere of infrared radiation. GWPs are calculated as the absorption that would result from the emission of 1 kg of gas to that from the emission of 1 kg carbon dioxide over 100 years.

Ozone depletion ODP

The index used to translate the level of emissions of various substances into a common measure to compare their contributions to the breakdown of the ozone layer. ODPs are calculated as the change that would result from the emission of 1 kg of a substance to that from the emission of 1 kg of CFC-aa (a freon).

Photochemical ozone creation POCP

The index used to translate the level of emissions of various gases into a common measure to compare their contributions to the change of ground-level ozone concentration. POCPs are calculated as the change that would result from the emission of 1 kg of a gas to that from the emission of 1 kg of ethylene.

This product has been certified by ABB Group as **Industrial IT Enabled™ - Information Level**. All product information is supplied in interactive electronic format, based on ABB Aspect Object™ technology. The Industrial IT commitment from ABB ensures that every enterprise building block is equipped with the integral tools necessary to install, operate, and maintain it efficiently throughout the product lifecycle.



ABB Oy, Distribution Automation
P.O.Box 699
FIN-65101 VAASA, Finland
Phone: +358 10 22 11
Fax: +358 10 22 41094
www.abb.com/substationautomation