

## Material Safety Data Sheet

Report No.: BST-MSDS-02Product Name: Ni-MH Rechargeable BatteryDate: 2018-01-05

Australian Contact  
ABB Australia Pty Ltd  
1 Bapaume Road, Moorebank  
NSW 2170  
Mobile: 0414808069

Prepared by: *Nengzhi Chen* 2018.01.05  
Checked by: *Zhang Yong Hu* 5/1.18  
Approved by: *Guofeng Ma* 2018.1.5

## 1. Chemical Product and Company Identification

### Product Identification

Product model:

H-AAA, H-AA, H-A, H-SC, H-7/5SC,H-C, H-18700,H-18900

Nominal voltage: 1.2V

Discharge cut-off voltage:1.0V

### Temperature Range For Operation

Standard charge:0°C~+70°C

Trickle charge: 0°C~+70°C

Discharge:0°C~+70°C

### Temperature Range For Storage

Within 6 months: -20°C~+30°C

Within a month: -20°C~+40°C

Within 6 months: -20°C~+50°C

### Manufacturer

BST POWER (SHENZHEN) LIMITED

No.37 Xinlong Road, Dakang, Henggang Street ,Longgang District, Shenzhen.

### Emergency Telephone Number

Emergency Telephone: +86-84260300

Fax: /

E-mail: [bcw@bstbattery.com](mailto:bcw@bstbattery.com)

## 2. Composition Information

Description	Approximate % of total weight
Nickel hydroxide	36%
KOH	2%
Electrolyte	2%
Ni(OH) <sub>2</sub>	24%
Mercury	<5ppm
Other	36%

### **3. Hazards Identification**

#### **Fatalness:**

Basically non-toxic, but exposure to the ingredients contained or their ingredients products could be dangerous.

**Invasion route: Skin touch:** There will be no dangerous during normal use.

**Eye touch:** There will be no dangerous during normal use.

**Inhalation:** There will be no dangerous during normal use.

**Ingestion:** Ingestion of internal chemical materials may cause mouth, throat and intestinal buns irritation and damage. Get medical aid.

#### **Health hazards:**

For internal components, chemical materials are stored in a hermetically sealed shell, during normal use, there is no physical danger of ignition or explosion and chemical danger of hazardous materials leakage.

#### **Environment hazards:**

Ingredients contained or their ingredients products could be harmful to environment.

#### **Burn & Burst danger:**

Do not dispose of battery in fire - may explode. Do not short-circuit battery - may cause burns.

### **4. First Aid Measures**

The cell is not hazard with eye and skin contact under normal circumstance. In case of the enclosure is damaged, the cell can't be used and touched. It is safety except that the cell is damaged by fire or rupture. The leakage of internal hazardous substance and formation of hazardous substance would occur, take the following measures if contact with the cell.

#### **Skin touch:**

If there is any unwell felling, wash thoroughly with soap & water, flush with plenty of water. If irritation persists, seek medical advice.

#### **Eyes touch:**

Rinse immediately with plenty of water for at least 15 mins. Contact a doctor if symptoms persist.

**Inhalation:**

Remove from exposure site to fresh air. Keep at rest. Obtain medical attention.

**Ingestion:**

Rinse mouth out with water. Seek medical advice immediately.

**5. Fire Fighting Measures****Danger characteristic:**

Meet high fever, flame, there may cause explode danger.

**Extinguishing Media:**

Use dry graphite, sandy soil as appropriate for materials in surrounding fire.

**Fire-Fighting:**

The staff must wear the clothes which can deference the fire and toxic gas. Put out the fire in the upwind direction. Avoid using direct streams of water or foam on molten burning material as it may scatter and spread the fire.

**Recommended:** N/A

**Special measures:** N/A

**Extinguishing procedures:** N/A

**6. Accidental Release Measures****Personal precautions:**

If the cell is released, remove personnel from area until fumes dissipate. Provide maximum ventilation to clear out hazardous gases. The preferred response is to leave the area and allow the vapors to dissipate. Avoid skin and eyes contact or inhalation of vapors. Remove spilled liquid with absorbent and incinerated. If leakage of the cell happens, liquid could be absorbed with sand, earth or other inert substance and contaminated area should be ventilated meantime.

**Environment precautions:**

Make a limitation for burning and throwing into garbage. Do not flush into surface water.

**Cleaning up methods:** N/A

## **7. Handling and Storage**

### **Precautions in handling:**

Do not expose the cell to excessive physical shocked or vibration. Short-circuiting should be avoided. Prolonged short circuits may damage the cell.

### **Storage conditions:**

Don't place the cell near heating equipment, nor expose to direct sunlight for long periods. Elevated temperatures can result in shortened cell life and degrade performance.

## **8. Exposure Controls/Personal Protection**

### **Respiratory protection:**

No necessary under normal use. In case electrolyte leakage from the cell, protect hand with chemical resistant rubber gloves. If cell is burning, leave the area immediately.

### **Hand protection:**

None under normal use. In case of spilling, use PVC, neoprene or nitrile gloves of 15mils (0.015 inch) or thicker.

### **Eye protection:**

None required under normal conditions. Use approved chemical work safety goggles or face shield, if handling a leaking or rupture cell.

### **Skin protection:**

No necessary under normal use. Use rubber apron and protective working in case of handling of a rupture cell.

### **Other protective equipment:**

Chemical resistance clothing is recommended along with eye wash station and safety shower should be available. Work hygienic practices: Use good chemical hygiene practice. Wash hands after use and before drinking, eating or smoking. Wash hands thoroughly after cleaning-up component spill caused by leaking cell. No eating, drinking, or smoking in cell storage area.

## **9. Physical and Chemical Properties**

### **Physical State:**

The sample is not single chemical material; there are no specific physical and

chemical properties

**Color:** The sample is composed of several components, there is no specific color.

**Odor:** N.A

**Boiling point:** N.A

**Melting point:** N.A

## 10. Stability and Reactivity

**Stability:** Stable during normal operation conditions.

### **Conditions/materials to avoid:**

Incompatible with water, moisture, strong oxidizing agents, reducing agents, acids and bases.

### **Hazardous decomposition or byproducts:**

None under normal operating conditions. Carbon dioxide and hydrogen fluoride gas may be generated during combustion of cell.

**Ventilation requirements:** Well-ventilated area away from incompatible substances

## 11. Toxicological Information

Not applicable under normal conditions of use.

## 12. Ecological Information

**Degradability:** N.A

**Precautions:** Not available

## 13. Disposal Considerations

**Nature of waste:** Hazardous Waste

**Waste disposal methods:**

- a. Disposal of the cell should be performed by permitted, professional disposal firms knowledgeable in federal, state or local requirements of hazardous waste treatment and hazardous waste transportation.
- b. Incineration should never be performed by cell used. The batteries contained recyclable materials. Recycling options available in your local area should be considered when disposing of this product, through licensed waste carrier.
- c. The cell should have their terminal insulated in order to prevent short circuits during transportation to the disposal site.

**Note:** Consult your local or region authorities, disposal maybe subject to national, state, or local laws.

**14. Transport Information**

BST batteries are considered to be "Dry Cell" batteries and are unregulated for purposes of transportation by the U.S. Department of Transportation (DOT), International Civil Aviation Administration (ICAO), International Air Transport Association (IATA) and International Maritime Dangerous Goods Regulations (IMDG), The only DOT requirement for shipping these batteries is special provision 130 which states:"Batteries, dry are not subject to the requirements of this subchapter only when they are offered for transportation in a manner that prevents the dangerous evolution of heat (For example, by the effective insulation of exposed terminals). As of 1/1/97 IATA requires that batteries being transported by air must be protected from short-circuiting and protected from movement that could lead to short-circuiting.

**15.Regulatory Information**

Special requirement should be according to the local regulatory.

**16.Other Information**

The data in this Material Safety Data Sheet relates only to the specific material designated herein.