

CERTIFICATE OF COMPLIANCE

Certificate Number 20150602-E36588
Report Reference E36588-20150530
Issue Date 2015-JUNE-02

Issued to: ABB AB, CONTROL PRODUCTS
MOTORGRAND 20
SE-721 61 VASTERAS SWEDEN

**This is to certify that
representative samples of**

COMPONENT - MOTOR CONTROLLERS, MAGNETIC
See next page for Models/Product

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:

UL 60947-4-1 And CAN/CSA C22.2 No. 60947-4-1-07 -
Low-Voltage Switchgear and Controlgear – Part 1:
Contactors and motor-starters – Electromechanical
contactors and motor-starters


Additional Information:

See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's
Certification and Follow-Up Service.

Recognized components are incomplete in certain constructional features or restricted in performance
capabilities and are intended for use as components of complete equipment submitted for investigation rather
than for direct separate installation in the field. The final acceptance of the component is dependent upon its
installation and use in complete equipment submitted to UL LLC.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please
contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20150602-E36588
Report Reference E36588-20150530
Issue Date 2015-JUNE-02

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Open type, magnetic motor controllers and Type AF190B or AF205B followed by -30, followed by -22, followed by RT, followed by additional suffixes indicating coil voltage

May be used with USL,CNL - Accessories for AF190 or AF205 Contactors:

Terminal shroud Type. LT205-30C, LT205-30L

Connection device Type. LL205


Connection bar Type Nos. BEA205/XT4, BEA205/T4, BEA205H/XT4, BEA205H/T4, BER205-4, BEP205-30, BEY190-4, BEY205-4

Terminal extension Type. LY185, LX205, LW205, LP185

Aux. contact blocks Type. CAL19-11-RT, CAL19-11B-RT, CEL19-10-RT, CEL19-01-RT

Accessories Type. BFP205-30

Mechanical interlocks Type. VM19 and VM140/190



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

