



PRE-1/LED

Self-contained 1 watt, maintained surface mount led luminaire, including automatic self test, series Previs. The luminaire is including the pictogram escape route straight forward (P51-PRE).

Product Information

Type	PRE-1/LED
Catalog number	14062112
Category_	Escape route signalisation
GTIN	08713812749679
GID	7TCA091160R0021
Serie	Previs
Warranty (Year)	5
Other	The luminaire is equipped with a light dimming circuit, the minimum output is in accordance with the standard



Characteristics

Power supply system	Self-contained individual battery
Continuous operation	Yes
Mounting Method	Wall
Mounting form	Surface
Material housing	Plastic
Colour housing	White
Material cover	Plastic, transparent
Material	Polycarbonate
Colour	White
Length (mm)	287
Width (mm)	136
Height/depth (mm)	67
Nominal voltage (V)	230
Voltage type	AC
Duration (hours)	1
Battery	NiCd
Monitoring equipment	Automatic self test
With lamp	Yes
Lamp Type	Led
Lamp holder	Other
Lamp power (W)	1
Number of lamps	2
Average lifespan light source (hours)	100.000
Colour of light	White
Colour temperature (K)	6350
CRI	73
Protection class	II
Degree of protection (IP)	40
With remote switch connection	No
Wiring system	Maintained / non-maintained circuit
Type of indicator	Single / double-sided
Labelling type	Insert sheet/plate
Recognition distance (m)	25
Circuit	Other
Power consumption maintained mode (W)	5,2 / 1,5
Apparent power consumption maintained	

Apparent power consumption maintenance mode (VA)	10,3 / 4
Nominal current (mA)	44,7
Inrush Current (A - 0.1ms)	25
Powerfactor	0,5
Temperature range (°C)	0 ~ +35

Article Details

Product class	Emergency luminaire
E-code	EC001957
Discount group	30901
Harmonized code	9405408440
GLN	8713812000008

Ordering information

Orderable	Yes
Order-Unit	Pieces
Minimum order quantity	1
Order Increment	1

Supply Information

Weight (kg)	0,975
Packaging	Cardboard box
Packaging dimensions (LxWxH) (mm)	300 x 150 x 95