Breaker protection REQ650
Relion® 650 series Ver. 1.3

Features

- Fully IEC 61850 compliant
- Parallel Redundancy Protocol (PRP) according to IEC 62439-3 Ed.2
- Protection, control and monitoring integrated in one IED
- Extensive self-supervision including analog channels
- Four independent parameter setting groups
- Large HMI for visualization of single line diagrams and on-line measurements
- Accurate time synchronization via SNTP, DNP 3.0, IEC 60870-5-103 and IRIG-B serial interface
- Ethernet interface for fast and easy communication with PC
- Signal matrix for easy configuration of binary and analog signals
- User management and authority handling
- Activity logging
- Available in customized and configured solutions

Configured solutions

- Breaker bay with back-up protection functions, three-phase tripping
- Breaker bay with back-up protection functions, single-phase tripping, single busbar section
- Breaker bay with back-up protection functions, single-phase tripping, two busbar sections

Most important protection functions

- Current
  - Instantaneous phase overcurrent protection
  - Instantaneous residual overcurrent protection
  - Four step directional phase overcurrent protection with definite and inverse time characteristics with 2nd harmonic blocking
  - Four step residual non-directional/directional overcurrent protection with definite and inverse time characteristics and with voltage, current or dual polarization, based on zero sequence or negative sequence quantities with 2nd harmonic blocking
  - Sensitive directional earth-fault protection
  - Thermal overload protection
  - Breaker failure protection
  - Stub protection
  - Pole discordance protection
  - Broken conductor check
  - Two step negative sequence based overcurrent protection
- Power functions
  - Directional under- and overpower protection
- Voltage
  - Two step phase- and residual overvoltage protection with definite and inverse time characteristics
  - Two step undervoltage protection with definite and inverse time characteristics
  - Loss of voltage check
- Frequency protection
  - Under- and overfrequency protection
  - Rate-of-change frequency protection
- Secondary system supervision
  - Current circuit supervision
  - Fuse failure supervision
  - Breaker close/trip circuit monitoring

Control functions

- Selective single-phase and three-phase autorecloser
- Synchronizing, synchrocheck and energizing check
- Selectable operator place allocation
- Control of circuit breaker from local/remote
- Versatile switch with two positions
- Selector switch with up to 32 positions

Logic
- Tripping logic
- Trip matrix logic
- Configurable logic blocks
- Configurable logic blocks with quality and time

Monitoring
- Disturbance recorder
  - 100 disturbances
  - 40 analog channels (30 physical and 10 derived)
  - 96 binary channels
- Event list for 1000 events
- User activity logging for 2048 entries
- Disturbance report
- Event and trip value recorders
- Event counters
- Supervision of AC input quantities
- Insulation gas monitoring function
- Insulation liquid monitoring function
- Circuit breaker condition monitoring
- Station battery supervision
- Indication of up to 135 binary signals via 15 three-color-state indication LEDs

Measurements
- U, I, P, Q, S, f and cos φ
- AC input quantities with accuracy better than 0.5%

Metering
- Energy metering function for energy statistics
- Pulse counting support for energy metering

Communication
- IEC 61850-8-1 including GOOSE messaging
- DNP 3.0 slave protocol
- IEC 60870-5-103 serial communication
- Parallel Redundancy Protocol (PRP) according to IEC 62439-3 Ed.2

Setting, configuration and disturbance handling
- Protection and control IED manager PCM600

Hardware
- 1/1 x 19” width, 3U height case
- 10 analog inputs (5 CT and 5 VT inputs) in configured solutions
- Universal 1A/5A CT inputs
- Choice of communication and processor module with
  - 12 binary inputs, TCP/IP optical, IRIG-B, galvanic RS485 and optical serial communication ports
  - TCP/IP optical with PRP redundancy, IRIG-B, galvanic RS485 and optical serial communication ports
- Binary input/output modules with 9 inputs and 9 outputs
- Possibility to add up to two optional binary input/output modules depending on the selected configured solution
- I/Os customizable to
  - 10 analog inputs (selected combinations of CT/VT inputs) and up to four binary input/output modules
  - 20 analog inputs (selected combinations of CT/VT inputs) and up to two binary input/output modules
- Power supply modules from 24 to 30 V DC, 48 to 250 V DC or 100 to 240 V AC with 9 outputs, 3 of which with trip circuit supervision
- Connector types: compression type or ring-lug type

Technical details are available in the REQ650 Product Guide.

For more information please contact:

ABB AB
Substation Automation Products
721 59 Västerås, Sweden
Phone: +46 (0) 21 32 50 00

www.abb.com/protection-control

Note:
We reserve the right to make technical changes or modify the contents of this document without prior notice. ABB AB does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.
We reserve all rights in this document and in the subject matter and illustrations contained herein. Any reproduction, disclosure to third parties or utilization of its contents – in whole or in part – is forbidden without prior written consent of ABB AB.

© Copyright 2013 ABB. All rights reserved.

Scan this QR code to visit our website

1MRK500112-SEN 10/2013

Power and productivity
for a better world™