


---

 TECHNICAL DATA SHEET

# Commercial Hubs

## *Steel City*<sup>®</sup>



01

02

---

 01 - Commercial Hub  
 02 - Commercial Grounded Hub

---

**Description:**

- The Steel City Commercial die-cast zinc hub with insulated throat and sealing ring is the perfect choice to terminate conduits in an enclosure or box, providing superior sealing for exceptional watertight performance

---

**Features & Benefits:**

- Die-cast zinc hub with insulated throat and sealing ring for smooth wire pulling and environmental protection
- Available in grounding and standard version for maximum flexibility in planning
- Full range of trade sizes from ½" to 4"
- Part of comprehensive Steel City portfolio for commercial, industrial and residential construction

The Steel City Commercial die-cast zinc hub with insulated throat and sealing ring for Rigid/IMC applications.

**Certifications / Standards:**



---

**Certifications/Standards:**

- Standard: UL/cUL File No. E23018
- Grounding: UL/cUL File No. E3060
- Suitable for wet locations
- Conforms to UL514B



---

**Material / Materials / Finishes:**

- Body and Locknut – Zamak #3 Type Zinc
- Insulated Throat – Flame Retardant PP Compound Resin
- Sealing Ring – Nitrile Rubber
- Finish: Natural

## Steel City Commercial Hubs

Product selection and dimensions:

Product Selection								
	CAT NO.	Trade Size	A	B	Pack Qty.	Weight (lb/ea)	Grounding Screw Size	Max Ground Conductor Size (Cu/AL)
<b>Standard Commercial Hub</b>								
	HUB050-SC	½"	1.39	1.41	25	0.159	–	–
	HUB075-SC	¾"	1.54	1.65	10	0.258	–	–
	HUB100-SC	1"	1.76	1.94	10	0.332	–	–
	HUB125-SC	1½"	1.70	2.40	2	0.446	–	–
	HUB150-SC	1½"	1.78	2.69	2	0.588	–	–
	HUB200-SC	2"	1.77	3.17	2	0.825	–	–
	HUB250-SC	2½"	2.57	3.68	2	1.424	–	–
	HUB300-SC	3"	2.56	4.32	2	1.814	–	–
	HUB350-SC	3½"	2.56	4.94	1	2.194	–	–
	HUB400-SC	4"	2.48	5.42	1	2.518	–	–
<b>Grounding Commercial Hub</b>								
	HUB050GR-SC	½"	1.39	1.41	25	0.169	#10-24 UNC	8 AWG
	HUB075GR-SC	¾"	1.54	1.65	10	0.266	#10-24 UNC	6 AWG
	HUB100GR-SC	1"	1.76	1.94	10	0.344	#10-24 UNC	6 AWG
	HUB125GR-SC	1½"	1.70	2.40	2	0.465	#¼-20 UNC	4 AWG
	HUB150GR-SC	1½"	1.78	2.69	2	0.610	#¼-20 UNC	4 AWG
	HUB200GR-SC	2"	1.77	3.17	2	0.848	#¼-20 UNC	2 AWG
	HUB250GR-SC	2½"	2.57	3.68	2	1.461	#¼-20 UNC	1 AWG
	HUB300GR-SC	3"	2.56	4.32	2	1.833	#¼-20 UNC	1/0 AWG
	HUB350GR-SC	3½"	2.56	4.94	1	2.238	#¼-20 UNC	1/0 AWG
	HUB400GR-SC	4"	2.48	5.42	1	2.549	#¼-20 UNC	1/0 AWG

Note: Product must be installed in accordance with applicable national and local electrical codes.

ABB Inc.  
Electrification products  
Memphis, Tennessee  
USA

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB Inc. does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction – in whole or in parts – is forbidden without prior written consent of ABB Inc. Copyright © 2018 ABB Inc.  
All rights reserved

Let's write the future.  
Together. [abb.com](http://abb.com)