



# IECEx Certificate of Conformity

## INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification System for Explosive Atmospheres

for rules and details of the IECEx Scheme visit [www.iecex.com](http://www.iecex.com)

Certificate No.: **IECEx BVS 17.0073** Page 1 of 3 [Certificate history:](#)

Status: **Current** Issue No: 0

Date of Issue: 2019-12-09

Applicant: **ABB STOTZ-KONTAKT GmbH**  
Eppelheimer Straße 82  
69123 Heidelberg  
Germany

Equipment: **Thermal overload relay type TF42-\***

Optional accessory:

Type of Protection: **Flameproof enclosures "d"; Increased safety "e"; Dust ignition protection by enclosure "t"**

Marking: [Ex]

Approved for issue on behalf of the IECEx  
Certification Body:

**Jörg Koch**

Position:

**Head of Certification Body**

Signature:  
(for printed version)

Date:

1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting [www.iecex.com](http://www.iecex.com) or use of this QR Code.



Certificate issued by:

**DEKRA Testing and Certification GmbH**  
Certification Body  
Dinnendahlstrasse 9  
44809 Bochum  
Germany

 **DEKRA**  
On the safe side.



# IECEX Certificate of Conformity

Certificate No.: **IECEX BVS 17.0073**

Page 2 of 3

Date of issue: 2019-12-09

Issue No: 0

Manufacturer: **ABB STOTZ-KONTAKT GmbH**  
Eppelheimer Straße 82  
69123 Heidelberg  
Germany

Additional  
manufacturing  
locations:

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended

## STANDARDS :

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

**IEC 60079-0:2017** Explosive atmospheres - Part 0: Equipment - General requirements  
Edition:7.0

**IEC 60079-1:2014-06** Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d"  
Edition:7.0

**IEC 60079-31:2013** Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure "t"  
Edition:2

**IEC 60079-7:2017** Explosive atmospheres - Part 7: Equipment protection by increased safety "e"  
Edition:5.1

This Certificate **does not** indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

## TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Report:

[DE/BVS/ExTR19.0077/00](#)

Quality Assessment Report:

[DE/BVS/QAR14.0004/06](#)



# IECEX Certificate of Conformity

Certificate No.: **IECEX BVS 17.0073**

Page 3 of 3

Date of issue: 2019-12-09

Issue No: 0

## **EQUIPMENT:**

Equipment and systems covered by this Certificate are as follows:

### **General product information:**

The thermal overload relays were tested according to IEC 60947-4-1:2009/A1:2012 and IEC 60947-5-1:2003/A1:2009.

A thermal overload relay (bi-metallic overload relay) has been installed, which has a delaying effect and a phase failure protection, so that the switches of the safety device (protective device for indirect temperature control) can be used to protect motors in order to avoid non-permitted temperatures.

In general they can be used if the electrical engine is protected by indirect temperature monitoring. This should be stated in the Test Report. The thermal overload relay will be erected outside of the hazardous area.

The thermal overload relays are safety devices. They contribute to or are required for the safe functioning of equipment with respect to the hazards of ignition or with respect to the hazard of uncontrolled explosion. The overload relays can be used as overload protective devices for electric motors of type of protection Ex e 'Increased Safety' or Ex d 'Flameproof Enclosure' e.g.

The type series TF42-\* consists of 23 modules which differ in their current setting ranges, reaching from 0.13 A to 40 A. The individual types of each module are of identical electrical construction. In the full labelling, the asterisk (\*) will be replaced by the maximum rated operating current which can be set and which stands for the following values:

Table see Annex

### **Electrical parameters**

See Annex

### **Other parameters**

See Annex

**SPECIFIC CONDITIONS OF USE: NO**