

# Stanilite®

## Platinum exit LED Quickfit® theatre mask



### Range

Platinum range

### Product group

Exit LED Quickfit



### Features

- LED technology 100,000 hours plus lamp life
- Low power consumption and LED light source for reduced operation and maintenance costs
- Advanced charging technology combined with Lithium iron phosphate battery for long life and low maintenance
- Quickfit unique steel slide connect bracket for quick installation and easy maintenance
- Includes all pictograph diffuser options for single sided installation
- Universal wall/ceiling mounting, can also be rod or wire suspended
- Retrofit capability; fits into any existing Quickfit mounting bracket

Catalogue no.	Description
<b>EM products</b>	
PQFBLEDP	Platinum exit LED Quickfit theatre mask single sided includes all pictograph inserts
<b>Accessories</b>	
MQFCL	Cantilever bracket (white)
QFWGCM	Wire guard - ceiling
QFWGWM	Wire guard - wall
PWQFKITPOLY	IP65 kit - polycarbonate for single or double sided installation
PWQFKITACRY	IP65 kit - acrylic for single or double sided installation
21-OPMD056	Diffuser theatre mask without pictograph inserts *
29-PIQFTM	Standard theatre mask pictograph inserts
Note: * For a double sided configuration additional diffuser 21-OPMD056 is required	
<b>Spare parts</b>	
03-01302P	Battery LiFePO4 3.2V 3.2Ah
PQFBLEDP-LB	Platinum exit LED Quickfit theatre mask less bracket pictograph
PQFBLEDP-FR	Platinum exit LED Quickfit theatre mask frame only

Note:

- The exit comes complete including pictograph insert pack as single sided exit. For double sided exit add diffuser 21-OPMD056



Dimensions			
	Length	Width	Height (incl. bracket)
	379mm	72mm	214mm
Weight			
	Model	Weight	
	EM	1.8kg	

<b>Construction</b>		
	<b>Part</b>	<b>Construction</b>
	Body	UV/FR ABS body
	Diffuser	Acrylic
	Bracket	Black powder coated zinc steel
<b>Light source</b>		
	<b>Model</b>	<b>Light source</b>
	EM	Multiple LED 1.6W
<b>Power consumption</b>		
	<b>Model</b>	<b>Power consumption</b>
	EM	3.2W

Note: Preliminary results

Note:

- Designed to comply with AS2293 and meet relevant Australian EMC standards