
 TECHNICAL DATA SHEET

PMA Smart Line - ALAD-M - Fitting

45°elbow, one-piece, IP66, metric thread

PMA



One-piece, IP66 polyamide fitting for flexible non-metallic conduit



Applications:

- In machine building, installation and construction industries

Features & Benefits:

- Economical
- Easy „push-in“ installation
- Re-opening with screwdriver (for security reasons hand opening not possible)
- Space saving due to compact design
- Fits both conduit profiles - fine (T) and coarse (G)

Ingress protection:

- IP66 (EN/IEC 60529)

Materials:

- High-grade, specially formulated polyamide 6

Compatible with:

- PMAFLEX Pro Conduits
- PMAFLEX Multilayer Conduits
- PMAFLEX Conduits
- PMA Smart Line Conduits

Weathering resistance:

- Very good UV resistance and weathering characteristics, particularly in black

Colour:

- Black
- Grey

Chemical properties:

- Please refer to www.pma.ch (Technical Information / Chemical Resistance)


Environmental properties:

- Free from halogens and cadmium
- RoHS and REACH compliant

Product selection:

Part no.		Thread size	Conduit size	Dimensions in mm (nom.)				Weight	Packing unit
black	grey	metric	NW	g	d2	A	B	kg/100 pcs	pcs/PU
ALAD-M120	SLAD-M120	M12x1.5	10	11.0	21.5	42.5	33.0	0.6	100
ALAD-M160	SLAD-M160	M16x1.5	10	11.0	21.5	42.5	35.0	0.7	100
ALAD-M162	SLAD-M162	M16x1.5	12	11.0	25.0	47.5	39.5	0.8	100
ALAD-M202	SLAD-M202	M20x1.5	12	11.0	25.0	47.5	41.5	0.9	100
ALAD-M207	SLAD-M207	M20x1.5	17	11.0	31.0	54.0	46.0	1.2	100
ALAD-M253	SLAD-M253	M25x1.5	23	12.0	39.0	63.5	55.5	2.2	50
ALAD-M257	SLAD-M257	M25x1.5	17	12.0	31.0	55.0	48.5	1.3	100
ALAD-M323	SLAD-M323	M32x1.5	23	15.0	39.0	67.0	60.0	2.3	50
ALAD-M329	SLAD-M329	M32x1.5	29	15.0	46.0	72.5	63.5	3.2	30
ALAD-M406	SLAD-M406	M40x1.5	36	19.0	56.0	87.5	78.0	5.6	20
ALAD-M409	SLAD-M409	M40x1.5	29	19.0	46.0	76.5	66.5	3.2	30
ALAD-M506	SLAD-M506	M50x1.5	36	19.0	56.0	88.0	82.0	5.6	20
ALAD-M508	SLAD-M508	M50x1.5	48	19.0	68.0	97.5	88.0	8.5	10
ALAD-M638	SLAD-M638	M63x1.5	48	19.0	68.0	97.5	94.5	7.8	10

Our customer service dept. or local distribution partner will be pleased to help you concerning product availability and lead time



Mechanical Properties:	Value:	Test parameters:	Test method:
Tensile modulus	1'200 ... 3'700 N/mm ²		ISO 527
Tensile strength	45 ... 65 N/mm ²		ISO 527
Notched bar impact test	4 ... 20 kJ/m ²		ISO 180/1C

Thermal properties:	Value:	Test parameters:	Test method:
Continuous application temperature	-50 ... +105°C		PMA DO 9.21-4510
Upper application temperature	+120°C	(20'000 h)	PMA DO 9.21-4360
Short-term	+160°C	(168 h)	PMA DO 9.21-4360

Fire safety properties:	Value:	Test parameters:	Test method:
Fire performance	non flame-propagating		IEC EN 61386-1
Flame class	V2		UL 94

Content of delivery:

- Fitting

Assembly instructions:

- When mounting, push-in conduit completely and then pull back slightly to ensure the locking mechanism is fully engaged
- To Disassembly: reopen with screwdriver and tiwst for easy release
- Please consider the appropriate assembly instructions on www.pma.ch

ABB Switzerland Ltd,
PMA Cable Protection
Aathalstrasse 90
8610 Uster, Switzerland
Phone: +41 58 585 00 11
pma-info@ch.abb.com
www.pma.ch

Let's write the future.
Together. **abb.com**

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB Installation Products Inc. does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its contents – in whole or in parts – is forbidden without prior written consent of ABB Inc. Copyright© 2019 ABB Installation Products Inc. All rights reserved

