

## SAFETY DATA SHEET

# Mercasol 3110 WaxCoat

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

##### Trade name

Mercasol 3110 WaxCoat

##### Product no.

44700

##### Unique formula identifier (UFI)

E471-20D0-700R-A9G2

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses of the substance or mixture

Used as corrosion protection on iron and steel structures that are not exposed to direct mechanical abrasion. Used as topcoat in the Waxcoat system  
Restricted to professional users.

##### Use descriptors (UK REACH)

Sectors of use	Description
----------------	-------------

LCS "IS"	Industrial uses: Uses of substances as such or in preparations at industrial sites
----------	--

Product category	Description
------------------	-------------

PC 14	Metal surface treatment products, including galvanic and electroplating products
-------	--

##### Uses advised against

None known.

#### 1.3. Details of the supplier of the safety data sheet

##### Company and address

###### Auson AB

Verkstadsgatan 3  
S-434 42 KUNGSBACKA  
Sweden

##### Contact person

Nina Nyth

##### E-mail

nina.nyth@auson.se

##### Revision

07/01/2024

##### SDS Version

1.0

#### 1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).  
See section 4 "First aid measures".

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Flam. Liq. 3; H226, Flammable liquid and vapour.  
Skin Sens. 1; H317, May cause an allergic skin reaction.  
STOT SE 3; H336, May cause drowsiness or dizziness.

#### 2.2. Label elements

##### Hazard pictogram(s)



##### Signal word

Warning

#### Hazard statement(s)

Flammable liquid and vapour. (H226)  
May cause an allergic skin reaction. (H317)  
May cause drowsiness or dizziness. (H336)

#### Precautionary statement(s)

##### General

-

##### Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)  
Avoid breathing mist/vapour. (P261)  
Use only outdoors or in a well-ventilated area. (P271)  
Wear eye protection/protective gloves/protective clothing. (P280)

##### Response

IF SWALLOWED: Immediately call a POISON CENTER/doctor. (P301+P310)  
IF INHALED: Remove person to fresh air and keep comfortable for breathing. (P304+P340)

##### Storage

Store in a well-ventilated place. Keep cool. (P403+P235)

##### Disposal

Dispose of contents/container in accordance with local regulation (P501)

#### Hazardous substances

Naphtha (petroleum), hydrotreated heavy, benzene < 0,1%  
Calcium sulfonate

#### Additional labelling

EUH066, Repeated exposure may cause skin dryness or cracking.  
UFI: E471-20D0-700R-A9G2

#### VOC

VOC content: 388 g/L  
MAXIMUM VOC CONTENT (Phase II, category B/e: 840 g/L)

### 2.3. Other hazards

#### Additional warnings

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.  
This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable. This product is a mixture.

### 3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Naphtha (petroleum), hydrotreated heavy, benzene < 0,1%	CAS No.: 64742-48-9 EC No.: 919-857-5 UK-REACH: Index No.: 649-327-00-6	35 - 40 %	EUH066 Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336	[15], [19]
Wax	CAS No.: 63231-60-7 EC No.: 264-038-1 UK-REACH: Index No.:	10 - 15 %		
Calcium sulfonate	CAS No.: 61789-86-4 EC No.: 263-093-9 UK-REACH: Index No.:	10-15%	Skin Sens. 1B, H317	[19]
Talc	CAS No.: 14807-96-6 EC No.: 238-877-9 UK-REACH: Index No.:	3 - 5 %		
Oleic acid, compound with (Z)-N-octadec-9-enylpropane-1,3diamine (2:1)	CAS No.: 34140-91-5 EC No.: 251-846-4 UK-REACH: Index No.:	< 0,6 %	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT RE 2, H373 Aquatic Acute 1, H400	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

#### Other information

[15] The classification as a carcinogen / mutagen will not be taken into account as the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7) (CLP, Annex VI, note P).

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet.  
Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

##### Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

##### Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

##### Eye contact

If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during transport.

##### Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

##### Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

#### 4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact.

Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Call a POISON CENTER/doctor if you feel unwell.

If skin irritation or rash occurs: Get medical advice/attention.

#### Information to medics

Bring this safety data sheet or the label from this product.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

Flammable liquid and vapour.

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

#### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact

The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

Hazchem Code: ●3Y

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Avoid direct contact with spilled substances.

Ensure adequate ventilation, especially in confined areas.

Avoid inhalation of vapours from spilled material.

Contaminated areas may be slippery.

### 6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

### 6.3. Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

### 6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Ground and bond container and receiving equipment.

Use explosion-proof [electrical/lighting/ventilating] equipment.

Use non-sparking tools.

Take action to prevent static discharges.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

### 7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Take action to prevent static discharges.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

#### Recommended storage material

Always store in containers of the same material as the original container.

#### Storage temperature

Dry, cool and well ventilated. Shelf life: 12 months

#### Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

### 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Natural Calcium Carbonate

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 10(inhalable)/4(respirable)

Talc

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 1

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.  
EH40/2005 Workplace exposure limits (Fourth Edition 2020).

### DNEL

Calcium sulfonate

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Dermal	513 µg/cm <sup>2</sup>

Long term – Local effects - Workers	Dermal	1.03 mg/cm <sup>2</sup>
Long term – Systemic effects - General population	Dermal	1.667 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	3.33 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	2.9 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	11.75 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	833.3 µg/kgbw/day
Naphtha (petroleum), hydrotreated heavy, benzene < 0,1%		
<b>Duration:</b>	<b>Route of exposure:</b>	<b>DNEL:</b>
Long term – Local effects - General population	Inhalation	178.57 mg/m <sup>3</sup>
Long term – Local effects - Workers	Inhalation	837.5 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Inhalation	410 µg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	1.9 mg/m <sup>3</sup>
Short term – Local effects - General population	Inhalation	640 mg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	1066.67 mg/m <sup>3</sup>
Short term – Systemic effects - General population	Inhalation	1152 mg/m <sup>3</sup>
Short term – Systemic effects - Workers	Inhalation	1286.4 mg/m <sup>3</sup>
Oleic acid, compound with (Z)-N-octadec-9-enylpropane-1,3diamine (2:1)		
<b>Duration:</b>	<b>Route of exposure:</b>	<b>DNEL:</b>
Long term – Systemic effects - General population	Dermal	5 µg/kgbw/day
Long term – Systemic effects - Workers	Dermal	14 µg/kgbw/day
Long term – Systemic effects - General population	Inhalation	17.4 µg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	98.4 µg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	5 µg/kgbw/day
Talc		
<b>Duration:</b>	<b>Route of exposure:</b>	<b>DNEL:</b>
Long term – Local effects - General population	Dermal	2.27 mg/cm <sup>2</sup>
Long term – Local effects - Workers	Dermal	4.54 mg/cm <sup>2</sup>
Long term – Systemic effects - General population	Dermal	21.6 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	43.2 mg/kg bw/day
Long term – Local effects - General population	Inhalation	1.8 mg/m <sup>3</sup>
Long term – Local effects - Workers	Inhalation	3.6 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Inhalation	1.08 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	2.16 mg/m <sup>3</sup>
Short term – Local effects - General population	Inhalation	1.8 mg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	3.6 mg/m <sup>3</sup>
Short term – Systemic effects - General population	Inhalation	1.08 mg/m <sup>3</sup>
Short term – Systemic effects - Workers	Inhalation	2.16 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	160 mg/kg bw/day
Short term – Systemic effects - General population	Oral	160 mg/kg bw/day
<b>PNEC</b>		
Calcium sulfonate		
<b>Route of exposure:</b>	<b>Duration of Exposure:</b>	<b>PNEC:</b>
Freshwater		1 mg/L
Freshwater sediment		226000000 mg/kg
Intermittent release (freshwater)		10 mg/L
Marine water		1 mg/L
Marine water sediment		226000000 mg/kg

Predators	16.667 mg/kg
Sewage treatment plant	1 g/L
Soil	271000 g/kg
Oleic acid, compound with (Z)-N-octadec-9-enylpropane-1,3diamine (2:1)	
<b>Route of exposure:</b>	<b>Duration of Exposure:</b> <b>PNEC:</b>
Freshwater	6.46 µg/L
Freshwater sediment	388 mg/kg
Intermittent release (freshwater)	4.1 µg/L
Marine water	646 ng/L
Marine water sediment	38.8 mg/kg
Soil	11.1 mg/kg
Talc	
<b>Route of exposure:</b>	<b>Duration of Exposure:</b> <b>PNEC:</b>
Air	10 mg/m³
Freshwater	597.97 mg/L
Freshwater sediment	31.33 mg/kg
Intermittent release (freshwater)	597.97 mg/L
Intermittent release (marine water)	141.26 mg/L
Marine water	141.26 mg/L
Marine water sediment	3.13 mg/kg

## 8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

### General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

### Exposure scenarios

There are no exposure scenarios implemented for this product.

### Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

### Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

### Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

### Measures to avoid environmental exposure

No specific requirements.

## Individual protection measures, such as personal protective equipment

### Generally

Use only UKCA marked protective equipment.



### Respiratory Equipment

Type	Class	Colour	Standards
Respiratory protection is not needed in the event of adequate ventilation.			

### Skin protection

Recommended	Type/Category	Standards
Wear appropriate protection clothing, e.g. coveralls in polypropylene or working clothes in	-	-



Recommended	Type/Category	Standards	
cotton or polyester.			
Hand protection			
Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
Nitrile	0,38	> 480	EN374-2, EN374-3, EN388
			
Eye protection			
Type	Standards		
Safety glasses	EN166		
			

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Physical state

Liquid

#### Colour

Tan

#### Odour / Odour threshold

Solvent

#### pH

Not applicable - pH is not defined for non-aqueous systems

#### Density (g/cm<sup>3</sup>)

1,08 -1,12 (20 °C)

#### Kinematic viscosity

>20,5 mm<sup>2</sup>/s (40 °C)

#### Particle characteristics

Not applicable - product is a liquid

#### Phase changes

##### Melting point/Freezing point (°C)

Not applicable - product is a liquid

##### Softening point/range (waxes and pastes) (°C)

Does not apply to liquids.

##### Boiling point (°C)

150 - 200

##### Vapour pressure

3 hPa (20 °C)

##### Relative vapour density

> 3

##### Decomposition temperature (°C)

Not applicable - based on structure

#### Data on fire and explosion hazards

##### Flash point (°C)

40

##### Flammability (°C)

The material is ignitable.

##### Auto-ignition temperature (°C)

>200

##### Lower and upper explosion limit (% v/v)

0.6 - 7

#### Solubility

##### Solubility in water

Insoluble

##### n-octanol/water coefficient (LogKow)

> 6

#### Solubility in fat (g/L)

Testing not relevant or not possible due to the nature of the product.

#### 9.2. Other information

##### VOC (g/l)

388

##### Oxidizing properties

Non-oxidizing

##### Other physical and chemical parameters

No data available.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No data available.

#### 10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

#### 10.3. Possibility of hazardous reactions

None known.

#### 10.4. Conditions to avoid

Avoid static electricity.

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

#### 10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

#### 10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 as retained and amended in UK law

##### Acute toxicity

Product/substance	Naphtha (petroleum), hydrotreated heavy, benzene < 0,1%
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	> 5000 mg/m <sup>3</sup>

Product/substance	Naphtha (petroleum), hydrotreated heavy, benzene < 0,1%
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	> 2000 mg/kg

Product/substance	Naphtha (petroleum), hydrotreated heavy, benzene < 0,1%
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	> 2000 mg/kg

##### Skin corrosion/irritation

Based on available data, the classification criteria are not met.

##### Serious eye damage/irritation

Based on available data, the classification criteria are not met.

##### Respiratory sensitisation

Based on available data, the classification criteria are not met.

##### Skin sensitisation

May cause an allergic skin reaction.

##### Germ cell mutagenicity

The chemical structure does not suggest a mutagenic effect.

##### Carcinogenicity

Does not present any cancer hazards.

##### Reproductive toxicity

The chemical structure does not suggest such an effect.

##### STOT-single exposure



May cause drowsiness or dizziness.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Not classified.

#### 11.2. Information on other hazards

##### Long term effects

None known.

##### Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

##### Other information

Talc has been classified by IARC as a group 3 carcinogen.

## SECTION 12: Ecological information

### 12.1. Toxicity

Product/substance	Naphtha (petroleum), hydrotreated heavy, benzene < 0,1%
Species:	Fish
Duration:	No data available.
Result:	> 100 mg/L

Product/substance	Naphtha (petroleum), hydrotreated heavy, benzene < 0,1%
Species:	Algae
Duration:	No data available.
Result:	> 100 mg/L

Product/substance	Naphtha (petroleum), hydrotreated heavy, benzene < 0,1%
Species:	Crustacean
Duration:	No data available.
Result:	> 100 mg/L

Product/substance	Oleic acid, compound with (Z)-N-octadec-9-enylpropane-1,3diamine (2:1)
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	0,13 mg/l

Product/substance	Oleic acid, compound with (Z)-N-octadec-9-enylpropane-1,3diamine (2:1)
Species:	Algae
Duration:	72 hours
Test:	ERC50
Result:	0,041 mg/l

Product/substance	Oleic acid, compound with (Z)-N-octadec-9-enylpropane-1,3diamine (2:1)
Species:	Crustacean
Duration:	21 days
Test:	EC50
Result:	0,14 mg/l

### 12.2. Persistence and degradability

No data available.

### 12.3. Bioaccumulative potential

No data available.

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

### 12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

### 12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

## SECTION 13: Disposal considerations

### Waste treatment methods

Product is covered by the regulations on hazardous waste. (\*)

HP 3 - Flammable

HP 13 – Sensitising

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

### EWC code




08 01 11\* Waste paint and varnish containing organic solvents or other dangerous substances

### Specific labelling

#### Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

## SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	UN1139	COATING SOLUTION	Transport hazard class: 3 Label: 3 Classification code: F1 	III	No	Limited quantities: 5 L Tunnel restriction code: (D/E) See below for additional information.
IMDG	UN1139	COATING SOLUTION	Transport hazard class: 3 Label: 3 Classification code: F1 	III	No	Limited quantities: 5 L EmS: F-E S-E See below for additional information.
IATA	UN1139	COATING SOLUTION	Transport hazard class: 3 Label: 3 Classification code: F1 	III	No	See below for additional information.

\* Packing group

\*\* Environmental hazards

### Additional information

ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

This product is within scope of the regulations of transport of dangerous goods.

Hazchem Code: ●3Y

### 14.6. Special precautions for user

Not applicable.

### 14.7. Maritime transport in bulk according to IMO instruments

No data available.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Restrictions for application

Restricted to professional users.

People under the age of 18 shall not be exposed to this product.

#### Demands for specific education

No specific requirements.

#### SEVESO - Categories / dangerous substances

P5c - FLAMMABLE LIQUIDS, Qualifying quantity (lower-tier): 5.000 tonnes / (upper-tier): 50.000 tonnes

#### UK-REACH, Annex XVII

Naphtha (petroleum), hydrotreated heavy, benzene < 0,1% is subject to UK-REACH restrictions, UK-REACH annex XVII (entry 40).

#### Additional information

Not applicable.

#### Sources

The Management of Health and Safety at Work Regulations 1999.

Control of Major Accident Hazards (COMAH) Regulations 2015.

2012 No. 1715 ENVIRONMENTAL PROTECTION: The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

#### 15.2. Chemical safety assessment

No

### SECTION 16: Other information

#### Full text of H-phrases as mentioned in section 3

H226, Repeated exposure may cause skin dryness or cracking.

H304, Flammable liquid and vapour.

H304, May be fatal if swallowed and enters airways.

H315, Causes skin irritation.

H317, May cause an allergic skin reaction.

H319, Causes serious eye irritation.

H336, May cause drowsiness or dizziness.

H373, May cause damage to organs through prolonged or repeated exposure.

H400, Very toxic to aquatic life.

H411, Toxic to aquatic life with long lasting effects.

#### The full text of identified uses as mentioned in section 1

LCS "IS" = Industrial uses: Uses of substances as such or in preparations at industrial sites

PC 14 = Metal surface treatment products, including galvanic and electroplating products

#### Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EuPCS = European Product Categorisation System

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

---

OECD = Organisation for Economic Co-operation and Development  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail  
RRN = REACH Registration Number  
SCL = A specific concentration limit  
SVHC = Substances of Very High Concern  
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure  
STOT-SE = Specific Target Organ Toxicity - Single Exposure  
TWA = Time weighted average  
UN = United Nations  
UVBC = Unknown or variable composition, complex reaction products or of biological materials  
VOC = Volatile Organic Compound  
vPvB = Very Persistent and Very Bioaccumulative

#### Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the mixture in regard to physical hazards has been based on experimental data.

#### The safety data sheet is validated by

Nina Nyth

#### Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en