

## Routine verification checklist (routine check protocol)

Manufacturer of the ASSEMBLY:						Company stamp
Customer: Order number:						
Project:		<u>.</u>				
Туре:			L			_
1. Degree of protection of enclos	ures (seals, sealing)	IEC 61439-1,	section	11.2		
Criterion	Requirement	Testing	Asses: [o.k. / r	sment n.o.k. / r	n.c.]	Remark / Examiner
IP-enclosure	IP (from contract)	see contract				
Mechanical impact strength of in- door installations (use by ordinary persons)	IK05	see contract				
Enclosures suited for outdoor installations (UV-resistance, water protection, dew condensation)	According to data provided by original manufacturer	see contract				
Mechanical impact strength of outdoor installations (use by ordinary persons)	IK07	see contract				
Verification of the measures taken to achieve the degree of protection	Cable entries, flanges fastened correctly and closed	Visual inspection				
2. Clearances and creepage dista		IEC 61439-1,				T
Criterion	Requirement	Testing	Asses:	sment n.o.k. / n	i.c.]	Remark / Examiner
Clearance verification (see Table 1)	Rated impulse withstand voltage U <sub>imp</sub> =V  Minimum clearances in air = mm	Visual inspection <sup>1)</sup> <sup>1)</sup> if n.o.k., then Testing for rated peak withstand current U <sub>imp</sub> pursuant to 10.9.3				
Verification of the creepage distances (see Table 2)	Rated insulation voltage  U <sub>i</sub> =V (Attention: U <sub>i</sub> ≥ U <sub>e</sub> ) Minimum creepage distance in =mm (Attention: Minimum creepage distance ≥ Minimum clearance in air)	Visual inspection <sup>2)</sup> if not obviously o.k., then verification by physical measurement				



3. Protection against electric shock and continuity of the protective circuits IEC 61439-1, section 11.4								
Criterion	Requirement	Testing	Assessment [o.k. / n.o.k. / n.c.]		c.]	Remark / Examiner		
Protection against hazardous body currents	Protection by automatic disconnection     Protection by double insulation	Plan = implementation 1+2, 3 = n.c. 1+3, 2 = n.c.						
Verify basic protection	Complete covering of all conductive parts by double insulation	Visual inspection						
	Enclosures and covers have completely and as a minimum IPXXB (>1.6 m above the base, minimum IPXXD)	Visual inspection						
	If PCII and/or use by ordinary persons: Enclosures and covers have completely and as a minimum IP2XC	Visual inspection						
2. Fault protection	Full integration of all components into the protective circuit	Visual inspection						
	Complete marking of the protective conductors PE/PEN	Visual inspection						
	Continuous connection of the protective circuit	Resistance measurement < 0.1Ω						
	Spot checks screw connections	Torque check						
3. Fault protection	No connection of the components to the protective circuit	Visual inspection						
	Graphic symbol attached	Visual inspection						
4. Accomply of a winners	IFO	C1400 4	44 E					
4. Assembly of equipment IEC 61439-1, section 11.5  Criterion Requirement Testing Assessment Remark / Examiner								
Criterion	Requirement	Testing		.o.k. / n.d	c.]	Remark / Examiner		
Equipment marking (readability / assignment)	Texts comply with manu- facturing documentation	Visual inspection						
Use of equipment (auxiliary contacts, fuse links)	Complies with wiring diagram	Visual inspection						
Equipment arrangement	complies with assembly plan	Visual inspection						
Installation position of:			1					
Breaker actuators (direct drive, rotary drive, motor)	Complies with wiring diagram / assembly plan	Visual inspection						
Measurement devices (in door, behind the door)	Complies with assembly plan	Visual inspection						
Control and signalling devices	Complies with assembly plan	Visual inspection						
5. Internal electrical circuits and o	connections IEC 64	1439-1, section	11.6					
Criterion Requirement Testing Assessment Remark / Examiner								
- THE HOLL	ricquii cificiit	resulty		.o.k. / n.d	c.]	TIGHIGIN / LAGHIIIIGI		
Electrical connections / devices and busbar system (spot checks of the cross-sections and torques)	According to data provided by original manufacturer (spot check matrix)	Spot check and visual inspection						



6. Terminals for external conductors IEC 61439-1, section 11.7					
Criterion	Requirement	Testing	Assessment [o.k. / n.o.k. / n.c.]	Remark / Examiner	
Outgoing terminals (cross-section, clamping capacity)	Compliance with manu- facturing documentation	Visual inspection			
Material (copper, aluminium)	Compliance with manu- facturing documentation	Visual inspection			
Type of contacting (plug-in, screw-in)	Compliance with manu- facturing documentation	Visual inspection			
Conductor type (flexible, rigid)	Compliance with manu- facturing documentation	Visual inspection			
7. Mechanical function (actuation	elements, interlocks)	IEC 61439-1	, section 11.8		
Criterion	Requirement	Testing	Assessment	Remark / Examiner	
			[o.k. / n.o.k. / n.c.]		
Ventilation grid, assembled, if necessary	Compliance with manu- facturing documentation	Visual inspection			
Actuation elements (breakers / resetting devices / interlocks / selector switches)	Compliance with manu- facturing documentation	Functional and visual inspection			
Interlocks / locks	Compliance with manu- facturing documentation	Functional and visual inspection			
Door couplings / switch actuators	Compliance with manu- facturing documentation	Functional and visual inspection			
Screw connections / device installation / fastening	According to data provided by original manufacturer	Functional and visual inspection			
Cabling / fastening / type of installation	According to data provided by original manufacturer	Visual inspection			
Door requirements (door hinge I./r.)	Compliance with manu- facturing documentation	Functional and visual inspection			
Closure system (double bit, swivel handle,)	Compliance with manu- facturing documentation	Visual inspection			
Cabinet and/or enclosure type (wall, floor-standing, modular consumer units)	Compliance with manu- facturing documentation	Visual inspection			
Screw connections of the mechanical parts (plinths, supply, surface-mounted wall enclosures) fixed	Torque requirements complied with	Functional and visual inspection			
Compliance with max. height / width / depth	Compliance with manu- facturing documentation	Visual inspection			
Plinth dimensions (e.g. 200 mm)	Compliance with manu- facturing documentation	Visual inspection			
Colour (RAL)	Compliance with manu- facturing documentation	Visual inspection			
Cable inlet flanges	Compliance with manu- facturing documentation	Visual inspection			



8. Dielectric properties IEC 61439	-1, section 11.9					
Criterion	Requirement	Testing	Asse	ssment		Remark / Examiner
			[o.k. /	′ n.o.k. / r	i.c.]	
Insulation check (10.9.1 General / 1 (secure sample by barrier, only the ex		• .	n of no	t less thar	n 1 s.)	
Rated insulation voltage U <sub>i</sub>	Test voltage (AC effective value)					
Phase conductor to enclosure / constructive parts	pursuant to Table 8	Measurement V				
Conductor to conductor	· · · · · · · · · · · · · · · · · · ·	Measurement V				
N to PE		Measurement V				
Auxiliary circuit to main circuits	pursuant to Table 9	Measurement V				
Auxiliary circuit to enclosure / constructive parts		Measurement V				
As alternative to the insulation test	for ASSEMBLIES with an inc	coming protect	ive dev	rice rated	up to	250 A:
Insulation resistance verification (in Testing of the insulation resistance (>				,	te to e	earth)
Testing of the insulation resistance	Compliance with	Visual				arriy
$(>1000 \Omega/V)$ per circuit referred to the supply voltage of the circuits to earth)	manufacturing documentation	inspection				
Phase conductor to enclosure / constructive parts	1k Ω/V * U <sub>e</sub> V =kΩ	Measurement kΩ				
Conductor to conductor		Measurement kΩ				
N to PE		Measurement kΩ				
Auxiliary circuit to main circuits		Measurement kΩ				
Auxiliary circuit to enclosure / constructive parts		Measurement kΩ				
9. Wiring, operational performance	e and function	IEC 61439-1, s	ection	11.10		
Criterion	Requirement	Testing	Assessment [o.k. / n.o.k. / n.c.]			Remark / Examiner
Cable colours and marking main circuits	IEC 60446 AC/DC: black (brown, grey)	Visual inspection				
Cable colours and marking control circuits	IEC 60204 AC: red, DC: blue Exceptions: orange	Visual inspection				
Cable colours and marking PE- and N-conductor	IEC 60446 (green/yellow for PE, blue for N, PEN green/yellow with blue marking at the end)	Visual inspection				
Wiring /cables / cable and fastening type	No installation to sharp-edged corners and edges	Visual inspection				
Wiring and equipment arrangement with regard to interferences / EMC (check for shielded cables, grounding, etc.)	Compliance with manufacturing documentation	Visual inspection				
Complies with wiring diagram	Compliance with manufacturing documentation	Functional test				
Circuitry / control / interlocks (complete circuitry/ complete control / special circuitry requirements)	Compliance with manufacturing documentation	Functional test				
Individual switching devices (where possible, e.g. circuit breaker/RCD)	Compliance with manufacturing documentation	Functional test				
Settings (e.g. motor protection switch, circuit breaker)	Compliance with manufacturing documentation	Setting				



Criterion	Requirement	Testing	Assessment [o.k. / n.o.k. / n.c.]		n.c.]	Remark / Examiner	
Designation label - Name of the manufacturer or trade mark - Type designation or identifier	Completed with all numerals and values	Visual inspection					
- Date of manufacture - Applied standard IEC 61439-2/-3 - Rated voltage (Un) - Rated current (In) - Rated frequency (fn) - Degree of protection - Protection class - CE marking							
Recorded to the documentation:							
Rated operational voltage		Visual inspection					
(U <sub>e</sub> ) of the outgoing circuits		Visual inspection					
Rated impulse withstand voltage (U <sub>imp</sub> )		Visual inspection					
Rated insulation voltage (U <sub>i</sub> )		Visual inspection					
Rated current (I <sub>nc</sub> ) of the outgoing circuits		Visual inspection					
Rated Diversity Factor (RDF)		Visual inspection					
Rated peak withstand current (I <sub>pk</sub> )		Visual inspection					
Rated short-time withstand current $(I_{\rm cw})$		Visual inspection					
Conditional rated short-time withstand current (I <sub>cc</sub> )		Visual inspection					
Included in the documentation							
Wiring diagram		Visual inspection					
Assembly plan		Visual inspection					
Design verification		Visual inspection					
Assembly, operating instructions		Visual inspection					
CE - Declaration of conformity		Visual inspection					
Final testing							
Cleanliness of the installation	No shavings, cable residues, pollution	Visual inspection					
Documentation attached		Visual inspection					
Enclosure surface	Free from scratches, pollution, pockets	Visual inspection					
Installation suited for transport	Fixed to transport means, no loose parts, labels	Visual inspection					
Routine verification performed:							
Place / Date		Name and	l signatu	re of the p	erforme	er	
Place / Date		Name and	l signatu	re of the te	ester		