


FurseWELD

Cable to cable CC6

Cable to cable CC6 - FurseWELD



Stranded/solid circular conductor size A (mm ²)	Stranded/solid circular conductor size B (mm ²)	Mould part no.	Order code	Powder cartridge part no.	Handle clamp part no.
16 *	16 *	CC6-4-1616	7TCA083910R1533	65P10	HCPK4
25	25	CC6-4-2525	7TCA083910R1537	45P10	HCPK4
35	35	CC6-4-3535	7TCA083910R1538	65P10	HCPK4
35	25	CC6-4-3525	7TCA083910R2959	65P10	HCPK4
50	50	CC6-4-5050	7TCA083910R1541	90P10	HCPK4
50	35	CC6-4-5035	7TCA083910R1540	65P10	HCPK4
50	25	CC6-4-5025	7TCA083910R1539	65P10	HCPK4
70	70	CC6-4-7070	7TCA083910R1545	115P10	HCPK4
70	50	CC6-4-7050	7TCA083910R1544	115P10	HCPK4
70	35	CC6-4-7035	7TCA083910R1543	90P10	HCPK4
70	25	CC6-4-7025	7TCA083910R1542	90P10	HCPK4
95	95	CC6-4-9595	7TCA083910R1553	150P10	HCPK4
95	70	CC6-4-9570	7TCA083910R1552	115P10	HCPK4
95	50	CC6-4-9550	7TCA083910R1551	115P10	HCPK4
95	35	CC6-4-9535	7TCA083910R1550	115P10	HCPK4
120	120	CC6-4-120120	7TCA083910R1525	200P10	HCPK4
120	95	CC6-4-12095	7TCA083910R1530	200P10	HCPK4
120	70	CC6-4-12070	7TCA083910R1529	150P10	HCPK4
120	50	CC6-4-12050	7TCA083910R1528	115P10	HCPK4

Special moulds for all FurseWELD products can be manufactured to meet specific customer applications on request

*3 x S103 Sleeve required when joining conductors 16 mm² or smaller

For order codes of powder cartridges and handle clamps, see pages 49-50

FurseWELD moulds should only be used with FurseWELD powders, handle clamps and accessories. If moulds, powders, handle clamps and accessories from other manufacturers are utilized, we cannot guarantee the safe use or the integrity of the completed joint

FurseWELD moulds for use with stranded conductor are designed for use with non-compacted conductor to BS EN 60228. If a mould for compacted conductor is required, please contact your local representative

Conductors must be installed in the orientation shown to achieve the correct connection