


FurseWELD

Cable to steel surface & pipe CS1 & CS2

Cable to steel surface & pipe CS1 - FurseWELD

	Stranded/solid circular conductor size A (mm ²)	Mould part no.	Order code	Powder cartridge part no.	Handle clamp part no.
	16				Use CS8
	25				Use CS8
	35				Use CS8
	50	CS1-4-50-FU	7TCA083910R2004	90P10	HCPK4
	70	CS1-4-70	7TCA083910R2005	90P10	HCPK4
	95	CS1-4-95	7TCA083910R2006	115P10	HCPK4
	120	CS1-4-120	7TCA014980R0164	115P10	HCPK4
	150	CS1-4-150	7TCA083910R2000	150P10	HCPK4
	185	CS1-4-185	7TCA083910R2001	200P10	HCPK4
	240	CS1-4-240	7TCA083910R2002	200P10	HCPK4
	300	CS1-4-300	7TCA083910R2003	250P10	HCPK4

Special moulds for all FurseWELD products can be manufactured to meet specific customer applications on request


For order codes of powder cartridges and handle clamps, see pages 49-50

FurseWELD moulds should only be used with FurseWELD powders, handle clamps and accessories. If moulds, powders, handle clamps and accessories from other manufacturers are utilized, we cannot guarantee the safe use or the integrity of the completed joint

FurseWELD moulds for use with stranded conductor are designed for use with non-compacted conductor to BS EN 60228. If a mould for compacted conductor is required, please contact your local representative

Conductors must be installed in the orientation shown to achieve the correct connection

Cable to steel surface & pipe CS2 - FurseWELD

	Stranded/solid circular conductor size A (mm ²)	Mould part no.	Order code	Powder cartridge part no.	Handle clamp part no.
	16				Use CS9
	25				Use CS9
	35				Use CS9
	50	CS2-4-50	7TCA083910R2011	90P10	HCPK4
	70	CS2-4-70	7TCA083910R2012	115P10	HCPK4
	95	CS2-4-95	7TCA083910R2013	115P10	HCPK4
	120	CS2-4-120	7TCA083910R2009	150P10	HCPK4
	150	CS2-4-150	7TCA083910R2010	200P10	HCPK4
	185	CS2-4-185	7TCA083910R3006	250P10	HCPK4
	240	CS2-5-240	7TCA083910R2561	2 x 150P10	HCPK5
	300	CS2-5-300	7TCA083910R3030	2 x 200P10	HCPK5

Special moulds for all FurseWELD products can be manufactured to meet specific customer applications on request

For order codes of powder cartridges and handle clamps, see pages 49-50

FurseWELD moulds should only be used with FurseWELD powders, handle clamps and accessories. If moulds, powders, handle clamps and accessories from other manufacturers are utilized, we cannot guarantee the safe use or the integrity of the completed joint

FurseWELD moulds for use with stranded conductor are designed for use with non-compacted conductor to BS EN 60228. If a mould for compacted conductor is required, please contact your local representative

Conductors must be installed in the orientation shown to achieve the correct connection