

TECHNICAL CATALOGUE

System pro E power

Main distribution switchboards
up to 6300A



Summary

Main distribution switchboards
up to 6300A

STRUCTURE

INTERNAL KITS

MAIN DISTRIBUTION
SYSTEMS

SEGREGATIONS

DEDICATED SOLUTION

TECHNICAL DETAILS
AND CERTIFICATIONS

OVERALL DIMENSIONS


LIST OF CODES

The ABB SACE website:

makes your work easier, develops your business

- News, to keep you up to date about the latest electrical engineering innovations
- Products, just a simple click for an overview of ABB SACE products 24 hours a day
- Catalogues that you can consult, download and request
- Technical documentation where you can check circuit diagrams, dimensional drawings, instruction sheets, installation manuals
- Work tools for designing in complete safety
- Training, where you can consult the training catalogue and register for courses online

[www.new.abb.com/
low-voltage](http://www.new.abb.com/low-voltage)
The ABB SACE website will help you in your daily work with an innovative approach to the world of low voltage electrical installations and industrial automation.



Technical software Calculation and cost estimate tools

e-Design: everyone has a project, ABB has a solution to make it happen.

e-Design is the integrated suite, designed and created by ABB, dedicated to designers, technicians, engineering companies, panel builders and wholesalers. Thanks to e-Design you can design an electrical installation and optimize the processing time, while benefiting from a product portfolio you can use in synergy and with intuitive and simple functions.

We would like to highlight several positive features:

- **Reliable in extreme conditions**
Thanks to the tests performed on the product, the enclosures can stand a rated short-time withstand current (Icw) up to 150 kA and a Maximum rated current up to 6300A. The solution is also provided of an ant seismic certification, thanks to a shock level test up to 0.75 g performed with the installation of specific accessories. The safety is also guaranteed by the complete range of segregation forms up to 4b and by the blind tops arc fault resistant (composed by two flaps that, in case of internal arc fault, allow its outburst upward, protecting an operator that could be present in front of the switchboard).
- **Speed up your projects**
It is possible to save valuable time (up to 5% of the total time) by choosing the incoming column with DOC software, where a list of pre-configured incomer columns is already uploaded. Additional time can be saved thanks to the breaker kit package that with one single code provides all the components for a breaker kit installation (panel, plate, supports and screws); the pre-assembled DIN rail kit allows to save up to 70% on the time in case of System pro M components installation.
- **Space saving**
A wide variety of dimensions are available to meet all customer requests: 2 heights, 5 depths and 6 widths. Furthermore, amperage from 2500A to 6300A can be reached in the minimum widths listed below:
Up to 2500A (3P) installable in W=400mm
Up to 4000A (3P) installable in W=600mm
Up to 4000A (4P) installable in W=800mm
Up to 6300A (4P) installable in W=1000/1250mm
For example, further space (up to 38%) can be saved by mounting two air circuit breakers in one column In 2500A, width 400mm (E2.2 F/W 3P), thanks to the dedicated components.



- Simple and immediate selection and configuration of products, even for those who are not familiar
- with ABB products, simply by defining technical features
- The automatic user-friendly design process based on the list of devices simplifies one of the most
- complex design stages and avoids compatibility errors between products, assembly kits and busbar systems
- Effective product organization with tree views, so that the user can work methodically, view the relevant product immediately and define the switchboards with ease
- Availability of a dedicated module for busbar configuration

Well aware of market requirements, ABB now capitalizes on its experience and presents the new e-Design suite as a practical answer to every critical aspect of the design process.

The registration procedure is very easy and, once completed, you can immediately download installers and upgrades.

DOC Electrical installation Dimensioning

EDS Switchboard Configuration

PDC Switchboard Engineering

CAT Product Selection and Configuration

The suite's appealing and brandnew look, combined with general optimization of the functions that have always characterized ABBsoftware, make it an innovative tool, up to date with the technologies currently available in the sector. After only a brief introduction, the user can already design, calculate, archive and perform project planning. No special CAD skills are required. Software operation is based on dialog boxes. The user is led through the program.

e-Design suite is structured with integrated functional modules, allowing it to support all planning stages of an electrical installation.

All solutions are studied in detail, from electrical network dimensioning, to switchboard configuration, through to the final cost estimate stage.

System pro E power

Even more easy and fast

In order to make more easy the use of System pro E power available information, new labels have been created as a useful tool to stock and mount the enclosures.

In the new product labels 5 fields have been added:

- ① Through the QR code it is possible having a fast access to the ABB System pro E power web site with all support material regarding the product:**
 - Multimedia
 - Promotional videos, Velocity, Flexibility,
 - Semplicity is Power
 - 3D drawings
 - Structure
 - Kits for internal installation
 - Main documents
 - Technical catalogue
 - Instruction handbook
 - Video manuals
 - Mounting sequence animations
 - Preconfigured enclosures
- ② Mounting video specific for a component**
- ③ Mounting sequence**
- ④ ABB web site**
- ⑤ Country of origin**



A yellow label, put on the package of the depth crosspieces, presents 5 QR codes that links to ABB Youtube channel, were the corresponding mounting videos are stored. Furthermore, a recap sheet has been added on the same package in order to facilitate the usage of the new labels.



System pro E power

User's guide




Chapter 1

Range presentation
Overview, introduction and advantages of the new main distribution switchboard range up to 6300A.




Chapter 2

Structure
Distinctive features of the new switchboards with selection guides for rapid choice of the structure. Ordering codes for the framework and external covers.



Chapter 3

Internal kits
Assembly kits for the circuit-breakers and the accessories available for the new switchboard solution.




Chapter 4

Main distribution systems
Description of the different busbar system combinations that can be created. Selection guides and capacity tables.




Chapter 5

Segregations
Segregation kits up to Form 4b available for busbar and breakers with front/rear terminal.



Chapter 6

Dedicated solution
Assembly kits for CombiLine and InLine.



Chapter 7

Technical details, certifications and configuration examples
Specifications of the new switchboard, regulatory framework, Italian and international certifications.



Chapter 8

Overall dimensions
Overall dimensions of the switchboards and the relative components available.



Chapter 9

List of codes
Analytical list of codes.

Chapter 1

Range presentation

1–2 Introduction

1–4 Advantages

1–4 Reliable in extreme conditions

1–5 Speed up your projects

1–5 Space saving

1–6 Composition of the series

Range presentation

System pro E power, ABB's pioneering new solution for main distribution switchboards with rated current up to 6300A and short-circuit current up to 150kA, meets all plant requirements depending on the type of installation, required degree of protection and electrical and mechanical specifications.





Range presentation

Introduction

Thanks to the new switchboard, ABB can provide complete solutions for main electric power distribution in infrastructures and industries, in accordance with the regulatory framework.

Typical fields of application are airports, subways, hospitals, industrial and residential estates, ports, tunnels, railways, theatres, etc. In addition, System pro E power guarantees full synergy with all the other ABB apparatus (i.e. modular circuit-breakers, Tmax T and XT moulded-case circuit-breakers, Emax 2 air circuit-breakers) while being extremely simple to assemble and ensuring ease of wiring.

Great attention has been made to the wiring requirements, with adequately sized structures and pre-engineered sites for mounting the horizontal and vertical plastic ducts.

The switchboards comprise the following components:

- Structure: simple and quick to assemble. Stability is ensured thanks to the new double-surface profile of the upright and the new patented joining system.
- Internal kits: designed to integrate ABB's low voltage products. Save time during the assembly work thanks to the patented new click-in mounting system.

- Main distribution systems: available in the linear and scaled versions. Allow the busbars to be installed in any position, horizontally or vertically

The range of System pro E power structures can be used to create lots of switchboard configurations while guaranteeing flexibility and a certified product. Up to 120 different configurations can be assembled with just a few part numbers. This new series features a structure in hot-dip galvanized sheet steel that guarantees equipotential bonding of the switchboard.

IP protection degrees for all types of applications, i.e. up to IP65, can be obtained. It's the only switchboard to reach such a high value. Certification was achieved after stringent tests involving the entire configuration (structure, circuit-breakers and busbar system), thus systems conforming to the new international standard IEC 61439-1-2 can be created by following ABB's instructions. ABB apparatus can be installed inside the switchboards with high-level integration and optimized use of the available space thanks to the new modules, i.e. 150mm in height, as well as the usual 200mm modules. The circuit-breakers can be internally separated from Form 1 to Form 4b.

Main characteristics of the series

Compliance with Standard	IEC 61439-1-2	
Vibration test	In accordance with Standard IEC 60068-2-57	
Seismic withstand capability test	In accordance with Standard IEE Std 693	
Rated service voltage Ue	up to 1000V AC - 1500V DC	
Rated insulation voltage Ui	up to 1000V AC - 1500V DC	
Rated frequency	50-60Hz	
Rated impulse withstand voltage Uimp	12kV	
Rated current In	up to 6300A	
Rated short-time withstand current Icw	up to 150kA	
Rated peak short-circuit current Ipk	up to 330kA	
IP protection class	IP30, IP31, IP40, IP41, IP65	
Functional dimensions	Height (mm)	1800, 2000mm
	Width (mm)	300, 400, 600, 800, 1000, 1250mm
	Depth (mm)	200, 300, 500, 700, 900mm



Reliable in extreme conditions


Thanks to the tests performed on the product, the enclosures can stand a rated short-time withstand current (I_{cw}) up to 150 kA and a Maximum rated current up to 6300A. The solution is also provided of an ant seismic certification, thanks to a shock level test up to 0.75 g performed with the installation of specific accessories. The safety is also guaranteed by the complete range of segregation forms up to 4b and by the blind tops arc fault resistant (composed by two flaps that, in case of internal arc fault, allow its outburst upward, protecting an operator that could be present in front of the switchboard).



Speed up your projects

It is possible to save valuable time (up to 5% of the total time) by choosing the incoming column with DOC software, where a list of preconfigured

incomer columns is already uploaded. Additional time can be saved thanks to the breaker kit package that with one single code provides all the components for a breaker kit installation (panel, plate, supports and screws); the pre-assembled DIN rail kit allows to save up to 70% on the time in case of System pro M components installation.



Space saving

A wide variety of dimensions are available to meet all customer requests: 2 heights, 5 depths and 6 widths. Furthermore, amperage from 2500A to 6300A can be reached in the minimum widths listed below:

Up to 2500A (3P) installable in W=400mm

Up to 4000A (3P) installable in W=600mm

Up to 4000A (4P) installable in W=800mm


Up to 6300A (4P) installable in W=1000/1250mm

For example, further space (up to 38%) can be saved by mounting two air circuit breakers in one column In 2500A, width 400mm (E2.2 F/W 3P), thanks to the dedicated components.




Range presentation

Composition of the series



STRUCTURE		EXTERNAL COVERS											
Functional dimensions		Top/Bottom			Rear panel		Side panels		Door				
		Blind	Open ⁽¹⁾	Internal bottom	Blind	Vented	Blind	Vented	Glass	Blind	IP40/41	IP65	
H (mm)	W (mm)	D (mm)	IP30 to 65	IP65	IP40	IP30 to 65	IP30 to 41	IP30 to 65	IP30 to 41	IP40/41	IP65	IP40/41	IP65
300	500	200	✓		✓	✓	✓	✓				✓	✓
		300	✓	✓	✓	✓	✓	✓	✓			✓	✓
		500	✓	✓	✓	✓	✓	✓	✓			✓	✓
		700	✓	✓	✓	✓	✓	✓	✓			✓	✓
400	500	900	✓	✓	✓	✓	✓	✓	✓			✓	✓
		200	✓	✓	✓	✓	✓	✓	✓			✓	✓
		300	✓	✓	✓	✓	✓	✓	✓			✓	✓
		500	✓	✓	✓	✓	✓	✓	✓			✓	✓
600	500	700	✓	✓	✓	✓	✓	✓	✓			✓	✓
		900	✓	✓	✓	✓	✓	✓	✓			✓	✓
		200	✓	✓	✓	✓	✓	✓	✓			✓	✓
		300	✓	✓	✓	✓	✓	✓	✓			✓	✓
1800 2000	500	500	✓	✓	✓	✓	✓	✓	✓			✓	✓
		700	✓	✓	✓	✓	✓	✓	✓			✓	✓
		900	✓	✓	✓	✓	✓	✓	✓			✓	✓
		200	✓	✓	✓	✓	✓	✓	✓			✓	✓
800	500	300	✓	✓	✓	✓	✓	✓	✓			✓	✓
		500	✓	✓	✓	✓	✓	✓	✓			✓	✓
		700	✓	✓	✓	✓	✓	✓	✓			✓	✓
		900	✓	✓	✓	✓	✓	✓	✓			✓	✓
1000	500	200	✓	✓	✓	✓	✓	✓	✓			✓	✓
		300	✓	✓	✓	✓	✓	✓	✓			✓	✓
		500	✓	✓	✓	✓	✓	✓	✓			✓	✓
		700	✓	✓	✓	✓	✓	✓	✓			✓	✓
1250	500	900	✓	✓	✓	✓	✓	✓	✓			✓	✓
		200	✓	✓	✓	✓	✓	✓	✓			✓	✓
		900	✓	✓	✓	✓	✓	✓	✓			✓	✓

⁽¹⁾ Use the dedicated incoming cable flanges to obtain protection class IP65.



KITS FOR APPARATUS

MAIN DISTRIBUTION SYSTEM

Chapter 2

Structure

2-2 General information

Choice of the structure

2-8 H=1800mm quick selection guide

2-10 H=2000mm quick selection guide

2-14 Guide to the order codes

Order codes

2-13 Frame

2-19 External covers

2-36 Finishing components

2-44 Accessories and spare parts

Structure

General information

The range of System pro E power structures can be used to create lots of switchboard configurations while guaranteeing scalability, flexibility and a certified product.

Structure

The structure can be assembled in different ways. Moreover, assembly is error-free since the uprights and crosspieces are symmetrical.

The structure comprises:

- Uprights and crosspieces
- Plinth and flanges
- Top/Bottom
- Door and panels

To ensure the utmost freedom of choice, flexibility and to save on storage space, the components that form the structure are supplied loose, each one identified by an order code.

Functional dimensions available

Type of installation	Dimensions
Height (functional)	1800, 2000mm
Width (functional)	300, 400, 600, 800, 1000, 1250mm
Depth (functional)	200, 300, 500, 700, 900mm

Uprights and crosspieces

The uprights and crosspieces (width and depth) have the same laser-beam welded 13-fold profile

and are assembled by means of a patented new joining system with 3 axial screws that makes the switchboard incredibly sturdy.

The uprights are available in galvanized sheet metal or AISI 304 stainless steel for In >4000A rated current values, able to limit stray currents.

Thanks to its shape, the new profile provides 2 surface levels on the same side to allow different kits to be mounted.

The holes made inside are an important innovation, i.e. the 25mm pitch alternation between a round hole and a square one. Selfthreading screws can be inserted into the round holes while the square hole has been created for fastening kits.

The holes made on the outside are different, since there are two round holes with different diameters able to take self-threading screws and round cage nuts. The two different types of holes alternate with a 25mm pitch as required by the DIN Standards.



Structures with blind door

W (mm)	300	400	600	800	1000	1250*
DIN modules	12	24	36	48	-	

* Double door version with overlapping closing.



Structures with glass door

W (mm)	400	600	800	1000	1250*
DIN modules	12	24	36	48	-

* Double door version with overlapping closing.



Structures with glass door and internal cable compartment

W (mm)	400	600	800
DIN modules	12	24	36



New laser-beam welded upright with 13 folds. Extremely sturdy without being too heavy.

Plinth and flanges

The innovative plinth angle piece featuring a patented "folding" system guarantees high-level mechanical strength and can be fastened from the inside and outside of the structure. The switchboard can also be ordered without plinth and, if required by the project specifications or requested by the end customer, the plinth angle piece can be fixed to the structure in a successive stage.

The plinth has an anti-rotation device for easier transport on transpallets. The reinforced version is available on request and allows the switchboard to be moved on rollers.

Top/Bottom

New types of top/bottom have been used so as to allow cables to enter from above or below, also thanks to the special flanges that guarantee the desired IP class.

Door and Panels

The doors are available in the glass or blind versions and open through 135° on single units. Door opening through 180° can be obtained on request.

For maximum flexibility and ease of use, the hinges are no longer fixed to the uprights but are supplied in the door Pkg.

The handle is not fixed and allows the user to choose whether the door must open towards the right or left.

The handle can house various types of closing inserts (double tab, key-operated, etc.).

The panels are fixed with TORX screws and come in the RAL7035 orange peel.

Structure

General information

—
01 New 3-way connection in aluminium. Allows the plinth to be assembled and the structure to be lifted. Double-profile uprights for mounting accessories and kits at different depths.

—
02 New plinth with highlevel mechanical strength. Equipped with anti-rotation system. Thanks to its innovative shape, it can be fixed from the inside and outside of the structure.

Frame

Uprights and crosspieces

- New profile with 2 surface levels on the same side to allow different kits to be mounted.
- Uprights and crosspieces in galvanized sheet metal or AISI 304 stainless steel for In >4000A rated current values, able to limit stray currents.
- Easy to assemble: new joining system with 3 axial screws.
- Extremely sturdy: 13 laser-beam welded folds.
- Small Pkgs.
- Internal kits mounted with a rapid system using 1/4-turn screws.

Plinth

- High-level mechanical strength.
- Can be fixed from the outside and from the inside of the structure.
- Can be fixed to the structure in a successive phase.
- Plinth angle piece with anti-rotation system.
- Bottom can be transported on a transpallet.



—
03 The handle can house different types of closing inserts and comes with hinges no longer fixed to the uprights, but supplied with the door and panel accessories.

—
04 The stylish handles are customized with the ABB logo.

External covers

The new design partly reflects ABB's distinctive, classic style while System pro E power adds to the elegant appearance without forgoing functionality or sturdiness.

The family feeling proposed by the versions and accessories in ABB's range is underscored throughout, thereby guaranteeing the utmost flexibility as to assembly.

Thanks to the handle, which can house different types of closing inserts and is supplied with the door hinges (no longer fixed to the upright), a vast range of assembly solutions can be obtained to suit the customers' requirements.

It is impossible to commit errors when assembling the structure. Ease of assembly is guaranteed since

the hinges are no longer already fixed to the uprights but are supplied with the door and panel accessories.

Tops and bottoms are not pre-assembled but supplied separately to allow different incoming-outgoing combinations to be obtained.

The new main distribution switchboards are available in versions with glass or blind doors.

Doors and panels

- Family feeling that reflects in all the versions/applications/installations (glass door, blind door).
- The handle allows different inserts to be used.
- The handle and hinges are supplied disassembled. This allows the customer to choose whether the door must open towards the right or left.



Blind top/bottom, open bottom and for applications without plinth for up to IP65 degree of protection in pickled steel sheet painted in RAL 7035 orange peel.
Pag. 2/16

Glass door or blind door in pickled steel sheet painted in RAL 7035 orange peel, up to IP65 degree of protection.
Pag. 2/24

External rear panel in pickled steel sheet painted in RAL 7035 orange peel, up to IP65 degree of protection.
Pag. 2/20

External side panel in pickled steel sheet painted in RAL 7035 orange peel, up to IP65 degree of protection.
Pag. 2/22

Incoming cable flanges in pickled steel sheet.
Pag. 2/32




Structure


Choice of the structure

Realization of the different IP protection class example


IP30




IP40




IP30



IP40



IP65



—
01 Structure with rear cable compartment: to be realized by means of 2 crosspieces for structure PCCM.... and 2 uprights for internal cable compartment PUCM.... o PUCS....


—
02 Back to back structure

—
03 Structure with double internal cable compartment: to be realized by means of crosspieces for internal cable compartment PCCS.... and uprights for internal cable compartment PUCM.... o PUCS....


—
04 Struttura con vano cavi interno destro o sinistro: utilizzare traverse per vano cavi interno PCCS.... in combinazione con montanti per vano cavi interno PUCM.... o PUCS.... I kit vanno scelti in funzione della larghezza C.

Examples of use


—
01




—
02



—
03




—
04



Structure

Choice of the structure



H=1800mm quick selection guide

Functional dimensions Height 1800mm	External * dimensions Height 2013mm	FRAME						EXTERNAL COVERS									
		Uprights	Structure crosspieces	H=100mm plinth		Top/bottom panels		Front/side panels									
W (mm)	D (mm)	W (mm)	D (mm)	Galvanized sheet metal In>4000A	Stainless steel and galvanized sheet metal In>4000A*	Sides	Galvanized sheet metal	Galvanized sheet metal	Plinth flanges	Blind	Open ⁽²⁾	Bottom	Without plinth	Blind	Vented		
300	200	416	316	PUPM1802	PCFM0300	PPAM0100	PPFM1030	PPFM1020	PTBB3026	PTBB3020	PTBQ3020	IP40	PBWP3020	IP65	PPEB1836		
	300	416					PPCFM0200	PPCFM0300	PPFM1030	PTBB3036	PTBB3030	PTBQ3030		PBWP3030			
	500	616					PPCFM0500	PPFM1050	PPFM1050	PTBB3056	PTBB3050	PTBQ3050		PBWP3050			
	700	816					PPCFM0700	PPFM1070	PPFM1070	PTBB3076	PTBB3070	PTBQ3070		PBWP3070			
	900	1016					PPCFM0900	PPFM1090	PPFM1090	PTBB3096	PTBB3090	PTBQ3090		PBWP3090			
	1250	1366					PPCFM1250	PPFM1250	PPFM1250		1STQ005579B0000	1STQ005573B0000	1STQ005590B0000		PPEA1830		
400	200	516	316	PUPM1802	PCFM0400	PPAM0100	PPFM1040	PPFM1020	PTBB4026	PTBB4020	PTBQ4020	IP65	PBWP4020	IP65	PPEB1846		
	300	416					PPCFM0200	PPCFM0300	PPFM1030	PTBB4036	PTBB4030	PTBQ4030		PBWP4030			
	500	616					PPCFM0500	PPFM1050	PPFM1050	PTBB4056	PTBB4050	PTBQ4050		PBWP4050			
	700	816					PPCFM0700	PPFM1070	PPFM1070	PTBB4076	PTBB4070	PTBQ4070		PBWP4070			
	900	1016					PPCFM0900	PPFM1090	PPFM1090	PTBB4096	PTBB4090	PTBQ4090		PBWP4090			
	1250	1366					PPCFM1250	PPFM1250	PPFM1250		1STQ005580B0000	1STQ005574B0000	1STQ005591B0000		PPEA1840		
600	200	716	316	PUPM1802	PCFM0600	PPAM0100	PPFM1060	PPFM1020	PTBB6026	PTBB6020	PTBQ6020	IP65	PBWP6020	IP65	PPEB1866		
	300	416					PPCFM0200	PPCFM0300	PPFM1030	PTBB6036	PTBB6030	PTBQ6030		PBWP6030			
	500	616					PPCFM0500	PPFM1050	PPFM1050	PTBB6056	PTBB6050	PTBQ6050		PBWP6050			
	700	816					PPCFM0700	PPFM1070	PPFM1070	PTBB6076	PTBB6070	PTBQ6070		PBWP6070			
	900	1016					PPCFM0900	PPFM1090	PPFM1090	PTBB6096	PTBB6090	PTBQ6090		PBWP6090			
	1250	1366					PPCFM1250	PPFM1250	PPFM1250		1STQ005581B0000	1STQ005575B0000	1STQ005592B0000		PPEA1860		
800	200	916	316	PUPM1802	PCFM0800	PPAM0100	PPFM1080	PPFM1020	PTBB8026	PTBB8020	PTBQ8020	IP65	PBWP8020	IP65	PPEB1886		
	300	416					PPCFM0200	PPCFM0300	PPFM1030	PTBB8036	PTBB8030	PTBQ8030		PBWP8030			
	500	616					PPCFM0500	PPFM1050	PPFM1050	PTBB8056	PTBB8050	PTBQ8050		PBWP8050			
	700	816					PPCFM0700	PPFM1070	PPFM1070	PTBB8076	PTBB8070	PTBQ8070		PBWP8070			
	900	1016					PPCFM0900	PPFM1090	PPFM1090	PTBB8096	PTBB8090	PTBQ8090		PBWP8090			
	1250	1366					PPCFM1250	PPFM1250	PPFM1250		1STQ005582B0000	1STQ005576B0000	1STQ005593B0000		PPEA1880		
1000	200	1116	316	PUPM1802	PCFM1000	PPAM0100	PPFM1010	PPFM1020	PTBB1026	PTBB1020					PPEB1810		
	300	416					PPCFM0200	PPCFM0300	PPFM1030	PTBB1036	PTBB1030	PTBQ1030		PBWP1030			
	500	616					PPCFM0500	PPFM1050	PPFM1050	PTBB1056	PTBB1050	PTBQ1050		PBWP1050			
	700	816					PPCFM0700	PPFM1070	PPFM1070	PTBB1076	PTBB1070	PTBQ1070		PBWP1070			
	900	1016					PPCFM0900	PPFM1090	PPFM1090	PTBB1096	PTBB1090	PTBQ1090		PBWP1090			
	1250	1366					PPCFM1250	PPFM1250	PPFM1250		1STQ005583B0000	1STQ005577B0000	1STQ005594B0000		PPEA1810		
1250	200	1366	316		PCFM0200		PPFM1020			PTBB1220							
	900	1016			PCFM0900		PPFM1090			PTBB1290	PTBQ1290			PPEB1880	PPEB1860		
	1250	1366			PCFM1250	PPAM0100 + PPM0100	PPFM1250			PPFM1250	1STQ005584B0000	1STQ005578B0000	1STQ005595B0000		PPRA180 ⁽³⁾	PPRA180 ⁽³⁾	

* The external dimensions include the H=100mm plinth and the panels.

** This code has to be used for application with In >4000A. It includes No. 2 stainless steel uprights and No. 2 galvanized sheet metal uprights see pag. 2/15.

Consult page 2/12 and 7/2 for selection of the protection class.

(1) In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit, page 2/24.

(2) Use the dedicated incoming cable flanges to obtain protection class IP65.

Cables flanges page 2/28.

(3) Right rear panel for structures W=1250mm.

(4) Left rear panel for structures W=1250mm.

(5) Door with overlapping for the double door version.

(6) Door with handle for the double door version.



(7) Finishing profile vertical internal cable compartment.

(8) PCCM... to be ordered when there is an intermediate upright for mounting kit (PUCM....) or an intermediate crosspiece for installing busbars horizontally under the top or on the bottom of the (PCKL....) structure or when vertical side partitions are installed. Not compatible with IP40 PBWP....
PUCM... The front upright is always required.


The rear upright is used for fixing the crosspieces that support the busbars and for

fixing the vertical side partitions of the structure. For $In > 4000A$ the rear upright for ICC is PUCS....

(9) The intermediate uprights (PUK1....) are not required for assembling fixed Tmax XT1, XT2, XT3, XT4, T4, T5, T6 and XT1, XT3 with Direct Rotary Handle only in not segregated structures. Order 2 uprights for the kits. To be ordered (2 pieces) for segregation structure except for 2b with kits that don't require PUK1.... To be ordered in case of vertical/horizontal busbar system pag.3/21.

Structure

Choice of the structure



H=2000mm quick selection guide

Functional dimensions				External * dimensions		FRAME				EXTERNAL COVERS							
Height 1800mm		Height 2013mm		Uprights		Structure crosspieces	H=100mm plinth		Top/bottom panels						Front/side panels		
W (mm)	D (mm)	W (mm)	D (mm)	Galvanized sheet metal In≤4000A	Stainless steel and Galvanized sheet metal In>4000A**	Front/Rear Sides	Galvanized sheet metal	Plinth flanges	Blind	Open ⁽²⁾	Without plinth	Bottom	Rear panel	Blind	Vented		
300	200	416	316	PCFM0200	PUPM2002	PPAM0100	PPFM1030	PTBB3026	PTBB3020	PTBO3020	PBWP3020	IP65	IP40	IP65	PPEB2036		
	300	416		PCFM0300			PPFM1030	PTBB3036	PTBB3030	PTBO3030	PBWP3030				PPEB2030		
	500	616		PCFM0500			PPFM1050	PTBB3056	PTBB3050	PTBO3050	PBWP3050				PPEB2050		
	700	816		PCFM0700			PPFM1070	PTBB3076	PTBB3070	PTBO3070	PBWP3070				PPEB2070		
	900	1016		PCFM0900			PPFM1090	PTBB3096	PTBB3090	PTBO3090	PBWP3090				PPEB2090		
	1250	1366		PCFM1250			PPFM1250		1STQ005579B0000	1STQ005573B0000	1STQ005590B0000						
400	200	516	316	PCFM0200	PUPM2002	PPAM0100	PPFM1040	PTBB4026	PTBB4020	PTBO4020	PBWP4020	IP65	IP40	IP65	PPEB2046		
	300	416		PCFM0300			PPFM1030	PTBB4036	PTBB4030	PTBO4030	PBWP4030				PPEB2030		
	500	616		PCFM0500			PPFM1050	PTBB4056	PTBB4050	PTBO4050	PBWP4050				PPEB2050		
	700	816		PCFM0700			PPFM1070	PTBB4076	PTBB4070	PTBO4070	PBWP4070				PPEB2070		
	900	1016		PCFM0900			PPFM1090	PTBB4096	PTBB4090	PTBO4090	PBWP4090				PPEB2090		
	1250	1366		PCFM1250			PPFM1250		1STQ005580B0000	1STQ005574B0000	1STQ005591B0000						
600	200	716	316	PCFM0200	PUPM2002	PPAM0100	PPFM1060	PTBB6026	PTBB6020	PTBO6020	PBWP6020	IP65	IP40	IP65	PPEB2066		
	300	416		PCFM0300			PPFM1030	PTBB6036	PTBB6030	PTBO6030	PBWP6030				PPEB2030		
	500	616		PCFM0500			PPFM1050	PTBB6056	PTBB6050	PTBO6050	PBWP6050				PPEB2050		
	700	816		PCFM0700			PPFM1070	PTBB6076	PTBB6070	PTBO6070	PBWP6070				PPEB2070		
	900	1016		PCFM0900			PPFM1090	PTBB6096	PTBB6090	PTBO6090	PBWP6090				PPEB2090		
	1250	1366		PCFM1250			PPFM1250		1STQ005581B0000	1STQ005575B0000	1STQ005592B0000						
800	200	916	316	PCFM0200	PUPM2002	PPAM0100	PPFM1080	PTBB8026	PTBB8020	PTBO8020	PBWP8020	IP65	IP40	IP65	PPEB2086		
	300	416		PCFM0300			PPFM1030	PTBB8036	PTBB8030	PTBO8030	PBWP8030				PPEB2030		
	500	616		PCFM0500			PPFM1050	PTBB8056	PTBB8050	PTBO8050	PBWP8050				PPEB2050		
	700	816		PCFM0700			PPFM1070	PTBB8076	PTBB8070	PTBO8070	PBWP8070				PPEB2070		
	900	1016		PCFM0900			PPFM1090	PTBB8096	PTBB8090	PTBO8090	PBWP8090				PPEB2090		
	1250	1366		PCFM1250			PPFM1250		1STQ005582B0000	1STQ005576B0000	1STQ005593B0000						
1000	200	1116	316	PCFM0200	PUPM2002	PPAM0100	PPFM1010	PTBB1026	PTBB1020	PTBO1020	PBWP1020	IP65	IP40	IP65	PPEB2016		
	300	416		PCFM0300			PPFM1030	PTBB1036	PTBB1030	PTBO1030	PBWP1030				PPEB2010		
	500	616		PCFM0500			PPFM1050	PTBB1056	PTBB1050	PTBO1050	PBWP1050				PPEB2050		
	700	816		PCFM0700			PPFM1070	PTBB1076	PTBB1070	PTBO1070	PBWP1070				PPEB2070		
	900	1016		PCFM0900			PPFM1090	PTBB1096	PTBB1090	PTBO1090	PBWP1090				PPEB2090		
	1250	1366		PCFM1250			PPFM1250		1STQ005583B0000	1STQ005577B0000	1STQ005594B0000						
1250	200	1366	316	PCFM0200	PUPM2002	PPAM0100	PPFM1020		PTBB1220								
	900	1016		PCFM0900		PPAM0100	PPFM1090		PTBB1290	PTBB1290	PTBO1290	PBWP1290	IP65	IP40	IP65	PPEB2080	
	1250	1366		PCFM1250		PPAM0100	PPFM1250		PPFM1250	1STQ005584B0000	1STQ005578B0000	1STQ005595B0000				PPEA2080	

* The external dimensions include the H=100mm plinth and the panels.

** This code has to be used for application with In > 4000A. It includes No. 2 stainless steel uprights and No. 2 galvanized sheet metal uprights see pag. 2/15.

Consult page 2/12 and 7/2 for selection of the protection class.

(1) In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit, page 2/24.

(2) Use the dedicated incoming cable flanges to obtain protection class IP65. Cables franges page 2/28.

(3) Right rear panel for structures W=1250mm.

(4) Left rear panel for structures W=1250mm.

(5) Door with overlapping for the double door version.

(6) Door with handle for the double door version.



⁽⁷⁾ Finishing profile vertical internal cable compartment.

(8) PCCM... to be ordered when there is an intermediate upright for mounting kit (PUKI....) or an intermediate crosspiece for installing busbars horizontally under the top or on the bottom of the (PKI...) structure or when vertical side partitions are installed. Not compatible with IP40 PBWP....

PUCM... The front upright is always required.
The rear upright is used for fixing the crosspieces that support the busbars and for


fixing the vertical side partitions of the structure. For $In > 4000A$ the rear upright for ICC is PUCS....

(b) The intermediate uprights (PUK1....) are not required for assembling fixed Tmax XT1, XT2, XT3, XT4, T4, T5, T6 and XT1, XT3 with Direct Rotary Handle only in not segregated structures. Order 2 uprights for the kits. To be ordered (2 pieces) for segregation structure except for 2b with kits that don't required PUK1.... To be ordered in case of vertical/horizontal busbar system pag.3/21.

Structure

Guide to the order codes

The new code is formed by 4 letters standing for English terms and 4 numbers, without spaces in between.



RANGE IDENTIFIER

The first letter of all the codes of the new main distribution switchboard "P" stands for "power". Thus the new product is clearly identified by the same initial used for all new components of ABB's System pro E power

TYPE OF PRODUCT AND CHARACTERISTICS

The second letter in the code indicates the type of product or component of the switchboard. The third and fourth letters describe the characteristics or material in more detail.

U = Upright
C = Crosspieces
P = Plinth, Panel, Profile
T = Top
B = Bottom
D = Door
K = Kit

P = Upright, Profile
C = Cable compartment
F = Frame, Flanges, Finishing
A = Plinth angle pieces
I = Intermediate
**B = Bottom
W = Without plinth
E = External cover
D = Double tab insert**


M = Metal/Galvanized sheet metal
S = Stainless steel
B = Blind
O = Open
P = Plinth
A = Vented
G = Glass
H = Horizontal
V = Vertical
T = Top

MEASUREMENTS

The last 4 numbers usually refer to one of the component's measurements or to several dimensions concerning the code. In certain cases, if the last number is 6, it refers to the IP65 protection class.

Structure

Order codes - Frame



Uprights – Galvanized sheet metal

Upright formed by a closed profile made of galvanized sheet metal. The uprights include 8 already assembled 3-way joints, 8 already assembled axial screws and 16 loose axial screws. For applications with In ≤4000A.

Description	Dimensions H (mm)	Type	Order code	Pkg/ No. pcs
No.4 galvanized sheet metal uprights	1800	PUPM1800	1STQ007033A0000	1/4
No.4 galvanized sheet metal uprights	2000	PUPM2000	1STQ007034A0000	1/4

Uprights for enclosure In>4000A

The uprights include 8 already assembled 3-way joints, 8 already assembled axial screws and 16 loose axial screws. For applications with In >4000A.

Description	Dimensions H (mm)	Type	Order code	Pkg/ No. pcs
No.2 stainless steel uprights and no.2 galvanized sheet metal uprights	1800	PUPM1802	1STQ002031B0000	1/4
No.2 stainless steel uprights and no.2 galvanized sheet metal uprights	2000	PUPM2002	1STQ002032B0000	1/4


Examples of use

Galvanized sheet metal In ≤4000A

PUPM1800

PUPM2000

Metal sheet




Uprights for enclosure In>4000A

PUPM1802


PUPM2002

Stainless steel
(AISI304)



Structure


Order codes - Frame



Structure crosspieces

Depth and width crosspieces for structures.

Description	Dimensions (mm)		Type	Order code	Pkg/ No. pcs
	W	D			
Width crosspieces galvanized sheet metal					
No.4 crosspieces in galvanized sheet metal	300		PCFM0300	1STQ007037A0000	1/4
No.4 crosspieces in galvanized sheet metal	400		PCFM0400	1STQ007038A0000	1/4
No.4 crosspieces in galvanized sheet metal	600		PCFM0600	1STQ007040A0000	1/4
No.4 crosspieces in galvanized sheet metal	800		PCFM0800	1STQ007042A0000	1/4
No.4 crosspieces in galvanized sheet metal	1000		PCFM1000	1STQ007043A0000	1/4
No.4 crosspieces in galvanized sheet metal	1250		PCFM1250	1STQ007044A0000	1/4
Depth crosspieces galvanized sheet metal					
No.4 crosspieces in galvanized sheet metal	200		PCFM0200	1STQ007045A0000	1/4
No.4 crosspieces in galvanized sheet metal	300		PCFM0300	1STQ007037A0000	1/4
No.4 crosspieces in galvanized sheet metal	500		PCFM0500	1STQ007039A0000	1/4
No.4 crosspieces in galvanized sheet metal	700		PCFM0700	1STQ007046A0000	1/4
No.4 crosspieces in galvanized sheet metal	900		PCFM0900	1STQ007047A0000	1/4
No.4 crosspieces in galvanized sheet metal	1250		PCFM1250	1STQ007044A0000	1/4
Width crosspieces stainless steel					
No.4 width crosspieces in stainless steel	300		PCFS0300	1STQ007206A0000	1/4
No.4 width crosspieces in stainless steel	400		PCFS0400	1STQ007062A0000	1/4
No.4 width crosspieces in stainless steel	600		PCFS0600	1STQ007063A0000	1/4
No.4 width crosspieces in stainless steel	800		PCFS0800	1STQ007064A0000	1/4
No.4 width crosspieces in stainless steel	1000		PCFS1000	1STQ007065A0000	1/4
No.4 width crosspieces in stainless steel	1250		PCFS1250	1STQ007066A0000	1/4
Depth crosspieces stainless steel					
Depth crosspieces stainless steel	200		PCFS0200	1STQ009174A0000	1/4
Depth crosspieces stainless steel	700		PCFS0700	1STQ007067A0000	1/4
Depth crosspieces stainless steel	900		PCFS0900	1STQ007068A0000	1/4
No.4 width crosspieces in stainless steel	1250		PCFS1250	1STQ007066A0000	1/4




Uprights for internal cable compartment – Galvanized sheet metal

Upright formed by a closed profile in galvanized sheet metal for internal cable compartment with fixing brackets.

Description	Dimensions H (mm)	Dimensions		Pkg/ No. pcs
		Type	Order code	
No.1 galv. sheet metal upright for cable compartment	1800	PUCM1800	1STQ007742A0000	1/1
No.1 galv. sheet metal upright for cable compartment	2000	PUCM2000	1STQ007743A0000	1/1

Structure

Order codes - Frame




Uprights for internal cable compartment – Stainless steel

Upright formed by a closed profile in AISI 304 stainless steel for internal cable compartment with fixing brackets. For applications with $In > 4000A$, the rear internal cable compartment uprights has to be in stainless steel.

Description	Dimensions H (mm)	Type	Order code	Pkg/ No. pcs
No.1 stainless steel upright for cable compartment	1800	PUCS1800	1STQ007749B0000	1/1
No.1 stainless steel upright for cable compartment	2000	PUCS2000	1STQ007750B0000	1/1

The front upright is always required. The rear upright is used for fixing the crosspieces that support the busbars and for fixing the vertical side partitions of the structure. In case of $In > 4000A$ the rear internal cable compartment upright has to be in stainless steel.

Applications examples




Examples of use

Galvanized sheet metal $In \leq 4000A$


PUPM1800
PUPM2000
Metal sheet

PUPM1800
PUPM2000
Metal sheet




Uprights for enclosure $In > 4000A$

PUPM1802
PUPM2002
Stainless steel
(AISI304)



Structure

Order codes - Frame





Uprights for internal cable compartment – Galvanized sheet metal

Upright formed by a closed profile in galvanized sheet metal for internal cable compartment with fixing brackets.

Description	Dimensions P (mm)	Type	Order code	Pkg/ No. pcs
No.2 galvanized sheet cable cont. crosspieces	200	PCCM0200	1STQ007744A0000	1/2
No.2 galvanized sheet cable cont. crosspieces	300	PCCM0300	1STQ007745A0000	1/2
No.2 galvanized sheet cable cont. crosspieces	500	PCCM0500	1STQ007746A0000	1/2
No.2 galvanized sheet cable cont. crosspieces	700	PCCM0700	1STQ007747A0000	1/2
No.2 galvanized sheet cable cont. crosspieces	900	PCCM0900	1STQ007748A0000	1/2
No.2 stainless steel cable cont. crosspieces	700	PCCS0700	1STQ007751A0000	1/2
No.2 stainless steel cable cont. crosspieces	900	PCCS0900	1STQ007752A0000	1/2

To be ordered when there is an intermediate upright for mounting kit PUKI.... or an intermediate crosspiece for installing busbars horizontally under the top or on the bottom of the PCKI.... structure or when vertical side partitions are installed. Not compatible with IP40 PBWP....

Applications examples



Crosspieces for structures – Galvanized sheet metal

Allows the creation of a cable compartment with D=200mm or D=350mm and D=400mm at the back of the structures. To be assembled with 2 intermediate uprights for internal cable container PUCM.... or PUCS....


Description	Dimensions W (mm)	Type	Order code	Pkg/ No. pcs
No.2 galvanized sheet crosspieces for structures	300	PCCM0300	1STQ007745A0000	1/2
No.2 galvanized sheet crosspieces for structures	400	PCCM0400	1STQ001337B0000	1/2
No.2 galvanized sheet crosspieces for structures	600	PCCM0600	1STQ001337B0000	1/2
No.2 galvanized sheet crosspieces for structures	800	PCCM0800	1STQ001338B0000	1/2
No.2 galvanized sheet crosspieces for structures	1000	PCCM1000	1STQ001339B0000	1/2

PUCM1800
PUCM2000


Structure

Order codes - Frame

PPAM0100



PPAM0200




Universal angle pieces for plinths in galvanized sheet metal

Not pre-assembled to the structure. New angle piece with high mechanical strength. Can be fixed from the outside and from the inside of the structure even at a later date. Equipped with anti-rotation system and bottom that can be transported with a transpallet.


Description	Dimensions H (mm)	Type	Order code	Pkg/ No. pcs
No.4 plinth angle pieces	100	PPAM0100	1STQ007048A0000	1/4
No.8 plinth angle pieces H=100mm pre-assembled*	200	PPAM0200	1STQ007207A0000	1/8

*Order no. 2 pieces of H=100mm covering flange kits to complete the H=200mm plinth.

PPIM0100



PPIM0200




Intermediate plinth

Intermediate plinth only for structures W=1250mm

Description	Dimensions H (mm)	Type	Order code	Pkg/ No. pcs
No.2 intermediate plinths	100	PPIM0100*	1STQ007208A0000	1/2
No.4 intermediate plinths H=100mm pre-assembled*	200	PPIM0200*	1STQ007209A0000	1/4

* Order no. 2 pieces of H=100mm covering flange kits to complete the H=200mm intermediate plinth..




Brackets for fixing to the floor

The kit allows the floor or on container fixing of the structure by means of M12 screws.

Description	Type	Order code	Pkg/ No. pcs
No.4 floor fixing brackets	ZN1041	1STQ006833A0000	1/4

Structure


Order codes - Frame



Plinth flanges

Side and front/rear plinth flanges H=100mm RAL 7012.

Description	Dimensions (mm)			Pkg/ No. pcs
	W	D	Type	
Front/rear plinth flanges				
No.2 plinth flanges	300	PPFM1030	1STQ007050A0000	1/2
No.2 plinth flanges	400	PPFM1040	1STQ007051A0000	1/2
No.2 plinth flanges	600	PPFM1060	1STQ007053A0000	1/2
No.2 plinth flanges	800	PPFM1080	1STQ007055A0000	1/2
No.2 plinth flanges	1000	PPFM1010	1STQ007056A0000	1/2
No.4 plinth flanges	1250	PPFM1250	1STQ007057A0000	1/4
Side plinth flanges				
No.2 plinth flanges	200	PPFM1020	1STQ007058A0000	1/2
No.2 plinth flanges	300	PPFM1030	1STQ007050A0000	1/2
No.2 plinth flanges	500	PPFM1050	1STQ007052A0000	1/2
No.2 plinth flanges	700	PPFM1070	1STQ007059A0000	1/2
No.2 plinth flanges	900	PPFM1090	1STQ007060A0000	1/2




Brackets for bottoms without plinth

The kit allows the mounting of the angle pieces PPAM.... from the inside of the structure or the application of enclosures without plinth when combined with the proper internal bottom PBWP.... IP40 or the other bottom codes available that have to be cut according to the drilling indication in chapter 8.

Description	Type	Order code	Pkg/ No. pcs
No. 4 brackets for bottoms without plinth	PBRB0004	1STQ008127A0000	1/4

Structure

Order codes - External covers




Blind Top/Bottom IP65 – Pickled sheet steel

Pickled sheet steel with IP65 gasket. The article comprises one single component that can be used as either a top or bottom. In order to purchase both the top and the bottom, please order two quantities of the same code or two different top/bottom codes according to the desired design of the structure. The code includes four M12x20 screws.

Description	Dimensions (mm)			Pkg/ No. pcs
	W	D	Type	
Blind Top/Bottom IP65	300	200	PTBB3026	1/1
Blind Top/Bottom IP65	300	300	PTBB3036	1/1
Blind Top/Bottom IP65	300	500	PTBB3056	1/1
Blind Top/Bottom IP65	300	700	PTBB3076	1/1
Blind Top/Bottom IP65	300	900	PTBB3096	1/1
Blind Top/Bottom IP65	400	200	PTBB4026	1/1
Blind Top/Bottom IP65	400	300	PTBB4036	1/1
Blind Top/Bottom IP65	400	500	PTBB4056	1/1
Blind Top/Bottom IP65	400	700	PTBB4076	1/1
Blind Top/Bottom IP65	400	900	PTBB4096	1/1
Blind Top/Bottom IP65	600	200	PTBB6026	1/1
Blind Top/Bottom IP65	600	300	PTBB6036	1/1
Blind Top/Bottom IP65	600	500	PTBB6056	1/1
Blind Top/Bottom IP65	600	700	PTBB6076	1/1
Blind Top/Bottom IP65	600	900	PTBB6096	1/1
Blind Top/Bottom IP65	800	200	PTBB8026	1/1
Blind Top/Bottom IP65	800	300	PTBB8036	1/1
Blind Top/Bottom IP65	800	500	PTBB8056	1/1
Blind Top/Bottom IP65	800	700	PTBB8076	1/1
Blind Top/Bottom IP65	800	900	PTBB8096	1/1
Blind Top/Bottom IP65	1000	200	PTBB1026	1/1
Blind Top/Bottom IP65	1000	300	PTBB1036	1/1
Blind Top/Bottom IP65	1000	500	PTBB1056	1/1
Blind Top/Bottom IP65	1000	700	PTBB1076	1/1
Blind Top/Bottom IP65	1000	900	PTBB1096	1/1
Blind Top/Bottom IP65	1250	300	PTBB1230	1/1

Structure

Order codes - External covers



Open top/bottom IP65 – for internal cable container

Pickled sheet steel with IP65 gasket. In order to reach IP65 protection degree, use the dedicated fixed cable incoming flanges both for equipment compartment and internal cable compartment.

Use the fixed cable incoming flanges with the same dimension as the equipment compartment PFCF....
Pag 2/27.

Description	Dimensions (mm)			Order code	Pkg/ No. pcs
	W	D	Type		
Open top/bottom IP65					
Open top/bottom 600+200mm	800	300	PTBO8231	1STQ002076B0000	1/1
Open top/bottom 600+200mm	800	500	PTBO8251	1STQ002077B0000	1/1
Open top/bottom 600+200mm	800	700	PTBO8271	1STQ002078B0000	1/1
Open top/bottom 600+200mm	800	900	PTBO8291	1STQ002079B0000	1/1
Open top/bottom 800+200mm	1000	300	PTBO1231	1STQ002080B0000	1/1
Open top/bottom 800+200mm	1000	500	PTBO1251	1STQ002081B0000	1/1
Open top/bottom 800+200mm	1000	700	PTBO1271	1STQ002082B0000	1/1
Open top/bottom 800+200mm	1000	900	PTBO1291	1STQ002083B0000	1/1
Open top/bottom 600+400mm	1000	300	PTBO1431	1STQ002084B0000	1/1
Open top/bottom 600+400mm	1000	500	PTBO1451	1STQ002085B0000	1/1
Open top/bottom 600+400mm	1000	700	PTBO1471	1STQ002086B0000	1/1
Open top/bottom 600+400mm	1000	900	PTBO1491	1STQ002087B0000	1/1
Blind fixed flange IP65 for internal cable container					
Blind fixed flange	200	300	PFCF2031	1STQ002048B0000	1/1
Blind fixed flange	200	500	PFCF2051	1STQ002049B0000	1/1
Blind fixed flange	200	700	PFCF2071	1STQ002050B0000	1/1
Blind fixed flange	200	900	PFCF2091	1STQ002051B0000	1/1
Blind fixed flange	400	300	PFCF4031	1STQ002052B0000	1/1
Blind fixed flange	400	500	PFCF4051	1STQ002053B0000	1/1
Blind fixed flange	400	700	PFCF4071	1STQ002054B0000	1/1
Blind fixed flange	400	900	PFCF4091	1STQ002055B0000	1/1

Example:

Base IP65 W 800mm D 500mm with 200mm W internal cable container.

Order:


n°1 PTBO8251 open bottom W 800mm (600 + 200) D 500mm

n°1 PFCF2051 blind fixed flange for internal cable container W 200mm D 500mm

n°1 PFCF6050 blind fixed flange for equipment compartment W 600mm D 500mm

Structure

Order codes - External covers




Top/bottom IP65 for corner structures

Pickled sheet steel with IP65 gasket. The article comprises one single component that can be used as either a top or bottom. In order to purchase both the top and the bottom, please order two quantities of the same code or two different top/bottom codes according to the desired design of the structure. It requires the use of the relating kit PSCS0579 in case of joining corner structures.

Description	Dimensions (mm)			Pkg/ No. pcs
	W	D	Type	
Blind Top/Bottom IP65	500	500	PTBB5050	1STQ009179A0000
Blind Top/Bottom IP65	700	700	PTBB7070	1STQ009180A0000
Blind Top/Bottom IP65	900	900	PTBB9090	1STQ009181A0000


In order to complete the corner structure, use all the standard codes except from n.1 Kit for joining corner structures PSCS0579 (pag.2/40) and, if it is the case, the Top sealing kit IP31/IP4 (pag.2-23).

In case of horizontal busbars, the passage is permitted only on the back or under the top by using no.2 brackets PBCB0002 and the universal crosspieces PCRM2013 to be cut accordingly.



Structure

Order codes - External covers



Blind Top/Bottom IP30, IP40 – Pickled sheet steel

Pickled sheet steel without gasket. In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit, page 2-23.

The article comprises one single component that can be used as either a top or bottom. In order to purchase both the top and the bottom, please order two quantities of the same code or two different top/bottom codes according to the desired design of the structure. The code includes four M12x20 screws.

Description	Dimensions (mm)			Pkg/ No. pcs
	W	D	Type	
Blind Top/Bottom IP30, 40	300	200	PTBB3020	1STQ007107A0000
Blind Top/Bottom IP30, 40	300	300	PTBB3030	1STQ007108A0000
Blind Top/Bottom IP30, 40	300	500	PTBB3050	1STQ007109A0000
Blind Top/Bottom IP30, 40	300	700	PTBB3070	1STQ007110A0000
Blind Top/Bottom IP30, 40	300	900	PTBB3090	1STQ007111A0000
Blind Top/Bottom IP30, 40 NEW*	300	1250	PTBB3012	1STQ005579B0000
Blind Top/Bottom IP30, 40	400	200	PTBB4020	1STQ007112A0000
Blind Top/Bottom IP30, 40	400	300	PTBB4030	1STQ007113A0000
Blind Top/Bottom IP30, 40	400	500	PTBB4050	1STQ007114A0000
Blind Top/Bottom IP30, 40	400	700	PTBB4070	1STQ007115A0000
Blind Top/Bottom IP30, 40	400	900	PTBB4090	1STQ007116A0000
Blind Top/Bottom IP30, 40 NEW*	400	1250	PTBB4012	1STQ005580B0000
Blind Top/Bottom IP30, 40	600	200	PTBB6020	1STQ007117A0000
Blind Top/Bottom IP30, 40	600	300	PTBB6030	1STQ007118A0000
Blind Top/Bottom IP30, 40	600	500	PTBB6050	1STQ007119A0000
Blind Top/Bottom IP30, 40	600	700	PTBB6070	1STQ007120A0000
Blind Top/Bottom IP30, 40	600	900	PTBB6090	1STQ007121A0000
Blind Top/Bottom IP30, 40 NEW*	600	1250	PTBB6012	1STQ005581B0000
Blind Top/Bottom IP30, 40	800	200	PTBB8020	1STQ007122A0000
Blind Top/Bottom IP30, 40	800	300	PTBB8030	1STQ007123A0000
Blind Top/Bottom IP30, 40	800	500	PTBB8050	1STQ007124A0000
Blind Top/Bottom IP30, 40	800	700	PTBB8070	1STQ007125A0000
Blind Top/Bottom IP30, 40	800	900	PTBB8090	1STQ007126A0000
Blind Top/Bottom IP30, 40 NEW*	800	1250	PTBB8012	1STQ005582B0000
Blind Top/Bottom IP30, 40	1000	200	PTBB1020	1STQ009152A0000
Blind Top/Bottom IP30, 40	1000	300	PTBB1030	1STQ007127A0000
Blind Top/Bottom IP30, 40	1000	500	PTBB1050	1STQ007128A0000
Blind Top/Bottom IP30, 40	1000	700	PTBB1070	1STQ007129A0000
Blind Top/Bottom IP30, 40	1000	900	PTBB1090	1STQ007130A0000
Blind Top/Bottom IP30, 40 NEW*	1000	1250	PTBB1012	1STQ005583B0000
Blind Top/Bottom IP30, 40	1250	200	PTBB1220	1STQ009153A0000
Blind Top/Bottom IP30, 40	1250	900	PTBB1290	1STQ007131A0000
Blind Top/Bottom IP30, 40 NEW*	1250	1250	PTBB1212	1STQ005584B0000

* Codes available for sales starting from January 2018

Realization of the different IP protection class:

IP30: IP30, IP40 panels + vertical finishing profiles for structure or external cable container PPPV.... or vertical finishing profiles for internal cable container PPCV.... and horizontal finishing profiles PPFH....

IP31: add to IP30 codes the top sealing kit PKST.... and PKDT


IP40: IP30, IP40 panels + blind door IP40/IP41 PDLB.... or glass door IP40/IP41 PDLG....

IP41: add to IP40 codes the top sealing kit PKDT.... PKST and PKDT

IP65: dedicated IP65 codes

Structure

Order codes - External covers




Top sealing kit IP31/IP41

Profiles for IP31/IP41 for top.

Description	Dimensions (mm)			Pkg/ No. pcs
	W	D	Type	
N.2 roof profiles for single column	200		PKST0200	1STQ001905B0000
N.2 roof profiles for single column	300		PKST0301	1STQ001935B0000
N.2 roof profiles for single column	500		PKST0501	1STQ001936B0000
N.2 roof profiles for single column	700		PKST0700	1STQ001911B0000
N.2 roof profiles for single column	900		PKST0900	1STQ001914B0000
N.2 roof profiles for single column	250		PKST0250	1STQ001906B0000
N.2 roof profiles for single column	300		PKST0300	1STQ001907B0000
N.2 roof profiles for single column	400		PKST0400	1STQ001908B0000
N.2 roof profiles for single column	500		PKST0500	1STQ001909B0000
N.2 roof profiles for single column	600		PKST0600	1STQ001910B0000
N.2 roof profiles for single column	750		PKST0750	1STQ001912B0000
N.2 roof profiles for single column	800		PKST0800	1STQ001913B0000
N.2 roof profiles for single column	1000		PKST1000	1STQ001915B0000
N.2 roof profiles for single column	1250		PKST1250	1STQ001916B0000
N.1 roof profile for side by side column	200		PKDT0200	1STQ001917B0000
N.1 roof profile for side by side column	300		PKDT0301	1STQ001937B0000
N.1 roof profile for side by side column	700		PKDT0700	1STQ001923B0000
N.1 roof profile for side by side column	900		PKDT0900	1STQ001926B0000
N.1 roof profile for side by side column	500		PKDT0501	1STQ001938B0000
N.1 roof profile for back to back column	250		PKDT0250	1STQ001918B0000
N.1 roof profile for back to back column	300		PKDT0300	1STQ001919B0000
N.1 roof profile for back to back column	400		PKDT0400	1STQ001920B0000
N.1 roof profile for back to back column	500		PKDT0500	1STQ001921B0000
N.1 roof profile for back to back column	600		PKDT0600	1STQ001922B0000
N.1 roof profile for back to back column	750		PKDT0750	1STQ001924B0000
N.1 roof profile for back to back column	800		PKDT0800	1STQ001925B0000
N.1 roof profile for back to back column	1000		PKDT1000	1STQ001927B0000
N.1 roof profile for back to back column	1250		PKDT1250	1STQ001928B0000
Roof profiles for corner structure	500	500	PKAT5050	1STQ001939B0000
Roof profiles for corner structure	700	700	PKAT7070	1STQ001941B0000
Roof profiles for corner structure	900	900	PKAT9090	1STQ001943B0000

Structure

Order codes - External covers



Open Top/Bottom


Pickled sheet steel with holes. The code comprises one single component that can be used as either a top or bottom. In order to purchase both the top and the bottom, please order two quantities of the same code or two different top/bottom codes according to the desired design of the structure.

In order to reach IP65 protection degree, use the dedicated fixed cable incoming flanges PFCF....; in order to reach IP40 protection degree, use the dedicated swinging cable incoming flanges PFCS.... at page 2/25. The use of the single open top/bottom without flanges does not guarantee any degree of protection IP. The open top/ bottom, associated with sliding flanges, is incompatible with crosspieces assembled inside the cable compartment.

Description	Dimensions (mm)			Pkg/ No. pcs
	W	D	Type	
Open Top/Bottom	300	200	PTBO3020	1STQ007135A0000
Open Top/Bottom	300	300	PTBO3030	1STQ007136A0000
Open Top/Bottom	300	500	PTBO3050	1STQ007137A0000
Open Top/Bottom	300	700	PTBO3070	1STQ007138A0000
Open Top/Bottom	300	900	PTBO3090	1STQ007139A0000
Open Top/Bottom	400	200	PTBO4020	1STQ007140A0000
Open Top/Bottom	400	300	PTBO4030	1STQ007141A0000
Open Top/Bottom	400	500	PTBO4050	1STQ007142A0000
Open Top/Bottom	400	700	PTBO4070	1STQ007143A0000
Open Top/Bottom	400	900	PTBO4090	1STQ007144A0000
Open Top/Bottom	600	200	PTBO6020	1STQ007147A0000
Open Top/Bottom	600	300	PTBO6030	1STQ007148A0000
Open Top/Bottom	600	500	PTBO6050	1STQ007149A0000
Open Top/Bottom	600	700	PTBO6070	1STQ007150A0000
Open Top/Bottom	600	900	PTBO6090	1STQ007151A0000
Open Top/Bottom	800	200	PTBO8020	1STQ007155A0000
Open Top/Bottom	800	300	PTBO8030	1STQ007156A0000
Open Top/Bottom	800	500	PTBO8050	1STQ007157A0000
Open Top/Bottom	800	700	PTBO8070	1STQ007158A0000
Open Top/Bottom	800	900	PTBO8090	1STQ007159A0000
Open Top/Bottom	1000	300	PTBO1030	1STQ007160A0000
Open Top/Bottom	1000	500	PTBO1050	1STQ007161A0000
Open Top/Bottom	1000	700	PTBO1070	1STQ007162A0000
Open Top/Bottom	1000	900	PTBO1090	1STQ007163A0000
Open Top/Bottom	1250	900	PTBO1290	1STQ007167A0000

Structure

Order codes - External covers




Fixed incoming cable flange

Fixed incoming cable flange in sheet metal to use in conjunction with the open bottom to guarantee IP65 protection class. With internal cable compartment crosspieces it is necessary to mount the fixed flange first.

Description	Dimensions (mm)			Pkg/ No. pcs
	W	D	Type	
Fixed incoming cable flange	300	200	PFCF3020	1STQ007658A0000
Fixed incoming cable flange	300	300	PFCF3030	1STQ007659A0000
Fixed incoming cable flange	300	500	PFCF3050	1STQ007660A0000
Fixed incoming cable flange	300	700	PFCF3070	1STQ007661A0000
Fixed incoming cable flange	300	900	PFCF3090	1STQ007662A0000
Fixed incoming cable flange	400	200	PFCF4020	1STQ007663A0000
Fixed incoming cable flange	400	300	PFCF4030	1STQ007664A0000
Fixed incoming cable flange	400	500	PFCF4050	1STQ007665A0000
Fixed incoming cable flange	400	700	PFCF4070	1STQ007666A0000
Fixed incoming cable flange	400	900	PFCF4090	1STQ007667A0000
Fixed incoming cable flange	600	200	PFCF6020	1STQ007670A0000
Fixed incoming cable flange	600	300	PFCF6030	1STQ007671A0000
Fixed incoming cable flange	600	500	PFCF6050	1STQ007672A0000
Fixed incoming cable flange	600	700	PFCF6070	1STQ007673A0000
Fixed incoming cable flange	600	900	PFCF6090	1STQ007674A0000
Fixed incoming cable flange	800	200	PFCF8020	1STQ007678A0000
Fixed incoming cable flange	800	300	PFCF8030	1STQ007679A0000
Fixed incoming cable flange	800	500	PFCF8050	1STQ007680A0000
Fixed incoming cable flange	800	700	PFCF8070	1STQ007681A0000
Fixed incoming cable flange	800	900	PFCF8090	1STQ007682A0000
Fixed incoming cable flange	1000	300	PFCF1030	1STQ007683A0000
Fixed incoming cable flange	1000	500	PFCF1050	1STQ007684A0000
Fixed incoming cable flange	1000	700	PFCF1070	1STQ007685A0000
Fixed incoming cable flange	1000	900	PFCF1090	1STQ007686A0000
Fixed incoming cable flange	1250	900	2xPFCF6090	1STQ007674A0000

Structure


Order codes - External covers



NEW Blind top arc fault resistant

Top panel composed by 2 flaps that, in case of internal arc fault, they allows its outburst upward, protecting an operator that could be present in front of the switchboard. All the switchboard must be composed by IP65 panels but, due to flap presence, its final protection grade will be IP41.

Description	Dimensions (mm)		Type	Order code	Pkg/ No. pcs
	W	D			
Blind top arc fault	300	700	PTAB3070	1STQ002035B0000	1/1
Blind top arc fault	300	900	PTAB3090	1STQ002036B0000	1/1
Blind top arc fault	400	700	PTAB4070	1STQ002037B0000	1/1
Blind top arc fault	400	900	PTAB4090	1STQ002038B0000	1/1
Blind top arc fault	600	700	PTAB6076	1STQ002023B0000	1/1
Blind top arc fault	600	900	PTAB6096	1STQ002024B0000	1/1
Blind top arc fault	800	700	PTAB8076	1STQ002025B0000	1/1
Blind top arc fault	800	900	PTAB8096	1STQ002026B0000	1/1
Blind top arc fault	1000	700	PTAB1076	1STQ002027B0000	1/1
Blind top arc fault	1000	900	PTAB1096	1STQ002028B0000	1/1




Sliding incoming cable flanges in sheet metal

Sliding incoming cable flanges in sheet metal to use in conjunction with the open bottom to guarantee IP40 protection class. It is not possible to assemble the sliding flanges in structures with internal cable compartment.

Description	Dimensions (mm)		Type	Order code	Pkg/ No. pcs
	W	D			
No.2 sliding flanges	400	500	PFCS4050	1STQ007699A0000	1/2
No.2 sliding flanges	400	700	PFCS4070	1STQ007700A0000	1/2
No.2 sliding flanges	400	900	PFCS4090	1STQ007701A0000	1/2
No.2 sliding flanges	600	500	PFCS6050	1STQ007705A0000	1/2
No.2 sliding flanges	600	700	PFCS6070	1STQ007706A0000	1/2
No.2 sliding flanges	600	900	PFCS6090	1STQ007707A0000	1/2
No.2 sliding flanges	800	500	PFCS8050	1STQ007712A0000	1/2
No.2 sliding flanges	800	700	PFCS8070	1STQ007713A0000	1/2
No.2 sliding flanges	800	900	PFCS8090	1STQ007714A0000	1/2
No.2 sliding flanges	1000	500	PFCS1050	1STQ007716A0000	1/2
No.2 sliding flanges	1000	700	PFCS1070	1STQ007717A0000	1/2
No.2 sliding flanges	1000	900	PFCS1090	1STQ007718A0000	1/2
No.2 sliding flanges	1250	900	2xPFCS6090	1STQ007707A0000	1/2



Structure

Order codes - External covers



Internal bottom IP40

Internal galvanized steel bottom with special brackets kit included (special brackets kit available also as spare part with the code PBRB0004). In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit PKST...and PKDT..., page 2/25.




Description	Dimensions (mm)			Order code	Pkg/ No. pcs
	W	D	Type		
Internal bottom	300	200	PBWP3020	1STQ007171A0000	1/1
Internal bottom	300	300	PBWP3030	1STQ007172A0000	1/1
Internal bottom	300	500	PBWP3050	1STQ007173A0000	1/1
Internal bottom	300	700	PBWP3070	1STQ007174A0000	1/1
Internal bottom	300	900	PBWP3090	1STQ007175A0000	1/1
Internal bottom NEW*	300	1250	1STQ005590B0000	1STQ005590B0000	1/1
Internal bottom	400	200	PBWP4020	1STQ007176A0000	1/1
Internal bottom	400	300	PBWP4030	1STQ007177A0000	1/1
Internal bottom	400	500	PBWP4050	1STQ007178A0000	1/1
Internal bottom	400	700	PBWP4070	1STQ007179A0000	1/1
Internal bottom	400	900	PBWP4090	1STQ007180A0000	1/1
Internal bottom NEW*	400	1250	1STQ005591B0000	1STQ005591B0000	1/1
Internal bottom	600	200	PBWP6020	1STQ007183A0000	1/1
Internal bottom	600	300	PBWP6030	1STQ007184A0000	1/1
Internal bottom	600	500	PBWP6050	1STQ007185A0000	1/1
Internal bottom	600	700	PBWP6070	1STQ007186A0000	1/1
Internal bottom	600	900	PBWP6090	1STQ007187A0000	1/1
Internal bottom NEW*	600	1250	1STQ005592B0000	1STQ005592B0000	1/1
Internal bottom	800	200	PBWP8020	1STQ007191A0000	1/1
Internal bottom	800	300	PBWP8030	1STQ007192A0000	1/1
Internal bottom	800	500	PBWP8050	1STQ007193A0000	1/1
Internal bottom	800	700	PBWP8070	1STQ007194A0000	1/1
Internal bottom	800	900	PBWP8090	1STQ007195A0000	1/1
Internal bottom NEW*	800	1250	1STQ005593B0000	1STQ005593B0000	1/1
Internal bottom	1000	300	PBWP1030	1STQ007196A0000	1/1
Internal bottom	1000	500	PBWP1050	1STQ007197A0000	1/1
Internal bottom	1000	700	PBWP1070	1STQ007198A0000	1/1
Internal bottom	1000	900	PBWP1090	1STQ007199A0000	1/1
Internal bottom NEW*	1000	1250	1STQ005594B0000	1STQ005594B0000	1/1
Internal bottom	1250	900	PBWP1290	1STQ007203A0000	1/1
Internal bottom NEW*	1250	1250	1STQ005595B0000	1STQ005595B0000	1/1

* Codes available for sales starting from January 2018

Structure


Order codes - External covers



External blind rear panel IP65

Pickled sheet steel with gasket and plugs IP65.

Description	Dimensions (mm)			Pkg/ No. pcs
	H	W	Type	
Blind rear panel IP65	1800	300	PPEB1836	1STQ007577A0000
Blind rear panel IP65	1800	400	PPEB1846	1STQ007578A0000
Blind rear panel IP65	1800	600	PPEB1866	1STQ007580A0000
Blind rear panel IP65	1800	800	PPEB1886	1STQ007583A0000
Blind rear panel IP65	1800	1000	PPEB1816	1STQ007585A0000
Blind rear panel IP65	2000	300	PPEB2036	1STQ007589A0000
Blind rear panel IP65	2000	400	PPEB2046	1STQ007590A0000
Blind rear panel IP65	2000	600	PPEB2066	1STQ007592A0000
Blind rear panel IP65	2000	800	PPEB2086	1STQ007594A0000
Blind rear panel IP65	2000	1000	PPEB2016	1STQ007596A0000



External blind rear panel IP30, IP40

Pickled sheet steel without gasket. In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit PKST...and PKDT..., page 2/25.

Description	Dimensions (mm)			Pkg/ No. pcs	
	H	W	Type		
Blind rear panel IP30, IP40	1800	300	PPEB1830	1STQ007608A0000	
Blind rear panel IP30, IP40	1800	400	PPEB1840	1STQ007609A0000	
Blind rear panel IP30, IP40	1800	600	PPEB1860	1STQ007611A0000	
Blind rear panel IP30, IP40	1800	800	PPEB1880	1STQ007613A0000	
Blind rear panel IP30, IP40	1800	1000	PPEB1810	1STQ007615A0000	
Blind rear panel IP30, IP40	right	1800	1250	PPRB1820	1STQ007616A0000
Blind rear panel IP30, IP40	left	1800	1250	PPLB1820	1STQ007617A0000
Blind rear panel IP30, IP40	2000	300	PPEB2030	1STQ007619A0000	
Blind rear panel IP30, IP40	2000	400	PPEB2040	1STQ007620A0000	
Blind rear panel IP30, IP40	2000	600	PPEB2060	1STQ007622A0000	
Blind rear panel IP30, IP40	2000	800	PPEB2080	1STQ007624A0000	
Blind rear panel IP30, IP40	2000	1000	PPEB2010	1STQ007626A0000	
Blind rear panel IP30, IP40	right	2000	1250	PPRB2020	1STQ007627A0000
Blind rear panel IP30, IP40	left	2000	1250	PPLB2020	1STQ007628A0000

Realization of the different IP protection class:

IP30: IP30, IP40 panels + vertical finishing profiles for structure or external cable container PPFV.... or vertical finishing profiles for internal cable container PPCV.... and horizontal finishing profiles PPFH....

IP31: add to IP30 codes the top sealing kit PKPT....

IP40: IP30, IP40 panels + blind door IP40/IP41 PDLB.... or glass door IP40/IP41 PDLG....


IP41: add to IP40 codes the top sealing kit PKPT....

IP65: dedicated IP65 codes

Structure

Order codes - External covers


2



External vented rear panel IP30

In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit PKST...and PKDT..., page 2/25.

Description	No. Vented grates	Dimensions (mm)			Type	Order code	Pkg/ No. pcs
		H	W				
Vented rear panel IP30	2	1800	300	PPEA1830	1STQ007630A0000		1/1
Vented rear panel IP30	2	1800	400	PPEA1840	1STQ007631A0000		1/1
Vented rear panel IP30	2	1800	600	PPEA1860	1STQ007633A0000		1/1
Vented rear panel IP30	4	1800	800	PPEA1880	1STQ007636A0000		1/1
Vented rear panel IP30	6	1800	1000	PPEA1810	1STQ007638A0000		1/1
Vented rear panel IP30/31 with gasket	right 6 left 6	1800	1250	PPRA1820	1STQ007639A0000		1/1
Vented rear panel IP30	2	2000	300	PPEA2030	1STQ007641A0000		1/1
Vented rear panel IP30	2	2000	400	PPEA2040	1STQ007642A0000		1/1
Vented rear panel IP30	2	2000	600	PPEA2060	1STQ007644A0000		1/1
Vented rear panel IP30	4	2000	800	PPEA2080	1STQ007646A0000		1/1
Vented rear panel IP30	6	2000	1000	PPEA2010	1STQ007648A0000		1/1
Vented rear panel IP30 with gasket	right 4 left 4	2000	1250	PPRA2020	1STQ007649A0000		1/1
		2000	1250	PPLA2020	1STQ007650A0000		1/1




External blind side panel IP65

Pickled sheet steel with gasket and plugs IP65. The code refers to one single side panel.

Description	Dimensions (mm)			Type	Order code	Pkg/ No. pcs
	H	D				
Blind side panel IP65	1800	200	PPEB1826	1STQ007575A0000		1/1
Blind side panel IP65	1800	300	PPEB1836	1STQ007577A0000		1/1
Blind side panel IP65	1800	500	PPEB1856	1STQ007579A0000		1/1
Blind side panel IP65	1800	700	PPEB1876	1STQ007581A0000		1/1
Blind side panel IP65	1800	900	PPEB1896	1STQ007584A0000		1/1
Blind side panel IP65	2000	200	PPEB2026	1STQ007588A0000		1/1
Blind side panel IP65	2000	300	PPEB2036	1STQ007589A0000		1/1
Blind side panel IP65	2000	500	PPEB2056	1STQ008106A0000		1/1
Blind side panel IP65	2000	700	PPEB2076	1STQ008107A0000		1/1
Blind side panel IP65	2000	900	PPEB2096	1STQ008108A0000		1/1

Structure

Order codes - External covers




External blind side panel IP30, IP40

Pickled sheet steel with gasket. The code refers to one single side panel. In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit PKST...and PKDT..., page 2/25.

Description	Dimensions (mm)			Pkg/ No. pcs
	H	D	Type	
Blind side panel IP30, IP40	1800	200	PPEB1820	1/1
Blind side panel IP30, IP40	1800	300	PPEB1830	1/1
Blind side panel IP30, IP40	1800	500	PPEB1850	1/1
Blind side panel IP30, IP40	1800	700	PPEB1870	1/1
Blind side panel IP30, IP40	1800	900	PPEB1890	1/1
Blind side panel IP30, IP40	2000	200	PPEB2020	1/1
Blind side panel IP30, IP40	2000	300	PPEB2030	1/1
Blind side panel IP30, IP40	2000	500	PPEB2050	1/1
Blind side panel IP30, IP40	2000	700	PPEB2070	1/1
Blind side panel IP30, IP40	2000	900	PPEB2090	1/1

Structure

Order codes - External covers



External vented side panel IP30

Pickled sheet steel without gasket. The code refers to one single side panel. For IP40 order the dedicated grate PGPP0040. In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit PKST...and PKDT..., page 2/25.

Description	No. Vented grates	Dimensions (mm)		Type	Order code	Pkg/ No. pcs
		H	D			
Vented side panel IP30	2	1800	300	PPEA1830	1STQ007630A0000	1/1
Vented side panel IP30	2	1800	500	PPEA1850	1STQ007632A0000	1/1
Vented side panel IP30	2	1800	700	PPEA1870	1STQ007634A0000	1/1
Vented side panel IP30	4	1800	900	PPEA1890	1STQ007637A0000	1/1
Vented side panel IP30	2	2000	300	PPEA2030	1STQ007641A0000	1/1
Vented side panel IP30	2	2000	500	PPEA2050	1STQ007643A0000	1/1
Vented side panel IP30	2	2000	700	PPEA2070	1STQ007645A0000	1/1
Vented side panel IP30	4	2000	900	PPEA2090	1STQ007647A0000	1/1

Realization of the different IP protection class:


IP30: IP30, IP40 panels + vertical finishing profiles for structure or external cable container PPFV.... or vertical finishing profiles for internal cable container PPCV.... and horizontal finishing profiles PPFH....

IP31: add to IP30 codes the top sealing kit PKPT....

IP40: IP30, IP40 panels + blind door IP40/IP41 PDLB.... or glass door IP40/IP41 PDLG....

IP41: add to IP40 codes the top sealing kit PKPT....

IP65: dedicated IP65 codes




IP40 grate for Vented external panels

Accessory for Vented panels. Allows IP40 protection class to be obtained. Order the quantity on the basis of the number of grates on the panel. In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit, page 2/25.

Description	Type	Order code	Pkg/ No. pcs
No. IP40 grates for Vented panels	PGPP0040	1STQ008090A0000	1/2

Structure

Order codes - External covers




Glass door IP65

Pickled sheet steel with gasket. Opens through 135° (single column). Complete with 4 hinges to be screwed onto the uprights, 4 door closing brackets with cover and handle. Handle and hinges provided (not pre-assembled for complete reversibility). Doors can be mounted both on the front and on the back of the enclosures.

Description	No. DIN modules H	Dimensions (mm)		Cable compartment W	Type	Order code	Pkg/ No. pcs
		W	H				
Glass door							
Glass door IP65	12	1800	400		PDLG1846	1STQ007303A0000	1/1
Glass door IP65	24	1800	600		PDLG1866	1STQ007305A0000	1/1
Glass door IP65	36	1800	800		PDLG1886	1STQ007308A0000	1/1
Glass door IP65	48	1800	1000		PDLG1816	1STQ007311A0000	1/1
Glass door IP65	12	2000	400		PDLG2046	1STQ007314A0000	1/1
Glass door IP65	24	2000	600		PDLG2066	1STQ007316A0000	1/1
Glass door IP65	36	2000	800		PDLG2086	1STQ007319A0000	1/1
Glass door IP65	48	2000	1000		PDLG2016	1STQ007322A0000	1/1
Glass door for structures with internal cable compartment							
Glass door IP65	12	1800	600	200	PDLG1842	1STQ007304A0000	1/1
Glass door IP65	12	1800	800	400	PDLG1844	1STQ007306A0000	1/1
Glass door IP65	24	1800	800	200	PDLG1862	1STQ007307A0000	1/1
Glass door IP65	24	1800	1000	400	PDLG1864	1STQ007309A0000	1/1
Glass door IP65	36	1800	1000	200	PDLG1882	1STQ007310A0000	1/1
Glass door IP65	12	2000	600	200	PDLG2042	1STQ007315A0000	1/1
Glass door IP65	12	2000	800	400	PDLG2044	1STQ007317A0000	1/1
Glass door IP65	24	2000	800	200	PDLG2062	1STQ007318A0000	1/1
Glass door IP65	24	2000	1000	400	PDLG2064	1STQ007320A0000	1/1
Glass door IP65	36	2000	1000	200	PDLG2082	1STQ007321A0000	1/1

Structure


Order codes - External covers



Glass door IP40


Pickled sheet steel without gasket and 4 rubber overlapping plugs. Opens through 135° (single column). Complete with 4 hinges to be screwed onto the uprights, 4 door closing brackets with cover and handle. Handle and hinges provided (not pre-assembled for complete reversibility). In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit PKST...and PKDT..., page 2/25. Doors can be mounted both on the front and on the back of the enclosures.

Description	No. DIN modules H	Dimensions (mm)		Cable compartment W	Type	Order code	Pkg/ No. pcs
		W	H				
Glass door							
Glass door IP40	12	1800	400		PDLG1840	1STQ007325A0000	1/1
Glass door IP40	24	1800	600		PDLG1860	1STQ007327A0000	1/1
Glass door IP40	36	1800	800		PDLG1880	1STQ007330A0000	1/1
Glass door IP40	48	1800	1000		PDLG1810	1STQ007333A0000	1/1
Glass door IP40	12	2000	400		PDLG2040	1STQ007336A0000	1/1
Glass door IP40	24	2000	600		PDLG2060	1STQ007338A0000	1/1
Glass door IP40	36	2000	800		PDLG2080	1STQ007341A0000	1/1
Glass door IP40	48	2000	1000		PDLG2010	1STQ007344A0000	1/1
Glass door for structures with internal cable compartment							
Glass door IP40	12	1800	600	200	PDLG8420	1STQ007326A0000	1/1
Glass door IP40	12	1800	800	400	PDLG8440	1STQ007328A0000	1/1
Glass door IP40	24	1800	800	200	PDLG8620	1STQ007329A0000	1/1
Glass door IP40	24	1800	1000	400	PDLG8640	1STQ007331A0000	1/1
Glass door IP40	36	1800	1000	200	PDLG8820	1STQ007332A0000	1/1
Glass door IP40	12	2000	600	200	PDLG2420	1STQ007337A0000	1/1
Glass door IP40	12	2000	800	400	PDLG2440	1STQ007339A0000	1/1
Glass door IP40	24	2000	800	200	PDLG2620	1STQ007340A0000	1/1
Glass door IP40	24	2000	1000	400	PDLG2640	1STQ007342A0000	1/1
Glass door IP40	36	2000	1000	200	PDLG2820	1STQ007343A0000	1/1



Blind door IP65


Pickled sheet steel with gasket. Opens through 135° (single column). Complete with 4 hinges to be screwed onto the uprights, 4 door closing brackets with cover and handle. Handle and hinges provided (not pre-assembled for complete reversibility). Doors can be mounted both on the front and on the back of the enclosures. Reinforcing tubes for W>400mm



Description	No. DIN modules H	Dimensions (mm)		Type	Order code	Pkg/ No. pcs
		W	H			
Blind door IP65 cable compartment						
Blind door IP65 cable compartment -		1800	300	PDLB1836	1STQ007347A0000	1/1
Blind door IP65	12	1800	400	PDLB1846	1STQ007348A0000	1/1
Blind door IP65	24	1800	600	PDLB1866	1STQ007349A0000	1/1
Blind door IP65	36	1800	800	PDLB1886	1STQ007350A0000	1/1
Blind door IP65	48	1800	1000	PDLB1816	1STQ007351A0000	1/1
Blind door IP65 cable compartment -		2000	300	PDLB2036	1STQ007354A0000	1/1
Blind door IP65	12	2000	400	PDLB2046	1STQ007355A0000	1/1
Blind door IP65	24	2000	600	PDLB2066	1STQ007356A0000	1/1
Blind door IP65	36	2000	800	PDLB2086	1STQ007357A0000	1/1
Blind door IP65	48	2000	1000	PDLB2016	1STQ007358A0000	1/1

Structure


Order codes - External covers



Blind door IP40

Pickled sheet steel without gasket and 4 rubber overlapping plugs. Opens through 135° (single column). Complete with 4 hinges to be screwed onto the uprights, 4 door closing brackets with cover and handle. Handle and hinges provided (not pre-assembled for complete reversibility). In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit PKST...and PKDT..., page 2/25. Doors can be mounted both on the front and on the back of the enclosures. Reinforcing tubes for W>400mm

Description	Dimensions (mm)			Type	Order code	Pkg/ No. pcs
	No. DIN modules	H	W			
Blind door IP40 cable compartment -		1800	300	PDLB1830	1STQ007361A0000	1/1
Blind door IP40	12	1800	400	PDLB1840	1STQ007362A0000	1/1
Blind door IP40	24	1800	600	PDLB1860	1STQ007363A0000	1/1
Blind door IP40	36	1800	800	PDLB1880	1STQ007364A0000	1/1
Blind door IP40	48	1800	1000	PDLB1810	1STQ007365A0000	1/1
Blind door IP40 cable compartment -		2000	300	PDLB2030	1STQ007368A0000	1/1
Blind door IP40	12	2000	400	PDLB2040	1STQ007369A0000	1/1
Blind door IP40	24	2000	600	PDLB2060	1STQ007370A0000	1/1
Blind door IP40	36	2000	800	PDLB2080	1STQ007371A0000	1/1
Blind door IP40	48	2000	1000	PDLB2010	1STQ007372A0000	1/1




Double doors IP40 for W=1250mm structures

Doors with overlapping to use with the door with handle to create switchboards with double doors. Handle and hinges provided (not pre-assembled for complete reversibility). Doors can be mounted both on the front and on the back of the enclosures. In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit, page 2/25.

Description	Dimensions (mm)			Type	Order code	Pkg/ No. pcs
	H	W	Type			
Door with overlapping						
Blind door with overlapping IP40	1800	250	PDLB8120	1STQ007366A0000		1/1
Blind door with overlapping IP40	2000	250	PDLB2120	1STQ007373A0000		1/1
Door with handle						
Glass door with handle IP40	1800	1000	PDLG8500	1STQ007335A0000		1/1
Glass door with handle IP40	2000	1000	PDLG2500	1STQ007346A0000		1/1
Blind door with handle IP40	1800	1000	PDLB8500	1STQ007367A0000		1/1
Blind door with handle IP40	2000	1000	PDLB2500	1STQ007374A0000		1/1

Structure


Order codes - External covers



Horizontal/vertical front closing profiles IP30

Profiles for IP30/IP31 pickled sheet painted RAL 7012. In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit PKST...and PKDT..., page 2/25.


Description	Dimensions (mm)			Pkg/ No. pcs
	H	W	Type	
Finishing profiles vertical structure and external cable compartment				
No.2 vertical profiles IP30	1800	PPFV1800	1STQ008059A0000	1/2
No.2 vertical profiles IP30	2000	PPFV2000	1STQ008060A0000	1/2
Finishing profile vertical internal cable compartment				
No.1 profile vertical IP30	1800	PPCV1800	1STQ009294A0000	1/1
No.1 profile vertical IP30	2000	PPCV2000	1STQ009295A0000	1/1
Finishing profiles horizontal structure and external cable compartment				
No.2 horizontal profiles IP30	300	PPFH0300	1STQ008053A0000	1/2
No.2 horizontal profiles IP30	400	PPFH0400	1STQ008054A0000	1/2
No.2 horizontal profiles IP30	600	PPFH0600	1STQ008055A0000	1/2
No.2 horizontal profiles IP30	800	PPFH0800	1STQ008056A0000	1/2
No.2 horizontal profiles IP30	1000	PPFH1000	1STQ008057A0000	1/2
No.2 horizontal profiles IP30	1250	PPFH1250	1STQ008058A0000	1/2



Internal door for internal cable compartment

Internal door in pickled steel sheet for cable compartment IP30.

Description	Dimensions (mm)			Pkg/ No. pcs
	H	D	Type	
Blind door for internal cable compartment	1800	200	PDCB1820	1/1
Blind door for internal cable compartment	1800	400	PDCB1840	1/1
Blind door for internal cable compartment	2000	200	PDCB2020	1/1
Blind door for internal cable compartment	2000	400	PDCB2040	1/1




Internal door for external cable compartment

Internal door in pickled steel sheet for cable compartment IP30.

Description	Dimensions (mm)			Pkg/ No. pcs
	H	D	Type	
Blind door for external cable compartment	1800	200	PDCB1830	1/1
Blind door for external cable compartment	1800	400	PDCB1844	1/1
Blind door for external cable compartment	2000	200	PDCB2030	1/1
Blind door for external cable compartment	2000	400	PDCB2044	1/1

Structure

Order codes - Structure finishing components




Pre-configured plastic cable gland flanges IP65

Allow numerous cables to be installed and guarantee that the components inside the switchboards are protected.

The inserts have a membrane through which the cable can be easily pushed without the need for tools. IP65 protection class is guaranteed over the entire flange regardless of the number of cables installed. Cable clamp, and cable gland with cable clamp can also be installed.

RAL 7035 grey colour; operating temperature from -20 °C to +125 °C, IP65 protection class in accordance with EN 60529 specifications.

Description	Dimensions (mm)			Type	Order code	Pkg/ No. pcs
	W	D				
No.1 pre-configured incoming cable flange for 18 cables (Ø min/max 8/14mm) and 10 cables (Ø min/max 4/10mm)	214	90		EV0114	1STQ006545A0000	1/1
No.1 pre-configured incoming cable flange for 30 cables (Ø min/max 4/10mm), 2 cables (M20 Ø min/max 7/13mm) and 2 cables (M25 Ø min/max 8/17mm)	214	90		EV0116	1STQ006546A0000	1/1



Flanges with adaptable plastic cable gland inserts IP65

Thanks to the frame and inserts available, the flange can be adapted to suit the size, quantity and position of the cables installed. The inserts have a membrane through which the cable can be easily pushed without the need for tools. IP65 protection class is guaranteed over the entire flange regardless of the number of cables installed. Cable clamp, and cable gland with cable clamp can also be installed. RAL 7035 grey colour; operating temperature from -20 °C to +125 °C, IP65 protection class in accordance with EN 60529 specifications.

Description	Dimensions (mm)			Type	Order code	Pkg/ No. pcs
	W	D				
Adaptable modular flanges						
	214	90		EV0117	1STQ006547A0000	1/1
Inserts for adaptable flanges						
No.10 (ten) 68x68mm inserts for 4 incoming cables, 2 cables (M25 Ø min/ max 8/17mm), 2 cables (M16 Ø min/max 5/10mm)	68	68		EV0119	1STQ006548A0000	1/1
No.10 (ten) 68x68mm inserts for 1 incoming cable type M32 / M40 / M50	68	68		EV0121	1STQ006549A0000	1/1
No.10 (ten) 68x68mm inserts for 9 incoming cables (Ø min/max 8/14mm)	68	68		EV0123	1STQ006550A0000	1/1
No.10 (ten) 68x68mm inserts for 4 incoming cables, 2 (Ø min/max 10/20) and 2 (Ø min/max 20/30mm)	68	68		EV0124	1STQ006551A0000	1/1
No.10 (ten) 34x68mm inserts for 2 incoming cables (Ø min/max 8/17mm)	34	68		EV0125	1STQ006552A0000	1/1
No.10 (ten) 34x68mm inserts for 2 incoming cables (Ø min/max 7/13mm)	34	68		EV0126	1STQ006553A0000	1/1
No.10 (ten) 34x68mm inserts for 10 incoming cables (Ø min/max 4/10mm)	34	68		EV0127	1STQ006554A0000	1/1

Structure

Order codes - Structure finishing components



NEW Anti-seismic kit

Anti-seismic is an important thematic which is properly implemented in ABB by testing product solutions that meet the growing security demands and requirements from different markets.

Cabinet without specific accessories


According to standards EC 60068-2-57 - IEEE Std 693	According to Seismic Zone IEC 68-3-3	Magnitude according to Richter scale	Intensity according to Mercalli scale
Resistance capacity up to 0.5 g	Zone 4	7	9

Cabinet with specific accessories PRAS0012 + reinforced base compartment PPUN0100

According to standards IEC 60068-2-57 - IEEE Std 693	According to Seismic Zone IEC 68-3-3	Magnitude according to Richter scale	Intensity according to Mercalli scale
Resistance capacity up to 0.75 g	Zone 4	7.5	10

* The references to the intensity scales are indicative.

Order code for solution >0,75g



After the seismic event in the defined limits and conditions, it is guaranteed:

- No collapse of the structure.
- Operation of the switchboard after the earthquake.
- Maintaining of the mechanical characteristics, IP and IK.

Some suggestions are provided in order to increase the capability of the switchboard to withstand to a seismic event:

- It is better to distribute the weight at the bottom of the switchboard.
- Tighten the structure, by segregating it or by increasing the number of busbar holders.
- Fixing of floor structure with M12 class 8.8 screws.
- Avoid fixing the frame to the wall, possibly keeping a distance of 600mm to avoid the "hammer" effect during the earthquake, if there is no space make sure the wall is structured for fastening.
- Give maintenance instructions, for example after a seismic event of 0.5g check the tightening torques.
- Busways can compromise stability.
- If it is possible, it is better to reduce height dimension of the enclosure.
- Two structures side by side carry more than a single one.
- The lifting bar strengthens the structure. If you have a cable feed, expect an additional length in the cables.

Structure


Order codes - Structure finishing components

NEW Column with 1250mm depth

This enclosure is composed by 900mm structure +350m internal rear cable container.

The column foreseen two breakers with a busbar system between them.

Since the breakers have the incoming on the same position (both up or both down), in a regular structure there is no space for wiring passage, while in the new 1250mm depth column , thanks to the internal cable container on the back, is possible to guarantee the passage and so the perfect functionality of the solution.




Structure

Order codes - Structure finishing components


Structure D=1250mm

Upright formed by a closed profile made of galvanized sheet metal. The uprights include 8 already assembled 3-way joints, 8 already assembled axial screws and 16 loose axial screws. For applications with In ≤ 4000A.

Crosspieces are available in both galvanized sheet for In ≤ 4000A applications and stainless steel for In > 4000A applications.



Description	Dimensions (mm)			Type	Order code	Pkg/ No. pcs
	H	W	D			
Uprights galvanized sheet metal						
No.4 galvanized sheet metal uprights	1800			PUPM1800	1STQ007033A0000	1/4
No.4 galvanized sheet metal uprights	2000			PUPM2000	1STQ007034A0000	1/4
Width crosspieces galvanized sheet metal						
No.4 width crosspieces	300			PCFM0300	1STQ007037A0000	1/4
No.4 width crosspieces	400			PCFM0400	1STQ007038A0000	1/4
No.4 width crosspieces	600			PCFM0600	1STQ007040A0000	1/4
No.4 width crosspieces	800			PCFM0800	1STQ007042A0000	1/4
No.4 width crosspieces	1000			PCFM1000	1STQ007043A0000	1/4
No.4 width crosspieces	1250			PCFM1250	1STQ007044A0000	1/4
Width crosspieces galvanized sheet metal						
	1250	PCFM1250	1STQ007044A0000			1/4
Depth crosspieces stainless steel						
No.4 depth crosspieces	1250	PCFS1250	1STQ007066A0000			1/4



NEW External blind side panel IP41 for D=1250mm


Pickled sheet steel without gasket IP41.

Description	Dimensions (mm)			Type	Order code	Pkg/ No. pcs
	H	D				
Aerated side panel	1800	900			1STQ005569B0000	1/1
Blind side panel					1STQ005570B0000	1/1
Aerated side panel	2000	900			1STQ005571B0000	1/1
Blind side panel					1STQ005572B0000	1/1
Blind side panel	1800	350			1STQ005833B0000	1/1
Blind side panel	2000	350			1STQ005834B0000	1/1

Codes available for sales starting from January 2018

Structure

Order codes - Structure finishing components




NEW Blind Top/Bottom IP30, IP40 for D=1250mm

Pickled sheet steel without gasket. The article comprises one single component that can be used as either a top or bottom. In order to purchase both the top and the bottom, please order two quantities of the same code or two different top/bottom codes according to the desired design of the structure. The code includes four M12x20 screws. In addition it is necessary to add the proper top sealing kit PKST...and PKDT..., page 2-23.

Description	Dimensions (mm)			Order code	Pkg/ No. pcs
	W	D	Type		
Blind Top/Bottom IP30, 40	300	1250		1STQ005579B0000	1/1
Blind Top/Bottom IP30, 40	400	1250		1STQ005580B0000	1/1
Blind Top/Bottom IP30, 40	600	1250		1STQ005581B0000	1/1
Blind Top/Bottom IP30, 40	800	1250		1STQ005582B0000	1/1
Blind Top/Bottom IP30, 40	1000	1250		1STQ005583B0000	1/1
Blind Top/Bottom IP30, 40	1250	1250		1STQ005584B0000	1/1

Codes available for sales starting from January 2018



NEW Internal bottom for D=1250mm


Internal galvanized steel bottom with special brackets kit included.

Description	Dimensions (mm)			Order code	Pkg/ No. pcs
	W	D	Type		
Internal bottom	300	1250		1STQ005590B0000	1/1
Internal bottom	400	1250		1STQ005591B0000	1/1
Internal bottom	600	1250		1STQ005592B0000	1/1
Internal bottom	800	1250		1STQ005593B0000	1/1
Internal bottom	1000	1250		1STQ005594B0000	1/1
Internal bottom	1250	1250		1STQ005595B0000	1/1

Codes available for sales starting from January 2018

Structure

Order codes - Structure finishing components




NEW Open top/bottom IP30/40 for D=1250mm

Pickled sheet steel with holes. The code comprises one single component that can be used as either a top or bottom. In order to purchase both the top and the bottom, please order two quantities of the same code or two different top/bottom codes according to the desired design of the structure.

Description	Dimensions (mm)			Pkg/ No. pcs
	W	D	Type	
Open top/bottom IP30/40	300	1250		1/1
Open top/bottom IP30/40	400	1250		1/1
Open top/bottom IP30/40	600	1250		1/1
Open top/bottom IP30/40	800	1250		1/1
Open top/bottom IP30/40	1000	1250		1/1
Open top/bottom IP30/40	1250	1250		1/1

Codes available for sales starting from January 2018



NEW Fixed incoming cable flange for Depth=350mm


Fixed incoming cable flange in sheet metal to use in conjunction with the open bottom. With internal cable compartment crosspieces it is necessary to mount the fixed flange first.

Description	Dimensions (mm)			Pkg/ No. pcs
	W	D	Type	
Fixed incoming cable flange	300	350		1/1
Fixed incoming cable flange	400	350		1/1
Fixed incoming cable flange	600	350		1/1
Fixed incoming cable flange	800	350		1/1
Fixed incoming cable flange	1000	350		1/1
Fixed incoming cable flange	1250	350		1/1

Codes available for sales starting from January 2018

Structure

Order codes - Structure finishing components



Plastic pocket for documents

Complete with adhesive parts for fixing to the door.

Description	Type	Order code	Pkg/ No. pcs
Plastic pocket for A4 documents	EV1075K	1STQ008199A0000	1/1

PHLS0010



PHLL0020



AD1058



AA6200

AA8004

PIFH0020



AA1570

PITH0064



AA1560

PISH0007



PIEH0008

EV1036

EV1037


Closing systems

Can replace the standard closing systems of the external doors. The inserts are interchangeable and can be easily replaced by loosening just one nut.

Description	Type	Order code	Pkg/ No. pcs
Handle			
Standard lever handle (spare)		1STQ008126A0000	1/1
Padlockable lever handle (spare)		1STQ008128A0000	1/1
Inserts			
Yale insert+key for external door, single door version	AA6200	1STQ009135A0000	1/1
E739 ronis insert+key for external door, single door version	AA8004	1STQ009136A0000	1/1
6.4 triangular male insert on Ø 7.6 for external door, single door version	PITH0064	1STQ008119A0000	1/1
7 square male insert for external door, single door version	PISH0007	1STQ008120A0000	1/1
Box with double tab insert in plastic with key for inner door (Nema TYPE 12)	EV1008	1STQ000956A0000	1/1
One-code Yale insert for inner door	EV1036	1STQ000974A0000	1/1
Insert 8mm hex socket type for standard handle (Key not available)	PIEH0008	1STQ008121A0000	1/1
Ronis 405 insert and key for standard handle	PIRH0405	1STQ008123A0000	1/1
Ronis insert 2432 and key for standard handle	PIRH2432	1STQ002030B0000	1/1
FIAT type insert for lever handle	PIFH0020	1STQ008122A0000	1/1
FIAT key	AA1570	1STQ009137A0000	1/1
Key for triangular insert	AA1560	1STQ009138A0000	1/1
Double tab insert for closing handle/box	PIDH0010	1STQ008118A0000	1/1
Key zama for double tab insert	AD1058	1STQ009134A0000	1/1
Ronis 455 insert for EV1008	EV1037	1STQ000975A0000	1/1
Key			
Ronis 455 insert and key for standard handle	PIRH0455	1STQ008124A0000	
Ronis 1242 insert and key for standard handle	PIRH1242	1STQ008125A0000	
3mm double tab insert for inner door	EV1039	1STQ000976A0000	

Structure


Order codes - Structure finishing components



Kit for joining structures


The kit for joining structures is composed of different brackets and a gasket for the maintenance of the IP protection degree and allows both a side-by-side and a back-to-back joining of structures.

Description	Type	Order code	Pkg/ No. pcs
Kit for joining structures side by side / back to back	PSBS0065	1STQ008113A0000	1/8
Kit for joining corner structures	PSCS0579	1STQ009185A0000	1/12




Brackets for circuit-breaker kit

Description	Type	Order code	Pkg/ No. pcs
Brackets for circuit-breaker kit left and right side	PBKT0002	1STQ002008B0000	1/2



Brackets for intermediate upright

Description	Type	Order code	Pkg/ No. pcs
No.2 brackets for intermediate upright	PKMI0002	1STQ002021B0000	1/2



Eyebolts for lifting

Allow wired switchboards to be lifted. Made of steel treated with a white passivated galvanizing process.

Description	Type	Order code	Pkg/ No. pcs
No.4 steel M12 eyebolts	PEBL0004	1STQ008112A0000	1/4


Lifting reinforcements

Used for handling several adjacent switchboards.

Description	Type	Order code	Pkg/ No. pcs
No.2 lifting reinforcements for adjacent switchboards	PBRL0002	1STQ008116A0000	1/2

Structure

Order codes - Accessories and spare parts



Wall-mounting brackets


Allow the switchboards to be fixed to a wall

Description	Type	Order code	Pkg/ No. pcs
No.2 wall-mounting brackets	PBWF0002	1STQ008115A0000	1/2

PSCP0024



PCSS0024



Screws

Description	Type	Order code	Pkg/ No. pcs
No.1000 self-perforating 4.2x13mm cross-head crews	EV1100	1STQ001005A0000	1/1000
No.1000 self-perforating 4.2x19mm cross-head screws	EV1101	1STQ001006A0000	1/1000
No.24 screws for side/rear panels	PSCP0024	1STQ009182A0000	1/24
No.24 screws 1/4 turn with washers	PCSS0024	1STQ009183A0000	1/24
No.20 M5 Torx screws and nylon washers L=16mm	EV0103	1STQ006608A0000	1/20
No.20 M6 Torx screws and nylon washers L=16mm	EV0104	1STQ006609A0000	1/20



Axial screws for uprights

Axial screws for 3 way joint uprights.

Description	Type	Order code	Pkg/ No. pcs
No.16 axial screws for uprights	PSAF0016	1STQ008110A0000	1/16

Hinges for standard doors

Description	Type	Order code	Pkg/ No. pcs
No.4 hinges for standard door	PHDR0004	1STQ009159A0000	1/4
No.4 180° opening hinges	PHFR4180	1STQ009158A0000	1/4

Chapter 3

Internal kits

General information

- 3–2 Kits for Emax 2 air circuit-breakers**
- 3–2 Kits for Tmax XT and Tmax T moulded-case circuit-breakers**
- 3–3 Kits for System Pro M e modular circuit-breakers XT1 and XT3 moulded-case circuit-breakers**
- 3–3 Kits for OT switch-disconnectors**

Quick selection guides

- 3–4 Recommended installation solutions**
- 3–10 Examples of use**
- 3–12 Quick selection guide**

Order codes

- 2–67 Guide to the order code**
- 2–68 Internal kits**
- 2–97 Accessories and spare parts**

Internal kits

General information

The switchboards can be assembled very quickly even when extremely complex apparatus is involved thanks to the innovative internal kits designed for System pro E power.

—
01 Quick click-in fixing system with $\frac{1}{4}$ turn screws.

—
02 Kits for Emax 2 air circuit-breakers


They match perfectly with the new uprights and crosspieces with double fixing levels and are available for air and moulded-case circuit-breakers, switch-disconnectors, modular circuit-breakers and internal segregation partitions.

The main advantages are:

- Quick click-in fixing system with $\frac{1}{4}$ turn screws
- Common kits for 3- and 4-pole moulded-case circuit-breakers installed horizontally
- Same front panels for fixed and swing frames, and for screwed and hinged solutions
- Two front panel height sizes available (150 and 200mm) for DIN rail kits.

Simple, effective systems for fixing the kits save time when the switchboards are assembled.

—
01



Kits for Emax 2 air circuit-breakers

Available for all sizes from E1.2 to E6.2 in fixed and withdrawable versions. Sturdy and simple, they meet the requirements of all applications, from 630 to 6300A.

—
02



Kits for Tmax XT and Tmax T moulded-case circuit-breakers

Available for XT1 to XT4 and T4 to T7 circuit-breakers. The major innovations include the common kit for 3- and 4-pole circuit-breakers installed horizontally and the 150mm height panel, which allows more circuit-breakers to be installed in the same unit than the 200mm panel solution.



—
03 Kits for System Pro M, Tmax XT and Tmax T moulded-case circuit-breakers

—
04 Plate for Tmax XT and Tmax T moulded-case circuit-breakers.
Holes with shaped openings for rear connections for 3P circuit-breakers; pre-cut holes included for 4P. Holes for front terminals, with flexible insulated connections that proceed behind the plate for fixed circuit-breakers (for W=400mm only Tmax XT1 and XT2); all terminal covers for segregated versions are required.
Holes for front terminals with connections routed from the side; these can be anchored by fixing the dedicated accessory to the round holes (allowing flexible busbars to be fastened). The clamps can be threaded through the rectangular holes..

Kits for System Pro M and XT1 and XT2 moulded-case circuit-breakers

Available for all modular circuit-breakers and for XT1 and XT2 moulded-case circuit-breakers.


The DIN rail provides two pre-engineered assembly positions, corresponding to the depth of System pro M and Tmax XT circuit-breakers, respectively. The 150mm height panel also allows more circuit-breakers to be installed in the same

—
03



unit than the 200mm panel solution. same unit than the 200mm panel solution.

—
04



Kits for OT switch-disconnectors

Available for OT up to 1600 A both in the vertical and horizontal versions.

For more information about ABB apparatus, go to the following link: <http://new.abb.com/low-voltage/products/circuit-breakers>.

Internal kits

Quick selection guides

Recommended installation solutions

		Type of structure/installation				
		Form 1, Form 2b switchboard		D=300mm		D=500mm
		HORIZ.	VERT.	HORIZ.	VERT.	HORIZ.
Modular and Tmax moulded-case circuit-breakers	System pro-M					
Tmax XT1	front terminals with side exit	fixed	✓	✓	✓	✓
		plug-in		✓	✓	✓
		fixed+diff	✓	✓	✓	✓
	rear/front terminals with rear exit	fixed	✓	✓	✓	✓
		plug-in		✓	✓	✓
Tmax XT2	front terminals with side exit	fixed	✓	✓	✓	✓
		plug-in		✓	✓	✓
		withdrawable		✓	✓	✓
		withdrawable+ diff		✓	✓	✓
	rear/front terminals with rear exit	fixed+diff	✓	✓	✓	✓
		fixed	✓	✓	✓	✓
		plug-in		✓	✓	✓
		withdrawable		✓	✓	✓
		withdrawable+ diff		✓	✓	✓
Tmax XT3	front terminals with side exit	fixed	✓	✓	✓	✓
		plug-in		✓	✓	✓
		fixed+diff	✓	✓	✓	✓
	rear/front terminals with rear exit	fixed		✓	✓	✓
		plug-in		✓	✓	✓
Tmax XT4	front terminals with side exit	fixed	✓	✓	✓	✓
		plug-in		✓	✓	✓
		withdrawable		✓	✓	✓
		withdrawable+ diff		✓	✓	✓
	rear/front terminals with rear exit	fixed+diff	✓	✓	✓	✓
		fixed	✓	✓	✓	✓
		plug-in		✓	✓	✓
		withdrawable		✓	✓	✓
		withdrawable+ diff		✓	✓	✓
Tmax T4	front terminals with side exit	fixed	✓	✓	✓	✓
		fixed+diff	✓	✓	✓	✓
	rear/front terminals with rear exit	fixed		✓	✓	✓
		fixed+diff		✓	✓	✓
Tmax T5	front terminals with side exit	fixed	✓	✓	✓	✓
		plug-in		✓	✓	✓
		plug-in+diff		✓	✓	✓
		withdrawable		✓	✓	✓
	rear/front terminals with rear exit	fixed+diff	✓	✓	✓	✓
		fixed		✓	✓	✓
		plug-in		✓	✓	✓
		plug-in+diff		✓	✓	✓
		withdrawable		✓	✓	✓
		fixed+diff		✓	✓	✓
Tmax T6	front terminals with side exit	fixed	✓	✓	✓	✓
	rear/front terminals with rear exit ⁽¹⁾	withdrawable		✓	✓	✓
		fixed	✓	✓	✓	✓
		withdrawable		✓	✓	✓
Tmax T7	front terminals with side exit	fixed		✓	✓	✓
	rear/front terminals with rear exit	withdrawable		✓		✓
		fixed		✓		✓
		withdrawable				

⁽¹⁾ Front terminals with rear exit, only Form 1. ⁽²⁾ Only Form 1.

Internal kits

Quick selection guides

Recommended installation solutions

			Type of structure/installation			
			Form 1, Form 2b switchboard			
			D=300mm		D=500mm	
		HORIZ.	VERT.	HORIZ.	VERT.	
Emax air circuit-breakers						
Emax E1.2	front and rear terminals	fixed	✓	✓	✓	✓
	rear terminals	withdrawable			✓	✓
Emax E2.2	rear terminals	fixed				✓
		withdrawable				
Emax E4.2	rear terminals	fixed				
		withdrawable				
Emax E6.2	rear terminals	fixed				
		withdrawable				

(¹) For busbar systems from 3200A. (²) The busbar systems cannot be placed behind the breakers.

Recommended installation solutions for accessorized apparatus

			Type of structure/installation			
			Form 1, Form 2b switchboard			
			D=300mm		D=500mm	
		HORIZ.	VERT.	HORIZ.	VERT.	
Tmax moulded-case circuit-breakers with Direct Rotary Handle operating mechanism or motor operator						
Tmax T4	front terminals with side exit	fixed	✓	✓	✓	✓
	rear/front terminals with rear exit	fixed	✓	✓	✓	✓
Tmax T5	front terminals with side exit	fixed	✓	✓	✓	✓
		plug-in	✓	✓	✓	✓
		withdrawable	✓	✓	✓	✓
	rear/front terminals with rear exit	fixed	✓	✓	✓	✓
		plug-in	✓	✓	✓	✓
		withdrawable	✓	✓	✓	✓
Tmax T6	front terminals with side exit	fixed	✓	✓	✓	✓
		withdrawable (²)	✓	✓	✓	✓
	rear/front terminals with rear exit (¹)	fixed	✓	✓	✓	✓
		withdrawable	✓	✓	✓	✓
Tmax T7	front terminals with side exit	fixed	✓	✓	✓	✓
		withdrawable				
	rear/front terminals with rear exit	fixed	✓	✓	✓	✓
Tmax XT1	front terminals with side exit	fixed	✓	✓	✓	✓
		plug-in	✓	✓	✓	✓
	rear/front terminals with rear exit	fixed	✓	✓	✓	✓
Tmax XT2	front terminals with side exit	fixed	✓	✓	✓	✓
		plug-in	✓	✓	✓	✓
	rear/front terminals with rear exit	fixed	✓	✓	✓	✓
Tmax XT3	front terminals with side exit	fixed	✓	✓	✓	✓
		plug-in	✓	✓	✓	✓
	rear/front terminals with rear exit	fixed	✓	✓	✓	✓
Tmax XT4	front terminals with side exit	fixed	✓	✓	✓	✓
		plug-in	✓	✓	✓	✓
	rear/front terminals with rear exit	fixed	✓	✓	✓	✓
		plug-in	✓	✓	✓	✓
		withdrawable	✓	✓	✓	✓

(¹) Front terminals with rear exit, only Form 1. (²) Only Form 1.

				Type of structure/installation							
				Form 2a-3a, Form 3b, Form 4b switchboard							
D=700mm		D=900mm		D=500mm		D=700mm		D=900mm			
HORIZ.	VERT.	HORIZ.	VERT.	HORIZ.	VERT.	HORIZ.	VERT.	HORIZ.	VERT.	HORIZ.	VERT.
✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
✓	✓	✓	✓		✓	✓	✓	✓	✓	✓	✓
	✓		✓		✓			✓			✓
	✓				✓ ⁽²⁾			✓			✓
			✓						✓		✓
									✓		✓
✓ ⁽¹⁾			✓					✓ ⁽¹⁾			✓
✓ ⁽¹⁾			✓					✓ ⁽¹⁾			✓
			✓								✓
				✓							✓

Internal kits

Quick selection guides

Recommended installation solutions for accessorized apparatus

			Type of structure/installation			
			Form 1, Form 2b switchboard			
			D=300mm		D=500mm	
			HORIZ.	VERT.	HORIZ.	VERT.
Switch disconnectors with rotating handle deferred						
OT-OTEV	OT200-OT250-OTEV160	fisso	✓	✓	✓	✓
	OT315-OT400	fisso	✓	✓	✓	✓
	OT630-OT800	fisso	✓	✓	✓	✓
	OT1000-OT1250-OT1600	fisso		✓	✓	✓
Tmax interlocked, interlocked motor-operated moulded-case circuit-breakers						
Tmax T4	front terminals with side exit	fixed	✓		✓	
	rear/front terminals with rear exit	fixed	✓		✓	
Tmax T5	front terminals with side exit	fixed	✓		✓	
		plug-in	✓		✓	
		withdrawable	✓		✓	
	rear/front terminals with rear exit	fixed	✓		✓	
		plug-in	✓		✓	
		withdrawable	✓		✓	
Tmax T6	front terminals with side exit	fixed	✓		✓	
	rear/front terminals with rear exit ⁽¹⁾	fixed	✓		✓	
		withdrawable				
Tmax T7	front terminals with side exit	fixed				
	rear/front terminals with rear exit	fixed			✓	✓
		withdrawable				
Tmax XT1	front terminals with side exit	fixed	✓		✓	
	front terminals with side exit	plug-in	✓		✓	
		fixed	✓		✓	
Tmax XT2	front terminals with side exit	fixed	✓		✓	
		plug-in	✓		✓	
		withdrawable	✓		✓	
	rear/front terminals with rear exit	fixed	✓		✓	
		plug-in	✓		✓	
		withdrawable	✓		✓	
Tmax XT3	front terminals with side exit	fixed	✓		✓	
	rear/front terminals with rear exit	fixed	✓		✓	
		plug-in	✓		✓	
Tmax XT4	front terminals with side exit	fixed	✓		✓	
		plug-in	✓		✓	
		withdrawable	✓		✓	
	rear/front terminals with rear exit	fixed	✓		✓	
		plug-in	✓		✓	
		withdrawable	✓		✓	
Emax air circuit-breakers						
Emax E1.2	front and rear terminals	fixed	✓	✓	✓	✓
	rear terminals	withdrawable			✓	✓
Emax E2.2	rear terminals	fixed				
		withdrawable				
Emax E4.2	rear terminals	fixed				
		withdrawable				
Emax E6.2	rear terminals	fixed				
		withdrawable				

⁽¹⁾ Front terminals with rear exit, only Form 1. ⁽²⁾ Only Form 1.


⁽³⁾ For busbar systems from 3200A. ⁽⁴⁾ The busbar systems cannot be placed behind the breakers.

Internal kits


Examples of use

- 01 Segregation Form 1
- 02 Segregation Form 2a - 3a
- 03 Segregation Form 2b
- 04 segregation Form 3b vertical bars
- 05 segregation Form 4b vertical bars
- 06 segregation Form 3b horizontal bars
- 07 segregation Form 4b horizontal bars
- 08 segregation Form 3b horizontal and vertical bars
- 09 segregation Form 4b horizontal and vertical bars


01




02








03



04



—
05—
06—
07—
08—
09

Internal kits

Quick selection guides

Tmax XT1

HORIZONTAL INSTALLATION

W=400mm				W=600mm					
Cell height (mm)	No. of poles	Execution	No. of breakers per cell	Segregation form			Segregation form		
				F 2a - 3a*	F 3b	F 4b			
Front/Rear terminals									
150	3/4 F	1	PHBX1401	PPVS200	PSHS1904		PHCX1401		
	3/4 F - RHD	1	PHBX1405	2xPPRS0150			PHCX1405		
200	3/4 F	1	PHBX1101	PPVS200	PSVS2050	PCVS0204	PCVS1204	PCVS2204	PHCX1101
	3/4 F - MO	1	PHBX1404		PSVS2070	PCVS1204	PCVS2204	PHCX1404	
	3 F - RC	1	PHBX1323		PSVS2090	PCVS1204	PCVS2204	PHCX1323	
	4 F - RC	1	PHBX1423		PRVS2041	PLBS2052	PCVS1204	PCVS2204	PHCX1423
	3/4 F - RHD	1	PHBX1105			PLBS2072	PCVS1204	PCVS2204	PHCX1105
	3/4 P	1	PHBX1407			PLBS2092	PCVS1204	PCVS2204	PHCX1407
	3/4 P - RHD	1	PHBX1427			PCVS0204	PCVS1204	PCVS2204	PHCX1427
	3/4 P - MO ⁽¹⁾	1	PHBX1409				PCVS2204	PCVS2204	PHCX1409
500	3/4 F - I	2	PHBX1422	PPVS2500	PSVS2051	PCVS0204	PCVS1204	PCVS2204	PHCX1422
	3/4 F - I - MO ⁽¹⁾	2	PHBX1424		PSVS2071	PCVS1204	PCVS2204	PHCX1424	
	3/4 P - I	2	PHBX1422		PSVS2091	PCVS1204	PCVS2204	PHCX1422	
	3/4 P - I - MO ⁽¹⁾	2	PHBX1424				PCVS2204	PCVS2204	PHCX1424

VERTICAL INSTALLATION

W=400mm				W=600mm			
Cell height (mm)	No. of poles	Execution	No. of breakers per cell	Segregation form			Segregation form
				F 2a - 3a*	F 3b (for form 4b order the double of the vertical rear and side segregations)	Vertical rear segregation	
Front/Rear terminals							
300	3/4 F	1	PVBX1401	PPVS2300	PSHS1904	PSHS4050	Segregation form
	3/4 F - MO	1	PVBX1404		PSHS4070	PSHS4090	F 2a - 3a*
	4 F - RC	1	PVBX1423		PSHS4050	PRVS1582	F 3b
	3/4 F - RHD	1	PVBX1405			PRVS1541	(for form 4b order the double of the vertical rear and side segregations)
	3/4 P	1	PVBX1407				
	3/4 P - RHD	1	PVBX1427				
	3/4 P - MO ⁽¹⁾	1	PVBX1409				
	3/4 P	3	-				
	3 P F	4	-				
	3/4 P	4	-				

⁽¹⁾ kit with recessed mounting plate

* Mandatory everytime that the breaker kits have plates distant more than 38mm or for segregations form 4b

PLVS2052												
PLVS2072												
PLVS2092	PCVS0206	PCVS0206	PCVS1206	PCVS2206	PHDX1401	-		2xPPRS0150	PSHS1908			
	PCVS0206		PCVS1206	PCVS2206	PHDX1404				PSHS1908			
	PCVS0206	PCVS0206	PCVS1206	PCVS2206	-				PSVS2050			
	PCVS0206	PCVS0206	PCVS1206	PCVS2206	PHDX1423				PSVS2070			
	PCVS0206		PCVS1206	PCVS2206	PHDX1105				PSVS2090			
		PCVS0206	PCVS1206	PCVS2206	PHDX1407				PRVS2081			
			PCVS1206	PCVS2206	PHDX1427				PLVS2052			
				PCVS2206	PHDX1409				PLVS2072			
					PHDX1402				PLVS2092			
					PHDX1403					PCVS0208	PCVS0208	PCVS1208
					PHDX1422					PCVS0208	PCVS1208	PCVS2208
					PHDX1424					PCVS0208	PCVS1208	PCVS2208
					PPVS2500					PCVS0208	PCVS1208	PCVS2208
					PSHS1908					PCVS0208	PCVS1208	PCVS2208
					PSVS2051					PCVS0208	PCVS1208	PCVS2208
					PSVS2071					PCVS0208	PCVS1208	PCVS2208
					PSVS2091					PCVS0208	PCVS1208	PCVS2208

Key:

Key:

F - I fixed interlocked

F - I-MO fixed interlocked motor-operated

F - MO fixed motor-operated

F - RC fixed with residual current

F - RHD fixed with Direct Rotary Handle

F & F - I fixed and fixed interlocked

P & P - I Fixed a
P plug-in

P - I plug-in interlocked

P - I-MO plug-in interlocked motor-operated

P - MO plug-in motor-operated

P - RC plug-in with residual current

P - RHD plug-in with Direct Rotary Handle

W withdrawable

W - I with

W - I-MO withdrawable inter

W - MO withdrawable motor-operated

W - RC withdrawable with residual current

W - RHD withdrawable with Direct Rotary Hammer

W & W - I withdrawable and withdrawable inter

Internal kits

Quick selection guides

Tmax XT2

HORIZONTAL INSTALLATION

				W=400mm			W=600mm		
				Segregation form			Segregation form		
				F 2a - 3a*	F 3b		F 4b		F 2a - 3a*
Cell height (mm)				Universal horizontal shelf			Universal horizontal shelf		
No. of poles				Terminals separator			Terminals separator		
Execution				D (mm)			D (mm)		
				500	700	900	500	700	900
Front/Rear terminals				Rear segregation bars side			Rear segregation bars side		
150 3 F 1 PHBX2301				Side rear segregation			Side rear segregation		
				D (mm)			D (mm)		
				500	700	900	500	700	900
				Mounting position			Mounting position		
				P0/P1	P0	P1	P0	P1	P2
				breaker terminals			breaker terminals		
				Front	Rear		Front	Rear	
				Base kit (segregation form 1)			Base kit (segregation form 1)		
150 3 F 1 PHBX2301				PPVS0150			PPVS0150		
200 3/4 F 1 PHBX2401				PSHS1904			PSHS1906		
3/4 F-MO 1 PHBX2404				PSVS2050			PSVS2050		
4 F-RC 1 PHBX2423				PSVS2070			PSVS2070		
3/4 F-RHD 1 PHBX2405				PSVS2090			PSVS2090		
3/4 P 1 PHBX2407				PRVS2041			PRVS2041		
3/4 P-RHD 1 PHBX2427				PLVS2052			PLVS2052		
3/4 P-MO ⁽¹⁾ 1 PHBX2409				PLVS2072			PLVS2072		
3 W 1 PHBX2310				PLVS2092			PLVS2092		
3 W-RHD 1 PHBX2300				PCVS0206			PCVS0206		
3 W-MO ⁽¹⁾ 1 PHBX2312				PCVS0206			PCVS0206		
250 4 P-RC 1 PHBX2428				PCVS0206			PCVS0206		
3/4 W 1 PHBX2410				PCVS1204			PCVS1204		
4 W-RC 1 -				PCVS2204			PCVS2204		
3/4 W-RHD 1 PHBX2400				PHCX2401			PHCX2401		
3/4 W-MO ⁽¹⁾ 1 PHBX2412				PHCX2404			PHCX2404		
500 3/4 F-I 2 PHBX2402				PCVS2204			PCVS2204		
3/4 F-I-MO ⁽¹⁾ 2 PHBX2424				PHCX2404			PHCX2404		
3/4 P-I ⁽¹⁾ 2 PHBX2431				PCVS2204			PHCX2431		
3/4 P-I-MO ⁽¹⁾ 2 PHBX2424				PHCX2404			PHCX2404		
3/4 W-I ⁽¹⁾ 2 PHBX2425				PHCX2404			PHCX2404		
3/4 W-I-MO ⁽¹⁾ 2 PHBX2425				PHCX2404			PHCX2404		

⁽¹⁾ kit with recessed mounting plate

* Mandatory everytime that the breaker kits have plates distant more than 38mm or for segregations form 4b

W=800											
F 4b				Segregation form				F 4b			
Rear cubicle				F 2a - 3a*		F 3b		Rear cubicle			
Mounting position				Base kit (segregation form 1)		Cell side closing		Mounting position			
P0/P1	P0	P1	P2	Universal horizontal shelf		Terminals separator		P0/P1	P0	P1	P2
D (mm)	breaker terminals				D (mm)	D (mm)	D (mm)	breaker terminals			
500	700	900	Front	Rear	500	700	900	500	700	900	Front
PLVS2052	PCVS0206	PCVS0206	PCVS1206	PCVS2206	PHDX2401	PPVS2200	PSHS1908	PCVS0208	PCVS0208	PCVS1208	PCVS2208
PLVS2072	PCVS0206	PCVS1206	PCVS2206	PHDX2404		PSVS2050		PCVS0208	PCVS1208	PCVS2208	
PLVS2092	PCVS0206	PCVS0206	PCVS1206	PCVS2206	PHDX2423	PSVS2070	PSVS2090	PCVS0208	PCVS1208	PCVS2208	
	PCVS0206		PCVS1206	PCVS2206	PHDX2405	PRVS2081		PCVS0208	PCVS1208	PCVS2208	
			PCVS1206	PCVS2206	PHDX2407	PLVS2052		PCVS0208	PCVS1208	PCVS2208	
			PCVS1206	PCVS2206	PHDX2427	PLVS2072		PCVS0208	PCVS1208	PCVS2208	
			PCVS1206	PCVS2206	PHDX2409	PLVS2092		PCVS1208	PCVS2208	PCVS2208	
				PCVS1206	PCVS2206	-					
				PCVS1206	PCVS2206	-					
				PCVS2206	-						
PLVS2552	PCVS1256	PCVS2256	PHDX2428	PPVS2250	PSHS1908	PSVS2551	PSVS2550	PCVS1258	PCVS2258		
PLVS2572	PCVS1256	PCVS2256	PHDX2410			PSVS2571	PSVS2570	PSVS2571	PCVS1258	PCVS2258	
PLVS2592	PCVS1256	PCVS2256	PHDX2417			PSVS2591	PSVS2590	PSVS2591	PCVS1258	PCVS2258	
	PCVS1256	PCVS2256	PHDX2400	PRVS2581		PLVS2552		PLVS2552	PCVS1258	PCVS2258	
		PCVS2256	PHDX2412			PLVS2572		PLVS2572	PCVS1258	PCVS2258	
				PPVS2500	PSHS1908	PSVS2551	PSVS2550	PSVS2551	PCVS1258	PCVS2258	
						PSVS2571	PSVS2570	PSVS2571	PCVS1258	PCVS2258	
						PSVS2591	PSVS2590	PSVS2591	PCVS1258	PCVS2258	
						PLVS2552		PLVS2552	PCVS1258	PCVS2258	
						PLVS2572		PLVS2572	PCVS1258	PCVS2258	
						PLVS2592		PLVS2592	PCVS1258	PCVS2258	
						PHDX2402					
						PHDX2403					
						PHDX2432					
						-					
						PHDX2425					

Key:

F fixed
F - I fixed interlocked
F - I-MO fixed interlocked motor-operated
F - MO fixed motor-operated
F - RC fixed with residual current
F - RHD fixed with Direct Rotary Handle

F & F - I fixed and fixed interlocked
P plug-in
P - I plug-in interlocked
P - I-MO plug-in interlocked motor-operated
P - MO plug-in motor-operated
P - RC plug-in with residual current
P - RHD plug-in with Direct Rotary Handle

W withdrawable
W - I withdrawable interlocked
W - I-MO withdrawable interlocked motor-operated
W - MO withdrawable motor-operated
W - RC withdrawable with residual current
W - RHD withdrawable with Direct Rotary Handle
W & W - I withdrawable and withdrawable interlocked

Internal kits

Quick selection guides

Tmax XT2

VERTICAL INSTALLATION

Cell height (mm)	No. of poles	Execution	No. of breakers per cell	Base kit (segregation form 1)	W=400mm			W=600mm			Segregation form F 2a - 3a*	Universal horizontal shelf				
					Segregation form			Vertical rear segregation								
					F 2a - 3a*		F 3b (for form 4b order the double of the vertical rear and side segregations)			Without upright		With upright		D (mm)		
Front/Rear terminals																
300	3/4	F	3	-	PPVS2300	PSHS1904	PSHS4050	PRVS1532	PRVS1541	PLVS1552	PLVS1572	PLVS1592	PVCX2701	PPVS2300	PSHS1906	
	3/4	F	4	-			PSHS4050						-	PPVS2300	PSHS1906	
	3/4	F	1	PVBX2401			PSHS4070						PVCX2401			
	3/4	F - RHD	1	PVBX2405			PSHS4090						PVCX2405			
	3/4	F - MO	1	PVBX2404			PRVS1582						PVCX2404			
	3/4	P	3	-									PVCX2707			
	3/4	P	4	-									PVCX2407			
	3/4	P	1	PVBX2407									PVCX2427			
	3/4	P - RHD	1	PVBX2427									PVCX2409			
	3/4	P - MO ⁽¹⁾	1	PVBX2409									PVCX2410			
350	3/4	W	1	PVBX2410									PVCX2400			
	3/4	W - RHD	1	PVBX2400									PVCX2412			
	3/4	W - MO ⁽¹⁾	1	PVBX2412									PVCX2423			
	4	F - RC	1	PVBX2423	PPVS2350	PSHS1904	PSHS4050	PRVS1740	PRVS1741	PLVS1552	PLVS1572	PLVS1592	PVCX2417	PPVS2350	PSHS1906	
	4	W - RC	1	PVBX2417			PSHS4070						PVCX2412			

⁽¹⁾ kit with recessed mounting plate

* Mandatory everytime that the breaker kits have plates distant more than 38mm or for segregations form 4b

W=800mm											
Segregation form											
F 2a - 3a*											
F 3b (for form 4b order the double of the vertical rear and side segregations)											
Vertical rear segregation											
Vertical side segregation											
With upright											
Without upright											
D (mm)											
500	700	900									
Terminals separator											
PSHS6050	PSHS6050	PSHS6050	PRVS1560	PRVS1561	PRVS1562	PLVS1552	PLVS1572	PLVS1592	PVDX2801	PPVS2300	PSHS1908
PSHS6070	PSHS6070	PSHS6070	PRVS1560	PRVS1561	PRVS1562	PLVS1552	PLVS1572	PLVS1592	-	-	-
PSHS6090	PSHS6090	PSHS6090	PRVS1560	PRVS1561	PRVS1562	PLVS1552	PLVS1572	PLVS1592	PVDX2807	PPVS2300	PSHS1908
PRVS1760	PRVS1761	PRVS1762	PLVS1752	PLVS1752	PLVS1752	-	-	-	-	-	-
PRVS1760	PRVS1761	PRVS1762	PLVS1752	PLVS1752	PLVS1752	-	-	-	-	-	-
PRVS1761	PRVS1762	PLVS1752	PLVS1752	PLVS1752	PLVS1752	-	-	-	-	-	-
PLVS1752	PLVS1772	PLVS1792	PLVS1792	PLVS1792	PLVS1792	-	-	-	-	-	-
PLVS1772	PLVS1792	-	-	-	-	-	-	-	-	-	-
PLVS1792	-	-	-	-	-	-	-	-	-	-	-

Key:

F fixed
 F - I fixed interlocked
 F - I-MO fixed interlocked motor-operated
 F - MO fixed motor-operated
 F - RC fixed with residual current
 F - RHD fixed with Direct Rotary Handle

F & F - I fixed and fixed interlocked
 P plug-in
 P - I plug-in interlocked
 P - I-MO plug-in interlocked motor-operated
 P - MO plug-in motor-operated
 P - RC plug-in with residual current
 P - RHD plug-in with Direct Rotary Handle

W withdrawable
 W - I withdrawable interlocked
 W - I-MO withdrawable interlocked motor-operated
 W - MO withdrawable motor-operated
 W - RC withdrawable with residual current
 W - RHD withdrawable with Direct Rotary Handle
 W & W - I withdrawable and withdrawable interlocked

Internal kits

Quick selection guides

Tmax XT3

HORIZONTAL INSTALLATION

W=400mm										W=600mm																			
Segregation form					F 2a - 3a*					F 3b					Segregation form														
Cell height (mm)		No. of poles		Execution		No. of breakers per cell		Base kit (segregation form1)		Cell side closing		Universal horizontal shelf		F 4b		Rear cubicle		Mounting position											
												Terminals separator		P0/P1		P0		P1		P2									
								D (mm)		500 700 900		Rear segregation bars side		D (mm)		500 700 900		Front		Rear									
Front/Rear terminals																													
150	3	F	1	PHBX3301 ⁽²⁾																									
	3	F - RHD	1	PHBX3305						2xPPRS0150																			
200	3/4	F	1	PHBX3401 ⁽²⁾						PPVS2200																			
	3/4	F - MO	1	PHBX3404						PSHS1904																			
	4	F - RC	1	-						PSVS2550																			
	3/4	F - RHD	1	PHBX3405						PSVS2570																			
	3/4	P	1	PHBX3407						PSVS2590																			
	3/4	P - RHD	1	PHBX3427						PRVS2541																			
	3/4	P - MO ⁽¹⁾	1	PHBX3409						PLVS2552																			
250	4	F - RC	1	PHBX3423 ⁽²⁾						PPVS2250																			
					PSHS1904					PSVS2500																			
500	3/4	F - I	2	PHBX3422						PPVS2300																			
	3/4	F - I - MO ⁽¹⁾	2	PHBX3424						PSHS1906																			
	3/4	P - I	2	PHBX3422						PSVS2550																			
	3/4	P - I - MO ⁽¹⁾	2	PHBX3424						PSVS2570																			
					PPVS2250					PSHS1906																			
					PSVS2590					PSVS2091																			
					PRVS2561																								

⁽¹⁾ kit with recessed mounting plate

* Mandatory everytime that the breaker kits have plates distant more than 38mm or for segregations form 4b

W=800											
F 4b				Segregation form				F 4b			
Rear cubicle				F 2a - 3a*		F 3b		Rear cubicle			
Mounting position				Base kit (segregation form 1)				Mounting position			
P0/P1	P0	P1	P2	F 2a - 3a*	F 3b	Cell side closing	Universal horizontal shelf	P0/P1	P0	P1	P2
D (mm)	breaker terminals			Terminals separator	D (mm)	500 700 900	Rear segregation bars side	Side rear segregation	D (mm)	500 700 900	breaker terminals
500 700 900	Front	Rear							Front	Rear	
PLVS052	PLVS2072	PLVS2092	PCVS0206	PCVS0206	PCVS1206	PCVS2206	PHDX3401	PPVS2200	PSHS1908	PSVS2050	PSVS2070
			PCVS0206		PCVS1206	PCVS2206	PHDX3404			PSVS2090	PRVS2081
							PHDX3423				PLVS052
			PCVS0206		PCVS1206	PCVS2206	PHDX3405			PLVS2072	PLVS2092
					PCVS1206	PCVS2206	PHDX3407				PCVS0208
					PCVS1206	PCVS2206	PHDX3427				PCVS0208
						PCVS2206	PHDX3409				PCVS1208
PLVS2552	PLVS2572	PLVS2592	PCVS0256	PCVS0256	PCVS1256	PCVS2256	-		PSVS2051	PSVS2071	PSVS2091
							PHDX3402	PPVS2500	PSHS1908		
							PHDX3403				
							-				

Key:

F fixed
F - I fixed interlocked
F - I-MO fixed interlocked motor-operated
F - MO fixed motor-operated
F - RC fixed with residual current
F - RHD fixed with Direct Rotary Handle

F & F - I fixed and fixed interlocked
P plug-in
P - I plug-in interlocked
P - I-MO plug-in interlocked motor-operated
P - MO plug-in motor-operated
P - RC plug-in with residual current
P - RHD plug-in with Direct Rotary Handle

W withdrawable
W - I withdrawable interlocked
W - I-MO withdrawable interlocked motor-operated
W - MO withdrawable motor-operated
W - RC withdrawable with residual current
W - RHD withdrawable with Direct Rotary Handle
W & W - I withdrawable and withdrawable interlocked

Internal kits

Quick selection guides

Tmax XT3

VERTICAL INSTALLATION

Cell height (mm)	No. of poles	Execution	No. of breakers per cell	Base kit (segregation form 1)	W=400mm			W=600mm			Segregation form	F 2a - 3a*		
					Segregation form			Vertical rear segregation						
					F 2a - 3a* (for form 4b order the double of the vertical rear and side segregations)			With upright			Vertical side segregation			
Front/Rear terminals														
300	3/4	F	1	PVBX3401	PPVS2300	PSHS1904		Terminals separator	D (mm)	Without upright	Bars side	Exits side	D (mm)	Base kit (segregation form 1)
	3/4	F - RHD	1	PVBX3405		PSHS4050			500 700 900				500 700 900	F 2a - 3a*
	3/4	F - MO	1	PVBX3404		PSHS4070								Segregation form
	3/4	P	1	PVBX3407		PSHS4090								Universal horizontal shelf
	3/4	P	2	-		PRVS1582								
	3/4	P	3	-		PRVS1541								
	3	P	3	-										
	4	P	4	-										
	3/4	P - RHD	1	PVBX3427										
	3/4	P - MO ⁽¹⁾	1	PVBX3409										
400	4	F - RC	1	PVBX3423	PPVS2400	PSHS1904								PSHS1906

⁽¹⁾ kit with recessed mounting plate

⁽²⁾ Not compatible with high terminal covers. Front only in form 1

* Mandatory everytime that the breaker kits have plates distant more than 38mm or for segregations form 4b

Internal kits

Quick selection guides

Tmax XT4

HORIZONTAL INSTALLATION

Cell height (mm)	No. of poles	Execution	No. of breakers per cell	Base kit (segregation form 1)	W=400mm			W=600mm			Base kit (segregation form 1)	Segregation form						
					Segregation form			F 4b				Segregation form						
F 2a - 3a*			F 3b			Rear cubicle			F 2a - 3a*			F 3b						
Front/Rear terminals																		
150	3	F	1	PHBX4301 ⁽²⁾	2xPPRS0150	PSHS1904	PSHS1905	PSVS2200	PSVS2200	PSHS1906	PSHS1906	PSHS1904	PSHS1905	PSHS1906				
200	3/4	F	1	PHBX4401 ⁽²⁾	PPVS2200	PSHS1904	PSVS2050	PSVS2051	PSVS2050	PSHS1906	PSHS1906	PPVS2200	PPVS2200	PSHS1906				
	3/4	F - MO	1	PHBX4404			PSVS2070	PSVS2071	PSVS2070	PSVS2070	PSVS2071							
	4	F - RC	1	PHBX4423 ⁽²⁾			PSVS2090	PSVS2091	PSVS2090	PSVS2090	PSVS2091							
	3/4	F - RHD	1	PHBX4405			PRVS2041											
	3/4	P	1	PHBX4407			PLVS2052											
	3/4	P - RHD	1	PHBX4427			PLVS2072											
	3/4	P - MO ⁽¹⁾	1	PHBX4409			PLVS2092											
250	4	P - RC	1	PHBX4428	PPVS2250	PSHS1904	PSVS2550	PSVS2551	PSVS2550	PSHS1906	PSHS1906	PPVS2250	PPVS2250	PSHS1906				
	3/4	W	1	PHBX4410			PSVS2571	PSVS2570	PSVS2570	PSVS2570	PSVS2571							
	4	W - RC	1				PSVS2590	PSVS2591	PSVS2590	PSVS2590	PSVS2591							
	3/4	W - RHD	1	PHBX4400			PRVS2541											
	3/4	W - MO ⁽¹⁾	1	PHBX4412			PLVS2552											
							PLVS2572											
							PLVS2592											
500	3/4	F - I	2	PHBX4402	PPVS2500	PSHS1904	PSVS2550	PSVS2551	PSVS2550	PSHS1906	PSHS1906	PPVS2500	PPVS2500	PSHS1906				
	3/4	F - I-MO ⁽¹⁾	2	PHBX4424														
	3/4	P - I ⁽¹⁾	2	PHBX4431														
	3/4	P - I-MO ⁽¹⁾	2	PHBX4424														
	3/4	W - I ⁽¹⁾	2	PHBX4425														
	3/4	W - I-MO ⁽¹⁾	2	PHBX4425														

⁽¹⁾ kit with recessed mounting plate

⁽²⁾ Not compatible with high terminal covers. Front only in form 1

* Mandatory everytime that the breaker kits have plates distant more than 38mm or for segregations form 4b

Key:

F	fixed
F - I	fixed interlocked
F - I-MO	fixed interlocked motor-operated
F - MO	fixed motor-operated
F - RC	fixed with residual current
F - RHD	fixed with Direct Rotary Handle

F & F - I	fixed and fixed interlocked
P	plug-in
P - I	plug-in interlocked
P - I-MO	plug-in interlocked motor-operated
P - MO	plug-in motor-operated
P - RC	plug-in with residual current
P - RHD	plug-in with Direct Rotary Handle

W	withdrawable
W - I	withdrawable interlocked
W - I-MO	withdrawable interlocked motor-operated
W - MO	withdrawable motor-operated
W - RC	withdrawable with residual current
W - RHD	withdrawable with Direct Rotary Handle
W & W - I	withdrawable and withdrawable interlocked

Internal kits

Quick selection guides

Tmax XT4

VERTICAL INSTALLATION

Cell height (mm)	No. of poles	Execution	No. of breakers per cell	Base kit (segregation form 1)	W=400mm			W=600mm			Segregation form	F 2a - 3a*	
					Segregation form			F 3b (for form 4b order the double of the vertical rear and side segregations)					
					Terminals separator			Vertical rear segregation			Vertical side segregation		
Front/Rear terminals													
300	3/4	F	2	-	PPVS2300	PSHS1904		PSHS4050			PRVS1541	PVCX4601	
	3/4	F	3	-				PSHS4070			PLVS1552	PVCX4701	
	3	F	3	-				PSHS4090			PLVS1572	PVCX4401	
	3	F	4	-				PRVS1740			PLVS1592	PVCX4405	
	3/4	F	1	PVBX4401				PRVS1741				PVCX4404	
	3/4	F - RHD	1	PVBX4405								-	
	3/4	F - MO	1	PVBX4404								PVCX4407	
	3	P	4	-								PVCX4409	
350	3/4	P	2	-	PPVS2350	PSHS1904		PSHS4050			PRVS1740	PVCX4427	
	3/4	P	3	-				PSHS4070				PVCX4410	
	3	P	3	-				PSHS4090					
	3/4	P	1	PVBX4407				PRVS1740					
	3/4	P - MO ⁽¹⁾	1	PVBX4409				PRVS1741					
	3/4	P - RHD	1	PVBX4427									
	3/4	W	1	PVBX4410									
	3/4	W - MO ⁽¹⁾	1	PVBX4412									
	3/4	W - RHD	1	PVBX4400									
400	4	F - RC	1	PVBX4423	PPVS2400	PSHS1904	PSHS4050	PSHS4070	PSHS4090	PRVS2040	PRVS2041	PLVS1752	PVCX4412
	4	W - RC	1	PVBX4417									PVCX4400

⁽¹⁾ kit with recessed mounting plate

* Mandatory everytime that the breaker kits have plates distant more than 38mm or for segregations form 4b

W=800mm											
Segregation form											
F 3b (for form 4b order the double of the vertical rear and side segregations)											
F 2a - 3a*						F 3b (for form 4b order the double of the vertical rear and side segregations)					
Vertical rear segregation			Vertical side segregation			Vertical rear segregation			Vertical side segregation		
With upright			With upright			With upright			With upright		
Terminals separator		D (mm)		D (mm)		Terminals separator		D (mm)		D (mm)	
500	700	900	500	700	900	500	700	900	500	700	900
PSHS6050	PSHS6050	PSHS6050	PRV51560	PRV51561	PRV51562	PLVS1752	PLVS1752	PLVS1752	PPVS2300	PPVS2300	PPVS2300
PSHS6070	PSHS6070	PSHS6070	PRV51760	PRV51761	PRV51762	PLVS1752	PLVS1752	PLVS1752	PSHS1908	PSHS1908	PSHS1908
PSHS6090	PSHS6090	PSHS6090	PRV51760	PRV51761	PRV51762	PLVS1752	PLVS1772	PLVS1772	PPVS2350	PPVS2350	PPVS2350
PRVS2060	PRVS1760	PRVS1760	PRV51761	PRV51762	PRV51762	PLVS1752	PLVS1772	PLVS1772	PSHS1908	PSHS1908	PSHS1908
PRVS2061	PRVS1761	PRVS1761	PRV51762	PRV51762	PRV51762	PLVS1752	PLVS1772	PLVS1772	-	-	-
PLVS2052	PLVS1752	PLVS1752	PLVS1752	PLVS1752	PLVS1752	PLVS1772	PLVS1772	PLVS1772	PVDX4701	PVDX4701	PVDX4701
PLVS2072	PLVS1772	PLVS1772	PLVS1772	PLVS1772	PLVS1772	PLVS1792	PLVS1792	PLVS1792	PVDX4801	PVDX4801	PVDX4801
PLVS2092	PLVS1792	PLVS1792	PLVS1792	PLVS1792	PLVS1792	-	-	-	-	-	-

Key:

F fixed
 F - I fixed interlocked
 F - I-MO fixed interlocked motor-operated
 F - MO fixed motor-operated
 F - RC fixed with residual current
 F - RHD fixed with Direct Rotary Handle

F & F - I fixed and fixed interlocked
 P plug-in
 P - I plug-in interlocked
 P - I-MO plug-in interlocked motor-operated
 P - MO plug-in motor-operated
 P - RC plug-in with residual current
 P - RHD plug-in with Direct Rotary Handle

W withdrawable
 W - I withdrawable interlocked
 W - I-MO withdrawable interlocked motor-operated
 W - MO withdrawable motor-operated
 W - RC withdrawable with residual current
 W - RHD withdrawable with Direct Rotary Handle
 W & W - I withdrawable and withdrawable interlocked

Internal kits

Quick selection guides

Tmax T4

HORIZONTAL INSTALLATION

			W=400mm			W=600mm		
			Segregation form			Segregation form		
			F 2a - 3a*		F 3b	F 2a - 3a*		F 3b
Cell height (mm)	No. of poles	Execution	No. of breakers per cell	Base kit (segregation form 1)				
Front/Rear terminals								
150	3	F	1	PHBT4301 ⁽²⁾				
					2xPPRS0150			
					PSHS1904			
200	3/4	F	1	PHBT4406 ⁽²⁾	PPVS2200	PSHS1904	PSVS2051	PSVS2050
	4	F - RC	1	-		PSVS1904	PSVS2071	PSVS2070
	3/4	F - RHD	1	PHBT4406 ⁽²⁾	PPVS2200	PSVS2091	PSVS2090	PRVS2041
	3/4	F - MO ⁽¹⁾	1	PHBT4404		PLVS2052	PLVS2072	PLVS2092
600	3/4	F - I	2	PHBT4402	PPVS2600	PSHS1904	PSVS2051	PSVS2050
	3/4	F - I-MO ⁽¹⁾	2	-		PSVS1904	PSVS2071	PSVS2070

VERTICAL INSTALLATION

			W=400mm			W=600mm		
			Segregation form			Segregation form		
			F 2a - 3a*		F 3b (for form 4b order the double of the vertical rear and side segregations)	F 2a - 3a*		F 3b
Cell height (mm)	No. of poles	Execution	No. of breakers per cell	Base kit (segregation form 1)				
Front/Rear terminals								
350	3/4	F	1	PVBT4406	PPVS2350	PSHS1904	PSHS4050	PSHS4050
	3/4	F - RHD	1	PVBT4406	PPVS2350	PSHS1904	PSHS4070	PSHS4070
	3/4	F - MO ⁽¹⁾	1	PVBT4404			PSHS4090	PSHS4090
450	4	F - RC	1	PVBT4423	PPVS2450	PSHS1904	PSHS4050	PSHS4070

⁽¹⁾ kit with recessed mounting plate

⁽²⁾ Not compatible with high terminal covers. Front only in form 1

* Mandatory everytime that the breaker kits have plates distant more than 38mm or for segregations form 4b

Key:

F	fixed
F - I	fixed interlocked
F - I-MO	fixed interlocked motor-operated
F - MO	fixed motor-operated
F - RC	fixed with residual current
F - RHD	fixed with Direct Rotary Handle

F & F - I	fixed and fixed interlocked
P	plug-in
P - I	plug-in interlocked
P - I-MO	plug-in interlocked motor-operated
P - MO	plug-in motor-operated
P - RC	plug-in with residual current
P - PHD	plug-in with Direct Rotary Handle

W	withdrawable
W - I	withdrawable interlocked
W - I-MO	withdrawable interlocked motor-operated
W - MO	withdrawable motor-operated
W - RC	withdrawable with residual current
W - RHD	withdrawable with Direct Rotary Handle
W & W - I	withdrawable and withdrawable interlocked

Internal kits

Quick selection guides

Tmax T5 400A

HORIZONTAL INSTALLATION

Cell height (mm)	No. of poles	Execution	No. of breakers per cell	Base kit (segregation form 1)			Universal horizontal shelf	W=400mm			Base kit (segregation form 1)			W=600mm			
				Segregation form				F 2a - 3a*			F 3b			Segregation form			
Front/Rear terminals																	
200	3	F	1	PHBT5306	(2)		PPV/S2200	PSHS1904	PSVS2050	PSVS2051	PSVS2050	PSVS2050	PSVS2051	PSHS1906	PSVS2050	PSVS2051	
	3	F - RHD	1	PHBT5306	(2)			PPV/S2200	PSVS2050	PSVS2051	PSVS2050	PSVS2050	PSVS2051	PPV/S2200	PSVS2050	PSVS2051	
	3	F - MO ⁽¹⁾	1	PHBT5304				PSHS1904	PSVS2050	PSVS2051	PSVS2050	PSVS2050	PSVS2051	PSHS1906	PSVS2050	PSVS2051	
	3	P	1	PHBT5326				PSHS1904	PSVS2050	PSVS2051	PSVS2050	PSVS2050	PSVS2051	PSHS1906	PSVS2050	PSVS2051	
	3	P - RHD	1	PHBT5326				PSHS1904	PSVS2050	PSVS2051	PSVS2050	PSVS2050	PSVS2051	PSHS1906	PSVS2050	PSVS2051	
	3	P - MO ⁽¹⁾	1	PHBT5309				PSHS1904	PSVS2050	PSVS2051	PSVS2050	PSVS2050	PSVS2051	PSHS1906	PSVS2050	PSVS2051	
250	3/4	F	1	PHBT5406	(2)		PPV/S2250	PSHS1904	PSVS2050	PSVS2051	PSVS2050	PSVS2050	PSVS2051	PSHS1906	PSVS2050	PSVS2051	
	4	F - RC	1	-				PSHS1904	PSVS2050	PSVS2051	PSVS2050	PSVS2050	PSVS2051	PSHS1906	PSVS2050	PSVS2051	
	3/4	F - RHD	1	PHBT5406	(2)			PSHS1904	PSVS2050	PSVS2051	PSVS2050	PSVS2050	PSVS2051	PSHS1906	PSVS2050	PSVS2051	
	3/4	F - MO ⁽¹⁾	1	PHBT5404				PSHS1904	PSVS2050	PSVS2051	PSVS2050	PSVS2050	PSVS2051	PSHS1906	PSVS2050	PSVS2051	
	3/4	P	1	PHBT5426				PLV/S2552	PLV/S2552	PLV/S2552	PLV/S2552	PLV/S2552	PLV/S2552	PLV/S2550	PLV/S2550	PLV/S2550	
	3/4	P - RHD	1	PHBT5426				PLV/S2572	PLV/S2572	PLV/S2572	PLV/S2572	PLV/S2572	PLV/S2572	PLV/S2550	PLV/S2550	PLV/S2550	
	3/4	P - MO ⁽¹⁾	1	PHBT5409				PLV/S2592	PLV/S2592	PLV/S2592	PLV/S2592	PLV/S2592	PLV/S2592	PLV/S2550	PLV/S2550	PLV/S2550	
	300	3	W	1	PHBT5314		PPV/S2300	PSHS1904	PSVS1204	PSVS1204	PSVS1204	PSVS1204	PSVS1204	PSHS1906	PSVS1204	PSVS1204	
	3	W - RHD	1	PHBT5314				PSHS1904	PSVS1204	PSVS1204	PSVS1204	PSVS1204	PSVS1204	PSHS1906	PSVS1204	PSVS1204	
	3	W - MO ⁽¹⁾	1	PHBT5312				PRV/S3041	PSVS1204	PSVS1204	PSVS1204	PSVS1204	PSVS1204	PSHS1906	PSVS1204	PSVS1204	
	350	3/4	W	1	PHBT5414		PPV/S2350	PSHS1904	PSVS1204	PSVS1204	PSVS1204	PSVS1204	PSVS1204	PSHS1906	PSVS1204	PSVS1204	
	3/4	W - RHD	1	PHBT5414				PSHS1904	PSVS1204	PSVS1204	PSVS1204	PSVS1204	PSVS1204	PSHS1906	PSVS1204	PSVS1204	
	3/4	W - MO ⁽¹⁾	1	PHBT5412				PRV/S3541	PSVS1204	PSVS1204	PSVS1204	PSVS1204	PSVS1204	PSHS1906	PSVS1204	PSVS1204	
	600	3/4	F - I	2	-									PPV/S2350	PPV/S2350	PPV/S2350	
	3/4	F - I-MO ⁽¹⁾	2	-				PSVS3551	PSVS3550	PSVS3551	PSVS3550	PSVS3550	PSVS3550	PSHS1906	PSVS3550	PSVS3550	
	3/4	P - I ⁽¹⁾	2	-				PSVS3571	PSVS3570	PSVS3571	PSVS3570	PSVS3570	PSVS3570	PSHS1906	PSVS3570	PSVS3570	
	3/4	P - I-MO ⁽¹⁾	2	-				PSVS3591	PSVS3590	PSVS3591	PSVS3590	PSVS3590	PSVS3590	PSHS1906	PSVS3590	PSVS3590	
	3/4	W - I ⁽¹⁾	2	-										PPV/S2600	PPV/S2600	PPV/S2600	
	3/4	W - I-MO ⁽¹⁾	2	-										PSHS1906	PSHS1906	PSHS1906	

⁽¹⁾ kit with recessed mounting plate

⁽²⁾ Not compatible with high terminal covers. Front only in form 1

* Mandatory everytime that the breaker kits have plates distant more than 38mm or for segregations form 4b

W=800									
F 4b Rear cubicle			Segregation form				F 4b Rear cubicle		
Mounting position			F 2a - 3a*		F 3b		Mounting position		
D (mm)	P0/P1	P0	P1	P2			P0/P1	P0	P1
500	Front	Rear			Base kit (segregation form 1)	Cell side closing	Universal horizontal shelf	Front	Rear
PLVS2052	PCVS0206	PCVS1206	PCVS2206	PHDT5306	PPVS2200	PSHS1908	PSHS1908	PCVS0208	PCVS1208
PLVS2072	PCVS0206	PCVS1206	PCVS2206	PHDT5306			PSVS2050	PSVS2051	PSVS2208
PLVS2092	PCVS1206	PCVS2206	PHDT5304		PPVS2250	PSHS1908	PSVS2050	PSVS2051	PSVS2208
PLVS2552	PCVS1206	PCVS2206	PHDT5326				PSVS2050	PSVS2051	PSVS2208
PLVS2572	PCVS1206	PCVS2206	PHDT5326				PSVS2070	PSVS2071	PSVS2208
PLVS2592	PCVS0256	PCVS1256	PCVS2256	PHDT5406			PSVS2090	PSVS2091	PSVS2208
PLVS3052	PCVS0256	PCVS1256	PCVS2256	PHDT5423			PRVS2081	PLVS2052	PCVS1208
PLVS3072	PCVS0256	PCVS1256	PCVS2256	PHDT5406				PLVS2072	PCVS1208
PLVS3092	PCVS0256	PCVS1256	PCVS2256	PHDT5404				PLVS2092	PCVS1208
PLVS3352	PCVS1256	PCVS2256	PHDT5426						PCVS1208
PLVS3372	PCVS1256	PCVS2256	PHDT5426						PCVS1208
PLVS3392	PCVS1306	PCVS2306	PHDT5314		PPVS2300	PSHS1908	PSVS2550	PSVS2551	PSVS2208
PLVS3552	PCVS1306	PCVS2306	PHDT5314				PSVS2550	PSVS2551	PSVS2208
PLVS3572	PCVS1306	PCVS2306	PHDT5314				PSVS2570	PSVS2571	PSVS2208
PLVS3592	PCVS1356	PCVS2356	PHDT5414		PPVS2350	PSHS1908	PSVS2590	PSVS2591	PSVS2208
PLVS3552	PCVS1356	PCVS2356	PHDT5414				PSVS2590	PSVS2591	PSVS2208
PLVS3572	PCVS1356	PCVS2356	PHDT5414				PRVS2581	PRVS2581	PRVS2208
PLVS3592	PCVS1356	PCVS2356	PHDT5412					PLVS2552	PCVS1258
PLVS3552	PCVS1356	PCVS2356	PHDT5412					PLVS2572	PCVS1258
PLVS3572	PCVS1356	PCVS2356	PHDT5412					PLVS2592	PCVS1258
PLVS3592	PCVS1356	PCVS2356	PHDT5411					PLVS2592	PCVS1258
PLVS3552	PCVS1358	PCVS2358	PHDT5425						PCVS1308
PLVS3572	PCVS1358	PCVS2358	PHDT5425						PCVS1308
PLVS3592	PCVS1358	PCVS2358	PHDT5411						PCVS1308

Key:

F	fixed
F - I	fixed interlocked
F - I-MO	fixed interlocked motor-operated
F - MO	fixed motor-operated
F - RC	fixed with residual current
F - RHD	fixed with Direct Rotary Handle

F & F - I	fixed and fixed interlocked
P	plug-in
P - I	plug-in interlocked
P - I-MO	plug-in interlocked motor-operated
P - MO	plug-in motor-operated
P - RC	plug-in with residual current
P - RHD	plug-in with Direct Rotary Handle

W	withdrawable
W - I	withdrawable interlocked
W - I-MO	withdrawable interlocked motor-operated
W - MO	withdrawable motor-operated
W - RC	withdrawable with residual current
W - RHD	withdrawable with Direct Rotary Handle
W & W - I	withdrawable and withdrawable interlocked

Internal kits

Quick selection guides

Tmax T5 400A VERTICAL INSTALLATION

W=400mm				W=600mm											
Segregation form				Segregation form											
F 2a - 3a*		F 3b (for form 4b order the double of the vertical rear and side segregations)		F 2a - 3a*											
Cell height (mm)	No. of poles	Execution	No. of breakers per cell	Base kit (segregation form 1)	Cell side closing	Universal horizontal shelf	Terminals separator								
					D (mm)										
					500 700 900	Without upright	Vertical rear segregation								
						Bars side	Vertical side segregation								
						500 700 900	D (mm)								
Front/Rear terminals				Base kit (segregation form 1)											
350	3/4 F	1	PVBT5406	PPVS2350	PSHS1904	PSHS4050	PRVS1740	PRVS1741	PLVS1752	PLVS1772	PLVS1792	PVCT5406	PPVS2350	PSHS1906	
	3/4 F	2				PSHS4070						PVCT5406			
	3/4 F - RHD	1	PVBT5406			PSHS4090						PVCT5404			
	3/4 F - MO ⁽¹⁾	1	PVBT5404									PVCT5426			
	3/4 P	1	PVBT5426									PVCT5426			
	3/4 P - RHD	1	PVBT5426									-			
	3/4 W	3	-									-			
	3 W	4	-									-			
	3/4 W	2	-									-			
	3/4 W	1	PVBT5414									PVCT5414			
	3/4 W - RHD	1	PVBT5414									PVCT5414			
450				Base kit (segregation form 1)				Base kit (segregation form 1)				Base kit (segregation form 1)			
	3/4 W - MO ⁽¹⁾	1	PVBT5412	PPVS2450	PSHS1904	PSHS4050	PRVS2240	PRVS2241	PLVS2252	PLVS2272	PLVS2292	PVCT5412	PPVS2450	PSHS1906	
	3/4 W - MO ⁽¹⁾	2	-			PSHS4070						-			
	3/4 W - MO ⁽¹⁾	3	-			PSHS4090						-			
	3 W - MO ⁽¹⁾	4	-									-			
	4 F - RC	1	PVBT5423									PVCT5423			
	4 P - RC	1	PVBT5428									PVCT5428			

⁽¹⁾ kit with recessed mounting plate

* Mandatory everytime that the breaker kits have plates distant more than 38mm or for segregations form 4b

W=800mm										W=1000mm										
Segregation form										Segregation form										
F 3b (for form 4b order the double of the vertical rear and side segregations)										F 2a - 3a* (for form 4b order the double of the vertical rear and side segregations)										
Terminals separator					Terminals separator					Terminals separator					Terminals separator					
D (mm)		Without upright		With upright		D (mm)		Without upright		With upright		D (mm)		Without upright		With upright		D (mm)		
500	700	900				Bars side	Exits side	500	700	900		Bars side	Exits side	500	700	900		Bars side	Exits side	
PSHS6050	PSHS6050	PSHS6050	PRVS1760	PRVS1760	PRVS1761	PLVS1752	PLVS1772	PLVS1792	PPVTS2350	PSHS1908	PSHS8050	PSHS8050	PSHS8070	PSHS8070	PSHS8090	PRVS1780	PRVS1781	PRVS1782	PRVS1782	PRVS1782
PSHS6070	PSHS6070	PSHS6070	PRVS1760	PRVS1760	PRVS1761	PLVS1752	PLVS1772	PLVS1792	PPVTS2350	PSHS1908	PSHS8050	PSHS8050	PSHS8070	PSHS8070	PSHS8090	PRVS1780	PRVS1781	PRVS1782	PRVS1782	PRVS1782
PSHS6090	PSHS6090	PSHS6090	PRVS1760	PRVS1760	PRVS1761	PLVS1752	PLVS1772	PLVS1792	PPVTS2350	PSHS1908	PSHS8050	PSHS8050	PSHS8070	PSHS8070	PSHS8090	PRVS1780	PRVS1781	PRVS1782	PRVS1782	PRVS1782
PRVS2260	PRVS2260	PRVS2260	PRVS1762	PRVS1762	PRVS1762	PLVS1752	PLVS1772	PLVS1792	PPVTS2350	PSHS1908	PSHS8050	PSHS8050	PSHS8070	PSHS8070	PSHS8090	PRVS1780	PRVS1781	PRVS1782	PRVS1782	PRVS1782
PRVS2261	PRVS2261	PRVS2261	PRVS1762	PRVS1762	PRVS1762	PLVS1752	PLVS1772	PLVS1792	PPVTS2350	PSHS1908	PSHS8050	PSHS8050	PSHS8070	PSHS8070	PSHS8090	PRVS1780	PRVS1781	PRVS1782	PRVS1782	PRVS1782
PRVS2262	PRVS2262	PRVS2262	PRVS1762	PRVS1762	PRVS1762	PLVS1752	PLVS1772	PLVS1792	PPVTS2350	PSHS1908	PSHS8050	PSHS8050	PSHS8070	PSHS8070	PSHS8090	PRVS1780	PRVS1781	PRVS1782	PRVS1782	PRVS1782
PLVS2252	PLVS2252	PLVS2252	PLVS1762	PLVS1762	PLVS1762	PLVS1752	PLVS1772	PLVS1792	PPVTS2350	PSHS1908	PSHS8050	PSHS8050	PSHS8070	PSHS8070	PSHS8090	PRVS1780	PRVS1781	PRVS1782	PRVS1782	PRVS1782
PLVS2272	PLVS2272	PLVS2272	PLVS1762	PLVS1762	PLVS1762	PLVS1752	PLVS1772	PLVS1792	PPVTS2350	PSHS1908	PSHS8050	PSHS8050	PSHS8070	PSHS8070	PSHS8090	PRVS1780	PRVS1781	PRVS1782	PRVS1782	PRVS1782
PLVS2292	PLVS2292	PLVS2292	PLVS1762	PLVS1762	PLVS1762	PLVS1752	PLVS1772	PLVS1792	PPVTS2350	PSHS1908	PSHS8050	PSHS8050	PSHS8070	PSHS8070	PSHS8090	PRVS1780	PRVS1781	PRVS1782	PRVS1782	PRVS1782
PVDT5406	PVDT5406	PVDT5406	PVDT5406	PVDT5406	PVDT5406	PVDT5406	PVDT5406	PVDT5406	PPVTS2350	PSHS1908	PSHS8050	PSHS8050	PSHS8070	PSHS8070	PSHS8090	PRVS1780	PRVS1781	PRVS1782	PRVS1782	PRVS1782
PVDT5410	PVDT5410	PVDT5410	PVDT5410	PVDT5410	PVDT5410	PVDT5410	PVDT5410	PVDT5410	PPVTS2350	PSHS1908	PSHS8050	PSHS8050	PSHS8070	PSHS8070	PSHS8090	PRVS1780	PRVS1781	PRVS1782	PRVS1782	PRVS1782
PVDT5414	PVDT5414	PVDT5414	PVDT5414	PVDT5414	PVDT5414	PVDT5414	PVDT5414	PVDT5414	PPVTS2350	PSHS1908	PSHS8050	PSHS8050	PSHS8070	PSHS8070	PSHS8090	PRVS1780	PRVS1781	PRVS1782	PRVS1782	PRVS1782
PVDT5412	PVDT5412	PVDT5412	PVDT5412	PVDT5412	PVDT5412	PVDT5412	PVDT5412	PVDT5412	PPVTS2350	PSHS1908	PSHS8050	PSHS8050	PSHS8070	PSHS8070	PSHS8090	PRVS1780	PRVS1781	PRVS1782	PRVS1782	PRVS1782
PVDT5612	PVDT5612	PVDT5612	PVDT5612	PVDT5612	PVDT5612	PVDT5612	PVDT5612	PVDT5612	PPVTS2350	PSHS1908	PSHS8050	PSHS8050	PSHS8070	PSHS8070	PSHS8090	PRVS1780	PRVS1781	PRVS1782	PRVS1782	PRVS1782
PVDT5423	PVDT5423	PVDT5423	PVDT5423	PVDT5423	PVDT5423	PVDT5423	PVDT5423	PVDT5423	PPVTS2350	PSHS1908	PSHS8050	PSHS8050	PSHS8070	PSHS8070	PSHS8090	PRVS1780	PRVS1781	PRVS1782	PRVS1782	PRVS1782
PVDT5428	PVDT5428	PVDT5428	PVDT5428	PVDT5428	PVDT5428	PVDT5428	PVDT5428	PVDT5428	PPVTS2350	PSHS1908	PSHS8050	PSHS8050	PSHS8070	PSHS8070	PSHS8090	PRVS1780	PRVS1781	PRVS1782	PRVS1782	PRVS1782
PRVS2282	PRVS2282	PRVS2282	PRVS2282	PRVS2282	PRVS2282	PRVS2282	PRVS2282	PRVS2282	PPVTS2350	PSHS1908	PSHS8050	PSHS8050	PSHS8070	PSHS8070	PSHS8090	PRVS1780	PRVS1781	PRVS1782	PRVS1782	PRVS1782
PLVS2252	PLVS2252	PLVS2252	PLVS2252	PLVS2252	PLVS2252	PLVS2252	PLVS2252	PLVS2252	PPVTS2350	PSHS1908	PSHS8050	PSHS8050	PSHS8070	PSHS8070	PSHS8090	PRVS1780	PRVS1781	PRVS1782	PRVS1782	PRVS1782
PLVS2272	PLVS2272	PLVS2272	PLVS2272	PLVS2272	PLVS2272	PLVS2272	PLVS2272	PLVS2272	PPVTS2350	PSHS1908	PSHS8050	PSHS8050	PSHS8070	PSHS8070	PSHS8090	PRVS1780	PRVS1781	PRVS1782	PRVS1782	PRVS1782
PLVS2292	PLVS2292	PLVS2292	PLVS2292	PLVS2292	PLVS2292	PLVS2292	PLVS2292	PLVS2292	PPVTS2350	PSHS1908	PSHS8050	PSHS8050	PSHS8070	PSHS8070	PSHS8090	PRVS1780	PRVS1781	PRVS1782	PRVS1782	PRVS1782
PVFT5710	PVFT5710	PVFT5710	PVFT5710	PVFT5710	PVFT5710	PVFT5710	PVFT5710	PVFT5710	PPVTS2350	PSHS1908	PSHS8050	PSHS8050	PSHS8070	PSHS8070	PSHS8090	PRVS1780	PRVS1781	PRVS1782	PRVS1782	PRVS1782
PVFT5812	PVFT5812	PVFT5812	PVFT5812	PVFT5812	PVFT5812	PVFT5812	PVFT5812	PVFT5812	PPVTS2350	PSHS1908	PSHS8050	PSHS8050	PSHS8070	PSHS8070	PSHS8090	PRVS1780	PRVS1781	PRVS1782	PRVS1782	PRVS1782

Key:	F & F - I	fixed and fixed interlocked	W	withdrawable
F - I	fixed interlocked	plug-in	W - I	withdrawable interlocked
F - MO	fixed interlocked motor-operated	plug-in interlocked	W - I-MO	withdrawable interlocked motor-operated
F - MO	fixed motor-operated	plug-in motor-operated	W - MO	withdrawable motor-operated
F - RC	fixed with residual current	plug-in with residual current	W - RC	withdrawable with residual current
F - RHD	fixed with Direct Rotary Handle	plug-in with Direct Rotary Handle	W - RHD	withdrawable with Direct Rotary Handle
			W & W - I	withdrawable and withdrawable interlocked

Internal kits

Quick selection guides

Tmax T5 630A

HORIZONTAL INSTALLATION

W=400mm										W=600mm																	
Cell height (mm)	No. of poles	Execution	No. of breakers per cell	Base kit (segregation form 1)			Cell side closing			Universal horizontal shelf			Segregation form			Base kit (segregation form 1)			Cell side closing			Universal horizontal shelf			Segregation form		
				F 2a - 3a*			F 3b			F 4b			Rear segregation bars side			Mounting position			F 2a - 3a*			F 3b					
				500	700	900				D (mm)					P0/P1	P0	P1	P2									
				500	700	900				D (mm)					Front	Rear											
Front/Rear terminals																											
200	3	F	1	PHBT5306 ⁽²⁾	PPVS2200	PSHS1904	PPVS2200	PSVS2050	PSVS2070	PSVS2090	PSVS2041	PLVS2052	PLVS2072	PLVS2092	PCVS0204	PCVS1204	PCVS2204	PHCT5306	PPVS2200	PSHS1906	PPVS2200	PSVS2050	PSVS2070	PSVS2090	PRVS2061		
	3	F - RHD	1	PHBT5306 ⁽²⁾											PCVS0204	PCVS1204	PCVS2204	PHCT5306	PPVS2200	PSHS1906	PPVS2200	PSVS2050	PSVS2070	PSVS2090	PRVS2061		
	3	F - MO ⁽¹⁾	1	PHBT5304											PCVS1204			PCVS2204	PHCT5304								
250	3/4	F	1	PHBT5406 ⁽²⁾	PPVS2250	PSHS1904	PPVS2250	PSVS2550	PSVS2570	PSVS2590	PSVS2541	PLVS2552	PLVS2572	PLVS2592	PCVS0254	PCVS1254	PCVS2254	PHCT5406	PPVS2250	PSHS1906	PPVS2250	PSVS2550	PSVS2570	PSVS2590	PRVS2061		
	4	F - RC	1	-											PCVS0254	PCVS1254	PCVS2254	PHCT5423	PPVS2250	PSHS1906	PPVS2250	PSVS2550	PSVS2570	PSVS2590	PRVS2061		
	3/4	F - RHD	1	PHBT5406 ⁽²⁾											PCVS0254	PCVS1254	PCVS2254	PHCT5406	PPVS2250	PSHS1906	PPVS2250	PSVS2550	PSVS2570	PSVS2590	PRVS2061		
	3/4	F - MO ⁽¹⁾	1	PHBT5404											PCVS1254	PCVS2254	PHCT5404		PPVS2250	PSHS1906	PPVS2250	PSVS2550	PSVS2570	PSVS2590	PRVS2061		
	3/4	P	1	-														PHCT5407									
	3/4	P - MO ⁽¹⁾	1	-														PHCT5427									
600	3/4	F-I	2	-														PHCT5402	PPVS2600	PSHS1906	PPVS2600	PSHS1906	PPVS2600	PSHS1906	PPVS2600	PSHS1906	
	3/4	F-I-MO ⁽¹⁾	2	-														PHCT5403									
	3/4	P-I ⁽¹⁾	2	-														-									
	3/4	P-I-MO ⁽¹⁾	2	-														-									

⁽¹⁾ kit with recessed mounting plate

⁽²⁾ Not compatible with high terminal covers. Front only in form 1

* Mandatory everytime that the breaker kits have plates distant more than 38mm or for segregations form 4b

W=800													
Side rear segregation	F 4b				Segregation form				F 4b				
	Rear cubicle				F 2a - 3a*		F 3b		Rear cubicle				
	Mounting position				P0/P1	P0	P1	P2	P0/P1	P0	P1	P2	
	D (mm)	breaker terminals				Universal horizontal shelf				breaker terminals			
	500 700 900	Front	Rear		Base kit (segregation form 1)	Cell side closing			500 700 900	Front	Rear		
					PPVS2200	PSHS1908	PSVS2050	PSVS2070	PSVS2090				
PLVS2052	PCVS0206	PCVS1206	PCVS2206	PHDT5306	PPVS2200	PSHS1908	PSVS2051	PSVS2071	PSVS2091	PRVS2081	PLVS2052	PCVS0208	PCVS1208 PCVS2208
PLVS2072	PCVS0206	PCVS1206	PCVS2206	PHDT5306							PLVS2072	PCVS0208	PCVS1208 PCVS2208
PLVS2092	PCVS1206		PCVS2206	PHDT5304							PLVS2092	PCVS1208	PCVS2208
PLVS2552	PCVS0256	PCVS1256	PCVS2256	PHDT5406	PPVS2250	PSHS1908	PSVS2550	PSVS2570	PSVS2590	PRVS2581	PLVS2552	PCVS0258	PCVS1258 PCVS2258
PLVS2572	PCVS0256	PCVS1256	PCVS2256	PHDT5423							PLVS2572	PCVS0258	PCVS1258 PCVS2258
PLVS2592	PCVS0256	PCVS1256	PCVS2256	PHDT5406							PLVS2592	PCVS0258	PCVS1258 PCVS2258
	PCVS1256		PCVS2256	PHDT5404								PCVS1258	PCVS2258
		PCVS1256	PCVS2256	PHDT5407									PCVS1258 PCVS2258
				PHDT5428									
					-		PSVS2553	PSVS2573	PSVS2593	PRVS2600			
					PHDT5431		PSVS2550	PSVS2570	PSVS2590	PSHS1908			
					PHDT5432								

Key:

F fixed
F - I fixed interlocked
F - I-MO fixed interlocked motor-operated
F - MO fixed motor-operated
F - RC fixed with residual current
F - RHD fixed with Direct Rotary Handle

F & F - I fixed and fixed interlocked
P plug-in
P - I plug-in interlocked
P - I-MO plug-in interlocked motor-operated
P - MO plug-in motor-operated
P - RC plug-in with residual current
P - RHD plug-in with Direct Rotary Handle

W withdrawable
W - I withdrawable interlocked
W - I-MO withdrawable interlocked motor-operated
W - MO withdrawable motor-operated
W - RC withdrawable with residual current
W - RHD withdrawable with Direct Rotary Handle
W & W - I withdrawable and withdrawable interlocked

Internal kits

Quick selection guides

Tmax T5 630A

VERTICAL INSTALLATION

		W=400mm			W=600mm				
		Segregation form			Segregation form				
		F 2a - 3a*			F 3b (for form 4b order the double of the vertical rear and side segregations)				
Cell height (mm)	No. of poles	Execution	No. of breakers per cell	Base kit (segregation form 1)	Cell side closing	Universal horizontal shelf	Terminals separator	Vertical rear segregation	Vertical side segregation
							D (mm)	With upright	
							500 700 900	Bars side	D (mm)
Front/Rear terminals									Base kit (segregation form 1)
350	3/4	F	1	PVBT5406	PPVS2350	PSHS1904	PSHS4050	PSHS4070	PVCT5406
	3/4	F - RHD	1	PVBT5406			PSHS4090	PRV51740	PPVS2350
	3/4	F - MO ⁽¹⁾	1	PVBT5404				PRV51741	PSHS1906
	3/4	W	2	-				PLV51752	
	3/4	W	3	-				PLV51772	
	3	W	4	-				PLV51792	
	3/4	W - MO ⁽¹⁾	3	-					PVCT5406
	3	W - MO ⁽¹⁾	4	-					PVCT5430
400	3/4	P	1	-	PPVS2400	PSHS1904			
	3/4	P - MO ⁽¹⁾	1	PVBT5409					PVCT5409
	3/4	W - MO ⁽¹⁾	1	-					PVCT5430

⁽¹⁾ kit with recessed mounting plate

* Mandatory everytime that the breaker kits have plates distant more than 38mm or for segregations form 4b

W=800mm										W=1000mm												
Segregation form										Segregation Form												
F 3b (for form 4b order the double of the vertical rear and side segregations)					F 2a - 3a*					F 3b (for form 4b order the double of the vertical rear and side segregations)					F 2a - 3a*							
Terminals separator	Vertical rear segregation	Vertical side segregation	With upright	Without upright	Terminals separator	Vertical rear segregation	Vertical side segregation	With upright	Without upright	Terminals separator	Vertical rear segregation	Vertical side segregation	With upright	Without upright	Terminals separator	Vertical rear segregation	Vertical side segregation	With upright	Without upright			
D (mm)					D (mm)					D (mm)					D (mm)							
500	700	900			Bars side	Exits side	500	700	900	Bars side	Exits side	500	700	900	Bars side	Exits side	500	700	900			
PSHS6050	PSHS6070	PSHS6090	PRVS1760	PRVS1761	PRV51762	PLVS1752	PLVS1772	PLVS1792	PVDT5406	PPVS2350	PSHS1908	PSHS8050	PSHS8070	PSHS8090	PRVS1780	PRVS1781	PRV51782	PLVS1752	PLVS1772	PLVS1792	PPVS2350	PSHS1901
									PVDT5404													
									PVDT5610													
									-													
									-													
									-													
									-													
									PVDT5407	PPVS2400	PSHS1908	PSHS8050	PSHS8070	PSHS8090	PRVS2080	PRVS2081	PRV52082	PLVS2052	PLVS2072	PLVS2092	PPVS2350	
									PVDT5409													
									PVDT5430													

Key:

- F fixed
 F - I fixed interlocked
 F - I-MO fixed interlocked motor-operated
 F - MO fixed motor-operated
 F - RC fixed with residual current
 F - RHD fixed with Direct Rotary Handle

- F & F - I fixed and fixed interlocked
 P plug-in
 P - I plug-in interlocked
 P - I-MO plug-in interlocked motor-operated
 P - MO plug-in motor-operated
 P - RC plug-in with residual current
 P - RHD plug-in with Direct Rotary Handle

- W withdrawable
 W - I withdrawable interlocked
 W - I-MO withdrawable interlocked motor-operated
 W - MO withdrawable motor-operated
 W - RC withdrawable with residual current
 W - RHD withdrawable with Direct Rotary Handle
 W & W - I withdrawable and withdrawable interlocked

Internal kits

Quick selection guides

Tmax T6

HORIZONTAL INSTALLATION

Cell height (mm)	No. of poles	Execution	No. of breakers per cell	W=400mm			W=600mm		
				Segregation form			Segregation form		
				F 2a - 3a*	F 3b	F 4b	F 2a - 3a*	F 3b	Rear cubicle
Cell height (mm)	No. of poles	Execution	No. of breakers per cell	Base kit (segregation form 1)	Universal horizontal shelf	Side rear segregation	Base kit (segregation form 1)	Universal horizontal shelf	Rear segregation bars side
					Terminals separator	D (mm)			
					500 700 900	500 700 900			
				Cell side closing		Side rear segregation	Mounting position	Terminals separator	
						D (mm)	P0/P1 P0 P1 P2	500 700 900	
							breaker terminals		
							Front Rear		
Front/Rear terminals									
300	3	F	1				PHCT6301	PPVS2300	
	3	F - RHD	1				PHCT6305	PSHS1906	
	3	F - MO ⁽¹⁾	1				PHCT6304	PPVS3050	
350	3/4	F	1				PHCT6401	PPVS2350	
	3/4	F - RHD	1				PHCT6405	PSHS1906	
	3/4	F - MO ⁽¹⁾	1				PHCT6404	PSVS3053	
	3	W ⁽²⁾	1				PHCT6314	PSVS3550	
	3	W - RHD ⁽²⁾	1				PHCT6314	PSVS3570	
	3	W - MO ^{(1) (2)}	1				PHCT6312	PSVS3593	
500	3/4	W ⁽²⁾	1				PHCT6410	PSVS2500	
	3/4	W - RHD ⁽²⁾	1				PHCT6400	PSHS1906	
	3/4	W - MO ^{(1) (2)}	1				PHCT6412	PSVS3551	
700	3/4	F-I	2				PHCT6402	PPVS2700	
	3/4	F - I-MO ⁽¹⁾	2				PHCT6403	PSHS1906	
	3/4	W - I ^{(1) (2)}	2				PHCT6425	PSVS0502	
	3/4	W - I-MO ^{(1) (2)}	2				PHCT6411	PSVS05072	
								PSVS5092	PSVS5090
								PSVS5061	PSVS3591

(1) kit with recessed mounting plate

(2) Front terminals only in Form 1, high terminal cover not available.

* Mandatory everytime that the breaker kits have plates distant more than 38mm or for segregations form 4b

W=800												
side rear segregation	F 4b				Segregation form				F 4b			
	Rear cubicle				F 2a - 3a*		F 3b		Rear cubicle			
	Mounting position				Base kit (segregation form 1)		Cell side closing		Mounting position			
	P0/P1	P0	P1	P2	D (mm)		Universal horizontal shelf		P0/P1			
	500	700	900	Front	D (mm)		Terminals separator		P0			
	500	700	900	Rear	D (mm)		Rear segregation bars side		P1			
PLVS3052	PCVS0306	PCVS1306	PCVS2306	PHDT6301	PPVS2300		PSHS1908		P2			
PLVS3072	PCVS0306	PCVS1306	PCVS2306	PHDT6305	PPVS2350		PSVS0503		breaker terminals			
PLVS3092	PCVS1306		PCVS2306	PHDT6304	PPVS2700		PSVS0505		breaker terminals			
PLVS5552	PCVS0356	PCVS1356	PCVS2356	PHDT6401	PSHS1908		PSVS0503		PCVS1308			
PLVS3572	PCVS0356	PCVS1356	PCVS2356	PHDT6405	PSVS3550		PSVS05073		PCVS1308			
PLVS5592	PCVS1356		PCVS2356	PHDT6404	PSVS3570		PSVS3590		PCVS1308			
PLVS5592		PCVS1356	PCVS2356	PHDT6314	PSVS3593		PSVS3090		PCVS1308			
PLVS5592		PCVS1356	PCVS2356	PHDT6314	PSVS3581		PSVS3081		PCVS1308			
PLVS5592			PCVS2356	PHDT6312	PLVS3052		PLVS3072		PCVS1358			
PLVS5592			PCVS1506	PCVS2506	PLVS3552		PLVS3572		PCVS1358			
PLVS5592			PCVS1506	PCVS2506	PLVS3592		PLVS3092		PCVS1358			
PLVS5592				PHDT6412	PCVS1508		PCVS2508		PCVS1508			
PLVS5592				PHDT6402	PSVS0502		PSVS05072		PCVS1508			
PLVS5592				PHDT6403	PSVS05072		PSVS05092		PCVS1508			
PLVS5592				-	PSVS2700		PSHS1908		PCVS1508			

Key:

F	fixed
F - I	fixed interlocked
F - I-MO	fixed interlocked motor-operated
F - MO	fixed motor-operated
F - RC	fixed with residual current
F - RHD	fixed with Direct Rotary Handle

F & F - I	fixed and fixed interlocked
P	plug-in
P - I	plug-in interlocked
P - I-MO	plug-in interlocked motor-operated
P - MO	plug-in motor-operated
P - RC	plug-in with residual current
P - RHD	plug-in with Direct Rotary Handle

W	withdrawable
W - I	withdrawable interlocked
W - I-MO	withdrawable interlocked motor-operated
W - MO	withdrawable motor-operated
W - RC	withdrawable with residual current
W - RHD	withdrawable with Direct Rotary Handle
W & W - I	withdrawable and withdrawable interlocked

Internal kits

Quick selection guides

Tmax T6

VERTICAL INSTALLATION

				W=400mm										W=600mm														
Cell height (mm)	No. of poles	Execution	No. of breakers per cell	Base kit (segregation form 1)				Universal horizontal shelf				Segregation form				Base kit (segregation form 1)				Universal horizontal shelf				Segregation form				
				F 2a - 3a*				F 3b (for form 4b order the double of the vertical rear and side segregations)				Vertical rear segregation				Vertical side segregation				F 2a - 3a*				Segregation form				
				D (mm)	500	700	900	Terminals separator	Without upright				With upright				D (mm)				Base kit (segregation form 1)				Segregation form			
Front/Rear terminals																												
400	3/4	F	1	PVBT6401	PPVS2400	PSHS1904			PSHS4050		PSHS4070		PRVS2040		PRVS2041		PLVS2052		PLVS2072		PLVS2092		PVCT6401					
	3/4	F - RHD	1	PVBT6405	PPVS2450	PSHS1904			PSHS4050		PSHS4070		PSHS4090		PRVS2240		PRVS2241		PLVS2252		PLVS2272		PLVS2292		PVCT6405			
	3/4	F - MO ⁽¹⁾	1	PVBT6404					PSHS4050		PSHS4070		PSHS4090		PRVS2240		PRVS2241		PLVS2252		PLVS2272		PLVS2292		PVCT6404			
450	3/4	W ⁽²⁾	2	-					PSHS4050		PSHS4070		PSHS4090		PRVS2240		PRVS2241		PLVS2252		PLVS2272		PLVS2292		-			
	3/4	W - MO ⁽¹⁾⁽²⁾	2	-					PSHS4050		PSHS4070		PSHS4090		PRVS2240		PRVS2241		PLVS2252		PLVS2272		PLVS2292		-			
	3	W ⁽²⁾	1	PVBT6314					PSHS4050		PSHS4070		PSHS4090		PRVS2240		PRVS2241		PLVS2252		PLVS2272		PLVS2292		PVCT6414			
	3	W - MO ⁽¹⁾⁽²⁾	1	PVBT6312					PSHS4050		PSHS4070		PSHS4090		PRVS2240		PRVS2241		PLVS2252		PLVS2272		PLVS2292		PVCT6412			
	3	W - RHD ⁽²⁾	1	PVBT6314					PSHS4050		PSHS4070		PSHS4090		PRVS2240		PRVS2241		PLVS2252		PLVS2272		PLVS2292		PVCT6414			
	3/4	W ⁽²⁾	1	-					PSHS4050		PSHS4070		PSHS4090		PRVS2240		PRVS2241		PLVS2252		PLVS2272		PLVS2292		-			
	3/4	W - MO ⁽¹⁾⁽²⁾	1	-					PSHS4050		PSHS4070		PSHS4090		PRVS2240		PRVS2241		PLVS2252		PLVS2272		PLVS2292		-			
	3/4	W - RHD ⁽²⁾	1	-					PSHS4050		PSHS4070		PSHS4090		PRVS2240		PRVS2241		PLVS2252		PLVS2272		PLVS2292		-			

⁽¹⁾ kit with recessed mounting plate

⁽²⁾ Front terminals only in Form 1, high terminal cover not available.

* Mandatory everytime that the breaker kits have plates distant more than 38mm or for segregations form 4b

W=800mm												W=1000mm												
F 3b (for form 4b order the double of the vertical rear and side segregations)												Segregation form												
Terminals separator				Vertical rear segregation				Vertical side segregation				F 2a - 3a*				F 3b (for form 4b order the double of the vertical rear and side segregations)				Segregation Form				
D (mm)	500	700	900	Without upright				With upright				D (mm)				D (mm)				F 2a - 3a*				
D (mm)	500	700	900	Bars side	Exits side	500	700	900	Bars side	Exits side	500	PPV2400	PVDT6401	PVDT6405	PVDT6404	PPV2450	PRVS2062	PLVS202	PLVS2072	PLVS2092	PRVS2080	PPV2400	PRVS2081	PRVS2082
PSHS6050	PSHS6050	PSHS6050	PSHS6050	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PSHS1908	PSHS1908	PSHS1908	PSHS1908	PSHS1908	PSHS8050	PSHS8050	PSHS8050	PSHS8050	PSHS8050	PSHS8050	PSHS8050	PSHS8050
PSHS6070	PSHS6070	PSHS6070	PSHS6070	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PSHS1908	PSHS1908	PSHS1908	PSHS1908	PSHS1908	PSHS8070	PSHS8070	PSHS8070	PSHS8070	PSHS8070	PSHS8070	PSHS8070	PSHS8070
PSHS6090	PSHS6090	PSHS6090	PSHS6090	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PSHS1908	PSHS1908	PSHS1908	PSHS1908	PSHS1908	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600
PRVS2260	PRVS2260	PRVS2260	PRVS2260	PRVS2260	PRVS2260	PRVS2260	PRVS2260	PRVS2260	PRVS2260	PRVS2260	PRVS2260	PSHS1908	PSHS1908	PSHS1908	PSHS1908	PSHS1908	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600
PRVS2261	PRVS2261	PRVS2261	PRVS2261	PRVS2261	PRVS2261	PRVS2261	PRVS2261	PRVS2261	PRVS2261	PRVS2261	PRVS2261	PSHS1908	PSHS1908	PSHS1908	PSHS1908	PSHS1908	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600
PRVS2262	PRVS2262	PRVS2262	PRVS2262	PRVS2262	PRVS2262	PRVS2262	PRVS2262	PRVS2262	PRVS2262	PRVS2262	PRVS2262	PSHS1908	PSHS1908	PSHS1908	PSHS1908	PSHS1908	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600
PLVS2252	PLVS2252	PLVS2252	PLVS2252	PLVS2252	PLVS2252	PLVS2252	PLVS2252	PLVS2252	PLVS2252	PLVS2252	PLVS2252	PSHS1908	PSHS1908	PSHS1908	PSHS1908	PSHS1908	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600
PLVS2272	PLVS2272	PLVS2272	PLVS2272	PLVS2272	PLVS2272	PLVS2272	PLVS2272	PLVS2272	PLVS2272	PLVS2272	PLVS2272	PSHS1908	PSHS1908	PSHS1908	PSHS1908	PSHS1908	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600
PLVS2292	PLVS2292	PLVS2292	PLVS2292	PLVS2292	PLVS2292	PLVS2292	PLVS2292	PLVS2292	PLVS2292	PLVS2292	PLVS2292	PSHS1908	PSHS1908	PSHS1908	PSHS1908	PSHS1908	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600
PVDT6414	PVDT6414	PVDT6414	PVDT6414	PVDT6414	PVDT6414	PVDT6414	PVDT6414	PVDT6414	PVDT6414	PVDT6414	PVDT6414	PPV2450	PPV2450	PPV2450	PPV2450	PPV2450	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600
PVDT6412	PVDT6412	PVDT6412	PVDT6412	PVDT6412	PVDT6412	PVDT6412	PVDT6412	PVDT6412	PVDT6412	PVDT6412	PVDT6412	PSHS1908	PSHS1908	PSHS1908	PSHS1908	PSHS1908	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600
PVDT6414	PVDT6414	PVDT6414	PVDT6414	PVDT6414	PVDT6414	PVDT6414	PVDT6414	PVDT6414	PVDT6414	PVDT6414	PVDT6414	PSHS1908	PSHS1908	PSHS1908	PSHS1908	PSHS1908	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600	PRVS0600

Key:

F fixed
 F - I fixed interlocked
 F - I-MO fixed interlocked motor-operated
 F - MO fixed motor-operated
 F - RC fixed with residual current
 F - RHD fixed with Direct Rotary Handle

F & F - I fixed and fixed interlocked
 P plug-in
 P - I plug-in interlocked
 P - I-MO plug-in interlocked motor-operated
 P - MO plug-in motor-operated
 P - RC plug-in with residual current
 P - RHD plug-in with Direct Rotary Handle

W withdrawable
 W - I withdrawable interlocked
 W - I-MO withdrawable interlocked motor-operated
 W - MO withdrawable motor-operated
 W - RC withdrawable with residual current
 W - RHD withdrawable with Direct Rotary Handle
 W & W - I withdrawable and withdrawable interlocked

Internal kits

Quick selection guides

Tmax T7

HORIZONTAL INSTALLATION

Cell height (mm)	No. of poles	Execution	No. of breakers per cell	W=400mm			W=600mm					
				Segregation form		Base kit (segregation form 1)	F 4b Rear cubicle			Segregation form		
Front/Rear terminals			F 2a - 3a*		F 3b	Base kit (segregation form 1)	Mounting position			F 2a - 3a*		
				D (mm)			P0/P1	P0	P1	P2		
				500	700	900	500	700	900	Front	Rear	
300	3	F	1									PHCT7329
	3	F-I	1									PHCT7329
	3	F-I-MO	1									PHCT7329
	3	F-MO	1									PHCT7329
	3	F-RHD	1									PHCT7329
350	3/4	F	1									PHCT7420
	3/4	F-MO	1									PHCT7420
	3/4	F-RHD	1									PHCT7420
400	3/4	F-I	1									PHCT7418
	3/4	F-I-MO	1									PHCT7418
500	3/4	W ⁽²⁾	1									PHCT7430
	3/4	W-I ⁽²⁾	1									PHCT7430
	3/4	W-I-MO ⁽²⁾	1									PHCT7430
	3/4	W-MO ⁽²⁾	1									PHCT7430
	3/4	W-RHD ⁽²⁾	1									PHCT7430

VERTICAL INSTALLATION

Cell height (mm)	No. of poles	Execution	No. of breakers per cell	W=400mm			W=600mm				
				Segregation form		Base kit (segregation form 1)	Vertical rear segregation			Base kit (segregation form 1)	
Front/Rear terminals			F 2a - 3a*		F 3b (for form 4b order the double of the vertical rear and side segregations)	Base kit (segregation form 1)	With upright			Base kit (segregation form 1)	
				D (mm)				Bars side	Exits side	D (mm)	
				500	700	900		500	700	900	
450	3/4	F	1								PVCT7419
	3/4	F-I	1								PVCT7419
	3/4	F-I-MO	1								PVCT7419
	3/4	F-MO	1								PVCT7419
500	3/4	W ⁽²⁾	2								-
	3/4	W-MO ⁽²⁾	2								-
	3/4	W ⁽²⁾	1								PVCT7413
	3/4	W-I ⁽²⁾	1								PVCT7413
	3/4	W-I-MO ⁽²⁾	1								PVCT7413
	3/4	W-MO ⁽²⁾	1								PVCT7413

⁽²⁾ Solo attacchi posteriori

* Mandatory everytime that the breaker kits have plates distant more than 38mm or for segregations form 4b.

W=800									
F 4b Rear cubicle					Segregation form F 2a - 3a* F 3b				
Mounting position					Base kit (segregation form 1)				
P0/P1 P0 P1 P2					Cell side closing				
breaker terminals					Universal horizontal shelf:				
D (mm)	500	700	900	Front	Rear	500	700	900	500
PLVS4052	PLVS3552	PLVS3052	PCVS0306	PCVS1306	PCVS2306	PHDT7329	PPVS2300	PSHS1908	PCVS0308
PLVS4072	PLVS3572	PLVS3072	PCVS0306	PCVS1306	PCVS2306	PHDT7329	PSVS3050	PSVS3050	PCVS1308
PLVS5092	PLVS4092	PLVS3592	PCVS0306	PCVS1306	PCVS2306	PHDT7329	PSVS3070	PSVS3070	PCVS1308
			PCVS0306	PCVS1306	PCVS2306	PHDT7329	PSVS3090	PSVS3090	PCVS1308
			PCVS0356	PCVS1356	PCVS2356	PHDT7420	PRVS3081	PRVS3081	PCVS0308
			PCVS0356	PCVS1356	PCVS2356	PHDT7420	PSVS4050	PSVS4050	PCVS1308
			PCVS0356	PCVS1356	PCVS2356	PHDT7420	PSVS4070	PSVS4070	PCVS1358
			PCVS0406	PCVS1406	PCVS2406	PHDT7418	PSHW5081	PSHS1908	PCVS0358
			PCVS0406	PCVS1406	PCVS2406	PHDT7418	PPVS2400	PPVS2350	PCVS0358
				PCVS5060		PHDT7430	PSVS0055	PSVS3550	PCVS0358
				PCVS5060		PHDT7430	PSVS0057	PSVS3590	PCVS1358
				PCVS5060		PHDT7430	PRVS4081	PRVS3581	PCVS1358
				PCVS5060		PHDT7430	PLVS4052	PLVS3552	PCVS2358
				PCVS5060		PHDT7430	PLVS4072	PLVS3572	PCVS2358
				PCVS5060		PHDT7430	PLVS5092	PLVS3592	PCVS0408
				PCVS5060		PHDT7430			PCVS1408

Key:

F	fixed
F - I	fixed interlocked
F - I-MO	fixed interlocked motor-operated
F - MO	fixed motor-operated
F - RC	fixed with residual current
F - RHD	fixed with Direct Rotary Handle

F & F - I	fixed and fixed interlocked
P	plug-in
P - I	plug-in interlocked
P - I-MO	plug-in interlocked motor-operated
P - MO	plug-in motor-operated
P - RC	plug-in with residual current
P - RHD	plug-in with Direct Rotary Hand

W	withdrawable
W - I	withdrawable interlocked
W - I-MO	withdrawable interlocked motor-operated
W - MO	withdrawable motor-operated
W - RC	withdrawable with residual current
W - RHD	withdrawable with Direct Rotary Handle
W & W - I	withdrawable and withdrawable interlocked

Internal kits

Quick selection guides

Emax E1.2

HORIZONTAL INSTALLATION

W=400mm			W=600mm		
Segregation form			Segregation form		
F 2a - 3a*		F 3b	F 4b		F 2a - 3a*
Cell height (mm)	No. of poles	Execution	Base kit (segregation form 1)	Terminals separator	Base kit (segregation form 1)
			Cell side closing	D (mm)	Cell side closing
			Universal horizontal shelf	500 700 900	Universal horizontal shelf
			Rear segregation bars side		Rear segregation bars side
Front/Rear terminals					
400	3/4	F	1		PHCE1241
	3/4	F-I	1		PHCE1241
500	3/4	W ⁽²⁾	1		PHCE1240
	3/4	W-I ⁽²⁾	1		PHCE1240
					PSHW5061
					PPVS2400
					PSHS1906
					PSV/S4050
					PSV/S4070
					PSV/S035
					PSV/S057
					PSV/S4090
					PRVS4061
					PRVS5061

VERTICAL INSTALLATION

W=400mm			W=600mm		
Segregation form			Segregation form		
F 2a - 3a*		F 3b (for form 4b order the double of the vertical rear and side segregations)	Vertical rear segregation		F 2a - 3a*
Cell height (mm)	No. of poles	Execution	Base kit (segregation form 1)	Terminals separator	Base kit (segregation form 1)
			Cell side closing	D (mm)	Cell side closing
			Universal horizontal shelf	500 700 900	Universal horizontal shelf
			Vertical side segregation		Vertical side segregation
Front/Rear terminals					
450	3/4	F	2	-	PLVS2252
	3/4	F	1	PVBE1241	PLVS2272
	3/4	F-I	1	PVBE1241	PLVS2292
500	3/4	W ⁽²⁾	2	-	PVCE1241
	3/4	W ⁽²⁾	1	-	PVCE1241
	3/4	W-I ⁽²⁾	1	-	PSVW5061
					PVCE1240
					PSHS1906

⁽²⁾ Solo attacchi posteriori.

* Mandatory everytime that the breaker kits have plates distant more than 38mm or for segregations form 4b

Key:

F	fixed
F - I	fixed interlocked
F - I-MO	fixed interlocked motor-operated
F - MO	fixed motor-operated
F - RC	fixed with residual current
F - RHD	fixed with Direct Rotary Handle

F & F - I	fixed and fixed interlocked
P	plug-in
P - I	plug-in interlocked
P - I-MO	plug-in interlocked motor-operated
P - MO	plug-in motor-operated
P - RC	plug-in with residual current
P - RHD	plug-in with Direct Rotary Handle

W	withdrawable
W - I	withdrawable interlocked
W - I-MO	withdrawable interlocked motor-operated
W - MO	withdrawable motor-operated
W - RC	withdrawable with residual current
W - RHD	withdrawable with Direct Rotary Handle
W & W - I	withdrawable and withdrawable interlocked

Internal kits

Quick selection guides

Emax E2.2

VERTICAL INSTALLATION

		W=400mm			W=600mm		
		Segregation form			Segregation form		
		F 2a - 3a*			F 2a - 3a*		
Cell height (mm)	No. of poles	No. of breakers per cell	Base kit (segregation form 1)	No.2 horizontal shelves No.1 back plate No.2 side shelves	Terminals separator	Vertical rear segregation	Vertical side segregation
					D (mm)	Without upright	With upright
					500 700 900		D (mm)
						Bars side	Exits side
Front/Rear terminals							
600	3/4	F	1				PVCE2441
	3/4	F - I	1				PVCE2441
	3/4	W	1				PVCE2450
	3/4	W - I	1				PVCE2450
							PSY/W6062

* Mandatory everytime that the breaker kits have plates distant more than 38mm or for segregations form 4b

Emax E4.2

VERTICAL INSTALLATION

		W=400mm			W=600mm		
		Segregation form			Segregation form		
		F 2a - 3a*			F 2a - 3a*		
Cell height (mm)	No. of poles	No. of breakers per cell	Base kit (segregation form 1)	No.2 horizontal shelves No.1 back plate No.2 side shelves	Terminals separator	Vertical rear segregation	Vertical side segregation
					D (mm)	Without upright	With upright
					500 700 900		D (mm)
						Bars side	Exits side
Front/Rear terminals							
600	3/4	F	1				PVCE2442
	3/4	F - I	1				-
	3	W	1				PVCE4350
	3	W - I	1				PVCE4350
	3/4	W	1				-
	3/4	W - I	1				-
							PSY/W6062

* Mandatory everytime that the breaker kits have plates distant more than 38mm or for segregations form 4b

Key:

F	fixed
F - I	fixed interlocked
F - I-MO	fixed interlocked motor-operated
F - MO	fixed motor-operated
F - RC	fixed with residual current
F - RHD	fixed with Direct Rotary Handle

F & F - I	fixed and fixed interlocked
P	plug-in
P - I	plug-in interlocked
P - I-MO	plug-in interlocked motor-operated
P - MO	plug-in motor-operated
P - RC	plug-in with residual current
P - RHD	plug-in with Direct Rotary Handle

W	withdrawable
W - I	withdrawable interlocked
W - I-MO	withdrawable interlocked motor-operated
W - MO	withdrawable motor-operated
W - RC	withdrawable with residual current
W - RHD	withdrawable with Direct Rotary Handle
W & W - I	withdrawable and withdrawable interlocked

Internal kits

Quick selection guides

Emax E6.2

VERTICAL INSTALLATION

W=1000mm										W=1250mm															
Cell height (mm)	No. of poles	Execution	No. of breakers per cell	Base kit (segregation form 1)	Segregation form										Segregation form										
					F 2a - 3a* F 3b (for form 4b order the double of the vertical rear and side segregations)										F 2a - 3a* F 3b (for form 4b order the double of the vertical rear and side segregations)										
					Vertical rear segregation	Vertical side segregation	With upright		Without upright		Vertical rear segregation		Vertical side segregation	With upright		Without upright		Vertical rear segregation		Vertical side segregation					
No.2 horizontal shelves					No.1 back plate	No.2 side shelves	D (mm)		D (mm)		D (mm)		D (mm)		D (mm)		D (mm)		D (mm)						
No.2 horizontal shelves					500	700	900	Without upright		Without upright		Bars side		Exits side		500		700		900					
Front/Rear terminals																									
700	3/4 HS	F	1	PVFE6231												-	PVGE6231								
	4 FS	F	1	-												-	PSVF7126								
	3	F - I	1	PVFE6231	PSVF7016											-	PSHF1296								
	4 HS/FS	F - I	1	-												PRVS3501									
	3	W	1	PVFE6230																					
	4 HS/FS	W	1	-																					
	3	W - I	1	PVFE6230	PSVW7016																				
	4 HS/FS	W - I	1	-																					

* Mandatory everytime that the breaker kits have plates distant more than 38mm or for segregations form 4b

OT
 VERTICAL INSTALLATION

Cell height (mm)	Switch	W=600mm						W=800mm						Segregation Form					
		No. of poles	Execution	Accessory	No. of switches per cell	Handle maximum lenght (mm)	Shaft minimum lenght (mm)	Lever position	Base kit (segregation form 1)	High terminals covers	Cell side closing	Universal horizontal shelf	Base kit (segregation form 1)	High terminals covers	Cell side closing	Universal horizontal shelf	F 2a - 3a*	F 2a - 3a*	F 2a - 3a*
Attacchi anteriori																			
250	OTEV 160	3/4	F	RHE	1	80 (Ø6)	130 (Ø6)	E03-E04	PKOH1660	SI	PPVS2250	PSHS1906	PKOH1680	SI	PPVS2250	PSHS1908			
	OT 200	3/4	F	RHE	1	80 (Ø6)	130 (Ø6)	E03-E04	PKOH1660	SI	PPVS2250	PSHS1906	PKOH1680	SI	PPVS2250	PSHS1908			
	OT 250	3/4	F	RHE	1	80 (Ø6)	130 (Ø6)	E03-E04	PKOH1660	SI	PPVS2250	PSHS1906	PKOH1680	SI	PPVS2250	PSHS1908			
300	OT 315	3/4	F	RHE	1	175 (Ø12)	95 (Ø12)	E03-E04	PKOH3160	SI	PPVS2300	PSHS1906	PKOH3180	SI	PPVS2300	PSHS1908			
	OT 400	3/4	F	RHE	1	175 (Ø12)	95 (Ø12)	E03-E04	PKOH3160	SI	PPVS2300	PSHS1906	PKOH3180	SI	PPVS2300	PSHS1908			
500	OT 630	3/4	F	RHE	1	175 (Ø12)	70 (Ø12)	E03-E04	PKOH6360	SI	PPVS2500	PSHS1906	PKOH6380	SI	PPVS2500	PSHS1908			
	OT 800	3/4	F	RHE	1	175 (Ø12)	70 (Ø12)	E03-E04	PKOH6360	SI	PPVS2500	PSHS1906	PKOH6380	SI	PPVS2500	PSHS1908			
600	OT 1000	3/4	F ⁽¹⁾	RHE	1	175 (Ø12)	170 (Ø12)	E12-E22	PKOH1060	NO			PKOH1080	SI	PPVS2600	PSHS1908			
	OT 1250	3/4	F ⁽¹⁾	RHE	1	175 (Ø12)	170 (Ø12)	E12-E22	PKOH1060	NO			PKOH1080	SI	PPVS2600	PSHS1908			
	OT 1600	3/4	F ⁽¹⁾	RHE	1	175 (Ø12)	170 (Ø12)	E12-E22	PKOH1060	NO			PKOH1080	SI	PPVS2600	PSHS1908			

HORIZONTAL INSTALLATION

Cell height (mm)	Switch	W=600mm						W=800mm						Segregation Form					
		No. of poles	Execution	Accessory	No. of switches per cell	Handle maximum lenght (mm)	Shaft minimum lenght (mm)	Lever position	Base kit (segregation form 1)	High terminals covers	Cell side closing	Universal horizontal shelf	Base kit (segregation form 1)	High terminals covers	Cell side closing	Universal horizontal shelf	F 2a - 3a*	F 2a - 3a*	F 2a - 3a*
Attacchi anteriori																			
250	OTEV 160	3/4	F	RHE	1	80 (Ø6)	130 (Ø6)	E03-E04	PKOV1660	SI	PPVS2350	PSHS1906	PKOV1680	SI	PPVS2350	PSHS1908			
	OT 200	3/4	F	RHE	1	80 (Ø6)	130 (Ø6)	E03-E04	PKOV1660	SI	PPVS2350	PSHS1906	PKOV1680	SI	PPVS2350	PSHS1908			
	OT 250	3/4	F	RHE	1	80 (Ø6)	130 (Ø6)	E03-E04	PKOV1660	SI	PPVS2350	PSHS1906	PKOV1680	SI	PPVS2350	PSHS1908			
300	OT 315	3/4	F	RHE	1	175 (Ø12)	95 (Ø12)	E03-E04	PKOV3160	SI	PPVS2450	PSHS1906	PKOV3180	SI	PPVS2450	PSHS1908			
	OT 400	3/4	F	RHE	1	175 (Ø12)	95 (Ø12)	E03-E04	PKOV3160	SI	PPVS2450	PSHS1906	PKOV3180	SI	PPVS2450	PSHS1908			
500	OT 630	3/4	F	RHE	1	175 (Ø12)	70 (Ø12)	E03-E04	PKOV6360	SI	PPVS2500	PSHS1906	PKOV6380	SI	PPVS2500	PSHS1908			
	OT 800	3/4	F	RHE	1	175 (Ø12)	70 (Ø12)	E03-E04	PKOV6360	SI	PPVS2500	PSHS1906	PKOV6380	SI	PPVS2500	PSHS1908			
600	OT 1000	3/4	F ⁽¹⁾	RHE	1	175 (Ø12)	170 (Ø12)	E12-E22	PKOV1060	SI	PPVS2600	PSHS1906	PKOV1080	SI	PPVS2600	PSHS1908			
	OT 1250	3/4	F ⁽¹⁾	RHE	1	175 (Ø12)	170 (Ø12)	E12-E22	PKOV1060	SI	PPVS2600	PSHS1906	PKOV1080	SI	PPVS2600	PSHS1908			
	OT 1600	3/4	F ⁽¹⁾	RHE	1	175 (Ø12)	170 (Ø12)	E12-E22	PKOV1060	SI	PPVS2600	PSHS1906	PKOV1080	SI	PPVS2600	PSHS1908			

⁽¹⁾ kit with recessed mounting plate

* Mandatory everytime that the breaker kits have plates distant more than 38mm or for segregations form 4b

Key:	F & F - I	fixed and fixed interlocked	W	withdrawable
F - I	fixed interlocked	plug-in	W - I	withdrawable interlocked
F - I-MO	fixed interlocked motor-operated	plug-in interlocked	W - I-MO	withdrawable interlocked motor-operated
F - MO	fixed motor-operated	plug-in motor-operated	W - MO	withdrawable motor-operated
F - RC	fixed with residual current	plug-in with residual current	W - RC	withdrawable with residual current
F - RHD	fixed with Direct Rotary Handle	plug-in with Direct Rotary Handle	W - RHD	withdrawable with Direct Rotary Handle
			W & W - I	withdrawable and withdrawable interlocked

Internal kits

Quick selection guides

DIN RAIL

HORIZONTAL SEGREGATION

		W=400mm			W=600mm				
		Segregation form			Segregation form				
		F 2a - 3a*	F 3b					F 2a - 3a*	
Cell height (mm)	Panel	DIN rail kit (segregation form 1)	Cell side closing Front segregations	Universal horizontal shelf	Terminals separator	Rear segregation bars side	Side rear segregation	DIN rail kit (segregation form 1)	Segregation form
					D (mm)		D (mm)		
					500 700 900		500 700 900		
150	PPMF1540	PDRS0400	PPDS0200 + PFVS2042	PSHS1904	PRVS2070	PRVS2041	PLVS2052	PPMF1560 PDRS0600	Cell side closing Front segregations
200	PPMF2040	PDRS0400			PSVS2070		PLVS2072	PPMF2060 PDRS0600	Universal horizontal shelf
300							PLVS2092		
	PPMF3040	2xPDRS0400						PPMU3060 PDRS0600	
	PPMD3040	PDRS0400						PPMF3060 2xPDRS0600	
								PPMD3060 PDRS0600	

VERTICAL SEGREGATION

		W=400mm			W=600mm				
		Segregation form			Segregation form				
		F 2a - 3a*	F 3b					F 2a - 3a*	
Cell height (mm)	Panel	DIN rail kit (segregation form 1)	Cell side closing Front segregations	Universal horizontal shelf	Without upright	Vertical rear segregation	Vertical side segregation	DIN rail kit (segregation form 1)	Segregation form
						With upright			
							D (mm)		
						Bars side	Exits side	500 700 900	
150	PPMF1540	PDRS0400	PPDS0200 + PFVS2042	PSHS1904	PRVS2040		PLVS2052	PPMF1560 PDRS0600	Cell side closing Front segregations
200	PPMF2040	PDRS0400			PRVS2041		PLVS2072	PPMF2060 PDRS0600	Universal horizontal shelf
300							PLVS2092		
	PPMF3040	2xPDRS0400						PPMU3060 PDRS0600	
	PPMD3040	PDRS0400						PPMF3060 2xPDRS0600	
								PPMD3060 PDRS0600	

* Mandatory everytime that the breaker kits have plates distant more than 38mm or for segregations form 4b

W=800mm											
F 3b				Segregation form							
Terminals separator			Rear segregation bars side			Side rear segregation			F 2a - 3a*		
D (mm)	500	700	900	D (mm)	500	700	900	Panel	DIN rail kit (segregation form 1)		
PSVS2050				PRVS2041				PPMF1580	PDRS0800	Cell side closing	
PSVS2070				PLVS2052				PPMF2080	PDRS0800	Front segregation	
PSVS2090				PLVS2072				PPMU3080	PDRS0800	Universal horizontal shelf	
				PLVS2092				PPMF3080	2xPDRS0800		
								PPMD3080	PDRS0800		

W=800mm												
F 3b				Segregation form								
Vertical rear segregation			Vertical side segregation			F 2a - 3a*			F 3b			
Without upright	With upright			D (mm)			With upright			Vertical rear segregation		
	Bars side	Exits side		500	700	900	Without upright	Bars side	Exits side	500	700	900
PRVS2060				PRVS2061			PRVS2062			PLVS2052		
				PLVS2072			PLVS2092			PPMF1580	PDRS0800	Cell side closing
							PPMF2080	PDRS0800		PPDS0200 + PFS2082		Front segregation
							PPMU3080	PDRS0800		PSHS1908		Universal horizontal shelf
							PPMF3080	2xPDRS0800				
							PPMD3080	PDRS0800				

Key:
 F fixed
 F - I fixed interlocked
 F - I-MO fixed interlocked motor-operated
 F - MO fixed motor-operated
 F - RC fixed with residual current
 F - RHD fixed with Direct Rotary Handle

F & F - I fixed and fixed interlocked
 P plug-in
 P - I plug-in interlocked
 P - I-MO plug-in interlocked motor-operated
 P - MO plug-in motor-operated
 P - RC plug-in with residual current
 P - RHD plug-in with Direct Rotary Handle

W withdrawable
 W - I withdrawable interlocked
 W - I-MO withdrawable interlocked motor-operated
 W - MO withdrawable motor-operated
 W - RC withdrawable with residual current
 W - RHD withdrawable with Direct Rotary Handle
 W & W - I withdrawable and withdrawable interlocked

Internal kits

Quick selection guides

Blind mounting plate

HORIZONTAL SEGREGATION

W=400mm				W=600mm				W=800mm				
Segregation form				Segregation form				Segregation form				
	F 2a - 3a*	F 3b		F 2a - 3a*	F 3b		F 2a - 3a*	F 3b		F 2a - 3a*	F 3b	
Cell height (mm)	Plate (segregation form 1)			Plate (segregation form 1)			Plate (segregation form 1)			Plate (segregation form 1)		
150	PPMB1540		PPVS2300	PPVS2200	2xPPRS0150	Cell side dosing	PSHS1904	PSHS1904	Universal horizontal shelf	PSHS1904		Universal horizontal shelf
200	PPMB2040		PPVS2500	PPVS2400	PSHS1904	PSHS1904	PSVS3050	PSVS2950	PSVS2050	PSVS3050		PSVS2050
250	PPMB2540		PPVS2500	PPVS2400	PSHS1904	PSHS1904	PSVS3070	PSVS2570	PSVS22070	PSVS3070		PSVS22070
300	PPMB3040		PPVS2500	PPVS2400	PSHS1904	PSHS1904	PSVS3090	PSVS2590	PSVS2290	PSVS3090		PSVS2290
350							PRVS041	PRVS2541	PRVS2041	PRVS041		Rear segregation bars side
400	PPMB4040		PPVS2500	PPVS2400	PSHS1904	PSHS1904	PLVS3052	PLVS2552	PLVS2052	PLVS3052		Side rear segregation
500	PPBM5004		PPVS2600	PPVS2500	PSHS1904	PSHS1904	PLVS5072	PLVS2572	PLVS2072	PLVS5072		D (mm)
600	PPMB6040		PPVS2600	PPVS2500	PSHS1904	PSHS1904	PLVS5092	PLVS2592	PLVS2092	PLVS5092		500 700 900
							PPMB1560	PPMB2060	PPMB2060	PPMB1560		500 700 900
							PPVS2300	PPVS2290	PPVS2290	PPVS2300		500 700 900
							PSHS1906	PSHS1906	PSHS1906	PSHS1906		500 700 900
							PSVS3050	PSVS2550	PSVS2050	PSVS3050		500 700 900
							PSVS3070	PSVS2570	PSVS2070	PSVS3070		500 700 900
							PSVS3090	PSVS2590	PSVS2090	PSVS3090		500 700 900
							PRVS061	PRVS2561	PRVS2061	PRVS061		500 700 900
							PLVS5052	PLVS2552	PLVS2052	PLVS5052		500 700 900
							PLVS5072	PLVS2572	PLVS2072	PLVS5072		500 700 900
							PLVS5092	PLVS2592	PLVS2092	PLVS5092		500 700 900
							PPMB3060	PPMB2560	PPMB2060	PPMB3060		500 700 900
							PPVS2300	PPVS2290	PPVS2290	PPVS2300		500 700 900
							PSHS1906	PSHS1906	PSHS1906	PSHS1906		500 700 900
							PSVS3050	PSVS2550	PSVS2050	PSVS3050		500 700 900
							PSVS3070	PSVS2570	PSVS2070	PSVS3070		500 700 900
							PSVS3090	PSVS2590	PSVS2090	PSVS3090		500 700 900
							PRVS061	PRVS2561	PRVS2061	PRVS061		500 700 900
							PLVS5052	PLVS2552	PLVS2052	PLVS5052		500 700 900
							PLVS5072	PLVS2572	PLVS2072	PLVS5072		500 700 900
							PLVS5092	PLVS2592	PLVS2092	PLVS5092		500 700 900
							PPMB3080	PPMB2580	PPMB2080	PPMB3080		500 700 900
							PPVS2300	PPVS2290	PPVS2290	PPVS2300		500 700 900
							PSHS1908	PSHS1908	PSHS1908	PSHS1908		500 700 900
							PSVS3050	PSVS2550	PSVS2050	PSVS3050		500 700 900
							PSVS3070	PSVS2570	PSVS2070	PSVS3070		500 700 900
							PSVS3090	PSVS2590	PSVS2090	PSVS3090		500 700 900

* Mandatory everytime that the breaker kits have plates distant more than 38mm or for segregations form 4b

		W=1000mm			W=1250mm		
		Segregation form		Segregation form			
		F 2a - 3a*	F 3b	F 2a - 3a*	F 3b		
		D (mm)		D (mm)		D (mm)	
		500	700	500	700	500	700
PRVS6081	PRVS5081	PRVS3081	PRVS2081	PRVS3081	PRVS2081	PRVS3081	PRVS2081
PLVS6052	PLVS5052	PLVS3052	PLVS2052	PLVS3052	PLVS2052	PLVS3052	PLVS2052
PLVS6072	PLVS5072	PLVS3072	PLVS2072	PLVS3072	PLVS2072	PLVS3072	PLVS2072
PLVS6092	PLVS5092	PLVS3092	PLVS2092	PLVS3092	PLVS2092	PLVS3092	PLVS2092
		Plate (segregation form 1)		Plate (segregation form 1)		Plate (segregation form 1)	
		PPMB3010		PPMB2010		PPMB2012	
		PPVS2300	PPVS2300	PPVS2300	PPVS2300	PPVS2300	PPVS2300
		PSHS1901	PSHS1901	PSHS1901	PSHS1901	PSHS1901	PSHS1901
		PSVS5050	PSVS4050	PSVS3050	PSVS2050	PSVS3050	PSVS2050
		PSVS6070	PSVS5070	PSVS4070	PSVS3070	PSVS2070	PSVS3070
		PSVS6090	PSVS5090	PSVS4090	PSVS3090	PSVS2090	PSVS3090
		PPBM5001		PPMB6010		PPMB2512	
		PPVS2500	PPVS2400	PPVS2300	PPVS2300	PPVS2300	PPVS2300
		PSHS1901	PSHS1901	PSHS1901	PSHS1901	PSHS1901	PSHS1901
		PSVS5050	PSVS4050	PSVS3050	PSVS2050	PSVS3050	PSVS2050
		PSVS6070	PSVS5070	PSVS4070	PSVS3070	PSVS2070	PSVS3070
		PSVS6090	PSVS5090	PSVS4090	PSVS3090	PSVS2090	PSVS3090
		PPMB3012		PPMB3012		PPMB2512	
		PLVS3052	PLVS4052	PLVS3052	PLVS2052	PLVS3052	PLVS2052
		PLVS6072	PLVS5072	PLVS4072	PLVS3072	PLVS2072	PLVS3072
		PLVS6092	PLVS5092	PLVS4092	PLVS3092	PLVS2092	PLVS3092
		PPMB3512		PPMB3512		PPMB2512	
		PPVS3350	PPVS2350	PPVS3350	PPVS2350	PPVS3350	PPVS2350
		PSVS3550	PSVS3050	PSVS3550	PSVS2050	PSVS3550	PSVS2050
		PSVS3570	PSVS3070	PSVS3570	PSVS2070	PSVS3570	PSVS2070
		PSVS3590	PSVS3090	PSVS3590	PSVS2090	PSVS3590	PSVS2090
		PPMB3012		PPMB3012		PPMB2512	
		PPVS2300	PPVS2300	PPVS2300	PPVS2300	PPVS2300	PPVS2300
		Cell side closing		Cell side closing		Cell side closing	
		Universal horizontal shelf		Universal horizontal shelf		Universal horizontal shelf	
		Rear segregation bars side		Rear segregation bars side		Rear segregation bars side	
		Side rear segregation		Side rear segregation		Side rear segregation	
		D (mm)		D (mm)		D (mm)	
		500		500		500	
		700		700		700	
		900		900		900	

Key:

F fixed
F - I fixed interlocked
F - I-MO fixed interlocked motor-operated
F - MO fixed motor-operated
F - RC fixed with residual current
F - RHD fixed with Direct Rotary Handle

F & F - I fixed and fixed interlocked
F - I plug-in interlocked
P - I plug-in interlocked
P - I-MO plug-in interlocked motor-operated
P - MO plug-in motor-operated
P - RC plug-in with residual current
P - RHD plug-in with Direct Rotary Handle

W withdrawable
W - I withdrawable interlocked
W - I-MO withdrawable interlocked motor-operated
W - MO withdrawable motor-operated
W - RC withdrawable with residual current
W - RHD withdrawable with Direct Rotary Handle
W & W - I withdrawable and withdrawable interlocked

Internal kits

Quick selection guides

Blind mounting plate

VERTICAL SEGREGATION

		W=400mm		W=600mm		W=800mm	
		Segregation form		Segregation form		Segregation form	
		F 2a - 3a*	F 3b	F 2a - 3a*	F 3b	F 2a - 3a*	
		Vertical rear segregation	Vertical side segregation	Vertical rear segregation	Vertical side segregation	Vertical rear segregation	
		With upright					
		Bars side	Exits side	Bars side	Exits side	Bars side	
		D (mm)		D (mm)		D (mm)	
150	PPMB1540	PPVS2200	PPVS2250	PPVS2200	PPVS2250	PPVS2200	PPVS2250
200	PPMB2040	PPVS2300	PSHS1904	PSHS1904	PRVS2040	PRVS1582	PRVS1582
250	PPMB2540	PPVS2300	PSHS1904	PSHS1904	PLVS2552	PLVS2552	PLVS2552
300	PPMB3040	PPVS2300	PSHS1904	PSHS1904	PLVS3052	PLVS3052	PLVS3052
350					PLVS3072	PLVS3072	PLVS3072
400	PPMB4040	PPVS2400	PSHS1904	PSHS1904	PLVS4092	PLVS4092	PLVS4092
500	PPBM5004	PPVS2500	PSHS1904	PSHS1904	PPBM5006	PPBM5006	PPBM5006
600	PPMB6040	PPVS2600	PSHS1904	PSHS1904	PPMB6060	PPMB6060	PPMB6060
					PPVS2600	PPVS2600	PPVS2600
					PSHS1906	PSHS1906	PSHS1906
					PRVS3060	PRVS3060	PRVS3060
					PLVS6052	PLVS6052	PLVS6052
					PLVS6072	PLVS6072	PLVS6072
					PLVS6092	PLVS6092	PLVS6092
					PPMB4060	PPMB4060	PPMB4060
					PPVS2400	PPVS2400	PPVS2400
					PSHS1906	PSHS1906	PSHS1906
					PRVS3061	PRVS3061	PRVS3061
					PRVS3062	PRVS3062	PRVS3062
					PLVS5052	PLVS5052	PLVS5052
					PLVS5072	PLVS5072	PLVS5072
					PLVS5092	PLVS5092	PLVS5092
					PPMB2060	PPMB2060	PPMB2060
					PPVS2200	PPVS2200	PPVS2200
					PSHS1906	PSHS1906	PSHS1906
					PRVS2060	PRVS2060	PRVS2060
					PLVS2552	PLVS2552	PLVS2552
					PLVS2572	PLVS2572	PLVS2572
					PLVS2592	PLVS2592	PLVS2592
					PPMB1560	PPMB1560	PPMB1560
					PPVS2200	PPVS2200	PPVS2200
					PSHS1906	PSHS1906	PSHS1906
					PRVS1560	PRVS1560	PRVS1560
					PLVS2552	PLVS2552	PLVS2552
					PLVS2572	PLVS2572	PLVS2572
					PLVS2592	PLVS2592	PLVS2592
					PPMB1580	PPMB1580	PPMB1580
					PPVS2250	PPVS2250	PPVS2250
					PSHS1908	PSHS1908	PSHS1908
					PPMB2080	PPMB2080	PPMB2080
					PPVS2300	PPVS2300	PPVS2300
					PSHS1908	PSHS1908	PSHS1908
					PPMB3080	PPMB3080	PPMB3080
					PPVS2400	PPVS2400	PPVS2400
					PSHS1908	PSHS1908	PSHS1908
					PPMB4080	PPMB4080	PPMB4080
					PPVS2500	PPVS2500	PPVS2500
					PSHS1908	PSHS1908	PSHS1908
					PPMB6080	PPMB6080	PPMB6080
					PPVS2600	PPVS2600	PPVS2600
					PSHS1908	PSHS1908	PSHS1908
					PPMB5008	PPMB5008	PPMB5008
					PPVS2500	PPVS2500	PPVS2500
					PSHS1908	PSHS1908	PSHS1908
					PPMB2080	PPMB2080	PPMB2080
					PPVS2200	PPVS2200	PPVS2200
					PSHS1908	PSHS1908	PSHS1908
					PPMB3080	PPMB3080	PPMB3080
					PPVS2300	PPVS2300	PPVS2300
					PSHS1908	PSHS1908	PSHS1908
					PPMB4080	PPMB4080	PPMB4080
					PPVS2400	PPVS2400	PPVS2400
					PSHS1908	PSHS1908	PSHS1908
					PPMB5008	PPMB5008	PPMB5008
					PPVS2500	PPVS2500	PPVS2500
					PSHS1908	PSHS1908	PSHS1908
					PPMB2080	PPMB2080	PPMB2080
					PPVS2200	PPVS2200	PPVS2200
					PSHS1908	PSHS1908	PSHS1908
					PPMB3080	PPMB3080	PPMB3080
					PPVS2300	PPVS2300	PPVS2300
					PSHS1908	PSHS1908	PSHS1908
					PPMB4080	PPMB4080	PPMB4080
					PPVS2400	PPVS2400	PPVS2400
					PSHS1908	PSHS1908	PSHS1908
					PPMB5008	PPMB5008	PPMB5008
					PPVS2500	PPVS2500	PPVS2500
					PSHS1908	PSHS1908	PSHS1908
					PPMB2080	PPMB2080	PPMB2080
					PPVS2200	PPVS2200	PPVS2200
					PSHS1908	PSHS1908	PSHS1908
					PPMB3080	PPMB3080	PPMB3080
					PPVS2300	PPVS2300	PPVS2300
					PSHS1908	PSHS1908	PSHS1908
					PPMB4080	PPMB4080	PPMB4080
					PPVS2400	PPVS2400	PPVS2400
					PSHS1908	PSHS1908	PSHS1908
					PPMB5008	PPMB5008	PPMB5008
					PPVS2500	PPVS2500	PPVS2500
					PSHS1908	PSHS1908	PSHS1908
					PPMB2080	PPMB2080	PPMB2080
					PPVS2200	PPVS2200	PPVS2200
					PSHS1908	PSHS1908	PSHS1908
					PPMB3080	PPMB3080	PPMB3080
					PPVS2300	PPVS2300	PPVS2300
					PSHS1908	PSHS1908	PSHS1908
					PPMB4080	PPMB4080	PPMB4080
					PPVS2400	PPVS2400	PPVS2400
					PSHS1908	PSHS1908	PSHS1908
					PPMB5008	PPMB5008	PPMB5008
					PPVS2500	PPVS2500	PPVS2500
					PSHS1908	PSHS1908	PSHS1908
					PPMB2080	PPMB2080	PPMB2080
					PPVS2200	PPVS2200	PPVS2200
					PSHS1908	PSHS1908	PSHS1908
					PPMB3080	PPMB3080	PPMB3080
					PPVS2300	PPVS2300	PPVS2300
					PSHS1908	PSHS1908	PSHS1908
					PPMB4080	PPMB4080	PPMB4080
					PPVS2400	PPVS2400	PPVS2400
					PSHS1908	PSHS1908	PSHS1908
					PPMB5008	PPMB5008	PPMB5008
					PPVS2500	PPVS2500	PPVS2500
					PSHS1908	PSHS1908	PSHS1908
					PPMB2080	PPMB2080	PPMB2080
					PPVS2200	PPVS2200	PPVS2200
					PSHS1908	PSHS1908	PSHS1908
					PPMB3080	PPMB3080	PPMB3080
					PPVS2300	PPVS2300	PPVS2300
					PSHS1908	PSHS1908	PSHS1908
					PPMB4080	PPMB4080	PPMB4080
					PPVS2400	PPVS2400	PPVS2400
					PSHS1908	PSHS1908	PSHS1908
					PPMB5008	PPMB5008	PPMB5008
					PPVS2500	PPVS2500	PPVS2500
					PSHS1908	PSHS1908	PSHS1908
					PPMB2080	PPMB2080	PPMB2080
					PPVS2200	PPVS2200	PPVS2200
					PSHS1908	PSHS1908	PSHS1908
					PPMB3080	PPMB3080	PPMB3080
					PPVS2300	PPVS2300	PPVS2300
					PSHS1908	PSHS1908	PSHS1908
					PPMB4080	PPMB4080	PPMB4080
					PPVS2400	PPVS2400	PPVS2400
					PSHS1908	PSHS1908	PSHS1908
					PPMB5008	PPMB5008	PPMB5008
					PPVS2500	PPVS2500	PPVS2500
					PSHS1908	PSHS1908	PSHS1908
					PPMB2080	PPMB2080	PPMB2080
					PPVS2200	PPVS2200	PPVS2200
					PSHS1908	PSHS1908	PSHS1908
					PPMB3080	PPMB3080	PPMB3080
					PPVS2300	PPVS2300	PPVS2300
					PSHS1908	PSHS1908	PSHS1908
					PPMB4080	PPMB4080	PPMB4080
					PPVS2400	PPVS2400	PPVS2400
					PSHS1908	PSHS1908	PSHS1908
					PPMB5008	PPMB5008	PPMB5008
					PPVS2500	PPVS2500	PPVS2500
					PSHS1908	PSHS1908	PSHS1908
					PPMB2080	PPMB2080	PPMB2080
					PPVS2200	PPVS2200	PPVS2200
					PSHS1908	PSHS1908	PSHS1908
					PPMB3080	PPMB3080	PPMB3080
					PPVS2300	PPVS2300	PPVS2300
					PSHS1908	PSHS1908	PSHS1908
					PPMB4080	PPMB4080	PPMB4080
					PPVS2400	PPVS2400	PPVS2400
					PSHS1908	PSHS1908	PSHS1908
					PPMB5008	PPMB5008	PPMB5008
					PPVS2500	PPVS2500	PPVS2500
					PSHS1908	PSHS1908	PSHS1908
					PPMB2080	PPMB2080	PPMB2080
					PPVS2200	PPVS2200	PPVS2200
					PSHS1908	PSHS1908	PSHS1908
					PPMB3080	PPMB3080	PPMB3080
					PPVS2300	PPVS2300	PPVS2300
					PSHS1908	PSHS1908	PSHS1908
					PPMB4080	PPMB4080	PPMB4080
					PPVS2400	PPVS2400	PPVS2400
					PSHS1908	PSHS1908</	

W=1000mm												W=1250mm													
Segregation form												Segregation form													
F 3b						F 2a - 3a*						F 3b						F 2a - 3a*						F 3b	
Vertical rear segregation						Vertical side segregation						Vertical rear segregation						Vertical side segregation						Vertical side segregation	
With upright						D (mm)						With upright						D (mm)						With upright	
Bars side	Exits side					500	700	900				Bars side	Exits side					Bars side	Exits side					Bars side	
PRVS2080	PRVS2080	PRVS1580	PRVS1581	PRVS2081	PRVS2581	PRVS1582	PRVS1582	PLVS2052	PLVS2552	PLVS2072	PLVS2572	PLVS2092	PLVS2592	PPMB2010	PPV2200	PPV2300	PSHS1901	PSHS1901	PRVS2010	PPMB2012	PPMB2512	PPV2200	PPV2250	PPV2300	
PRVS3080	PRVS3080	PLVS4052	PLVS4072	PLVS3072	PLVS2552	PLVS2572	PLVS2092	PPMB3010	PPMB4010	PPV2400	PPV2500	PSHS1901	PSHS1901	PRVS3010	PLVS3052	PLVS3072	PLVS3092	PPMB3012	PPMB3512	PRVS3125	PRVS2125	PRVS3501	PLVS3552	PLVS3572	PLVS3092
PRVS3081	PRVS3081	PLVS5052	PLVS6072	PLVS5072	PLVS4092	PLVS3092	PLVS3092	PPMB3010	PPMB4010	PPV2400	PPV2500	PSHS1901	PSHS1901	PRVS3010	PLVS3052	PLVS3072	PLVS3092	PPMB3012	PPMB3512	PRVS3125	PRVS2125	PRVS3501	PLVS3552	PLVS3572	PLVS3092
PRVS3082	PRVS3082	PLVS5052	PLVS6072	PLVS5072	PLVS4092	PLVS3092	PLVS3092	PPMB3010	PPMB4010	PPV2400	PPV2500	PSHS1901	PSHS1901	PRVS3010	PLVS3052	PLVS3072	PLVS3092	PPMB3012	PPMB3512	PRVS3125	PRVS2125	PRVS3501	PLVS3552	PLVS3572	PLVS3092
PLVS5052	PLVS5052	PLVS5052	PLVS6072	PLVS5072	PLVS4092	PLVS3092	PLVS3092	PPBM5001	PPMB6010	PPV2400	PPV2500	PSHS1901	PSHS1901	PRVS3010	PLVS3052	PLVS3072	PLVS3092	PPMB3012	PPMB3512	PRVS3125	PRVS2125	PRVS3501	PLVS3552	PLVS3572	PLVS3092
PLVS6052	PLVS6052	PLVS6052	PLVS6072	PLVS5072	PLVS4092	PLVS3092	PLVS3092	PPMB6010	PPV2600	PPV2500	PSHS1901	PSHS1901	PRVS3010	PLVS3052	PLVS3072	PLVS3092	PPMB3012	PPMB3512	PRVS3125	PRVS2125	PRVS3501	PLVS3552	PLVS3572	PLVS3092	
PLVS6072	PLVS6072	PLVS6072	PLVS6072	PLVS5072	PLVS4092	PLVS3092	PLVS3092	PPMB6010	PPV2600	PPV2500	PSHS1901	PSHS1901	PRVS3010	PLVS3052	PLVS3072	PLVS3092	PPMB3012	PPMB3512	PRVS3125	PRVS2125	PRVS3501	PLVS3552	PLVS3572	PLVS3092	
PLVS6092	PLVS6092	PLVS6092	PLVS6092	PLVS5092	PLVS4092	PLVS3092	PLVS3092	PPMB6010	PPV2600	PPV2500	PSHS1901	PSHS1901	PRVS3010	PLVS3052	PLVS3072	PLVS3092	PPMB3012	PPMB3512	PRVS3125	PRVS2125	PRVS3501	PLVS3552	PLVS3572	PLVS3092	

Key:

F fixed
 F - I fixed interlocked
 F - I-MO fixed interlocked motor-operated
 F - MO fixed motor-operated
 F - RC fixed with residual current
 F - RHD fixed with Direct Rotary Handle

F & F - I fixed and fixed interlocked
 P plug-in
 P - I plug-in interlocked
 P - I-MO plug-in interlocked motor-operated
 P - MO plug-in motor-operated
 P - RC plug-in with residual current
 P - RHD plug-in with Direct Rotary Handle

W withdrawable
 W - I withdrawable interlocked
 W - I-MO withdrawable interlocked motor-operated
 W - MO withdrawable motor-operated
 W - RC withdrawable with residual current
 W - RHD withdrawable with Direct Rotary Handle
 W & W - I withdrawable and withdrawable interlocked

Internal kits

Quick selection guides

Blind cell for segregation

HORIZONTAL SEGREGATION

* Mandatory everytime that the breaker kits have plates distant more than 38mm or for segregations form 4b

W=800mm										W=1000mm									
Cell (segregation form 2a)					Segregation form					Cell (segregation form 2a)					Segregation form				
F 3a*		F 3b								F 3a*		F 3b							
PCBS5080	PSHS1908	PSHS1908	PSHS1908	Universal horizontal shelf	Side shelf	Side shelf	Side shelf	Side shelf	Side shelf	PSHS1901	PSHS1901	PSHS1901	PSHS1901	PSHS1901	PSHS1901	PSHS1901	PSHS1901	PSHS1901	PSHS1901
PCBS1080	PPBS0300	PPBS0250	PPBS0200	PPBS0150	PPBS0100	PPBS0050	PPBS0050	PPBS0050	PPBS0050	PPBS0200	PPBS0150	PPBS0100	PPBS0050	PPBS0050	PPBS0050	PPBS0050	PPBS0050	PPBS0050	PPBS0050
PCBS1580	PSVS3050	PSVS3250	PSVS2050	PSVS2070	PSVS2070	PSVS2070	PSVS2070	PSVS2070	PSVS2070	PSVS2090	PSVS2090	PSVS2081	PSVS2081	PSVS2081	PSVS2081	PSVS2081	PSVS2081	PSVS2081	PSVS2081
PCBS2080	PSHS1908	PSHS1908	PSHS1908	PSHS1908	PSHS1908	PSHS1908	PSHS1908	PSHS1908	PSHS1908	PLVS2552	PLVS2552	PLVS2052	PLVS2052	PLVS2052	PLVS2052	PLVS2052	PLVS2052	PLVS2052	PLVS2052
PCBS2580	PSHS1908	PPBS0300	PPBS0250	PPBS0200	PPBS0150	PPBS0100	PPBS0050	PPBS0050	PPBS0050	PLVS2572	PLVS2572	PLVS2072	PLVS2072	PLVS2072	PLVS2072	PLVS2072	PLVS2072	PLVS2072	PLVS2072
PCBS3080	PSHS1908	PSVS3090	PSVS3290	PSVS2090	PSVS2090	PSVS2090	PSVS2090	PSVS2090	PSVS2090	PLVS3052	PLVS3052	PLVS3052	PLVS3052	PLVS3052	PLVS3052	PLVS3052	PLVS3052	PLVS3052	PLVS3052
										PSVS3092	PSVS3092	PSVS3092	PSVS3092	PSVS3092	PSVS3092	PSVS3092	PSVS3092	PSVS3092	PSVS3092
										PCBS2510	PCBS2510	PCBS2010	PCBS2010	PCBS2010	PCBS2010	PCBS2010	PCBS2010	PCBS2010	PCBS2010
										PSHS1901	PSHS1901	PSHS1901	PSHS1901	PSHS1901	PSHS1901	PSHS1901	PSHS1901	PSHS1901	PSHS1901
										PPBS0300	PPBS0250	PPBS0200	PPBS0150	PPBS0100	PPBS0050	PPBS0050	PPBS0050	PPBS0050	PPBS0050
										PSVS3050	PSVS3250	PSVS2050	PSVS2050	PSVS2050	PSVS2050	PSVS2050	PSVS2050	PSVS2050	PSVS2050
										PSVS3070	PSVS3270	PSVS2070	PSVS2070	PSVS2070	PSVS2070	PSVS2070	PSVS2070	PSVS2070	PSVS2070
										PSVS3090	PSVS3290	PSVS2090	PSVS2090	PSVS2090	PSVS2090	PSVS2090	PSVS2090	PSVS2090	PSVS2090
										PLVS3052	PLVS3052	PLVS2552	PLVS2552	PLVS2552	PLVS2552	PLVS2552	PLVS2552	PLVS2552	PLVS2552
										PLVS3072	PLVS3072	PLVS2572	PLVS2572	PLVS2572	PLVS2572	PLVS2572	PLVS2572	PLVS2572	PLVS2572
										PLVS3092	PLVS3092	PLVS2592	PLVS2592	PLVS2592	PLVS2592	PLVS2592	PLVS2592	PLVS2592	PLVS2592

Key:	F & F - I	fixed and fixed interlocked	W	withdrawable
F - I	fixed interlocked	plug-in	W - I	withdrawable interlocked
F - I-MO	fixed interlocked motor-operated	plug-in interlocked	W - I-MO	withdrawable interlocked motor-operated
F - MO	fixed motor-operated	plug-in motor-operated	W - MO	withdrawable motor-operated
F - RC	fixed with residual current	plug-in with residual current	W - RC	withdrawable with residual current
F - RHD	fixed with Direct Rotary Handle	plug-in with Direct Rotary Handle	W - RHD	withdrawable with Direct Rotary Handle
			W & W - I	withdrawable and withdrawable interlocked

Internal kits

Quick selection guides

Blind cell for segregation

VERTICAL SEGREGATION

W=400mm				W=600mm				
Cell height (mm)	Segregation form				Segregation form			
	F 3a*		F 3b		F 3a*		F 3b	
	Vertical rear segregation	Vertical side segregation	With upright	Without upright	Vertical rear segregation	Vertical side segregation	With upright	Without upright
	Bars side	Exits side	D (mm)		Bars side	Exits side	D (mm)	
50 PCBSS5040	PSHS1904	PSHS1904	Universal horizontal shelf	PRVS0541	PLVS0552	PRVS0582	PLVS0552	PCBS5060
100 PCBS1040	PSHS1904	PSHS1904	Side shelf	PRVS0141	PLVS0502	PRVS0182	PLVS0572	PSHS1906
150 PCBS1540	PSHS1904	PPBS0150	PPBS0150	PRVS1541	PLVS1552	PRVS1582	PLVS1072	PPBS0100
200 PCBS2040	PSHS1904	PPBS0200	PPBS0200	PRVS2041	PLVS2052	PRVS2040	PLVS2072	PPBS0050
250 PCBS2540	PSHS1904	PPBS0250	PPBS0250	PRVS2541	PLVS2552	PLVS3052	PLVS3072	PRVS0161
300 PCBS3040	PSHS1904	PPBS0300	PPBS0300	PRVS3041	PLVS2092	PLVS2092	PLVS2092	PRVS0561.
					PCBS1560	PCBS2060	PCBS3060	PRVS0162
					PSHS1906	PSHS1906	PSHS1906	PRVS0562
					PPBS0200	PPBS0250	PPBS0300	PRVS006
					PRVS2061	PRVS2561	PRVS3061	PRVS1562
					PLVS2060	PLVS2560	PLVS3060	PLVS0552
					PLVS2052	PLVS2552	PLVS3052	PLVS0572
					PLVS2072	PLVS2572	PLVS3072	PLVS1092
					PLVS1592	PLVS2092	PLVS3092	PLVS0592

* Mandatory everytime that the breaker kits have plates distant more than 38mm or for segregations form 4b

W=800mm										W=1000mm									
Cell (segregation form 2a)										Cell (segregation form 2a)									
				Segregation form				Segregation form											
F 3a*		F 3b		Vertical rear segregation	Vertical side segregation			Vertical rear segregation	Vertical side segregation										
				With upright				With upright											
				Without upright		D (mm)		Without upright		D (mm)									
				Side shelf		Bars side	Exits side			Bars side	Exits side								
PCBS5080	PSHS1908	PSHS1908	PPBS0050	Universal horizontal shelf	PRVS0581	PRVS0581	PRVS0582	PRVS0580	PLVS0552	PLVS0572	PLVS0572	PLVS0592	PCBS5010	PSHS1901	PPBS0050	PRVS0581	PRVS0582	PLVS0552	PLVS0572
PCBS1080	PSHS1908	PSHS1908	PPBS0100	Side shelf	PRVS0181	PRVS0181	PRVS0182	PRVS0108	PLVS1052	PLVS1072	PLVS1092	PLVS1092	PCBS1010	PSHS1901	PPBS0100	PRVS0181	PRVS0182	PLVS1052	PLVS1072
PCBS1580	PSHS1908	PSHS1908	PPBS0150		PRVS1581	PRVS1581	PRVS1582	PRVS1008	PLVS1552	PLVS1572	PLVS1592	PLVS1592	PCBS1510	PSHS1901	PPBS0150	PRVS1581	PRVS1582	PLVS1552	PLVS1572
PCBS2080	PSHS1908	PSHS1908	PPBS0200		PRVS2081	PRVS2081	PRVS2082	PRVS2080	PLVS2052	PLVS2072	PLVS2092	PLVS2092	PCBS2010	PSHS1901	PPBS0200	PRVS2081	PRVS2082	PLVS2052	PLVS2072
PCBS2580	PSHS1908	PSHS1908	PPBS0250		PRVS2581	PRVS2581	PRVS2582	PRVS2580	PLVS2552	PLVS2572	PLVS2592	PLVS2592	PCBS2510	PSHS1901	PPBS0250	PRVS2581	PRVS2582	PLVS2552	PLVS2572
PCBS3080	PSHS1908	PSHS1908	PPBS0300		PRVS3081	PRVS3081	PRVS3082	PRVS3080	PLVS3052	PLVS3072	PLVS3092	PLVS3092	PCBS3010	PSHS1901	PPBS0300	PRVS3081	PRVS3082	PLVS3052	PLVS3072

Key:	F & F - I	fixed and fixed interlocked	F & F - I	fixed and fixed interlocked	W	withdrawable
F - I	fixed interlocked	plug-in	P - I	plug-in interlocked	W - I	withdrawable interlocked
F - I-MO	fixed interlocked motor-operated	plug-in interlocked motor-operated	P - I-MO	plug-in interlocked motor-operated	W - I-MO	withdrawable interlocked motor-operated
F - MO	fixed motor-operated	plug-in motor-operated	P - MO	plug-in motor-operated	W - MO	withdrawable motor-operated
F - RC	fixed with residual current	plug-in with residual current	P - RC	plug-in with residual current	W - RC	withdrawable with residual current
F - RHD	fixed with Direct Rotary Handle	plug-in with Direct Rotary Handle	P - RHD	plug-in with Direct Rotary Handle	W - RHD	withdrawable with Direct Rotary Handle
					W & W - I	withdrawable and withdrawable interlocked


Internal kits

Quick selection guides

Tmax XT horizontal installation

To assemble these kits, order the dedicated intermediate depth uprights PUKI1800 for H= 1800mm or PUKI2000 for H=2000mm. Intermediate uprights are not required for assembling fixed Tmax XT1, XT2, XT3, XT4, T4, T5, T6 and XT1, XT3 with

Direct Rotary Handle only in non-segregated structures. Order the dedicated fixed frame PFPF.... or swing frame PFPS.... for assembling internal panels. For D=300mm structures, consult the details on page 3/21.




NON-ACCESSORIZED CIRCUIT-BREAKERS

Front or rear CB connections	No. poles	Dimensions (mm)		No. CB per compart.	FIXED	PLUG-IN	WITHDRAWABLE
XT1	3P 4P	150	400	1	PHBX1401		
	3P 4P	150	600	1	PHCX1401		
	3P 4P	150	800	1	PHDX1301		
	3P 4P	200	400	1	PHBX1101	PHBX1407	
	3P 4P	200	600	1	PHCX1101	PHCX1407	
	3P 4P	200	800	1	PHDX1401	PHDX1407	
XT2	3P	150	400	1	PHBX2301		
	3P	150	600	1	PHCX2301		
	3P 4P	200	400	1	PHBX2401	PHBX2407	PHBX2310 ⁽¹⁾
	3P 4P	200	600	1	PHCX2401	PHCX2407	PHCX2310 ⁽¹⁾
	3P 4P	200	800	1	PHDX2401	PHDX2407	
	3P 4P	250	400	1			PHBX2410
	3P 4P	250	600	1			PHCX2410
	3P 4P	250	800	1			PHDX2410
	XT3	3P	150	400	1	PHBX3301 ⁽²⁾	
XT4	3P	150	600	1	PHCX3301		
	3P 4P	200	400	1	PHBX3401 ⁽²⁾	PHBX3407	
	3P 4P	200	600	1	PHCX3401	PHCX3407	
	3P 4P	200	800	1	PHDX3401	PHDX3407	
	3P	150	400	1	PHBX4301 ⁽²⁾		
	3P	150	600	1	PHCX4301		
	3P 4P	200	400	1	PHBX4401 ⁽²⁾	PHBX4407	
	3P 4P	200	600	1	PHCX4401	PHCX4407	
	3P 4P	200	800	1	PHDX4401	PHDX4407	
	3P 4P	250	400	1			PHBX4410
	3P 4P	250	600	1			PHCX4410
	3P 4P	250	800	1			PHDX4410

⁽¹⁾ Only 3 poles.

⁽²⁾ Not compatible with high terminal covers.



ACCESSORIZED CIRCUIT-BREAKERS

		Dimensions (mm)			No. CB per compartment	Residual current device	Direct Rotary Handle	Motor operator	Interlocked	Interlocked motor-operated
Front or rear CB connections	No. poles	H	W							
FIXED										
XT1	3P	200	400	1	PHBX1323					
	3P	200	600	1	PHCX1323					
	3P 4P	150	400	1		PHBX1405				
	3P 4P	150	600	1		PHCX1405				
	3P 4P	200	400	1	PHBX1423 ⁽²⁾	PHBX1105	PHBX1404			
	3P 4P	200	600	1	PHCX1423 ⁽²⁾	PHCX1105	PHCX1404			
	3P 4P	500	400	2				PHBX1422	PHBX1424	
	3P 4P	500	600	2				PHCX1422	PHCX1424	
	4P	200	800	1	PHDX1423					
	3P 4P	200	800	1		PHDX1105	PHDX1404			
	3P 4P	500	800	2				PHDX1402	PHDX1403	
XT2	3P 4P	200	400	1	PHBX2423 ⁽²⁾	PHBX2405	PHBX2404			
	3P 4P	200	600	1	PHCX2423 ⁽²⁾	PHCX2405	PHCX2404			
	3P 4P	200	800	1	PHDX2423 ⁽²⁾	PHDX2405	PHDX2404			
	3P 4P	500	400	2				PHBX2402	PHBX2424	
	3P 4P	500	600	2				PHCX2402	PHCX2424	
XT2	3P 4P	250	800	1						
	3P 4P	500	800	2						
	3P 4P	150	400	1		PHBX3305				
	3P 4P	150	600	1		PHCX3305				
	3P 4P	200	400	1		PHBX3405	PHBX3404			
XT3	3P 4P	200	600	1		PHCX3405	PHCX3404			
	3P 4P	500	400	2				PHBX3422	PHBX3424	
	3P 4P	500	600	2				PHCX3422	PHCX3424	
	4P	250	400	1	PHBX3423 ⁽⁴⁾					
	4P	250	600	1	PHCX3423					
XT4	3P 4P	200	800	1	PHDX3423 ⁽²⁾	PHDX3405	PHDX3404			
	3P 4P	500	800	2						
	3P 4P	200	400	1	PHBX4423 ⁽²⁾ ⁽⁴⁾	PHBX4405	PHBX4404			
	3P 4P	200	600	1	PHCX4423 ⁽²⁾	PHCX4405	PHCX4404			
	3P 4P	200	800	1	PHDX4423 ⁽²⁾	PHDX4405	PHDX4404			
PLUG-IN	3P 4P	500	400	2				PHBX4402	PHBX4424	
	3P 4P	500	600	2				PHCX4402	PHCX4424	
	3P 4P	500	800	2				PHDX4402	PHDX4403	
	3P 4P	200	400	1	PHBX4427	PHBX1409				
	3P 4P	200	600	1	PHCX4427	PHCX1409				
XT2	3P 4P	500	400	2				PHBX1422	PHBX1424	
	3P 4P	500	600	2				PHCX1422	PHCX1424	
	3P 4P	200	800	1	PHDX1427	PHDX1409				
	3P 4P	500	800	2				PHDX1422	PHDX1424	
	3P 4P	200	400	1		PHBX2427	PHBX2409			
XT3	3P 4P	200	600	1		PHCX2427	PHCX2409			
	3P 4P	200	800	1		PHDX2427	PHDX2409			
	3P 4P	250	400	1	PHBX2428 ⁽²⁾					
	3P 4P	500	400	2				PHBX2431	PHBX2424	
	3P 4P	500	600	2				PHCX2431	PHCX2424	
XT4	3P 4P	250	800	1	PHDX2428 ⁽²⁾					
	3P 4P	200	400	1		PHBX3427	PHBX3409			
	3P 4P	200	600	1		PHCX3427	PHCX3409			
	3P 4P	500	400	2				PHBX3422	PHBX3424	
	3P 4P	500	600	2				PHCX3422	PHCX3424	
XT4	3P 4P	200	800	1		PHDX3427	PHDX3409			
	3P 4P	500	800	2						
	3P 4P	200	400	1	PHBX4427	PHBX4409				
	3P 4P	200	600	1	PHCX4427	PHCX4409				
	3P 4P	200	800	1	PHDX4427	PHDX4409				
WITHDRAWABLE	3P 4P	250	400	1	PHBX4428 ⁽²⁾					
	3P 4P	500	400	2				PHBX4431	PHBX4424	
	3P 4P	500	600	2				PHCX4431	PHCX4424	
	3P 4P	250	800	1	PHDX4428 ⁽²⁾					
	3P 4P	500	800	2						
XT2	3P 4P	200	400	1	PHBX2300 ⁽¹⁾	PHBX2312 ⁽¹⁾				
	3P 4P	200	600	1	PHCX2300 ⁽¹⁾	PHCX2312 ⁽¹⁾				
	3P 4P	200	800	1		PHDX2409				
	3P 4P	250	400	1	PHBX2400	PHBX2412				
	3P 4P	250	600	1	PHCX2400	PHCX2412				
XT4	3P 4P	500	400	2				PHBX2425	PHBX2425	
	3P 4P	500	600	2				PHCX2425	PHCX2425	
	3P 4P	250	800	1	PHDX2417 ⁽²⁾	PHDX2400	PHDX2412			
	3P 4P	500	800	2						
	3P 4P	250	400	1	PHBX4400	PHBX4412				
XT4	3P 4P	250	600	1	PHCX4400	PHCX4412				
	3P 4P	500	400	2				PHBX4425	PHBX4425	
	3P 4P	500	600	2				PHCX4425	PHCX4425	
	3P 4P	250	800	1	PHDX4417 ⁽²⁾	PHDX4400	PHDX4412			
	3P 4P	500	800	2						

⁽¹⁾ Only 3 poles.⁽²⁾ Only 4 poles.⁽³⁾ Compatible residual current devices: RC Inst. XT1-XT3, RC Sel.

XT1-XT3 and RC Sel.. XT2-XT4 Type A. For XT1-XT3 fixed with residual current device high terminal covers are not available.

⁽⁴⁾ Not compatible with high terminal covers.

For fixed and withdrawable 3P breakers Tmax XT, non accessorized and mounted on 3/4P kit, it is necessary to order the dedicated cover flanges: AD3305 flange for XT1 3P mounted on plate, AD3306 flange for XT2 3P mounted on plate, AD3307 flange for XT3 3P mounted on plate, AD3308 flange for XT4 3P mounted on plate. With interlocked or interlocked motor-operated kits, it is necessary to order the quantity of flanges equal to the quantity of breakers.


Internal kits

Quick selection guides

Tmax T horizontal installation

To assemble these kits, order the dedicated intermediate depth uprights PUKI1800 for H= 1800mm or PUKI2000 for H=2000mm. Intermediate uprights are not required for assembling fixed Tmax XT1, XT2, XT3, XT4, T4, T5, T6 and XT1, XT3 with

Direct Rotary Handle only in non-segregated structures. Order the dedicated fixed frame PFPF.... or swing frame PFPS.... for assembling internal panels. For D=300mm structures, consult the details on page 3/21.



NON-ACCESSORIZED CIRCUIT-BREAKERS

Front or rear CB connections	No. poles	Dimensions (mm)		No. CB per compart.	FIXED	PLUG-IN	WITHDRAWABLE
T4	3P	150	400	1	PHBT4301(3)		
	3P	150	600	1	PHCT4301		
	3P 4P	200	400	1	PHBT4406(3)		
	3P 4P	200	600	1	PHCT4406		
T5	400A 3P	200	400	1		PHBT5326	
	3P	200	600	1		PHCT5326	
	3P	200	800	1		PHDT5326	
	3P	300	400	1			PHBT5314
	3P	300	600	1			PHCT5314
	3P	300	800	1			PHDT5314
	400/630A 3P	200	400	1	PHBT5306(3)		
	3P	200	600	1	PHCT5306		
	3P	200	800	1	PHDT5306		
	400A 3P 4P	250	400	1		PHBT5426	
T6	3P 4P	250	600	1		PHCT5426	
	3P 4P	250	800	1		PHDT5426	
	3P 4P	350	400	1			PHBT5414
	3P 4P	350	600	1			PHCT5414
	3P 4P	350	800	1			PHDT5414
	400/630A 3P 4P	250	400	1	PHBT5406 ⁽³⁾		
	3P 4P	250	600	1	PHCT5406		
	3P 4P	250	800	1	PHDT5406		
	630A 3P	200	600	1		PHCT5307 ■	
	3P 4P	250	600	1		PHCT5407	
T7	3P 4P	250	800	1		PHDT5407	
	3P	300	600	1			PHCT5310 ■
	3P	300	600	1	PHCT6301 ⁽⁴⁾		
	3P	300	800	1	PHDT6301		
	3P 4P	350	600	1	PHCT6401 ⁽⁴⁾		PHCT6314 ⁽¹⁾ ■
	3P 4P	350	800	1	PHDT6401 ⁽⁴⁾		PHDT6314 ⁽¹⁾ ■
T8	3P 4P	500	600	1			PHCT6410 ■
	3P 4P	500	800	1			PHDT6414 ■
	3P	300	600	1	PHCT7329		
	3P	300	800	1	PHDT7329		
	3P 4P	350	600	1	PHCT7420		
	3P 4P	350	800	1	PHDT7420		
T9	3P 4P	500	600	1			PHCT7430 *
	3P 4P	500	800	1			PHDT7430 *

⁽¹⁾ Only 3 poles


⁽²⁾ Only 4 poles

⁽³⁾ Not compatible with high terminal covers.

⁽⁴⁾ T6 1000A front terminals in width 800mm.

■ Front terminals, only Form 1

* Only rear terminals

**ACCESSORIZED CIRCUIT-BREAKERS**

Dimensions (mm)							
Front or rear CB connections	No. poles	H	W	No. CB per compart.	Residual current device	Direct Rotary Handle	Motor operator
FIXED							
T4	3P 4P	200	400	1	PHBT4406 ⁽³⁾	PHBT4404	
	3P 4P	200	600	1	PHCT4423 ⁽²⁾	PHCT4406	PHCT4404
	3P 4P	600	400	2			PHBT4402
	3P 4P	600	600	2			PHCT4402
	3P 4P	600	800	2			PHDT4402
T5 400A/630A	3P	200	400	1	PHBT5306 ⁽³⁾	PHBT5304	
	3P	200	600	1	PHCT5306	PHCT5304	
	3P	200	800	1	PHDT5306	PHDT5304	
	3P 4P	250	400	1	PHBT5406 ⁽³⁾	PHBT5404	
	3P 4P	250	600	1	PHCT5406	PHCT5404	
	3P 4P	250	800	1	PHDT5406	PHDT5404	
	3P 4P	600	600	2			PHCT5402
	3P 4P	600	800	2			PHCT5403
	400A 4P	250	600	1	PHCT5423		
	4P	250	800	1	PHDT5423		
T6	3P	300	600	1	PHCT6305 ⁽⁶⁾	PHCT6304 ⁽⁶⁾	
	3P	300	800	1	PHDT6305	PHDT6304	
	3P 4P	350	600	1	PHCT6405	PHCT6404	
	3P 4P	350	800	1	PHDT6405	PHDT6404	
	3P 4P	700	600	2			PHCT6402
	3P 4P	700	800	2			PHDT6402
T7	3P	300	600	1	PHCT7329	PHCT7329	PHCT7329
	3P	300	800	1	PHDT7329	PHDT7329	PHDT7329
	3P 4P	350	600	1	PHCT7420	PHCT7420	
	3P 4P	350	800	1	PHDT7420	PHDT7420	
	3P 4P	400	600	1			PHCT7418
	3P 4P	400	800	1			PHDT7418
PLUG-IN							
T5 400A	3P	200	400	1	PHBT5326	PHBT5309	
	3P	200	600	1	PHCT5326	PHCT5309	
	3P	200	800	1	PHDT5326	PHDT5309	
	3P 4P	250	400	1	PHBT5426	PHBT5409	
	3P 4P	250	600	1	PHCT5426	PHCT5409	
	3P 4P	250	800	1	PHDT5426	PHDT5409	
400A/630A	3P 4P	250	600	1		PHCT5427 ⁽⁵⁾	
	3P 4P	250	800	1		PHDT5428 ⁽⁵⁾	
	3P 4P	600	600	2			PHCT5431
	3P 4P	600	800	2			PHDT5431 ⁽⁵⁾
							PHDT5432 ⁽⁵⁾
WITHDRAWABLE							
T5 400A	3P	300	400	1	PHBT5314	PHBT5312	
	3P	300	600	1	PHCT5314	PHCT5312	
	3P	300	800	1	PHDT5314	PHDT5312	
	3P 4P	350	400	1	PHBT5414	PHBT5412	
	3P 4P	350	600	1	PHCT5414	PHCT5412	
	3P 4P	350	800	1	PHDT5414	PHDT5412	
	3P 4P	250	400	1			
400A/630A	3P 4P	250	600	1		PHCT5425	PHDT5411
	3P 4P	250	800	1		PHCT5425	PHDT5411
T6	3P 4P	350	600	1	PHCT6314 ⁽¹⁾ n	PHCT6312 ⁽¹⁾ ■	
	3P 4P	350	800	1	PHDT6314 ⁽¹⁾ n	PHDT6312 ⁽¹⁾ ■	
	3P 4P	500	600	1	PHCT6410■	PHCT6412■	
	3P 4P	500	800	1	PHDT6410■	PHDT6412■	
	3P 4P	700	600	2		PHCT6425 n	PHCT6411*
T7	3P 4P	500	600	1	PHCT7430*	PHCT7430*	PHCT7430*
	3P 4P	500	800	1	PHDT7430*	PHDT7430*	PHDT7430*

⁽¹⁾ Only 3 poles⁽⁴⁾ T6 1000A front terminals in width 800mm.⁽²⁾ Only 4 poles

■ Front terminals, only Form 1

⁽³⁾ Not compatible with high terminal covers.

* Only rear terminals


Internal kits

Quick selection guides

Tmax XT vertical installation


To assemble these kits, order the dedicated intermediate depth uprights PUKI1800 for H= 1800mm or PUKI2000 for H=2000mm. Intermediate uprights are not required for assembling fixed Tmax XT1, XT2, XT3, XT4, T4, T5, T6 and XT1, XT3 with

Direct Rotary Handle only in non-segregated structures. Order the dedicated fixed frame PFPF.... or swing frame PFPS.... for assembling internal panels. For D=300mm structures, consult the details on page 3/21.



NON-ACCESSORIZED CIRCUIT-BREAKERS

Front or rear CB connections	No. poles	Dimensions (mm)		No. CB per compart.	FIXED	PLUG-IN	WITHDRAWABLE
XT1	3P 4P	300	400	1	PVBX1401	PVBX1407	
	3P 4P	300	600	1	PVCX1401	PVCX1407	
	3P	300	600	4	PVCX1301	PVCX1707	
	3P	300	600	4	PVCX1301		
	3P 4P	300	800	4		PVDX1807	
XT2	3P 4P	300	400	1	PVBX2401	PVBX2407	PVBX2410
	3P 4P	300	600	1	PVCX2401	PVCX2407	PVCX2410
	3P 4P	300	600	3	PVCX2701	PVCX2707	
	3P 4P	300	800	4	PVDX2801	PVDX2807	
XT3	3P 4P	300	400	1	PVBX3401	PVBX3407	
	3P	300	600	3		PVCX3707	
	3P 4P	300	600	1	PVCX3401	PVCX3407	
	3P	300	600	3	PVCX3301	PVCX3607	
	3P	300	600	3	PVCX3301		
	3P	300	800	4		PVDX3807	
	3P 4P	300	800	3		PVDX3707	
XT4	3P 4P	300	400	1	PVBX4401		
	3P 4P	300	600	1	PVCX4401		
	3P 4P	300	600	2	PVCX4601		
	3P	300	600	3	PVCX4701		
	3P 4P	300	800	3	PVDX4701		
	3P	300	800	4	PVDX4801		
	3P 4P	350	400	1		PVBX4407	PVBX4410
	3P	350	600	3		PVCX4707	
	3P 4P	350	600	1		PVCX4407	PVCX4410
	3P 4P	350	600	2		PVCX4607	
	3P	350	800	4		PVDX4807	
	3P 4P	350	800	3		PVDX4707	



ACCESSORIZED CIRCUIT-BREAKERS

Dimensions (mm)						
Front or rear CB connections	No. poles	H	W	No. CB per compartment.	Residual current device	Direct Rotary Handle
FIXED						
XT1	3P 4P	300	400	1	PVBX1423 ⁽¹⁾	PVBX1405
	3P 4P	300	600	1	PVCX1423 ⁽¹⁾	PVCX1405
XT2	3P 4P	300	400	1		PVBX2405
	3P 4P	300	600	1		PVCX2405
	4P	350	400	1	PVBX2423	
	4P	350	600	1	PVCX2423	
XT3	3P 4P	300	400	1		PVBX3405
	3P 4P	300	600	1		PVCX3405
	4P	400	400	1	PVBX3423	
	4P	400	600	1	PVCX3423	
XT4	3P 4P	300	400	1		PVBX4405
	3P 4P	300	600	1		PVCX4405
	4P	400	400	1	PVBX4423	
	4P	400	600	1	PVCX4423	
PLUG-IN						
XT1	3P 4P	300	400	1		PVBX1427
	3P 4P	300	600	1		PVCX1427
XT2	3P 4P	300	400	1		PVBX2427
	3P 4P	300	600	1		PVCX2427
XT3	3P 4P	300	400	1		PVBX3427
	3P 4P	300	600	1		PVCX3427
XT4	3P 4P	350	400	1		PVBX4427
	3P 4P	350	600	1		PVCX4427
WITHDRAWABLE						
XT2	3P 4P	300	400	1		PVBX2400
	3P 4P	300	600	1		PVCX2400
	4P	350	400	1	PVBX2417	
	4P	350	600	1	PVCX2417	
XT4	3P 4P	350	400	1		PVBX4400
	3P 4P	350	600	1		PVCX4400
	4P	400	400	1	PVBX4417	
	4P	400	600	1	PVCX4417	

⁽¹⁾ Only 4 poles.⁽²⁾ Compatible residual current devices: RC Inst. XT1-XT3, RC Sel.

XT1-XT3 and RC Sel.. XT2-XT4 Type A. For XT1-XT3 fixed with residual current device high terminal covers are not available.

For fixed and withdrawable 3P breakers Tmax XT, non accessordized and mounted on 3/4P kit, it is necessary to order the dedicated cover flanges: AD3305 flange for XT1 3P mounted on plate, AD3306 flange for XT2 3P mounted on plate, AD3307 flange for XT3 3P mounted on plate, AD3308 flange for XT4 3P mounted on plate. With interlocked or interlocked motor-operated kits, it is necessary to order the quantity of flanges equal to the quantity of breakers


Internal kits

Quick selection guides

Tmax T vertical installation

To assemble these kits, order the dedicated intermediate depth uprights PUKI1800 for H= 1800mm or PUKI2000 for H=2000mm. Intermediate uprights are not required for assembling fixed Tmax XT1, XT2, XT3, XT4, T4, T5, T6 and XT1, XT3 with Dir-

ect Rotary Handle only in non-segregated structures. Order the dedicated fixed frame PFPF.... or swing frame PFPS.... for assembling internal panels. For D=300mm structures, consult the details on page 3/21.




NON-ACCESSORIZED CIRCUIT-BREAKERS

Front or rear CB connections	No. poles	Dimensions (mm)		No. CB per compart.	FIXED	PLUG-IN	WITHDRAWABLE
T4	3P 4P	350	400	1	PVBT4406		
	3P 4P	350	600	1	PVCT4406		
T5	3P 4P	350	800	2	PVDT5601		PVDT5610
	3P	350	1000	4			PVFT5810
	3P 4P	350	1000	3			PVFT5710
	400A	3P 4P	350	400	1	PVBT5426	PVBT5414
	3P 4P	350	600	1	PVCT5426	PVCT5414	
	3P 4P	350	800	1	PVDT5426	PVDT5414	
400/630A	3P 4P	350	400	1	PVBT5406		
	3P 4P	350	600	1	PVCT5406		
	3P 4P	350	800	1	PVDT5406		
	3P 4P	350	600	2	PVCT5712		
	3P 4P	350	800	3	PVDT5813		
	3P 4P	400	600	1		PVCT5407(2)	
	3P 4P	400	800	1		PVDT5407(2)	
	630A ⁽¹⁾	3P	450	600	3	PVCT5710	
	3P	450	800	4	PVDT5810		
	3P	450	600	2			PVCT5601
T6	3P	450	800	3			PVDT5701
	3P	450	400	1			PVBT5319
	3P	450	600	1		PVCT5307	
	3P	450	400	1			PVBT6314
	3P 4P	400	400	1	PVBT6401		
	3P 4P	400	600	1	PVCT6401		
	3P 4P	400	800	1	PVDT6401		
	3P 4P	450	600	1			PVCT6414■
	3P 4P	450	800	1			PVDT6414■
	3P 4P	450	1000	2			PVFT6610■
T7	3P 4P	450	600	1	PVCT7419		
	3P 4P	450	800	1	PVDT7419		
	3P 4P	500	600	1			PVCT7413 *
	3P 4P	500	800	1			PVDT7413 *
	3P 4P	500	1000	2			PVFT7633 *

⁽¹⁾ Only front terminals not segregated.

⁽²⁾ Only 630A.

■ Front terminals, only Form 1



ACCESSORIZED CIRCUIT-BREAKERS

Dimensions (mm)							
Front or rear CB connections	No. poles	H	W	No. CB per compart.	Residual current device ⁽²⁾	Direct Rotary Handle	Motor operator
FIXED							
T4	3P 4P	350	400	1		PVBT4406	PVBT4404
	3P 4P	350	600	1		PVCT4406	PVCT4404
	4P	450	400	1	PVBT4423		
	4P	450	600	1	PVCT4423		
T5	400A 4P	450	400	1	PVBT5423		
		450	600	1	PVCT5423		
		450	800	1	PVDT5423		
	400A/630A	3P 4P	350	400	1	PVBT5406	PVBT5404
		350	600	1	PVCT5406	PVCT5404	
		350	800	1	PVDT5406	PVDT5404	
T6	3P 4P	400	400	1		PVBT6405	PVBT6404
	3P 4P	400	600	1		PVCT6405	PVCT6404
	3P 4P	400	800	1		PVDT6405	PVDT6404
T7	3P 4P	450	600	1		PVCT7419	PVCT7419
	3P 4P	450	800	1		PVDT7419	PVDT7419
PLUG-IN							
T5	400A 3P 4P	350	400	1		PVBT5426	
		350	600	1		PVCT5426	
		350	800	1		PVDT5426	
	3P 4P	400	400	1		PVBT5409 ⁽²⁾	
	3P 4P	400	600	1		PVCT5409 ⁽²⁾	
	3P 4P	400	800	1		PVDT5409 ⁽²⁾	
	4P	450	400	1	PVBT5428		
	4P	450	600	1	PVCT5428		
	4P	450	800	1	PVDT5428		
WITHDRAWABLE							
T5	3P 4P	350	800	2		PVDT5612	
	3P	350	1000	4		PVFT5812	
	3P 4P	350	1000	3		PVFT5712	
	400A 3P 4P	350	400	1	PVBT5414	PVBT5412	
		350	600	1	PVCT5414	PVCT5412	
		350	800	1	PVDT5414	PVDT5412	
	3P 4P	400	600	1		PVCT5430 ⁽²⁾	
	3P 4P	400	800	1		PVDT5430 ⁽²⁾	
T6	3P	450	400	1	PVBT6314	PVBT6312	
	3P 4P	450	600	1	PVCT6414 ⁿ	PVCT6412 ⁿ	
	3P 4P	450	800	1	PVDT6414 ⁿ	PVDT6412 ⁿ	
	3P 4P	450	1000	2	PVFT6610	PVFT6612 ⁿ	
T7	3P 4P	500	600	1		PVCT7413 *	PVCT7413 *
	3P 4P	500	800	1		PVDT7413 *	PVDT7413 *
	3P 4P	500	1000	2		PVFT7633 *	

⁽²⁾ Compatible residual current devices: RC222 for T4 and T5.

■ Front terminals, only Form 1

* Only rear terminals


Internal kits

Quick selection guides

Emax 2 horizontal / vertical installation

To assemble these kits, order the dedicated intermediate depth upright PUKI1800 for H=1800mm or PUKI2000 for H=2000mm.

Order the dedicated fixed frame PFPF.... or swing frame PFPS.... for assembling internal panels.



NON-ACCESSORIZED CIRCUIT-BREAKERS

Front or rear CB connections	No. poles	Dimensions (mm)			FIXED	WITHDRAWABLE
Front or rear connections, horizontal installation						
E1.2	3P 4P	400	600	PHCE1241		
	3P 4P	400	800	PHDE1241		
	3P 4P	500	600		PHCE1240 *	
	3P 4P	500	800		PHDE1240 *	
Front or rear connections, vertical installation						
E1.2	3P 4P	450	400	PVBE1241		
	3P 4P	450	600	PVCE1241		
	3P 4P	450	800	PVDE1241		
	3P 4P	450	800	PVDE1262 ⁽¹⁾		
	3P 4P	500	600		PVCE1240 *	
	3P 4P	500	800		PVDE1240 *	
	3P 4P	500	1000		PVFE1263 ⁽¹⁾ *	
Rear connections, vertical installation						
E2.2	3P 4P	600	600	PVCE2441	PVCE2450	
	3P 4P	600	800	PVDE2441	PVDE2440	
E4.2	3P 4P	600	600	PVCE2442	PVCE4350 ⁽²⁾	
	3P 4P	600	800	PVDE2441	PVDE2440	
E6.2	3P	700	1000		PVFE6230	
E6.2	Neutral 50% 3P 4P	700	1000	PVFE6231		
E6.2	Neutral 50/100% 4P	700	1250		PVGE6230	
E6.2	Neutral 50/100% 4P	700	1250	PVGE6231		

ACCESSORIZED CIRCUIT-BREAKERS

Front or rear CB connections	No. poles	Dimensions (mm)			FIXED INTERLOCKED	WITHDRAWABLE INTERLOCKED
Front or rear connections, horizontal installation						
E1.2	3P 4P	400	600	PHCE1241		
	3P 4P	400	800	PHDE1241		
	3P 4P	500	600		PHCE1240	
	3P 4P	500	800		PHDE1240	
Front or rear connections, vertical installation						
E1.2	3P 4P	450	400	PVBE1241		
	3P 4P	450	600	PVCE1241		
	3P 4P	450	800	PVDE1241		
	3P 4P	500	600		PVCE1240 *	
	3P 4P	500	800		PVDE1240 *	
Rear connections, vertical installation						
E2.2	3P 4P	600	600	PVCE2441	PVCE2450	
	3P 4P	600	800	PVDE2441	PVDE2440	
E4.2	3P	600	600		PVCE4350	
	3P 4P	600	800	PVDE2441	PVDE2440	
E6.2	3P	700	1000	PVFE6231	PVFE6230	
E6.2	50/100% Neutral 4P	700	1250	PVGE6231	PVGE6230	

For 3200A busbar systems use structures with D=700mm, for 4000A busbar systems use structures with D=900mm.

⁽¹⁾ Kit for 2 adjacent circuit-breakers.

⁽²⁾ Only 3 poles.

* Only rear terminals.

Internal kits

Guide to the order codes

The new code is formed by 4 letters standing for English terms and 4 numbers, without spaces in between.

RANGE IDENTIFIER

The first letter of all the codes of the new main distribution switchboard "P" stands for "power". Thus the new product is clearly identified by the same initial used for all new components of ABB's System pro E power

H = Horizontal

V = Vertical

D = DIN-rail

P = Panel

K = Kit

F = Frame

B = 400mm - **C** = 600mm - **D** = 800mm - **F** = 1000mm - **G** = 1250mm
(Compartment width)

R = Rail

M = System pro M, Mounting

O = OT

P = Panel

F = Flat

B = Blind

X = Tmax XT

T = Tmax T

E = Emax 2

S = Standard, Swing

F = Front, Fixed

H = Horizontal

V = Vertical

R = Recessed

B = Blind

Tmax

For Tmax, the first out of the four digits combined with the last letter, gives the breakers type. The second digit refers to the number of poles or side-by-side breakers. The last two digits specify the execution as below indicated.

3 = 3 Poles / 4 = 4/3-4 Poles / 6 = 2 Breakers / 7 = 3 Breakers / 8 = 4 Breakers / 9 = 5 Breakers

00 = W - RHD / 01 = F / 02 = F - I / 03 = F - I-MO / 04 = F - MO
05 = F - RHD / 06 = F, F - RHD / 07 = P / 09 = P - MO / 10 = W / 11 = W - I-MO / 12 = W - MO / 13 = W, W - I, W - I-MO, W - MO / 14 = W, W - RHD / 17 = W - RC / 18 = F - I, F - I-MO / 19 = F, F - I, F - I-MO, F - MO / 20 = F, F - RHD, F - MO / 22 = F - I, P - I / 23 = F - RC / 24 = F - I-MO, P - I-MO / 25 = W - I26 = P, P - RHD / 27 = P - RHD / 28 = P - RC
29 = F, F - I, F - I-MO, F - MO, F - RHD / 30 = W, W - I, W - I-MO, W - MO, W - RHD 31 = P - I, P - I-MO / 32 = P - I-MO / 33 = W, W - MO / 36 = W, W - MO / 46 = W / 56 = W - MO

Emax 2


For Emax 2, the first two digits, combined with the last letter, gives the breakers type. The last digit specifies the execution as below indicated.
3 = 3 Poli / 4 = 4 Poli, 3-4 Poli / 5 = 3 o 3-4 Poli / 6 = 4 Poli, 3-4 Poli Cell height=600mm

0 = W, W - I / 1 = F, F - I / 2 = F / 3 = W / 6 = W

P	H	B	X	1	4	0	1
----------	----------	----------	----------	----------	----------	----------	----------

Internal kits


Order codes - Internal kits



Fixed frame for panels

Fixed frame for internal panels; the useful height of the switchboard can be used to full advantage. With fixed frame for panels, maximum wiring ducts dimension is 80x60mm.

Description	Dimensions (mm)				Pkg/ No. pcs
	H	W	Type	Order code	
Fixed frame for panels	1800	400	PFPPF1840	1STQ007449A0000	1/1
Fixed frame for panels	1800	600	PFPPF1860	1STQ007450A0000	1/1
Fixed frame for panels	1800	800	PFPPF1880	1STQ007451A0000	1/1
Fixed frame for panels	1800	1000	PFPPF1810	1STQ007452A0000	1/1
Fixed frame for panels	1800	1250	PFPPF1812	1STQ007453A0000	1/1
Fixed frame for panels	2000	400	PFPPF2040	1STQ007454A0000	1/1
Fixed frame for panels	2000	600	PFPPF2060	1STQ007455A0000	1/1
Fixed frame for panels	2000	800	PFPPF2080	1STQ007456A0000	1/1
Fixed frame for panels	2000	1000	PFPPF2010	1STQ007457A0000	1/1
Fixed frame for panels	2000	1250	PFPPF2012	1STQ007458A0000	1/1




Special fixed frame for panels

Fixed frame for internal panels; the useful height of the switchboard can be used to full advantage. With fixed frame for panels, maximum wiring ducts dimension is 80x60mm.

The main advantage of the special fixed frame is to permit the addition of MCCBS kit or Din rail kits without having to remove the entire frame with the front panels already installed.

Description	Dimensions (mm)				Pkg/ No. pcs
	H	W	Type	Order code	
Special fixed frame for panels	1800	400	PFFFA1840	1STQ001889B0000	1/1
Special fixed frame for panels	1800	600	PFFFA1860	1STQ001890B0000	1/1
Special fixed frame for panels	1800	800	PFFFA1880	1STQ001891B0000	1/1
Special fixed frame for panels	1800	1000	PFFFA1810	1STQ001892B0000	1/1
Special fixed frame for panels	1800	1250	PFFFA1825	1STQ001893B0000	1/1
Special fixed frame for panels	2000	400	PFFFA2040	1STQ001894B0000	1/1
Special fixed frame for panels	2000	600	PFFFA2060	1STQ001895B0000	1/1
Special fixed frame for panels	2000	800	PFFFA2080	1STQ001896B0000	1/1
Special fixed frame for panels	2000	1000	PFFFA2010	1STQ001897B0000	1/1
Special fixed frame for panels	2000	1250	PFFFA2025	1STQ001898B0000	1/1




Swing frame for panels and counterdoor application

Swing frame for panels, reduces the available useful space by 100mm. After its opening, it is possible to remove all the internal panels at once or one by one. In structures without intermediate upright, swing frame PFPS... cannot be installed with horizontal busbars at all height. In combination with flat blind panel H=1800mm or H=2000mm operates or counterdoor application.

Description	Dimensions (mm)				Pkg/ No. pcs
	H	W	Type	Order code	
Swing frame for panels	1800	400	PFPS1840	1STQ007459A0000	1/1
Swing frame for panels	1800	600	PFPS1860	1STQ007460A0000	1/1
Swing frame for panels	1800	800	PFPS1880	1STQ007461A0000	1/1
Swing frame for panels	2000	400	PFPS2040	1STQ007462A0000	1/1
Swing frame for panels	2000	600	PFPS2060	1STQ007463A0000	1/1
Swing frame for panels	2000	800	PFPS2080	1STQ007464A0000	1/1

Internal kits


Order codes - Internal kits



Intermediate upright for internal kit assembly

Intermediate depth upright for assembling kits for Tmax and Emax 2. The intermediate uprights are not required for assembling fixed Tmax XT1, XT2, XT3, XT4, T4, T5, T6 and XT1, XT3 with Direct Rotary Handle only in nonsegregated structures. Order 2 uprights for the kits.

Description	Dimensions (mm)		Pkg/ No. pcs
	H	Type	
Intermediate upright for internal kits	1800	PUKI1800	1STQ008039A0000
Intermediate upright for internal kits	2000	PUKI2000	1STQ008040A0000




Extension kit for D=300mm structures

To be used as an alternative to the intermediate upright in D=300mm structures.

The extension kit PKEK0004 cannot be mounted on the first cell at the top or at the bottom of the enclosure, but a minimum H=50mm space must be left empty from the top or the bottom. It consists of 4 parts that connect the ends of the kit fixing brackets to the structural rear uprights of D=300mm structures.

Description	Type	Order code	Pkg/ No. pcs
			1/1
Extension kit	PKEK0004	1STQ008198A0000	1/1



Circuit-breakers and busbars that can be installed in D=300mm structures

Only use circuit-breakers with front terminals.

Circuit-breaker version	XT1	XT2	XT3	XT4	T4	T5	T6	T7	E1.1
Fixed	■	■	■	■	■	■	■	●	●
Fixed with Direct Rotary Handle (RHD)	■	◆	■	◆	●	●	●	●	●
Fixed with motor operator (MO)	●	●	●	●	●	●	●	●	●
Fixed interlocked	●	●	●	●	●	●	●	●	●
Fixed interlocked motor-operated								●	●
Plug-in	◆	●	◆	●	●	●			
Plug-in with Direct Rotary Handle (RHD)	●	●	●	●	●	●			
Plug-in with motor operator (MO)	●	●	●	●					
Plug-in interlocked	●		●						
Plug-in interlocked motor-operated									
Withdrawable		●	●	●	●	●	●	●	
Withdrawable with Direct Rotary Handle (RHD)	●	●	●	●	●	●	●	●	
Withdrawable with motor operator (MO)	●		●						
Withdrawable interlocked									
Withdrawable interlocked motor-operated									


Key

- Circuit-breaker for installation with extension in position B
- Circuit-breaker for installation without extension in position A and B
- ◆ Circuit-breaker for installation with extension in position A and B


Internal kits

Order codes - Internal kits

D=300mm structure and cable container without rear upright



D=300mm structure and cable container without rear upright



Circuit-breakers and busbars that can be installed in D=300mm structures with cable container

Only use circuit-breakers with front terminals.



Circuit-breaker version	XT1	XT2	XT3	XT4	T4	T5	T6	T7	E1.1
Circuit-breaker version	■	■	■	■	■	■	■	●	●
Fixed	■	●	■	●	●	●	●	●	●
Fixed with Direct Rotary Handle (RHD)	●	●	●	●	●	●	●	●	●
Fixed with motor operator (MO)	●	●	●	●	●	●	●	●	●
Fixed interlocked								●	●
Fixed interlocked motor-operated	●	●	●	●	●	●	●		
Plug-in	●	●	●	●	●	●	●		
Plug-in with Direct Rotary Handle (RHD)	●	●	●	●					
Plug-in with motor operator (MO)	●		●						
Plug-in interlocked									
Plug-in interlocked motor-operated					●	●	●	●	
Withdrawable		●			●	●	●	●	
Withdrawable with Direct Rotary Handle (RHD)	●				●				
Withdrawable with motor operator (MO)									
Withdrawable interlocked									
Withdrawable interlocked motor-operated									

Key

- Circuit-breaker for installation without extension in C structures
- Circuit-breaker for installation with extension in D structures

Kits for DIN rail*

Swing frame for panels, reduces the available useful space by 100mm. After its opening, it is possible to remove all the internal panels at once or one by one. In structures without intermediate upright, swing frame PFPS.... cannot be installed with horizontal busbars at all height. In combination with flat blind panel H=1800mm or H=2000mm operates or counterdoor application.



Pre-assembled DIN rail kits

Description	Dimensions (mm)			Pkg/ No. pcs
	W	Type	Order code	
Standard DIN rail	400	PDRS0400	1STQ008041A0000	1/1
Standard DIN rail	600	PDRS0600	1STQ008042A0000	1/1
Standard DIN rail	800	PDRS0800	1STQ008043A0000	1/1

*Cable duct 80x60mm.

N° circuit breakers for each DIN rail

Tmax	A (mm)		
	12 mod.	24 mod.	36 mod.
XT1 3P	2	5	8
XT1 4P	2	4	6
XT3 3P	2	4	6
XT3 4P	1	3	4


• Quick selection guides page 2-8

• Technical details page 7-1

• Overall dimensions page 8-1

Internal kits


Order codes - Internal kits



Panels for System Pro-M modular circuit-breakers

Panels with 1/4 turn screws, hinged on the right or the left with the dedicated PHFP0020 kit.

Description	Dimensions (mm)			Pkg/ No. pcs
	H	W	Type	
Panel with 12 DIN modules	150	400	PPMF1540	1STQ008044A0000
Panel with 24 DIN modules	150	600	PPMF1560	1STQ008045A0000
Panel with 36 DIN modules	150	800	PPMF1580	1STQ008046A0000
Panel with 12x2 DIN modules	300	400	PPMF3040	1STQ008050A0000
Panel with 24x2 DIN modules	300	600	PPMF3060	1STQ008051A0000
Panel with 36x2 DIN modules	300	800	PPMF3080	1STQ008052A0000




Panels for System Pro-M modular circuit-breakers and Tmax XT1 and Tmax XT3 moulded-case circuit-breakers not accessored or with differential module side RC sel 200⁽¹⁾

Panels with 1/4 turn screws, hinged on the right or the left with the dedicated PHFP0020 kit.

Description	Dimensions (mm)			Pkg/ No. pcs
	H	W	Type	
Panel with 12 DIN modules	200	400	PPMF2040	1STQ008047A0000
Panel with 24 DIN modules	200	600	PPMF2060	1STQ008048A0000
Panel with 36 DIN modules	200	800	PPMF2080	1STQ008049A0000
Panel with 24 DIN modules	300	600	PPMU3060	1STQ008299A0000
Panel with 36 DIN modules	300	800	PPMU3080	1STQ008300A0000

⁽¹⁾The bracket and glossy plate kit can be ordered from the circuit-breaker catalogue. The sole glossy plate is available among the accessories in this catalogue.



Panels for Tmax XT1 and Tmax XT3 moulded-case circuit-breakers with differential module under-place RC⁽¹⁾


Panels with 1/4 turn screws, hinged on the right or the left with the dedicated PHFP0020 kit.

Description	Dimensions (mm)			Pkg/ No. pcs
	H	W	Type	
Panel with 12 DIN modules	300	400	PPMD3040	1STQ001560B0000
Panel with 24 DIN modules	300	600	PPMD3060	1STQ001561B0000
Panel with 36 DIN modules	300	800	PPMD3080	1STQ001562B0000

⁽¹⁾The bracket and glossy plate kit can be ordered from the circuit-breaker catalogue. The sole glossy plate is available among the accessories in this catalogue.

Internal kits

Order codes - Internal kits



Kits for installation of Tmax circuit-breakers

Horizontal installation (front or rear connections)

The kit includes the dedicated fixing brackets, the mounting plate and panels with 1/4 turn screws, hinged on the right or the left with the dedicated PHFP0020 kit.

Tmax	No. poles	Versions	Dimensions H (mm)	No. CB per compart.	Type	Order code	Pkg/ No. pcs
12 DIN modules - W=400mm							
XT1	3	F - RC	200	1	PHBX1323	1STQ001442B0000	1/1
XT1	3/4	F	150	1	PHBX1401	1STQ007757A0000	1/1
XT1	3/4	F - RHD	150	1	PHBX1405	1STQ007761A0000	1/1
XT1	3/4	F	200	1	PHBX1101	1STQ008473A0000	1/1
XT1	3/4	F - MO	200	1	PHBX1404	1STQ007759A0000	1/1
XT1	3/4	P	200	1	PHBX1407	1STQ007763A0000	1/1
XT1	3/4	P - MO	200	1	PHBX1409	1STQ007765A0000	1/1
XT1	3/4	P - RHD	200	1	PHBX1427	1STQ007767A0000	1/1
XT1	3/4	F - RHD	200	1	PHBX1105	1STQ008475A0000	1/1
XT1	3/4	F - I	500	2	PHBX1422	1STQ008410A0000	1/1
XT1	3/4	F - I-MO	500	2	PHBX1424	1STQ008411A0000	1/1
XT1	3/4	P - I	500	2	PHBX1422	1STQ008410A0000	1/1
XT1	3/4	P - I-MO	500	2	PHBX1424	1STQ008411A0000	1/1
XT1	4	F - RC	200	1	PHBX1423	1STQ007769A0000	1/1
XT2	3	F	150	1	PHBX2301	1STQ007771A0000	1/1
XT2	3	W	200	1	PHBX2310	1STQ007787A0000	1/1
XT2	3	W - MO	200	1	PHBX2312	1STQ007789A0000	1/1
XT2	3	W - RHD	200	1	PHBX2300	1STQ007791A0000	1/1
XT2	3/4	F	200	1	PHBX2401	1STQ007773A0000	1/1
XT2	3/4	F - MO	200	1	PHBX2404	1STQ007775A0000	1/1
XT2	3/4	F - RHD	200	1	PHBX2405	1STQ007779A0000	1/1
XT2	3/4	P	200	1	PHBX2407	1STQ007781A0000	1/1
XT2	4	P - RC	250	1	PHBX2428	1STQ001450B0000	1/1
XT2	3/4	P - MO	200	1	PHBX2409	1STQ007783A0000	1/1
XT2	3/4	P - RHD	200	1	PHBX2427	1STQ007785A0000	1/1
XT2	3/4	W	250	1	PHBX2410	1STQ007793A0000	1/1
XT2	3/4	W - MO	250	1	PHBX2412	1STQ007795A0000	1/1
XT2	3/4	W - RHD	250	1	PHBX2400	1STQ007799A0000	1/1
XT2	3/4	F - I	500	2	PHBX2402	1STQ008412A0000	1/1
XT2	3/4	F - I-MO	500	2	PHBX2424	1STQ008415A0000	1/1
XT2	3/4	P - I	500	2	PHBX2431	1STQ008413A0000	1/1
XT2	3/4	P - I-MO	500	2	PHBX2424	1STQ008415A0000	1/1
XT2	3/4	W - I	500	2	PHBX2425	1STQ008414A0000	1/1
XT2	3/4	W - I-MO	500	2	PHBX2425	1STQ008414A0000	1/1
XT2	4	F - RC	200	1	PHBX2423	1STQ007777A0000	1/1
XT3	3	F	150	1	PHBX3301*	1STQ007801A0000	1/1
XT3	3	F - RHD	150	1	PHBX3305	1STQ007803A0000	1/1
XT3	3/4	F	200	1	PHBX3401*	1STQ007805A0000	1/1
XT3	3/4	F - MO	200	1	PHBX3404	1STQ007807A0000	1/1
XT3	3/4	F - RHD	200	1	PHBX3405	1STQ007809A0000	1/1
XT3	3/4	P	200	1	PHBX3407	1STQ007811A0000	1/1
XT3	3/4	P - MO	200	1	PHBX3409	1STQ007813A0000	1/1
XT3	3/4	P - RHD	200	1	PHBX3427	1STQ007815A0000	1/1
XT3	3/4	F - I	500	2	PHBX3422	1STQ008417A0000	1/1
XT3	3/4	F - I-MO	500	2	PHBX3424	1STQ008418A0000	1/1
XT3	3/4	P - I	500	2	PHBX3422	1STQ008417A0000	1/1

* Not compatible with high terminal covers.


• Quick selection guides page 2-8

• Technical details page 7-1

• Overall dimensions page 8-1

Internal kits

Order codes - Internal kits



Kits for installation of Tmax circuit-breakers

Horizontal installation (front or rear connections)

The kit includes the dedicated fixing brackets, the mounting plate and panels with 1/4 turn screws, hinged on the right or the left with the dedicated PHFP0020 kit.

Tmax	No. poles	Versions	Dimensions H (mm)	No. CB per compart.	Type	Order code	Pkg/ No. pcs
12 DIN modules - W=400mm							
XT3	3/4	P - I-MO	500	2	PHBX3424	1STQ008418A0000	1/1
XT3	4	F - RC	250	1	PHBX3423*	1STQ007817A0000	1/1
XT4	3	F	150	1	PHBX4301*	1STQ007819A0000	1/1
XT4	3/4	F	200	1	PHBX4401*	1STQ007821A0000	1/1
XT4	3/4	F - MO	200	1	PHBX4404	1STQ007823A0000	1/1
XT4	3/4	F - RHD	200	1	PHBX4405	1STQ007827A0000	1/1
XT4	3/4	P	200	1	PHBX4407	1STQ007829A0000	1/1
XT4	4	P - RC	250	1	PHBX4428	1STQ001451B0000	1/1
XT4	3/4	P - MO	200	1	PHBX4409	1STQ007831A0000	1/1
XT4	3/4	P - RHD	200	1	PHBX4427	1STQ007833A0000	1/1
XT4	3/4	W	250	1	PHBX4410	1STQ007835A0000	1/1
XT4	3/4	W - MO	250	1	PHBX4412	1STQ007837A0000	1/1
XT4	3/4	W - RHD	250	1	PHBX4400	1STQ007841A0000	1/1
XT4	3/4	F - I	500	2	PHBX4402	1STQ008419A0000	1/1
XT4	3/4	F - I-MO	500	2	PHBX4424	1STQ008422A0000	1/1
XT4	3/4	P - I	500	2	PHBX4431	1STQ008420A0000	1/1
XT4	3/4	P - I-MO	500	2	PHBX4424	1STQ008422A0000	1/1
XT4	3/4	W - I	500	2	PHBX4425	1STQ008421A0000	1/1
XT4	3/4	W - I-MO	500	2	PHBX4425	1STQ008421A0000	1/1
XT4	4	F - RC	200	1	PHBX4423	1STQ007825A0000	1/1
T4	3	F	150	1	PHBT4301*	1STQ007843A0000	1/1
T4	3/4	F	200	1	PHBT4406*	1STQ007845A0000	1/1
T4	3/4	F - MO	200	1	PHBT4404	1STQ007847A0000	1/1
T4	3/4	F - RHD	200	1	PHBT4406*	1STQ007845A0000	1/1
T4	3/4	F - I	600	2	PHBT4402	1STQ008424A0000	1/1
T5	3	F 400A/630A	200	1	PHBT5306*	1STQ007850A0000	1/1
T5	3	F - MO 400A/630A	200	1	PHBT5304	1STQ007852A0000	1/1

* Not compatible with high terminal covers.

To assemble these kits, order the dedicated intermediate depth uprights PUKI1800 for H= 1800mm or PUKI2000 for H=2000mm. Intermediate uprights are not required for assembling fixed Tmax XT1, XT2, XT3, XT4, T4, T5, T6 and XT1, XT3 with Direct Rotary Handle only in non-segregated structures. Order the dedicated fixed frame PFPPF... or swing frame PFPS... for assembling internal panels. For D=300mm structures, consult the details on page 3/21. For fixed and withdrawable 3P breakers Tmax XT, non accessorized and mounted on 3/4P kit, it is necessary to order the dedicated cover flanges: AD3305 flange for XT1 3P mounted on plate, AD3306 flange for XT2 3P mounted on plate, AD3307 flange for XT3 3P mounted on plate, AD3308 flange for XT4 3P mounted on plate. With interlocked or interlocked motor-operated kits, it is necessary to order the quantity of flanges equal to the quantity of breakers.

Compatible residual current devices:

Tmax XT

RC Inst XT1-XT3, RC Sel. XT1-XT3 and RC Sel.. XT2-XT4 Type A. For XT1-XT3 fixed with residual current device high terminal covers are not available.


Tmax T

RC222 for T4 and T5.

Key:	P - I	plug-in interlocked	W - MO	withdrawable motor-operated	
F	fixed	P - I-MO	plug-in interlocked motoroperated	W - RC	withdrawable with residual current
F - I	fixed interlocked	P - MO	plug-in motor-operated	W - RHD	withdrawable with Direct Rotary Handle
F - I-MO	fixed interlocked motor-operated	P - RC	plug-in with residual current		
F - MO	fixed motor-operated	P - RHD	plug-in with Direct Rotary Handle		
F - RC	fixed with residual current	W	withdrawable	W & W - I	withdrawable and withdrawable interlocked
F - RHD	fixed with Direct Rotary Handle	W - I	withdrawable interlocked		
F & F - I	fixed and fixed interlocked	W - I-MO	withdrawable interlocked		
P	plug-in		motor-operated		

Internal kits

Order codes - Internal kits



Kits for installation of Tmax circuit-breakers

Horizontal installation (front or rear connections)

The kit includes the dedicated fixing brackets, the mounting plate and panels with 1/4 turn screws, hinged on the right or the left with the dedicated PHFP0020 kit.


Tmax	No. poles	Versions	Dimensions H (mm)	No. CB per compart.	Type	Order code	Pkg/ No. pcs
12 DIN modules - W=400mm							
T5	3	F - RHD 400A/630A	200	1	PHBT5306*	1STQ007850A0000	1/1
T5	3	P 400A	200	1	PHBT5326	1STQ007854A0000	1/1
T5	3	P - MO 400A	200	1	PHBT5309	1STQ008406A0000	1/1
T5	3	P - RHD 400A	200	1	PHBT5326	1STQ007854A0000	1/1
T5	3	W 400A	300	1	PHBT5314	1STQ007862A0000	1/1
T5	3	W - MO 400A	300	1	PHBT5312	1STQ008408A0000	1/1
T5	3	W - RHD 400A	300	1	PHBT5314	1STQ007862A0000	1/1
T5	3/4	F 400A/630A	250	1	PHBT5406*	1STQ007856A0000	1/1
T5	3/4	F - MO 400A/630A	250	1	PHBT5404	1STQ007858A0000	1/1
T5	3/4	F - RHD 400A/630A	250	1	PHBT5406*	1STQ007856A0000	1/1
T5	3/4	P 400A	250	1	PHBT5426	1STQ007860A0000	1/1
T5	3/4	P - MO 400A	250	1	PHBT5409	1STQ008407A0000	1/1
T5	3/4	P - RHD 400A	250	1	PHBT5426	1STQ007860A0000	1/1
T5	3/4	W 400A	350	1	PHBT5414	1STQ007864A0000	1/1
T5	3/4	W - MO 400A	350	1	PHBT5412	1STQ008409A0000	1/1
T5	3/4	W - RHD 400A	350	1	PHBT5414	1STQ007864A0000	1/1

* Not compatible with high terminal covers.

Tmax	No. poles	Versions	Dimensions H (mm)	No. CB per compart.	Type	Order code	Pkg/ No. pcs
24 DIN modules - W=600mm							
XT1	3/4	F	200	1	PHCX1101	1STQ008474A0000	1/1
XT1	3	F - RC	200	1	PHCX1323	1STQ001443B0000	1/1
XT1	3/4	F	150	1	PHCX1401	1STQ007758A0000	1/1
XT1	3/4	F - RHD	150	1	PHCX1405	1STQ007762A0000	1/1
XT1	3/4	F - RHD	200	1	PHCX1105	1STQ008476A0000	1/1
XT1	3/4	F - MO	200	1	PHCX1404	1STQ007760A0000	1/1
XT1	3/4	P	200	1	PHCX1407	1STQ007764A0000	1/1
XT1	3/4	P - MO	200	1	PHCX1409	1STQ007766A0000	1/1
XT1	3/4	P - RHD	200	1	PHCX1427	1STQ007768A0000	1/1
XT1	3/4	F - I	500	2	PHCX1422	1STQ008432A0000	1/1
XT1	3/4	F - I-MO	500	2	PHCX1424	1STQ008433A0000	1/1
XT1	3/4	P - I	500	2	PHCX1422	1STQ008432A0000	1/1
XT1	3/4	P - I-MO	500	2	PHCX1424	1STQ008433A0000	1/1
XT1	4	F - RC	200	1	PHCX1423	1STQ007770A0000	1/1
XT2	3	F	150	1	PHCX2301	1STQ007772A0000	1/1
XT2	3	W	200	1	PHCX2310	1STQ007788A0000	1/1
XT2	3	W - MO	200	1	PHCX2312	1STQ007790A0000	1/1
XT2	3	W - RHD	200	1	PHCX2300	1STQ007792A0000	1/1
XT2	3/4	F	200	1	PHCX2401	1STQ007774A0000	1/1
XT2	3/4	F - MO	200	1	PHCX2404	1STQ007776A0000	1/1
XT2	3/4	F - RHD	200	1	PHCX2405	1STQ007780A0000	1/1
XT2	3/4	P	200	1	PHCX2407	1STQ007782A0000	1/1
XT2	3/4	P - MO	200	1	PHCX2409	1STQ007784A0000	1/1

Internal kits

Order codes - Internal kits



Tmax	No. poles	Versions	Dimensions H (mm)	No. CB per compart.	Type	Order code	Pkg/ No. pcs
24 DIN modules - W=600mm							
XT2	3/4	P - RHD	200	1	PHCX2427	1STQ007786A0000	1/1
XT2	3/4	W	250	1	PHCX2410	1STQ007794A0000	1/1
XT2	3/4	W - MO	250	1	PHCX2412	1STQ007796A0000	1/1
XT2	3/4	W - RHD	250	1	PHCX2400	1STQ007800A0000	1/1
XT2	3/4	F - I	500	2	PHCX2402	1STQ008434A0000	1/1
XT2	3/4	F - I-MO	500	2	PHCX2424	1STQ008437A0000	1/1
XT2	3/4	P - I	500	2	PHCX2431	1STQ008435A0000	1/1
XT2	3/4	P - I-MO	500	2	PHCX2424	1STQ008437A0000	1/1
XT2	3/4	W - I	500	2	PHCX2425	1STQ008436A0000	1/1
XT2	3/4	W - I-MO	500	2	PHCX2425	1STQ008436A0000	1/1
XT2	4	F - RC	200	1	PHCX2423	1STQ007778A0000	1/1
XT2	4	W - RC	250	1	PHCX2417	1STQ007798A0000	1/1
XT3	3	F	150	1	PHCX3301	1STQ007802A0000	1/1
XT3	3	F - RHD	150	1	PHCX3305	1STQ007804A0000	1/1
XT3	3/4	F	200	1	PHCX3401	1STQ007806A0000	1/1
XT3	3/4	F - MO	200	1	PHCX3404	1STQ007808A0000	1/1
XT3	3/4	F - RHD	200	1	PHCX3405	1STQ007810A0000	1/1
XT3	3/4	P	200	1	PHCX3407	1STQ007812A0000	1/1
XT3	3/4	P - MO	200	1	PHCX3409	1STQ007814A0000	1/1
XT3	3/4	P - RHD	200	1	PHCX3427	1STQ007816A0000	1/1
XT3	3/4	F - I	500	2	PHCX3422	1STQ008439A0000	1/1
XT3	3/4	F - I-MO	500	2	PHCX3424	1STQ008440A0000	1/1
XT3	3/4	P - I	500	2	PHCX3422	1STQ008439A0000	1/1
XT3	3/4	P - I-MO	500	2	PHCX3424	1STQ008440A0000	1/1
XT3	4	F - RC	250	1	PHCX3423	1STQ007818A0000	1/1
XT4	3	F	150	1	PHCX4301	1STQ007820A0000	1/1
XT4	3/4	F	200	1	PHCX4401	1STQ007822A0000	1/1
XT4	3/4	F - MO	200	1	PHCX4404	1STQ007824A0000	1/1
XT4	3/4	F - RHD	200	1	PHCX4405	1STQ007828A0000	1/1
XT4	3/4	P	200	1	PHCX4407	1STQ007830A0000	1/1
XT4	3/4	P - MO	200	1	PHCX4409	1STQ007832A0000	1/1

To assemble these kits, order the dedicated intermediate depth uprights PUKI1800 for H= 1800mm or PUKI2000 for H=2000mm. Intermediate uprights are not required for assembling fixed Tmax XT1, XT2, XT3, XT4, T4, T5, T6 and XT1, XT3 with Direct Rotary Handle only in non-segregated structures. Order the dedicated fixed frame PPF... or swing frame PFPS... for assembling internal panels. For D=300mm structures, consult the details on page 3/21. For fixed and withdrawable 3P breakers Tmax XT, non accessorized and mounted on 3/4P kit, it is necessary to order the dedicated cover flanges: AD3305 flange for XT1 3P mounted on plate, AD3306 flange for XT2 3P mounted on plate, AD3307 flange for XT3 3P mounted on plate, AD3308 flange for XT4 3P mounted on plate. With interlocked or interlocked motor-operated kits, it is necessary to order the quantity of flanges equal to the quantity of breakers.

Compatible residual current devices:

Tmax XT

RC Inst XT1-XT3, RC Sel. XT1-XT3 and RC Sel.. XT2-XT4 Type A. For XT1-XT3 fixed with residual current device high terminal covers are not available.


Tmax T

RC222 for T4 and T5.

Key:	P - I	plug-in interlocked	W - MO	withdrawable motor-operated	
F	fixed	P - I-MO	plug-in interlocked motoroperated	W - RC	withdrawable with residual current
F - I	fixed interlocked	P - MO	plug-in motor-operated	W - RHD	withdrawable with Direct Rotary Handle
F - I-MO	fixed interlocked motor-operated	P - RC	plug-in with residual current	W & W - I	withdrawable and withdrawable interlocked
F - MO	fixed motor-operated	P - RHD	plug-in with Direct Rotary Handle		
F - RC	fixed with residual current	W	withdrawable		
F - RHD	fixed with Direct Rotary Handle	W - I	withdrawable interlocked		
F & F - I	fixed and fixed interlocked	W - I-MO	withdrawable interlocked		
P	plug-in		motor-operated		

Internal kits

Order codes - Internal kits



Kits for installation of Tmax circuit-breakers


Horizontal installation (front or rear connections)

The kit includes the dedicated fixing brackets, the mounting plate and panels with 1/4 turn screws, hinged on the right or the left with the dedicated PHFP0020 kit.

Tmax	No. poles	Versions	Dimensions H (mm)	No. CB per compart.	Type	Order code	Pkg/ No. pcs
24 DIN modules - W=600mm							
XT4	3/4	P - RHD	200	1	PHCX4427	1STQ007834A0000	1/1
XT4	3/4	W	250	1	PHCX4410	1STQ007836A0000	1/1
XT4	3/4	W - MO	250	1	PHCX4412	1STQ007838A0000	1/1
XT4	3/4	W - RHD	250	1	PHCX4400	1STQ007842A0000	1/1
XT4	3/4	F - I	500	2	PHCX4402	1STQ008441A0000	1/1
XT4	3/4	F - I-MO	500	2	PHCX4424	1STQ008444A0000	1/1
XT4	3/4	P - I	500	2	PHCX4431	1STQ008442A0000	1/1
XT4	3/4	P - I-MO	500	2	PHCX4424	1STQ008444A0000	1/1
XT4	3/4	W - I	500	2	PHCX4425	1STQ008443A0000	1/1
XT4	3/4	W - I-MO	500	2	PHCX4425	1STQ008443A0000	1/1
XT4	4	F - RC	200	1	PHCX4423	1STQ007826A0000	1/1
XT4	4	W - RC	250	1	PHCX4417	1STQ007840A0000	1/1
T4	3	F	150	1	PHCT4301	1STQ007844A0000	1/1
T4	3/4	F	200	1	PHCT4406	1STQ007846A0000	1/1
T4	3/4	F - MO	200	1	PHCT4404	1STQ007848A0000	1/1
T4	3/4	F - RHD	200	1	PHCT4406	1STQ007846A0000	1/1
T4	3/4	F - I	600	2	PHCT4402	1STQ008446A0000	1/1
T4	3/4	F - I-MO	600	2	PHCT4403	1STQ008447A0000	1/1
T4	4	F - RC	200	1	PHCT4423	1STQ007849A0000	1/1
T5	3	F 400A/630A	200	1	PHCT5306	1STQ007851A0000	1/1
T5	3	F - MO 400A/630A	200	1	PHCT5304	1STQ007853A0000	1/1
T5	3	F - RHD 400A/630A	200	1	PHCT5306	1STQ007851A0000	1/1
T5	3	P 400A	200	1	PHCT5326	1STQ007855A0000	1/1
T5	3/4	P 630A	250	1	PHCT5407	1STQ002113B0000	1/1
T5	3	P - MO 400A	200	1	PHCT5309	1STQ008428A0000	1/1
T5	3	P - RHD 400A	200	1	PHCT5326	1STQ007855A0000	1/1
T5	3	W 400A	300	1	PHCT5314	1STQ007863A0000	1/1
T5	3	W - MO 400A	300	1	PHCT5312	1STQ008430A0000	1/1
T5	3/4	P - MO 630A	250	1	PHCT5427	1STQ002114A0000	1/1
T5	3	W - RHD 400A	300	1	PHCT5314	1STQ007863A0000	1/1
T5	3/4	F 400A/630A	250	1	PHCT5406	1STQ007857A0000	1/1
T5	3/4	F - MO 400A/630A	250	1	PHCT5404	1STQ007859A0000	1/1
T5	3/4	F - RHD 400A/630A	250	1	PHCT5406	1STQ007857A0000	1/1
T5	3/4	P 400A	250	1	PHCT5426	1STQ007861A0000	1/1
T5	3/4	P - MO 400A	250	1	PHCT5409	1STQ008429A0000	1/1
T5	3/4	P - RHD 400A	250	1	PHCT5426	1STQ007861A0000	1/1
T5	3/4	W 400A	350	1	PHCT5414	1STQ007865A0000	1/1
T5	3/4	W - MO 400A	350	1	PHCT5412	1STQ008431A0000	1/1
T5	3/4	W - RHD 400A	350	1	PHCT5414	1STQ007865A0000	1/1
T5	3/4	F - I 400A/630A	600	2	PHCT5402	1STQ007868A0000	1/1
T5	3/4	F - I-MO 400A/630A	600	2	PHCT5403	1STQ008448A0000	1/1
T5	3/4	P - I 400A	600	2	PHCT5431	1STQ008449A0000	1/1
T5	3/4	P - I-MO 400A	600	2	PHCT5432	1STQ008450A0000	1/1
T5	3/4	W - I 400A	600	2	PHCT5425	1STQ008451A0000	1/1

Internal kits

Order codes - Internal kits



Tmax	No. poles	Versions	Dimensions H (mm)	No. CB per compart.	Type	Order code	Pkg/ No. pcs
24 DIN modules - W=600mm							
T5	3/4	W - I-MO 400A	600	2	PHCT5411	1STQ008452A0000	1/1
T5	3/4	F - I 400A/630A	600	2	PHCT5402	1STQ007868A0000	1/1
T5	4	F - RC	250	1	PHCT5423	1STQ007866A0000	1/1
T6	3	F	300	1	PHCT6301**	1STQ007877A0000	1/1
T6	3	F - MO	300	1	PHCT6304**	1STQ007879A0000	1/1
T6	3	F - RHD	300	1	PHCT6305**	1STQ007881A0000	1/1
T6	3	W	350	1	PHCT6314^n	1STQ007891A0000	1/1
T6	3	W - MO	350	1	PHCT6312^n	1STQ007889A0000	1/1
T6	3	W - RHD	350	1	PHCT6314^n	1STQ007891A0000	1/1
T6	3/4	F	350	1	PHCT6401**	1STQ007883A0000	1/1
T6	3/4	F - MO	350	1	PHCT6404	1STQ007885A0000	1/1
T6	3/4	F - RHD	350	1	PHCT6405	1STQ007887A0000	1/1
T6	3/4	W	500	1	PHCT6410^n	1STQ007893A0000	1/1
T6	3/4	W - MO	500	1	PHCT6412^n	1STQ007894A0000	1/1
T6	3/4	W - RHD	500	1	PHCT6410^n	1STQ007896A0000	1/1
T6	3/4	F - I	700	2	PHCT6402	1STQ008453A0000	1/1
T6	3/4	F - I-MO	700	2	PHCT6403	1STQ008454A0000	1/1
T6	3/4	W - I	700	2	PHCT6425^n	1STQ008455A0000	1/1
T6	3/4	W - I-MO	700	2	PHCT6411*	1STQ008456A0000	1/1
T7	3	F	300	1	PHCT7329	1STQ007898A0000	1/1
T7	3	F - I	300	1	PHCT7329	1STQ007898A0000	1/1
T7	3	F - I-MO	300	1	PHCT7329	1STQ007898A0000	1/1
T7	3	F - MO	300	1	PHCT7329	1STQ007898A0000	1/1
T7	3	F - RHD	300	1	PHCT7329	1STQ007898A0000	1/1
T7	3/4	F	350	1	PHCT7420	1STQ007899A0000	1/1
T7	3/4	F - MO	350	1	PHCT7420	1STQ007899A0000	1/1
T7	3/4	F - RHD	350	1	PHCT7420	1STQ007899A0000	1/1
T7	3/4	F - I	400	1	PHCT7418	1STQ007900A0000	1/1
T7	3/4	F - I-MO	400	1	PHCT7418	1STQ007900A0000	1/1

** T6 1000A front terminals in width 800mm.

■ Front terminals, only Form 1

To assemble these kits, order the dedicated intermediate depth uprights PUKI1800 for H= 1800mm or PUKI2000 for H=2000mm. Intermediate uprights are not required for assembling fixed Tmax XT1, XT2, XT3, XT4, T4, T5, T6 and XT1, XT3 with Direct Rotary Handle only in non-segregated structures. Order the dedicated fixed frame PFPF.... or swing frame PFPS.... for assembling internal panels. For D=300mm structures, consult the details on page 3/21. For fixed and withdrawable 3P breakers Tmax XT, non accessorized and mounted on 3/4P kit, it is necessary to order the dedicated cover flanges: AD3305 flange for XT1 3P mounted on plate, AD3306 flange for XT2 3P mounted on plate, AD3307 flange for XT3 3P mounted on plate, AD3308 flange for XT4 3P mounted on plate. With interlocked or interlocked motor-operated kits, it is necessary to order the quantity of flanges equal to the quantity of breakers.

Compatible residual current devices:

Tmax XT

RC Inst XT1-XT3, RC Sel. XT1-XT3 and RC Sel.. XT2-XT4 Type A. For XT1-XT3 fixed with residual current device high terminal covers are not available.


Tmax T

RC222 for T4 and T5.

Key:	P - I	plug-in interlocked	W - MO	withdrawable motor-operated	
F	fixed	P - I-MO	plug-in interlocked motoroperated	W - RC	withdrawable with residual current
F - I	fixed interlocked	P - MO	plug-in motor-operated	W - RHD	withdrawable with Direct Rotary Handle
F - I-MO	fixed interlocked motor-operated	P - RC	plug-in with residual current	W & W - I	withdrawable and withdrawable interlocked
F - MO	fixed motor-operated	P - RHD	plug-in with Direct Rotary Handle		
F - RC	fixed with residual current	W	withdrawable		
F - RHD	fixed with Direct Rotary Handle	W - I	withdrawable interlocked		
F & F - I	fixed and fixed interlocked	W - I-MO	withdrawable interlocked motor-operated		
P	plug-in				

Internal kits

Order codes - Internal kits



Kits for installation of Tmax circuit-breakers

Horizontal installation (front or rear connections)

The kit includes the dedicated fixing brackets, the mounting plate and panels with 1/4 turn screws, hinged on the right or the left with the dedicated PHFP0020 kit.

Tmax	No. poles	Versions	Dimensions H (mm)	No. CB per compart.	Type	Order code	Pkg/ No. pcs
24 DIN modules - W=600mm							
T7	3/4	W	500	1	PHCT7430 *	1STQ007902A0000	1/1
T7	3/4	W - I	500	1	PHCT7430 *	1STQ007902A0000	1/1
T7	3/4	W - I-MO	500	1	PHCT7430 *	1STQ007902A0000	1/1
T7	3/4	W - MO	500	1	PHCT7430 *	1STQ007902A0000	1/1
T7	3/4	W - RHD	500	1	PHCT7430 *	1STQ007902A0000	1/1

Tmax	No. poles	Versions	Dimensions H (mm)	No. CB per compart.	Type	Order code	Pkg/ No. pcs
36 DIN modules - W=800mm							
XT1	3/4	F	150	1	PHDX1301	1STQ002098B0000	1/1
XT1	3/4	F	200	1	PHDX1401	1STQ002097B0000	1/1
XT1 NEW	3/4	F - MO	200	1	PHDX1404	1STQ002427B0000	1/1
XT1 NEW	4	F - RC	200	1	PHDX1423	1STQ001472B0000	1/1
XT1	3/4	F - RHD	200	1	PHDX1105	1STQ002426B0000	1/1
XT1 NEW	3/4	P	200	1	PHDX1407	1STQ002428B0000	1/1
XT1 NEW	3/4	P - MO	200	1	PHDX1409	1STQ002430B0000	1/1
XT1 NEW	3/4	P - RHD	200	1	PHDX1427	1STQ002429B0000	1/1
XT1 NEW	3/4	P - I	500	2	PHDX1422	1STQ002432B0000	1/1
XT1 NEW	3/4	P - I - MO	500	2	PHDX1424	1STQ002431B0000	1/1
XT1 NEW	3/4	F - I	500	2	PHDX1402	1STQ002125B0000	1/1
XT1 NEW	3/4	F - I - MO	500	2	PHDX1403	1STQ002126B0000	1/1
XT2	3/4	F	200	1	PHDX2401	1STQ001444B0000	1/1
XT2	3/4	P	200	1	PHDX2407	1STQ002099B0000	1/1
XT2	3/4	F - MO	200	1	PHDX2404	1STQ001445B0000	1/1
XT2	4	F - RC	200	1	PHDX2423	1STQ001446B0000	1/1
XT2 NEW	3/4	F - RHD	200	1	PHDX2405	1STQ002433B0000	1/1
XT2 NEW	3/4	P - RHD	200	1	PHDX2427	1STQ002434B0000	1/1
XT2	4	P - RC	250	1	PHDX2428	1STQ001464B0000	1/1
XT2 NEW	3/4	P - MO	200	1	PHDX2409	1STQ002100B0000	1/1
XT2 NEW	3/4	W	250	1	PHDX2410	1STQ002435B0000	1/1
XT2 NEW	3/4	W - RHD	250	1	PHDX2400	1STQ002436B0000	1/1
XT2 NEW	3/4	W - RC	250	1	PHDX2417	1STQ002437B0000	1/1
XT2 NEW	3/4	W - MO	250	1	PHDX2412	1STQ002438B0000	1/1
XT2 NEW	3/4	W - I - MO	500	2	PHDX2425	1STQ002439B0000	1/1
XT2 NEW	3/4	F - I	500	2	PHDX2402	1STQ002127B0000	1/1
XT2 NEW	3/4	F - I - MO	500	2	PHDX2403	1STQ002128B0000	1/1
XT2 NEW	3/4	P - I	500	2	PHDX2432	1STQ002129B0000	1/1
XT3	3/4	F	200	1	PHDX3401	1STQ002101B0000	1/1
XT3 NEW	3/4	F - MO	200	1	PHDX3404	1STQ002441B0000	1/1
XT3 NEW	3/4	F - RHD	200	1	PHDX3405	1STQ002440B0000	1/1
XT3	4	F - RC	200	1	PHDX3423	1STQ001473B0000	1/1
XT3	3/4	P	200	1	PHDX3407	1STQ002106B0000	1/1


** T6 1000A front terminals in width 800mm.

■ Front terminals, only Form 1

* Only rear terminals

Internal kits

Order codes - Internal kits



Tmax	No. poles	Versions	Dimensions H (mm)	No. CB per compart.	Type	Order code	Pkg/ No. pcs
36 DIN modules - W=800mm							
XT3 NEW	3/4	P - RHD	200	1	PHDX3427	1STQ002442B0000	1/1
XT3 NEW	3/4	P - MO	200	1	PHDX3409	1STQ002443B0000	1/1
XT3 NEW	3/4	F - I	500	2	PHDX3402	1STQ002102B0000	1/1
XT3 NEW	3/4	F - I - MO	500	2	PHDX3403	1STQ002104B0000	1/1
XT4	3/4	F	200	1	PHDX4401	1STQ001447B0000	1/1
XT4	3/4	F - RHD	200	1	PHDX4405	1STQ002131B0000	1/1
XT4	3/4	F - MO	200	1	PHDX4404	1STQ001448B0000	1/1
XT4	4	F - RC	200	1	PHDX4423	1STQ001449B0000	1/1
XT4	3/4	P	200	1	PHDX4407	1STQ002110B0000	1/1
XT4 NEW	3/4	P - RHD	200	1	PHDX4427	1STQ002444B0000	1/1
XT4	4	P - RC	250	1	PHDX4428	1STQ001451B0000	1/1
XT4 NEW	3/4	W	250	1	PHDX4410	1STQ002445B0000	1/1
XT4 NEW	3/4	W - RHD	250	1	PHDX4400	1STQ002446B0000	1/1
XT4 NEW	3/4	W - RC	250	1	PHDX4417	1STQ002447B0000	1/1
XT4 NEW	3/4	W - MO	250	1	PHDX4412	1STQ002448B0000	1/1
XT4 NEW	3/4	W - I - MO	500	2	PHDX4425	1STQ002449B0000	1/1
XT4 NEW	3/4	F - I	500	2	PHDX4402	1STQ002107B0000	1/1
XT4 NEW	3/4	F - I - MO	500	2	PHDX4403	1STQ002108B0000	1/1
XT4 NEW	3/4	P - I	500	2	PHDX4422	1STQ002112B0000	1/1
T4	3/4	F - I	600	2	PHDT4402	1STQ008463A0000	1/1
T4	3/4	F - I-MO	600	2	PHDT4403	1STQ008464A0000	1/1
T5	3	F 400A/630A	200	1	PHDT5306	1STQ007869A0000	1/1
T5	3	F - MO 400A/630A	200	1	PHDT5304	1STQ007870A0000	1/1
T5	3	F - RHD 400A/630A	200	1	PHDT5306	1STQ007869A0000	1/1
T5	3P	P - MO 400A	200	1	PHDT5309	1STQ008457A0000	1/1
T5	3	P 400A	200	1	PHDT5326	1STQ007871A0000	1/1
T5	3P	P - MO 400A	200	1	PHDT5309	1STQ008457A0000	1/1
T5	3	P - RHD 400A	200	1	PHDT5326	1STQ007871A0000	1/1
T5	3	W 400A	300	1	PHDT5314	1STQ007875A0000	1/1
T5	3P	W - MO 400A	300	1	PHDT5312	1STQ008459A0000	1/1
T5	3	W - RHD 400A	300	1	PHDT5314	1STQ007875A0000	1/1
T5	3/4	F 400A/630A	250	1	PHDT5406	1STQ007872A0000	1/1
T5	3/4	F - MO 400A/630A	250	1	PHDT5404	1STQ007873A0000	1/1

To assemble these kits, order the dedicated intermediate depth uprights PUKI1800 for H= 1800mm or PUKI2000 for H=2000mm. Intermediate uprights are not required for assembling fixed Tmax XT1, XT2, XT3, XT4, T4, T5, T6 and XT1, XT3 with Direct Rotary Handle only in non-segregated structures. Order the dedicated fixed frame PF Pf... or swing frame PF Pf... for assembling internal panels. For D=300mm structures, consult the details on page 3/21. For fixed and withdrawable 3P breakers Tmax XT, non accessorized and mounted on 3/4P kit, it is necessary to order the dedicated cover flanges: AD3305 flange for XT1 3P mounted on plate, AD3303 flange for XT2 3P mounted on plate, AD3307 flange for XT3 3P mounted on plate, AD3308 flange for XT4 3P mounted on plate. With interlocked or interlocked motor-operated kits, it is necessary to order the quantity of flanges equal to the quantity of breakers.

Compatible residual current devices:

Tmax XT

RC Inst XT1-XT3, RC Sel. XT1-XT3 and RC Sel.. XT2-XT4 Type A. For XT1-XT3 fixed with residual current device high terminal covers are not available.


Tmax T

RC222 for T4 and T5.

Key:	P - I	plug-in interlocked	W - MO	withdrawable motor-operated
F fixed	P - I-MO	plug-in interlocked motor-operated	W - RC	withdrawable with residual current
F - I fixed interlocked	P - MO	plug-in motor-operated	W - RHD	withdrawable with Direct Rotary Handle
F - I-MO fixed interlocked motor-operated	P - RC	plug-in with residual current	W & W - I	withdrawable and withdrawable interlocked
F - MO fixed motor-operated	P - RHD	plug-in with Direct Rotary Handle		
F - RC fixed with residual current	W	withdrawable		
F - RHD fixed with Direct Rotary Handle	W - I	withdrawable interlocked		
F & F - I fixed and fixed interlocked	W - I-MO	withdrawable interlocked motor-operated		
P plug-in				

Internal kits

Order codes - Internal kits



Kits for installation of Tmax circuit-breakers

Horizontal installation (front or rear connections)

The kit includes the dedicated fixing brackets, the mounting plate and panels with 1/4 turn screws, hinged on the right or the left with the dedicated PHFP0020 kit.

Tmax	No. poles	Versions	Dimensions H (mm)	No. CB per compart.	Type	Order code	Pkg/ No. pcs
36 DIN modules - W=800mm							
T5	3/4	F - RHD 400A/630A	250	1	PHDT5406	1STQ007872A0000	1/1
T5	3/4	P 400A	250	1	PHDT5426	1STQ007874A0000	1/1
T5 NEW	3/4	P 630A	250	1	PHDT5407	1STQ002115B0000	1/1
T5	3/4	P - MO 400A	250	1	PHDT5409	1STQ008458A0000	1/1
T5 NEW	3/4	P - MO 630A	250	1	PHDT5428	1STQ002116B0000	1/1
T5	3/4	P - RHD 400A	250	1	PHDT5426	1STQ007874A0000	1/1
T5	3/4	W 400A	350	1	PHDT5414	1STQ007876A0000	1/1
T5	3/4	W - MO 400A	350	1	PHDT5412	1STQ008460A0000	1/1
T5	3/4	W - RHD 400A	350	1	PHDT5414	1STQ007876A0000	1/1
T5	3/4	W - I 400A	600	1	PHDT5425	1STQ008461A0000	1/1
T5	3/4	W - I - MO 400A	600	1	PHDT5411	1STQ008462A0000	1/1
T5 NEW	3/4	P - I 630A	600	2	PHDT5431	1STQ002119B0000	1/1
T5 NEW	3/4	P - I - MO 630A	600	2	PHDT5432	1STQ002120B0000	1/1
T5	4	F - RC 400A	250	1	PHDT5423	1STQ007867A0000	1/1
T5	4	F - RC	250	1	PHDT5423	1STQ007867A0000	1/1
T6	3	F	300	1	PHDT6301	1STQ007878A0000	1/1
T6	3	F - MO	300	1	PHDT6304	1STQ007880A0000	1/1
T6	3	F - RHD	300	1	PHDT6305	1STQ007882A0000	1/1
T6	3	W	350	1	PHDT6314 ■	1STQ007892A0000	1/1
T6	3	W - MO	350	1	PHDT6312 ■	1STQ007890A0000	1/1
T6	3	W - RHD	350	1	PHDT6314 ■	1STQ007892A0000	1/1
T6	3/4	F	350	1	PHDT6401	1STQ007884A0000	1/1
T6	3/4	F - MO	350	1	PHDT6404	1STQ007886A0000	1/1
T6	3/4	F - RHD	350	1	PHDT6405	1STQ007888A0000	1/1
T6	3/4	W	500	1	PHDT6414 ■	1STQ007897A0000	1/1
T6	3/4	W - MO	500	1	PHDT6412 ■	1STQ007895A0000	1/1
T6	3/4	W - RHD	500	1	PHDT6414 ■	1STQ007897A0000	1/1
T6 NEW	3/4	F - I	700	2	PHDT6402	1STQ002121B0000	1/1
T6 NEW	3/4	F - I - MO	700	2	PHDT6403	1STQ002122B0000	1/1
T7	3	F	300	1	PHDT7329	1STQ007903A0000	1/1
T7	3	F - I	300	1	PHDT7329	1STQ007903A0000	1/1
T7	3	F - I - MO	300	1	PHDT7329	1STQ007903A0000	1/1
T7	3	F - MO	300	1	PHDT7329	1STQ007903A0000	1/1
T7	3	F - RHD	300	1	PHDT7329	1STQ007903A0000	1/1
T7	3/4	F	350	1	PHDT7420	1STQ007904A0000	1/1
T7	3/4	F - MO	350	1	PHDT7420	1STQ007904A0000	1/1
T7	3/4	F - RHD	350	1	PHDT7420	1STQ007904A0000	1/1
T7	3/4	F - I	400	1	PHDT7418	1STQ007905A0000	1/1
T7	3/4	F - I - MO	400	1	PHDT7418	1STQ007905A0000	1/1
T7	3/4	W	500	1	PHDT7430 *	1STQ007907A0000	1/1
T7	3/4	W - I	500	1	PHDT7430 *	1STQ007907A0000	1/1
T7	3/4	W - I - MO	500	1	PHDT7430 *	1STQ007907A0000	1/1
T7	3/4	W - MO	500	1	PHDT7430 *	1STQ007907A0000	1/1
T7	3/4	W - RHD	500	1	PHDT7430 *	1STQ007907A0000	1/1

■ Front terminals, only Form 1


• Quick selection guides page 2-8

• Technical details page 7-1

• Overall dimensions page 8-1

Internal kits

Order codes - Internal kits



Kits for installation of Emax 2 circuit-breakers

Horizontal installation (front or rear connections)

The kit includes the dedicated fixing brackets, the mounting plate and panels with 1/4 turn screws, hinged on the right or the left with the dedicated PHFP0020 kit.

No. Emax poles	Versions	Dimensions H (mm)	No. CB per compartment	Type	Order code	Pkg/ No. pcs
24 DIN modules - W=600mm						
E1.2	3/4 F	400	1	PHCE1241	1STQ008151A0000	1/1
E1.2	3/4 F-I	400	1	PHCE1241	1STQ008151A0000	1/1
E1.2	3/4 W	500	1	PHCE1240 *	1STQ008164A0000	1/1
E1.2	3/4 W-I	500	1	PHCE1240 *	1STQ008164A0000	1/1
36 DIN modules - W=800mm						
E1.2	3/4 F	400	1	PHDE1241	1STQ008150A0000	1/1
E1.2	3/4 F-I	400	1	PHDE1241	1STQ008150A0000	1/1
E1.2	3/4 W	500	1	PHDE1240 *	1STQ008386A0000	1/1
E1.2	3/4 W-I	500	1	PHDE1240 *	1STQ008386A0000	1/1

* Only rear terminals

To assemble these kits, order the dedicated intermediate depth uprights PUKI1800 for H= 1800mm or PUKI2000 for H=2000mm. Order the dedicated fixed frame PFPF.... or swing frame PFPS.... for assembling internal panels.

Key:

- F fixed
- F - I fixed interlocked
- W withdrawable
- W - I withdrawable interlocked

■ Front terminals, only Form 1

* Only rear terminals

To assemble these kits, order the dedicated intermediate depth uprights PUKI1800 for H= 1800mm or PUKI2000 for H=2000mm. Intermediate uprights are not required for assembling fixed Tmax XT1, XT2, XT3, XT4, T4, T5, T6 and XT1, XT3 with Direct Rotary Handle only in non-segregated structures. Order the dedicated fixed frame PFPF.... or swing frame PFPS.... for assembling internal panels. For D=300mm structures, consult the details on page 3/21. For fixed and withdrawable 3P breakers Tmax XT, non accessorized and mounted on 3/4P kit, it is necessary to order the dedicated cover flanges: AD3305 flange for XT1 3P mounted on plate, AD3306 flange for XT2 3P mounted on plate, AD3307 flange for XT3 3P mounted on plate, AD3308 flange for XT4 3P mounted on plate. With interlocked or interlocked motor-operated kits, it is necessary to order the quantity of flanges equal to the quantity of breakers.

Compatible residual current devices:

Tmax XT

RC Inst XT1-XT3, RC Sel. XT1-XT3 and RC Sel.. XT2-XT4 Type A. For XT1-XT3 fixed with residual current device high terminal covers are not available.


Tmax T

RC222 for T4 and T5.

Key:	P - I	plug-in interlocked	W - MO	withdrawable motor-operated
F fixed	P - I-MO	plug-in interlocked motoroperated	W - RC	withdrawable with residual current
F - I fixed interlocked	P - MO	plug-in motor-operated	W - RHD	withdrawable with Direct Rotary Handle
F - I-MO fixed interlocked motor-operated	P - RC	plug-in with residual current	W & W - I	withdrawable and withdrawable interlocked
F - MO fixed motor-operated	P - RHD	plug-in with Direct Rotary Handle		
F - RC fixed with residual current	W	withdrawable		
F - RHD fixed with Direct Rotary Handle	W - I	withdrawable interlocked		
F & F - I fixed and fixed interlocked	W - I-MO	withdrawable interlocked motor-operated		
P plug-in				

Internal kits

Order codes - Internal kits



Kits for installation of Tmax circuit-breakers

Vertical installation (front or rear connections)

The kit includes the dedicated fixing brackets, the mounting plate and panels with 1/4 turn screws, hinged on the right or the left with the dedicated PHFP0020 kit.

Tmax	No. poles	Versions	Dimensions H (mm)	No. CB per compart.	Type	Order code	Pkg/ No. pcs
12 DIN modules - W=400mm							
XT1	3/4	F	300	1	PVBX1401	1STQ007908A0000	1/1
XT1	3/4	F - MO	300	1	PVBX1404	1STQ008465A0000	1/1
XT1	3/4	F - RHD	300	1	PVBX1405	1STQ007912A0000	1/1
XT1	3/4	P	300	1	PVBX1407	1STQ007914A0000	1/1
XT1	3/4	P - MO	300	1	PVBX1409	1STQ007916A0000	1/1
XT1	3/4	P - RHD	300	1	PVBX1427	1STQ007918A0000	1/1
XT1	4	F - RC	300	1	PVBX1423	1STQ007910A0000	1/1
XT1	3/4	F - MO	300	1	PVBX1404	1STQ008465A0000	1/1
XT2	3/4	F - MO	300	1	PVBX2404	1STQ008466A0000	1/1
XT2	3/4	F	300	1	PVBX2401	1STQ007921A0000	1/1
XT2	3/4	F - RHD	300	1	PVBX2405	1STQ007925A0000	1/1
XT2	3/4	P	300	1	PVBX2407	1STQ007927A0000	1/1
XT2	3/4	P - MO	300	1	PVBX2409	1STQ007931A0000	1/1
XT2	3/4	P - RHD	300	1	PVBX2427	1STQ007933A0000	1/1
XT2	3/4	W	300	1	PVBX2410	1STQ007935A0000	1/1
XT2	3/4	W - MO	300	1	PVBX2412	1STQ007937A0000	1/1
XT2	3/4	W - RHD	300	1	PVBX2400	1STQ007939A0000	1/1
XT2	4	F - RC	350	1	PVBX2423	1STQ007941A0000	1/1
XT2	4	W - RC	350	1	PVBX2417	1STQ007943A0000	1/1
XT3	3/4	F	300	1	PVBX3401	1STQ007945A0000	1/1
XT3	3/4	F - MO	300	1	PVBX3404	1STQ008467A0000	1/1
XT3	3/4	F - RHD	300	1	PVBX3405	1STQ007947A0000	1/1
XT3	3/4	P	300	1	PVBX3407	1STQ007949A0000	1/1
XT3	3/4	P - MO	300	1	PVBX3409	1STQ007952A0000	1/1
XT3	3/4	P - RHD	300	1	PVBX3427	1STQ007954A0000	1/1
XT3	4	F - RC	400	1	PVBX3423	1STQ007956A0000	1/1
XT4	3/4	F	300	1	PVBX4401	1STQ007960A0000	1/1

To assemble these kits, order the dedicated intermediate depth uprights PUKI1800 for H=1800mm or PUKI2000 for H=2000mm.

Intermediate uprights are not required for assembling fixed Tmax XT1, XT2, XT3, XT4, T4, T5, T6 and XT1, XT3 with Direct Rotary Handle only in non-segregated structures. Order the dedicated fixed frame PFPPF.... or swing frame PFPS.... for assembling internal panels. For D=300mm structures, consult the details on page 3/21. For fixed and withdrawable 3P breakers Tmax XT, non accessorized and mounted on 3/4P kit, it is necessary to order the dedicated cover flanges: AD3305 flange for XT1 3P mounted on plate, AD3306 flange for XT2 3P mounted on plate, AD3307 flange for XT3 3P mounted on plate, AD3308 flange for XT4 3P mounted on plate. With interlocked or interlocked motor-operated kits, it is necessary to order the quantity of flanges equal to the quantity of breakers.

Compatible residual current devices:

Tmax XT

RC Inst XT1-XT3, RC Sel. XT1-XT3 and RC Sel.. XT2-XT4 Type A. For XT1-XT3 fixed with residual current device high terminal covers are not available.


Tmax T

RC222 for T4 and T5.

Key:	P - I	plug-in interlocked	W - MO	withdrawable motor-operated	
F	fixed	P - I-MO	plug-in interlocked motoroperated	W - RC	withdrawable with residual current
F - I	fixed interlocked	P - MO	plug-in motor-operated	W - RHD	withdrawable with Direct Rotary Handle
F - I-MO	fixed interlocked motor-operated	P - RC	plug-in with residual current	W - W - I	withdrawable and withdrawable interlocked
F - MO	fixed motor-operated	P - RHD	plug-in with Direct Rotary Handle		
F - RC	fixed with residual current	W	withdrawable		
F - RHD	fixed with Direct Rotary Handle	W - I	withdrawable interlocked		
F & F - I	fixed and fixed interlocked	W - I-MO	withdrawable interlocked motor-operated		
P	plug-in				

Internal kits

Order codes - Internal kits



Kits for installation of Tmax circuit-breakers

Vertical installation (front or rear connections)

The kit includes the dedicated fixing brackets, the mounting plate and panels with 1/4 turn screws, hinged on the right or the left with the dedicated PHFP0020 kit.


Tmax	No. poles	Versions	Dimensions H (mm)	No. CB per compart.	Type	Order code	Pkg/ No. pcs
12 DIN modules - W=400mm							
XT4	3/4	F - MO	300	1	PVBX4404	1STQ008468A0000	1/1
XT4	3/4	F - RHD	300	1	PVBX4405	1STQ007964A0000	1/1
XT4	3/4	P	350	1	PVBX4407	1STQ007966A0000	1/1
XT4	3/4	P - MO	350	1	PVBX4409	1STQ007970A0000	1/1
XT4	3/4	P - RHD	350	1	PVBX4427	1STQ007972A0000	1/1
XT4	3/4	W	350	1	PVBX4410	1STQ007974A0000	1/1
XT4	3/4	W - MO	350	1	PVBX4412	1STQ007976A0000	1/1
XT4	3/4	W - RHD	350	1	PVBX4400	1STQ007978A0000	1/1
XT4	4	F - RC	400	1	PVBX4423	1STQ007958A0000	1/1
XT4	4	W - RC	400	1	PVBX4417	1STQ007980A0000	1/1
T4	3/4	F	350	1	PVBT4406	1STQ007982A0000	1/1
T4	3/4	F - MO	350	1	PVBT4404	1STQ007984A0000	1/1
T4	3/4	F - RHD	350	1	PVBT4406	1STQ007982A0000	1/1
T4	4	F - RC	450	1	PVBT4423	1STQ007986A0000	1/1
T5	3/4	F 400A/630A	350	1	PVBT5406	1STQ007988A0000	1/1
T5	3/4	F - MO 400A/630A	350	1	PVBT5404	1STQ007990A0000	1/1
T5	3/4	F - RHD 400A/630A	350	1	PVBT5406	1STQ007988A0000	1/1
T5	3/4	P 400A	350	1	PVBT5426	1STQ007992A0000	1/1
T5 NEW	3/4	P - MO 630A	400	1	PVBT5409	1STQ002132B0000	1/1
T5	3/4	P - RHD 400A	350	1	PVBT5426	1STQ007992A0000	1/1
T5	3/4	W 400A	350	1	PVBT5414	1STQ007993A0000	1/1
T5	3/4	W - MO 400A	350	1	PVBT5412	1STQ007995A0000	1/1
T5	3/4	W - RHD 400A	350	1	PVBT5414	1STQ007993A0000	1/1
T5	4	F - RC 400A	450	1	PVBT5423	1STQ007998A0000	1/1
T5	4	P - RC 400A	450	1	PVBT5428	1STQ008001A0000	1/1
T5	3	W 630A	450	1	PVBT5319 ■	1STQ001470B0000	1/1
T6	3	W	450	1	PVBT6314 ■	1STQ008024A0000	1/1
T6	3	W - MO	450	1	PVBT6312 ■	1STQ008025A0000	1/1
T6	3	W - RHD	450	1	PVBT6314 ■	1STQ008024A0000	1/1
T6	3/4	F	400	1	PVBT6401	1STQ008015A0000	1/1
T6	3/4	F - MO	400	1	PVBT6404	1STQ008018A0000	1/1
T6	3/4	F - RHD	400	1	PVBT6405	1STQ008021A0000	1/1

Tmax	No. poles	Versions	Dimensions H (mm)	No. CB per compart.	Type	Order code	Pkg/ No. pcs
24 DIN modules - W=600mm							
XT1	3/4	F	300	1	PVCX1401	1STQ007909A0000	1/1
XT1	3	F	300	4	PVCX1301	1STQ001885B0000	1/1
XT1	3/4	F - MO	300	1	PVCX1404	1STQ008469A0000	1/1
XT1	3/4	F - RHD	300	1	PVCX1405	1STQ007913A0000	1/1
XT1	3/4	P	300	1	PVCX1407	1STQ007915A0000	1/1
XT1	3/4	P	300	3	PVCX1707	1STQ009146A0000	1/1
XT1	3/4	P - MO	300	1	PVCX1409	1STQ007917A0000	1/1

■ Front terminals, only Form 1

Internal kits

Order codes - Internal kits



Tmax	No. poles	Versions	Dimensions H (mm)	No. CB per compart.	Type	Order code	Pkg/ No. pcs
24 DIN modules - W=600mm							
XT1	3/4	P - RHD	300	1	PVCX1427	1STQ007919A0000	1/1
XT1	4	F - RC	300	1	PVCX1423	1STQ007911A0000	1/1
XT2	3/4	F	300	3	PVCX2701	1STQ007923A0000	1/1
XT2	3/4	F	300	1	PVCX2401	1STQ007922A0000	1/1
XT2	3/4	F - MO	300	1	PVCX2404	1STQ008470A0000	1/1
XT2	3/4	F - RHD	300	1	PVCX2405	1STQ007926A0000	1/1
XT2	3/4	P	300	3	PVCX2707	1STQ007929A0000	1/1
XT2	3/4	P	300	1	PVCX2407	1STQ007928A0000	1/1
XT2	3/4	P - MO	300	1	PVCX2409	1STQ007932A0000	1/1
XT2	3/4	P - RHD	300	1	PVCX2427	1STQ007934A0000	1/1
XT2	3/4	W	300	1	PVCX2410	1STQ007936A0000	1/1
XT2	3/4	W - MO	300	1	PVCX2412	1STQ007938A0000	1/1
XT2	3/4	W - RHD	300	1	PVCX2400	1STQ007940A0000	1/1
XT2	4	F - RC	350	1	PVCX2423	1STQ007942A0000	1/1
XT2	4	W - RC	350	1	PVCX2417	1STQ007944A0000	1/1
XT3	3	P	300	3	PVCX3707	1STQ009149A0000	1/1
XT3	3/4	F	300	1	PVCX3401	1STQ007946A0000	1/1
XT3	3	F	300	3	PVCX3301	1STQ001886B0000	1/1
XT3	3/4	F - MO	300	1	PVCX3404	1STQ008471A0000	1/1
XT3	3/4	F - RHD	300	1	PVCX3405	1STQ007948A0000	1/1
XT3	3/4	P	300	1	PVCX3407	1STQ007950A0000	1/1
XT3	3/4	P	300	2	PVCX3607	1STQ009148A0000	1/1
XT3	3/4	P - MO	300	1	PVCX3409	1STQ007953A0000	1/1
XT3	3/4	P - RHD	300	1	PVCX3427	1STQ007955A0000	1/1
XT3	4	F - RC	400	1	PVCX3423	1STQ007957A0000	1/1
XT4	3/4	F	300	1	PVCX4401	1STQ007961A0000	1/1
XT4	3/4	F	300	2	PVCX4601	1STQ009142A0000	1/1
XT4	3	F	300	3	PVCX4701	1STQ007962A0000	1/1
XT4	3/4	F - MO	300	1	PVCX4404	1STQ008472A0000	1/1
XT4	3/4	F - RHD	300	1	PVCX4405	1STQ007965A0000	1/1
XT4	3	P	350	3	PVCX4707	1STQ007968A0000	1/1
XT4	3/4	P	350	1	PVCX4407	1STQ007967A0000	1/1
XT4	3/4	P	350	2	PVCX4607	1STQ009144A0000	1/1

To assemble these kits, order the dedicated intermediate depth uprights PUKI1800 for H=1800mm or PUKI2000 for H=2000mm.

Intermediate uprights are not required for assembling fixed Tmax XT1, XT2, XT3, XT4, T4, T5, T6 and XT1, XT3 with Direct Rotary Handle only in non-segregated structures. Order the dedicated fixed frame PFPPF.... or swing frame PFPS.... for assembling internal panels. For D=300mm structures, consult the details on page 3/21. For fixed and withdrawable 3P breakers Tmax XT, non accessorized and mounted on 3/4P kit, it is necessary to order the dedicated cover flanges: AD3305 flange for XT1 3P mounted on plate, AD3306 flange for XT2 3P mounted on plate, AD3307 flange for XT3 3P mounted on plate, AD3308 flange for XT4 3P mounted on plate. With interlocked or interlocked motor-operated kits, it is necessary to order the quantity of flanges equal to the quantity of breakers.

Compatible residual current devices:

Tmax XT

RC Inst XT1-XT3, RC Sel. XT1-XT3 and RC Sel.. XT2-XT4 Type A. For XT1-XT3 fixed with residual current device high terminal covers are not available.

Tmax T

RC222 for T4 and T5.

Key:


F	fixed
F - I	fixed interlocked
F - I-MO	fixed interlocked motor-operated
F - MO	fixed motor-operated
F - RC	fixed with residual current
F - RHD	fixed with Direct Rotary Handle
F & F - I	fixed and fixed interlocked
P	plug-in

P - I	plug-in interlocked
P - I-MO	plug-in interlocked motoroperated
P - MO	plug-in motor-operated
P - RC	plug-in with residual current
P - RHD	plug-in with Direct Rotary Handle
W	withdrawable
W - I	withdrawable interlocked
W - I-MO	withdrawable interlocked motor-operated

W - MO	withdrawable motor-operated
W - RC	withdrawable with residual current
W - RHD	withdrawable with Direct Rotary Handle
W & W - I	withdrawable and withdrawable interlocked

Internal kits

Order codes - Internal kits



Kits for installation of Tmax circuit-breakers

Vertical installation (front or rear connections)

The kit includes the dedicated fixing brackets, the mounting plate and panels with 1/4 turn screws, hinged on the right or the left with the dedicated PHFP0020 kit.


Tmax	No. poles	Versions	Dimensions H (mm)	No. CB per compart.	Type	Order code	Pkg/ No. pcs
24 DIN modules - W=600mm							
XT4	3/4	P - MO	350	1	PVCX4409	1STQ007971A0000	1/1
XT4	3/4	P - RHD	350	1	PVCX4427	1STQ007973A0000	1/1
XT4	3/4	W	350	1	PVCX4410	1STQ007975A0000	1/1
XT4	3/4	W - MO	350	1	PVCX4412	1STQ007977A0000	1/1
XT4	3/4	W - RHD	350	1	PVCX4400	1STQ007979A0000	1/1
XT4	4	F - RC	400	1	PVCX4423	1STQ007959A0000	1/1
XT4	4	W - RC	400	1	PVCX4417	1STQ007981A0000	1/1
T4	3/4	F	350	1	PVCT4406	1STQ007983A0000	1/1
T4	3/4	F - MO	350	1	PVCT4404	1STQ007985A0000	1/1
T4	3/4	F - RHD	350	1	PVCT4406	1STQ007983A0000	1/1
T4	4	F - RC	450	1	PVCT4423	1STQ007987A0000	1/1
T5	3	P	200	1	PHCT5307 ■	1STQ001467B0000	1/1
T5	3	W	300	1	PHCT5310 ■	1STQ001469B0000	1/1
T5	3/4	F 400A/630A	350	1	PVCT5406	1STQ007989A0000	1/1
T5	3/4	F 400A/630A	350	2	PVCT5712	1STQ005221B0000	1/1
T5	3/4	F - MO 400A/630A	350	1	PVCT5404	1STQ007991A0000	1/1
T5	3/4	F - RHD 400A/630A	350	1	PVCT5406	1STQ007989A0000	1/1
T5	3/4	F 400/630A	350	2	PVCT5712	1STQ005221B0000	1/1
T5	3/4	P 400A	350	1	PVCT5426	1STQ008004A0000	1/1
T5	3/4	P - RHD 400A	350	1	PVCT5426	1STQ008004A0000	1/1
T5	3/4	W 400A	350	1	PVCT5414	1STQ007994A0000	1/1
T5	3/4	W - MO 400A	350	1	PVCT5412	1STQ007996A0000	1/1
T5	3/4	W - RHD 400A	350	1	PVCT5414	1STQ007994A0000	1/1
T5	4	F - RC 400A	450	1	PVCT5423	1STQ007999A0000	1/1
T5	4	P - RC 400A	450	1	PVCT5428	1STQ008002A0000	1/1
T5	3	P 630A	450	1	PVCT5307 ■	1STQ001468B0000	1/1
T5 NEW	3/4	P 630A	400	1	PVCT5407	1STQ002123B0000	1/1
T5 NEW	3/4	P - MO 630A	400	1	PVCT5409	1STQ002133B0000	1/1
T5 NEW	3/4	W - MO 630A	400	1	PVCT5430	1STQ002135B0000	1/1
T5	3	F 630A	450	3	PVCT5710 ■	1STQ001438B0000	1/1
T5	3	W 630A	450	2	PVCT5601 ■	1STQ001440B0000	1/1
T6	3/4	F	400	1	PVCT6401	1STQ008016A0000	1/1
T6	3/4	F - MO	400	1	PVCT6404	1STQ008019A0000	1/1
T6	3/4	F - RHD	400	1	PVCT6405	1STQ008022A0000	1/1
T6	3/4	W	450	1	PVCT6414 ■	1STQ008026A0000	1/1
T6	3/4	W - MO	450	1	PVCT6412 ■	1STQ008028A0000	1/1
T6	3/4	W - RHD	450	1	PVCT6414 ■	1STQ008026A0000	1/1
T7	3/4	F	450	1	PVCT7419	1STQ008034A0000	1/1
T7	3/4	F - I	450	1	PVCT7419	1STQ008034A0000	1/1
T7	3/4	F - I-MO	450	1	PVCT7419	1STQ008034A0000	1/1
T7	3/4	F - MO	450	1	PVCT7419	1STQ008034A0000	1/1
T7	3/4	W	500	1	PVCT7413 *	1STQ008035A0000	1/1

■ Front terminals, only Form 1

* Only rear terminals

Internal kits

Order codes - Internal kits



Tmax	No. poles	Versions	Dimensions H (mm)	No. CB per compart.	Type	Order code	Pkg/ No. pcs
24 DIN modules - W=600mm							
T7	3/4	W - I	500	1	PVCT7413 *	1STQ008035A0000	1/1
T7	3/4	W - I-MO	500	1	PVCT7413 *	1STQ008035A0000	1/1
T7	3/4	W - MO	500	1	PVCT7413 *	1STQ008035A0000	1/1
36 DIN modules - W=800mm							
XT1	3/4	P	300	4	PVDX1807	1STQ009147A0000	1/1
XT2	3/4	F	300	4	PVDX2801	1STQ007924A0000	1/1
XT2	3/4	P	300	4	PVDX2807	1STQ007930A0000	1/1
XT3	3	P	300	4	PVDX3807	1STQ009151A0000	1/1
XT3	3/4	P	300	3	PVDX3707	1STQ009150A0000	1/1
XT4	3/4	F	300	3	PVDX4701	1STQ009143A0000	1/1
XT4	3	F	300	4	PVDX4801	1STQ007963A0000	1/1
XT4	3	P	300	4	PVDX4807	1STQ007969A0000	1/1
XT4	3/4P	P	350	3	PVDX4707	1STQ009145A0000	1/1
T5	3/4	F 400A/630A	350	1	PVDT5406	1STQ008006A0000	1/1
T5	3/4	F 400/630A	350	1	PVDT5813	1STQ005222B0000	1/1
T5	3/4	F - MO 400A/630A	350	1	PVDT5404	1STQ008007A0000	1/1
T5	3/4	F - RHD 400A/630A	350	1	PVDT5406	1STQ008006A0000	1/1
T5	3/4	P 400A	350	1	PVDT5426	1STQ008005A0000	1/1
T5 NEW	3/4	P 630A	400	1	PVDT5407	1STQ002124B0000	1/1
T5 NEW	3/4	P - MO 630A	400	1	PVDT5409	1STQ002134B0000	1/1
T5	3/4	P - RHD 400A	350	1	PVDT5426	1STQ008005A0000	1/1
T5 NEW	3/4	F	350	2	PVDT5601	1STQ005067B0000	1/1
T5	3/4	W	350	2	PVDT5610	1STQ008480A0000	1/1
T5	3/4	W 400A	350	1	PVDT5414	1STQ008008A0000	1/1
T5	3/4	W - MO	350	2	PVDT5612	1STQ008481A0000	1/1
T5	3/4	W - MO 400A	350	1	PVDT5412	1STQ007997A0000	1/1
T5 NEW	3/4	W - MO 630A	400	1	PVDT5430	1STQ002136B0000	1/1
T5	3/4	W - RHD 400A	350	1	PVDT5414	1STQ008008A0000	1/1

* Only rear terminals

To assemble these kits, order the dedicated intermediate depth uprights PUKI1800 for H=1800mm or PUKI2000 for H=2000mm. Intermediate uprights are not required for assembling fixed Tmax XT1, XT2, XT3, XT4, T4, T5, T6 and XT1, XT3 with Direct Rotary Handle only in non-segregated structures. Order the dedicated fixed frame PFPPF.... or swing frame PFPS.... for assembling internal panels. For D=300mm structures, consult the details on page 3/21. For fixed and withdrawable 3P breakers Tmax XT, non accessorized and mounted on 3/4P kit, it is necessary to order the dedicated cover flanges: AD3305 flange for XT1 3P mounted on plate, AD3306 flange for XT2 3P mounted on plate, AD3307 flange for XT3 3P mounted on plate, AD3308 flange for XT4 3P mounted on plate. With interlocked or interlocked motor-operated kits, it is necessary to order the quantity of flanges equal to the quantity of breakers.

Compatible residual current devices:

Tmax XT

RC Inst XT1-XT3, RC Sel. XT1-XT3 and RC Sel.. XT2-XT4 Type A. For XT1-XT3 fixed with residual current device high terminal covers are not available.

Tmax T

RC222 for T4 and T5.

Key:	P - I	plug-in interlocked	W - MO	withdrawable motor-operated	
F	fixed	P - I-MO	plug-in interlocked motoroperated	W - RC	withdrawable with residual current
F - I	fixed interlocked	P - MO	plug-in motor-operated	W - RHD	withdrawable with Direct Rotary Handle
F - I-MO	fixed interlocked motor-operated	P - RC	plug-in with residual current	W & W - I	withdrawable and withdrawable interlocked
F - MO	fixed motor-operated	P - RHD	plug-in with Direct Rotary Handle		
F - RC	fixed with residual current	W	withdrawable		
F - RHD	fixed with Direct Rotary Handle	W - I	withdrawable interlocked		
F & F - I	fixed and fixed interlocked	W - I-MO	withdrawable interlocked		
P	plug-in		motor-operated		


• Quick selection guides page 2-8

• Technical details page 7-1

• Overall dimensions page 8-1

Internal kits

Order codes - Internal kits



Kits for installation of Tmax circuit-breakers

Vertical installation (front or rear connections)

The kit includes the dedicated fixing brackets, the mounting plate and panels with 1/4 turn screws, hinged on the right or the left with the dedicated PHFP0020 kit.

Tmax	No. poles	No. Versions	Dimensions H (mm)	No. CB per compart.	Type	Order code	Pkg/ No. pcs
36 DIN modules - W=800mm							
T5	4	F - RC 400A	450	1	PVDT5423	1STQ008000A0000	1/1
T5	4	P - RC 400A	450	1	PVDT5428	1STQ008003A0000	1/1
T5	3	F 630A	450	4	PVDT5810 ■	1STQ001439B0000	1/1
T5	3	W 630A	450	3	PVDT5701 ■	1STQ001441B0000	1/1
T6	3/4	F	400	1	PVDT6401	1STQ008017A0000	1/1
T6	3/4	F - MO	400	1	PVDT6404	1STQ008020A0000	1/1
T6	3/4	F - RHD	400	1	PVDT6405	1STQ008023A0000	1/1
T6	3/4	W	450	1	PVDT6414 ■	1STQ008027A0000	1/1
T6	3/4	W - MO	450	1	PVDT6412 ■	1STQ008029A0000	1/1
T6	3/4	W - RHD	450	1	PVDT6414 ■	1STQ008027A0000	1/1
T7	3/4	F	450	1	PVDT7419	1STQ008036A0000	1/1
T7	3/4	F - I	450	1	PVDT7419	1STQ008036A0000	1/1
T7	3/4	F - I-MO	450	1	PVDT7419	1STQ008036A0000	1/1
T7	3/4	F - MO	450	1	PVDT7419	1STQ008036A0000	1/1
T7	3/4	W	500	1	PVDT7413 *	1STQ008037A0000	1/1
T7	3/4	W - I	500	1	PVDT7413 *	1STQ008037A0000	1/1
T7	3/4	W - I-MO	500	1	PVDT7413 *	1STQ008037A0000	1/1
T7	3/4	W - MO	500	1	PVDT7413 *	1STQ008037A0000	1/1

Tmax	No. poles	No. Versions	Dimensions H (mm)	No. CB per compart.	Type	Order code	Pkg/ No. pcs
48 DIN modules - W=1000mm							
T5	3	W	350	4	PVFT5810	1STQ008013A0000	1/1
T5	3	W - MO	350	4	PVFT5812	1STQ008014A0000	1/1
T5	3/4	W	350	3	PVFT5710	1STQ008482A0000	1/1
T5	3/4	W - MO	350	3	PVFT5712	1STQ008483A0000	1/1
T6	3/4	W	450	2	PVFT6610 n	1STQ008478A0000	1/1
T6	3/4	W - RHD	450	2	PVFT6610	1STQ008478A0000	1/1
T6	3/4	W - MO	450	2	PVFT6612 n	1STQ008479A0000	1/1
T7	3/4	W	500	2	PVFT7633 *	1STQ008477A0000	1/1
T7	3/4	W - MO	500	2	PVFT7633 *	1STQ008477A0000	1/1

■ Front terminals, only Form 1

* Only rear terminals

To assemble these kits, order the dedicated intermediate depth uprights PUKI1800 for H= 1800mm or PUKI2000 for H=2000mm. Intermediate uprights are not required for assembling fixed Tmax XT1, XT2, XT3, XT4, T4, T5, T6 and XT1, XT3 with Direct Rotary Handle only in non-segregated structures. Order the dedicated fixed frame PF... or swing frame PFPS... for assembling internal panels. For D=300mm structures, consult the details on page 3/21. For fixed and withdrawable 3P breakers Tmax XT, non accessorized and mounted on 3/4P kit, it is necessary to order the dedicated cover flanges: AD3305 flange for XT1 3P mounted on plate, AD3306 flange for XT2 3P mounted on plate, AD3307 flange for XT3 3P mounted on plate, AD3308 flange for XT4 3P mounted on plate. With interlocked or interlocked motor-operated kits, it is necessary to order the quantity of flanges equal to the quantity of breakers.

Compatible residual current devices:

Tmax XT


RC Inst XT1-XT3, RC Sel. XT1-XT3 and RC Sel.. XT2-XT4 Type A. For XT1-XT3 fixed with residual current device high terminal covers are not available.

Tmax T

RC222 for T4 and T5.

Internal kits

Order codes - Internal kits



Kit for installing Emax 2 breakers

Vertical installation (front or rear connections)

The kit includes the dedicated fixing brackets, the mounting plate and panels with 1/4 turn screws, hinged on the right or the left with the dedicated PHFP0020 kit.

Front or rear connections

Tmax	No. poles	Versions	Dimensions H (mm)	No. CB per compart.	Type	Order code	Pkg/ No. pcs
12 DIN modules - W=400mm							
E1.2	3/4	F	450	1	PVBE1241	1STQ008179A0000	1/1
E1.2	3/4	F - I	450	1	PVBE1241	1STQ008179A0000	1/1
24 DIN modules - W=600mm							
E1.2	3/4	F	450	1	PVCE1241	1STQ008184A0000	1/1
E1.2	3/4	F - I	450	1	PVCE1241	1STQ008184A0000	1/1
E1.2	3/4	W	500	1	PVCE1240	1STQ008185A0000	1/1
E1.2	3/4	W - I	500	1	PVCE1240	1STQ008185A0000	1/1
36 DIN modules - W=800mm							
E1.2	3/4	F	450	1	PVDE1241	1STQ008188A0000	1/1
E1.2	3/4	F - I	450	1	PVDE1241	1STQ008188A0000	1/1
E1.2	3/4	F	450	2	PVDE1262	1STQ008485A0000	1/1
E1.2	3/4	W	500	1	PVDE1240	1STQ008189A0000	1/1
E1.2	3/4	W - I	500	1	PVDE1240	1STQ008189A0000	1/1
48 DIN modules - W=1000mm							
E1.2	3/4	W	500	2	PVFE1263	1STQ008486A0000	1/1


To assemble these kits, order the dedicated intermediate depth uprights PUKI1800 for H=1800mm or PUKI2000 for H=2000mm.
Order the dedicated fixed frame PFPF.... or swing frame PFPS.... for assembling internal panels.

Key:

F	fixed
F - I	fixed interlocked
W	withdrawable
W - I	withdrawable interlocked
HS	50% neutral
FS	100% neutral

Internal kits

Order codes - Internal kits



Kit for installing Emax 2 circuit-breakers

Vertical installation (front or rear connections)

The kit includes the dedicated fixing brackets, the mounting plate and panels with 1/4 turn screws, hinged on the right or the left with the dedicated PHFP0020 kit.

Only rear connections

Tmax	No. poles	Versions	Dimensions H (mm)	No. CB per compart.	Type	Order code	Pkg/ No. pcs
24 DIN modules - W=600mm							
E2.2	3/4	F	600	1	PVCE2441	1STQ008186A0000	1/1
E2.2	3/4	F - I	600	1	PVCE2441	1STQ008186A0000	1/1
E2.2	3/4	W	600	1	PVCE2450	1STQ008187A0000	1/1
E2.2	3/4	W - I	600	1	PVCE2450	1STQ008187A0000	1/1
E4.2	3	W	600	1	PVCE4350	1STQ009991A0000	1/1
E4.2	3	W - I	600	1	PVCE4350	1STQ009991A0000	1/1
E4.2	3/4	F	600	1	PVCE2442	1STQ008484A0000	1/1
36 DIN modules - W=800mm							
E2.2	3/4	F	600	1	PVDE2441	1STQ008190A0000	1/1
E2.2	3/4	F - I	600	1	PVDE2441	1STQ008190A0000	1/1
E2.2	3/4	W	600	1	PVDE2440	1STQ008191A0000	1/1
E2.2	3/4	W - I	600	1	PVDE2440	1STQ008191A0000	1/1
E4.2	3/4	F	600	1	PVDE2441	1STQ008190A0000	1/1
E4.2	3/4	F - I	600	1	PVDE2441	1STQ008190A0000	1/1
E4.2	3/4	W	600	1	PVDE2440	1STQ008191A0000	1/1
E4.2	3/4	W - I	600	1	PVDE2440	1STQ008191A0000	1/1
48 DIN modules - W=1000mm							
E6.2	3/4 HS	F	700	1	PVFE6231	1STQ008192A0000	1/1
E6.2	3	F - I	700	1	PVFE6231	1STQ008192A0000	1/1
E6.2	3	W	700	1	PVFE6230	1STQ008193A0000	1/1
E6.2	3	W - I	700	1	PVFE6230	1STQ008193A0000	1/1
62 DIN modules - W=1250mm							
E2.2	3/4	W	600	1	PVGE2440	1STQ004225B0000	1/1
E6.2	4 HS/FS	F	700	1	PVGE6231	1STQ008194A0000	1/1
E6.2	4 HS/FS	F - I	700	1	PVGE6231	1STQ008194A0000	1/1
E6.2	4 HS/FS	W	700	1	PVGE6230	1STQ008195A0000	1/1
E6.2	4 HS/FS	W - I	700	1	PVGE6230	1STQ008195A0000	1/1


To assemble these kits, order the dedicated intermediate depth uprights PUKI1800 for H= 1800mm or PUKI2000 for H=2000mm.
Order the dedicated fixed frame PFPF.... or swing frame PFPS.... for assembling internal panels.

Key:

- F fixed
- F - I fixed interlocked
- W withdrawable
- W - I withdrawable interlocked
- HS 50% neutral
- FS 100% neutral

Internal kits


Order codes - Internal kits



NEW Anchoring plates for Emax breakers

Description	Type	Order code	Pkg/ No. pcs
Anchoring plate T7 - E1.2 vertical installation 70 mm	PBBE0712	1STQ005077B0000	1/1
Anchoring plate E2.2 - E 4.2 vertical installation 90-126 mm	PBBE2242	1STQ005078B0000	1/1
Anchoring plate E6.2 vertical installation 252 mm	PBBE0062	1STQ005079B0000	1/1

* For screws and anchoring plates selection, see technical section page....




Kits for OT

Kit for OT switch-disconnectors available up to 1600A both in horizontal and vertical version. The kit includes the dedicated fixing brackets, the mounting plate and panels with 1/4 turn screws, hinged on the right or the left with the dedicated PHFP0020 kit. For structure with intermediate upright.

Description	Dimensions		(A) Max lever (mm)	(B) Min. shaft (mm)	Lenght	Lever position	Type	Order code	Pkg/ No. pcs
	H (mm)	L							
Vertical installation kit 3/4 poles									
OT 160, 200, 250	350	600	80	130 (6)	E03-E04	PKOV1660	1STQ007437A0000		1/1
OT 160, 200, 250	350	800	80	130 (6)	E03-E04	PKOV1680	1STQ007440A0000		1/1
OT 315, 400	450	600	175	95 (12)	E03-E04	PKOV3160	1STQ008399A0000		1/1
OT 315, 400	450	800	175	95 (12)	E03-E04	PKOV3180	1STQ008400A0000		1/1
OT 630, 800	500	600	175	70 (12)	E03-E04	PKOV6360	1STQ007438A0000		1/1
OT 630, 800	500	800	175	70 (12)	E03-E04	PKOV6380	1STQ007441A0000		1/1
OT 1000, 1250, 1600	600	600	175	170 (12)	E12-E22	PKOV1060	1STQ007439A0000		1/1
OT 1000, 1250, 1600	600	800	175	170 (12)	E12-E22	PKOV1080	1STQ007442A0000		1/1
Horizontal installation kit 3/4 poles									
OT 160, 200, 250	250	600	80	130 (6)	E03-E04	PKOH1660	1STQ007443A0000		1/1
OT 160, 200, 250	250	800	80	130 (6)	E03-E04	PKOH1680	1STQ007446A0000		1/1
OT 315, 400	300	600	175	95 (12)	E03-E04	PKOH3160	1STQ008401A0000		1/1
OT 315, 400	300	800	175	95 (12)	E03-E04	PKOH3180	1STQ008402A0000		1/1
OT 630, 800	500	600	175	70 (12)	E03-E04	PKOH6360	1STQ007444A0000		1/1
OT 630, 800	500	800	175	70 (12)	E03-E04	PKOH6380	1STQ007447A0000		1/1
OT 1000, 1250, 1600	600	600	175	170 (12)	E12-E22 ⁽¹⁾	PKOH1060	1STQ007445A0000		1/1
OT 1000, 1250, 1600	600	800	175	170 (12)	E12-E22	PKOH1080	1STQ007448A0000		1/1


⁽¹⁾ Only low terminal covers.

Order the dedicated fixed frame PFPF.... or swing frame PFPS.... for assembling internal panels.



Internal kits

Order codes - Internal kits




NEW Kits for Easy Line XLP

Kit for Easy Line Fuse Switch Disconnector XLP up to 630A 3P vertical mounting.

The kit includes the dedicated fixing brackets, the mounting plate and panels with 1/4 turn screws.

For each device type and quantity per kit order the frontframe cover as table below.

Description	Dimensions (mm)			Type	Order code	Pkg/ No. pcs
	H	W	N. XLP per KIT			
Kit for XLP00 up to 2 devices	300	400	up to 2	PXLP0040	1STQ005299B0000	1/1
Kit for XLP00 up to 3 devices	300	600	up to 3	PXLP0060	1STQ005300B0000	1/1
Kit for XLP01 for 1 device	400	400	1	PXLP0140	1STQ005301B0000	1/1
Kit for XLP01 up to 2 devices	400	600	up to 2	PXLP0160	1STQ005302B0000	1/1
Kit for XLP02 for 1 device	450	400	1	PXLP0240	1STQ005303B0000	1/1
Kit for XLP02 up to 2 devices	450	600	up to 2	PXLP0260	1STQ005304B0000	1/1
Kit for XLP03 for 1 device	550	400	1	PXLP0340	1STQ005305B0000	1/1
Kit for XLP03 for 1 device	550	600	1	PXLP0360	1STQ005306B0000	1/1




NEW Frontframe for XLP

For each device type and quantity per kit order the frontframe cover as table below.

Description	Dimensions (mm)			Kit XLP Order code	No. XLP per KIT	Order code	Pkg/ No. pcs
	H	W	Kit XLP Order code				
XLP00 Frontframe for 1 XLP00	300	400	1STQ005299B0000	1	1SEP407792R0001	1	1/1
				2	1SEP407792R0002	1	1/1
XLP00 Frontframe for 1 XLP00	300	600	1STQ005300B0000	1	1SEP407792R0001	1	1/1
				2	1SEP407792R0002	1	1/1
XLP00 Frontframe for 3 XLP00				3	1SEP407792R0003	1	1/1
XLP1 Frontframe for 1 XLP1	400	400	1STQ005301B0000	1	1SEP407815R0001	1	1/1
XLP1 Frontframe for 1 XLP1	400	600	1STQ005302B0000	1	1SEP407815R0001	1	1/1
XLP1 Frontframe for 2 XLP1				2	1SEP407815R0002	1	1/1
XLP2 Frontframe for 1 XLP2	450	400	1STQ005303B0000	1	1SEP407951R0001	1	1/1
XLP2 Frontframe for 1 XLP2	450	600	1STQ005304B0000	1	1SEP407951R0001	1	1/1
XLP2 Frontframe for 2 XLP2				2	1SEP407951R0002	1	1/1
XLP3 Frontframe for 1 XLP3	550	400	1STQ005305B0000	1	1SEP407955R0001	1	1/1
XLP3 Frontframe for 1 XLP3	550	600	1STQ005306B0000	1	1SEP407955R0001	1	1/1

Internal kits

Order codes - Internal kits




Blind mounting plates


The kit includes the dedicated fixing brackets and the mounting plate.

Description	Dimensions (mm)			Pkg/ No. pcs
	H	W	Type	
Blind assembly plate	150	400	PPMB1540	1STQ007521A0000
Blind assembly plate	200	400	PPMB2040	1STQ007522A0000
Blind assembly plate	250	400	PPMB2540	1STQ007523A0000
Blind assembly plate	300	400	PPMB3040	1STQ007524A0000
Blind assembly plate	350	400	PPMB3540	1STQ002009B0000
Blind assembly plate	400	400	PPMB4040	1STQ007525A0000
Blind assembly plate	450	400	PPMB4540	1STQ002010B0000
Blind assembly plate	500	400	PPMB5004	1STQ007526A0000
Blind assembly plate	600	400	PPMB6040	1STQ007527A0000
Blind assembly plate	150	600	PPMB1560	1STQ007533A0000
Blind assembly plate	200	600	PPMB2060	1STQ007534A0000
Blind assembly plate	250	600	PPMB2560	1STQ007535A0000
Blind assembly plate	300	600	PPMB3060	1STQ007536A0000
Blind assembly plate	350	600	PPMB3560	1STQ002011B0000
Blind assembly plate	400	600	PPMB4060	1STQ007537A0000
Blind assembly plate	450	600	PPMB4560	1STQ002012B0000
Blind assembly plate	500	600	PPMB5006	1STQ007538A0000
Blind assembly plate	600	600	PPMB6060	1STQ007539A0000
Blind assembly plate	150	800	PPMB1580	1STQ007545A0000
Blind assembly plate	200	800	PPMB2080	1STQ007546A0000
Blind assembly plate	250	800	PPMB2580	1STQ007547A0000
Blind assembly plate	300	800	PPMB3080	1STQ007548A0000
Blind assembly plate	350	800	PPMB3580	1STQ002013B0000
Blind assembly plate	400	800	PPMB4080	1STQ007549A0000
Blind assembly plate	450	800	PPMB4580	1STQ002014B0000
Blind assembly plate	500	800	PPMB5008	1STQ007550A0000
Blind assembly plate	600	800	PPMB6080	1STQ007551A0000
Blind assembly plate	150	1000	PPMB1510	1STQ001587B0000
Blind assembly plate	200	1000	PPMB2010	1STQ007556A0000
Blind assembly plate	300	1000	PPMB3010	1STQ007557A0000
Blind assembly plate	400	1000	PPMB4010	1STQ007558A0000
Blind assembly plate	500	1000	PPMB5001	1STQ007559A0000
Blind assembly plate	600	1000	PPMB6010	1STQ007560A0000
Blind assembly plate	200	1250	PPMB2012	1STQ007565A0000
Blind assembly plate	250	1250	PPMB2512	1STQ009156A0000
Blind assembly plate	300	1250	PPMB3012	1STQ007566A0000
Blind assembly plate	350	1250	PPMB3512	1STQ009157A0000

PPMB1540 - PPMB1580




PPMB2040....PPMB6010




Internal kits

Order codes - Internal kits



Blind mounting plates total height


Description	Dimensions (mm)			Type	Order code	Pkg/ No. pcs
	H	W	D			
Blind mounting plate	1600	400	1600	PWRP1640	1STQ001965B0000	1/1
Blind assembly plate	1600	600	1600	PWRP1660	1STQ001966B0000	1/1
Blind assembly plate	1600	800	1600	PWRP1680	1STQ001967B0000	1/1
Blind assembly plate	1800	400	1800	PWRP1840	1STQ001899B0000	1/1
Blind assembly plate	1800	600	1800	PWRP1860	1STQ001900B0000	1/1
Blind assembly plate	1800	800	1800	PWRP1880	1STQ001901B0000	1/1
Blind assembly plate	2000	400	2000	PWRP2040	1STQ001902B0000	1/1
Blind assembly plate	2000	600	2000	PWRP2060	1STQ001903B0000	1/1
Blind assembly plate	2000	800	2000	PWRP2080	1STQ001904B0000	1/1
Tracks for front insertion						
Pair of tracks for total height mounting plate	300	PDRP0300	1STQ002335B0000			1/1
Pair of tracks for total height mounting plate	500	PDRP0500	1STQ002336B0000			1/1
Pair of tracks for total height mounting plate	700	PDRP0700	1STQ002337B0000			1/1
Pair of tracks for total height mounting plate	900	PDRP0900	1STQ002338B0000			1/1



Crosspieces for mounting blind total height plate

Description	Dimensions (mm)			Type	Order code	Pkg/ No. pcs
	D					
No.2 crosspieces	200	PCCM0200	1STQ007744A0000			1/2
No.2 crosspieces	300	PCCM0300	1STQ007745A0000			1/2
No.2 crosspieces	500	PCCM0500	1STQ007746A0000			1/2
No.2 crosspieces	700	PCCM0700	1STQ007747A0000			1/2
No.2 crosspieces	900	PCCM0900	1STQ007748A0000			1/2

If the enclosure is higher than total height mounting plate, order no. 1 PCCM.... to mount the total height blind plate.



NEW Motor Control Center Fixed plate


The System Pro E Power MCC fixed plate allows the installation of command and control devices for the operation of motors in a reliable, secure and efficient manner. Typical devices are: Magnetic only circuit-breakers, Contactors, External thermal relays, switch-disconnectors, thermal-magnetic circuit breakers, soft starters. Each code comprehends one plate in galvanized sheet metal, two supports per side and the fixing elements. The end user will be able to install the devices on the plate before assembling it in the enclosure.

Description	Plate Width (mm)	Plate Height (mm)	Dimensions (mm)		Type	Order code	Pkg/ No. pcs
			W	H			
Asolated plate MCC	600	200	600	200	PMCC2060	1STQ005521B0000	
Asolated plate MCC	600	300	600	300	PMCC3060	1STQ005522B0000	
Asolated plate MCC	600	400	600	400	PMCC4060	1STQ005523B0000	
Asolated plate MCC	600	600	600	600	PMCC6060	1STQ005524B0000	
Asolated plate MCC	600	800	600	800	PMCC8060	1STQ005525B0000	

For devices selection, please go to the following ABB link: <https://applications.it.abb.com/SOC/Page/Selection.aspx>

Internal kits

Order codes - Internal kits



Flat blind panels

Panels with 1/4 turn screws, hinged on the right or left with the dedicated PHFP0020 kit.


Description	Dimensions (mm)			Pkg/ No. pcs
	H	W	Type	
Flat blind panel	50	400	PPFB5040	1STQ007465A0000
Flat blind panel	100	400	PPFB1040	1STQ007466A0000
Flat blind panel	150	400	PPFB1540	1STQ007467A0000
Flat blind panel	200	400	PPFB2040	1STQ007468A0000
Flat blind panel	250	400	PPFB2540	1STQ007469A0000
Flat blind panel	300	400	PPFB3040	1STQ007470A0000
Flat blind panel	350	400	PPFB3540	1STQ002015B0000
Flat blind panel	400	400	PPFB4040	1STQ007471A0000
Flat blind panel	450	400	PPFB4540	1STQ002016B0000
Flat blind panel	500	400	PPFB5004	1STQ007472A0000
Flat blind panel	600	400	PPFB6040	1STQ007473A0000
Flat blind panel	800	400	PPFB8040	1STQ007474A0000
Flat blind panel	1800	400	PPFB1840*	1STQ007475A0000
Flat blind panel	2000	400	PPFB2004*	1STQ007476A0000
Flat blind panel	50	600	PPFB5060	1STQ007477A0000
Flat blind panel	100	600	PPFB1060	1STQ007478A0000
Flat blind panel	150	600	PPFB1560	1STQ007479A0000
Flat blind panel	200	600	PPFB2060	1STQ007480A0000
Flat blind panel	250	600	PPFB2560	1STQ007481A0000
Flat blind panel	300	600	PPFB3060	1STQ007482A0000
Flat blind panel	350	600	PPFB3560	1STQ002017B0000
Flat blind panel	400	600	PPFB4060	1STQ007483A0000
Flat blind panel	450	600	PPFB4560	1STQ002018B0000
Flat blind panel	500	600	PPFB5006	1STQ007484A0000
Flat blind panel	600	600	PPFB6060	1STQ007485A0000
Flat blind panel	800	600	PPFB8060	1STQ007486A0000
Flat blind panel	1800	600	PPFB1860*	1STQ007487A0000
Flat blind panel	2000	600	PPFB2006*	1STQ007488A0000
Flat blind panel	50	800	PPFB5080	1STQ007489A0000
Flat blind panel	100	800	PPFB1080	1STQ007490A0000
Flat blind panel	150	800	PPFB1580	1STQ007491A0000
Flat blind panel	200	800	PPFB2080	1STQ007492A0000
Flat blind panel	250	800	PPFB2580	1STQ007493A0000
Flat blind panel	300	800	PPFB3080	1STQ007494A0000
Flat blind panel	350	800	PPFB3580	1STQ002019B0000
Flat blind panel	400	800	PPFB4080	1STQ007495A0000
Flat blind panel	450	800	PPFB4580	1STQ002020B0000
Flat blind panel	500	800	PPFB5008	1STQ007496A0000
Flat blind panel	600	800	PPFB6080	1STQ007497A0000
Flat blind panel	800	800	PPFB8080	1STQ007498A0000
Flat blind panel	1800	800	PPFB1880*	1STQ007499A0000
Flat blind panel	2000	800	PPFB2008*	1STQ007500A0000
Flat blind panel	100	1000	PPFB1010	1STQ007501A0000
Flat blind panel	150	1000	PPFB1510	1STQ001479B0000
Flat blind panel	200	1000	PPFB2010	1STQ007502A0000
Flat blind panel	300	1000	PPFB3010	1STQ007503A0000
Flat blind panel	400	1000	PPFB4010	1STQ007504A0000
Flat blind panel	500	1000	PPFB5001	1STQ007505A0000
Flat blind panel	600	1000	PPFB6010	1STQ007506A0000
Flat blind panel	800	1000	PPFB8010	1STQ007507A0000
Flat blind panel	100	1250	PPFB1013	1STQ004229B0000
Flat blind panel	200	1250	PPFB2012	1STQ007511A0000
Flat blind panel	250	1250	PPFB2512	1STQ009154A0000
Flat blind panel	300	1250	PPFB3012	1STQ007512A0000
Flat blind panel	350	1250	PPFB3512	1STQ009155A0000

Order the dedicated fixed frame PPFP.... or swing frame PFPS.... for assembling internal panels.

* Only for swing frame PFPS.... Not compatible with the hinges accessory PHFP0020.

Internal kits

Order codes - Internal kits



Panels for square measuring instruments

Panels with 1/4 turn screws, hinged on the right or left with the dedicated PHFP0020 kit.

Description	Dimensions (mm)				Pkg/ No. pcs
	H	W	Type	Order code	
Panel 2 instruments 72x72	200	600	PPFI2726	1STQ008092A0000	1/1
Panel 2 instruments 72x72	200	800	PPFI2728	1STQ008093A0000	1/1
Panel 2 instruments 96x96	200	600	PPFI2966	1STQ008094A0000	1/1
Panel 2 instruments 96x96	200	800	PPFI2968	1STQ008095A0000	1/1
Panel 4 instruments 72x72	200	600	PPFI4726	1STQ008096A0000	1/1
Panel 4 instruments 72x72	200	800	PPFI4728	1STQ008097A0000	1/1
Panel 4 instruments 96x96	200	800	PPFI4968	1STQ008098A0000	1/1

Recessed blind panels

Description	Dimensions (mm)				Pkg/ No. pcs
	H	W	D	Type	
Recessed blind panel	200	400	30	PPBR2040	1STQ007723A0000
Recessed blind panel	400	400	30	PPBR4040	1STQ007724A0000
Recessed blind panel	600	400	30	PPBR6040	1STQ007725A0000
Recessed blind panel	200	600	30	PPBR2060	1STQ007726A0000
Recessed blind panel	200	600	80	PPBR2068	1STQ001399B0000
Recessed blind panel	400	600	30	PPBR4060	1STQ007727A0000
Recessed blind panel	600	600	30	PPBR6060	1STQ007728A0000
Recessed blind panel	200	800	80	PPBR2080	1STQ007729A0000
Recessed blind panel	200	800	30	PPBR2088	1STQ001400B0000
Recessed blind panel	400	800	30	PPBR4080	1STQ007730A0000
Recessed blind panel	600	800	30	PPBR6080	1STQ007731A0000


Ventilated panels

Description	Dimensions (mm)				Pkg/ No. pcs
	H	W	Type	Order code	
Ventilated panel	100	400	PPFA1040	1STQ007732A0000	1/1
Ventilated panel	200	400	PPFA2040	1STQ007733A0000	1/1
Ventilated panel	100	600	PPFA1060	1STQ007734A0000	1/1
Ventilated panel	200	600	PPFA2060	1STQ007735A0000	1/1
Ventilated panel	100	800	PPFA1080	1STQ007736A0000	1/1
Ventilated panel	200	800	PPFA2080	1STQ007737A0000	1/1
Ventilated panel	100	1000	PPFA1010	1STQ007738A0000	1/1
Ventilated panel	200	1000	PPFA2010	1STQ007739A0000	1/1

Order the dedicated fixed frame PFPF.... or swing frame PFPS.... for assembling internal panels.

Internal kits


Order codes - Internal kits



“Space-saving” column W=400mm

The “space-saving” column is composed of one reduced fixed frame (H=1800mm or H=2000mm) for W=400mm columns with two fixed positions for the kit exclusively dedicated to: E1.2 3/4P W; E2.2 3P F; E2.2 3P W. In order to complete this solution: blind panel H=100, 200, 300 and 600mm; modular or instrument panels H=200mm. In this column type, it is not possible to mount kits for air-circuit breakers, moulded-case circuit breakers or modular breakers. The only possible configurations are the following ones.

Description	Dimensions (mm)			Type	Order code	Pkg/ No. pcs
	H	W	D			
Frame						
Reduced fixed frame	1800	400		PRFR1840	1STQ009283A0000	1/1
Reduced fixed frame	2000	400		PRFR2040	1STQ009284A0000	1/1
Kit for reduced frame						
E1.2 3/4 P W vertical	600	400		PRBE1243	1STQ009285A0000	1/1
E2.2 3 P F vertical	600	400		PRBE2232	1STQ009286A0000	1/1
E2.2 3 P W vertical	600	400		PRBE2233	1STQ009287A0000	1/1
Recessed blind mounting plate	600	400		PBRR6040	1STQ001565B0000	1/1
Panel for reduced frame						
Blind panel	100	400		PBRP1040	1STQ009288A0000	1/1
Blind panel	200	400		PBRP2040	1STQ009289A0000	1/1
Blind panel	300	400		PBRP3040	1STQ009290A0000	1/1
Blind panel	600	400		PBRP6040	1STQ009291A0000	1/1
Blind recessed panel	600	400		PPRR6040	1STQ001566B0000	1/1
Modular panel	200	400		PMRP2040	1STQ009292A0000	1/1
Standard DIN Rail		400		PDRS0400	1STQ008041A0000	1/1
Panel 2 instruments 72x72	200	400		PIRP2040	1STQ009293A0000	1/1
Segregation Form 2a-3a						
E1.2 W	600	400		PSVW6041	1STQ001568B0000	1/1
E2.2 F	600	400		PSVF6042	1STQ001569B0000	1/1
E2.2 W	600	400		PSVW6042	1STQ001570B0000	1/1
Segregation Form 3b						
E1.2 W	400	500		PSHW4051	1STQ001571B0000	1/1
E1.2 W	400	700		PSHW4071	1STQ001572B0000	1/1
E1.2 W	400	900		PSHW4091	1STQ001573B0000	1/1
E2.2 F	400	700		PSHF4072	1STQ001574B0000	1/1
E2.2 F	400	900		PSHF4092	1STQ001575B0000	1/1
E2.2 W	400	700		PSHW4072	1STQ001576B0000	1/1
E2.2 W	400	900		PSHW4092	1STQ001577B0000	1/1




• Quick selection guides page 2-8

• Technical details page 7-1

• Overall dimensions page 8-1

Internal kits

Accessories and spare parts




DIN rail accessories

With fixed frame for panels, maximum wiring ducts dimension is 60x60mm.

Description	Type	Order code	Pkg/ No. pcs
Supports for horizontal wiring ducts			
No.4 plastic supports for horizontal wiring ducts	AD1009*	1STQ008200A0000	1/4
No.4 plastic supports for horizontal wiring ducts	AD1037*	1STQ008201A0000	1/4
No.4 metal supports reduced wiring ducts	PSRM1515**	1STQ009164A0000	1/4
Depth adapter			
Depth adapter for Tmax T1-T2-T3-XT1-XT3 W=600mm	AP6000	1STQ008202A0000	1/1


* To be used in case of not segregated DIN rail with panels H≥200mm.

** To be used in case of DIN rail with panels H=300mm (2 DIN rail) or always in case of segregated DIN rail.



Universal cable holder brackets

Description	Type	Order code	Pkg/ No. pcs
No.5 cable holder D=28,5mm	EV0036	1STQ006605A0000	1/5
No.5 cable holder D=55mm	EV0037	1STQ006627A0000	1/5




Angled supports for terminal boxes and earthing busbars

Description	Type	Order code	Pkg/ No. pcs
No.50 angled supports 1 row of terminals	EV1110	1STQ001007A0000	1/50
No.10 angled supports 1 row of terminals	EV2110	1STQ003202A0000	1/10
No.10 angled supports double row of terminals	EV1111	1STQ001008A0000	1/10
No.50 angled supports 1 row of terminals + earth	EV1112	1STQ001009A0000	1/50
No.10 angled supports 1 row of terminals + earth	EV2112	1STQ003203A0000	1/10

Internal kits


Accessories and spare parts



Din rail and support for cable duct


With fixed frame for panels, maximum wiring ducts dimension is 60x60mm.

Description	Type	Order code	Pkg/ No. pcs
No.4 horizontal/vertical support for cable duct	EV0042	1STQ006589A0000	1/4
No. 4 plastic supports for horizontal wiring ducts	AD1009	1STQ008200A0000	1/4



Holes covering strip RAL7035 colour

Description	Type	Order code	Pkg/ No. pcs
No. 10 hole covers W=2000mm, grey	AD1086	1STQ009173A0000	1/10




Panel Accessories

Description	Type	Order code	Pkg/ No. pcs
No. 20 label holders 24 DIN mod	AD1600	1STQ008205A0000	1/20
No. 20 label holders 36 DIN mod	AD1800	1STQ008206A0000	1/20
No.10 hole covers W=2000mm, grey	AD1086	1STQ009173A0000	1/10
No. 288 labels 1 DIN mod. 15x17mm (HxW)	AD1101*	1STQ008207A0000	1/288
No. 192 labels 2 DIN mod. 15x27mm (HxW)	AD1102*	1STQ008208A0000	1/192
No. 96 labels 3 DIN mod. 15x50mm (HxW)	AD1103*	1STQ008209A0000	1/96
No. 96 labels 4 DIN mod. 15x67mm (HxW)	AD1104*	1STQ008210A0000	1/96

* labels can be written using compatible Grafoplast system.


Internal kits

Accessories and spare parts



Closing plug for instrument holder panels

Description	Type	Order code	Pkg/ No. pcs
No.10 closing plug for instrument holder panels 72x72mm	EV1135	1STQ001023A0000	1/10
No.5 closing plug for instrument holder panels 96x96mm	EV1136	1STQ001024A0000	1/5
No.50 closing plugs for pushbuttons Ø22mm	EV1137	1STQ001025A0000	1/50




Hinges for panels

Hinges kit for panels (blind, instruments, recessed and vented panels). Not suitable for blind panels H=1800/2000mm.


Description	Type	Order code	Pkg/ No. pcs
No. 20 hinges for frontal panels	PHFP0020	1STQ008111A0000	1/20

For the mounting of the internal panels order the fixed PFPF.... or swing PFPS.... dedicated frame



Spare parts Tmax XT cover plate for DIN rail

Description	Type	Order code	Pkg/ No. pcs
Cover plate for Tmax XT1 3P mounted on DIN rail	AD3301	1STQ008301A0000	1/1
Cover plate for Tmax XT1 4P mounted on DIN rail	AD3302	1STQ008302A0000	1/1
Cover plate for Tmax XT3 3P mounted on DIN rail	AD3303	1STQ008303A0000	1/1
Cover plate for Tmax XT3 4P mounted on DIN rail	AD3304	1STQ008304A0000	1/1
Cover for panel XT1 3P mounted on plate	AD3305	1STQ009216A0000	1/1
Cover for panel XT2 3P mounted on plate	AD3306	1STQ009217A0000	1/1
Cover for panel XT3 3P mounted on plate	AD3307	1STQ009218A0000	1/1
Cover for panel XT4 3P mounted on plate	AD3308	1STQ009219A0000	1/1



Chapter 4

Main distribution systems

4-2 General information

4-8 Example of use

4-12 Selection guides

4-28 Guide to the order codes

4-28 Codes for ordering

4-29 Order codes

Main distribution systems

General information

The distribution systems that can be used inside System pro E power switchboards meet the requirements of all applications, with 250A to 6300A configurations.

—
01 The crosspieces that fix to the structure are for universal use for both linear and scaled busbar holders.

—
02 The linear and scaled insulating supports house 5mm flat busbar systems on one side, while the other side houses shaped profile or 10mm section flat busbar systems.

—
03 One single tie rod in different lengths is used to fasten all types of busbars.

The new System pro E power distribution system has been designed for improved flexibility and simple busbar connections.

Linear and scaled solutions are available and allow the busbars to be installed in any position: horizontally, under the top, on the bottom and at each height; vertically, along the side or at the rear and in the cable compartment. The structural components include:

- insulating support and tie rods
- crosspieces and brackets

The main advantages are:

- same construction philosophy for 250A to 6300A applications



- same multifunction insulating supports able to house flat 5 and 10mm thick and shaped busbars ("click in" installation method for the linear version)
- the center distance between phases can be increased for the linear version by simply sliding the insulation support fastenings along the crosspieces
- same fixing crosspieces for both linear and scaled solutions
- stainless steel crosspieces for applications with $I_n \geq 4000A$ to limit the effect of stray currents


The capacity of the busbars is as follows:

- flat copper busbars up to 6300A
- shaped profile busbars up to 2500A

Air and moulded-case circuit-breakers can be connected to the busbars by means of prefabricated rigid or flexible connections.

Number of busbars installable per insulator

	Linear System	Scaled System
Flat busbars	1,2,3 or 4 bars per phase	50mm block 2000A 75mm block 3200A 100mm block 6300A
Shaped busbars	1 per phase	1,2,3 or 4 bars per phase 50mm block 1600A 75mm block 2000A 100mm block 2500A






The linear busbar holder is formed by inserting, with a “click”, the insulating supports onto the crosspieces, which are fixed directly inside the switchboard by means of simple brackets.

LINEAR SYSTEM

The new busbar holder consists of:

- a polyamide insulating support (maximum operating temperature 130 °C) featuring shaped grooves for the busbars and pins for fixing to the crosspieces, able to house both flat and shaped profile busbars;
- crosspieces available in different lengths, made of hot-dip galvanized steel sheet for In <4000A current values or crosspieces in AISI 304 stainless steel for In ≥4000A current values.




The crosspiece is an integral part of the busbar holder and is fixed directly inside the cubicle with the purpose-made brackets. In addition, it can also be used as a universal

crosspiece thanks to 5.5mm diameter round holes on the side and 10mm diameter holes for fixing the cage nuts.

Lastly, the crosspieces can be coupled on the external side to make the busbar system sturdier. Since the insulating supports are modular, the center distance between the phases can be increased by spacing them at a 12.5mm pitch.

The tie rods that fix the insulating supports are made of thermoplastic material (for In <4000A current values). They are available in a single length of 195mm and can be adjusted to suit the busbars installed. The AISI 304 stainless steel tie rods (for In ≥4000A current values) are available for 120mm, 160mm and 200mm busbars.

The linear system can house flat busbars (5 and 10mm thick) and shaped profile busbars in copper.



The center distance between phases can be increased by 12.5mm by simply sliding the insulation supports along the crosspieces. When the distance between phases is increased, the length of the closing crosspiece must also be increased.

Main distribution systems

General information

—
01 All the insulators are reversible and can house:
5mm and 10mm flat busbars and all shaped profile busbars

—
02 The scaled insulating supports house 5mm flat busbar systems on one side, while the other side houses 10mm flat busbars and all shaped profile busbars.

Advantages

- scalability: structure with modular insulating supports for 3P or 4P
- saving: the 4P system does not always have a full section neutral: the insulating supports allow structures of different sizes or with fewer insulating supports to be created, thus reducing costs.


- modularity: the linear system allows the center distance between the phases to be increased by spacing them at a 12.5mm pitch instead of installing them one against the other.
- sturdiness: the crosspieces can be coupled on the external side to make the busbar system sturdier.

Busbars installable with the insulating supports of the linear system

Length of insulating support	Notes	No. Flat busbars per phase	Slot dimensions	Maximum busbar H	Minimum busbar H
50mm	can house busbars on both sides	1x10mm	12mm slot	120x10	25x10
		2x5mm	9.5mm slot	120x5	20x5
75mm	can house busbars on both sides	2x10mm	12mm slot	120x10	25x10
		4x5mm	12mm slot	125x5	25x5
100mm	can house busbars on both sides	3x10mm	1mm slot	120x10	25x10
		2x10mm	12mm slot	120x10	25x10

All the shaped busbars can be housed in the insulating supports on a level with the slots for 10mm busbars.

—
01






The scaled busbar holder can house flat busbars up to 2000A or shaped busbars up to 1600A.

SCALED SYSTEM

The insulating support is a single unit that can be screwed onto the crosspiece with the aid of a threaded spacer. The linear system is connected to the distribution busbars with tie rods, which are the same for all types of busbars.

—
02

Busbars installable with the insulating supports of the scaled system

Insulating support	Notes	No. Flat busbars per phase	Slot dimensions	Maximum busbar H	Minimum busbar H
One type of insulating support	can house busbars on both side	1x10mm 2x5mm	12mm slot 9.5mm slot	120x10 125x5	30x10 20x5


All the shaped busbars can be housed in the insulating supports on a level with the slots for 10mm busbars.

Main distribution systems

Selection guides

LINEAR SYSTEM - FLAT BUSBARS AND SHAPED BUSBARS

Fixing busbar holders to the structure.




For vertical busbars in structure D≥500mm, the intermediate upright is always necessary


A - Vertical busbars at the rear of the structure
B1 - vertical busbars on the side of the structure **B2/B3** - vertical busbars with horizontal busbars in the structure under the top/on the bottom **B4/B5** - vertical busbars in the cable compartment with horizontal busbars top/bottom ⁽¹⁾

CROSSPIECES FOR BUSBAR HOLDERS (1 piece per busbar holder)

SUPPORTS FOR FIXING CROSSPIECES TO THE STRUCTURE *	Structure W (mm)	Crosspiece in galvanized sheet metal	Crosspiece in stainless steel for In≥4000A	Structure D (mm)	Crosspiece in galvanized sheet metal	Crosspiece in galvanized sheet metal + intermediate upright	Crosspiece in stainless steel for In≥4000A(5)	Crosspiece in stainless steel for In≥4000A + intermediate upright
(2 pieces per crosspiece)				200	PCRM0188			
	300	PCRM0288		300	PCRM0288			
	400	PCRM0388	PCRS0388	500	PCRM0488	PCRM0238		
	600	PCRM0588	PCRS0588	700	PCRM0688	PCRM0438	PCRS0438	
	800	PCRM0788	PCRS0788	900	PCRM0888	PCRM0638	PCRS0888	PCRS0638
	1000	PCRM0988	PCRS0988					
See example page 5/8-5/9	1250	PCRM1238	PCRS1238					

⁽¹⁾ Use busbars with 100x10mm maximum section for structures with internal cable compartment L=200mm with horizontal busbars top/bottom.





C/C1 - Horizontal busbars under the top or on the bottom of the structure⁽²⁾

D1 - Horizontal busbars at any height of the structure and internal cable compartment

D2 - Vertical busbars in the cable compartment with orizontal busbars in the structure at any hight⁽³⁾

D3 - Horizontal busbars at any hight in side by side structures and vertical busbars in the internal cable compartment

Structure D (mm)	Crosspiece in galvanized sheet metal + intermediate crosspiece PCKI....	Crosspiece in stainless steel for In≥4000A(4) + intermediate crosspiece PCKI....	Structure D (mm)	Crosspiece in galvanized sheet metal ⁽⁵⁾	Crosspiece in galvanized sheet metal + intermediate upright	Crosspiece in stainless steel for In≥4000A ⁽⁴⁾	Crosspiece in stainless steel for In≥4000A + intermediate upright
			200	PCRM0188			
			300	PCRM0288			
500	PCRM0238		500	PCRM0488	PCRM0238		
700	PCRM0438	PCRS0438	700	PCRM0688	PCRM0438	PCRS0438	
900	PCRM0638	PCRS0638	900	PCRM0888	PCRM0638	PCRS0888	PCRS0638

⁽²⁾ Order crosspieces PCKI.... to assemble busbars under the top or on the bottom, for assembly in D>300mm structures with internal cable compartment, order PCCM.... cable compartment depth crosspieces as well.

⁽³⁾ Use busbars with 80x10mm maximum section for structures with internal cable compartment L=200mm. With orizontal busbars in the structure at any hight.

⁽⁴⁾ Only flat busbars.

⁽⁵⁾ In structures without intermediate upright, swing frame PFPS.... cannot be installed with horizontal busbars at all height.

* The new bracket, PBBU0008 is not compatible with the old ones (PBBT0008, PBBV0008, PBBH0004), on the same busbar system, both horizontal and vertical, it is not possible the coexisting between old and new ones. The fixing of the crosspieces for busbar system must be done with only one kind of bracket.


Main distribution systems

Examples of use

LINEAR SYSTEM - FLAT BUSBARS AND SHAPED BUSBARS


Fixing busbar holders to the structure.

A
Vertical busbars at
the rear of the
structure




B1
Vertical busbars
on the side of the
structure


PBBU0008




PBBT0008




PBBV0008




B2/B3
Vertical busbars with horizontal busbars
in the structure




PBBU0008






PBBT0008



PBBV0008







C/C1
Horizontal busbars under the top or on
the bottom of the structure




B4/B5


vertical busbars in the cable compartment with orizontal busbars in the structure

**PBBU0008****PBBT0008****PBBV0008****D1**








Horizontal busbars at any height of the structure and internal cable compartment

**D2**

Vertical busbars in the cable compartment with orizontal busbars in the structure at any height

**D3**


Horizontal busbars at any hight in side by side structures and vertical busbars in the internal cable compartment





Main distribution systems

Examples of use

Example use of crosspieces



Description	Enclosure	Length [mm]	To be fitted in the following functional dimensions	Code
Crosspieces with "C" profile	Structure without intermediate upright	188 288 388 488 588 688 788 888 988 1238	200 300 400 500 600 700 800 900 1000 1250	PCRM0188 PCRM0288 PCRM0388 PCRM0488 PCRM0588 PCRM0688 PCRM0788 PCRM0888 PCRM0988 PCRM1238
	Structure with vertical intermediate upright	238 338 438 538 638 738	500 with intermediate upright 600 with intermediate upright 700 with intermediate upright 800 with intermediate upright 900 with intermediate upright 1000 with intermediate upright	PCRM0238 PCRM0338 PCRM0438 PCRM0538 PCRM0638 PCRM0738
	Any type	2013	To be cut according to the need	PCRM2013
Crosspieces with intermediate upright profile	Any type	300 400 600 800 1000 1250 1800 2000	300 400 600 800 1000 1250 1800 2000	PCKI0300 PCKI0400 PCKI0600 PCKI0800 PCKI1000 PCKI1250 PUKI1800 PUKI2000




Main distribution systems

Selection guides

LINEAR SYSTEM - COPPER FLAT BUSBARS

Choice of busbar holders and closing crosspieces in relation to the rated current In (A) and IP protection class.



Capacity In (A)	Number of busbars per phase	Section (mm)	Recommended D1 (busbar/ circuit-breaker/connection interaction) minimum			Busbars L1 L2 L3	Closing crosspiece 3-pole busbar holders 1 piece ⁽¹⁾
			D1≥300	D1≥700	D1=900		
IP30 / IP31 / IP43							
250	1	20x5	✓			3xPBFC2005	PCRM0188
400	1	25x5	✓			3xPBFC2505	PCRM0188
630	1	40x5	✓			3xPBFC4005	PCRM0188
800	1	30x10	✓			3xPBFC3010	PCRM0188
1000	1	80x5	✓			3xPBFC8005	PCRM0188
	1	40x10	✓			3xPBFC4010	PCRM0188
1250	1	100x5	✓			3xPBFC1005	PCRM0188
	1	50x10	✓			3xPBFC5010	PCRM0188
1600	2	80x5	✓			6xPBFC8005	PCRM0188
	1	80x10	✓			3xPBFC8010	PCRM0188
2000	2	100x5		✓		6xPBFC1005	PCRM0188
	2	50x10		✓		6xPBFC5010	PCRM0288
2500	4	80x5	✓			12xPBFC8005	PCRM0288
	2	80x10	✓			6xPBFC8010	PCRM0288
3200	4	100x5	✓			12xPBFC1005	PCRM0288
	2	100x10		✓		6xPBFC1001	PCRM0288
4000	3	100x10			✓	9xPBFC1001	PCRM0338 ⁽²⁾
IP30 / IP31 / IP40 / IP41							
5000	3	160x10			✓	9xPBFC1601	PCRS0338
7000	3	200x10			✓	9xPBFC2001	PCRS0338
IP40 / IP41 / IP65							
250	1	20x5	✓			3xPBFC2005	PCRM0188
400	1	32x5	✓			3xPBFC3205	PCRM0188
630	1	50x5	✓			3xPBFC5005	PCRM0188
800	1	63x5	✓			3xPBFC6305	PCRM0188
1000	2	40x5	✓			6xPBFC4005	PCRM0188
1250	1	100x5	✓			3xPBFC1005	PCRM0188
1600	1	100x10	✓			3xPBFC1001	PCRM0188
2000	1	120x10		✓		3xPBFC1201	PCRM0188
2000	2	60x10		✓		6xPBFC6010	PCRM0288
2500	2	100x10		✓		6xPBFC1001	PCRM0288
3200	3	100x10		✓		9xPBFC1001	PCRM0338
4000	3	120x10			✓	9xPBFC1201	PCRS0338


⁽¹⁾ When busbars with increased center distance are installed, the length of the closing crosspiece must also be increased.

⁽²⁾ Use sheet metal crosspiece and nylon tie rods.

⁽³⁾ Excluding D=500mm with intermediate upright.

⁽⁴⁾ The Pkg contains 24 pieces.

⁽⁵⁾ The Pkg contains 10 pieces.



Overall dimensions
crosspieces supports
4-pole D2 (mm)


4 poles		100% Neutral		50% Neutral		Closing crosspiece 4-pole bus-bar holders			Insulators ⁽⁴⁾		Tie rods ⁽⁵⁾	
Number of bus-bars per phase	Section (mm)	Section (mm)	100% N	Number busbars per phase	Section (mm)	Busbars L1 L2 L3 50%N	1 piece ⁽¹⁾	D2≥300	D2≥700 ⁽³⁾	D2=900 ⁽³⁾	3 poles 6 pieces	3 poles 4 pieces
1	20x5	4xPBFC2005	-	-	-	PCRM0238	✓				PBHB1125	PTRN1951
1	25x5	4xPBFC2505	-	-	-	PCRM0238	✓				PBHB1125	PTRN1951
1	40x5	4xPBFC4005	-	-	-	PCRM0238	✓				PBHB1125	PTRN1951
1	30x10	4xPBFC3010	-	-	-	PCRM0238	✓				PBHB1125	PTRN1951
1	80x5	4xPBFC8005	-	-	-	PCRM0238	✓				PBHB1125	PTRN1951
1	40x10	4xPBFC4010	1	40x5	PBFC4005	PCRM0238	✓				PBHB1125	PTRN1951
1	100x5	4xPBFC1005	-	-	-	PCRM0238	✓				PBHB1125	PTRN1951
1	50x10	4xPBFC5010	1	50x5	PBFC5005	PCRM0238	✓				PBHB1125	PTRN1951
2	80x5	8xPBFC8005	-	-	-	PCRM0238	✓				PBHB1125	PTRN1951
1	80x10	4xPBFC8010	1	80x5	7xPBFC8005	PCRM0238	✓				PBHB1125	PTRN1951
2	100x5	8xPBFC1005	1	100x5	7xPBFC1005	PCRM0238	✓				PBHB1125	PTRN1951
2	50x10	8xPBFC5010	1	50x10	7xPBFC5010	PCRM0338		✓			PBHB2145	PTRN1951
4	80x5	16xPBFC8005	2	80x5	14xPBFC8005	PCRM0338		✓			PBHB2145	PTRN1951
2	80x10	8xPBFC8010	1	80x10	7xPBFC8010	PCRM0338		✓			PBHB2145	PTRN1951
4	100x5	16xPBFC1005	2	100x5	14xPBFC1005	PCRM0338		✓			PBHB2145	PTRN1951
2	100x10	8xPBFC1001	1	100x10	7xPBFC1001	PCRM0338		✓			PBHB2145	PTRN1951
3	100x10	12xPBFC1001	2	100x10	11xPBFC1001	PCRM0438 ⁽²⁾			✓		PBHB3121	PTRN1951 ⁽²⁾
3	160x10	12xPBFC1601	2	160x10	11xPBFC1601	PCRS0438			✓		PBHB3121	PTRS1601
3	200x10	12xPBFC2001	2	200x10	11xPBFC2001	PCRS0438			✓		PBHB3121	PTRS2001
1	20x5	4xPBFC2005	-	-	-	PCRM0238	✓				PBHB1125	PTRN1951
1	32x5	4xPBFC3205	-	-	-	PCRM0238	✓				PBHB1125	PTRN1951
1	50x5	4xPBFC5005	-	-	-	PCRM0238	✓				PBHB1125	PTRN1951
1	63x5	4xPBFC6305	-	-	-	PCRM0238	✓				PBHB1125	PTRN1951
2	40x5	8xPBFC4005	1	40x5	7xPBFC4005	PCRM0238	✓				PBHB1125	PTRN1951
1	100x5	4xPBFC1005	-	-	-	PCRM0238	✓				PBHB1125	PTRN1951
1	100x10	4xPBFC1001	1	100x5	PBFC1005	PCRM0238	✓				PBHB1125	PTRN1951
1	120x10	4xPBFC1201	-	-	-	PCRM0238	✓				PBHB1125	PTRN1951
2	60x10	8xPBFC6010	1	60x10	7xPBFC6010	PCRM0338		✓			PBHB2145	PTRN1951
2	100x10	8xPBFC1001	1	100x10	7xPBFC1001	PCRM0338		✓			PBHB2145	PTRN1951
3	100x10	12xPBFC1001	2	100x10	11xPBFC1001	PCRM0438			✓		PBHB3121	PTRN1951
3	120x10	12xPBFC1201	2	120x10	11xPBFC1201	PCRS0438			✓		PBHB3121	PTRS1201

Main distribution systems

Selection guides

LINEAR SYSTEM - CUPONAL FLAT BUSBARS

Choice of busbar holders and closing crosspieces in relation to the rated current In (A) and IP protection class.



Description		Recommended D1 (busbar/circuit-breaker/connection interaction) minimum 3 pole 3 poles				Closing crosspiece 3-pole busbar holders 1 piece ⁽¹⁾
Capacity In (A)	Number of busbars per phase	Section (mm)	D1≥300	D1≥700	Busbars L1 L2 L3	
IP30 / IP31						
250	1	20x5	✓		3xPBFA2005	PCRM0188
400	1	30x5	✓		3xPBFA3005	PCRM0188
630	1	50x5	✓		3xPBFA5005	PCRM0188
800	1	40x10	✓		3xPBFA4010	PCRM0188
1000	1	50x10	✓		3xPBFA5010	PCRM0188
1000	2	40x5	✓		6xPBFA4005	PCRM0188
1250	1	75x10	✓		3xPBFA7510	PCRM0188
1250	2	60x5	✓		6xPBFA6005	PCRM0188
1600	2	80x5	✓		6xPBFA8005	PCRM0188
2000	1	120x10		✓	3xPBFA1201	PCRM0188
2000	4	50x5		✓	12xPBFA5005	PCRM0288
2500	2	80x10		✓	6xPBFA8010	PCRM0288
2500	4	80x5		✓	12xPBFA8005	PCRM0288
3200	2	120x10		✓	6xPBFA1201	PCRM0288
IP40 / IP41 / IP65						
250	1	25x5	✓		3xPBFA2505	PCRM0188
400	1	40x5	✓		3xPBFA4005	PCRM0188
630	1	60x5	✓		3xPBFA6005	PCRM0188
800	1	80x5	✓		3xPBFA8005	PCRM0188
1000	2	50x5	✓		6xPBFA5005	PCRM0188
1250	1	80x10	✓		3xPBFA8010	PCRM0188
1600	1	100x10	✓		3xPBFA1001	PCRM0188
2000	2	75x10		✓	6xPBFA7510	PCRM0288
2500	2	100x10		✓	6xPBFA1001	PCRM0288
3200	3	100x10		✓	9xPBFA1001	PCRM0338


⁽¹⁾ When busbars with increased center distance are installed, the length of the closing crosspiece must also be increased.

⁽²⁾ Use sheet metal crosspiece and nylon tie rods.

⁽³⁾ Excluding D=500mm with intermediate upright.

⁽⁴⁾ The Pkg contains 24 pieces.

⁽⁵⁾ The Pkg contains 10 pieces.



4 poles 100% Neutral		50% Neutral		Overall dimensions crosspieces supports 4-pole D2 (mm)			Insulators ⁽³⁾	Tie rods ⁽⁴⁾				
Number of busbars per phase	Section (mm)	Number busbars per phase	Section (mm)	Busbars	L1	L2	Closing crosspiece 4-pole busbar holders 1 piece ⁽¹⁾	D2≥300	D2≥700 ⁽²⁾	D2=900 ⁽²⁾	3 poles 6 pieces	3 poles 4 pieces
1	20x5	4xPBFA2005	-	-	-	-	PCRM0238	✓			PBHB1125	PTRN1951
1	30x5	4xPBFA3005	-	-	-	-	PCRM0238	✓			PBHB1125	PTRN1951
1	50x5	4xPBFA5005	-	-	-	-	PCRM0238	✓			PBHB1125	PTRN1951
1	40x10	4xPBFA4010	1	40x5	PBFA4005	PCRM0238	✓				PBHB1125	PTRN1951
1	50x10	4xPBFA5010	1	50x5	PBFA5005	PCRM0238	✓				PBHB1125	PTRN1951
2	40x5	8xPBFA4005	1	40x5	7xPBFA4005	PCRM0238	✓				PBHB1125	PTRN1951
1	75x10	4xPBFA7510	-	-	-	-	PCRM0238	✓			PBHB1125	PTRN1951
2	60x5	8xPBFA6005	1	60x5	7xPBFA6005	PCRM0238	✓				PBHB1125	PTRN1951
2	80x5	8xPBFA8005	1	80x5	7xPBFA8005	PCRM0238	✓				PBHB1125	PTRN1951
1	120x10	4xPBFA1201	-	-	-	-	PCRM0238	✓			PBHB1125	PTRN1951
4	50x5	16xPBFA5005	2	50x5	14xPBFA5005	PCRM0338		✓			PBHB2145	PTRN1951
2	80x10	8xPBFA8010	1	80x10	7xPBFA8010	PCRM0338		✓			PBHB2145	PTRN1951
4	80x5	16xPBFA8005	2	80x5	14xPBFA8005	PCRM0338		✓			PBHB2145	PTRN1951
2	120x10	8xPBFA1201	1	120x10	7xPBFA1201	PCRM0338		✓			PBHB2145	PTRN1951
1	25x5	4xPBFA2505	-	-	-	-	PCRM0238	✓			PBHB1125	PTRN1951
1	40x5	4xPBFA4005	-	-	-	-	PCRM0238	✓			PBHB1125	PTRN1951
1	60x5	4xPBFA6005	-	-	-	-	PCRM0238	✓			PBHB1125	PTRN1951
1	80x5	4xPBFA8005	-	-	-	-	PCRM0238	✓			PBHB1125	PTRN1951
2	50x5	8xPBFA5005	1	50x5	7xPBFA5005	PCRM0238	✓				PBHB1125	PTRN1951
1	80x10	4xPBFA8010	1	80x5	PBFA8005	PCRM0238	✓				PBHB1125	PTRN1951
1	100x10	4xPBFA1001	-	-	-	-	PCRM0238	✓			PBHB1125	PTRN1951
2	75x10	8xPBFA7510	1	75x10	7xPBFA7510	PCRM0338		✓			PBHB2145	PTRN1951
2	100x10	8xPBFA1001	1	100x10	7xPBFA1001	PCRM0338		✓			PBHB2145	PTRN1951
3	100x10	12xPBFA1001	2	100x10	11xPBFA1001	PCRM0438		✓			PBHB3121	PTRN1951

Main distribution systems

Selection guides

LINEAR SYSTEM - SHAPED BUSBARS

Choice of busbar holders and closing crosspieces in relation to rated current In (A) and IP protection class.


Recommended D1 (busbar/circuit-breaker/connection interaction) minimum 3 pole 3 poles												
Capacity In (A)	IP30/31	IP40/41	IP65	Number of busbars per phase	WxW (mm)	Section (mm²)	Busbars	D1≥300	D1≥500	D1≥700	L1 L2 L3	Closing crosspiece 3-pole busbar holder 1 piece
475	440	400	1	1	30x10	165	PBSC0400	✓			3xPBSC0400	PCRM0188
655	643	630	1	1	35x10	204	PBSC0630	✓			3xPBSC0630	PCRM0188
958	840	800	1	1	45x10	324	PBSC0800	✓			3xPBSC0800	PCRM0188
1342	1220	1000	1	1	67x10	454	PBSC1000	✓			3xPBSC1000	PCRM0188
1418	1338	1250	1	1	70x10	516	PBSC1250	✓			3xPBSC1250	PCRM0188
1857	1744	1600	1	1	95x10	758	PBSC1600	✓			3xPBSC1600	PCRM0188
2354	2200	2000	1	1	105x15	995	PBSC2000		✓		3xPBSC2000	PCRM0288
2860	2750	2500	1	1	105x15	1255	PBSC2500		✓		3xPBSC2500	PCRM0288

⁽¹⁾ When busbars with increased center distance are installed, the length of the closing crosspiece must also be increased.

⁽²⁾ Excluding D=500mm with intermediate upright.

⁽³⁾ The Pkg contains 24 pieces.

⁽⁴⁾ The Pkg contains 10 pieces.



		Overall dimensions crosspieces supports 4-pole D2 (mm)			Insulators ⁽³⁾	Tie rods ⁽⁴⁾	
4 poles		Closing crosspiece 4-pole busbar holder 1 piece ⁽¹⁾	D2≥300	D2≥500	D2≥400 ⁽²⁾	3 poles 6 pieces 4 poles 8 pieces	3 poles 4 pieces 4 poles 5 pieces
100% Neutral	50% Neutral	PCRM0238	✓			PBHB1125	PTRN1951
4xPBSC0400	-	PCRM0238	✓			PBHB1125	PTRN1951
4xPBSC0630	-	PCRM0238	✓			PBHB1125	PTRN1951
4xPBSC0800	-	PCRM0238	✓			PBHB1125	PTRN1951
4xPBSC1000	-	PCRM0238	✓			PBHB1125	PTRN1951
4xPBSC1250	-	PCRM0238	✓			PBHB1125	PTRN1951
4xPBSC1600	-	PCRM0238	✓			PBHB1125	PTRN1951
4xPBSC2000	-	PCRM0338		✓		PBHB2145	PTRN1951
4xPBSC2500	3xPBSC2500 + 1xPBSC2000	PCRM0338		✓		PBHB2145	PTRN1951


Main distribution systems

Selection guides

LINEAR SYSTEM - FLAT BUSBARS AND SHAPED BUSBARS

Choice and assembly of the number of busbar holders, in relation to maximum Icw

Use of the correct number of busbar holders guarantees electrodynamic stress withstand in the event of a short-circuit. Establish the maximum distance (X_{\max}) which must not be exceeded between two consecutive busbar holders, in relation to the maximum I_{cw} .



The distance between the first busbar holder and the end of the busbar must not exceed $\frac{1}{4}$ of "X".

Copper busbars

Description		No. busbar holders Lenght =1750mm in relation to Icw max																		
Capacity In (A)		Number of busbars per WxW		(mm)	Busbar	Insulators	15 kA	X max	25 kA	X max	36 kA	X max	50 kA	X max	65 kA	X max	75 kA	X max	85 kA	X max
		IP30/31	IP40/41				phase													
FLAT BUSBARS																				
250	250	250	1	20x5	PBFC2005	PBHB1125	7	275	-	-	-	-	-	-	-	-	-	-	-	
400	-	-	1	25x5	PBFC2505	PBHB1125	7	300	9	200	-	-	-	-	-	-	-	-	-	
-	400	400	1	32x5	PBFC3205	PBHB1125	5	450	7	275	-	-	-	-	-	-	-	-	-	
630	-	-	1	40x5	PBFC4005	PBHB1125	5	450	7	300	9	200	-	-	-	-	-	-	-	
-	630	630	1	50x5	PBFC5005	PBHB1125	5	475	7	300	9	225	-	-	-	-	-	-	-	
800	-	-	1	30x10	PBFC3010	PBHB1125	4	525	5	450	7	300	-	-	-	-	-	-	-	
-	800	800	1	63x5	PBFC6305	PBHB1125	4	525	5	425	6	325	-	-	-	-	-	-	-	
1000	-	-	1	40x10	PBFC4010	PBHB1125	4	525	5	450	6	375	9	225	-	-	-	-	-	
-	1000	1000	2	40x5	PBFC4005	PBHB1125	4	525	5	475	6	375	-	-	-	-	-	-	-	
1000	-	-	1	80x5	PBFC8005	PBHB1125	4	525	5	475	6	375	9	225	-	-	-	-	-	
1250	1250	1250	1	100x5	PBFC1005	PBHB1125	3	1000	4	525	6	375	7	275	-	-	-	-	-	
1250	-	-	1	50x10	PBFC5010	PBHB1125	3	1000	4	525	6	375	8	250	9	200	-	-	-	
-	1600	1600	1	100x10	PBFC1001	PBHB1125	3	1000	4	550	4	500	6	325	9	200	-	-	-	
1600	-	-	1	80x10	PBFC8010	PBHB1125	3	1000	4	525	5	475	7	300	9	200	-	-	-	
1600	-	-	2	80x5	PBFC8005	PBHB1125	3	1000	4	525	5	475	7	300	9	200	-	-	-	
2000	-	-	2	100x5	PBFC1005	PBHB1125	3	1000	4	550	4	500	6	325	9	200	-	-	-	
-	2000	2000	1	120x10	PBFC1201	PBHB1125	3	1000	4	550	4	500	6	325	9	200	-	-	-	
2000	-	-	2	50x10	PBFC5010	PBHB2145	3	1000	4	525	6	375	8	250	9	200	-	-	-	
-	2000	2000	2	60x10	PBFC6010	PBHB2145	3	1000	4	525	6	375	8	250	9	200	-	-	-	
2500	-	-	2	80x10	PBFC8010	PBHB2145	3	1000	3	1000	4	525	5	400	7	275	9	200	-	
2500	-	-	4	80x5	PBFC8005	PBHB2145	3	1000	3	1000	4	525	5	400	7	275	9	200	-	
3200	2500	2500	2	100x10	PBFC1001	PBHB2145	3	1000	3	1000	4	525	5	400	7	300	7	275	8	
3200	-	-	4	100x5	PBFC1005	PBHB2145	3	1000	3	1000	4	525	5	400	7	275	9	200	-	
4000	3200	3200	3	100x10	PBFC1001	PBHB3121	3	1000	3	1000	3	750	4	500	5	400	6	350	7	
-	4000	4000	3	120x10	PBFC1201	PBHB3121	3	1000	3	1000	3	750	4	500	5	400	6	350	7	
5000	5000	-	3	160x10	PBFC1601	PBHB3121	3	1000	3	1000	3	1000	3	750	5	400	6	350	7	
7000	7000	-	3	200x10	PBFC2001	PBHB3121	3	1000	3	1000	3	1000	3	750	5	400	6	350	7	
SHAPED BUSBARS																				
475	440	400	1	30x10	PBSC0400	PBHB1125	4	525	5	450	-	-	-	-	-	-	-	-	-	
655	643	630	1	35x10	PBSC0630	PBHB1125	4	525	5	450	7	300	-	-	-	-	-	-	-	
958	840	800	1	45x10	PBSC0800	PBHB1125	4	525	5	450	6	375	-	-	-	-	-	-	-	
1342	1220	1000	1	67x10	PBSC1000	PBHB1125	4	525	5	450	6	375	9	225	-	-	-	-	-	
1418	1338	1250	1	70x10	PBSC1250	PBHB1125	3	1000	4	525	6	375	8	250	-	-	-	-	-	
1857	1744	1600	1	95x10	PBSC1600	PBHB1125	3	1000	4	550	5	400	7	275	9	200	-	-	-	
2354	2200	2000	1	105x15	PBSC2000	PBHB2145	3	1000	4	550	4	500	6	325	9	225	9	200	-	
2860	2750	2500	1	105x15	PBSC2500	PBHB2145	3	1000	3	1000	4	525	5	400	7	275	9	200	-	

Cuponal busbars

				No. busbar holders Lenght =1750mm in relation to lcw max														
Capacity In (A)		Number of busbars per phase		WxW (mm)		Busbar	Insulators	15 kA	X max	25 kA	X max	36 kA	X max	50 kA	X max	65 kA	X max	
100 kA X max		120 kA X max		FLAT BUSBARS IP30/31														
-	-	-	-	250	1	20x5	PBFA2005	PBHB1125	10	225								
-	-	-	-	400	1	30x5	PBFA3005	PBHB1125	10	225	13	175						
-	-	-	-	630	1	50x5	PBFA5005	PBHB1125	7	275	10	225	13	175				
-	-	-	-	800	1	40x10	PBFA4010	PBHB1125	6	325	7	275	10	225				
-	-	-	-	1000	1	50x10	PBFA5010	PBHB1125	6	325	7	275	9	250	13	175		
-	-	-	-	1000	2	40x5	PBFA4005	PBHB1125	6	325	7	275	9	250	13	175		
-	-	-	-	1250	1	75x10	PBFA7510	PBHB1125	4	500	6	325	9	250	10	225		
-	-	-	-	1250	2	60x5	PBFA6005	PBHB1125	4	500	6	325	9	250	12	200	13	
-	-	-	-	1600	2	80x5	PBFA8005	PBHB1125	4	500	6	325	7	275	10	225	175	
-	-	-	-	2000	1	120x10	PBFA1201	PBHB1125	4	500	6	325	6	325	9	250	13	175
-	-	-	-	2000	4	50x5	PBFA5005	PBHB2145	4	500	6	325	9	250	12	200	13	175
-	-	-	-	2500	2	80x10	PBFA8010	PBHB2145	4	600	4	500	6	325	7	275	10	225
-	-	-	-	2500	4	80x5	PBFA8005	PBHB2145	4	600	4	500	6	325	7	275	10	225
-	-	-	-	3200	2	120x10	PBFA1201	PBHB2145	4	600	4	500	6	325	7	275	10	225
-	-	-	-	FLAT BUSBARS IP40/41/65														
9	225	-	-	250	1	25x5	PBFA2505	PBHB1125	10	225								
-	-	-	-	400	1	40x5	PBFA4005	PBHB1125	7	275	10	225						
9	200	-	-	630	1	60x5	PBFA6005	PBHB1125	7	275	10	225	13	175				
9	200	-	-	800	1	80x5	PBFA8005	PBHB1125	6	325	7	275	9	250				
9	200	9	200	1000	2	50x5	PBFA5005	PBHB1125	6	325	7	275	9	250				
9	200	9	200	1250	1	80x10	PBFA8010	PBHB1125	4	500	6	325	9	250	10	225		
-	-	-	-	1600	1	100x10	PBFA1001	PBHB1125	4	500	6	325	6	325	9	250	13	175
-	-	-	-	2000	2	75x10	PBFA7510	PBHB2145	4	500	6	325	9	250	12	200	13	175
-	-	-	-	2500	2	100x10	PBFA1001	PBHB2145	4	600	4	500	6	325	7	275	10	225
-	-	-	-	3200	3	100x10	PBFA1001	PBHB3121	4	600	4	500	4	500	6	325	7	275

Main distribution systems

Selection guides


SCALED SYSTEM-FLAT BUSBARS

Fixing busbar holders to the structure.

A		SUPPORTS FOR FIXING CROSPieces TO THE STRUCTURE (2 pieces per crosspiece)																
		A - Vertical busbars at the side of the structure																
		PBBV0008 ⁽¹⁾ PBBU0008																
		CROSPieces FOR BUSBAR HOLDERS (1 piece per busbar holder)																
<table border="1"> <thead> <tr> <th>Structure P (mm)</th> <th>Crosspiece in galvanized sheet metal</th> <th>Crosspiece in galvanized sheet metal + intermediate upright</th> </tr> </thead> <tbody> <tr> <td>300</td> <td>PCRM0288</td> <td></td> </tr> <tr> <td>500</td> <td>PCRM0488</td> <td>PCRM0238</td> </tr> <tr> <td>700</td> <td>PCRM0688</td> <td>PCRM0438</td> </tr> <tr> <td>900</td> <td>PCRM0888</td> <td>PCRM0638</td> </tr> </tbody> </table>				Structure P (mm)	Crosspiece in galvanized sheet metal	Crosspiece in galvanized sheet metal + intermediate upright	300	PCRM0288		500	PCRM0488	PCRM0238	700	PCRM0688	PCRM0438	900	PCRM0888	PCRM0638
Structure P (mm)	Crosspiece in galvanized sheet metal	Crosspiece in galvanized sheet metal + intermediate upright																
300	PCRM0288																	
500	PCRM0488	PCRM0238																
700	PCRM0688	PCRM0438																
900	PCRM0888	PCRM0638																

⁽¹⁾ Use busbars with 50x10mm maximum section for structures with internal cable compartment W=200mm.

Choice of busbar holders in relation to rated current In (A) and IP protection class. Copper busbars.




Number Capacity of busbars In (A) per phase	WxW (mm)	Switchboard installation Minimum depth (mm) D≥300 D≥700	3/4-pole insulator complete with tie rods ⁽¹⁾	Insulators 6 pieces for 3 poles 8 pieces for 4 poles ⁽²⁾	3 poles	4 poles	Busbars L1 L2 L3+ x100% Neutral	Busbars L1 L2 L3+ x50% Neutral
			PBHS1125		PBHB1125	3xPBFC2005	4xPBFC2005	
IP30 / IP31								
250A	1	20x5	✓	PBHS1125	PBHB1125	3xPBFC2005	4xPBFC2005	
400A	1	25x5	✓	PBHS1125	PBHB1125	3xPBFC2505	4xPBFC2505	
630A	1	40x5	✓	PBHS1125	PBHB1125	3xPBFC4005	4xPBFC4005	
800A	1	30x10	✓	PBHS1125	PBHB1125	3xPBFC3010	4xPBFC3010	
1000A	1	80x5	✓	PBHS1125	PBHB1125	3xPBFC8005	4xPBFC8005	
1000A	1	40x10	✓	PBHS1125	PBHB1125	3xPBFC4010	4xPBFC4010	3xPBFC4010+1xPBFC4005
1250A	1	100x5	✓	PBHS1125	PBHB1125	3xPBFC1005	4xPBFC1005	
1250A	1	50x10	✓	PBHS1125	PBHB1125	3xPBFC5010	4xPBFC5010	3xPBFC5010+1xPBFC5005
1600A	2	80x5	✓	PBHS1125	PBHB1125	6xPBFC8005	8xPBFC8005	7xPBFC8005
1600A	1	80x10	✓	PBHS1125	PBHB1125	3xPBFC8010	4xPBFC8010	3xPBFC8010+1xPBFC8005
2000A	2	100x5	✓	PBHS1125	PBHB1125	6xPBFC1005	8xPBFC1005	7xPBFC1005
IP40 / IP41 / 65								
250A	1	20x5	✓	PBHS1125	PBHB1125	3xPBFC2005	4xPBFC2005	
400A	1	32x5	✓	PBHS1125	PBHB1125	3xPBFC3205	4xPBFC3205	
630A	1	50x5	✓	PBHS1125	PBHB1125	3xPBFC5005	4xPBFC5005	
800A	1	63x5	✓	PBHS1125	PBHB1125	3xPBFC6305	4xPBFC6305	
1000A	2	40x5	✓	PBHS1125	PBHB1125	6xPBFC4005	8xPBFC4005	7xPBFC4005
1250A	1	100x5	✓	PBHS1125	PBHB1125	3xPBFC1005	4xPBFC1005	
1600A	1	100x10	✓	PBHS1125	PBHB1125	3xPBFC1001	4xPBFC1001	3xPBFC1001+1xPBFC1005
2000A	1	120x10	✓	PBHS1125	PBHB1125	3xPBFC1201	4xPBFC1201	

⁽¹⁾ The Pkg contains 1 scaled busbar holder provided with nylon tie-rods.

⁽²⁾ The Pkg contains 24 pieces.

SCALED SYSTEM-FLAT BUSBARS

Choice of busbar holders in relation to rated current In (A) and IP protection class. Cuponal busbars.




Capacity In (A)	Number of busbars per phase (mm)	Switchboard installation Minimum depth (mm)		3/4-pole insulator complete with tie rods ⁽¹⁾	Insulators 6 pieces for 3 poles 8 pieces for 4 poles ⁽²⁾	3 poles	4 poles
		D≥300	D≥700			Busbars L1 L2 L3	Busbars L1 L2 L3+100% Neutral
IP30 / IP31							
250	1	20x5	✓	PBHS1125	PBHB1125	3xPBFA2005	4xPBFA2005
400	1	30x5	✓	PBHS1125	PBHB1125	3xPBFA3005	4xPBFA3005
630	1	50x5	✓	PBHS1125	PBHB1125	3xPBFA5005	4xPBFA5005
800	1	40x10	✓	PBHS1125	PBHB1125	3xPBFA4010	4xPBFA4010
1000	1	50x10	✓	PBHS1125	PBHB1125	3xPBFA5010	4xPBFA5010
1000	2	40x5	✓	PBHS1125	PBHB1125	6xPBFA4005	8xPBFA4005
1250	1	75x10	✓	PBHS1125	PBHB1125	3xPBFA7510	4xPBFA7510
1250	2	60x5	✓	PBHS1125	PBHB1125	6xPBFA6005	8xPBFA6005
1600	2	80x5	✓	PBHS1125	PBHB1125	6xPBFA8005	8xPBFA8005
2000	1	120x10	✓	PBHS1125	PBHB1125	3xPBFA1201	4xPBFA1201
IP40 / IP41 / 65							
250	1	25x5	✓	PBHS1125	PBHB1125	3xPBFA2505	4xPBFA2505
400	1	40x5	✓	PBHS1125	PBHB1125	3xPBFA4005	4xPBFA4005
630	1	60x5	✓	PBHS1125	PBHB1125	3xPBFA6005	4xPBFA6005
800	1	80x5	✓	PBHS1125	PBHB1125	3xPBFA8005	4xPBFA8005
1000	2	50x5	✓	PBHS1125	PBHB1125	6xPBFA5005	8xPBFA5005
1250	1	80x10	✓	PBHS1125	PBHB1125	3xPBFA8010	4xPBFA8010
1600	1	100x10	✓	PBHS1125	PBHB1125	3xPBFA1001	4xPBFA1001

⁽¹⁾ The Pkg contains 1 scaled busbar holder provided with nylon tie-rods.

⁽²⁾ The Pkg contains 24 pieces.

SCALED SYSTEM - SHAPED BUSBARS

Choice of busbar holders in relation to rated current In (A) and IP protection class.



Capacity In (A)	Number of busbars per phase (mm)	Switchboard installation Minimum depth (mm)		3/4-pole insulator complete with tie rods ⁽¹⁾	Insulators 6 pieces for 3 poles 8 pieces for 4 poles ⁽²⁾	3 poles	4 poles			
		Section (mm ²)	D≥300			Busbars L1 L2 L3	Busbars L1 L2 L3+100% Neutral			
IP30/31 IP40/41 IP65										
475	440	400	1	30x10	165	✓	PBHS1125	PBHB1125	3xPBSC0400	4xPBSC0400
655	643	630	1	35x10	204	✓	PBHS1125	PBHB1125	3xPBSC0630	4xPBSC0630
958	840	800	1	45x10	324	✓	PBHS1125	PBHB1125	3xPBSC0800	4xPBSC0800
1342	1220	1000	1	67x10	454	✓	PBHS1125	PBHB1125	3xPBSC1000	4xPBSC1000
1418	1338	1250	1	70x10	516	✓	PBHS1125	PBHB1125	3xPBSC1250	4xPBSC1250
1857	1744	1600	1	95x10	758	✓	PBHS1125	PBHB1125	3xPBSC1600	4xPBSC1600

⁽¹⁾ The Pkg contains 1 scaled busbar holder provided with nylon tie-rods.

⁽²⁾ The Pkg contains 24 pieces.


Main distribution systems

Selection guides

SCALED SYSTEM - FLAT BUSBARS AND SHAPED BUSBARS

Choice and assembly of the number of busbar holders, in relation to maximum Icw

Use of the correct number of busbar holders guarantees electrodynamic stress withstand in the event of a short-circuit. Establish the maximum distance (X max) which must not be exceeded between two consecutive busbar holders, in relation to the maximum Icw.



The distance between the first busbar holder and the end of the busbar must not exceed $\frac{1}{4}$ of "X".

Copper busbars

Description				No. busbar holders Length =1750mm in relation to Icw max										
Capacity In (A)			Number of busbars per phase	WxW (mm)	BUSBAR	Insulators	15 kA	X max	25 kA	X max	36 kA	X max	50 kA	X max
IP30/31	IP40/41	IP65												
FLAT BUSBARS														
250	250	250	1	20x5	PBFC2005	PBHS1125	9	200	-	-	-	-	-	
400	-	-	1	25x5	PBFC2505	PBHS1125	7	300	-	-	-	-	-	
-	400	400	1	32x5	PBFC3205	PBHS1125	7	300	9	200	-	-	-	
630	-	-	1	40x5	PBFC4005	PBHS1125	7	300	9	200	-	-	-	
-	630	630	1	50x5	PBFC5005	PBHS1125	5	450	7	275	9	200	-	
800	-	-	1	30x10	PBFC3010	PBHS1125	5	450	6	375	9	225	-	
-	800	800	1	63x5	PBFC6305	PBHS1125	4	525	5	425	6	325	9	
1000	-	-	1	40x10	PBFC4010	PBHS1125	4	525	5	450	6	375	9	
-	1000	1000	2	40x5	PBFC4005	PBHS1125	4	525	5	475	7	300	-	
1000	-	-	1	80x5	PBFC8005	PBHS1125	4	525	5	475	6	375	9	
1250	1250	1250	1	100x5	PBFC1005	PBHS1125	4	525	4	525	6	375	8	
1250	-	-	1	50x10	PBFC5010	PBHS1125	4	525	4	525	6	375	8	
-	1600	1600	1	100x10	PBFC1001	PBHS1125	4	550	4	550	5	475	6	
1600	-	-	1	80x10	PBFC8010	PBHS1125	4	525	4	525	5	475	7	
1600	-	-	2	80x5	PBFC8005	PBHS1125	4	525	4	525	6	375	-	
2000	-	-	2	100x5	PBFC1005	PBHS1125	4	550	5	425	6	375	-	
-	2000	2000	1	120x10	PBFC1201	PBHS1125	4	550	4	550	5	475	7	
SHAPED BUSBARS														
475	440	400	1	30x10	PBSC0400	PBHS1125	5	450	6	375	9	225	-	
655	643	630	1	35x10	PBSC0630	PBHS1125	5	450	6	375	9	225	-	
958	840	800	1	45x10	PBSC0800	PBHS1125	4	525	5	425	6	325	9	
1342	1220	1000	1	67x10	PBSC1000	PBHS1125	4	525	5	450	6	375	9	
1418	1338	1250	1	70x10	PBSC1250	PBHS1125	4	525	4	525	6	375	8	
1857	1744	1600	1	95x10	PBSC1600	PBHS1125	4	550	4	550	5	475	6	

Cuponal busbars

Description			No. busbar holders Lenght =1750mm in relation to Icw max									
Capacity In (A) IP30/31	Number of busbars per phase	WxW (mm)	BUSBAR	Insulators	15 kA	X max	25 kA	X max	36 kA	X max	50 kA	X max
FLAT BUSBARS IP30/31												
250	1	20x5	PBFA2005	PBHS1125	13	175						
400	1	30x5	PBFA3005	PBHS1125	10	225						
630	1	50x5	PBFA5005	PBHS1125	10	225	13	175				
800	1	40x10	PBFA4010	PBHS1125	7	275	9	250	13	175		
1000	1	50x10	PBFA5010	PBHS1125	6	325	7	275	9	250	13	
1000	2	40x5	PBFA4005	PBHS1125	6	325	7	275	9	250	13	
1250	1	75x10	PBFA7510	PBHS1125	6	325	6	325	9	250	12	
1250	2	60x5	PBFA6005	PBHS1125	6	325	6	325	9	250	12	
1600	2	80x5	PBFA8005	PBHS1125	6	325	6	325	9	250		
2000	1	120x10	PBFA1201	PBHS1125	6	325	7	275	9	250		
FLAT BUSBARS IP40/41/65												
250	1	25x5	PBFA2505	PBHS1125	13	175						
400	1	40x5	PBFA4005	PBHS1125	10	225	13	175				
630	1	60x5	PBFA6005	PBHS1125	7	275	10	225	13	175		
800	1	80x5	PBFA8005	PBHS1125	6	325	7	275	9	250	13	
1000	2	50x5	PBFA5005	PBHS1125	6	325	7	275	10	225		
1250	1	80x10	PBFA8010	PBHS1125	6	325	6	325	9	250	12	
1600	1	100x10	PBFA1001	PBHS1125	6	325	6	325	7	275	9	

Connection to the circuit breaker

Choice of the copper bars to be used for the connection to the breakers' terminals.

Breaker type	Cross section and amount of the connected copper bars
Tmax T7 lu=1000A, Emax E1.2 lu=1000A	1x50x10
Tmax T7 lu=1250A, Emax E1.2 lu=1250A	2x50x10
Tmax T7 lu=1600A, Emax E1.2 lu=1600A	2x50x10
Emax E2.2 lu=2000A	2x60x10
Emax E2.2 lu=2500A	3x60x10
Emax E4.2 lu=3200A	3x100x10
Emax E4.2 lu=4000A	4x100x10
Emax E6.2 lu=5000A	5x100x10
Emax E6.2 lu=6300A	7x100x10 (terminals) + 4x160x10 (connection)

Please note that the cross section of the horizontal main busbar system might have the different size and configuration than the connection to the breaker of the same current. Double check with the connection's drawings is requested.

Main distribution systems

Selection guides

Compensators and connections for flat and shaped busbar

	Shaped busbars							
	In 400A	630A	800A	1000A	1250A	1600A	2000A	2500A
In								
400A	PFCB4080							PFCB4080
630A	PFCB4080							PFCB4080
800A	PFCB4080							PFCB4080
1000A				PFCB1016				PFCB1016
1250A				PFCB1016				PFCB1016
1600A					PFCB1016	PFCB2025	PFCB2025	
2000A						2x PFCB2025	2x PFCB2025	
2500A								2x PFCB2025

PFCB4080 – Connections between shaped busbar/shaped busbar or shaped busbar/flat busbar for 400A, 630A, 800A

PFCB1016 – Connections between shaped busbar/shaped busbar or shaped busbar/flat busbar for 1000A, 1250A, 1600A

PFCB2025 – Connections between shaped busbar/shaped busbar or shaped busbar/flat busbar for 2000A, 2500A

PFCC0023 – Compensator for configurations composed of no. of busbar per phase>1

The connections can be used also for joining flat busbar/ shaped busbar (as per the chart above) if the following conditions are fulfilled:

- use of insulating support of the same size both in H and in V
- use of flat busbar with 10mm thickness

In case of joining a main flat busbar system composed of more than one busbar per phase and shaped busbar distribution system, it is recommended to align the shaped busbar to the flat busbar in the most rearward position.

The number of code for connection shall be multiplied by the number of phases included into the busbars system.

Example



Connection between shaped busbars 2500A and flat busbars 2500A

3P busbars system	6 x PFCB2025 + 3 x PFCC0029
4P busbars system	8 x PFCB2025 + 4 x PFCC0029



Flat busbars											
800A	1000A	1250A	1600A	2000A	2000A	2500A	3200A	3200A	4000A	5000A	6300A
1 Busbar for phase				2 Busbars for phase				3 Busbars for phase			
PFCB4080							PFCB4080 + PFCC0023				
PFCB4080							PFCB4080 + PFCC0023				
PFCB4080							PFCB4080 + PFCC0023				
	PFCB1016						PFCB1016 + PFCC0023				
		PFCB1016					PFCB1016 + PFCC0023				
			PFCB2025				PFCB2025 + PFCC0023				
				2x PFCB2025 + PFCC0023							
				2x PFCB2025 + PFCC0023							

Examples of use



Flat busbars 2 for phase
Shaped busbar \leq 2000A
PFCB4080 or PFCB1016 or
PFCB2025





Flat busbars 2 for phase
Shaped busbar \geq 2000A
2 x PFCB2025 + PFCC0023







Flat busbars 3 for phase
Shaped busbar \leq 1600A
PFCB4080 or PFCB1016 or
PFCB2025 + PFCC0023



Flat busbars 3 for phase
Shaped busbar \geq 2000A
2 x PFCB2025 + PFCC0023



Examples of busbars junction







Main distribution systems

Selection guides

Flexible busbars up to 1250A

In (A)	Code	No. busbar/ phase	Capacity (A)			Dimensions			
			IP31	IP41	IP65	WxW (mm)	Section dimensions (mm ²)	Lenght (mm)	Weight (kg)
160	PBFC0160	1			160	15.5x3		46.5	2000
250	BF1602	1	395	323	250	20x3		60	2000
400	BF2502	1	498	460	400	20x5		100	2000
500	BF4002	1	660	620	500	24x6		144	2000
630	BF4012	1	758	702	630	32x5		160	2000
1000	BF6302	1	1203	1140	1000	40x8		320	2000
1250	BF8002	1	1515	1390	1250	50x10		500	2000

Flat drilled and threaded busbars for earthing connection

Cross-section	Code	Threading	Pitch (mm)	WxW (mm)	Lenght (mm)	AxB (mm)
	EV1119	6 MA	20	20x5	2000	
	EV1120	6 MA	20	25x5	2000	
	EV1121	6MA	25	50x5	2000	
	EV1122	6MA				30x30
	EV1123	8MA				30x30
	EV1124	6MA				40x50
	EV1125	8MA				40x50

Modular dividers

Single-pole		Three-poles					
Code	1SNL317510R0000	1SNL312510R0000 ⁽¹⁾	1SNL316010R0000 ⁽²⁾	1SNL325010R0000	1SNL340010R0000	1SNL312530R0000	1SNL317531R0000
In	IEC (A)	125	125	160	250	400	125
	UL (A)	115	115	160	230	310	115
Icw	(kA)	4.4	4.2	1.1	21	21	4.4
Version	pole	1	1	1	1	1	3
Installation	DIN35/plate	DIN35/plate	DIN35/plate	DIN35/plate	DIN35/plate	DIN35/plate	DIN35/plate
power supply	min.	10	6	10	35	95	10
Ø cable (mm ²)	max	35	35	70	120	185	35
No. outgoing feeder	1,5÷10				4	4	
Ø cable (mm ²)	2,5÷16	10	6	6	5	5	6
	2,5÷25				2	2	
Dimensions HxWxD	(mm)	71x45x42,5	74x27x47	92x35x49	95,5x45x49	95,5x45x49	71,5x80x42,5
No. DIN modules		2,5	1,5	2	3	3	4,5
Rated service voltage	(V)	1000 Vac 1500 Vdc	1000 Vac 1500 Vdc	1000 Vac 1500 Vdc	1000 Vac 1500 Vdc	1000 Vac 1500 Vdc	1000 Vac 1500 Vdc
Degree of protection	IP	20	20	20	20	20	20
Mark							
Three-poles							
Code	AD1004	AD1028	AD1029	AD1027	AD1034	AD1053	
In	(A)	125	125	125	160	250	250
Icw	(kA)	10	4.2	4.2	6.2	15	15
Ipk	(kA)	24	25	25	20	30	30
Version	poli	4.2	4	4	4	30	30
Installation	DIN35/plate	DIN35/plate	DIN35/plate	DIN35	4		4
power supply	Ø cable (mm ²)	min.	6	6	6	with AD1038 brackets	with AD1038 brackets
		max	35	25 with cable terminal	25 with cable terminal		
No. outgoing feeder	Ø cable (mm ²)	1/6 5/phase			No. 22 holes M5 with 17,5mm pitch per phase (threaded busb. 20x5mm)	No. 32 holes M5 with 17,5mm pitch per phase (threaded busb. 20x5mm)	
		1.5/6 4/neut-					
		ral					
		1.5/10 2/pha-					
		se	7	9			
		6/neut-					
		ral					
		1.5/16		2			
		2.5/16			8		
		6/25	2	2	3		
Dimensions HxWxD	(mm)	74,5x98x45	93x89x48	96x126x48	90x160,5x50	150x600x70	150x800x70
No. DIN modules		5,5	5	7	9	24	36
Rated service voltage	(V)	1000 Vac 1500 Vdc	440	440	440	500	500
Degree of protection	IP	20	20	20	20		
Mark	UL	UL	UL	UL	UL	UL	UL

⁽¹⁾ Possibility of putting in parallel with AD1083 connections.

(2) Possibility of putting in parallel with comb type connection (not supplied).

Assembly accessories

Description	Type	Order code	Pkg/ No. pcs
No. 2 fixing brackets for AD1034-AD1053	PBRF3453	1STQ0091840000	1/2

Main distribution systems

Guide to the order codes

The new code is formed by 4 letters standing for English terms and 4 numbers, without spaces in between.

RANGE IDENTIFIER

The first letter of all the codes of the new main distribution switchboard "P" stands for "power". Thus the new product is clearly identified by the same initial used for all new components of ABB's System pro E power

TYPE OF PRODUCT AND CHARACTERISTICS

The second letter in the code indicates the type of product or component of the switchboard. The third and fourth letters describe the characteristics or material in more detail.

C = Crosspieces

B = Busbar holder, Busbar, Brackets

T = Tie rods

R = Crosspieces, Tie rods

H = Busbar holder

F = Flat

S = Shaped

B = Busbar, Bottom

M = Metal

S = Stainless steel

B = Linear

S = Scaled

N = Nylon

C = Copper


V = Vertical

H = Horizontal

T = Top


MEASUREMENTS

The last 4 numbers usually refer to a measurement of the component or several dimensions pertaining to the code.



Main distribution systems


Order codes



Crosspieces – Galvanized sheet metal


Crosspieces in 20/10 thick hot-dip galvanized sheet metal, for < than 4000A current values. They are fixed directly inside the cubicle using a purpose-made bracket to form busbar holders or as universal crosspieces. Equipped with 12.5mm pitch rectangular holes, they are able to house insulating supports for thermoplastic busbar holders with snap-fit mechanism.

Description	Dimensions (mm)			Pkg/ No. pcs
	D	W	H	
Depth galvanized sheet metal crosspieces for structures without intermediate upright				
No.2 crosspieces	200			PCRM0188 1STQ007375A0000 1/2
No.2 crosspieces	300			PCRM0288 1STQ007376A0000 1/2
No.2 crosspieces	500			PCRM0488 1STQ007378A0000 1/2
No.2 crosspieces	700			PCRM0688 1STQ007380A0000 1/2
No.2 crosspieces	900			PCRM0888 1STQ007382A0000 1/2
Depth galvanized sheet metal crosspieces for structures with intermediate upright or PCKI.... crosspieces				
No.2 crosspieces	500			PCRM0238 1STQ007384A0000 1/2
No.2 crosspieces	700			PCRM0438 1STQ007386A0000 1/2
No.2 crosspieces	900			PCRM0638 1STQ007388A0000 1/2
Width galvanized sheet metal crosspieces for structures with or without intermediate upright				
No.2 crosspieces	300			PCRM0288 1STQ007376A0000 1/2
No.2 crosspieces	400			PCRM0388 1STQ007377A0000 1/2
No.2 crosspieces	600			PCRM0588 1STQ007379A0000 1/2
No.2 crosspieces	800			PCRM0788 1STQ007381A0000 1/2
No.2 crosspieces	1000			PCRM0988 1STQ007383A0000 1/2
No.2 crosspieces	1250			PCRM1238 1STQ007390A0000 1/2
Universal crosspieces				
No.2 crosspieces L=2013mm				PCRM2013 1STQ007391A0000 1/2
Closing galvanized sheet metal crosspieces with rear intermeiate upright				
No.2 crosspieces	600			PCRM0338 1STQ007385A0000 1/2
No.2 crosspieces	800			PCRM0538 1STQ007387A0000 1/2
No.2 crosspieces	1000			PCRM0738 1STQ007389A0000 1/2
Crosspieces total height				
No.2 galvanized sheet metal crosspieces for total height of enclosures	1800	PCRM1788	1STQ002007B0000	1/2
No.2 galvanized sheet metal crosspieces for total height of enclosures	2000	PCRM1988	1STQ002006B0000	1/2



Main distribution system


Order codes



Crosspieces – AISI 304 stainless steel

Crosspieces in 25/10 thick AISI 304 stainless steel for \geq than 4000A current values. They are fixed directly inside the cubicle using a purpose-made bracket to form busbar holders or as universal crosspieces. Equipped with 12.5mm pitch rectangular holes, they are able to house insulating supports for thermoplastic busbar holders with snap-fit mechanism. Since the components are modular, the center distance between the phases can be increased by spacing the insulating supports at a 12.5mm pitch.

Description	Dimensions (mm)				Pkg/ No. pcs
	W	H	Type	Order code	
Depth stainless steel crosspieces for structures without intermediate upright					
No. 2 crosspieces	900		PCRS0888	1STQ007395A0000	1/2
Depth stainless steel crosspieces for structures with intermediate upright or PCKI.... crosspieces					
No. 2 crosspieces	700		PCRS0438	1STQ007398A0000	1/2
No. 2 crosspieces	900		PCRS0638	1STQ007399A0000	1/2
Width stainless steel crosspieces for structures with or without intermediate upright					
No. 2 crosspieces	400		PCRS0388	1STQ007392A0000	1/2
No. 2 crosspieces	600		PCRS0588	1STQ007393A0000	1/2
No. 2 crosspieces	800		PCRS0788	1STQ007394A0000	1/2
No. 2 crosspieces	1000		PCRS0988	1STQ007396A0000	1/2
No. 2 crosspieces	1250		PCRS1238	1STQ007400A0000	1/2
Closing stainless steel crosspieces					
No. 2 crosspieces			PCRS0338	1STQ007397A0000	1/2
No. 2 crosspieces			PCRS0438	1STQ007398A0000	1/2
1/2 Universal crosspieces					
No. 2 crosspieces L=2013mm			PCRS2013	1STQ001335B0000	1/2




Flat copper busbars

Flat busbars Length =1750mm.

Description	WxW (mm)	No. row drillings	\varnothing drilling (mm)	Type	Order code	Pkg/ No. pcs
Flat copper busbar	20x5	1	6.5	PBFC2005	1STQ007401A0000	1/1
Flat copper busbar	25x5	1	6.5	PBFC2505	1STQ007402A0000	1/1
Flat copper busbar	32x5	1	6.5	PBFC3205	1STQ007403A0000	1/1
Flat copper busbar	40x5	1	6.5	PBFC4005	1STQ007404A0000	1/1
Flat copper busbar	50x5	2	10.5	PBFC5005	1STQ007405A0000	1/1
Flat copper busbar	63x5	2	10.5	PBFC6305	1STQ007406A0000	1/1
Flat copper busbar	80x5	2	10.5	PBFC8005	1STQ007407A0000	1/1
Flat copper busbar	100x5	2	10.5	PBFC1005	1STQ007408A0000	1/1
Flat copper busbar	30x10	1	10.5	PBFC3010	1STQ007409A0000	1/1
Flat copper busbar	40x10	-	-	PBFC4010	1STQ007410A0000	1/1
Flat copper busbar	50x10	-	-	PBFC5010	1STQ007411A0000	1/1
Flat copper busbar	60x10	-	-	PBFC6010	1STQ007412A0000	1/1
Flat copper busbar	80x10	-	-	PBFC8010	1STQ007413A0000	1/1
Flat copper busbar	100x10	-	-	PBFC1001	1STQ007414A0000	1/1
Flat copper busbar	120x10	-	-	PBFC1201	1STQ007415A0000	1/1
Flat copper busbar	160x10	-	-	PBFC1601	1STQ007416A0000	1/1
Flat copper busbar	200x10	-	-	PBFC2001	1STQ007417A0000	1/1

Main distribution system


Order codes



Flat busbars in Cuponal

Flat busbars in Cuponal (co-extruded copper-clad aluminium busbars) for In up to 3200A.

Description	WxW (mm)	Length (mm)	Type	Order code	Pkg/ No. pcs
Flat busbars in Cuponal	20x5	1750	PBFA2005	1STQ009187A0000	1/1
Flat busbars in Cuponal	25x5	1750	PBFA2505	1STQ009188A0000	1/1
Flat busbars in Cuponal	30x5	1750	PBFA3005	1STQ009189A0000	1/1
Flat busbars in Cuponal	40x5	1750	PBFA4005	1STQ009190A0000	1/1
Flat busbars in Cuponal	50x5	1750	PBFA5005	1STQ009191A0000	1/1
Flat busbars in Cuponal	60x5	1750	PBFA6005	1STQ009192A0000	1/1
Flat busbars in Cuponal	80x5	1750	PBFA8005	1STQ009193A0000	1/1
Flat busbars in Cuponal	40x10	1750	PBFA4010	1STQ009194A0000	1/1
Flat busbars in Cuponal	50x10	1750	PBFA5010	1STQ009195A0000	1/1
Flat busbars in Cuponal	75x10	1750	PBFA7510	1STQ009196A0000	1/1
Flat busbars in Cuponal	80x10	1750	PBFA8010	1STQ009197A0000	1/1
Flat busbars in Cuponal	100x10	1750	PBFA1001	1STQ009198A0000	1/1
Flat busbars in Cuponal	120x10	1750	PBFA1201	1STQ009199A0000	1/1







Shaped profile copper busbar

Shaped profile distribution busbars L=1750mm.

Description	WxW (mm)	In (A)	Length (mm)	Type	Order code	Pkg/ No. pcs
Shaped copper busbar	30x10	165	1750	PBSC0400	1STQ007418A0000	1/1
Shaped copper busbar	35x10	204	1750	PBSC0630	1STQ007419A0000	1/1
Shaped copper busbar	45x10	324	1750	PBSC0800	1STQ007420A0000	1/1
Shaped copper busbar	67x10	454	1750	PBSC1000	1STQ007421A0000	1/1
Shaped copper busbar	70x10	516	1750	PBSC1250	1STQ007422A0000	1/1
Shaped copper busbar	95x10	758	1750	PBSC1600	1STQ007423A0000	1/1
Shaped copper busbar	105x15	995	1750	PBSC2000	1STQ007424A0000	1/1
Shaped copper busbar	105x15	1255	1750	PBSC2500	1STQ007425A0000	1/1

Main distribution system

Order codes



Connections D=300mm for not accessorized fixed breakers (front terminals)

LINEAR BUSBAR HOLDER, SHAPED BUSBARS 1600A IN CABLE CONTAINER

For horizontal fixed breakers 3 P is necessary to use the relating 3/4 P mounting kit in order to assemble the connections. The busbar system must be build up with insulators W=50mm (PBHB1125). The busbars must be mounted into the most rear and farther position from the circuit breaker with the neutral in the first position towards the front. Use brackets PBBU008 for fixing the busbar system (see picture 2). The code includes an insulator mounted on the plate (see picture 1).


Circuit breakers	No. poles	In (A)	Structure width (mm)		Type	Order code	Pkg/ No. pcs
			External cable container W=300mm	Internal cable container W=400mm H			
Horizontal installation							
XT1	3P	160A	400	800	PBX1631	1STQ009229A0000	1/1
XT1	3P	160A	600	1000	PBTX1631	1STQ009230A0000	1/1
XT1	4P	160A	400	800	PDPX1631	1STQ009231A0000	1/1
XT1	4P	160A	600	1000	PDTX1631	1STQ009232A0000	1/1
XT2	3P	160A	400	800	PBX2631	1STQ009233A0000	1/1
XT2	3P	160A	600	1000	PBTX2631	1STQ009234A0000	1/1
XT2	4P	160A	400	800	PDPX2631	1STQ009235A0000	1/1
XT2	4P	160A	600	1000	PDTX2631	1STQ009236A0000	1/1
XT3	3P	250A	400	800	PBX3631	1STQ009237A0000	1/1
XT3	3P	250A	600	1000	PBTX3631	1STQ009238A0000	1/1
XT3	4P	250A	400	800	PDPX3631	1STQ009239A0000	1/1
XT3	4P	250A	600	1000	PDTX3631	1STQ009240A0000	1/1
XT4	3P	250A	400	800	PBX4631	1STQ009241A0000	1/1
XT4	3P	250A	600	1000	PBTX4631	1STQ009242A0000	1/1
XT4	4P	250A	400	800	PDPX4631	1STQ009243A0000	1/1
XT4	4P	250A	600	1000	PDTX4631	1STQ009244A0000	1/1
T4	3P	320A	400	800	PBPT4631	1STQ009245A0000	1/1
T4	3P	320A	600	1000	PBTT4631	1STQ009246A0000	1/1
T4	4P	320A	400	800	PDPT4631	1STQ009247A0000	1/1
T4	4P	320A	600	1000	PDTT4631	1STQ009248A0000	1/1
T5	3P	400A	400	800	PBPT5631	1STQ009249A0000	1/1
T5	3P	400A	600	1000	PBTT5631	1STQ009250A0000	1/1
T5	4P	400A	400	800	PDPT5631	1STQ009251A0000	1/1
T5	4P	400A	600	1000	PDTT5631	1STQ009252A0000	1/1
T6	3P	800A	600	1000	PBTT6631	1STQ009253A0000	1/1
T6	4P	800A	600	1000	PDTT6631	1STQ009254A0000	1/1
T7	3P	1600A	600	1000	PBTT7631	1STQ009255A0000	1/1
T7	4P	1600A	600	1000	PDTT7631	1STQ009256A0000	1/1
E1.2	3P	1600A	600	1000	PBTT7631	1STQ009255A0000	1/1
E1.2	4P	1600A	600	1000	PDTT7631	1STQ009256A0000	1/1
Vertical installation							
T6 ⁽¹⁾	3P	800A	600	1000	PCTT6631	1STQ009259A0000	1/1
T6 ⁽¹⁾	4P	800A	600	1000	PFTT6631	1STQ009260A0000	1/1
T7 ⁽²⁾	3P	1600A	600	1000	PCTT7631	1STQ009261A0000	1/1
T7 ⁽²⁾	4P	1600A	600	1000	PFTT7631	1STQ009262A0000	1/1
E1.2 ⁽²⁾	3P	1600A	600	1000	PCTT7631	1STQ009261A0000	1/1
E1.2 ⁽²⁾	4P	1600A	600	1000	PFTT7631	1STQ009262A0000	1/1

⁽¹⁾ For vertical T6 breakers it is necessary to leave a blind cell above H=200mm.

⁽²⁾ For vertical T7 and E1.2 it is necessary to leave a blind cell above H=350mm. The connections are designed for the high side of the circuit breakers with busbars to the right.

Main distribution system

Order codes



Connections D=300mm for not accessorized fixed breakers (front terminals)

LINEAR BUSBAR HOLDER, SHAPED BUSBARS 800A IN INTERNAL CABLE CONTAINER W=200mm

For horizontal fixed breakers 3 P is necessary to use the relating 3/4 P mounting kit in order to assemble the connections. The busbar system must be build up with insulators W=50mm (PBHB1125). The busbars must be mounted into the most rear and farther position from the circuit breaker with the neutral in the first position towards the front. Use brackets PBBU008 for fixing the busbar system (see picture 2). The code includes an insulator mounted on the plate (see picture 1).

Circuit breakers	No. poles	In (A)	Structure width (mm)	Type	Order code	Pkg/ No. pcs
Horizontal installation - Shaped busbars 800A						
XT1	3P	160A	600	PBGX1738	1STQ008663A0000	1/1
XT1	3P	160A	800	PBPX1738	1STQ009265A0000	1/1
XT1	4P	160A	600	PDGX1738	1STQ008664A0000	1/1
XT1	4P	160A	800	PDPX1738	1STQ009266A0000	1/1
XT2	3P	160A	600	PBGX2738	1STQ008667A0000	1/1
XT2	3P	160A	800	PBPX2738	1STQ009267A0000	1/1
XT2	4P	160A	600	PDGX2738	1STQ008668A0000	1/1
XT2	4P	160A	800	PDPX2738	1STQ009268A0000	1/1
XT3	3P	250A	600	PBGX3738	1STQ008671A0000	1/1
XT3	3P	250A	800	PBPX3738	1STQ009269A0000	1/1
XT3	4P	250A	600	PDGX3738	1STQ008672A0000	1/1
XT3	4P	250A	800	PDPX3738	1STQ009270A0000	1/1
XT4	3P	250A	600	PBGX4738	1STQ008675A0000	1/1
XT4	3P	250A	800	PBPX4738	1STQ009271A0000	1/1
XT4	4P	250A	600	PDGX4738	1STQ008676A0000	1/1
XT4	4P	250A	800	PDPX4738	1STQ009272A0000	1/1
T4	3P	320A	600	PBGT4738	1STQ008679A0000	1/1
T4	3P	320A	800	PBPT4738	1STQ009273A0000	1/1
T4	4P	320A	600	PDGT4738	1STQ008680A0000	1/1
T4	4P	320A	800	PDPT4738	1STQ009274A0000	1/1
T5	3P	400A	600	PBGT5738	1STQ008683A0000	1/1
T5	3P	400A	800	PBPT5738	1STQ009275A0000	1/1
T5	4P	400A	600	PDGT5738	1STQ008684A0000	1/1
T5	4P	400A	800	PDPT5738	1STQ009276A0000	1/1
T6	3P	800A	800	PBPT6738	1STQ009277A0000	1/1
T6	4P	800A	800	PDPT6738	1STQ009278A0000	1/1
Vertical installation - Shaped busbars 800A						
T6 ⁽¹⁾	3P	800A	800	PCPT6738	1STQ009279A0000	1/1
T6 ⁽¹⁾	4P	800A	800	PFPT6738	1STQ009280A0000	1/1


⁽¹⁾ For vertical T6 breakers it is necessary to leave a blind cell above H=200mm.

Insulator for connections


Description	Type	Order code	Pkg/ No. pcs
Horizontal insulator for XT1-XT2-XT3-XT4-T4	PITH1234	1STQ001474B0000	1/1
Horizontal insulator for T5	PITH5000	1STQ001475B0000	1/1
Horizontal insulator for T6	PITH6000	1STQ001476B0000	1/1
Vertical insulator for T6	PITV6000	1STQ001477B0000	1/1
Horizontal/Vertical insulator for T7-E1.2	PITE7120	1STQ001478B0000	1/1

Main distribution system


Order codes



PBHB1125 PBHB2145



PBHB3121



PBHS1125

Insulating supports for busbars

Insulating supports for busbars in polyamide 6.6 with 30% fiberglass, equipped with shaped grooves for housing busbars and pins for fixing to the crosspieces. Able to house both flat and shaped profile busbars.

Description	Dimensions W (mm)	Type	Order code	Pkg/ No. pcs
No.24 insulating supports for busbars	50	PBHB1125	1STQ007426A0000	1/24
No.24 insulating supports for busbars	75	PBHB2145	1STQ007427A0000	1/24
No.24 insulating supports for busbars	100	PBHB3121	1STQ007428A0000	1/24

Scaled busbar holder


Scaled busbar holder for flat-shaped busbars complete with tie rods.

Description	Type	Order code	Pkg/ No. pcs
Scaled busbar holder	PBHS1125	1STQ007429A0000	1/1
No.24 insulating supports for busbars	PBHB1125*	1STQ007426A0000	1/24

For 4 poles it is needed n. 8 insulators for each scaled busbar holder. For 3 poles it is needed n. 6 insulators for each scaled busbar holder.
PBHB1125 contains n. 24 insulators.

* For structures with internal cable container W=200mm use bars with maximum section 50x10mm


PBBU0008



Brackets for fixing vertical/horizontal busbars holder crosspieces

Description	Type	Order code	Pkg/ No. pcs
No. 8 brackets for crosspieces	PBBU0008	1STQ001588B0000	1/8

PBCB0002




Brackets for fixing horizontal top/bottom busbars in corner structure

Description	Type	Order code	Pkg/ No. pcs
No. 2 busbars backing brackets for corner structure	PBCB0002	1STQ009186A0000	1/2

Nylon tie rods

Nylon tie rods (thermoplastic material for In <4000A current values).



Description	Type	Order code	Pkg/ No. pcs
No.10 nylon tie rods L=195mm <4000A	PTRN1951	1STQ007433A0000	1/10




Tie rods in AISI 304 stainless steel

Tie rods in AISI 304 stainless steel (for In ≥4000A current values).

Description	Type	Order code	Pkg/ No. pcs
No. 10 Tie rods in AISI 304 stainless steel W=120mm	PTRS1201	1STQ007434A0000	1/10
No. 10 Tie rods in AISI 304 stainless steel W=160mm	PTRS1601	1STQ007435A0000	1/10
No. 10 Tie rods in AISI 304 stainless steel W=200mm	PTRS2001	1STQ007436A0000	1/10



Main distribution system

Order codes





Brackets for earth and neutral fixing

Description	Type	Order code	Pkg/ No. pcs
No. 2 brackets for earth fixing	PBRP0002	1STQ001554B0000	1/2
No. 2 brackets for neutral fixing	PBRN0002	1STQ001555B0000	1/2



Crosspiece fixing brackets - vertical/horizontal



Description	Type	Order code	Pkg/ No. pcs
No. 8 brackets for crosspieces	PBBV0008	1STQ007430A0000	1/8
No. 8 brackets for crosspieces	PBBT0008	1STQ007432A0000	1/8



Crosspiece for horizontal busbar assembly under top or on bottom of structure

For assembly in D>300mm structures with internal cable compartment, order PCCM.... cable compartment depth crosspieces as well.

Description	Dimensions W (mm)	Type	Order code	Pkg/ No. pcs
Intermediate crosspiece for busbars under top/on bottom	300	PCKI0300	1STQ008099A0000	1/1
Intermediate crosspiece for busbars under top/on bottom	400	PCKI0400	1STQ008100A0000	1/1
Intermediate crosspiece for busbars under top/on bottom	600	PCKI0600	1STQ008101A0000	1/1
Intermediate crosspiece for busbars under top/on bottom	800	PCKI0800	1STQ008102A0000	1/1
Intermediate crosspiece for busbars under top/on bottom	1000	PCKI1000	1STQ008103A0000	1/1
Intermediate crosspiece for busbars under top/on bottom	1250	PCKI1250	1STQ008104A0000	1/1



Compensators and connections for flat and shaped busbar

Description	Type	Order code	Pkg/ No. pcs
Connections between shaped busbar/shaped busbar or shaped busbar/flat busbar for 400A, 630A, 800A	PFBCB4080	1STQ009224A0000	1/1
Connections between shaped busbar/shaped busbar or shaped busbar/flat busbar for 1000A, 1250A, 1600A	PFBCB1016	1STQ009225A0000	1/1
Connections between shaped busbar/shaped busbar or shaped busbar/flat busbar for 2000A, 2500A	PFBCB2025	1STQ009226A0000	1/1
Compensator for configurations composed of no. of busbar per phase>1	PFCC0023	1STQ009227A0000	1/1

Main distribution system

Order codes

Unifix H system

Technical characteristics		Unifix H	Unifix L
Nominal operating voltage (U_n)		690V AC/DC	500V AC/DC
Rated insulation voltage (U_i)		1000V AC/DC	500V AC/DC
Rated pulse voltage (U_{imp})		8kV	6kV
Rated frequency		50/60Hz	50/60Hz
Nominal current (I_n)	central power supply	400A	100A
	side power supply	320A	80A
Rated short-time withstand current (I_{cw})		25kA	
Rated peak withstand current (I_{pk})		52,5kA-400V	
Maximum size of installable breaker		250A	100A
Rated conditional short-circuit Tmax T1 current	Tmax T2 N, S ⁽¹⁾	36kA-400V	
	Tmax T3	50kA-400V	
	Tmax XT1	50kA-400V	
	Tmax XT3	50kA-400V	
	S200	6kA-400V	6kA-400V
	S200M	10kA-400V	10kA-400V
	S200P	25kA-400V	25kA-400V
	S800	25kA-400V	
Degree of protection		IP20 with accessory	IP20
Characteristics of the insulating material		Self-extinguishing thermoplastic V1 (UL94)	Self-extinguishing thermoplastic V1 (UL94)
Characteristics of conductive material		Electrolytic copper	Electrolytic copper
Width (no. of modules/mm)	24/600	12/400	
	36/800	24/600	
		36/800	

Unifix system installation

Frame for Tmax T e Tmax XT	300x600mm (hxL)	ED2183
	300x800mm (hxL)	ED2191
Fixing supports H=300mm		AD1061
Fixing crosspiece for DIRECT CONNECTION TO busbars with shaped section with PB0803	L=600mm	TV6202 ⁽²⁾
		TV6203
	L=800mm	TV8203
bars 2P	12 mod.	ED2993
	18 mod.	ED3009
	24 mod.	ED3017
	36 mod.	ED3025
bars 4P	12 mod.	ED2944
	18 mod.	ED2951
	24 mod.	ED2969
	36 mod.	ED2977
Fixing support	12 mod.	GD4002
	24 mod.	GD6002
	36 mod.	GD8002

Main distribution system


Order codes

Unifix H - Connections selection according to the breaker

Breakers serie	Unifix H	Unifix L
SN201	(supply from above)	
DS941	ED2654 L1/N 40A	ED3272 L1/N 40A
	ED2662 L2/N 40A	ED3280 L2/N 40A
	ED2670 L3/N 40A	ED3298 L3/N 40A
S200 - DS200	(supply from above)	(supply from below)
F200 up to 63A (Unifix L)	ED2531 L1 63A ED2549 L2 63A ED2556 L3 63A ED2564 N 63A	ED2572 L1 63A ED2590 L2 63A ED2598 L3 63A ED2606 N 63A
	ED2845 base module false pole	ED3033 L1 100A ED3041 L2 100A ED3058 L3 100A ED3066 N 100A
S800	(aliment. alto) ED2557 L1 ≤32A ED2558 L2 ≤32A ED2559 L3 ≤32A ED2560 N ≤32A ED2551 L1 125A ED2552 L2 125A ED2553 L3 125A ED2554 N 125A	
	ED2550 base module false pole	
S280 (80-100A)	(supply from above)	
E200 up to 100A - RS370 - F200 80/100A (Unifix H)	ED2720 L1 100A ED2738 L2 100A ED2746 L3 100A ED2753 N 100A	ED3132 cables supply L1/L2/L3/N - 350mm ED0026 cables supply L1/L2/L3/N - 1500mm ED0025 cables supply L1/L2/L3/N - 2500mm
MDRC - Various equipment	(supply from above)	(supply from below)
	ED2894 L1/N 16A ED2902 L1/L2 16A	ED2910 L1/N 16A ED2928 L1/L2 16A
		ED3108 No.2 cables supply L1/N 16A ED3116 No.3 cables supply L1/L2/L3 16A ED3124 No.4 cables supply L1/L2/L3/N 16A
		ED3355 No.2 cables supply L1/N 40A ED3363 No.3 cables supply L1/L2/L3 40A ED3371 No.4 cables supply L1/L2/L3/N 71A
Tmax T1	Breaker	(aliment. supply from above/ below)
Tmax XT1		ED2217 L1 Above/L2 Below ED2225 L2 Above/L1 Below ED2233 L3 Above/N Below ED2241 N Above/L3 Below
	Differential	ED2373 Module false pole
	Solenoid control	ED2381 Module false pole
Tmax T2	Interruttore	(aliment. supply from above/ below)
		ED2258 L1 Above/L2 Below ED2266 L2 Above/L1 Below ED2274 L3 Above/N Below ED2282 N Above/L3 Below
	Differenziale	ED2373 Module false pole
	Comando solenoide	ED2399 Module false pole
Tmax T3	Breaker	(supply from above)
Tmax XT3		(supply from below)
		ED2290 L1 ED2308 L2 ED2316 L3 ED2324 N
	Differential	ED2373 Module false pole

Main distribution system

Order codes



Unifix H


Description	Dimensions W (mm)	Type	Order code	Pkg/ No. pcs
No.2 brackets for fixing Unifix to structure		PBUF0002	1STQ008117A0000	1/2
Frames for Tmax and modular circuit-breakers - System pro M				
Frames with 24 busbars DIN modules	600	ED2183	1STQ008228A0000	1/1
Frames with 36 busbars DIN modules	800	ED2191	1STQ008229A0000	1/1
Feeder modules				
4P 400A feeder module (for ED2183-ED2191)		ED2209	1STQ008230A0000	1/1
Basic module In 16A				
Basic module for auxiliaries DIN L1-N high 16A		ED2894	1STQ008255A0000	1/1
Basic module for auxiliaries DIN L1-L2 high 16A		ED2902	1STQ008256A0000	1/1
Basic module for auxiliaries DIN L1-N low 16A *		ED2910	1STQ008257A0000	1/1
Basic module for auxiliaries DIN L1-L2 low 16A *		ED2928	1STQ008258A0000	1/1
Basic module In 40A				
Basic module L1/Neutral high 40A		ED2654	1STQ008248A0000	1/1
Basic module L2/Neutral high 40A		ED2662	1STQ008249A0000	1/1
Basic module L3/Neutral high 40A		ED2670	1STQ008250A0000	1/1
Basic module In 63A				
Basic module L1 high 63A		ED2531	1STQ008231A0000	1/1
Basic module L2 high 63A		ED2549	1STQ008232A0000	1/1
Basic module L3 high 63A		ED2556	1STQ008238A0000	1/1
Basic module Neutral high 63A		ED2564	1STQ008243A0000	1/1
Basic module L1 low 63A *		ED2572	1STQ008244A0000	1/1
Basic module L2 low 63A *		ED2590	1STQ008245A0000	1/1
Basic module L3 low 63A *		ED2598	1STQ008246A0000	1/1
Basic module Neutral low 63A *		ED2606	1STQ008247A0000	1/1
Basic module In 100A				
Basic module with cable L1 high 100A		ED2720	1STQ008251A0000	1/1
Basic module with cable L2 high 100A		ED2738	1STQ008252A0000	1/1
Basic module with cable L3 high 100A		ED2746	1STQ008253A0000	1/1
Basic module with Neutral cable high 100A		ED2753	1STQ008254A0000	1/1
Basic modules ≤ In 40A S800				
Basic module L1 high ≤40A		ED2557	1STQ008239A0000	1/1
Basic module L2 high ≤40A		ED2558	1STQ008240A0000	1/1
Basic module L3 high ≤40A		ED2559	1STQ008241A0000	1/1
Basic module Neutral high ≤40A		ED2560	1STQ008242A0000	1/1
Basic modules ≤ In 125A S800				
Basic module L1 high 125A		ED2551	1STQ008234A0000	1/1
Basic module L2 high 125A		ED2552	1STQ008235A0000	1/1
Basic module L3 high 125A		ED2553	1STQ008236A0000	1/1
Basic module Neutral high 125A		ED2554	1STQ008237A0000	1/1
Basic module pole blank L=27mm		ED2550	1STQ008233A0000	1/1

*While supplies last


Main distribution system

Order codes


ED2217-ED2225
ED2233-ED2241
ED2258-ED2266
ED2274-ED2282
ED2332-ED2340
ED2357-ED2365




ED0001
ED0002
ED0003




ED2290-ED2308
ED2316-ED2324



ED2381
ED2399



PPMU3060
PPMU3080



Unifix H

Description	Type	Order code	Pkg/ No. pcs
Basic modules ≤ In 160A Tmax XT1 (front terminals FCCuAl)			
Basic module L1 high L2 low	ED2217	1STQ008263A0000	1/1
Basic module L2 high L1 low	ED2225	1STQ008264A0000	1/1
Basic module L3 high Neutral low	ED2233	1STQ008265A0000	1/1
Basic module Neutral high L3 low	ED2241	1STQ008266A0000	1/1
Basic module pole blank for RC221 residual current release	ED2373	1STQ008279A0000	1/1
Basic module pole blank for solenoid operating mechanism	ED2381	1STQ008280A0000	1/1
Basic modules ≤ I 160A Tmax T2			
Basic module L1 high L2 low *	ED2258	1STQ008267A0000	1/1
Basic module L2 high L1 low *	ED2266	1STQ008268A0000	1/1
Basic module L3 high N low *	ED2274	1STQ008269A0000	1/1
Basic module N high L3 low *	ED2282	1STQ008270A0000	1/1
Basic module pole blank for RC221 residual current release	ED2373	1STQ008279A0000	1/1
Basic module pole blank for solenoid operating mechanism *	ED2399	1STQ008281A0000	1/1
Basic modules ≤ I 250A Tmax XT3			
Basic module L1 high	ED2290	1STQ008271A0000	1/1
Basic module L2 high	ED2308	1STQ008272A0000	1/1
Basic module L3 high	ED2316	1STQ008273A0000	1/1
Basic module N high	ED2324	1STQ008274A0000	1/1
Basic module L1 low *	ED2332	1STQ008275A0000	1/1
Basic module L2 low *	ED2340	1STQ008276A0000	1/1
Basic module L3 low *	ED2357	1STQ008277A0000	1/1
Basic module N low *	ED2365	1STQ008278A0000	1/1
Basic module pole blank for RC221 residual current release	ED2373	1STQ008279A0000	1/1
Accessories			
Basic module pole blank for DDA W=17.5mm	ED2845	1STQ008283A0000	1/1
Basic module pole blank for MDRC modular units	ED2852	1STQ008284A0000	1/1
2 IP20 covers (for ED2183-ED2191) W=173mm (10 DIN mod.)	ED2407	1STQ008282A0000	1/2
6 duct supports 40x60mm (only with modular apparatus)	ED2936	1STQ008285A0000	1/6
Modular front panel 300x600mm (HxW)	PPMU3060	1STQ008299A0000	1/1
Modular front panel 300x800mm (HxW)	PPMU3080	1STQ008300A0000	1/1
Spare parts			
10 terminal covers for T1	ED0001	1STQ008259A0000	1/10
10 terminal covers for T2 *	ED0002	1STQ008260A0000	1/10
10 terminal covers for T3	ED0003	1STQ008261A0000	1/10
10 terminal covers for S200/F200	ED0004	1STQ008262A0000	1/10

*While supplies last

Main distribution system

Order codes




Unifix L

Description	Dimensions W (mm)	Type	Order code	Pkg/ No. pcs
2 brackets for fixing Unifix to structure		PBUF0002	1STQ008117A0000	1/2
2-pole busbars				
100A 2P busbar 8 modules *	200	ED2985	1STQ008313A0000	1/1
100A 2P busbar 12 modules *	400	ED2993	1STQ008314A0000	1/1
100A 2P busbar 18 modules *	450	ED3009	1STQ008315A0000	1/1
100A 2P busbar 24 modules *	600	ED3017	1STQ008316A0000	1/1
100A 2P busbar 36 modules *	800	ED3025	1STQ008317A0000	1/1
4-pole busbars				
100A 4P busbar 12 modules	400	ED2944	1STQ008307A0000	1/1
100A 4P busbar 18 modules	450	ED2951	1STQ008308A0000	1/1
100A 4P busbar 24 modules	600	ED2969	1STQ008311A0000	1/1
100A 4P busbar 36 modules	800	ED2977	1STQ008312A0000	1/1
Connections for various equipment				
Connection with 2 conductors L1/N 16A *		ED3108	1STQ008332A0000	1/1
Connection with 3 conductors L1/L2/L3 16A *		ED3116	1STQ008333A0000	1/6
Connection with 4 conductors L1/L2/L3/ 16A single-phase *		ED3124	1STQ008334A0000	1/1
Connection with 2 conductors L1/N 40A		ED3355	1STQ008339A0000	1/6
Connection with 3 conductors L1/L2/L3 40A		ED3363	1STQ008340A0000	1/6
Connection with 4 conductors L1/L2/L3/N 40A		ED3371	1STQ008341A0000	1/1
Connections for apparatuses				
Connections L1-N 40 A		ED3272	1STQ008336A0000	1/10
Connections L2-N 40 A		ED3280	1STQ008337A0000	1/10
Connections L3-N 40 A		ED3298	1STQ008338A0000	1/10
Connections L 1 100A		ED3033	1STQ008318A0000	1/10
Connections L 2 100A		ED3041	1STQ008319A0000	1/10
Connections L 3 100A		ED3058	1STQ008320A0000	1/10
Connections N 100A		ED3066	1STQ008321A0000	1/10
Feeder with cable 4P 100A (L=350mm)		ED3132	1STQ008335A0000	1/10
Feeder with cable 4P 100A (L=1500mm)		ED0026	1STQ008306A0000	1/10
Feeder with cable 4P 100A (L=2500mm)		ED0025	1STQ008305A0000	1/10
Feeder module with cable				
2P 100A parallel module with cable (L=600mm) *		ED3082	1STQ008322A0000	1/6
4P 100A parallel module with cable (L=400mm) *		ED3405	1STQ008342A0000	1/6
4P 100A parallel module with cable (L=600mm)		ED3090	1STQ008323A0000	1/6
4P 100A parallel module with cable (L=800mm)		ED3413	1STQ008343A0000	1/6
4P 100A parallel module with cable (L=1500mm)		ED3439	1STQ008344A0000	1/6
Feeder module without cable in 100A				
Single-pole feeder modules L 1		ED3101	1STQ008324A0000	1/10
Single-pole feeder modules L 2		ED3102	1STQ008326A0000	1/10
Single-pole feeder modules L 3		ED3103	1STQ008328A0000	1/10
Single-pole feeder modules N		ED3104	1STQ008330A0000	1/10
Accessories				
10 busbar covers (L=600mm)		ED2961	1STQ008309A0000	1/10
2 busbar covers (L=800mm)		ED2962	1STQ008310A0000	1/2

*While supplies last


Main distribution system

Order codes



Rack rails in painted Sendzimir steel wire L=3000mm

Description	Type	Order code	Pkg/ meters
H=35mm			
Basic straight rack rails 75mm	1SL9816A00	1SL9816A00	24
Basic straight rack rails 100mm	1SL9817A00	1SL9817A00	24
Basic straight rack rails 150mm	1SL9818A00	1SL9818A00	24
Basic straight rack rails 200mm	1SL9819A00	1SL9819A00	12
Basic straight rack rails 300mm	1SL9820A00	1SL9820A00	12
H=50mm			
Basic straight rack rails 75mm	1SL9836A00	1SL9836A00	24
Basic straight rack rails 100mm	1SL9037A00	1SL9037A00	24
Basic straight rack rails 150mm	1SL9838A00	1SL9838A00	24
Basic straight rack rails 200mm	1SL9839A00	1SL9839A00	12
Basic straight rack rails 300mm	1SL9840A00	1SL9840A00	12
Basic straight rack rails 400mm	1SL9841A00	1SL9841A00	6
Basic straight rack rails 500mm	1SL9842A00	1SL9842A00	6
H=75mm			
Basic straight rack rails 75mm	1SL9860A00	1SL9860A00	24
Basic straight rack rails 100mm	1SL9861A00	1SL9861A00	24
Basic straight rack rails 150mm	1SL9862A00	1SL9862A00	24
Basic straight rack rails 200mm	1SL9863A00	1SL9863A00	12
Basic straight rack rails 300mm	1SL9864A00	1SL9864A00	12
Basic straight rack rails 400mm	1SL9865A00	1SL9865A00	6
Basic straight rack rails 500mm	1SL9866A00	1SL9866A00	6




Rack rails in painted Sendzimir steel wire L=3000mm

Description	Type	Order code	Pkg/ No. pcs
L 2000mm separator profiles for rack rails H 35mm	1SL9904A00	1SL9904A00	1/20
L 2000mm separator profiles for rack rails H 50mm	06652	06652	1/20
L 2000mm separator profiles for rack rails H 75mm	07855	07855	1/20

Main distribution system


Order codes




Covers in Sendzimir L=3000mm

Description	Type	Order code	Pkg/meters
Basic straight cover 75mm	07241	07241	24
Basic straight cover 100mm	07242	07242	24
Basic straight cover 150mm	07243	07243	24
Basic straight cover 200mm	07244	07244	12
Basic straight cover 300mm	07245	07245	12
Basic straight cover 400mm	07246	07246	6
Basic straight cover 500mm	07247	07247	6

1SL9907A00-1SL9886A0
1SL9887A000



1SL9910A00+1SL9915A00



1SL9893A00




Accessories in Sendzimir

Description	Type	Order code	Pkg/No.pcs
Linear coupling	1SL9880A00	1SL9880A00	1/2
Linear snap-fit coupling for rack rails H 35mm	1SL9907A00	1SL9907A00	1/2
Linear snap-fit coupling for rack rails H 50mm	1SL9886A00	1SL9886A00	1/2
Linear snap-fit coupling for rack rails H 75mm	1SL9887A00	1SL9887A00	1/2
Bracket fixing element complete with screws	1SL9893A00	1SL9893A00	1/10
L 150mm crosspiece for rack rails B 75-100mm	1SL9910A00	1SL9910A00	1/10
L 200mm crosspiece for rack rails B 150mm	1SL9911A00	1SL9911A00	1/10
L 250mm crosspiece for rack rails B 200mm	1SL9912A00	1SL9912A00	1/10
L 350mm crosspiece for rack rails B 300mm	1SL9913A00	1SL9913A00	1/10
L 450mm crosspiece for rack rails B 400mm	1SL9914A00	1SL9914A00	1/10
L 550mm crosspiece for rack rails B 500mm	1SL9915A00	1SL9915A00	1/10




Note:

The steel wire racks are also available in the following versions: unpainted Sendzimir; electrogalvanized; hot-dip galvanized after machining.



Main distribution system

Order codes



Earthing copper busbars

Flat busbar, drilled and threaded for earthing.


Description	Type	Order code	Pkg/ No.pcs
No. 2 drilled and threaded busbars 20x5mm L=2000mm	EV1119	1STQ001014A0000	1/2
No. 2 drilled and threaded busbars 25x5mm L=2000mm	EV1120	1STQ001015A0000	1/2
No. 2 drilled and threaded busbars 50x5mm L=2000mm	EV1121	1STQ001016A0000	1/2



EV1122-EV1123
EV1124-EV1125


Insulators

Description	Type	Order code	Pkg/ No.pcs
No.50 hexagonal insulators 30x30mm M6	EV1122	1STQ001017A0000	1/50
No.50 hexagonal insulators 30x30mm M8	EV1123	1STQ001018A0000	1/50
No.25 hexagonal insulators 36x50mm M6	EV1124	1STQ001019A0000	1/25
No.25 hexagonal insulators 36x50mm M8	EV1125	1STQ001020A0000	1/25



Sliding aluminium rails for general purposes

Description	Type	Order code	Pkg/ No.pcs
No. 10 aluminium sections 30x15x1,8 - L=2000mm	EV1050	1STQ000981A0000	1/10
No. 25 fixing brackets for EV1050	EV1051	1STQ000982A0000	1/25
No. 100 M6 aluminium nuts for EV1050	EV1056	1STQ000983A0000	1/100
No. 100 M8 aluminium nuts for EV1050	EV1058	1STQ000984A0000	1/100




Brackets for anchoring cables

Adjustable cable clamping bracket. Can be mounted on sections with 10mm slot EV1050.

Description	Type	Order code	Pkg/ No.pcs
No.10 cable clamping brackets Ø9÷16mm min÷max	EV1090	1STQ000999A0000	1/10
No.10 cable clamping brackets Ø16÷30mm min÷max	EV1091	1STQ001000A0000	1/10
No.5 cable clamping brackets Ø30÷48mm min÷max	EV1092	1STQ001001A0000	1/5
No.5 cable clamping brackets Ø48÷72mm min÷max	EV1093	1STQ001002A0000	1/5

Main distribution system

Order codes



Angled supports for terminal boxes and earthing busbars


Description	Type	Order code	Pkg/ No.pcs
No.50 angled supports 1 row of terminals	EV1110	1STQ001007A0000	1/50
No.2 angled supports 1 row of terminals + earth	EV1113	1STQ003737A0000	1/2



Profiles for accessories


Universal profiles of different types for mounting any component or for cable locking.

Description	Dimensions (mm)			Pkg/ No.pcs
	L	Type	Order code	
No. 2 EN sections 5002 C30	2000	TS4011	1STQ008211A0000	1/2
No. 2 EN sections G32	2000	TS4012	1STQ008212A0000	1/2
No. 2 DIN EN sections 5022 35x7.5	2000	TS4013	1STQ008213A0000	1/2



Hammer-head screws for shaped profile busbars

Description	Type	Order code	Pkg/ No.pcs
No.12 screws M8 - L=20mm for cable terminals	AD1056	1STQ008214A0000	1/12
No.12 screws M8 - L=27mm for plates up to 10mm, complete with screw cap	AD1064	1STQ008215A0000	1/12
No.12 screws M8 - L=37mm for plates up to 20mm, complete with screw cap	AD1071	1STQ008216A0000	1/12
No.12 screws M8 - L=47mm for plates up to 30mm, complete with screw cap	AD1072	1STQ008217A0000	1/12




Couplings for shaped profile busbars

Description	Type	Order code	Pkg/ No.pcs
No.4 400A branch connectors in copper	AD1077	1STQ008218A0000	1/4

Main distribution system


Order codes



Busbar clamps

Kit for clamping flexible busbars to rigid busbars without forcing the flexible busbars.

Description	Type	Order code	Pkg/ No.pcs
2 pairs of fixing plates for busbars H=40mm	BS3250	1STQ008219A0000	1/4
2 pairs of fixing plates for busbars H=50mm	BS5050	1STQ008220A0000	1/4
2 pairs of fixing plates for busbars H=63mm	BS6350	1STQ008221A0000	1/4




Busbar clamps

Kit for clamping flexible busbars to rigid busbars without forcing the flexible busbars.

Description	WxW (mm)	Dimensions (mm)		Type	Order code	Pkg/ No.pcs
		L	In (A)			
No.2 flexible busbars (mm)	2000	160		PBFC0160	1STQ009175A0000	1/2
No.2 flexible busbars 20x3	2000	250		BF1602	1STQ008222A0000	1/2
No.2 flexible busbars 20x5	2000	400		BF2502	1STQ008223A0000	1/2
No.2 flexible busbars 24x6	2000	500		BF4002	1STQ008224A0000	1/2
No.2 flexible busbars 32x5	2000	630		BF4012 ⁽¹⁾	1STQ008225A0000	1/2
No.2 flexible busbars 40x8	2000	1000		BF6302	1STQ008226A0000	1/2
No.2 flexible busbars 50x10	2000	1250		BF8002	1STQ008227A0000	1/2

⁽¹⁾ Only for circuit-breakers with extended front connections or rear connections.



Lateral connection module for terminal ditching

Lateral drilled module 25mm pitch for fixing the crosspieces with insulating supports in width from the intermediate upright up to the rear structural upright. In order to complete the terminals ditching it is necessary to fix sideways the two connection modules included in the code. The crosspieces PCRM or PCRS is fixed using the special fixing brackets for module connection PBMC0002. The crosspiece is to be chosen and ordered separately according to the width of the structure.

Description	H (mm)	D (mm)	Type	Order code	Pkg/ No.pcs
No.2 lateral connection modules	175	500	PMCS1755	1STQ009200A0000	1/2
No.2 lateral connection modules	200	500	PMCS2050	1STQ009201A0000	1/2
No.2 lateral connection modules	225	500	PMCS2255	1STQ009202A0000	1/2
No.2 lateral connection modules	250	500	PMCS2550	1STQ009203A0000	1/2
No.2 lateral connection modules	300	500	PMCS3050	1STQ009204A0000	1/2
No.2 lateral connection modules	175	700	PMCS1757	1STQ009205A0000	1/2
No.2 lateral connection modules	200	700	PMCS2070	1STQ009206A0000	1/2
No.2 lateral connection modules	225	700	PMCS2257	1STQ009207A0000	1/2
No.2 lateral connection modules	250	700	PMCS2570	1STQ009208A0000	1/2
No.2 lateral connection modules	300	700	PMCS3070	1STQ009209A0000	1/2
No.2 lateral connection modules	175	900	PMCS1759	1STQ009210A0000	1/2
No.2 lateral connection modules	200	900	PMCS2090	1STQ009211A0000	1/2
No.2 lateral connection modules	225	900	PMCS2259	1STQ009212A0000	1/2
No.2 lateral connection modules	250	900	PMCS2590	1STQ009213A0000	1/2
No.2 lateral connection modules	300	900	PMCS3090	1STQ009214A0000	1/2
No.2 fixing brackets connection module			PBMC0002	1STQ009215A0000	1/2

Main distribution system

Order codes

Splitters

Four-poles




Mark	CE CE			
Code	AD1004	AD1028	AD1029	AD1027
In	(A) 125	125	125	160
Icw	(kA) 10	4.2	4.2	6.2
Ipk	(kA) 24	25	25	20
Version	poles 4.2	4	4	4
Installation	DIN35/plate	DIN35/plate	DIN35/plate	DIN35
Power supplye Ø cable (mm ²)	min. 6	6	6	10
	max 35	25 with cable terminal	25 with cable terminal	50
No.outgoing feeder (mm ²) Ø cable	With cable lugs 5L, 4Nx1,5-6mm ² 2L, 6Nx4-10mm ² 1L, 1Nx6-25mm ²	Rigid cable 7x1,5-10mm ² 2x6-25mm ² With cable lugs	Rigid cable 9x1,5-10mm ² 2x1,5-16mm ² 2x6-25mm ²	Rigid cable 8x2,25-25mm ² 1x10-50mm ² 3x16-35mm ²
	Without cable lugs 5L, 4Nx1,5-6mm ² 2L, 6Nx4-10mm ² 1L, 1Nx6-35mm ²	7x1,5-10mm ² 2x6-16mm ² Without cable lugs 7x2,5-16mm ² 2x6-35mm ²	With cable lugs 2x1,5-6mm ² 9x1,5-10mm ² 2x6-16mm ² Without cable lugs 11x2,5-16mm ² 2x6-35mm ²	With cable lugs 8x2,5-16mm ² 3x6-25mm ² 1x10-35mm ² 8x6-16mm ² 3x6-25mm ² 1x10-35mm ²
Dimensions HxWxD (mm)	74.5x98x45	93x89x48	96x126x48	90x160.5x50
No. DIN modules	5,5	5	7	9
Rated service voltage (V) Ue	1000 Vac 1500 Vdc	440	440	440
Degree of protection IP	20	20	20	20

Main distribution system

Order codes


Assembly accessories

Description	Type	Order code	Pkg/ No.pcs
Joining accessory for two AD1080	AD1083	1STQ008290A0000	1/1



Labels

Description	Type	Order code	Pkg/ No.pcs
No.490 ø12mm adhesive labels with N symbol	EV1150	1STQ001033A0000	1/490
No.490 ø12mm adhesive labels with L1 symbol	EV1151	1STQ001034A0000	1/490
No.490 ø12mm adhesive labels with L2 symbol	EV1152	1STQ001035A0000	1/490
No.490 ø12mm adhesive labels with L3 symbol	EV1153	1STQ001036A0000	1/490
No.490 ø12mm adhesive labels with T symbol	EV1154	1STQ001037A0000	1/490
No.10 triangular 125mm adhesive labels with 400V lightning flash symbol	EV1155	1STQ001038A0000	1/10
No.300 triangular 20mm adhesive labels with lightning flash symbol	EV1156	1STQ001039A0000	1/300



Chapter 5

Segregations

General information

**5-2 Segregations in accordance with
Standard IEC 61459-1-2**

5-4 Internal segregation kits

5-6 Segregation Form 2a - 3a

5-8 Segregation Form 2b -4a

5-8 Segregation Form 3b

5-10 Segregation Form 4b

5-12 Choice of segregation

5-22 Guide to the order codes

5-23 Order codes

Segregation

General information

Segregations in accordance with Standard IEC 61439-1-2

Segregation form means the type of division inside the switchboard. Segregation by means of metal or insulating barriers or partitions may be required to:

- Provide protection against direct contacts (at least IPXXB) when a de-energized part of a switchboard must be accessed while the rest of it remains energized.
- Reduce the possibility of internal arc ignition and propagation.
- Prevent solid bodies from passing between different parts of the switchboard (protection class at least IP2X).

Partition means the element that separates two compartments while the barrier protects the operator from direct contact and from the effects of the arc of a switching device in the usual direction of access.

The partition can also be a casing that is an integral part of an apparatus, e.g. a moulded-case circuit-breaker.

Internal segregation kits









The different segregation Forms, (Form 2a, 2b, 3a and 4b), that can be created in the new System pro E power main distribution switchboard are described in the following pages.

The descriptions include the following information for each segregation Form:

- the basic conditions for its creation
- the various solutions
- the reference tables for the choice of codes

Generally speaking, the basic segregation Form of the circuit-breaker kits (Form 1) passes to Form 4b by adding different accessories in sequence, depending on the case in question.

The main innovation introduced by the new System pro E power segregation system concerns the kits for circuit-breakers with front (with high terminals*) and rear terminals for Form 2b.

Symbols	Form 1	Form 2	Form 3	Form 4
	No internal segregation	Segregation of busbars from all functional units	Segregation of busbars from all functional units. <ul style="list-style-type: none"> • Segregation of all functional units from each other • Segregation of the terminals for external conductors associated with a functional unit from the terminals of any other functional unit and from the busbars 	Segregation of busbars from all functional units. <ul style="list-style-type: none"> • Segregation of all functional units from each other • Segregation of the terminals for external conductors associated with a functional unit from the terminals of any other functional unit and from the busbars • Segregation of the external conductors from the busbars • Segregation of the external conductors associated with a functional unit from other functional units and their terminals • The external conductors do not need to be separated from each other
	Form 2a The terminals for external conductors are not separated from the busbars	Form 3a The terminals for external conductors are not separated from the busbars		Form 4a The terminals for external conductors are in the same compartment as associated functional unit
				
	Form 2b The terminals for external conductors are separated from the busbars	Form 3b The terminals for external conductors and the external conductors are separated from the busbars		Form 4b The terminals for external conductors are not in the same compartment as associated functional unit but are in individual spaces or compartments, separated, enclosed and protected
Key	a Empty enclosure b Internal segregation c Functional unit, including the terminals for the associated external conductors d Busbars, including the distribution busbars			
				

The segregation Form 2a - 3a, 3b and 4b can be reached with front terminals (with high terminal covers*) or rear terminals only for fixed circuit-breakers. With plug-in or withdrawable circuit-breakers the segregations can be built up with rear terminals. Using side by side moulded case circuit-breakers and moulded case circuit breakers with recessed mounting plate the highest segregation form reachable is Form 3a. The side by side air circuit-breakers are not segregated.**

The segregations mainly consist of horizontal or vertical shelves at the front or rear in relation to the intermediate upright, or throughout the width/depth of structures without the intermediate upright.

The intermediate upright is required for all segregation Forms differing from Form 2b, even when not needed by the circuit-breaker version.

Segregation **Forma 2a - 3a**, designed for structures with $D \geq 500\text{mm}$, is created with side closing elements for the compartment and universal horizontal shelves to install between kits with different depths ($D \geq 38\text{mm}$), and above and below the kit compositions (top and bottom). With IP3X protection degree and cable compartment internal door it is necessary to install a vertical segregation and the intermediate upright (1 pcs. for internal cable container, 2 pcs. for external cable container).

With IP65/IP4X and cable compartment internal door it is not necessary any further segregation. Blind compartments are specially created to fill the empty spaces inside the structure, while there are special closing segregations for DIN rails. The blind compartments are not suitable for fixing accessories. Install a blind bottom plate and panel if required. If the blind compartment is mounted in the first or in the last position into a column, the universal horizontal shelves cannot be mounted at the top or at the bottom.

Where the terminals are separated by the busbars, segregation **Form 2b** can be obtained by a combination of pre-cut or blind $H=800/1000\text{mm}$ side walls that cover the structure at the side along its entire height and with horizontal and vertical shelves for

busbar segregation in structures with or without intermediate upright, for external and internal cable compartments.

Some vertical walls are pre-cut so as to accommodate the busbars.

To guarantee protection class IP=20, they have TPV rubber seals that adhere perfectly to the removed parts. If the column requires the installation of intermediate uprights, the cable container shall have the intermediate upright (1 pcs. for internal cable container, 2 pcs. for external cable container). If the column does not require the installation of intermediate uprights, no intermediate uprights have to be mounted into the cable container.


Segregation **Form 3b** is obtained by segregating the busbars from all the functional units, adding dedicated accessories for the installation of horizontal or vertical circuit-breakers. The horizontal circuit-breakers are segregated by means of sliding vertical rear separators that divide the input and output terminals, while the vertical circuit-breakers have a modular horizontal separator. The busbar side is segregated by panels fixed to the sides and bottom of the structure between the uprights.

In case of segregation **Form 3b**, vertical breakers can be installed in the first available position under the top of the structure (top) or the last available position in the structure (bottom), with a maximum of two vertical breakers per column.

Segregation **Form 4b** is obtained for horizontal circuit-breakers by means of cubicles that completely isolate the circuit-breaker terminals. The rear part of the segregation is created by a Lexan panel fixed with a dedicated bshelfet and shelves, depending on the depth of the circuit-breaker. Form 4b is obtained for vertical circuit-breakers by duplicating the codes of the vertical bottom segregations and vertical side segregations used for Form 3b, closing the circuit-breaker compartment and installing an additional vertical side segregation on the output side.

In **Form 3b** and **Form 4b** the intermediate upright is always mandatory (1 pcs. for internal cable container, 2 pcs. for external cable container).


* High terminal covers are available for all Tmax T/XT fixed and Emax E1.2 fixed, except for XT1, XT3 F-RC and kit PHBX3301, PHBX3401, PHBX4301, PHBX4401, PHBT4301, PHBT4406, PHBT5306, PHBT5406 and Tmax T6/T7 withdrawable and plug-in versions. For Tmax XT1/XT2/XT3/XT4 withdrawable and plug-in versions it is necessary to order the dedicated adapter covers for terminals. For Tmax T4/T5 withdrawable and plug-in versions it is necessary to order the dedicated high terminal covers for 3 or 4 poles.
** See page 8/10.



Structure

General information

Segregation Form 2a - 3a



- ① Universal compartment side closing element
PPVS....
- ② Universal horizontal shelf
PSHS.....

Examples of busbar use in the structure


- 01 Horizontal circuit-breaker with front terminals
- 02 Vertical circuit-breaker with front terminals
- 03 Horizontal circuit-breaker with rear terminals
- 04 Vertical circuit-breaker with rear terminals
- 05 Horizontal circuit-breaker with front/rear terminals

To obtain segregation Form 2a - 3a, use universal compartment side closing elements PPVS... and universal horizontal shelves PSHS.... under the


top and on the bottom, and whenever consecutive compartments contain circuit-breakers with $D \geq 38\text{mm}$ difference in depth.

Structures with intermediate upright


— 01




— 02




— 03



— 04



— 05





High terminal covers are available for all Tmax T/XT fixed and Emax E1.2 fixed, except for XT1, XT3 F-RC and kit PHBX3301, PHBX3401, PHBX4301, PHBX4401, PHBT4301, PHBT4406, PHBT5306, PHBT5406 and Tmax T6/T7 withdrawable and plug-in versions. For Tmax XT1/XT2/XT3/XT4 withdrawable and plug-in versions it is necessary to order the dedicated adapter covers for terminals. For Tmax T4/T5 withdrawable and plug-in versions it is necessary to order the dedicated high terminal covers for 3 or 4 poles.

Structure

General information

Segregation Form 2b/4a



Examples of busbar use in the cable compartment


- 01 Horizontal circuit-breaker with front terminals rear outputs
- 02 Horizontal circuit-breaker with front terminals side outputs
- 03 Horizontal circuit-breaker with front/rear terminals
- 04 Horizontal circuit-breaker with front/rear terminals
- 05 Horizontal circuit-breaker with front terminals rear outputs
- 06 Vertical circuit-breaker with front terminals
- 07 Horizontal circuit-breaker with front terminals side outputs
- 08 Vertical circuit-breaker with rear terminals

To obtain segregation Form 2b, use dedicated horizontal shelves PTHS.... and front segregations PFVS.... for the structure, internal cable compartment and external cable compartment. The busbars are segregated with precut PTVS... or blind PTVB... side segregations for columns,


which can be full-depth for structures without intermediate uprights and divided into front and rear for structures with intermediate uprights. Terminal covers to be ordered with the circuit-breakers must be used for circuit-breakers with front terminals.

Structures with intermediate upright


— 01




— 02



— 03




— 04




Structures with intermediate upright


— 05




— 06



— 07



— 08




High terminal covers are available for all Tmax T/XT fixed and Emax E1.2 fixed, except for XT1, XT3 F-RC and kit PHBX3301, PHBX3401, PHBX4301, PHBX4401, PHBT4301, PHBT4406, PHBT5306, PHBT5406 and Tmax T6/T7 withdrawable and plug-in versions. For Tmax XT1/XT2/XT3/XT4 withdrawable and plug-in versions it is necessary to order the dedicated adapter covers for terminals. For Tmax T4/T5 withdrawable and plug-in versions it is necessary to order the dedicated high terminal covers for 3 or 4 poles.


Structure

General information

Segregation Form 3b



- ① PSVS... Segregation for horizontal circuit-breaker
- ② PSVS...1 Segregation for busbar side of horizontal circuit-breakers
- ③ PSHS... Universal horizontal shelf
- ④ PLVS... Vertical side segregation of horizontal circuit-breaker compartment
- ⑤ PPVS... Universal compartment side closing element



Examples of busbar use in the structure


- 01 Horizontal circuit-breaker with front terminals
- 02 Vertical circuit-breaker with front terminals with rear intermediate upright*
- 03 Vertical circuit-breaker with front terminals
- 04 Horizontal circuit-breaker with rear terminals
- 05 Vertical circuit-breaker with rear terminals with rear intermediate upright*
- 06 Vertical circuit-breaker with rear terminals
- 07 Horizontal circuit-breaker with front/rear terminals

3b segregation begins with the components used for Form 2a - 3a with the addition of elements to separate the circuit-breaker terminals: for horizontal circuit-breakers this is obtained by means of sliding plate PSVS... while for vertical circuit-breakers, a pre-cut shelf, PSHS..., is used for the passage of busbars.
The busbar side must be isolated at the rear with

PRVS...1 busbar side segregations and at the sides, with PLVS... side segregations.

In case of segregation Form 3b, vertical breakers can be installed in the first available position under the top of the structure (top) or the last available position in the structure (bottom), with a maximum of two vertical breakers per column.

Structures with intermediate upright




* The rear intermediate upright is used when with the vertical breaker also an horizontal breaker is installed in the same column.

High terminal covers are available for all Tmax T/XT fixed and Emax E1.2 fixed, except for XT1, XT3 F-RC and kit PHBX3301, PHBX3401, PHBX4301, PHBX4401, PHBT4301, PHBT4406, PHBT5306, PHBT5406 and Tmax T6/T7 withdrawable and plug-in versions. For Tmax XT1/XT2/XT3/XT4 withdrawable and plug-in versions it is necessary to order the dedicated adapter covers for terminals. For Tmax T4/T5 withdrawable and plug-in versions it is necessary to order the dedicated high terminal covers for 3 or 4 poles.


Structure

General information

Segregation Form 4b



- ① PCVS... Output closing cubicles, to create according to the depth and type of circuit-breaker
- ② PSVS... Segregation for horizontal circuit-breaker
- ③ PSVS...1 Segregation for busbar side of horizontal circuit-breakers
- ④ PSHS... Universal horizontal shelf
- ⑤ PLVS... Vertical side segregation of horizontal circuit-breaker compartment
- ⑥ PPVS... Universal compartment side closing element




Examples of busbar use in the structure

- 01 Horizontal circuit-breaker with front terminals
- 02 Horizontal circuit-breaker with rear terminals
- 03 Horizontal circuit-breaker with front/rear terminals
- 04 Horizontal circuit-breaker with front terminals

4b segregation begins with the components used for Form 2a - 3a - 3b. It is obtained by means of dedicated PCVS... cubicles chosen to suit the depth of the circuit-breaker, and horizontal

shelves PSHS... required for each depth change of the output closing cubicles in the same column. Use universal vertical shelf PSHS.... for each compartment in order to reach Form 4b.

Structures with intermediate upright




High terminal covers are available for all Tmax T/XT fixed and Emax E1.2 fixed, except for XT1, XT3 F-RC and kit PHBX3301, PHBX3401, PHBX4301, PHBX4401, PHBT4301, PHBT4406, PHBT5306, PHBT5406 and Tmax T6/T7 withdrawable and plug-in versions. For Tmax XT1/XT2/XT3/XT4 withdrawable and plug-in versions it is necessary to order the dedicated adapter covers for terminals. For Tmax T4/T5 withdrawable and plug-in versions it is necessary to order the dedicated high terminal covers for 3 or 4 poles.

Structure

General information

Choice of segregation to suit height of kits
Tmax T and Tmax XT moulded-case circuit-breakers

Horizontal installation





Height of kits (mm)	Form 2a Universal compartment side closing element	Form 3a ⁽²⁾		Form 3b						Rear vertical bottom segregation on busbar side	
		Universal horizontal shelf		Vertical segregation of terminals			Depth of structure (mm)				
		Width of structure (mm)	For all depths	Width of structure (mm)	500	700	900				
200	PPVS2200	400	PSHS1904	400	PSVS2050	PSVS2070	PSVS2090	400	PRVS2041		
		600	PSHS1906	600	PSVS2050	PSVS2070	PSVS2090	600	PRVS2061		
		800	PSHS1908	800	PSVS2050	PSVS2070	PSVS2090	800	PRVS2081		
250	PPVS2250	400	PSHS1904	400	PSVS2550	PSVS2570	PSVS2590	400	PRVS2541		
		600	PSHS1906	600	PSVS2550	PSVS2570	PSVS2590	600	PRVS2561		
		800	PSHS1908	800	PSVS2550	PSVS2570	PSVS2590	800	PRVS2581		
300	PPVS2300	400	PSHS1904	400	PSVS3050	PSVS3070	PSVS3090	400	PRVS3041		
		600	PSHS1906	600	PSVS3050	PSVS3070	PSVS3090	600	PRVS3061		
		800	PSHS1908	800	PSVS3050	PSVS3070	PSVS3090	800	PRVS3081		
		1000	PSHS1901	1000	PSVS3050	PSVS3070	PSVS3090	1000			
350	PPVS2350	400	PSHS1904	400	PSVS3550	PSVS3570	PSVS3590	400	PRVS3541		
		600	PSHS1906	600	PSVS3550	PSVS3570	PSVS3590	600	PRVS3561		
		800	PSHS1908	800	PSVS3550	PSVS3570	PSVS3590	800	PRVS3581		
400	PPVS2400	400	PSHS1904	400	PSVS4050	PSVS4070	PSVS4090	400	PRVS4041		
		600 ⁽¹⁾	PSHS1906	600	PSVS4050	PSVS4070	PSVS4090	600	PRVS4061		
		800 ⁽¹⁾	PSHS1908	800	PSVS4050	PSVS4070	PSVS4090	800	PRVS4081		
500	PPVS2500	400	PSHS1904	400	PSVS5050	PSVS5070	PSVS5090	400	PRVS5041		
		600 ⁽³⁾	PSHS1906	600	PSVS5050	PSVS5070	PSVS5090	600	PRVS5061		
		800 ⁽³⁾	PSHS1908	800	PSVS5050	PSVS5070	PSVS5090	800	PRVS5081		
		1000	PSHS1901	1000	PSVS5050	PSVS5070	PSVS5090	1000			
600	PPVS2600	400	PSHS1904	400	PSVS6050	PSVS6070	PSVS6090	400	PRVS6041		
		600	PSHS1906	600	PSVS6050	PSVS6070	PSVS6090	600	PRVS6061		
		800	PSHS1908	800	PSVS6050	PSVS6070	PSVS6090	800	PRVS6081		
700	PPVS2700	600	PSHS1906								

⁽¹⁾ Also for fixed/interlocked horizontal Emax 2 E1.2 for W=600mm and W=800mm.

⁽²⁾ To install only between kits with different depths ($D \geq 38\text{mm}$) and above and below the kit compositions (top and bottom).

⁽³⁾ For T7 withdrawable and withdrawable interlocked use the segregations for horizontal E1.2 withdrawable for W=600mm and W=800mm.



For the cubicles assembly position please refer to page 6/46 taking into consideration the breakers type.

Form 4b

Cubicles to suit depth of circuit-breaker

Assembly position

Width of structure (mm)	Depth of structure (mm)			Assembly position		
	500	700	900	P0	P1	P2
400	PLVS2052	PLVS2072	PLVS2092	PCVS0204	PCVS1204	PCVS2204
600	PLVS2052	PLVS2072	PLVS2092	PCVS0206	PCVS1206	PCVS2206
800	PLVS2052	PLVS2072	PLVS2092	PCVS0208	PCVS1208	PCVS2208
400	PLVS2552	PLVS2572	PLVS2592	PCVS0254	PCVS1254	PCVS2254
600	PLVS2552	PLVS2572	PLVS2592	PCVS0256	PCVS1256	PCVS2256
800	PLVS2552	PLVS2572	PLVS2592	PCVS0258	PCVS1258	PCVS2258
400	PLVS3052	PLVS3072	PLVS3092	PCVS0304	PCVS1304	PCVS2304
600	PLVS3052	PLVS3072	PLVS3092	PCVS0306	PCVS1306	PCVS2306
800	PLVS3052	PLVS3072	PLVS3092	PCVS0308	PCVS1308	PCVS2308
1000						
400	PLVS3552	PLVS3572	PLVS3592	PCVS0354	PCVS1354	PCVS2354
600	PLVS3552	PLVS3572	PLVS3592	PCVS0356	PCVS1356	PCVS2356
800	PLVS3552	PLVS3572	PLVS3592	PCVS0358	PCVS1358	PCVS2358
400	PLVS4052	PLVS4072	PLVS4092	PCVS0404	PCVS1404	PCVS2404
600	PLVS4052	PLVS4072	PLVS4092	PCVS0406	PCVS1406	PCVS2406
800	PLVS4052	PLVS4072	PLVS4092	PCVS0408	PCVS1408	PCVS2408
400	PLVS5052	PLVS5072	PLVS5092	PCVS0504	PCVS1504	PCVS2504
600	PLVS5052	PLVS5072	PLVS5092	PCVS0506	PCVS1506	PCVS2506
800	PLVS5052	PLVS5072	PLVS5092	PCVS0508	PCVS1508	PCVS2508
1000						
400	PLVS6052	PLVS6072	PLVS6092	PCVS0604	PCVS1604	PCVS2604
600	PLVS6052	PLVS6072	PLVS6092	PCVS0606	PCVS1606	PCVS2606
800	PLVS6052	PLVS6072	PLVS6092	PCVS0608	PCVS1608	PCVS2608


⁽³⁾ Only required when columns are installed side by side, to separate the cable area and busbar area.

Structure

General information

Choice of segregation to suit height of kits
Tmax T and Tmax XT moulded-case circuit-breakers

Vertical installation





Height of kits (mm)	Form 2a Universal compartment side closing element	Form 3a ⁽²⁾		Form 3b			Rear vertical bottom segregation on busbar side		
		Width of structure (mm)	For all depths	Horizontal segregation of terminals			Width of structure (mm)	For all depths	
				500	700	900			
200	PPVS2200	400	PSHS1904	PSHS4050	PSHS4070	PSHS4090	400		
		600	PSHS1906	PSHS6050	PSHS6070	PSHS6090	600		
		800	PSHS1908	PSHS8050	PSHS8070	PSHS8090	800		
		1000	PSHS1901				1000		
300	PPVS2300	400	PSHS1904	PSHS4050	PSHS4070	PSHS4090	400		
		600	PSHS1906	PSHS6050	PSHS6070	PSHS6090	600		
		800	PSHS1908	PSHS8050	PSHS8070	PSHS8090	800		
		1000	PSHS1901				1000		
350	PPVS2350	400	PSHS1904	PSHS4050	PSHS4070	PSHS4090	400	PRVS1741	
		600	PSHS1906	PSHS6050	PSHS6070	PSHS6090	600	PRVS1761	
		800	PSHS1908	PSHS8050	PSHS8070	PSHS8090	800	PRVS1781	
		1000	PSHS1901				1000		
400	PPVS2400	400	PSHS1904	PSHS4050	PSHS4070	PSHS4090	400	PRVS2041	
		600	PSHS1906	PSHS6050	PSHS6070	PSHS6090	600	PRVS2061	
		800	PSHS1908	PSHS8050	PSHS8070	PSHS8090	800	PRVS2081	
		1000	PSHS1901				1000		
450	PPVS2450	400 ⁽¹⁾	PSHS1904	PSHS4050	PSHS4070	PSHS4090	400	PRVS2241	
		600 ⁽¹⁾	PSHS1906	PSHS6050	PSHS6070	PSHS6090	600	PRVS2261	
		800 ⁽¹⁾	PSHS1908	PSHS8050	PSHS8070	PSHS8090	800	PRVS2251	
		1000	PSHS1901				1000		
500	PPVS2500	400	PSHS1904	PSHS4050	PSHS4070	PSHS4090	400	PRVS2541	
		600 ⁽³⁾	PSHS1906	PSHS6050	PSHS6070	PSHS6090	600	PRVS2561	
		800 ⁽³⁾	PSHS1908	PSHS8050	PSHS8070	PSHS8090	800	PRVS2581	
		1000	PSHS1901				1000		
600	PPVS2600	400	PSHS1904	PSHS4050	PSHS4070	PSHS4090	400	PRVS3041	
		600	PSHS1906	PSHS6050	PSHS6070	PSHS6090	600	PRVS3061	
		800	PSHS1908	PSHS8050	PSHS8070	PSHS8090	800	PRVS3081	
		1000	PSHS1901				1000		
		1250					1250		

⁽¹⁾ Also for fixed/interlocked vertical Emax 2 E1.2 for L=400mm, L=600mm and L=800mm.

⁽²⁾ To install only between kits with different depths ($D \geq 38\text{mm}$) and above and below the kit compositions (top and bottom).

⁽³⁾ For T7 withdrawable and withdrawable interlocked use the segregations for vertical E1.2 withdrawable for W=600mm and W=800mm.



As an alternative to the PLVS... vertical side segregations, in the case of main circuit-breakers (Tmax T5, T6, T7), use the PMCS... side connection module for fixing terminal extensions and the relative fixing bshlefets PBMC0002 (page 4/40).

Form 4b


Form 4b is obtained by duplicating the codes of vertical bottom segregations PRVS... and vertical side segregations PLVS..., closing the circuit-breaker compartments over the entire height of the switchboard and installing an additional vertical side segregation on the output side.

Vertical bottom segregation on busbar side		Full width vertical bottom segregation		Vertical side segregation		
Width of structure (mm)	For all depths	Width of structure (mm)	For all depths	Depth of structure (mm)		
				500	700	900
400		400				
600		600				
800		800				
1000		1000				
400		400				
600		600				
800		800				
1000		1000				
400		400	PRVS1740	PLVS1752	PLVS1772	PLVS1792
600	PRVS1762	600	PRVS1760	PLVS1752	PLVS1772	PLVS1792
800	PRVS1782	800	PRVS1780	PLVS1752	PLVS1772	PLVS1792
1000		1000	PRVS1710	PLVS1752	PLVS1772	PLVS1792
400		400	PRVS2040	PLVS2052	PLVS2072	PLVS2092
600	PRVS2062	600	PRVS2060	PLVS2052	PLVS2072	PLVS2092
800	PRVS2082	800	PRVS2080	PLVS2052	PLVS2072	PLVS2092
1000		1000	PRVS2010	PLVS2052	PLVS2072	PLVS2092
400		400	PRVS2240	PLVS2252	PLVS2272	PLVS2292
600	PRVS2262	600	PRVS2260	PLVS2252	PLVS2272	PLVS2292
800	PRVS2282	800	PRVS2280	PLVS2252	PLVS2272	PLVS2292
1000		1000	PRVS2210	PLVS2252	PLVS2272	PLVS2292
400		400		PLVS2552	PLVS2572	PLVS2592
600	PRVS2562	600	PRVS2560	PLVS2552	PLVS2572	PLVS2592
800	PRVS2582	800	PRVS2580	PLVS2552	PLVS2572	PLVS2592
1000		1000	PRVS2510	PLVS2552	PLVS2572	PLVS2592
400		400	PRVS3040	PLVS3052	PLVS3072	PLVS3092
600	PRVS3062	600	PRVS3060	PLVS3052	PLVS3072	PLVS3092
800	PRVS3082	800	PRVS3080	PLVS3052	PLVS3072	PLVS3092
1000		1000	PRVS3010	PLVS3052	PLVS3072	PLVS3092
1250		1250	PRVS3125			

Structure

General information

Choice of segregation Emax 2 air circuit-breakers *



Vertical fixed Emax 2

Form 2a-3a			Form 3b						
Segregation kit			Horizontal terminal separator						
	E2.2	E4.2	E6.2		E2.2	E2.2	E4.2	E4.2	E6.2
Height of kits (mm)						Width of Kit/column (mm)			
Width of Kit/column (mm)	600	600	700		700	900	700	900	900
600	PSVF6062	PSVF6064			PSHF6072	PSHF6092	PSHF6072	PSHF6092	
800	PSVF6082	PSVF6084			PSHF8072	PSHF8092	PSHF8072	PSHF8092	
1000			PSVF7016	1000					PSHF1096
1250			PSVF7126	1250					PSHF1296

Vertical withdrawable Emax 2

Form 2a-3a				Form 3b									
Segregation kit				Horizontal terminal separator									
Width of Kit/column (mm)	E1.2	E2.2	E4.2	E6.2	Width of Kit/column (mm)	E1.2	E1.2	E1.2	E2.2	E2.2	E4.2	E4.2	E6.2
Height of kits (mm)								Depth (mm)					
(mm)	500	600	600	700	(mm)	500	700	900	700	900	700	900	900
600	PSVW5061 ⁽¹⁾	PSVW6062	PSVW6064		600	PSHW6051 ⁽¹⁾	PSHW6071 ⁽¹⁾	PSHW6091	PSHW6072	PSHW6092	PSHW6074	PSHW6094	
800	PSVW5081 ⁽¹⁾	PSVW6082	PSVW6084		800	PSHW8051 ⁽¹⁾	PSHW8071 ⁽¹⁾	PSHW8091	PSHW8072	PSHW8092	PSHW8074	PSHW8094	
1000				PSVW7016	1000							PSHW1096	
1250				PSVW6126	PSVW7126	1250						PSHW1296	


Horizontal withdrawable Emax 2


Form 2a-3a		Form 3b		Form 4b		
Segregation kit		Vertical terminal separator		Rear cubicle		
E1.2		E1.2		E1.2		
Height of kits (mm)		Width of kits (mm)		Depth (mm)		
600	800	700	900	600	800	
500	PSHW5061 ⁽²⁾	PSHW5081 ⁽²⁾	PSVS0055 ⁽²⁾	PSVS0057 ⁽²⁾	PCVS5060 ⁽²⁾	PCVS5080 ⁽²⁾

* For horizontal/vertical Emax E1.2 fixed see page 7/12 (kit H=400mm) and 7/14 (kit H=450mm).

⁽¹⁾ Also suitable for vertical T7 withdrawable and withdrawable interlocked.

⁽²⁾ Also suitable for horizontal T7 withdrawable and withdrawable interlocked.







Bottom segregations				Side segregations			
Width of Kit/column (mm)	Structures with rear intermediate upright on busbar side	Structures with rear intermediate upright on output side	Structures without intermediate rear upright full-width segregation	Assembly between intermediate upright and rear structural upright			
	E2.2/E4.2	E2.2/E4.2	E2.2/E4.2	E6.2	E2.2/E4.2	E6.2	Height of kits (mm)
600	PRVS3061	PRVS3062	PRVS3060	700	700	PLVS3072	PLVS3572
800	PRVS3081	PRVS3082	PRVS3080		900	PLVS3092	PLVS3592
1000			PRVS3010	PRVS3510			
1250			PRVS3125	PRVS3501			

Bottom segregations				Side segregations				
Width of Kit/column (mm)	Structures with rear intermediate upright on busbar side	Structures with rear intermediate upright on output side	Structures without intermediate rear upright full-width segregation	Assembly between intermediate upright and rear structural upright				
	Height of kits (mm)	500	600	500	600	700	900	Height of kits (mm)
600	PRVS2561	PRVS3061	PRVS2562	PRVS3062	PRVS2560	PRVS3060		500
800	PRVS2581	PRVS3081	PRVS2582	PRVS3082	PRVS2580	PRVS3080		600
1000					PRVS2510	PRVS3010	PRVS3510	700
1250					PRVS2512	PRVS3125	PRVS3501	PLVS3552

Form 2b
Breakers with rear terminals.
use dedicated kit 2a-3a and shelf
PTH... page 6/30.

Vertical circuit-breakers Form 4b






Form 4b is obtained by duplicating the codes of vertical bottom segregations PRVS... and vertical side segregations PLVS..., closing the circuit-breaker compartments over the entire height of the switchboard and installing an additional vertical side segregation on the output side.

As an alternative to the PLVS... vertical side segregations, in the case of main circuit-breakers, use the PMCS... side connection module for fixing terminal extensions and the relative fixing bshelves PBMC0002 (page 4/40).

Structure

General information

Choice of busbars segregation



Horizontal busbars

Segregation for horizontal busbars: at top, at the bottom and at each height⁽¹⁾

Width (mm)	Structure			External cable compartment				Internal cable compartment			
	Form 2b			Form 2b, 3b, 4b				Form 2b, 3b, 4b			
	Without intermediate upright			Without intermediate upright				Without intermediate upright side structure			
Horizontal shelves ⁽⁴⁾	Front/Rear segregations	Horizontal shelves ⁽⁴⁾	Front/Rear segregations	Horizontal shelves ⁽⁴⁾	Depth (mm)	Height (mm)	Horizontal shelves ⁽⁴⁾	Front/Rear segregations	Horizontal shelves ⁽⁴⁾	Depth (mm)	Front/Rear segregations
Width (mm)	300	500	700	200	300	500	700	900	200	300	500
200											
300	PTHS4030	PTHS4050	PTHS4070	PFVS2040	PTHS4030	PTHS3030	PTHS3050	PTHS3070	PTHS4190	PTHS2130	PTHS2030
400	PTHS6030	PTHS6050	PTHS6070	PFVS2060	PTHS4050	PTHS4070	PTHS4190	PFVS2140		PTHS4230	PTHS2050
600	PTHS8030	PTHS8050	PTHS8070	PFVS2080	PTHS4070	PTHS4190	PFVS2140			PTHS4250	PTHS2070
800										PTHS4270	PTHS2090
1000											PFVS2240
1250											

⁽¹⁾ Busbars at each height are foreseen only for segregation form different from Form 2b. For the closing at the back off the structure use Form 3b segregations PRVS.... busbars/outgoing side at whole height.

⁽²⁾ Busbars at each height are foreseen only for segregation form different from Form 2b.

⁽³⁾ For busbars at each height >100mm; for busbars at the top/bottom >120mm.

⁽⁴⁾ The horizontal shelves must be fixed to the vertical ones.


Segregation for horizontal busbars: at top, at the bottom and at each height⁽¹⁾


Structure		External cable compartment						Internal cable compartment					
Form 2b, 3b, 4b			Form 2b, 3b, 4b			Form 2b, 3b, 4b			Form 3b, 4b				
With intermediate upright			With intermediate upright			With intermediate upright side structure			Front segregations at each heights				
Horizontal shelves		Front segregations		Horizontal shelves		Front segregations		Horizontal shelves		Front segregations		Front segregations at each heights	
Depth (mm)	Height (mm)	Depth (mm)	Height (mm)	Depth (mm)	Height (mm)	Depth (mm)	Height (mm)	Depth (mm)	Height (mm)	Depth (mm)	Height (mm)	Depth (mm)	Height (mm)
500	700	900	200 ⁽²⁾	300 ⁽³⁾	500	700	900	200 ⁽²⁾	300 ⁽³⁾	500	700	900	200 ⁽²⁾

PTHS1052	PTHS6052	PTHS4052	PTHS8052	PTHS6072	PTHS4072	PTHS8072	PTHS8092	PTHS6092	PTHS4092	PFVS2042	PFVS2062	PFVS2082	PFVS2012	PFVS3082	PFVS3062	PFVS3042	PTHS4152	PTHS3052	PTHS4172	PTHS3072	PTHS4192	PTHS3092	PFVS2042	PFVS2132	PFVS2132	PFVS3042	PFVS3132	PTHS4252	PTHS2052	PTHS2072	PTHS2092	PFVS2242	PFVS2222	PFVS2222	PFVS3242	PFVS3243	PFVS3243	PFVS3243
PTHS1072	PTHS8072	PTHS4072	PTHS8092	PTHS6092	PTHS4092	PTHS8052	PTHS8072	PTHS6072	PTHS4072	PFVS2062	PFVS2082	PFVS2012	PFVS3082	PFVS3062	PFVS3042	PTHS4152	PTHS3052	PTHS4172	PTHS3072	PTHS4192	PTHS3092	PFVS2042	PFVS2132	PFVS2132	PFVS3042	PFVS3132	PTHS4252	PTHS2052	PTHS2072	PTHS2092	PFVS2242	PFVS2222	PFVS2222	PFVS3242	PFVS3243	PFVS3243	PFVS3243	
PTHS1092	PTHS8092	PTHS4092	PTHS8052	PTHS6072	PTHS4072	PTHS8072	PTHS802	PTHS602	PTHS402	PFVS2062	PFVS2082	PFVS2012	PFVS3082	PFVS3062	PFVS3042	PTHS4152	PTHS3052	PTHS4172	PTHS3072	PTHS4192	PTHS3092	PFVS2042	PFVS2132	PFVS2132	PFVS3042	PFVS3132	PTHS4252	PTHS2052	PTHS2072	PTHS2092	PFVS2242	PFVS2222	PFVS2222	PFVS3242	PFVS3243	PFVS3243	PFVS3243	
PTHS1292	PTHS8092	PTHS4092	PTHS8052	PTHS6072	PTHS4072	PTHS8072	PTHS802	PTHS602	PTHS402	PFVS2062	PFVS2082	PFVS2012	PFVS3082	PFVS3062	PFVS3042	PTHS4152	PTHS3052	PTHS4172	PTHS3072	PTHS4192	PTHS3092	PFVS2042	PFVS2132	PFVS2132	PFVS3042	PFVS3132	PTHS4252	PTHS2052	PTHS2072	PTHS2092	PFVS2242	PFVS2222	PFVS2222	PFVS3242	PFVS3243	PFVS3243	PFVS3243	
PFVS2122	PFVS3082	PFVS3062	PFVS3042	PTHS8072	PTHS4072	PTHS8092	PTHS802	PTHS602	PTHS402	PFVS2062	PFVS2082	PFVS2012	PFVS3082	PFVS3062	PFVS3042	PTHS4152	PTHS3052	PTHS4172	PTHS3072	PTHS4192	PTHS3092	PFVS2042	PFVS2132	PFVS2132	PFVS3042	PFVS3132	PTHS4252	PTHS2052	PTHS2072	PTHS2092	PFVS2242	PFVS2222	PFVS2222	PFVS3242	PFVS3243	PFVS3243	PFVS3243	
PFVS3122	PFVS3082	PFVS3062	PFVS3042	PTHS8072	PTHS4072	PTHS8092	PTHS802	PTHS602	PTHS402	PFVS2062	PFVS2082	PFVS2012	PFVS3082	PFVS3062	PFVS3042	PTHS4152	PTHS3052	PTHS4172	PTHS3072	PTHS4192	PTHS3092	PFVS2042	PFVS2132	PFVS2132	PFVS3042	PFVS3132	PTHS4252	PTHS2052	PTHS2072	PTHS2092	PFVS2242	PFVS2222	PFVS2222	PFVS3242	PFVS3243	PFVS3243	PFVS3243	

Structure

General information

Choice of busbars segregation




Vertical busbars

Height (mm)	Type	Side segregation for vertical busbars						Form 2b ⁽²⁾		Form 2b, 3b, 4b	
		Structure						Front		Rear	
Without intermediate upright						Depth (mm)		Depth (mm)		Depth (mm)	
700	blind	PTVS8020	PTBS8020	PTBS8030	PTBS8050	PTBS8070	PTBS8090	PTBS8001	PTBS8052	PLVS7052	PLVS7072
800	blind	PTVS8030	PTBS1020	PTBS1030	PTBS1050	PTBS1070	PTBS1090	PTBS1001	PTBS1052	PLVS8091	PLVS7092
1000	blind	PTVS8050	PTVS1020	PTVS1030	PTVS1050	PTVS1070	PTVS1090	PTVS8001	PTVS8052	PTVS8072	PTVS8091
800	pre-cut	PTVS8070	PTVS8090	PTVS1030	PTVS1050	PTVS1070	PTVS1090	PTVS1001	PTVS1052	PTVS8091	PTVS1091
1000	pre-cut	PTVS1090	PTVS1072	PTVS1091	PTVS1052	PTVS1072	PTVS1090	PTVS1001	PTVS1052	PTVS8091	PTVS1091

For the closing at the back off the structure use Form 3b segregations PRVS.... busbars/outgoing side at whole height.

⁽²⁾ Segregation Form 3b, 4b from the intermediate upright up to the front structural upright can be obtained only by means of lateral segregation closing Form 2a-3a.




Cable compartment

Blind side segregation for external cable compartment with intermediate upright	Rear segregation for external cable compartment			Rear segregation for internal cable compartment with rear intermediate upright			Internal door for external cable compartment		Internal door for internal cable compartment		Front vertical segregation for external cable compartment		Front vertical segregation for internal cable compartment	
	Depth (mm)	Width (mm)	Width (mm)	Width (mm)	Width (mm)	Width (mm)	Width (mm)	Width (mm)	Width (mm)	Width (mm)	Width (mm)	Width (mm)	Width (mm)	
PTBS1052	PTBS8052	PLVS7052	PLVS7072	PRVS8062	PRVS8082	PRBS1220	PRBS1240	PDCB2030	PDCB1830	PDCB2044	PDCB1844	PDCB2020	PDCB1820	
PTBS1072	PTBS8072													
PTVB1091	PTBS8091	PLVS7092												
PRVS1062														
PRVS1082														
PRBS11220														
PRBS11240														
PFVS1030														
PFBS1040														
PFBS1020														
PFBS1040														

Segregation

Guide to the order codes

The new code is formed by 4 letters standing for English terms and 4 numbers, without spaces in between.



RANGE IDENTIFIER

The first letter of all the codes of the new main distribution switchboard "P" stands for "power". Thus the new product is clearly identified by the same initial used for all new components of ABB's System pro E power

TYPE OF PRODUCT AND CHARACTERISTICS

The second letter in the code indicates the type of product or component of the switchboard. The third and fourth letters describe the characteristics

S = Segregation
R = Rears
L = Lateral
C = Crosspieces
P = Pre-cut
F = Frontal
C = Cell
T = Total

V = Vertical
H = Horizontal
B = Blind
R = Rubber
D = Nylon


S = Structure/Struttura Segregation/
Segregazione
F = Fixed/Fisso
W = Withdrawable/Estraibile

MEASUREMENTS

The last 4 numbers usually refer to a measurement of the component or several dimensions pertaining to the code.

Segregation


Order codes - Form 2a-3a segregations



Intermediate side and rear upright for assembly of internal kits and segregations

The intermediate upright is the same as the one used for installing the kits and can be assembled both on the side and bottom of the structure.


Description	Dimensions (mm)			Pkg/ No. pcs
	H	Type	Order code	
Intermediate upright	1800	PUKI1800	1STQ008039A0000	1/1
Intermediate upright	2000	PUKI2000	1STQ008040A0000	1/1



Universal horizontal shelf

Horizontal shelf to use whenever the plates of the circuit-breakers are further than 38mm , and above and below the kit compositions (top and bottom). For structures with intermediate uprights.

Description	Dimensions (mm)			Pkg/ No. pcs
	W	Type	Order code	
Universal horizontal shelf	400	PSHS1904	1STQ008691A0000	1/1
Universal horizontal shelf	600	PSHS1906	1STQ008692A0000	1/1
Universal horizontal shelf	800	PSHS1908	1STQ008693A0000	1/1
Universal horizontal shelf	1000	PSHS1901	1STQ008694A0000	1/1
Universal horizontal shelf	1250	PSHS1912	1STQ001567B0000	1/1



Universal compartment side closing element


Precut universal compartment side closing element for use with both horizontal and vertical circuit-breakers. Preengineered for housing compartment side closing elements in rubber.

For structures with intermediate uprights.


Description	Dimensions (mm)			Pkg/ No. pcs
	H	Type	Order code	
2 compartment side closing elements	200	PPVS2200	1STQ008695A0000	1/2
2 compartment side closing elements	250	PPVS2250	1STQ008696A0000	1/2
2 compartment side closing elements	300	PPVS2300	1STQ008697A0000	1/2
2 compartment side closing elements	350	PPVS2350	1STQ008698A0000	1/2
2 compartment side closing elements	400	PPVS2400	1STQ008699A0000	1/2
2 compartment side closing elements	450	PPVS2450	1STQ008700A0000	1/2
2 compartment side closing elements	500	PPVS2500	1STQ008701A0000	1/2
2 compartment side closing elements	600	PPVS2600	1STQ008702A0000	1/2
2 compartment side closing elements	700	PPVS2700	1STQ009228A0000	1/2

Segregation

Order codes - Form 2a-3a segregations




PPRS0150

PPRS0200....
....PPRS0600

Rubber cover for closing compartments at the side

Rubber cover for closing compartments at the side and routing connections.

Description	Cell dimensions (mm) H	Rubber dimensions (mm) H	Type	Order code	Pkg/ No. pcs
Rubber cover	150	-	PPRS0150	1STQ008726A0000	1/1
Rubber cover	200	150	PPRS0200	1STQ008583A0000	1/1
Rubber cover	250	200	PPRS0250	1STQ008584A0000	1/1
Rubber cover	300	250	PPRS0300	1STQ008585A0000	1/1
Rubber cover	350	300	PPRS0350	1STQ008586A0000	1/1
Rubber cover	400	350	PPRS0400	1STQ008587A0000	1/1
Rubber cover	450	400	PPRS0450	1STQ008588A0000	1/1
Rubber cover	500	450	PPRS0500	1STQ008589A0000	1/1
Rubber cover	600	550	PPRS0600	1STQ008590A0000	1/1




Segregation of modular assemblies

The code refers to two side walls. The segregation must be completed by ordering a front segregation and two PSHS... universal shelves, above and below. For structures with intermediate uprights.

Description	Dimensions (mm)			Pkg/ No. pcs	
	H	W	Type	Order code	
No.2 Side closing elements for DIN rail	200		PPDS0200	1STQ009080A0000	1/2
Front segregation	200	400	PFVS2042	1STQ008539A0000	1/1
Front segregation	200	600	PFVS2062	1STQ008540A0000	1/1
Front segregation	200	800	PFVS2082	1STQ008541A0000	1/1

The side closing elements pre-cuts for DIN rail measure H=50mm; from a rubber cover PPRS0200 it is possible to obtain 3 rubber covers for DIN rail H=50mm each.

Segregation for Unifix H





Description	Dimensions (mm)			Pkg/ No. pcs
	H	Type	Order code	
No. 2 Side closing elements for Unifix H	300	PLSU0300	1STQ001333B0000	1/2

Segregation

Order codes - Form 2a-3a segregations

E1.2 horizontal

E1.2 - E2.2 - E4.2 -
E6.2 vertical

Segregation for the SACE Emax 2 circuit-breaker

The codes include two horizontal shelves, one rear plate and two side walls. For structures with intermediate uprights.

Dimensions (mm)						Pkg/ No. pcs
Emax 2 circuit-breaker	Version	H	W	Type	Order code	
Horizontal circuit-breakers						
E1.2	W	500	600	PSHW5061 ⁽¹⁾	1STQ009281A0000	1/1
E1.2	W	500	800	PSHW5081 ⁽¹⁾	1STQ009282A0000	1/1
Vertical circuit-breakers						
E1.2	W	500	600	PSVW5061 ⁽²⁾	1STQ009055A0000	1/1
E1.2	W	500	800	PSVW5081 ⁽²⁾	1STQ009056A0000	1/1
E2.2	F	600	600	PSVF6062	1STQ009057A0000	1/1
E2.2	F	600	800	PSVF6082	1STQ009058A0000	1/1
E2.2	W	600	600	PSVW6062	1STQ009059A0000	1/1
E2.2	W	600	800	PSVW6082	1STQ009060A0000	1/1
E2.2	W	600	1250	PSVW6126	1STQ004226B0000	1/1
E4.2	F	600	600	PSVF6064	1STQ009061A0000	1/1
E4.2	F	600	800	PSVF6084	1STQ009062A0000	1/1
E4.2	W	600	600	PSVW6064	1STQ009063A0000	1/1
E4.2	W	600	800	PSVW6084	1STQ009064A0000	1/1
E6.2	F	700	1000	PSVF7016	1STQ009065A0000	1/1
E6.2	F	700	1250	PSVF7126	1STQ009066A0000	1/1
E6.2	W	700	1000	PSVW7016	1STQ009067A0000	1/1
E6.2	W	700	1250	PSVW7126	1STQ009068A0000	1/1

⁽¹⁾ Also suitable for horizontal T7 withdrawable and withdrawable interlocked.

⁽²⁾ Also suitable for vertical T7 withdrawable and withdrawable interlocked.

Segregation for the SACE Emax 2 circuit-breaker for space-saving column W=400mm

The codes include two horizontal shelves, one rear plate and two side walls. For structures with intermediate uprights.


Dimensions (mm)						Pkg/ No. pcs
Emax 2 circuit-breaker	Version	H	W	Type	Order code	
Vertical circuit-breakers						
E1.2	W	600	400	PSVW6041	1STQ001568B0000	1/1
E2.2	F	600	400	PSVF6042	1STQ001569B0000	1/1
E2.2	W	600	400	PSVW6042	1STQ001570B0000	1/1

Key:

F fixed
W withdrawable

Segregation

Order codes - Form 2a-3a segregations



Blind compartment for segregations

Blind compartment for filling empty spaces inside the structure. The blind compartments are not suitable for fixing accessories. For structures with intermediate uprights.


Description	Dimensions (mm)			Pkg/ No. pcs
	H	W	Type	Order code
Blind compartment	50	400	PCBS5040	1STQ008703A0000
Blind compartment	100	400	PCBS1040	1STQ008704A0000
Blind compartment	150	400	PCBS1540	1STQ008705A0000
Blind compartment	200	400	PCBS2040	1STQ008706A0000
Blind compartment	250	400	PCBS2540	1STQ008707A0000
Blind compartment	300	400	PCBS3040	1STQ009027A0000
Blind compartment	50	600	PCBS5060	1STQ008708A0000
Blind compartment	100	600	PCBS1060	1STQ008709A0000
Blind compartment	150	600	PCBS1560	1STQ008710A0000
Blind compartment	200	600	PCBS2060	1STQ008711A0000
Blind compartment	250	600	PCBS2560	1STQ008712A0000
Blind compartment	300	600	PCBS3060	1STQ009028A0000
Blind compartment	50	800	PCBS5080	1STQ008713A0000
Blind compartment	100	800	PCBS1080	1STQ008714A0000
Blind compartment	150	800	PCBS1580	1STQ008715A0000
Blind compartment	200	800	PCBS2080	1STQ008716A0000
Blind compartment	250	800	PCBS2580	1STQ008717A0000
Blind compartment	300	800	PCBS3080	1STQ009029A0000
Blind compartment	50	1000	PCBS5010	1STQ008718A0000
Blind compartment	100	1000	PCBS1010	1STQ008719A0000
Blind compartment	150	1000	PCBS1510	1STQ008720A0000
Blind compartment	200	1000	PCBS2010	1STQ008721A0000
Blind compartment	250	1000	PCBS2510	1STQ008722A0000
Blind compartment	300	1000	PCBS3010	1STQ009030A0000
Blind compartment	100	1250	PCBS1012	1STQ004228B0000

Not to mount above or below a kit with MO or a recessed external panels PPBR...

In this cases it is necessary using blind mounting plate and a blind flat panel to reach the segregation form 2A-3A.

Segregation

Order codes - Busbar segregations Form 2b-3b-4a-4b




Intermediate side and rear upright for assembly of internal kits and segregations

The intermediate upright is the same as the one used for installing the kits and can be assembled both on the side and bottom of the structure.

Description	Dimensions (mm)			Pkg/ No. pcs
	H	Type	Order code	
Intermediate upright	1800	PUKI1800	1STQ008039A0000	1/1
Intermediate upright	2000	PUKI2000	1STQ008040A0000	1/1

The intermediate upright is required for all segregation Forms differing from Form 2b, even when not needed by the circuit-breaker version.




Side segregation for structure without intermediate upright

Vertical side walls for assembly between front and rear structural uprights. To use for structures with fixed circuitbreakers that do not require the intermediate upright. The precuts in the segregations are at 50mm pitch. At least three vertical ones must be removed.

Description	Dimensions (mm)			Pkg/ No. pcs
	H	D	Type	
Precut				
Precut vertical side segregation	800	200	PTVS8020	1STQ009070A0000
Precut vertical side segregation	1000	200	PTVS1020	1STQ009071A0000
Precut vertical side segregation	800	300	PTVS8030	1STQ008487A0000
Precut vertical side segregation	1000	300	PTVS1030	1STQ008488A0000
Precut vertical side segregation	800	500	PTVS8050	1STQ008489A0000
Precut vertical side segregation	1000	500	PTVS1050	1STQ008490A0000
Precut vertical side segregation	800	700	PTVS8070	1STQ008491A0000
Precut vertical side segregation	1000	700	PTVS1070	1STQ008492A0000
Blind				
Blind vertical side segregation	800	200	PTBS8020	1STQ009072A0000
Blind vertical side segregation	1000	200	PTBS1020	1STQ009073A0000
Blind vertical side segregation	800	300	PTBS8030	1STQ008493A0000
Blind vertical side segregation	1000	300	PTBS1030	1STQ008494A0000
Blind vertical side segregation	800	500	PTBS8050	1STQ008495A0000
Blind vertical side segregation	1000	500	PTBS1050	1STQ008496A0000
Blind vertical side segregation	800	700	PTBS8070	1STQ008497A0000
Blind vertical side segregation	1000	700	PTBS1070	1STQ008498A0000
Blind vertical side segregation	800	900	PTBS8090	1STQ002004B0000
Blind vertical side segregation	1000	900	PTBS1090	1STQ002005B0000

Segregation

Order codes - Busbar segregations Form 2b-3b-4a-4b




Front side segregation for structure with intermediate upright

Precut vertical front side wall for assembly between intermediate upright and front structural upright.

Description	Dimensions (mm)			Pkg/ No. pcs
	H	Type	Order code	
Precut vertical front side segregation				
Vertical side segregation	800	PTVS8001	1STQ008511A0000	1/1
Vertical side segregation	1000	PTVS1001	1STQ008512A0000	1/1
Blind vertical front side segregation				
Vertical side segregation	800	PTBS8001	1STQ008513A0000	1/1
Vertical side segregation	1000	PTBS1001	1STQ008514A0000	1/1

Segregation Form 3b, 4b from the intermediate upright up to the front structural upright can be obtained only by means of lateral segregation closing Form 2a-3a.




Rear side segregation for structure with intermediate upright

Precut vertical rear side wall for assembly between intermediate upright and rear structural upright.

Description	Dimensions (mm)			Pkg/ No. pcs
	H	D	Type	
Segregazione verticale laterale posteriore con pretranciature				
Vertical side segregation	800	500	PTVS8052	1STQ008515A0000
Vertical side segregation	1000	500	PTVS1052	1STQ008516A0000
Vertical side segregation	800	700	PTVS8072	1STQ008517A0000
Vertical side segregation	1000	700	PTVS1072	1STQ008518A0000
Vertical side segregation	800	900	PTVS8091	1STQ008519A0000
Vertical side segregation	1000	900	PTVS1091	1STQ008520A0000
Segregazione verticale laterale posteriore con pretranciature				
Vertical side segregation	700	500	PLVS7052	1STQ009131A0000
Vertical side segregation	800	500	PTBS8052	1STQ008521A0000
Vertical side segregation	1000	500	PTBS1052	1STQ008522A0000
Vertical side segregation	700	700	PLVS7072	1STQ009132A0000
Vertical side segregation	800	700	PTBS8072	1STQ008523A0000
Vertical side segregation	1000	700	PTBS1072	1STQ008524A0000
Vertical side segregation	700	900	PLVS7092	1STQ009133A0000
Vertical side segregation	800	900	PTBS8091	1STQ008525A0000
Vertical side segregation	1000	900	PTVB1091	1STQ008526A0000

Segregation

Order codes - Busbar segregations Form 2b-3b-4a-4b




Rubber cover for precuts

Rubber cover for pre-cut vertical segregation for routing the connections that can be installed on vertical segregations with precuts.

Description	Dimensions (mm)			Pkg/ No. pcs
	H	Type	Order code	
Rubber cover	150	PPRS0200	1STQ008583A0000	1/1
Rubber cover	200	PPRS0250	1STQ008584A0000	1/1
Rubber cover	250	PPRS0300	1STQ008585A0000	1/1
Rubber cover	300	PPRS0350	1STQ008586A0000	1/1
Rubber cover	350	PPRS0400	1STQ008587A0000	1/1
Rubber cover	400	PPRS0450	1STQ008588A0000	1/1
Rubber cover	450	PPRS0500	1STQ008589A0000	1/1
Rubber cover	550	PPRS0600	1STQ008590A0000	1/1

For precuts H = 800mm use No. 2 rubber cover H = 400mm PPRS0450

For precuts H = 1000mm use No. 1 rubber cover H = 450mm PPRS0500 and No. 1 rubber cover H = 550mm PPRS0600



Horizontal busbar segregation in structures without intermediate upright Form 2b


Full-width and full-depth horizontal segregations and full-width vertical segregations for routing busbars installed horizontally on the top, on the bottom, behind an empty compartment H=200mm, for structures without intermediate uprights.

Description	Dimensions (mm)				Pkg/ No. pcs
	H	W	D	Type	
Horizontal busbar shelves					
Horizontal shelf	400	300	PTHS4030	1STQ008499A0000	1/1
Horizontal shelf	400	500	PTHS4050	1STQ008500A0000	1/1
Horizontal shelf	400	700	PTHS4070	1STQ008501A0000	1/1
Horizontal shelf	600	300	PTHS6030	1STQ008502A0000	1/1
Horizontal shelf	600	500	PTHS6050	1STQ008503A0000	1/1
Horizontal shelf	600	700	PTHS6070	1STQ008504A0000	1/1
Horizontal shelf	800	300	PTHS8030	1STQ008505A0000	1/1
Horizontal shelf	800	500	PTHS8050	1STQ008506A0000	1/1
Horizontal shelf	800	700	PTHS8070	1STQ008507A0000	1/1
Front busbar segregations					
Front segregation	200	400	PFVS2040	1STQ008508A0000	1/1
Front segregation	200	600	PFVS2060	1STQ008509A0000	1/1
Front segregation	200	800	PFVS2080	1STQ008510A0000	1/1
Rear busbar segregations					
Rear segregation	200	400	PRVS2040	1STQ008845A0000	1/1
Rear segregation	200	600	PRVS2060	1STQ008855A0000	1/1
Rear segregation	200	800	PRVS2080	1STQ008865A0000	1/1

The horizontal shelves must be fixed to the vertical ones


Segregation

Order codes - Busbar segregations Form 2b-3b-4a-4b




Horizontal busbar segregation for external cable compartment without intermediate upright Form 2b

Full-width and full-depth horizontal shelves and front busbar segregations for external cable compartments.



Description	Dimensions (mm)			Type	Order code	Pkg/ No. pcs
	H	W	D			
Horizontal busbar shelves						
Horizontal shelf	300	300	PTHS3030	1STQ008547A0000		1/1
Horizontal shelf	300	500	PTHS3050	1STQ008548A0000		1/1
Horizontal shelf	300	700	PTHS3070	1STQ008549A0000		1/1
Horizontal shelf	300	900	PTHS3090	1STQ009077A0000		1/1
Horizontal shelf	400	300	PTHS4030	1STQ008499A0000		1/1
Horizontal shelf	400	500	PTHS4050	1STQ008500A0000		1/1
Horizontal shelf	400	700	PTHS4070	1STQ008501A0000		1/1
Horizontal shelf	400	900	PTHS4190	1STQ009078A0000		1/1
Front busbar segregations						
Front segregation	200	300	PFVS2130	1STQ008553A0000		1/1
Front segregation	200	400	PFVS2140	1STQ008554A0000		1/1
Rear busbar segregations						
Rear segregation	200	300	PFRS2130	1STQ008845A0000		1/1
Rear segregation	200	400	PFRS2062	1STQ008815A0000		1/1

The horizontal shelves must be fixed to the vertical ones



Horizontal busbar segregation for internal cable compartment without intermediate upright Form 2b

Full-width and full-depth horizontal shelves and front busbar segregations for internal cable compartments.

Description	Dimensions (mm)			Type	Order code	Pkg/ No. pcs
	H	W	D			
Horizontal busbar shelves						
Horizontal shelf	200	300	PTHS2030	1STQ008565A0000		1/1
Horizontal shelf	200	500	PTHS2050	1STQ008566A0000		1/1
Horizontal shelf	200	700	PTHS2070	1STQ008567A0000		1/1
Horizontal shelf	200	900	PTHS2090	1STQ009079A0000		1/1
Horizontal shelf	400	300	PTHS4230	1STQ008568A0000		1/1
Horizontal shelf	400	500	PTHS4250	1STQ008569A0000		1/1
Horizontal shelf	400	700	PTHS4270	1STQ008570A0000		1/1
Horizontal shelf	400	900	PTHS4290	1STQ009081A0000		1/1
Front/Rear busbar segregations						
Front/Rear segregation	200	300	PFVS2220	1STQ008571A0000		1/1
Front/Rear segregation	200	400	PFVS2240	1STQ008572A0000		1/1

The horizontal shelves must be fixed to the vertical ones


Segregation

Order codes - Busbar segregations Form 2b-3b-4a-4b




Horizontal busbar segregation in structures with intermediate uprights

Horizontal shelves and front segregations for routing busbars installed horizontally on the top, on the bottom and at each heights. The busbar area can be 200 or 300mm in height.




Description	Dimensions (mm)			Type	Order code	Pkg/ No. pcs
	H	W	D			
Horizontal shelves for busbars under the top, on the bottom and at each heights						
Horizontal shelf	400	500	PTHS4052	1STQ008527A0000		1/1
Horizontal shelf	600	500	PTHS6052	1STQ008528A0000		1/1
Horizontal shelf	800	500	PTHS8052	1STQ008529A0000		1/1
Horizontal shelf	1000	500	PTHS1052	1STQ008530A0000		1/1
Horizontal shelf	400	700	PTHS4072	1STQ008531A0000		1/1
Horizontal shelf	600	700	PTHS6072	1STQ008532A0000		1/1
Horizontal shelf	800	700	PTHS8072	1STQ008533A0000		1/1
Horizontal shelf	1000	700	PTHS1072	1STQ008534A0000		1/1
Horizontal shelf	400	900	PTHS4092	1STQ008535A0000		1/1
Horizontal shelf	600	900	PTHS6092	1STQ008536A0000		1/1
Horizontal shelf	800	900	PTHS8092	1STQ008537A0000		1/1
Horizontal shelf	1000	900	PTHS1092	1STQ008538A0000		1/1
Horizontal shelf	1250	900	PTHS1292*	1STQ009074A0000		1/1



Front segregation for busbars under the top, on the bottom and at each heights

Front segregation	200	400	PFVS2042	1STQ008539A0000	1/1
Front segregation	200	600	PFVS2062	1STQ008540A0000	1/1
Front segregation	200	800	PFVS2082	1STQ008541A0000	1/1
Front segregation	200	1000	PFVS2012	1STQ008542A0000	1/1
Front segregation	200	1250	PFVS2122	1STQ009075A0000	1/1
Front segregation	300	400	PFVS3042	1STQ008543A0000	1/1
Front segregation	300	600	PFVS3062	1STQ008544A0000	1/1
Front segregation	300	800	PFVS3082	1STQ008545A0000	1/1
Front segregation	300	1000	PFVS3012	1STQ008546A0000	1/1
Front segregation	300	1250	PFVS3122	1STQ009076A0000	1/1




Rear segregation for busbars under the top, on the bottom and at each heights

Rear segregation	200	400	PRVS2040	1STQ008845A0000	1/1
Rear segregation	200	600	PRVS2060	1STQ008855A0000	1/1
Rear segregation	200	800	PRVS2080	1STQ008865A0000	1/1
Rear segregation	200	1000	PRVS2010	1STQ008875A0000	1/1
Rear segregation	200	1250	PRVS2125	1STQ009139A0000	1/1
Rear segregation	300	600	PRVS3060	1STQ008858A0000	1/1
Rear segregation	300	800	PRVS3080	1STQ008868A0000	1/1
Rear segregation	300	1000	PRVS3010	1STQ008878A0000	1/1
Rear segregation	300	1250	PRVS3125	1STQ008884A0000	1/1

Busbars at each heights can be used only for segregation forms different from Form 2b.

Segregation

Order codes - Busbar segregations Form 2b-3b-4a-4b




Horizontal busbar segregation in external cable compartment with intermediate upright

Full-width rear horizontal shelves and front busbar segregations for assembly between intermediate upright and structural rear upright in external cable compartments.

Description	Dimensions (mm)				Pkg/ No. pcs
	H	W	D	Type	
Horizontal shelves for busbars under the top, on the bottom and at each heights					
Horizontal shelf	300	500	PTHS3052	1STQ008555A0000	1/1
Horizontal shelf	300	700	PTHS3072	1STQ008556A0000	1/1
Horizontal shelf	300	900	PTHS3092	1STQ008557A0000	1/1
Horizontal shelf	400	500	PTHS4152	1STQ008558A0000	1/1
Horizontal shelf	400	700	PTHS4172	1STQ008559A0000	1/1
Horizontal shelf	400	900	PTHS4192	1STQ008560A0000	1/1
Front segregation for busbars under the top, on the bottom and at each heights					
Front segregation	200	300	PFVS2132	1STQ008561A0000	1/1
Front segregation	200	400	PFVS2042	1STQ008539A0000	1/1
Front segregation	300	300	PFVS3132	1STQ008563A0000	1/1
Front segregation	300	400	PFVS3042	1STQ008543A0000	1/1
Front rear segregation for busbars under the top or on the bottom					
Rear segregation	200	400	PRVS2040	1STQ008845A0000	1/1

Busbars at each heights can be used only for segregation forms different from Form 2b.



Horizontal busbar segregation in internal cable compartments with intermediate upright


Full-width rear segregation for horizontal busbars. Assembly between intermediate upright and structural rear upright.

Description	Dimensions (mm)				Pkg/ No. pcs
	H	W	D	Type	
Horizontal shelves for busbars under the top, on the bottom and at each heights					
Horizontal shelf	200	500	PTHS2052	1STQ008573A0000	1/1
Horizontal shelf	200	700	PTHS2072	1STQ008574A0000	1/1
Horizontal shelf	200	900	PTHS2092	1STQ008575A0000	1/1
Horizontal shelf	400	500	PTHS4252	1STQ008576A0000	1/1
Horizontal shelf	400	700	PTHS4272	1STQ008577A0000	1/1
Horizontal shelf	400	900	PTHS4292	1STQ008578A0000	1/1
Front rear segregation for busbars under the top or on the bottom					
Front segregation	200	200	PFVS2222	1STQ008579A0000	1/1
Front segregation	200	400	PFVS2242	1STQ008580A0000	1/1
Front segregation	300	200	PFVS3222	1STQ008581A0000	1/1
Front segregation	300	400	PFVS3242	1STQ008582A0000	1/1
Front rear segregation for busbars at each heights					
Front segregation	200	200	PFVS2223	1STQ009082A0000	1/1
Front segregation	200	400	PFVS2243	1STQ009083A0000	1/1
Front segregation	300	200	PFVS3223	1STQ009084A0000	1/1
Front segregation	300	400	PFVS3243	1STQ009085A0000	1/1

Busbars at each heights can be used only for segregation forms different from Form 2b.


Segregation

Order codes - Busbar segregations Form 2b-3b-4a-4b



Lateral segregation for horizontal busbars system

Description	Dimensions (mm)			Pkg/ No. pcs
	H	D	Type	
Horizontal shelves for busbars under the top, on the bottom and at each heights				
Horizontal shelf	200	500	PLLS2050	1STQ001590B0000
Horizontal shelf	200	700	PLLS2070	1STQ001591B0000
Horizontal shelf	200	900	PLLS2090	1STQ001592B0000
Horizontal shelf	300	500	PLLS3050	1STQ001593B0000
Horizontal shelf	300	700	PLLS3070	1STQ001594B0000
Horizontal shelf	300	900	PLLS3090	1STQ001595B0000




Intermediate side and rear upright for assembly of internal kits and segregations

The intermediate upright is the same as the one used for installing the kits and can be assembled both on the side and bottom of the structure. The intermediate upright is necessary for horizontal breakers in Form 3b.

Description	Dimensions (mm)			Pkg/ No. pcs
	H	Type	Order code	
Intermediate upright	1800	PUKI1800	1STQ008039A0000	1/1
Intermediate upright	2000	PUKI2000	1STQ008040A0000	1/1

Segregation


Order codes - Busbar segregations Form 2b-3b-4a-4b



Intermediate crosspiece for rear intermediate uprights

The intermediate crosspiece is necessary only for horizontal breakers in order to assemble terminals segregations when the breakers are installed in the first available position in the structure (under the roof) or in the last available position of the structure (bottom).


Description	Dimensions (mm)			Pkg/ No. pcs
	D	Type	Order code	
Intermediate crosspiece	500	PCIS0500	1STQ009165A0000	1/1
Intermediate crosspiece	700	PCIS0700	1STQ009166A0000	1/1
Intermediate crosspiece	900	PCIS0900	1STQ009167A0000	1/1



Side wall for input side. For blind compartment

To assemble from front upright to intermediate upright.

Description	Dimensions (mm)			Pkg/ No. pcs
	H	Type	Order code	
Side wall for blind compartment	50	PPBS0050	1STQ009168A0000	1/1
Side wall for blind compartment	100	PPBS0100	1STQ009169A0000	1/1
Side wall for blind compartment	150	PPBS0150	1STQ001230B0000	1/1
Side wall for blind compartment	200	PPBS0200	1STQ009170A0000	1/1
Side wall for blind compartment	250	PPBS0250	1STQ009171A0000	1/1
Side wall for blind compartment	300	PPBS0300	1STQ009172A0000	1/1



Horizontal circuit-breaker segregation in structures with intermediate rear upright


Rear vertical segregation with sliding plate at the same height as the circuit-breaker compartment. Assembly between the input and output terminals for horizontal circuit-breakers, from plate to rear intermediate upright.

Description	H	D	Type	Order code	Pkg/ No. pcs
Vertical terminal separator	200	500	PSVS2050	1STQ008727A0000	1/1
Vertical terminal separator	250	500	PSVS2550	1STQ008728A0000	1/1
Vertical terminal separator	300	500	PSVS3050	1STQ008729A0000	1/1
Vertical terminal separator	350	500	PSVS3550	1STQ008730A0000	1/1
Vertical terminal separator	400	500	PSVS4050	1STQ008731A0000	1/1
Vertical terminal separator	500	500	PSVS5050	1STQ008733A0000	1/1
Vertical terminal separator	500	700	PSVS0055*	1STQ009160A0000	1/1
Vertical terminal separator	600	500	PSVS6050	1STQ008734A0000	1/1
Vertical terminal separator	200	700	PSVS2070	1STQ008735A0000	1/1
Vertical terminal separator	250	700	PSVS2570	1STQ008736A0000	1/1
Vertical terminal separator	300	700	PSVS3070	1STQ008737A0000	1/1
Vertical terminal separator	350	700	PSVS3570	1STQ008738A0000	1/1
Vertical terminal separator	400	700	PSVS4070	1STQ008739A0000	1/1
Vertical terminal separator	500	700	PSVS5070	1STQ008741A0000	1/1
Vertical terminal separator	500	900	PSVS0057*	1STQ009161A0000	1/1
Vertical terminal separator	600	700	PSVS6070	1STQ008742A0000	1/1
Vertical terminal separator	200	900	PSVS2090	1STQ008743A0000	1/1
Vertical terminal separator	250	900	PSVS2590	1STQ008744A0000	1/1
Vertical terminal separator	300	900	PSVS3090	1STQ008745A0000	1/1
Vertical terminal separator	350	900	PSVS3590	1STQ008746A0000	1/1
Vertical terminal separator	400	900	PSVS4090	1STQ008747A0000	1/1
Vertical terminal separator	500	900	PSVS5090	1STQ008749A0000	1/1
Vertical terminal separator	600	900	PSVS6090	1STQ008750A0000	1/1

*For Tmax T7 and Emax E1.2 W and W - I

Segregation

Order codes - Busbar segregations Form 2b-3b-4a-4b



Horizontal circuit-breaker segregation in structures with intermediate rear upright (for Tmax T e XT motorized)

Rear vertical segregation with sliding plate at the same height as the circuit-breaker compartment. Assembly between the input and output terminals for horizontal circuit-breakers, from plate to rear intermediate upright.


Description	Kit for installation of Tmax circuit-breakers	Dimensions (mm)			Type	Order code	Pkg/ No. pcs
		H	D				
Vertical terminal separator	XT1-XT2-XT3-XT4 3/4 P MO T4 3/4P F MO T5 3P F MO 400/630A XT2 3P W MO	200	500		PSVS2051	1STQ002056B0000	1/1
	XT1-XT2-XT3-XT4 3/4 P MO T4 3/4P F MO T5 3P F MO 400/630A XT2 3P W MO	200	700		PSVS2071	1STQ002057B0000	1/1
	XT1-XT2-XT3-XT4 3/4 P MO T4 3/4P F MO T5 3P F MO 400/630A XT2 3P W MO	200	900		PSVS2091	1STQ002058B0000	1/1
	T5 3/4P F MO 400/630A XT2 XT4 3/4P W MO	250	500		PSVS2551	1STQ002059B0000	1/1
	T5 3/4P F MO 400/630A XT2 XT4 3/4P W MO	250	700		PSVS2571	1STQ002060B0000	1/1
	T5 3/4P F MO 400/630A XT2 XT4 3/4P W MO	250	900		PSVS2591	1STQ002061B0000	1/1
	T5 3P W MO	300	500		PSVS3051	1STQ002062B0000	1/1
	T5 3P W MO	300	700		PSVS3071	1STQ002063B0000	1/1
	T5 3P W MO	300	900		PSVS3091	1STQ002064B0000	1/1
	T5 3/4P W MO 400A T6 3P W MO	350	500		PSVS3551	1STQ002065B0000	1/1
	T5 3/4P W MO 400A T6 3P W MO	350	700		PSVS3571	1STQ002066B0000	1/1
	T5 3/4P W MO 400A T6 3P W MO	350	900		PSVS3591	1STQ002067B0000	1/1
	T6 3/4P W MO	500	500		PSVS5052	1STQ002379B0000	1/1
	T6 3/4P W MO	500	700		PSVS5072	1STQ002380B0000	1/1
	T6 3/4P W MO	500	900		PSVS5092	1STQ002381B0000	1/1
	T5 3/4P P MO	250	500		PSVS2553	1STQ002382B0000	1/1
	T5 3/4P P MO	250	700		PSVS2573	1STQ002383B0000	1/1
	T5 3/4P P MO	250	900		PSVS2593	1STQ002384B0000	1/1
	T6 3P F MO	300	500		PSVS5053	1STQ002385B0000	1/1
	T6 3P F MO	300	700		PSVS5073	1STQ002386B0000	1/1
	T6 3P F MO	300	900		PSVS5093	1STQ002387B0000	1/1
	T6 3/4P F MO	350	500		PSVS3553	1STQ002388B0000	1/1
	T6 3/4P F MO	350	700		PSVS3573	1STQ002389B0000	1/1
	T6 3/4P F MO	350	900		PSVS3593	1STQ002390B0000	1/1

Key:

- F - MO fixed motor-operated
- P - MO plug-in motor-operated
- W - MO withdrawable motor-operated

Segregation


Order codes - Form 3b segregations



Rear segregation for blind compartment

Rear vertical segregation with plate for blind compartment.

Description	Dimensions (mm)			Pkg/ No. pcs
	H	D	Type	
Rear vertical separator blind compartment	50	500	PSVS0505	1STQ009086A0000
Rear vertical separator blind compartment	100	500	PSVS0105	1STQ009087A0000
Rear vertical separator blind compartment	150	500	PSVS0155	1STQ009088A0000
Rear vertical separator blind compartment	200	500	PSVS0205	1STQ009089A0000
Rear vertical separator blind compartment	250	500	PSVS0255	1STQ009090A0000
Rear vertical separator blind compartment	300	500	PSVS0305	1STQ009091A0000
Rear vertical separator blind compartment	50	700	PSVS0507	1STQ009092A0000
Rear vertical separator blind compartment	100	700	PSVS0107	1STQ009093A0000
Rear vertical separator blind compartment	150	700	PSVS0157	1STQ009094A0000
Rear vertical separator blind compartment	200	700	PSVS0207	1STQ009095A0000
Rear vertical separator blind compartment	250	700	PSVS0257	1STQ009096A0000
Rear vertical separator blind compartment	300	700	PSVS0307	1STQ009097A0000
Rear vertical separator blind compartment	50	900	PSVS0509	1STQ009098A0000
Rear vertical separator blind compartment	100	900	PSVS0109	1STQ009099A0000
Rear vertical separator blind compartment	150	900	PSVS0159	1STQ009100A0000
Rear vertical separator blind compartment	200	900	PSVS0209	1STQ009101A0000
Rear vertical separator blind compartment	250	900	PSVS0259	1STQ009102A0000
Rear vertical separator blind compartment	300	900	PSVS0309	1STQ009103A0000



Segregation for busbar side of horizontal circuit-breaker in structures with intermediate rear upright


Vertical rear bottom segregation with height equal to the compartment height and width equal to the distance between intermediate rear upright and structural rear upright on the busbar side.

Description	Dimensions (mm)			Pkg/ No. pcs
	H	W	Type	
Segregation bottom busbar side	200	400	PRVS2041	1STQ008765A0000
Segregation bottom busbar side	250	400	PRVS2541	1STQ008767A0000
Segregation bottom busbar side	300	400	PRVS3041	1STQ008768A0000
Segregation bottom busbar side	350	400	PRVS3541	1STQ008769A0000
Segregation bottom busbar side	400	400	PRVS4041	1STQ008770A0000
Segregation bottom busbar side	500	400	PRVS5041	1STQ008772A0000
Segregation bottom busbar side	600	400	PRVS6041	1STQ008773A0000
Segregation bottom busbar side	700	400	PRVS7041	1STQ009122A0000
Segregation bottom busbar side	200	600	PRVS2061	1STQ008775A0000
Segregation bottom busbar side	250	600	PRVS2561	1STQ008777A0000
Segregation bottom busbar side	300	600	PRVS3061	1STQ008778A0000
Segregation bottom busbar side	350	600	PRVS3561	1STQ008779A0000
Segregation bottom busbar side	400	600	PRVS4061	1STQ008780A0000
Segregation bottom busbar side	500	600	PRVS5061	1STQ008782A0000
Segregation bottom busbar side	600	600	PRVS6061	1STQ008783A0000
Segregation bottom busbar side	700	600	PRVS7061	1STQ009125A0000
Segregation bottom busbar side	50	800	PRVS0581	1STQ001970B0000
Segregation bottom busbar side	100	800	PRVS0181	1STQ001973B0000
Segregation bottom busbar side	300	800	PRVS3081	1STQ008788A0000
Segregation bottom busbar side	350	800	PRVS3581	1STQ008789A0000
Segregation bottom busbar side	400	800	PRVS4081	1STQ008790A0000
Segregation bottom busbar side	500	800	PRVS5081	1STQ008792A0000
Segregation bottom busbar side	600	800	PRVS6081	1STQ008793A0000
Segregation bottom busbar side	700	800	PRVS7081	1STQ009128A0000

For the closing of consecutive compartments it is possible to use the segregations at each height page 5-44.

Segregation

Order codes - Form 3b segregations




Side segregations for horizontal circuit-breakers in structures with intermediate upright and rear structural upright

Vertical rear side segregation with height equal to circuit-breaker compartment height. Assembly between intermediate upright and rear structural upright. H=800mm or H=1000mm segregations can be used as alternatives. When the installation of the busbars fixing crosspieces is needed with side segregations, use the PBBT0008 fixing brackets.

Description	Dimensions (mm)			Order code	Pkg/ No. pcs
	H	D	Type		
Side compartment segregation	200	500	PLVS2052	1STQ008886A0000	1/1
Side compartment segregation	250	500	PLVS2552	1STQ008888A0000	1/1
Side compartment segregation	300	500	PLVS3052	1STQ008889A0000	1/1
Side compartment segregation	350	500	PLVS3552	1STQ008890A0000	1/1
Side compartment segregation	400	500	PLVS4052	1STQ008891A0000	1/1
Side compartment segregation	500	500	PLVS5052	1STQ008893A0000	1/1
Side compartment segregation	600	500	PLVS6052	1STQ008894A0000	1/1
Side compartment segregation	200	700	PLVS2072	1STQ008896A0000	1/1
Side compartment segregation	250	700	PLVS2572	1STQ008898A0000	1/1
Side compartment segregation	300	700	PLVS3072	1STQ008899A0000	1/1
Side compartment segregation	350	700	PLVS3572	1STQ008900A0000	1/1
Side compartment segregation	400	700	PLVS4072	1STQ008901A0000	1/1
Side compartment segregation	500	700	PLVS5072	1STQ008903A0000	1/1
Side compartment segregation	600	700	PLVS6072	1STQ008904A0000	1/1
Side compartment segregation	200	900	PLVS2092	1STQ008906A0000	1/1
Side compartment segregation	250	900	PLVS2592	1STQ008908A0000	1/1
Side compartment segregation	300	900	PLVS3092	1STQ008909A0000	1/1
Side compartment segregation	350	900	PLVS3592	1STQ008910A0000	1/1
Side compartment segregation	400	900	PLVS4092	1STQ008911A0000	1/1
Side compartment segregation	500	900	PLVS5092	1STQ008913A0000	1/1
Side compartment segregation	600	900	PLVS6092	1STQ008914A0000	1/1

For the closing of consecutive compartments it is possible to use the segregations at each height page 5-44.




Vertical circuit-breaker segregation in structures with or without intermediate rear upright

Horizontal rear segregation to fix behind plate as wide as the structure. In sheet metal for moulded-case Tmax T, XT and E1.2 fixed circuit-breakers. Useful for separating the terminals in vertical circuit-breakers. Pre-engineered for the presence/absence of an intermediate rear upright.

Description	Dimensions (mm)			Order code	Pkg/ No. pcs
	W	D	Type		
Horizontal terminal separator	400	500	PSHS4050	1STQ008751A0000	1/1
Horizontal terminal separator	600	500	PSHS6050	1STQ008752A0000	1/1
Horizontal terminal separator	800	500	PSHS8050	1STQ008753A0000	1/1
Horizontal terminal separator	400	700	PSHS4070	1STQ008755A0000	1/1
Horizontal terminal separator	600	700	PSHS6070	1STQ008756A0000	1/1
Horizontal terminal separator	800	700	PSHS8070	1STQ008757A0000	1/1
Horizontal terminal separator	400	900	PSHS4090	1STQ008759A0000	1/1
Horizontal terminal separator	600	900	PSHS6090	1STQ008760A0000	1/1
Horizontal terminal separator	800	900	PSHS8090	1STQ008761A0000	1/1

Segregation

Order codes - Form 3b segregations



Segregation in Lexan for SACE Emax2 vertical circuit-breakers in structures with or without intermediate upright

Emax 2 circuit-breaker	Version	Dimensions (mm)			Type	Order code	Pkg/ No. pcs
		H	W				
E1.2	W	600	500		PSHW6051 ⁽¹⁾	1STQ009031A0000	1/1
E1.2	W	600	700		PSHW6071 ⁽¹⁾	1STQ009032A0000	1/1
E1.2	W	600	900		PSHW6091	1STQ009917A0000	1/1
E1.2	W	800	500		PSHW8051 ⁽¹⁾	1STQ009033A0000	1/1
E1.2	W	800	700		PSHW8071 ⁽¹⁾	1STQ009034A0000	1/1
E1.2	W	800	900		PSHW8091	1STQ009918A0000	1/1
E2.2	F	600	700		PSHF6072	1STQ009035A0000	1/1
E2.2	F	600	900		PSHF6092	1STQ009036A0000	1/1
E2.2	F	800	700		PSHF8072	1STQ009037A0000	1/1
E2.2	F	800	900		PSHF8092	1STQ009038A0000	1/1
E2.2	W	600	700		PSHW6072	1STQ009039A0000	1/1
E2.2	W	600	900		PSHW6092	1STQ009040A0000	1/1
E2.2	W	800	700		PSHW8072	1STQ009041A0000	1/1
E2.2	W	800	900		PSHW8092	1STQ009042A0000	1/1
E2.2	W	1250	900		PSHW1292	1STQ004227B0000	1/1
E4.2	F	600	700		PSHF6072	1STQ009035A0000	1/1
E4.2	F	600	900		PSHF6092	1STQ009036A0000	1/1
E4.2	F	800	700		PSHF8072	1STQ009037A0000	1/1
E4.2	F	800	900		PSHF8092	1STQ009038A0000	1/1
E4.2	W	600	700		PSHW6074	1STQ009047A0000	1/1
E4.2	W	600	900		PSHW6094	1STQ009048A0000	1/1
E4.2	W	800	700		PSHW8074	1STQ009049A0000	1/1
E4.2	W	800	900		PSHW8094	1STQ009050A0000	1/1
E6.2	F	1000	900		PSHF1096	1STQ009051A0000	1/1
E6.2	F	1250	900		PSHF1296	1STQ009052A0000	1/1
E6.2	W	1000	900		PSHW1096	1STQ009053A0000	1/1
E6.2	W	1250	900		PSHW1296	1STQ009054A0000	1/1

⁽¹⁾ Also suitable for vertical T7 withdrawable and withdrawable interlocked.

Segregation in Lexan for the SACE Emax 2 circuit-breaker for space-saving column W=400mm


Emax 2 circuit-breaker	Version	Dimensions (mm)			Type	Order code	Pkg/ No. pcs
		D	W				
Vertical circuit-breakers							
E1.2	W	500	400		PSHW4051	1STQ001571B0000	1/1
E1.2	W	700	400		PSHW4071	1STQ001572B0000	1/1
E1.2	W	900	400		PSHW4091	1STQ001573B0000	1/1
E2.2	F	700	400		PSHF4072	1STQ001574B0000	1/1
E2.2	F	900	400		PSHF4092	1STQ001575B0000	1/1
E2.2	W	700	400		PSHW4072	1STQ001576B0000	1/1
E2.2	W	900	400		PSHW4092	1STQ001577B0000	1/1

Key:

F fixed
W withdrawable

Segregation

Order codes - Form 3b segregations




Vertical circuit-breaker segregation (segregation on busbar side) for fixed/ interlocked T5, T6, T7 and E1.2 in structures with intermediate rear uprights

Vertical rear bottom segregation with height equal to half the compartment height and width equal to the distance between intermediate rear upright and structural rear upright on the busbar side.

Description	Dimensions (mm)			Pkg/ No. pcs
	H	W	Type	
Segregation on bottom busbar side	175	400	PRVS1741	1STQ008764A0000
Segregation on bottom busbar side	200	400	PRVS2041	1STQ008765A0000
Segregation on bottom busbar side	225	400	PRVS2241	1STQ008766A0000
Segregation on bottom busbar side	300	400	PRVS3041	1STQ008768A0000
Segregation on bottom busbar side	175	600	PRVS1761	1STQ008774A0000
Segregation on bottom busbar side	200	600	PRVS2061	1STQ008775A0000
Segregation on bottom busbar side	225	600	PRVS2261	1STQ008776A0000
Segregation on bottom busbar side	250	600	PRVS2561	1STQ008777A0000
Segregation on bottom busbar side	300	600	PRVS3061	1STQ008778A0000
Segregation on bottom busbar side	175	800	PRVS1781	1STQ008784A0000
Segregation on bottom busbar side	200	800	PRVS2081	1STQ008785A0000
Segregation on bottom busbar side	225	800	PRVS2251	1STQ008786A0000
Segregation on bottom busbar side	250	800	PRVS2581	1STQ008787A0000
Segregation on bottom busbar side	300	800	PRVS3081	1STQ008788A0000

For the closing of consecutive compartments it is possible to use the segregations at each height page 5-44.



Vertical circuit-breaker segregation (segregation on busbar side) for Emax air circuit-breakers in structures with intermediate rear uprights


Vertical rear bottom segregation with height equal to half the compartment height and width equal to the distance between intermediate rear upright and structural rear upright on the busbar side.

Description	Dimensions (mm)			Pkg/ No. pcs
	H	W	Type	
Segregation on bottom busbar side	300	400	PRVS3041	1STQ008768A0000
Segregation on bottom busbar side	250	600	PRVS2561	1STQ008777A0000
Segregation on bottom busbar side	300	600	PRVS3061	1STQ008778A0000
Segregation on bottom busbar side	250	800	PRVS2581	1STQ008787A0000
Segregation on bottom busbar side	300	800	PRVS3081	1STQ008788A0000

For the closing of consecutive compartments it is possible to use the segregations at each height page 5-44.

Segregation

Order codes - Form 3b segregations




Vertical circuit-breaker segregation (segregation on output side) for fixed/ interlocked T5, T6, T7 and E1.2 in structures with intermediate rear uprights

Vertical rear bottom segregation with height equal to half the compartment height and width equal to the distance between intermediate rear upright and structural rear upright on the output side.

Description	Dimensions (mm)				Pkg/ No. pcs
	H	W	Type	Order code	
Segregation on bottom output side	175	600	PRVS1762	1STQ008814A0000	1/1
Segregation on bottom output side	200	600	PRVS2062	1STQ008815A0000	1/1
Segregation on bottom output side	225	600	PRVS2262	1STQ008816A0000	1/1
Segregation on bottom output side	250	600	PRVS2562	1STQ008817A0000	1/1
Segregation on bottom output side	175	800	PRVS1782	1STQ008824A0000	1/1
Segregation on bottom output side	200	800	PRVS2082	1STQ008825A0000	1/1
Segregation on bottom output side	225	800	PRVS2282	1STQ008826A0000	1/1
Segregation on bottom output side	250	800	PRVS2582	1STQ008827A0000	1/1

For the closing of consecutive compartments it is possible to use the segregations at each height page 5-44.



Vertical circuit-breaker segregation (segregation on output side) for SACE Emax 2 air circuit-breakers in structures with intermediate rear uprights


Vertical rear bottom segregation with height equal to half the compartment height and width equal to the distance between intermediate rear upright and structural rear upright on the output side.

Description	Dimensions (mm)				Pkg/ No. pcs
	H	W	Type	Order code	
Segregation on bottom output side	250	600	PRVS2562	1STQ008817A0000	1/1
Segregation on bottom output side	300	600	PRVS3062	1STQ008818A0000	1/1
Segregation on bottom output side	250	800	PRVS2582	1STQ008827A0000	1/1
Segregation on bottom output side	300	800	PRVS3082	1STQ008828A0000	1/1

For the closing of consecutive compartments it is possible to use the segregations at each height page 5-44.


Segregation

Order codes - Form 3b segregations




Vertical rear segregation in structures with intermediare rear upright

Description	Dimensions (mm)		Type	Order code	Pkg/ No. pcs
	H	W			
BUSBAR SIDE					
Segregation bottom busbar side	50	400	PRVS0541	1STQ001968B0000	1/1
Segregation bottom busbar side	100	400	PRVS0141	1STQ001971B0000	1/1
Segregation bottom busbar side	150	400	PRVS1541	1STQ001974B0000	1/1
Segregation bottom busbar side	50	600	PRVS0561	1STQ001969B0000	1/1
Segregation bottom busbar side	100	600	PRVS0161	1STQ001972B0000	1/1
Segregation bottom busbar side	150	600	PRVS1561	1STQ001975B0000	1/1
Segregation bottom busbar side	50	800	PRVS0581	1STQ001970B0000	1/1
Segregation bottom busbar side	100	800	PRVS0181	1STQ001973B0000	1/1
Segregation bottom busbar side	150	800	PRVS1581	1STQ001976B0000	1/1
OUTPUT SIDE					
Segregation on bottom output side	50	600	PRVS0562	1STQ001978B0000	1/1
Segregation on bottom output side	50	800	PRVS0582	1STQ001979B0000	1/1
Segregation on bottom output side	100	600	PRVS0162	1STQ001981B0000	1/1
Segregation on bottom output side	100	800	PRVS0182	1STQ001982B0000	1/1
Segregation on bottom output side	150	600	PRVS1562	1STQ001984B0000	1/1
Segregation on bottom output side	150	800	PRVS1582	1STQ001985B0000	1/1




Vertical rear segregation in structure without intermediate rear upright

Description	Dimensions (mm)		Type	Order code	Pkg/ No. pcs
	H	W			
Full-width vertical segregation on bottom					
Full-width vertical segregation on bottom	50	600	PRVS0560	1STQ001996B0000	1/1
Full-width vertical segregation on bottom	100	800	PRVS1008	1STQ002000B0000	1/1
Full-width vertical segregation on bottom	150	600	PRVS1560	1STQ002002B0000	1/1
Full-width vertical segregation on bottom	50	800	PRVS0580	1STQ001997B0000	1/1
Full-width vertical segregation on bottom	100	600	PRVS1006	1STQ001999B0000	1/1
Full-width vertical segregation on bottom	150	800	PRVS1580	1STQ002003B0000	1/1
Full-width vertical segregation on bottom	50	400	PRVS0582	1STQ001979B0000	1/1
Full-width vertical segregation on bottom	100	400	PRVS0182	1STQ001982B0000	1/1
Full-width vertical segregation on bottom	150	400	PRVS1582	1STQ001985B0000	1/1




Lateral segregation in structure with intermediate upright

Description	Dimensions (mm)		Type	Order code	Pkg/ No. pcs
	H	W			
Side compartment segregation					
Side compartment segregation	50	500	PLVS0552	1STQ001986B0000	1/1
Side compartment segregation	50	700	PLVS0572	1STQ001987B0000	1/1
Side compartment segregation	50	900	PLVS0592	1STQ001988B0000	1/1
Side compartment segregation	100	500	PLVS1052	1STQ001989B0000	1/1
Side compartment segregation	100	700	PLVS1072	1STQ001990B0000	1/1
Side compartment segregation	100	900	PLVS1092	1STQ001991B0000	1/1
Side compartment segregation	150	500	PLVS1552	1STQ001992B0000	1/1
Side compartment segregation	150	700	PLVS1572	1STQ001993B0000	1/1
Side compartment segregation	150	900	PLVS1592	1STQ001994B0000	1/1



Segregation

Order codes - Form 3b segregations




Segregation for vertical fixed/interlocked T5, T6, T7 and E1.2 circuit-breakers in structures without intermediate upright.

Vertical rear bottom segregation with height equal to half the compartment height and full-width.

Description	Dimensions (mm)		Type	Order code	Pkg/ No. pcs
	H	W			
Full-width segregation on bottom	175	400	PRVS1740	1STQ008844A0000	1/1
Full-width segregation on bottom	200	400	PRVS2040	1STQ008845A0000	1/1
Full-width segregation on bottom	225	400	PRVS2240	1STQ008846A0000	1/1
Full-width segregation on bottom	175	600	PRVS1760	1STQ008854A0000	1/1
Full-width segregation on bottom	200	600	PRVS2060	1STQ008855A0000	1/1
Full-width segregation on bottom	225	600	PRVS2260	1STQ008856A0000	1/1
Full-width segregation on bottom	250	600	PRVS2560	1STQ008857A0000	1/1
Full-width segregation on bottom	300	600	PRVS3060	1STQ008858A0000	1/1
Full-width segregation on bottom	175	800	PRVS1780	1STQ008864A0000	1/1
Full-width segregation on bottom	200	800	PRVS2080	1STQ008865A0000	1/1
Full-width segregation on bottom	225	800	PRVS2280	1STQ008866A0000	1/1
Full-width segregation on bottom	250	800	PRVS2580	1STQ008867A0000	1/1
Full-width segregation on bottom	300	800	PRVS3080	1STQ008868A0000	1/1
Full-width segregation on bottom	175	1000	PRVS1710	1STQ008874A0000	1/1
Full-width segregation on bottom	200	1000	PRVS2010	1STQ008875A0000	1/1
Full-width segregation on bottom	225	1000	PRVS2210	1STQ008876A0000	1/1
Full-width segregation on bottom	250	1000	PRVS2510	1STQ008877A0000	1/1
Full-width segregation on bottom	350	1000	PRVS3510	1STQ008879A0000	1/1
Full-width segregation on bottom	200	1250	PRVS2125	1STQ009139A0000	1/1
Full-width segregation on bottom	250	1250	PRVS2512	1STQ008837A0000	1/1

For the closing of consecutive compartments it is possible to use the segregations at each height page 5-44.



Segregation for SACE Emax2 vertical air circuit-breakers in structures without intermediate rear upright


Vertical rear bottom segregation with height equal to half the compartment height and full-width.

Description	Dimensions (mm)		Type	Order code	Pkg/ No. pcs
	H	W			
Full-width vertical segregation on bottom	250	600	PRVS2560	1STQ008857A0000	1/1
Full-width vertical segregation on bottom	300	600	PRVS3060	1STQ008858A0000	1/1
Full-width vertical segregation on bottom	250	800	PRVS2580	1STQ008867A0000	1/1
Full-width vertical segregation on bottom	300	800	PRVS3080	1STQ008868A0000	1/1
Full-width vertical segregation on bottom	250	1000	PRVS2510	1STQ008877A0000	1/1
Full-width vertical segregation on bottom	300	1000	PRVS3010	1STQ008878A0000	1/1
Full-width vertical segregation on bottom	350	1000	PRVS3510	1STQ008879A0000	1/1
Full-width vertical segregation on bottom	250	1250	PRVS2512	1STQ008837A0000	1/1
Full-width vertical segregation on bottom	300	1250	PRVS3125	1STQ008884A0000	1/1
Full-width vertical segregation on bottom	350	1250	PRVS3501	1STQ009141A0000	1/1

For the closing of consecutive compartments it is possible to use the segregations at each height page 5-44.

Segregation

Order codes - Form 3b segregations




Segregation for vertical fixed/interlocked T5, T6, T7 and E1.2 circuit-breakers with intermediate upright and structural rear upright.

Vertical side segregation with height equal to half the circuit-breaker compartment height. Assembly between intermediate upright and structural rear upright. H=800mm or H=1000mm segregations can be used.

Description	Dimensions (mm)			Pkg/ No. pcs
	H	W	Type	
Side compartment segregation	175	500	PLVS1752	1STQ008885A0000
Side compartment segregation	200	500	PLVS2052	1STQ008886A0000
Side compartment segregation	225	500	PLVS2252	1STQ008887A0000
Side compartment segregation	250	500	PLVS2552	1STQ008888A0000
Side compartment segregation	175	700	PLVS1772	1STQ008895A0000
Side compartment segregation	200	700	PLVS2072	1STQ008896A0000
Side compartment segregation	225	700	PLVS2272	1STQ008897A0000
Side compartment segregation	250	700	PLVS2572	1STQ008898A0000
Side compartment segregation	175	900	PLVS1792	1STQ008905A0000
Side compartment segregation	200	900	PLVS2092	1STQ008906A0000
Side compartment segregation	225	900	PLVS2292	1STQ008907A0000
Side compartment segregation	250	900	PLVS2592	1STQ008908A0000

For the closing of consecutive compartments it is possible to use the segregations at each height page 5-44.



Segregation for SACE Emax2 vertical air circuit-breakers in structures without intermediate rear upright


Vertical side segregation with height equal to half the circuit-breaker compartment height. Assembly between intermediate upright and rear structural upright. H=800mm or H=1000mm segregations can be used.

Description	Dimensions (mm)			Pkg/ No. pcs
	H	W	Type	
Side compartment segregation	250	500	PLVS2552	1STQ008888A0000
Side compartment segregation	300	500	PLVS3052	1STQ008889A0000
Side compartment segregation	350	500	PLVS3552	1STQ008890A0000
Side compartment segregation	250	700	PLVS2572	1STQ008898A0000
Side compartment segregation	300	700	PLVS3072	1STQ008899A0000
Side compartment segregation	350	700	PLVS3572	1STQ008900A0000
Side compartment segregation	250	900	PLVS2592	1STQ008908A0000
Side compartment segregation	300	900	PLVS3092	1STQ008909A0000
Side compartment segregation	350	900	PLVS3592	1STQ008910A0000

For the closing of consecutive compartments it is possible to use the segregations at each height page 5-44.

Segregation


Order codes - Form 3b segregations



Vertical segregations at each height

To be used in alternative to (rear and side) cells vertical segregations, with different breakers combined together up to H=700-800-1000mm.

Description	Dimensions (mm)				Pkg/ No. pcs
	H	W	D	Type	
Vertical segregations at each height busbars side					
Segregation at each height busbars side	700	400		PRVS7041	1STQ009122A0000
Segregation at each height busbars side	800	400		PRVS8041	1STQ009123A0000
Segregation at each height busbars side	1000	400		PRVS1041	1STQ009124A0000
Segregation at each height busbars side	700	600		PRVS7061	1STQ009125A0000
Segregation at each height busbars side	800	600		PRVS8061	1STQ009126A0000
Segregation at each height busbars side	1000	600		PRVS1061	1STQ009127A0000
Segregation at each height busbars side	700	800		PRVS7081	1STQ009128A0000
Segregation at each height busbars side	800	800		PRVS8081	1STQ009129A0000
Segregation at each height busbars side	1000	800		PRVS1081	1STQ009130A0000
Vertical side segregations at each height					
Side segregation at each height	700	500		PLVS7052	1STQ009131A0000
Side segregation at each height	800	500		PTBS8052	1STQ008521A0000
Side segregation at each height	1000	500		PTBS1052	1STQ008522A0000
Side segregation at each height	700	700		PLVS7072	1STQ009132A0000
Side segregation at each height	800	700		PTBS8072	1STQ008523A0000
Side segregation at each height	1000	700		PTBS1072	1STQ008524A0000
Side segregation at each height	700	900		PLVS7092	1STQ009133A0000
Side segregation at each height	800	900		PTBS8091	1STQ008525A0000
Side segregation at each height	1000	900		PTVB1091	1STQ008526A0000




Vertical circuit-breaker segregation in structures with intermediate rear upright

Vertical rear segregation 700/800/1000mm in height and width equal to the distance between intermediate upright and structural rear upright on the output side.

Description	Dimensions (mm)				Pkg/ No. pcs
	H	W	Type	Order code	
Rear segregation output side	700	600	PRVS7062	1STQ009104A0000	1/1
Rear segregation output side	800	600	PRVS8062	1STQ009105A0000	1/1
Rear segregation output side	1000	600	PRVS1062	1STQ009106A0000	1/1
Rear segregation output side	700	800	PRVS7082	1STQ009107A0000	1/1
Rear segregation output side	800	800	PRVS8082	1STQ009108A0000	1/1
Rear segregation output side	1000	800	PRVS1082	1STQ009109A0000	1/1

Segregation


Order codes - Form 3b segregations



Full-width vertical segregation on bottom

Full-width vertical rear segregation on bottom for structures without intermediate rear upright.


Description	Dimensions (mm)		Type	Order code	Pkg/ No. pcs
	H	W			
Full-width segregation on bottom	700	400	PRVS7040	1STQ009110A0000	1/1
Full-width segregation on bottom	800	400	PRVS8040	1STQ009111A0000	1/1
Full-width segregation on bottom	1000	400	PRVS1040	1STQ009112A0000	1/1
Full-width segregation on bottom	700	600	PRVS7060	1STQ009113A0000	1/1
Full-width segregation on bottom	800	600	PRVS8060	1STQ009114A0000	1/1
Full-width segregation on bottom	1000	600	PRVS1060	1STQ009115A0000	1/1
Full-width segregation on bottom	700	800	PRVS7080	1STQ009116A0000	1/1
Full-width segregation on bottom	800	800	PRVS8080	1STQ009117A0000	1/1
Full-width segregation on bottom	1000	800	PRVS1080	1STQ009118A0000	1/1
Full-width segregation on bottom	700	1000	PRVS7010	1STQ009119A0000	1/1
Full-width segregation on bottom	800	1000	PRVS8010	1STQ009120A0000	1/1
Full-width segregation on bottom	1000	1000	PRVS1010	1STQ009121A0000	1/1



Internal door for internal cable compartment – Pickled steel sheet


Internal door in pickled steel sheet for cable compartment IP30.

Description	Dimensions (mm)		Type	Order code	Pkg/ No. pcs
	H	W			
Blind door for internal cable compartment	1800	200	PDCB1820	1STQ007753A0000	1/1
Blind door for internal cable compartment	1800	400	PDCB1840	1STQ007754A0000	1/1
Blind door for internal cable compartment	2000	200	PDCB2020	1STQ007755A0000	1/1
Blind door for internal cable compartment	2000	400	PDCB2040	1STQ007756A0000	1/1



Vertical front segregation for internal cable compartment

Description	Dimensions (mm)		Type	Order code	Pkg/ No. pcs
	H	W			
Vertical front segregation	1800	200	PFBS8020	1STQ001481B0000	1/1
Vertical front segregation	1800	400	PFBS8040	1STQ001483B0000	1/1
Vertical front segregation	2000	200	PFBS1020	1STQ001482B0000	1/1
Vertical front segregation	2000	400	PFBS1040	1STQ001484B0000	1/1




Vertical segregation at intermediate upright in internal cable container

Description	Dimensions (mm)		Type	Order code	Pkg/ No. pcs
	H	W			
Vertical front segregation	1800	200	PFBS8021	1STQ002068B0000	1/1
Vertical front segregation	2000	200	PFBS1021	1STQ002069B0000	1/1
Vertical front segregation	1800	400	PFBS8041	1STQ002070B0000	1/1
Vertical front segregation	2000	400	PFBS1041	1STQ002071B0000	1/1

Segregation

Order codes - Form 3b segregations



Internal door for external cable compartment – Pickled steel sheet

Internal door in pickled steel sheet for cable compartment IP30.

Description	Dimensions (mm)			Pkg/ No. pcs
	H	W	Type	
Blind door for external cable compartment	1800	300	PDCB1830	1STQ008086A0000
Blind door for external cable compartment	1800	400	PDCB1844	1STQ008087A0000
Blind door for external cable compartment	2000	300	PDCB2030	1STQ008088A0000
Blind door for external cable compartment	2000	400	PDCB2044	1STQ008089A0000



Vertical front segregation for external cable compartment

To be used in IP3X protections degree enclosures Form 2a-3a or in segregated enclosures from Form 3b.

Description	Dimensions (mm)			Pkg/ No. pcs
	H	W	Type	
Vertical front segregation	1800	300	PFVS8030	1STQ001485B0000
Vertical front segregation	1800	400	PFVS8040	1STQ001487B0000
Vertical front segregation	2000	300	PFVS1030	1STQ001486B0000
Vertical front segregation	2000	400	PFVS1040	1STQ001488B0000




Vertical segregation at intermediate upright in external cable container

Description	Dimensions (mm)			Pkg/ No. pcs
	H	W	Type	
Vertical front segregation	1800	300	PFVS8032	1STQ002072B0000
Vertical front segregation	1800	400	PFVS8042	1STQ002073B0000
Vertical front segregation	2000	300	PFVS1032	1STQ002074B0000
Vertical front segregation	2000	400	PFVS1042	1STQ002075B0000

Segregation


Order codes - Form 3b segregations



vertical rear internal segregation

Blind rear vertical segregation for internal cable compartment.


Description	Dimensions (mm)			Pkg/ No. pcs
	H	W	Type	
Vertical rear segregation	800	200	PRBS8220	1STQ008915A0000
Vertical rear segregation	1000	200	PRBS1220	1STQ008916A0000
Vertical rear segregation	800	400	PRBS8240	1STQ008919A0000
Vertical rear segregation	1000	400	PRBS1240	1STQ008920A0000



vertical rear internal segregation

Blind rear vertical segregation for external cable compartment.

Description	Dimensions (mm)			Pkg/ No. pcs
	H	W	Type	
Vertical rear segregation	800	300	PRVS8062	1STQ009105A0000
Vertical rear segregation	1000	300	PRVS1062	1STQ009106A0000
Vertical rear segregation	800	400	PRVS8040	1STQ009111A0000
Vertical rear segregation	1000	400	PRVS1040	1STQ009112A0000



Side segregation for external cable compartment


Blind side segregation for external cable compartment.

Description	Dimensions (mm)			Pkg/ No. pcs
	H	W	Type	
Vertical side segregation	700	500	PLVS7052	1STQ009131A0000
Vertical side segregation	800	500	PTBS8052	1STQ008521A0000
Vertical side segregation	1000	500	PTBS1052	1STQ008522A0000
Vertical side segregation	700	700	PLVS7072	1STQ009132A0000
Vertical side segregation	800	700	PTBS8072	1STQ008523A0000
Vertical side segregation	1000	700	PTBS1072	1STQ008524A0000
Vertical side segregation	700	900	PLVS7092	1STQ009133A0000
Vertical side segregation	800	900	PTBS8091	1STQ008525A0000
Vertical side segregation	1000	900	PTVB1091	1STQ008526A0000

Codes PLVS...pag.5-37 can also be mounted here.

Segregation

Order codes - Form 4b segregations




Intermediate side and rear upright for assembly of internal kits and segregations

The intermediate upright is the same as the one used for installing the kits and can be assembled both on the side and bottom of the structure. The rear intermediate upright is necessary in order to mount the segregations for horizontal breakers.

Description	Dimensions (mm)			Pkg/ No. pcs
	H	Type	Order code	
Intermediate upright	1800	PUKI1800	1STQ008039A0000	1/1
Intermediate upright	2000	PUKI2000	1STQ008040A0000	1/1

Use universal vertical shelf PSHS.... for each compartment in order to reach Form 4b.




Position P0

Choice of segregation to suit depth of circuit-breaker

For segregation 4b, choose kits corresponding to the depth of each circuit-breaker in the required version, as indicated in the tables below.

Horizontal circuit-breakers with front terminals

Circuit-breaker version	XT1	XT2	XT3	XT4	T4	T5	T6	T7	E1.2
Fixed	P0	P0	P0	P0	P0	P0	P0	P0	P0
Fixed with direct crank handle (RHD)	P0	P0	P0	P0	P0	P0	P0	P0	
Fixed with motor operator (MO)	P0	P0	P0	P0				P0	
Fixed interlocked	P0	P0	P0	P0	P0	P0	P0	P0	P0
Fixed interlocked motor-operated								P0	



Position P1

Horizontal circuit-breakers with rear terminals

Circuit-breaker version	XT1	XT2	XT3	XT4	T4	T5	T6	T7	E1.2
Fixed	P0	P0	P0	P0	P1	P1	P1	P1	P1
Fixed with direct crank handle (RHD)	P1	P1	P1	P1	P1	P1	P1	P1	
Fixed with motor operator (MO)	P1	P1	P1	P1				P1	
Fixed interlocked								P1	
Fixed interlocked motor-operated								P1	
Plug-in	P0	P1	P1	P1			P1		
Plug-in with direct crank handle (RHD)	P1	P1	P1	P1			P1		
Plug-in with motor operator (MO)									
Plug-in interlocked									
Plug-in interlocked motor-operated									
Withdrawable		P1			P1		P1	P1	■ ■
Withdrawable with direct crank handle (RHD)		P1			P1		P1	P1	■ ■
Withdrawable with motor operator (MO)									
Withdrawable interlocked									
Withdrawable interlocked motor-operated									


■ See codes on page 6/16.

Position P2

The P2 segregations can replace the P0 and P1 segregation in order to obtain more useful space available inside the compartment.

Segregation

Order codes - Form 4b segregations




Position P0

Segregation for horizontal circuit-breakers in position 0

Sheet metal corner piece to fix to separator PSVS.... With vertical Lexan panel at compartment height.

Description	Assembly position	Dimensions (mm)			Order code	Pkg/ No. pcs
		H	W	Type		
Corner piece and panel in Lexan	P0	200	400	PCVS0204	1STQ008931A0000	1/1
Corner piece and panel in Lexan	P0	250	400	PCVS0254	1STQ008932A0000	1/1
Corner piece and panel in Lexan	P0	300	400	PCVS0304	1STQ008933A0000	1/1
Corner piece and panel in Lexan	P0	350	400	PCVS0354	1STQ008934A0000	1/1
Corner piece and panel in Lexan	P0	400	400	PCVS0404	1STQ008935A0000	1/1
Corner piece and panel in Lexan	P0	500	400	PCVS0504	1STQ008937A0000	1/1
Corner piece and panel in Lexan	P0	600	400	PCVS0604	1STQ008938A0000	1/1
Corner piece and panel in Lexan	P0	200	600	PCVS0206	1STQ008939A0000	1/1
Corner piece and panel in Lexan	P0	250	600	PCVS0256	1STQ008940A0000	1/1
Corner piece and panel in Lexan	P0	300	600	PCVS0306	1STQ008941A0000	1/1
Corner piece and panel in Lexan	P0	350	600	PCVS0356	1STQ008942A0000	1/1
Corner piece and panel in Lexan	P0	400	600	PCVS0406	1STQ008943A0000	1/1
Corner piece and panel in Lexan	P0	500	600	PCVS0506	1STQ008945A0000	1/1
Corner piece and panel in Lexan	P0	600	600	PCVS0606	1STQ008946A0000	1/1
Corner piece and panel in Lexan	P0	200	800	PCVS0208	1STQ008947A0000	1/1
Corner piece and panel in Lexan	P0	250	800	PCVS0258	1STQ008948A0000	1/1
Corner piece and panel in Lexan	P0	300	800	PCVS0308	1STQ008949A0000	1/1
Corner piece and panel in Lexan	P0	350	800	PCVS0358	1STQ008950A0000	1/1
Corner piece and panel in Lexan	P0	400	800	PCVS0408	1STQ008951A0000	1/1
Corner piece and panel in Lexan	P0	500	800	PCVS0508	1STQ008953A0000	1/1
Corner piece and panel in Lexan	P0	600	800	PCVS0608	1STQ008954A0000	1/1



Position P1


Segregation for horizontal circuit-breakers in position 1

Sheet metal corner piece to fix on separator PSVS.... With vertical Lexan panel at compartment height, horizontal shelf and side wall.

Description	Assembly position	Dimensions (mm)			Order code	Pkg/ No. pcs
		H	W	Type		
Rear cubicle	P1	200	400	PCVS1204	1STQ008963A0000	1/1
Rear cubicle	P1	250	400	PCVS1254	1STQ008964A0000	1/1
Rear cubicle	P1	300	400	PCVS1304	1STQ008965A0000	1/1
Rear cubicle	P1	350	400	PCVS1354	1STQ008966A0000	1/1
Rear cubicle	P1	400	400	PCVS1404	1STQ008967A0000	1/1
Rear cubicle	P1	500	400	PCVS1504	1STQ008969A0000	1/1
Rear cubicle	P1	600	400	PCVS1604	1STQ008970A0000	1/1
Rear cubicle	P1	200	600	PCVS1206	1STQ008971A0000	1/1
Rear cubicle	P1	250	600	PCVS1256	1STQ008972A0000	1/1
Rear cubicle	P1	300	600	PCVS1306	1STQ008973A0000	1/1
Rear cubicle	P1	350	600	PCVS1356	1STQ008974A0000	1/1
Rear cubicle	P1	400	600	PCVS1406	1STQ008975A0000	1/1
Rear cubicle	P1	500	600	PCVS1506	1STQ008977A0000	1/1
Rear cubicle	P1	600	600	PCVS1606	1STQ008978A0000	1/1
Rear cubicle	P1	200	800	PCVS1208	1STQ008979A0000	1/1
Rear cubicle	P1	250	800	PCVS1258	1STQ008980A0000	1/1
Rear cubicle	P1	300	800	PCVS1308	1STQ008981A0000	1/1
Rear cubicle	P1	350	800	PCVS1358	1STQ008982A0000	1/1
Rear cubicle	P1	400	800	PCVS1408	1STQ008983A0000	1/1
Rear cubicle	P1	500	800	PCVS1508	1STQ008985A0000	1/1
Rear cubicle	P1	600	800	PCVS1608	1STQ008986A0000	1/1

Segregation

Order codes - Form 4b segregations




Segregation for horizontal circuit-breakers in position 2

Sheet metal corner piece to fix on separator PSVS.... With vertical Lexan panel at compartment height, horizontal shelf and side wall.

Description	Assembly position	Dimensions (mm)		Type	Order code	Pkg/ No. pcs
		H	W			
Rear cubicle	P2	200	400	PCVS2204	1STQ008995A0000	1/1
Rear cubicle	P2	250	400	PCVS2254	1STQ008996A0000	1/1
Rear cubicle	P2	300	400	PCVS2304	1STQ008997A0000	1/1
Rear cubicle	P2	350	400	PCVS2354	1STQ008998A0000	1/1
Rear cubicle	P2	400	400	PCVS2404	1STQ008999A0000	1/1
Rear cubicle	P2	500	400	PCVS2504	1STQ009001A0000	1/1
Rear cubicle	P2	600	400	PCVS2604	1STQ009002A0000	1/1
Rear cubicle	P2	200	600	PCVS2206	1STQ009003A0000	1/1
Rear cubicle	P2	250	600	PCVS2256	1STQ009004A0000	1/1
Rear cubicle	P2	300	600	PCVS2306	1STQ009005A0000	1/1
Rear cubicle	P2	350	600	PCVS2356	1STQ009006A0000	1/1
Rear cubicle	P2	400	600	PCVS2406	1STQ009007A0000	1/1
Rear cubicle	P2	500	600	PCVS2506	1STQ009009A0000	1/1
Rear cubicle	P2	600	600	PCVS2606	1STQ009010A0000	1/1
Rear cubicle	P2	200	800	PCVS2208	1STQ009011A0000	1/1
Rear cubicle	P2	250	800	PCVS2258	1STQ009012A0000	1/1
Rear cubicle	P2	300	800	PCVS2308	1STQ009013A0000	1/1
Rear cubicle	P2	350	800	PCVS2358	1STQ009014A0000	1/1
Rear cubicle	P2	400	800	PCVS2408	1STQ009015A0000	1/1
Rear cubicle	P2	500	800	PCVS2508	1STQ009017A0000	1/1
Rear cubicle	P2	600	800	PCVS2608	1STQ009018A0000	1/1

Posizion P2


The P2 segregations can replace the P0 and P1 segregation in order to obtain more useful space available inside the compartment.



Segregation for horizontal withdrawable Emax E1.2 and Tmax T7 circuit-breakers

The code includes corner piece, vertical Lexan panel, 2 horizontal shelves and side wall.

Description	Dimensions (mm)			Type	Order code	Pkg/ No. pcs
	H	W				
Rear cubicle	500	600		PCVS5060	1STQ009162A0000	1/1
Rear cubicle	500	800		PCVS5080	1STQ009163A0000	1/1




Horizontal segregation for cubicles

Horizontal shelf for cubicles for 4b segregation. Required for all depth changes in compartments in the same column. Order the length corresponding to the larger position between two consecutive compartments.

Description	Assembly position	Dimensions (mm)		Type	Order code	Pkg/ No. pcs
		W				
Horizontal shelf for cubicles	P1	400		PSHS1400	1STQ008923A0000	1/1
Horizontal shelf for cubicles	P1	600		PSHS1600	1STQ008924A0000	1/1
Horizontal shelf for cubicles	P1	800		PSHS1800	1STQ008925A0000	1/1
Horizontal shelf for cubicles	P2	400		PSHS2400	1STQ008927A0000	1/1
Horizontal shelf for cubicles	P2	600		PSHS2600	1STQ008928A0000	1/1
Horizontal shelf for cubicles	P2	800		PSHS2800	1STQ008929A0000	1/1

Segregation

Order codes - Form 4b segregations




Lateral connection module for terminal ditching

Lateral drilled module 25mm pitch for fixing the crosspieces with insulating supports in width from the intermediate upright up to the rear structural upright. In order to complete the terminals ditching it is necessary to order two lateral connection modules, which have to be fixed sideways. The crosspieces PCRM or PCRS is fixed using the special fixing brackets for module connection PBMC0002. The crosspiece is to be chosen and ordered separately according to the width of the structure.

Description	Dimensions (mm)		Type	Order code	Pkg/ No. pcs
	H	D			
Lateral connection module	175	500	PMCS1755	1STQ009200A0000	1/1
Lateral connection module	200	500	PMCS2050	1STQ009201A0000	1/1
Lateral connection module	225	500	PMCS2255	1STQ009202A0000	1/1
Lateral connection module	250	500	PMCS2550	1STQ009203A0000	1/1
Lateral connection module	300	500	PMCS3050	1STQ009204A0000	1/1
Lateral connection module	175	700	PMCS1757	1STQ009205A0000	1/1
Lateral connection module	200	700	PMCS2070	1STQ009206A0000	1/1
Lateral connection module	225	700	PMCS2257	1STQ009207A0000	1/1
Lateral connection module	250	700	PMCS2570	1STQ009208A0000	1/1
Lateral connection module	300	700	PMCS3070	1STQ009209A0000	1/1
Lateral connection module	175	900	PMCS1759	1STQ009210A0000	1/1
Lateral connection module	200	900	PMCS2090	1STQ009211A0000	1/1
Lateral connection module	225	900	PMCS2259	1STQ009212A0000	1/1
Lateral connection module	250	900	PMCS2590	1STQ009213A0000	1/1
Lateral connection module	300	900	PMCS3090	1STQ009214A0000	1/1
No.2 fixing brackets connection module			PBMC0002	1STQ009215A0000	1/1

Segregations for vertical circuit-breakers

Form 4b of vertical circuit-breakers is obtained by duplicating the codes of vertical bottom segregations PRVS... and vertical side segregations PLVS..., closing the circuit-breaker compartments for the full height of the switchboard and installing an additional vertical side segregation on the output side.



As an alternative to the PLVS... vertical side segregations, in the case of main circuit-breakers, use the PMCS... side connection module for fixing terminal extensions and the relative fixing bshelves PBMC0002 (page 4/40).

Chapter 6

Dedicated solution

CombiLine

6-2 General information

6-4 Quick selection guide

6-8 Order codes

InLine II

6-22 General information

6-24 Quick selection guide

6-26 Order codes

Capacitor Bank

6-38 General information

6-40 Order codes

6-44 Declaration on thsted configuration and overall

6-45 Technical specification


Dedicated solution

CombiLine-M - General information

Modular distribution panel system CombiLine-M

The right module for every type of application up to 850A.

The perfect expansion of the modular cabinet series is no problem with the CombiLine-M modular distribution panel system.




Fast, efficient and easy to combine - just three product features of this system that speak for themselves. The result: maximum options using a minimum of components.

Integration in System pro E power

CombiLine-M solutions can be fitted in five different columns widths and is compatible with any enclosure depth.

The fitting of CombiLine-M solutions is realized thanks to the use of a dedicated fixing set as well as a touchguard.

An additional cover is needed for the enclosures with functional height 2000mm.






ABB



ABB

Dedicated solution

CombiLine-M - Quick selection guide



H=1800mm recommended installation solutions
GU-modules 12

Functional dimensions	External dimensions *	FRAME						EXTERNAL COVERS								
		Uprights	Structure crosspieces	H=100mm plinth			Top/bottom panels			Front/rear/side panels						
						Galvanized sheet metal In≤4000A **		Galvanized sheet metal In≤4000A **		Top/Bottom			Bottom			
						Plinth flanges			Blind			Without plinth	Rear panel			
						Open ⁽²⁾			Open ⁽²⁾			Blind				
Height 1800mm	Height 2013mm	Galvanized sheet metal In≤4000A **						IP30 ⁽¹⁾ IP40 ⁽¹⁾								
W (mm)	D (mm)	W (mm)	D (mm)	PW-mod.	In≤4000A	Front/Rear	Sides	Angle pieces	Front/Rear	Sides	IP65	IP65	IP40 ⁽³⁾	IP65		
250	200	350	316	1	PUPM1800	PCFM0250	PCFM0200	PPAM0100	PPFM1025	PPFM1020	PTBB2526	PTBB2520	PTBO2520	PBWP2520	PPEB1825	PPEB1827
							PCFM0300			PPFM1030	PTBB2536	PTBB2530	PTBO2530	PBWP2530		
							PCFM0500			PPFM1050	PTBB2556	PTBB2550	PTBO2550	PBWP2550		
							PCFM0700			PPFM1070	PTBB2576	PTBB2570	PTBO2570	PBWP2570		
							PCFM0900			PPFM1090	PTBB2596	PTBB2590	PTBO2590	PBWP2590		
500	200	600	316	2	PUPM1800	PCFM0500	PCFM0200	PPAM0100	PPFM1050	PPFM1020	PTBB5026	PTBB5020	PTBO5020	PBWP5020	PPEB1856	PPEB1850
							PCFM0300			PPFM1030	PTBB3056	PTBB3050	PTBO3050	PBWP3050		
							PCFM0500			PPFM1050	PTBB5050	PTBB5057	PTBO5050	PBWP5050		
							PCFM0700			PPFM1070	PTBB5076	PTBB5070	PTBO5070	PBWP5070		
							PCFM0900			PPFM1090	PTBB5096	PTBB5090	PTBO5090	PBWP5090		
750	200	850	316	3	PUPM1800	PCFM0750	PCFM0200	PPAM0100	PPFM1075	PPFM1020	PTBB7526	PTBB7520	PTBO7520	PBWP7520	PPEB1875	PPEB1877
							PCFM0300			PPFM1030	PTBB7536	PTBB7530	PTBO7530	PBWP7530		
							PCFM0500			PPFM1050	PTBB7556	PTBB7550	PTBO7550	PBWP7550		
							PCFM0700			PPFM1070	PTBB7576	PTBB7570	PTBO7570	PBWP7570		
							PCFM0900			PPFM1090	PTBB7596	PTBB7590	PTBO7590	PBWP7590		
1000	200	1100	316	4	PUPM1800	PCFM1000	PCFM0200	PPAM0100	PPFM1010	PPFM1020	PTBB1026	PTBB1020			PPEB1816	PPEB1810
							PCFM0300			PPFM1030	PTBB1036	PTBB1030	PTBO1030	PBWP1030		
							PCFM0500			PPFM1050	PTBB1056	PTBB1050	PTBO1050	PBWP1050		
							PCFM0700			PPFM1070	PTBB1076	PTBB1070	PTBO1070	PBWP1070		
							PCFM0900			PPFM1090	PTBB1096	PTBB1090	PTBO1090	PBWP1090		
1250	200	1350	316	5	PUPM1800	PCFM1250	PCFM0200	PPAM0100	PPFM1250	PPFM1020		PTBB1220			PPRB1820 ⁽⁴⁾	
							PCFM0300			PPFM1030		PTBB1230	PTBO1230	PBWP1230		PPLB1820 ⁽⁵⁾
							PCFM0500			PPFM1050		PTBB1250	PTBO1250	PBWP1250		
							PCFM0700			PPFM1070		PTBB1270	PTBO1270	PBWP1270		
							PCFM0900			PPFM1090		PTBB1290	PTBO1290	PBWP1290		


Consult page 2/12 and 7/2 for selection of the protection class.

* The external dimensions include the H=100mm plinth and the panels.

** Also available in stainless steel, see page 2/8.

⁽¹⁾ In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit, page 2/23.

⁽²⁾ Use the dedicated incoming cable flanges to obtain protection class IP65.



COMBILINE

Finishing profiles IP30

Side panel		Glass door 12/24/36/48 mod. DIN		Blind door 12/24/36/48 mod. DIN	
Vented	Blind	Vented			

	IP30 ⁽¹⁾	IP65	IP30 ⁽¹⁾	IP40 ⁽¹⁾	IP65	IP40 ⁽¹⁾	Vertical profile	Horizontal profile	Touch-guard	Bracket	WR frame	Depth support ⁽⁸⁾
PPEB1826	PPEB1820				PDLB1826	PDLB1825	PPFV1800	PPFH0250	PCTG1825	PBCM0004	WR181	
PPEB1836	PPEB1830	PPEA1830										
PPEB1856	PPEB1850	PPEA1850										
PPEB1876	PPEB1870	PPEA1870										
PPEB1896	PPEB1890	PPEA1890										
PPEB1826	PPEB1820		PDLG1856	PDLG1850	PDLB1856	PDLB1850	PPFV1800	PPFH0500	PCTG1850	PBCM0004	WR281	
PPEB1836	PPEB1830	PPEA1830										
PPEB1856	PPEB1850	PPEA1850										
PPEB1876	PPEB1870	PPEA1870										
PPEB1896	PPEB1890	PPEA1890										
PPEA1875	PPEB1826	PPEB1820		PDLG1876	PDLG1870	PDLB1876	PDLB1875	PPFV1800	PPFH0750	PCTG1875	PBCM0004	WR381
	PPEB1836	PPEB1830	PPEA1830									
	PPEB1856	PPEB1850	PPEA1850									
	PPEB1876	PPEB1870	PPEA1870									
	PPEB1896	PPEB1890	PPEA1890									
PPRA1820 ⁽⁴⁾	PPEB1826	PPEB1820		PDLG1816	PDLG1810	PDLB1816	PDLB1810	PPFV1800	PPFH1000	PCTG1810	PBCM0004	WR281
	PPEB1836	PPEB1830	PPEA1830									PDFC0200
	PPEB1856	PPEB1850	PPEA1850									PDFC0300
	PPEB1876	PPEB1870	PPEA1870									PDFC0500
	PPEB1896	PPEB1890	PPEA1890									PDFC0700
PPLA1820 ⁽⁵⁾	PPEB1826	PPEB1820			PDLB8120 ⁽⁶⁾		PPFV1800	PPFH1250	PCTG1812	PBCM0004	WR281	PDFC0900
	PPEB1836	PPEB1830	PPEA1830		PDLG8500 ⁽⁷⁾		PPFV1800	PPFH1250	PCTG1812	PBCM0004	WR381	PDFC0200
	PPEB1856	PPEB1850	PPEA1850									PDFC0300
	PPEB1876	PPEB1870	PPEA1870									PDFC0500
	PPEB1896	PPEB1890	PPEA1890									PDFC0700

⁽³⁾ Bottom for switchboard without plinth complete with the dedicated set of brackets, which can be ordered separately.

⁽⁴⁾ Right rear panel for structures W=1250mm.

⁽⁵⁾ Left rear panel for structures W=1250mm.


⁽⁶⁾ Door with overlapping for the double door version.

⁽⁷⁾ Door with handle for the double door version.

⁽⁸⁾ Order the RZ1P4 older for two frame.

Dedicated solution

CombiLine-M - Quick selection guide



H=2000mm recommended installation solutions

GU-modules 13

Functional dimensions	External dimensions *	FRAME						EXTERNAL COVERS								
		Uprights	Structure crosspieces	H=100mm plinth			Top/bottom panels			Front/rear/side panels						
		Galvanized sheet metal In≤4000A **		Galvanized sheet metal In≤4000A **		Top/Bottom			Bottom	Rear panel						
		Plinth flanges			Blind		Open ⁽²⁾		Without plinth	Blind						
Height 1800mm	Height 2013mm	Galvanized sheet														
W (mm)	D (mm)	W (mm)	D (mm)	PW-mod.	metal ** In≤4000A	Front/ Rear	Sides	Angle pieces	Front/ Rear	Sides	IP30 ⁽¹⁾ IP40 ⁽¹⁾	IP65	IP40 ⁽³⁾ IP65	IP30 ⁽¹⁾ IP40 ⁽¹⁾		
250	200	350	316	1	PUPM2000	PCFM0250	PCFM0200	PPAM0100	PPFM1025	PPFM1020	PTBB2526	PTBB2520	PTBO2520	PBWP2520	PPEB2025	PPEB2027
		300	416				PCFM0300			PPFM1030	PTBB2536	PTBB2530	PTBO2530	PBWP2530		
		500	616				PCFM0500			PPFM1050	PTBB2556	PTBB2550	PTBO2550	PBWP2550		
		700	816				PCFM0700			PPFM1070	PTBB2576	PTBB2570	PTBO2570	PBWP2570		
		900	1016				PCFM0900			PPFM1090	PTBB2596	PTBB2590	PTBO2590	PBWP2590		
500	200	600	316	2	PUPM2000	PCFM0250	PCFM0200	PPAM0100	PPFM1050	PPFM1020	PTBB5026	PTBB5020	PTBO5020	PBWP5020	PPEB2056	PPEB2050
		300	416				PCFM0300			PPFM1030	PTBB3056	PTBB3050	PTBO3050	PBWP3050		
		500	616				PCFM0500			PPFM1050	PTBB5050	PTBB5057	PTBO5050	PBWP5050		
		700	816				PCFM0700			PPFM1070	PTBB5076	PTBB5070	PTBO5070	PBWP5070		
		900	1016				PCFM0900			PPFM1090	PTBB5096	PTBB5090	PTBO5090	PBWP5090		
750	200	850	316	3	PUPM2000	PCFM0250	PCFM0200	PPAM0100	PPFM1075	PPFM1020	PTBB7526	PTBB7520	PTBO7520	PBWP7520	PPEB2075	PPEB2077
		300	416				PCFM0300			PPFM1030	PTBB7536	PTBB7530	PTBO7530	PBWP7530		
		500	616				PCFM0500			PPFM1050	PTBB7556	PTBB7550	PTBO7550	PBWP7550		
		700	816				PCFM0700			PPFM1070	PTBB7576	PTBB7570	PTBO7570	PBWP7570		
		900	1016				PCFM0900			PPFM1090	PTBB7596	PTBB7590	PTBO7590	PBWP7590		
1000	200	1100	316	4	PUPM2000	PCFM0250	PCFM0200	PPAM0100	PPFM1010	PPFM1020	PTBB1026	PTBB1020			PPEB2016	PPEB2010
		300	416				PCFM0300			PPFM1030	PTBB1036	PTBB1030	PTBO1030	PBWP1030		
		500	616				PCFM0500			PPFM1050	PTBB1056	PTBB1050	PTBO1050	PBWP1050		
		700	816				PCFM0700			PPFM1070	PTBB1076	PTBB1070	PTBO1070	PBWP1070		
		900	1016				PCFM0900			PPFM1090	PTBB1096	PTBB1090	PTBO1090	PBWP1090		
1250	200	1350	316	5	PUPM2000	PCFM0250	PCFM0200	PPAM0100	PPFM1250	PPFM1020		PTBB1220			PPRB2020 ⁽⁴⁾	
		300	416				PCFM0300			PPFM1030		PTBB1230	PTBO1230	PBWP1230	PPLB2020 ⁽⁵⁾	
		500	616				PCFM0500			PPFM1050		PTBB1250	PTBO1250	PBWP1250		
		700	816				PCFM0700			PPFM1070		PTBB1270	PTBO1270	PBWP1270		
		900	1016				PCFM0900			PPFM1090		PTBB1290	PTBO1290	PBWP1290		


Consult page 2/12 and 7/2 for selection of the protection class.

* The external dimensions include the H=100mm plinth and the the panels.

** Also available in stainless steel, see page 2/8.

⁽¹⁾ In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit, page 2/23.

⁽²⁾ Use the dedicated incoming cable flanges to obtain protection class IP65.

**COMBILINE****Finishing profiles IP30**

		Side panel		Glass door 12/24/36/48 mod. DIN		Blind door 12/24/36/48 mod. DIN		Adaptor for height 2000mm				WR frame	Depth support ⁽⁸⁾
Vented	Blind	Vent						Vertical profile	Horizontal profile	Touch- guard	Bracket		
IP30 ⁽¹⁾	IP65	IP30 ⁽¹⁾ IP40 ⁽¹⁾	IP30 ⁽¹⁾	IP65	IP40 ⁽¹⁾	IP65	IP40 ⁽¹⁾						
PPEB2026	PPEB2020			PDLB2026	PDLB2025	PPFV2000	PPFH0250	PCTG2025	PBCM0004	PCCM2025	WR191		
PPEB2036	PPEB2030	PPEA2030											
PPEB2056	PPEB2050	PPEA2050											
PPEB2076	PPEB2070	PPEA2070											
PPEB2096	PPEB2090	PPEA2090											
PPEB2026	PPEB2020		PDLG2056	PDLG2050	PDLB2056	PDLB2050	PPFV2000	PPFH0500	PCTG2050	PBCM0004	PCCM2050	WR291	
PPEB2036	PPEB2030	PPEA2030											
PPEB2056	PPEB2050	PPEA2050											
PPEB2076	PPEB2070	PPEA2070											
PPEB2096	PPEB2090	PPEA2090											
PPEA2075	PPEB2026	PPEB2020		PDLG2076	PDLG2070	PDLB2076	PDLB2075	PPFV2000	PPFH0750	PCTG2075	PBCM0004	PCCM2075	WR391
	PPEB2036	PPEB2030	PPEA2030										
	PPEB2056	PPEB2050	PPEA2050										
	PPEB2076	PPEB2070	PPEA2070										
	PPEB2096	PPEB2090	PPEA2090										
	PPEB2026	PPEB2020		PDLG2016	PDLG2010	PDLB2016	PDLB2010	PPFV2000	PPFH1000	PCTG2010	PBCM0004	PCCM2010	WR291
	PPEB2036	PPEB2030	PPEA2030										PDFOC200
	PPEB2056	PPEB2050	PPEA2050										PDFOC300
	PPEB2076	PPEB2070	PPEA2070										PDFOC500
	PPEB2096	PPEB2090	PPEA2090										PDFOC700
	PPRA2020 ⁽⁴⁾	PPEB2020		PDLB2120 ⁽⁶⁾		PDLB2120 ⁽⁶⁾	PPFV2000	PPFH1250	PCTG2012	PBCM0004	PCCM2012	WR291	PDFOC900
	PPLA2020 ⁽⁵⁾	PPEB2030	PPEA2030		PDLG2500 ⁽⁷⁾	PDLB2500 ⁽⁷⁾						WR391	PDFOC200
	PPEB2056	PPEB2050	PPEA2050										PDFOC300
	PPEB2076	PPEB2070	PPEA2070										PDFOC500
	PPEB2096	PPEB2090	PPEA2090										PDFOC700
													PDFOC900

⁽¹⁾ Bottom for switchboard without plinth complete with the dedicated set of brackets, which can be ordered separately.

⁽⁴⁾ Right rear panel for structures W=1250mm.

⁽⁵⁾ Left rear panel for structures W=1250mm.


⁽⁶⁾ Door with overlapping for the double door version.

⁽⁷⁾ Door with handle for the double door version.

⁽⁸⁾ Order the RZ1P4 older for two frame.

Dedicated solution


CombiLine-M - Order codes



Touch guard profile - dedicated solution for CombiLine-M

Profile to guarantee IP30 touch protection with CombiLine-M modules installed.


Description	Dimensions (mm)		Type	Order code	Pkg/ No. pcs
	H	W			
Touch Guard profile	1800	250	PCTG1825	1STQ009368A0000	1/1
Touch Guard profile	1800	500	PCTG1850	1STQ009406A0000	1/1
Touch Guard profile	1800	750	PCTG1875	1STQ009385A0000	1/1
Touch Guard profile	1800	1000	PCTG1810	1STQ009928A0000	1/1
Touch Guard profile	1800	1250	PCTG1812	1STQ001319B0000	1/1
Touch Guard profile	2000	250	PCTG2025	1STQ009379A0000	1/1
Touch Guard profile	2000	500	PCTG2050	1STQ009417A0000	1/1
Touch Guard profile	2000	750	PCTG2075	1STQ009399A0000	1/1
Touch Guard profile	2000	1000	PCTG2010	1STQ009929A0000	1/1
Touch Guard profile	2000	1250	PCTG2012	1STQ001320B0000	1/1



Fixing set - dedicated solution for CombiLine-M

Fixed set for the adaptation of standard WR frame on System pro E power structure.


Description	Type	Order code	Pkg/ No. pcs
CombiLine-M fixing set	PBCM0004	1STQ009354A0000	1/4
Depth support			
No.2 CombiLine crosspieces for frame D=200mm	PDFC0200	1STQ001929B0000	1/2
No.2 CombiLine crosspieces for frame D=300mm	PDFC0300	1STQ001930B0000	1/2
No.2 CombiLine crosspieces for frame D=500mm	PDFC0500	1STQ001931B0000	1/2
No.2 CombiLine crosspieces for frame D=700mm	PDFC0700	1STQ001932B0000	1/2
No.2 CombiLine crosspieces for frame D=900mm	PDFC0900	1STQ001933B0000	1/2
No.2 adaptor for Combiline H=2000mm	PBCM0001	1STQ001934B0000	1/2



Height adapters for 2000mm columns - dedicated solution for CombiLine-M

Adapters to use CombiLine-M modules in columns with functional height 2000mm. The components cover 50mm on the bottom and on the top.

Description	Dimensions (mm)		Type	Order code	Pkg/ No. pcs
	H	W			
CombiLine-M adapter	2000	250	PCCM2025	1STQ009355A0000	1/2
CombiLine-M adapter	2000	500	PCCM2050	1STQ009356A0000	1/2
CombiLine-M adapter	2000	750	PCCM2075	1STQ009357A0000	1/2
CombiLine-M adapter	2000	1000	PCCM2010	1STQ009358A0000	1/2
CombiLine-M adapter	2000	1250	PCCM2012	1STQ001318B0000	1/2



Uprights – Galvanized sheet metal *

Upright formed by a closed profile made of galvanized sheet metal. The uprights include 8 already assembled 3-way joints, 8 already assembled axial screws and 16 loose axial screws. For applications with In ≤4000A.

Description	Dimensions (mm)		Type	Order code	Pkg/ No. pcs
	H				
No.4 galvanized sheet metal uprights	1800		PUPM1800	1STQ007033A0000	1/4
No.4 galvanized sheet metal uprights	2000		PUPM2000	1STQ007034A0000	1/4

* Also available in stainless steel, see page 2/15.

Dedicated solution

CombiLine-M - Order codes




Structure crosspieces – Galvanized sheet metal *

Depth and width crosspieces for structures in galvanized sheet metal. For applications with In ≤4000A.

Description	Dimensions (mm)			Pkg/ No. pcs
	W	D	Type	
Width crosspieces				
No.4 width crosspieces galvanized sheet metal 250			PCFM0250	1STQ007036A0000
No.4 width crosspieces galvanized sheet metal 500			PCFM0500	1STQ007039A0000
No.4 width crosspieces galvanized sheet metal 750			PCFM0750	1STQ007041A0000
No.4 width crosspieces galvanized sheet metal 1000			PCFM1000	1STQ007043A0000
No.4 width crosspieces galvanized sheet metal 1250			PCFM1250	1STQ007044A0000
Depth crosspieces				
No.4 depth crosspieces galvanized sheet metal	200		PCFM0200	1STQ007045A0000
No.4 depth crosspieces galvanized sheet metal	300		PCFM0300	1STQ007037A0000
No.4 depth crosspieces galvanized sheet metal	500		PCFM0500	1STQ007039A0000
No.4 depth crosspieces galvanized sheet metal	700		PCFM0700	1STQ007046A0000
No.4 depth crosspieces galvanized sheet metal	900		PCFM0900	1STQ007047A0000

* Also available in stainless steel, see page 2/15..


PPAM0100



Universal angle pieces for plinths in galvanized sheet metal

Not pre-assembled to the structure. New angle piece with high mechanical strength. Can be fixed from the outside and from the inside of the structure even at a later date. Equipped with anti-rotation system and bottom that can be transported with a transpallet.

PPAM0200




Description	Dimensions (mm)			Pkg/ No. pcs
	H	Type	Order code	
No.4 plinth angle pieces	100	PPAM0100	1STQ007048A0000	1/4
No.8 plinth angle pieces	200	PPAM0200	1STQ007207A0000	1/4
H=100mm pre-assembled*				

*Order no. 2 pieces of H=100mm covering flange kits to complete the H=200mm plinth.

Plinth flanges


Side and front/rear plinth flanges H=100mm RAL 7012.



Description	Dimensions (mm)			Pkg/ No. pcs
	W	D	Type	
Front/rear plinth flanges				
No.2 plinth flanges	250		PPFM1025	1STQ007049A0000
No.2 plinth flanges	500		PPFM1050	1STQ007052A0000
No.2 plinth flanges	750		PPFM1075	1STQ007054A0000
No.2 plinth flanges	1000		PPFM1010	1STQ007056A0000
No.4 plinth flanges	1250		PPFM1250	1STQ007057A0000
Side plinth flanges				
No.2 plinth flanges	200		PPFM1020	1STQ007058A0000
No.2 plinth flanges	300		PPFM1030	1STQ007050A0000
No.2 plinth flanges	500		PPFM1050	1STQ007052A0000
No.2 plinth flanges	700		PPFM1070	1STQ007059A0000
No.2 plinth flanges	900		PPFM1090	1STQ007060A0000

Dedicated solution

CombiLine-M - Order codes




Blind Top/Bottom IP65 – Pickled sheet steel

Pickled sheet steel with IP65 gasket. The article comprises one single component that can be used as either a top or bottom. In order to purchase both the top and the bottom, please order two quantities of the same code or two different top/bottom codes according to the desired design of the structure. The code includes four M12x20 screws.

Description	Dimensions (mm)			Pkg/ No. pcs
	W	D	Type	
IP65 blind top/bottom	250	200	PTBB2526	1STQ001270B0000
IP65 blind top/bottom	250	300	PTBB2536	1STQ007071A0000
IP65 blind top/bottom	250	500	PTBB2556	1STQ007072A0000
IP65 blind top/bottom	250	700	PTBB2576	1STQ007073A0000
IP65 blind top/bottom	250	900	PTBB2596	1STQ001271B0000
IP65 blind top/bottom	500	200	PTBB5026	1STQ001284B0000
IP65 blind top/bottom	500	300	PTBB3056	1STQ007076A0000
IP65 blind top/bottom	500	500	PTBB5050	1STQ009179A0000
IP65 blind top/bottom	500	700	PTBB5076	1STQ007085A0000
IP65 blind top/bottom	500	900	PTBB5096	1STQ001286B0000
IP65 blind top/bottom	750	200	PTBB7526	1STQ001303B0000
IP65 blind top/bottom	750	300	PTBB7536	1STQ007091A0000
IP65 blind top/bottom	750	500	PTBB7556	1STQ007092A0000
IP65 blind top/bottom	750	700	PTBB7576	1STQ007093A0000
IP65 blind top/bottom	750	900	PTBB7596	1STQ001304B0000
Blind Top/Bottom IP65	1000	200	PTBB1026	1STQ009178A0000
Blind Top/Bottom IP65	1000	300	PTBB1036	1STQ007099A0000
Blind Top/Bottom IP65	1000	500	PTBB1056	1STQ007100A0000
Blind Top/Bottom IP65	1000	700	PTBB1076	1STQ007101A0000
Blind Top/Bottom IP65	1000	900	PTBB1096	1STQ007102A0000

Dedicated solution

CombiLine-M - Order codes




Blind Top/Bottom IP30, IP40 – Pickled sheet steel

Pickled sheet steel without gasket. In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit, page 6-12. The article comprises one single component that can be used as either a top or bottom. In order to purchase both the top and the bottom, please order two quantities of the same code or two different top/bottom codes according to the desired design of the structure. The code includes four M12x20 screws.

Description	Dimensions (mm)			Pkg/ No. pcs
	W	D	Type	
Blind Top/Bottom IP30, 40	250	200	PTBB2520	1STQ001267B0000
Blind Top/Bottom IP30, 40	250	300	PTBB2530	1STQ001268B0000
Blind Top/Bottom IP30, 40	250	500	PTBB2550	1STQ009370A0000
Blind Top/Bottom IP30, 40	250	700	PTBB2570	1STQ009423A0000
Blind Top/Bottom IP30, 40	250	900	PTBB2590	1STQ001269B0000
Blind Top/Bottom IP30, 40	500	200	PTBB5020	1STQ001281B0000
Blind Top/Bottom IP30, 40	500	300	PTBB3050	1STQ007109A0000
Blind Top/Bottom IP30, 40	500	500	PTBB5057	1STQ009407A0000
Blind Top/Bottom IP30, 40	500	700	PTBB5070	1STQ009435A0000
Blind Top/Bottom IP30, 40	500	900	PTBB5090	1STQ001283B0000
Blind Top/Bottom IP30, 40	750	200	PTBB7520	1STQ001300B0000
Blind Top/Bottom IP30, 40	750	300	PTBB7530	1STQ001301B0000
Blind Top/Bottom IP30, 40	750	500	PTBB7550	1STQ009387A0000
Blind Top/Bottom IP30, 40	750	700	PTBB7570	1STQ009429A0000
Blind Top/Bottom IP30, 40	750	900	PTBB7590	1STQ001302B0000
Blind Top/Bottom IP30, 40	1000	200	PTBB1020	1STQ009152A0000
Blind Top/Bottom IP30, 40	1000	300	PTBB1030	1STQ007127A0000
Blind Top/Bottom IP30, 40	1000	500	PTBB1050	1STQ007128A0000
Blind Top/Bottom IP30, 40	1000	700	PTBB1070	1STQ007129A0000
Blind Top/Bottom IP30, 40	1000	900	PTBB1090	1STQ007130A0000
Blind Top/Bottom IP30, 40	1250	200	PTBB1220	1STQ009153A0000
Blind Top/Bottom IP30, 40	1250	300	PTBB1230	1STQ001315B0000
Blind Top/Bottom IP30, 40	1250	500	PTBB1250	1STQ001316B0000
Blind Top/Bottom IP30, 40	1250	700	PTBB1270	1STQ001317B0000
Blind Top/Bottom IP30, 40	1250	900	PTBB1290	1STQ007131A0000

Dedicated solution

CombiLine-M - Order codes




Top sealing kit IP31/IP41

Profiles for IP31/IP41 for top.

Description	Dimensions (mm)		Type	Order code	Pkg/ No. pcs
	W	D			
N.2 roof profiles for single column	200		PKST0200	1STQ001905B0000	1/2
N.2 roof profiles for single column	300		PKST0301	1STQ001935B0000	1/1
N.2 roof profiles for single column	500		PKST0501	1STQ001936B0000	1/1
N.2 roof profiles for single column	700		PKST0700	1STQ001911B0000	1/2
N.2 roof profiles for single column	900		PKST0900	1STQ001914B0000	1/2
N.2 roof profiles for single column	250		PKST0250	1STQ001906B0000	1/2
N.2 roof profiles for single column	300		PKST0300	1STQ001907B0000	1/2
N.2 roof profiles for single column	400		PKST0400	1STQ001908B0000	1/2
N.2 roof profiles for single column	500		PKST0500	1STQ001909B0000	1/2
N.2 roof profiles for single column	600		PKST0600	1STQ001910B0000	1/2
N.2 roof profiles for single column	750		PKST0750	1STQ001912B0000	1/2
N.2 roof profiles for single column	800		PKST0800	1STQ001913B0000	1/2
N.2 roof profiles for single column	1000		PKST1000	1STQ001915B0000	1/2
N.2 roof profiles for single column	1250		PKST1250	1STQ001916B0000	1/2
N.1 roof profile for side by side column	200		PKDT0200	1STQ001917B0000	1/1
N.1 roof profile for side by side column	300		PKDT0301	1STQ001937B0000	1/1
N.1 roof profile for side by side column	700		PKDT0700	1STQ001923B0000	1/1
N.1 roof profile for side by side column	900		PKDT0900	1STQ001926B0000	1/1
N.1 roof profile for side by side column	500		PKDT0501	1STQ001938B0000	1/1
N.1 roof profile for back to back column	250		PKDT0250	1STQ001918B0000	1/1
N.1 roof profile for back to back column	300		PKDT0300	1STQ001919B0000	1/1
N.1 roof profile for back to back column	400		PKDT0400	1STQ001920B0000	1/1
N.1 roof profile for back to back column	500		PKDT0500	1STQ001921B0000	1/1
N.1 roof profile for back to back column	600		PKDT0600	1STQ001922B0000	1/1
N.1 roof profile for back to back column	750		PKDT0750	1STQ001924B0000	1/1
N.1 roof profile for back to back column	800		PKDT0800	1STQ001925B0000	1/1
N.1 roof profile for back to back column	1000		PKDT1000	1STQ001927B0000	1/1
N.1 roof profile for back to back column	1250		PKDT1250	1STQ001928B0000	1/1
Roof profiles for corner structure	500	500	PKAT5050	1STQ001939B0000	1/4
Roof profiles for corner structure	700	700	PKAT7070	1STQ001941B0000	1/4
Roof profiles for corner structure	900	900	PKAT9090	1STQ001943B0000	1/4

Dedicated solution

CombiLine-M - Order codes



Open Top/Bottom


Pickled sheet steel with holes. The code comprises one single component that can be used as either a top or bottom. In order to purchase both the top and the bottom, please order two quantities of the same code or two different top/bottom codes according to the desired design of the structure.

In order to reach IP65 protection degree, use the dedicated fixed cable incoming flanges PFCF....; in order to reach IP40 protection degree, use the dedicated swinging cable incoming flanges PFCS.... at page 4/13-4/14. The use of the single open top/bottom without flanges does not guarantee any degree of protection IP. The open top/bottom, associated with sliding flanges, is incompatible with crosspieces assembled inside the cable compartment.

Description	Dimensions (mm)				Pkg/ No. pcs
	W	D	Type	Order code	
Open Top/Bottom	250	200	PTBO2520	1STQ001272B0000	1/1
Open Top/Bottom	250	300	PTBO2530	1STQ007132A0000	1/1
Open Top/Bottom	250	500	PTBO2550	1STQ007133A0000	1/1
Open Top/Bottom	250	700	PTBO2570	1STQ007134A0000	1/1
Open Top/Bottom	250	900	PTBO2590	1STQ001273B0000	1/1
Open Top/Bottom	500	200	PTBO5020	1STQ001287B0000	1/1
Open Top/Bottom	500	300	PTBO3050	1STQ007137A0000	1/1
Open Top/Bottom	500	500	PTBO5050	1STQ007145A0000	1/1
Open Top/Bottom	500	700	PTBO5070	1STQ007146A0000	1/1
Open Top/Bottom	500	900	PTBO5090	1STQ001289B0000	1/1
Open Top/Bottom	750	200	PTBO7520	1STQ001305B0000	1/1
Open Top/Bottom	750	300	PTBO7530	1STQ007152A0000	1/1
Open Top/Bottom	750	500	PTBO7550	1STQ007153A0000	1/1
Open Top/Bottom	750	700	PTBO7570	1STQ007154A0000	1/1
Open Top/Bottom	750	900	PTBO7590	1STQ001306B0000	1/1
Open Top/Bottom	1000	300	PTBO1030	1STQ007160A0000	1/1
Open Top/Bottom	1000	500	PTBO1050	1STQ007161A0000	1/1
Open Top/Bottom	1000	700	PTBO1070	1STQ007162A0000	1/1
Open Top/Bottom	1000	900	PTBO1090	1STQ007163A0000	1/1
Open Top/Bottom	1250	300	PTBO1230	1STQ007164A0000	1/1
Open Top/Bottom	1250	500	PTBO1250	1STQ007165A0000	1/1
Open Top/Bottom	1250	700	PTBO1270	1STQ007166A0000	1/1
Open Top/Bottom	1250	900	PTBO1290	1STQ007167A0000	1/1

Dedicated solution


CombiLine-M - Order codes



Bottom without plinth IP40

Internal galvanized steel bottom with special brackets kit included (special brackets kit available also as spare part with the code PBRB0004). In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit PKPT..., page 6-12.

Description	Dimensions (mm)			Pkg/ No. pcs
	W	D	Type	
Bottom without plinth IP40	250	200	PBWP2520	1STQ001279B0000
Bottom without plinth IP40	250	300	PBWP2530	1STQ007168A0000
Bottom without plinth IP40	250	500	PBWP2550	1STQ007169A0000
Bottom without plinth IP40	250	700	PBWP2570	1STQ007170A0000
Bottom without plinth IP40	250	900	PBWP2590	1STQ001280B0000
Bottom without plinth IP40	500	200	PBWP5020	1STQ001297B0000
Bottom without plinth IP40	500	300	PBWP3050	1STQ007173A0000
Bottom without plinth IP40	500	500	PBWP5050	1STQ007181A0000
Bottom without plinth IP40	500	700	PBWP5070	1STQ007182A0000
Bottom without plinth IP40	500	900	PBWP5090	1STQ001299B0000
Bottom without plinth IP40	750	200	PBWP7520	1STQ001313B0000
Bottom without plinth IP40	750	300	PBWP7530	1STQ007188A0000
Bottom without plinth IP40	750	500	PBWP7550	1STQ007189A0000
Bottom without plinth IP40	750	700	PBWP7570	1STQ007190A0000
Bottom without plinth IP40	750	900	PBWP7590	1STQ001314B0000
Bottom without plinth IP40	1000	300	PBWP1030	1STQ007196A0000
Bottom without plinth IP40	1000	500	PBWP1050	1STQ007197A0000
Bottom without plinth IP40	1000	700	PBWP1070	1STQ007198A0000
Bottom without plinth IP40	1000	900	PBWP1090	1STQ007199A0000
Bottom without plinth IP40	1250	300	PBWP1230	1STQ007200A0000
Bottom without plinth IP40	1250	500	PBWP1250	1STQ007201A0000
Bottom without plinth IP40	1250	700	PBWP1270	1STQ007202A0000
Bottom without plinth IP40	1250	900	PBWP1290	1STQ007203A0000




Fixed incoming cable flange

Fixed incoming cable flange in sheet metal to use in conjunction with the open bottom to guarantee IP65 protection class. With internal cable compartment crosspieces it is necessary to mount the fixed flange first.

Description	Dimensions (mm)			Pkg/ No. pcs
	W	D	Type	
Fixed incoming cable flange	250	200	PFCF2520	1STQ001274B0000
Fixed incoming cable flange	250	300	PFCF2530	1STQ007655A0000
Fixed incoming cable flange	250	500	PFCF2550	1STQ007656A0000
Fixed incoming cable flange	250	700	PFCF2570	1STQ007657A0000
Fixed incoming cable flange	250	900	PFCF2590	1STQ001275B0000
Fixed incoming cable flange	500	200	PFCF5020	1STQ001290B0000
Fixed incoming cable flange	500	300	PFCF3050	1STQ007660A0000
Fixed incoming cable flange	500	500	PFCF5050	1STQ007668A0000
Fixed incoming cable flange	500	700	PFCF5070	1STQ007669A0000
Fixed incoming cable flange	500	900	PFCF5090	1STQ001292B0000
Fixed incoming cable flange	750	200	PFCF7520	1STQ001307B0000
Fixed incoming cable flange	750	300	PFCF7530	1STQ007675A0000
Fixed incoming cable flange	750	500	PFCF7550	1STQ007676A0000
Fixed incoming cable flange	750	700	PFCF7570	1STQ007677A0000
Fixed incoming cable flange	750	900	PFCF7590	1STQ001308B0000
Fixed incoming cable flange	1000	300	PFCF1030	1STQ007683A0000
Fixed incoming cable flange	1000	500	PFCF1050	1STQ007684A0000
Fixed incoming cable flange	1000	700	PFCF1070	1STQ007685A0000
Fixed incoming cable flange	1000	900	PFCF1090	1STQ007686A0000
Fixed incoming cable flange	1250	900	2xPFCF6090	1STQ007674A0000

Dedicated solution

CombiLine-M - Order codes



Sliding incoming cable flanges in sheet metal

Sliding incoming cable flanges in sheet metal to use in conjunction with the open bottom to guarantee IP40 protection class. It is not possible to assemble the sliding flanges in structures with internal cable compartment.


Description	Dimensions (mm)			Pkg/ No. pcs
	W	D	Type	
No.2 sliding flanges	500	500	PFCS5050	1STQ007702A0000
No.2 sliding flanges	500	700	PFCS5070	1STQ007703A0000
No.2 sliding flanges	500	900	PFCS5090	1STQ001293B0000
No.2 sliding flanges	750	500	PFCS7550	1STQ007709A0000
No.2 sliding flanges	750	700	PFCS7570	1STQ007710A0000
No.2 sliding flanges	750	900	PFCS7590	1STQ001309B0000
No.2 sliding flanges	1000	500	PFCS1050	1STQ007716A0000
No.2 sliding flanges	1000	700	PFCS1070	1STQ007717A0000
No.2 sliding flanges	1000	900	PFCS1090	1STQ007718A0000
No.2 sliding flanges	1250	900	2xPFCS6090	1STQ007707A0000



External blind rear panel IP65

Pickled sheet steel with gasket and plugs IP65.

Description	Dimensions (mm)			Pkg/ No. pcs
	H	W	Type	
Blind rear panel IP65	1800	250	PPEB1825	1STQ007576A0000
Blind rear panel IP65	1800	500	PPEB1856	1STQ007579A0000
Blind rear panel IP65	1800	750	PPEB1875	1STQ007582A0000
Blind rear panel IP65	1800	1000	PPEB1816	1STQ007585A0000
Blind rear panel IP65	2000	250	PPEB2025	1STQ009380A0000
Blind rear panel IP65	2000	500	PPEB2056	1STQ008106A0000
Blind rear panel IP65	2000	750	PPEB2075	1STQ009400A0000
Blind rear panel IP65	2000	1000	PPEB2016	1STQ007596A0000




External blind rear panel IP30, IP40

Pickled sheet steel without gasket. In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit PKPT..., page 6-12.

Description	Dimensions (mm)			Pkg/ No. pcs	
	H	W	Type		
Blind rear panel IP30, IP40	1800	250	PPEB1827	1STQ009375A0000	
Blind rear panel IP30, IP40	1800	500	PPEB1850	1STQ007610A0000	
Blind rear panel IP30, IP40	1800	750	PPEB1877	1STQ009393A0000	
Blind rear panel IP30, IP40	1800	1000	PPEB1810	1STQ007615A0000	
Blind rear panel IP30, IP40	right	1800	1250	PPRB1820	1STQ007616A0000
	left	1800	1250	PPLB1820	1STQ007617A0000
Blind rear panel IP30, IP40		2000	250	PPEB2027	1STQ009381A0000
Blind rear panel IP30, IP40		2000	500	PPEB2050	1STQ007621A0000
Blind rear panel IP30, IP40		2000	750	PPEB2077	1STQ009401A0000
Blind rear panel IP30, IP40		2000	1000	PPEB2010	1STQ007626A0000
Blind rear panel IP30, IP40	right	2000	1250	PPRB2020	1STQ007627A0000
	left	2000	1250	PPLB2020	1STQ007628A0000

Dedicated solution


CombiLine-M - Order codes



External vented rear panel IP30

In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit PKPT..., page 6-12.


Description	No. Vented grates	Dimensions (mm)		Type	Order code	Pkg/ No. pcs
		H	W			
Vented rear panel IP30	2	1800	750	PPEA1875	1STQ007635A0000	1/1
Vented rear panel IP30/31 with gasket	right 6 left 6	1800	1250	PPRA1820 PPLA1820	1STQ007639A0000 1STQ007640A0000	1/1 1/1
Vented rear panel IP30	2	2000	750	PPEA2075	1STQ009919A0000	1/1
Vented rear panel IP30 with gasket	right 4 left 4	2000	1250	PPRA2020 PPLA2020	1STQ007649A0000 1STQ007650A0000	1/1 1/1



External blind side panel IP65

Pickled sheet steel with gasket and plugs IP65. The code refers to one single side panel.

Description	Dimensions (mm)			Type	Order code	Pkg/ No. pcs
	H	D	Type			
Blind side panel IP65	1800	200	PPEB1826	1STQ007575A0000		1/1
Blind side panel IP65	1800	300	PPEB1836	1STQ007577A0000		1/1
Blind side panel IP65	1800	500	PPEB1856	1STQ007579A0000		1/1
Blind side panel IP65	1800	700	PPEB1876	1STQ007581A0000		1/1
Blind side panel IP65	1800	900	PPEB1896	1STQ007584A0000		1/1
Blind side panel IP65	2000	200	PPEB2026	1STQ007588A0000		1/1
Blind side panel IP65	2000	300	PPEB2036	1STQ007589A0000		1/1
Blind side panel IP65	2000	500	PPEB2056	1STQ008106A0000		1/1
Blind side panel IP65	2000	700	PPEB2076	1STQ008107A0000		1/1
Blind side panel IP65	2000	900	PPEB2096	1STQ008108A0000		1/1




External blind side panel IP30, IP40

Pickled sheet steel with gasket. The code refers to one single side panel. In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit PKPT..., page 6-12.

Description	Dimensions (mm)			Type	Order code	Pkg/ No. pcs
	H	D	Type			
Blind side panel IP30, IP40	1800	200	PPEB1820	1STQ007607A0000		1/1
Blind side panel IP30, IP40	1800	300	PPEB1830	1STQ007608A0000		1/1
Blind side panel IP30, IP40	1800	500	PPEB1850	1STQ007610A0000		1/1
Blind side panel IP30, IP40	1800	700	PPEB1870	1STQ007612A0000		1/1
Blind side panel IP30, IP40	1800	900	PPEB1890	1STQ007614A0000		1/1
Blind side panel IP30, IP40	2000	200	PPEB2020	1STQ007618A0000		1/1
Blind side panel IP30, IP40	2000	300	PPEB2030	1STQ007619A0000		1/1
Blind side panel IP30, IP40	2000	500	PPEB2050	1STQ007621A0000		1/1
Blind side panel IP30, IP40	2000	700	PPEB2070	1STQ007623A0000		1/1
Blind side panel IP30, IP40	2000	900	PPEB2090	1STQ007625A0000		1/1

Dedicated solution

CombiLine-M - Order codes



External vented rear panel IP30

In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit PKPT...., page 6-12.

Description	No. Vented grates	Dimensions (mm)		Type	Order code	Pkg/ No. pcs
		H	D			
Vented side panel IP30	2	1800	300	PPEA1830	1STQ007630A0000	1/1
Vented side panel IP30	2	1800	500	PPEA1850	1STQ007632A0000	1/1
Vented side panel IP30	2	1800	700	PPEA1870	1STQ007634A0000	1/1
Vented side panel IP30	4	1800	900	PPEA1890	1STQ007637A0000	1/1
Vented side panel IP30	2	2000	300	PPEA2030	1STQ007641A0000	1/1
Vented side panel IP30	2	2000	500	PPEA2050	1STQ007643A0000	1/1
Vented side panel IP30	2	2000	700	PPEA2070	1STQ007645A0000	1/1
Vented side panel IP30	4	2000	900	PPEA2090	1STQ007647A0000	1/1




IP40 grate for Vented external panels

Accessory for Vented panels. Allows IP40 protection class to be obtained. Order the quantity on the basis of the number of grates on the panel. In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit PKPT...., page 6-12.

Description	Type	Order code	Pkg/ No. pcs
No. IP40 grates for Vented panels	PGPP0040	1STQ008090A0000	1/2


Dedicated solution

CombiLine-M - Order codes




Glass door IP65

Pickled sheet steel with gasket. Opens through 135° (single column). Complete with 4 hinges to be screwed onto the uprights, 4 door closing brackets with cover and handle. Handle and hinges provided (not pre-assembled for complete reversibility). Doors can be mounted both on the front and on the back of the enclosures.




Description	Dimensions (mm)			Pkg/ No. pcs
	H	W	Type	
Glass door IP65	1800	500	PDLG1856	1STQ009414A0000
Glass door IP65	1800	750	PDLG1876	1STQ009396A0000
Glass door IP65	1800	1000	PDLG1816	1STQ007311A0000
Glass door IP65	2000	500	PDLG2056	1STQ009420A0000
Glass door IP65	2000	750	PDLG2066	1STQ007316A0000
Glass door IP65	2000	1000	PDLG2076	1STQ009404A0000



Glass door IP40


Pickled sheet steel without gasket and 4 rubber overlapping plugs. Opens through 135° (single column). Complete with 4 hinges to be screwed onto the uprights, 4 door closing brackets with cover and handle. Handle and hinges provided (not pre-assembled for complete reversibility). In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit PKPT...., page 6-12. Doors can be mounted both on the front and on the back of the enclosures.



Description	Dimensions (mm)			Pkg/ No. pcs
	H	W	Type	
Glass door IP40	1800	500	PDLG1850	1STQ009415A0000
Glass door IP40	1800	750	PDLG1870	1STQ009397A0000
Glass door IP40	1800	1000	PDLG1810	1STQ007333A0000
Glass door IP40	2000	500	PDLG2050	1STQ009421A0000
Glass door IP40	2000	750	PDLG2070	1STQ009405A0000
Glass door IP40	2000	1000	PDLG2010	1STQ007344A0000


Dedicated solution

CombiLine-M - Order codes




Blind door IP65

Pickled sheet steel with gasket. Opens through 135° (single column). Complete with 4 hinges to be screwed onto the uprights, 4 door closing brackets with cover and handle. Handle and hinges provided (not pre-assembled for complete reversibility). Doors can be mounted both on the front and on the back of the enclosures. Reinforcing tubes for W>400mm




Description	Dimensions (mm)			Pkg/ No. pcs
	H	W	Type	
Blind door IP65	1800	250	PDLB1826	1/1
Blind door IP65	1800	500	PDLB1856	1/1
Blind door IP65	1800	750	PDLB1876	1/1
Blind door IP65	1800	1000	PDLB1816	1/1
Blind door IP65	2000	250	PDLB2026	1/1
Blind door IP65	2000	500	PDLB2056	1/1
Blind door IP65	2000	750	PDLB2076	1/1
Blind door IP65	2000	1000	PDLB2016	1/1



Blind door IP40


Pickled sheet steel without gasket and 4 rubber overlapping plugs. Opens through 135° (single column). Complete with 4 hinges to be screwed onto the uprights, 4 door closing brackets with cover and handle. Handle and hinges provided (not pre-assembled for complete reversibility). In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit PKPT..., page 6-12. Doors can be mounted both on the front and on the back of the enclosures. Reinforcing tubes for W>400mm



Description	Dimensions (mm)			Pkg/ No. pcs
	H	W	Type	
Blind door IP40/IP41	1800	250	PDLB1825	1/1
Blind door IP40/IP41	1800	500	PDLB1850	1/1
Blind door IP40/IP41	1800	750	PDLB1875	1/1
Blind door IP40/IP41	1800	1000	PDLB1810	1/1
Blind door IP40/IP41	2000	250	PDLB2025	1/1
Blind door IP40/IP41	2000	500	PDLB2050	1/1
Blind door IP40/IP41	2000	750	PDLB2075	1/1
Blind door IP40/IP41	2000	1000	PDLB2010	1/1

Dedicated solution


CombiLine-M - Order codes



Horizontal/vertical front closing profiles IP30

Profiles for IP30/IP31 pickled sheet painted RAL 7035. In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit PKPT...., page 6-12.

Description	Dimensions (mm)			Pkg/ No. pcs
	H	W	Type	
Finishing profiles vertical structure and external cable compartment				
No.2 vertical profiles IP30	1800	PPFV1800	1STQ008059A0000	1/2
No.2 vertical profiles IP30	2000	PPFV2000	1STQ008060A0000	1/2
Finishing profile vertical internal cable compartment				
No.1 profile vertical IP30	1800	PPCV1800	1STQ009294A0000	1/1
No.1 profile vertical IP30	2000	PPCV2000	1STQ009295A0000	1/1
Finishing profiles horizontal structure and external cable compartment				
No.2 horizontal profiles IP30	250	PPFH0250	1STQ009378A0000	1/2
No.2 horizontal profiles IP30	500	PPFH0500	1STQ009416A0000	1/2
No.2 horizontal profiles IP30	750	PPFH0750	1STQ009398A0000	1/2
No.2 horizontal profiles IP30	1000	PPFH1000	1STQ008057A0000	1/2
No.2 horizontal profiles IP30	1250	PPFH1250	1STQ008058A0000	1/2



Crosspiece for horizontal busbar assembly under top or on bottom of structure

For assembly in D>300mm structures with internal cable compartment, order PCCM.... cable compartment depth.


Description	Dimensions (mm)			Pkg/ No. pcs
	W	Type	Order code	
Intermediate crosspiece for busbars under top/on bottom	250	PCKI0250	1STQ001328B0000	1/1
Intermediate crosspiece for busbars under top/on bottom	500	PCIS0500	1STQ009165A0000	1/1
Intermediate crosspiece for busbars under top/on bottom	750	PCKI0750	1STQ001330B0000	1/1
Intermediate crosspiece for busbars under top/on bottom	1000	PCKI1000	1STQ008103A0000	1/1
Intermediate crosspiece for busbars under top/on bottom	1250	PCKI1250	1STQ008104A0000	1/1

Dedicated solution

CombiLine-M - Order codes

Configuration example

Functional dimensions 2000x750x500mm (HxWxD) structure with H=100mm plinth, adapted to CombiLine-M fixing. WR frame and CombiLine-M modules to be added.



Quantity	Order code	Part	Description
1	PUPM2000	Structure	No. 4 galvanized sheet uprights H=2000mm
1	PCFM0750	Structure	No. 4 width stainless steel crosspieces W=750mm
1	PCFM0500	Structure	No. 4 depth galvanized sheet crosspieces D=500mm
1	PPAM0100	Structure	No. 4 corners plinth H=100mm
1	PPFM1075	Structure	No. 2 front/rear plinth flanges W=750mm
1	PPFM1050	Structure	No. 2 side plinth flanges D=500mm
2	PTBB7550	External covers	IP30/31, 40/41 blind top/bottom W=750mm D=500mm
1	PPEB2077	External covers	IP30/31, IP40/41 blind back panel H=2000mm W=750mm
2	PPEB2050	External covers	IP30/IP31, IP40/IP41 blind side panel H=2000mm D=500mm
1	PDLB2075	External covers	IP40/IP41 blind door H=2000mm W=750mm
1	PCTG2075	CombiLine-M adaptors	Touch Guard profile H2000 W750
1	PBCM0004	CombiLine-M adaptors	CombiLine-M fixing set
1	PCCM2075	CombiLine-M adaptors	CombiLine-M adapter H=2000 W=750

Dedicated solution


InLine II - General information

Introduction

The latest technology of Fuse Switch Disconnectors.

The new generation InLine II ensures the best stability and the highest safety in the power distribution network during operation and service.


Feature	InLine II ZLBM/ZHBM	
Rated operational voltage Ue	[V]	400 / 500 / 690
Rated operational current Ie	[A]	125...630





Dedicated solution

InLine II - Quick selection guide



H=1800mm recommended installation solutions

Functional dimensions	External dimensions	FRAME					EXTERNAL COVERS									
		Uprights	Structure crosspieces		H=100mm plinth			Top/bottom panels				Front/rear/side panels				
		Galvanized sheet metal In≤4000A *		Intermediate upright	Galvanized sheet metal In≤4000A *			Top/Bottom			Bottom	Rear panel				
								Plinth flanges			Without plinth	Blind				
Height	Height	Galvanized sheet metal *						Plinth flanges			Open ⁽²⁾	Blind				
1800mm	1913mm															
W (mm)	D (mm)	W (mm)	D (mm)	Front/Rear	Sides	Angle pieces	Front/Rear	Sides	IP30 ⁽¹⁾	IP40 ⁽¹⁾	IP65	IP40 ⁽³⁾	IP65	IP30 ⁽¹⁾		
600	500	700	616	PUPM1800	PCFM0600	PCFM0500	PUKI1800	PPMA0100	PPFM1060	PPFM1050	PTBB6056	PTBB6050	PTBO6050	PBWP2550	PPEB1866	PPEB1860
		700	816			PCFM0700			PPFM1070	PTBB6076	PTBB6070	PTBO6070		PBWP2570		
		900	1016			PCFM0900			PPFM1090	PTBB6096	PTBB6090	PTBO6090		PBWP2590		
800	500	900	616	PUPM1800	PCFM0800	PCFM0500	PUKI1800	PPMA0100	PPFM1060	PPFM1050	PTBB8050	PTBB8050	PTBO5050	PBWP5050	PPEB1886	PPEB1880
		700	816			PCFM0700			PPFM1070	PTBB8076	PTBB8070	PTBO5070		PBWP5070		
		900	1016			PCFM0900			PPFM1090	PTBB8096	PTBB8090	PTBO5090		PBWP5090		
1000	500	1000	616	PUPM1800	PCFM1000	PCFM0500	PUKI1800	PPMA0100	PPFM1060	PPFM1050	PTBB1056	PTBB1050	PTBO1050	PBWP1050	PPEB1816	PPEB1810
		700	816			PCFM0700			PPFM1070	PTBB1076	PTBB1070	PTBO1070		PBWP1070		
		900	1016			PCFM0900			PPFM1090	PTBB1096	PTBB1090	PTBO1090		PBWP1090		

H=2000mm recommended installation solutions

Functional dimensions	External dimensions	FRAME						EXTERNAL COVERS									
		Uprights		Structure crosspieces		H=100mm plinth		Top/bottom panels				Front/rear/side panels					
		Galvanized sheet metal In≤4000A *		Intermediate upright		Galvanized sheet metal In≤4000A *		Top/Bottom				Bottom		Rear panel			
		Plinth flanges				Blind				Open ⁽²⁾		Without plinth		Blind			
Height 1800mm	Height 1913mm	Galvanized sheet															
W (mm)	D (mm)	W (mm)	D (mm)	metal * In≤4000A	Front/Rear	Sides	Angle pieces	Front/Rear	Sides	IP30 ⁽¹⁾	IP40 ⁽¹⁾	IP65	IP65	IP40 ⁽³⁾	IP65	IP30 ⁽¹⁾	IP40 ⁽¹⁾
600	500	700	616	PUPM2000	PCFM0600	PCFM0500	PUKI2000	PPMA0100	PPFM1060	PPFM1050	PTBB6056	PTBB6050	PTBO6050	PBWP2550	PPEB2066	PPEB2060	
		700	816			PCFM0700				PPFM1070	PTBB6076	PTBB6070	PTBO6070	PBWP2570			
		900	1016			PCFM0900				PPFM1090	PTBB6096	PTBB6090	PTBO6090	PBWP2590			
800	500	900	616	PUPM2000	PCFM0800	PCFM0500	PUKI2000	PPMA0100	PPFM1060	PPFM1050	PTBB8050	PTBB8050	PTBO5050	PBWP5050	PPEB2086	PPEB2080	
		700	816			PCFM0700				PPFM1070	PTBB8076	PTBB8070	PTBO5070	PBWP5070			
		900	1016			PCFM0900				PPFM1090	PTBB8096	PTBB8090	PTBO5090	PBWP5090			
1000	500	1000	616	PUPM2000	PCFM1000	PCFM0500	PUKI2000	PPMA0100	PPFM1060	PPFM1050	PTBB1056	PTBB1050	PTBO1050	PBWP1050	PPEB2016	PPEB2010	
		700	816			PCFM0700				PPFM1070	PTBB1076	PTBB1070	PTBO1070	PBWP1070			
		900	1016			PCFM0900				PPFM1090	PTBB1096	PTBB1090	PTBO1090	PBWP1090			


Also available in stainless steel, see page 2/8

Also available in stainless steel, see page 2/8.
Consult page 2/12 and 7/2 for selection of the protection class.

⁽¹⁾ In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit, page 2/23.

⁽²⁾ Use the dedicated incoming cable flanges to obtain protection class IP65

(3) Bottom for switchboard without plinth complete with the dedicated set of brackets, which can be ordered separately

**INLINE II****Finishing profiles IP30**


Side panel			Glass door 24/36/48 mod. DIN		Blind door 24/36/48 mod. DIN		Horizontal profile		InLine II kit	Fixed frame	Front panels
Vented	Blind	Vented									
IP30 ⁽¹⁾ PPEA1860	IP65 PPEB1856	IP30 ⁽¹⁾ IP40 ⁽¹⁾ PPEB1850	IP30 ⁽¹⁾ PPEA1850	IP65 PDLG1866	IP40 ⁽¹⁾ PDLG1860	IP65 PDLB1866	IP40 ⁽¹⁾ PPFV1800	Vertical profile PPFH0600	InLine II kit PKNL1260	Fixed frame PFNL1860	Front panels No.2 PPNL3060
	PPEB1876	PPEB1870	PPEA1870								
	PPEB1896	PPEB1890	PPEA1890								
PPEA1880	PPEB1856 PPEB1876 PPEB1896	PPEB1850 PPEB1870 PPEB1890	PPEA1850 PPEA1870 PPEA1890	PDLG1886	PDLG1880	PDLB1886	PDLB1880	PPFV1800 PPFH0800	PKNL1280	PFNL1880	No.2 PPNL3080
PPEA1810	PPEB1856 PPEB1876 PPEB1896	PPEB1850 PPEB1870 PPEB1890	PPEA1850 PPEA1870 PPEA1890	PDLG1816	PDLG1810	PDLB1816	PDLB1810	PPFV1800 PPFH1000	PKNL1210	PFNL1810	No.2 PPNL3010

INLINE II**Finishing profiles IP30**

Side panel			Glass door 24/36/48 mod. DIN		Blind door 24/36/48 mod. DIN		Horizontal profile		InLine II kit	Fixed frame	Front panels
Vented	Blind	Vented									
IP30 ⁽¹⁾ PPEA2060	IP65 PPEB1856	IP30 ⁽¹⁾ IP40 ⁽¹⁾ PPEB1850	IP30 ⁽¹⁾ PPEA1850	IP65 PDLG2066	IP40 ⁽¹⁾ PDLG2060	IP65 PDLB2066	IP40 ⁽¹⁾ PPFV2000	Vertical profile PPFH0600	InLine II kit PKNL1260	Fixed frame PFNL2060	Front panels No.2 PPNL4060
	PPEB1876	PPEB1870	PPEA1870								
	PPEB1896	PPEB1890	PPEA1890								
PPEA2080	PPEB1856 PPEB1876 PPEB1896	PPEB1850 PPEB1870 PPEB1890	PPEA1850 PPEA1870 PPEA1890	PDLG2086	PDLG2080	PDLB2086	PDLB2080	PPFV2000 PPFH0800	PKNL1280	PFNL2080	No.2 PPNL4080
PPEA2010	PPEB1856 PPEB1876 PPEB1896	PPEB1850 PPEB1870 PPEB1890	PPEA1850 PPEA1870 PPEA1890	PDLG2016	PDLG2010	PDLB2016	PDLB2010	PPFV2000 PPFH1000	PKNL1210	PFNL2010	No.2 PPNL4010

Dedicated solution


InLine II - Order codes



InLine II mounting kit

Kit for the fixing of InLine II fuseholders


Description	Dimensions (mm)			Pkg/ No. pcs
	H	W	Type	
InLine mounting kit + front panel	1200	600	PKNL1260	1STQ009823A0000
InLine mounting kit + front panel	1200	800	PKNL1280	1STQ009847A0000
InLine mounting kit + front panel	1200	1000	PKNL1210	1STQ009863A0000



Fixed frame for InLine II panels

Fixed frame for InLine II internal panels. InLine II fixed frame allows to fit only InLine II panels listed below.

Description	Dimensions (mm)			Pkg/ No. pcs
	H	W	Type	
Fixed frame for panels in the InLine column	1800	600	PFNL1860	1STQ001372B0000
Fixed frame for panels in the InLine column	1800	800	PFNL1880	1STQ001374B0000
Fixed frame for panels in the InLine column	1800	1000	PFNL1810	1STQ001376B0000
Fixed frame for panels in the InLine column	2000	600	PFNL2060	1STQ001373B0000
Fixed frame for panels in the InLine column	2000	800	PFNL2080	1STQ001375B0000
Fixed frame for panels in the InLine column	2000	1000	PFNL2010	1STQ001377B0000




Flat blind panels for InLine II fixed frame

Panels with 1/4 turn screws, hinged on the right or left with the dedicated PHFP0020 kit. These panels are dedicated to InLine II fixed frame only.

Description	Dimensions (mm)			Pkg/ No. pcs
	H	W	Type	
Blind flat panel for InLine column	300	600	PPNL3060	1STQ001378B0000
Blind flat panel for InLine column	300	800	PPNL3080	1STQ001379B0000
Blind flat panel for InLine column	300	1000	PPNL3010	1STQ001380B0000
Blind flat panel for InLine column	400	600	PPNL4060	1STQ001381B0000
Blind flat panel for InLine column	400	800	PPNL4080	1STQ001382B0000
Blind flat panel for InLine column	400	1000	PPNL4010	1STQ001383B0000

Order 2 pieces for a complete structure.




InLine II dummy modules

Dummy modules InLine II to cover free space in the enclosure and guarantee touch protection.

Description	Dimensions (mm)			Pkg/ No. pcs
	W	Type	Order code	
InLine vertical compensator	50	PCNL0050	1STQ009406A0000	1/1
InLine vertical compensator	100	PCNL0100	1STQ009368A0000	1/1

Dedicated solution

InLine II - Order codes



Uprights – Galvanized sheet metal *

Upright formed by a closed profile made of galvanized sheet metal. The uprights include 8 already assembled 3-way joints, 8 already assembled axial screws and 16 loose axial screws. For applications with In ≤4000A.

Description	Dimensions (mm)			Pkg/ No. pcs
	H	Type	Order code	
No.4 galvanized sheet metal uprights	1800	PUPM1800	1STQ007033A0000	1/4
No.4 galvanized sheet metal uprights	2000	PUPM2000	1STQ007034A0000	1/4

* Also available in stainless steel, see page 2/15.




Structure crosspieces – Galvanized sheet metal *

Depth and width crosspieces for structures in galvanized sheet metal. For applications with ≤4000A.

Description	Dimensions (mm)			Pkg/ No. pcs
	W	D	Type	
Width crosspieces				
No.4 width crosspieces galvanized sheet metal	600		PCFM0600	1STQ007040A0000
No.4 width crosspieces galvanized sheet metal	800		PCFM0800	1STQ007042A0000
No.4 width crosspieces galvanized sheet metal	1000		PCFM1000	1STQ007043A0000
Depth crosspieces				
No.4 width crosspieces galvanized sheet metal	500		PCFM0500	1STQ007039A0000
No.4 width crosspieces galvanized sheet metal	700		PCFM0700	1STQ007046A0000
No.4 width crosspieces galvanized sheet metal	900		PCFM0900	1STQ007047A0000

* Also available in stainless steel, see page 2/15.



Intermediate upright for internal kit assembly


Intermediate depth upright for assembling kits for Tmax and Emax 2. The intermediate uprights are not required for assembling fixed Tmax XT1, XT2, XT3, XT4, T4, T5, T6 and XT1, XT3 with Direct Rotary Handle only in nonsegregated structures. Order 2 uprights for the kits.

Description	Dimensions (mm)			Pkg/ No. pcs
	H	Type	Order code	
Intermediate upright for internal kits	1800	PUKI1800	1STQ008039A0000	1/1
Intermediate upright for internal kits	2000	PUKI2000	1STQ008040A0000	1/1


Dedicated solution

InLine II - Order codes

PPAM0100



PPAM0200




Universal angle pieces for plinths in galvanized sheet metal

Not pre-assembled to the structure. New angle piece with high mechanical strength. Can be fixed from the outside and from the inside of the structure even at a later date. Equipped with anti-rotation system and bottom that can be transported with a transpallet.

Description	Dimensions (mm)			Pkg/ No. pcs
	H	Type	Order code	
No.4 plinth angle pieces	100	PPAM0100	1STQ007048A0000	1/4
No.8 plinth angle pieces	200	PPAM0200	1STQ007207A0000	1/4
H=100mm pre-assembled*				


*Order no. 2 pieces of H=100mm covering flange kits to complete the H=200mm plinth.



Plinth flanges

Side and front/rear plinth flanges H=100mm RAL 7012.

Description	Dimensions (mm)			Pkg/ No. pcs
	W	D	Type	
Front/rear plinth flanges				
No.2 plinth flanges	600		PPFM1060	1STQ007053A0000
No.2 plinth flanges	800		PPFM1080	1STQ007055A0000
No.2 plinth flanges	1000		PPFM1010	1STQ007056A0000
Side plinth flanges				
No.2 plinth flanges		500	PPFM1050	1STQ007052A0000
No.2 plinth flanges		700	PPFM1070	1STQ007059A0000
No.2 plinth flanges		900	PPFM1090	1STQ007060A0000




Blind Top/Bottom IP65 – Pickled sheet steel

Pickled sheet steel with IP65 gasket. The article comprises one single component that can be used as either a top or bottom. In order to purchase both the top and the bottom, please order two quantities of the same code or two different top/bottom codes according to the desired design of the structure. The code includes four M12x20 screws.

Description	Dimensions (mm)			Pkg/ No. pcs
	W	D	Type	
Blind Top/Bottom IP65	600	500	PTBB6056	1STQ007088A0000
Blind Top/Bottom IP65	600	700	PTBB6076	1STQ007089A0000
Blind Top/Bottom IP65	600	900	PTBB6096	1STQ007090A0000
Blind Top/Bottom IP65	800	500	PTBB8056	1STQ007096A0000
Blind Top/Bottom IP65	800	700	PTBB8076	1STQ007097A0000
Blind Top/Bottom IP65	800	900	PTBB8096	1STQ007098A0000
Blind Top/Bottom IP65	1000	500	PTBB1056	1STQ007100A0000
Blind Top/Bottom IP65	1000	700	PTBB1076	1STQ007101A0000
Blind Top/Bottom IP65	1000	900	PTBB1096	1STQ007102A0000

Dedicated solution


InLine II - Order codes



Blind Top/Bottom IP30, IP40 – Pickled sheet steel

Pickled sheet steel without gasket. In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit, page 6-12. The article comprises one single component that can be used as either a top or bottom. In order to purchase both the top and the bottom, please order two quantities of the same code or two different top/bottom codes according to the desired design of the structure. The code includes four M12x20 screws.

Description	Dimensions (mm)			Pkg/ No. pcs
	W	D	Type	
Blind Top/Bottom IP30, 40	600	500	PTBB6050	1STQ007119A0000
Blind Top/Bottom IP30, 40	600	700	PTBB6070	1STQ007120A0000
Blind Top/Bottom IP30, 40	600	900	PTBB6090	1STQ007121A0000
Blind Top/Bottom IP30, 40	800	500	PTBB8050	1STQ007124A0000
Blind Top/Bottom IP30, 40	800	700	PTBB8070	1STQ007125A0000
Blind Top/Bottom IP30, 40	800	900	PTBB8090	1STQ007126A0000
Blind Top/Bottom IP30, 40	1000	500	PTBB1050	1STQ007128A0000
Blind Top/Bottom IP30, 40	1000	700	PTBB1070	1STQ007129A0000
Blind Top/Bottom IP30, 40	1000	900	PTBB1090	1STQ007130A0000




Blind Top/Bottom IP65 – Pickled sheet steel

Pickled sheet steel with IP65 gasket. The article comprises one single component that can be used as either a top or bottom. In order to purchase both the top and the bottom, please order two quantities of the same code or two different top/bottom codes according to the desired design of the structure. The code includes four M12x20 screws.

Description	Dimensions (mm)			Pkg/ No. pcs
	W	D	Type	
IP65 blind top/bottom	250	200	PTBB2526	1STQ001270B0000
IP65 blind top/bottom	250	300	PTBB2536	1STQ007071A0000
IP65 blind top/bottom	250	500	PTBB2556	1STQ007072A0000
IP65 blind top/bottom	250	700	PTBB2576	1STQ007073A0000
IP65 blind top/bottom	250	900	PTBB2596	1STQ001271B0000
IP65 blind top/bottom	500	200	PTBB5026	1STQ001284B0000
IP65 blind top/bottom	500	300	PTBB3056	1STQ007076A0000
IP65 blind top/bottom	500	500	PTBB5050	1STQ009179A0000
IP65 blind top/bottom	500	700	PTBB5076	1STQ007085A0000
IP65 blind top/bottom	500	900	PTBB5096	1STQ001286B0000
IP65 blind top/bottom	750	200	PTBB7526	1STQ001303B0000
IP65 blind top/bottom	750	300	PTBB7536	1STQ007091A0000
IP65 blind top/bottom	750	500	PTBB7556	1STQ007092A0000
IP65 blind top/bottom	750	700	PTBB7576	1STQ007093A0000
IP65 blind top/bottom	750	900	PTBB7596	1STQ001304B0000
Blind Top/Bottom IP65	1000	200	PTBB1026	1STQ009178A0000
Blind Top/Bottom IP65	1000	300	PTBB1036	1STQ007099A0000
Blind Top/Bottom IP65	1000	500	PTBB1056	1STQ007100A0000
Blind Top/Bottom IP65	1000	700	PTBB1076	1STQ007101A0000
Blind Top/Bottom IP65	1000	900	PTBB1096	1STQ007102A0000

Dedicated solution

InLine II - Order codes



Top sealing kit IP31/IP41 *


Profiles for IP31/IP41 for top.

Description	Dimensions (mm)			Pkg/ No. pcs
	W	D	Type	
N.2 roof profiles for single column	200	PKST0200	1STQ001905B0000	1/2
N.2 roof profiles for single column	300	PKST0301	1STQ001935B0000	1/1
N.2 roof profiles for single column	500	PKST0501	1STQ001936B0000	1/1
N.2 roof profiles for single column	700	PKST0700	1STQ001911B0000	1/2
N.2 roof profiles for single column	900	PKST0900	1STQ001914B0000	1/2
N.2 roof profiles for single column	250	PKST0250	1STQ001906B0000	1/2
N.2 roof profiles for single column	300	PKST0300	1STQ001907B0000	1/2
N.2 roof profiles for single column	400	PKST0400	1STQ001908B0000	1/2
N.2 roof profiles for single column	500	PKST0500	1STQ001909B0000	1/2
N.2 roof profiles for single column	600	PKST0600	1STQ001910B0000	1/2
N.2 roof profiles for single column	750	PKST0750	1STQ001912B0000	1/2
N.2 roof profiles for single column	800	PKST0800	1STQ001913B0000	1/2
N.2 roof profiles for single column	1000	PKST1000	1STQ001915B0000	1/2
N.2 roof profiles for single column	1250	PKST1250	1STQ001916B0000	1/2
N.1 roof profile for side by side column	200	PKDT0200	1STQ001917B0000	1/1
N.1 roof profile for side by side column	300	PKDT0301	1STQ001937B0000	1/1
N.1 roof profile for side by side column	700	PKDT0700	1STQ001923B0000	1/1
N.1 roof profile for side by side column	900	PKDT0900	1STQ001926B0000	1/1
N.1 roof profile for side by side column	500	PKDT0501	1STQ001938B0000	1/1
N.1 roof profile for back to back column	250	PKDT0250	1STQ001918B0000	1/1
N.1 roof profile for back to back column	300	PKDT0300	1STQ001919B0000	1/1
N.1 roof profile for back to back column	400	PKDT0400	1STQ001920B0000	1/1
N.1 roof profile for back to back column	500	PKDT0500	1STQ001921B0000	1/1
N.1 roof profile for back to back column	600	PKDT0600	1STQ001922B0000	1/1
N.1 roof profile for back to back column	750	PKDT0750	1STQ001924B0000	1/1
N.1 roof profile for back to back column	800	PKDT0800	1STQ001925B0000	1/1
N.1 roof profile for back to back column	1000	PKDT1000	1STQ001927B0000	1/1
N.1 roof profile for back to back column	1250	PKDT1250	1STQ001928B0000	1/1
Roof profiles for corner structure	500	500	PKAT5050	1STQ001939B0000
Roof profiles for corner structure	700	700	PKAT7070	1STQ001941B0000
Roof profiles for corner structure	900	900	PKAT9090	1STQ001943B0000

*Available from January 2016.

Dedicated solution

InLine II - Order codes




Open Top/Bottom

Pickled sheet steel with holes. The code comprises one single component that can be used as either a top or bottom. In order to purchase both the top and the bottom, please order two quantities of the same code or two different top/bottom codes according to the desired design of the structure.

In order to reach IP65 protection degree, use the dedicated fixed cable incoming flanges PFCF....; in order to reach IP40 protection degree, use the dedicated swinging cable incoming flanges PFCS.... at page 4/28-4/29. The use of the single open top/bottom without flanges does not guarantee any degree of protection IP. The open top/bottom, associated with sliding flanges, is incompatible with crosspieces assembled inside the cable compartment.


Description	Dimensions (mm)			Pkg/ No. pcs
	W	D	Type	
Open Top/Bottom	600	500	PTBO6050	1STQ007149A0000
Open Top/Bottom	600	700	PTBO6070	1STQ007150A0000
Open Top/Bottom	600	900	PTBO6090	1STQ007151A0000
Open Top/Bottom	800	500	PTBO8050	1STQ007157A0000
Open Top/Bottom	800	700	PTBO8070	1STQ007158A0000
Open Top/Bottom	800	900	PTBO8090	1STQ007159A0000
Open Top/Bottom	1000	500	PTBO1050	1STQ007161A0000
Open Top/Bottom	1000	700	PTBO1070	1STQ007162A0000
Open Top/Bottom	1000	900	PTBO1090	1STQ007163A0000



Internal bottom IP40

Internal galvanized steel bottom with special brackets kit included (special brackets kit available also as spare part with the code PBRB0004). In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit PKPT..., page 6-12.

Description	Dimensions (mm)			Pkg/ No. pcs
	W	D	Type	
Internal bottom	600	500	PBWP6050	1STQ007185A0000
Internal bottom	600	700	PBWP6070	1STQ007186A0000
Internal bottom	600	900	PBWP6090	1STQ007187A0000
Internal bottom	800	500	PBWP8050	1STQ007193A0000
Internal bottom	800	700	PBWP8070	1STQ007194A0000
Internal bottom	800	900	PBWP8090	1STQ007195A0000
Internal bottom	1000	500	PBWP1050	1STQ007197A0000
Internal bottom	1000	700	PBWP1070	1STQ007198A0000
Internal bottom	1000	900	PBWP1090	1STQ007199A0000




Fixed incoming cable flange

Fixed incoming cable flange in sheet metal to use in conjunction with the open bottom to guarantee IP65 protection class. With internal cable compartment crosspieces it is necessary to mount the fixed flange first.

Description	Dimensions (mm)			Pkg/ No. pcs
	W	D	Type	
Fixed incoming cable flange	600	500	PFCF6050	1STQ007672A0000
Fixed incoming cable flange	600	700	PFCF6070	1STQ007673A0000
Fixed incoming cable flange	600	900	PFCF6090	1STQ007674A0000
Fixed incoming cable flange	800	500	PFCF8050	1STQ007680A0000
Fixed incoming cable flange	800	700	PFCF8070	1STQ007681A0000
Fixed incoming cable flange	800	900	PFCF8090	1STQ007682A0000
Fixed incoming cable flange	1000	500	PFCF1050	1STQ007684A0000
Fixed incoming cable flange	1000	700	PFCF1070	1STQ007685A0000
Fixed incoming cable flange	1000	900	PFCF1090	1STQ007686A0000

Dedicated solution


InLine II - Order codes



Sliding incoming cable flanges in sheet metal

Sliding incoming cable flanges in sheet metal to use in conjunction with the open bottom to guarantee IP40 protection class. It is not possible to assemble the sliding flanges in structures with internal cable compartment.


Description	Dimensions (mm)			Order code	Pkg/ No. pcs
	W	D	Type		
No.2 sliding flanges	600	500	PFCS6050	1STQ007705A0000	1/2
No.2 sliding flanges	600	700	PFCS6070	1STQ007706A0000	1/2
No.2 sliding flanges	600	900	PFCS6090	1STQ007707A0000	1/2
No.2 sliding flanges	800	500	PFCS8050	1STQ007712A0000	1/2
No.2 sliding flanges	800	700	PFCS8070	1STQ007713A0000	1/2
No.2 sliding flanges	800	900	PFCS8090	1STQ007714A0000	1/2
No.2 sliding flanges	1000	500	PFCS1050	1STQ007716A0000	1/2
No.2 sliding flanges	1000	700	PFCS1070	1STQ007717A0000	1/2
No.2 sliding flanges	1000	900	PFCS1090	1STQ007718A0000	1/2



External blind rear panel IP65

Pickled sheet steel with gasket and plugs IP65.

Description	Dimensions (mm)			Order code	Pkg/ No. pcs
	H	W	Type		
Blind rear panel IP65	1800	600	PPEB1866	1STQ007580A0000	1/1
Blind rear panel IP65	1800	800	PPEB1886	1STQ007583A0000	1/1
Blind rear panel IP65	1800	1000	PPEB1816	1STQ007585A0000	1/1
Blind rear panel IP65	2000	600	PPEB2066	1STQ007592A0000	1/1
Blind rear panel IP65	2000	800	PPEB2086	1STQ007594A0000	1/1
Blind rear panel IP65	2000	1000	PPEB2016	1STQ007596A0000	1/1




External blind rear panel IP30, IP40

Pickled sheet steel without gasket. In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit PKPT..., page 6-12.

Description	Dimensions (mm)			Order code	Pkg/ No. pcs
	H	W	Type		
Blind rear panel IP30, IP40	1800	600	PPEB1860	1STQ007611A0000	1/1
Blind rear panel IP30, IP40	1800	800	PPEB1880	1STQ007613A0000	1/1
Blind rear panel IP30, IP40	1800	1000	PPEB1810	1STQ007615A0000	1/1
Blind rear panel IP30, IP40	2000	600	PPEB2060	1STQ007622A0000	1/1
Blind rear panel IP30, IP40	2000	800	PPEB2080	1STQ007624A0000	1/1
Blind rear panel IP30, IP40	2000	1000	PPEB2010	1STQ007626A0000	1/1

Dedicated solution


InLine II - Order codes



External vented rear panel IP30

In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit PKPT...., page 6-12.


Description	No. Vented grates	Dimensions (mm)		Type	Order code	Pkg/ No. pcs
		H	W			
Vented rear panel IP30	2	1800	600	PPEA1860	1STQ007633A0000	1/1
Vented rear panel IP30	4	1800	800	PPEA1880	1STQ007636A0000	1/1
Vented rear panel IP30	6	1800	1000	PPEA1810	1STQ007638A0000	1/1
Vented rear panel IP30	2	2000	600	PPEA2060	1STQ007644A0000	1/1
Vented rear panel IP30	4	2000	800	PPEA2080	1STQ007646A0000	1/1
Vented rear panel IP30	6	2000	1000	PPEA2010	1STQ007648A0000	1/1



External blind side panel IP65

Pickled sheet steel with gasket and plugs IP65. The code refers to one single side panel.

Description	Dimensions (mm)			Type	Order code	Pkg/ No. pcs
	H	D	Type			
Blind side panel IP65	1800	500	PPEB1856	1STQ007579A0000	1/1	
Blind side panel IP65	1800	700	PPEB1876	1STQ007581A0000	1/1	
Blind side panel IP65	1800	900	PPEB1896	1STQ007584A0000	1/1	
Blind side panel IP65	2000	500	PPEB2056	1STQ008106A0000	1/1	
Blind side panel IP65	2000	700	PPEB2076	1STQ008107A0000	1/1	
Blind side panel IP65	2000	900	PPEB2096	1STQ008108A0000	1/1	




External blind side panel IP30, IP40

Pickled sheet steel with gasket. The code refers to one single side panel. In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit PKPT...., page 6-12.

Description	Dimensions (mm)			Type	Order code	Pkg/ No. pcs
	H	D	Type			
Blind side panel IP30, IP40	1800	500	PPEB1850	1STQ007610A0000	1/1	
Blind side panel IP30, IP40	1800	700	PPEB1870	1STQ007612A0000	1/1	
Blind side panel IP30, IP40	1800	900	PPEB1890	1STQ007614A0000	1/1	
Blind side panel IP30, IP40	2000	500	PPEB2050	1STQ007621A0000	1/1	
Blind side panel IP30, IP40	2000	700	PPEB2070	1STQ007623A0000	1/1	
Blind side panel IP30, IP40	2000	900	PPEB2090	1STQ007625A0000	1/1	

Dedicated solution

InLine II - Order codes



External vented side panel IP30

Pickled sheet steel without gasket. The code refers to one single side panel. In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit PKPT...., page 6-12.


Description	No. Vented grates	Dimensions (mm)		Type	Order code	Pkg/ No. pcs
		H	D			
Vented side panel IP30	2	1800	500	PPEA1850	1STQ007632A0000	1/1
Vented side panel IP30	2	1800	700	PPEA1870	1STQ007634A0000	1/1
Vented side panel IP30	4	1800	900	PPEA1890	1STQ007637A0000	1/1
Vented side panel IP30	2	2000	500	PPEA2050	1STQ007643A0000	1/1
Vented side panel IP30	2	2000	700	PPEA2070	1STQ007645A0000	1/1
Vented side panel IP30	4	2000	900	PPEA2090	1STQ007647A0000	1/1



IP40 grate for Vented external panels

Accessory for Vented panels. Allows IP40 protection class to be obtained. Order the quantity on the basis of the number of grates on the panel. In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit PKPT...., page 6-12.

Description	Type	Order code	Pkg/ No. pcs
No. IP40 grates for Vented panels	PGPP0040	1STQ008090A0000	1/2




Glass door IP65

Pickled sheet steel with gasket. Opens through 135° (single column). Complete with 4 hinges to be screwed onto the uprights, 4 door closing brackets with cover and handle. Handle and hinges provided (not pre-assembled for complete reversibility). Doors can be mounted both on the front and on the back of the enclosures.

Description	No. DIN modules	Dimensions (mm)		Type	Order code	Pkg/ No. pcs
		H	W			
Glass door IP65	24	1800	600	PDLG1866	1STQ007305A0000	1/1
Glass door IP65	36	1800	800	PDLG1886	1STQ007308A0000	1/1
Glass door IP65	48	1800	1000	PDLG1816	1STQ007311A0000	1/1
Glass door IP65	24	2000	600	PDLG2066	1STQ007316A0000	1/1
Glass door IP65	36	2000	800	PDLG2086	1STQ007319A0000	1/1
Glass door IP65	48	2000	1000	PDLG2016	1STQ007322A0000	1/1

Dedicated solution

InLine II - Order codes




Glass door IP40

Pickled sheet steel without gasket and 4 rubber overlapping plugs. Opens through 135° (single column). Complete with 4 hinges to be screwed onto the uprights, 4 door closing brackets with cover and handle. Handle and hinges provided (not pre-assembled for complete reversibility). In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit PKPT..., page 6-12. Doors can be mounted both on the front and on the back of the enclosures.




Description	No. Vented grates	Dimensions (mm)		Type	Order code	Pkg/ No. pcs
		H	W			
Glass door IP40	24	1800	600	PDLG1860	1STQ007327A0000	1/1
Glass door IP40	36	1800	800	PDLG1880	1STQ007330A0000	1/1
Glass door IP40	48	1800	1000	PDLG1810	1STQ007333A0000	1/1
Glass door IP40	24	2000	600	PDLG2060	1STQ007338A0000	1/1
Glass door IP40	36	2000	800	PDLG2080	1STQ007341A0000	1/1
Glass door IP40	48	2000	1000	PDLG2010	1STQ007344A0000	1/1



Blind door IP65


Pickled sheet steel with gasket. Opens through 135° (single column). Complete with 4 hinges to be screwed onto the uprights, 4 door closing brackets with cover and handle. Handle and hinges provided (not pre-assembled for complete reversibility). Doors can be mounted both on the front and on the back of the enclosures. Reinforcing tubes for W>400mm.



Description	No. DIN modules	Dimensions (mm)		Type	Order code	Pkg/ No. pcs
		H	W			
Blind door IP65	24	1800	600	PDLB1866	1STQ007349A0000	1/1
Blind door IP65	36	1800	800	PDLB1886	1STQ007350A0000	1/1
Blind door IP65	48	1800	1000	PDLB1816	1STQ007351A0000	1/1
Blind door IP65	24	2000	600	PDLB2066	1STQ007356A0000	1/1
Blind door IP65	36	2000	800	PDLB2086	1STQ007357A0000	1/1
Blind door IP65	48	2000	1000	PDLB2016	1STQ007358A0000	1/1


Dedicated solution

InLine II - Order codes




Blind door IP40/IP41

Pickled sheet steel without gasket and 4 rubber overlapping plugs. Opens through 135° (single column). Complete with 4 hinges to be screwed onto the uprights, 4 door closing brackets with cover and handle. Handle and hinges provided (not pre-assembled for complete reversibility). In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit PKPT..., page 6-12. Doors can be mounted both on the front and on the back of the enclosures. Reinforcing tubes for W>400mm



Horizontal/vertical front closing profiles IP30

Profiles for IP30/IP31 pickled sheet painted RAL 7035. In order to reach IPX1 protection degree it is necessary to add the proper top sealing kit PKPT..., page 6-12.




Description	Dimensions (mm)			Pkg/ No. pcs		
	No. DIN modules	H	W	Type	Order code	
Blind door IP40/IP41	24	1800	600	PDLB1860	1STQ007363A0000	1/1
Blind door IP40/IP41	36	1800	800	PDLB1880	1STQ007364A0000	1/1
Blind door IP40/IP41	48	1800	1000	PDLB1810	1STQ007365A0000	1/1
Blind door IP40/IP41	24	2000	600	PDLB2060	1STQ007370A0000	1/1
Blind door IP40/IP41	36	2000	800	PDLB2080	1STQ007371A0000	1/1
Blind door IP40/IP41	48	2000	1000	PDLB2010	1STQ007372A0000	1/1

Dedicated solution

InLine II - Order codes

Configuration example

Functional dimensions 1800x800x700mm (HxWxD) structure with H=100mm plinth, InLine II kits and front panels covers.



Quantity	Order code	Part	Description
1	PUPM1800	Structure	No. 4 galvanized sheet uprights H=1800mm
1	PCFM0800	Structure	No. 4 width galvanized sheet crosspieces W=800mm
1	PCFM0700	Structure	No. 4 depth galvanized sheet crosspieces D=700mm
1	PPAM0100	Structure	No. 4 corners plinth H=100mm
1	PPFM1080	Structure	No. 2 front/rear plinth flanges W=800mm
1	PPFM1070	Structure	No. 2 side plinth flanges D=700mm
2	PUKI2000	Kits	No. 1 Intermediate upright
1	PTBB8076	External covers	IP65 blind top/bottom W=800mm D=700mm
1	PPEB1886	External covers	IP65 blind back panel H=1800mm W=800mm
2	PPEB1876	External covers	IP65 blind side panel H=1800mm D=700mm
1	PDLG1886	External covers	IP65 36 DIN modules glass door H=1800mm W=800mm
1	PFNL1880	InLine II components	Fixed frame for panels in the InLine column H=1800mm W=800mm
2	PPNL3080	InLine II components	Blind flat panel for InLine column H=300mm W=800mm

Dedicated solution


Capacitor bank application

General information

For the application, ABB provides preassembled capacitor unit ready for the installation with protection devices. So-called capacitor power module PMOD has a standard range from 220 until 690V and ratings starting from 6.25 kvar up to 100 kvar in one module (option with de-tuning reactor included up to 50 kvar).

The PMOD unit includes withdrawable shelve, capacitors, detuning reactor if specified, UA contactor and fuse protection device XLP00 EasyLine.


PMOD equipped with front insulators/busbar supports of 60mm inter-axial distance between the phases and with the maximum holding capacity of 30x10mm bar. It is mandatory to add supporting rails to fix the PMOD unit.



- 1** EN0480K-EN0482K forced ventilation outlet. Page 6-41
- 2** PTBO50.. top with the cutout for outlet. Page 6-40
- 3** RVC/RVT power factor controller. Page 6-40
- 4** XLP00-A60/60 fuse switch-disconnector. Page 6-42
- 5** UA..RA contactor. Page 6-42
- 6** PFRJ0500 rail for PMOD. Page 6-40
- 7** PMOD capacitor unit. Page 6-42
- 8** PDLB... door with cutout for EN0325K air inlet. Page 6-40
- 9** EN0325K natural ventilation inlet IP21/54. Page 6-41

Example of IP54 capacitor bank completing

Column 2000x500x500mm, 400kvar - 4x100kvar (8 steps of 50 kvar), 400V, standard clean network*, without de-tuning reactor.



Quantity	Order code	Part	Description
1	PUPM2000	Structure	No.4 galvanized sheet metal uprights 2000mm
2	PCFM0500	Structure	No.4 width/depth crosspieces galvanized sheet metal
1	PTBB5050	Structure	IP65 blind bottom, W500/D500mm
1	PTBO5055	Structure	IP65 open bottom, W500/D500mm for "mushroom"
3	PPEB2056	Structure	Blind rear/side panel IP65, H2000/W500mm
1	PDLB2052	Structure	IP65 Door with the cutout for EN0325K air inlet
1	PPAM0100	Structure	No.4 plinth angle pieces
2	PPFM1050	Structure	No.2 front/rear plinth flanges W500mm
5	PFRJ0500	Kit	No.2 support rails for fixing capacitor bank drawer
1	EN0325K	Kit	IP21/54 natural ventilation inlet
1	EN0484K	Kit	IP54 forced ventilation outlet 230V 50/60Hz "mushroom"
1	EN0101K	Kit	NO ventilation thermostat
4	2GCA297404A0045	Equipment	PMOD XLP unit 100kvar (2 steps of 50), 400V
1	2GCA294985A0050	Equipment	RVC8 power factor controller, 8 steps


*suitable for installation when there are less than 15% of nonlinear loads and no resonance

Dedicated solution

Capacitor bank application - Order codes

Capacitor mounting set and System pro E power


Compatible with the 500mm width of the structure. Can be combined with the horizontal main busbar system and depth more than or equal 500mm. The design is feasible with the any protection degree parts of the System, from IP40 to IP65 (the cubicle will be de-rated to IP23 or IP54).



Fixing rails for PMOD capacitor module

Mandatory to chose one pack for one module.

Description	Type	Order code	Pkg/ No. pcs
N.2 support rails for fixing capacitor bank drawer	PFRJ0500	1STQ005045B0000	1/2




Open top prepared for the “mushroom” air outlet installation, forced ventilation

Description	Dimensions (mm)			Pkg/ No. pcs
	W	D	Type	
Open top with cut-out for EN0480K air outlet IP23	500	500	PTB05052	1STQ005037B0000
Open top with cut-out for EN0480K air outlet IP23	500	700	PTB05072	1STQ005038B0000
Open top with cut-out for EN0480K air outlet IP23	500	900	PTB05092	1STQ005039B0000
Open top with cut-out for EN0485K air outlet IP54	500	500	PTB05055	1STQ005040B0000
Open top with cut-out for EN0485K air outlet IP54	500	700	PTB05075	1STQ005041B0000
Open top with cut-out for EN0485K air outlet IP54	500	900	PTB05095	1STQ005042B0000



Door with the cutout for the EN0325K air inlet and RVC/RVT controller

Description	Dimensions (mm)			Pkg/ No. pcs
	H	D	Type	
Door with cutout for air inlet and controller	2000	2000	PDLB2052	1STQ005043B0000
Door with cutout for air inlet and controller	1800	1800	PDLB1852	1STQ005044B0000




Intermediate uprights

Mandatory to order 2 pieces for the structure of 700 and 900mm depth. It will provides additional fixing points for PFRJ0500 rails at the back.

Description	Dimensions (mm)			Pkg/ No. pcs
	H	Type	Order code	
No.1 galv. sheet metal upright for cable compartment	1800	PUCM1800	1STQ007742A0000	1/1
No.1 galv. sheet metal upright for cable compartment	2000	PUCM2000	1STQ007743A0000	1/1

Dedicated solution

Capacitor bank application - Order codes




Accessories for the internal ventilation and hitting dissipation

Ventilation inlet IP21/54 to be placed on the frontal door

Gratings made of insulating material (self-extinguishing ABS UL94V-0) RAL7035 colour, complete with high dust collection capacity filter cloth (600g/m²), able to reduce maintenance interventions (cleaning by means of washing in water or by beating). Degree of protection IP21 without filter, IP54 with filter according to IEC 60529.parts of the System, from IP40 to IP65 (the cubicle will be de-rated to IP23 or IP54).

Description	Dimensions (mm)					Pkg/ No. pcs
	W	H	Type	Order code		
IP21/54 natural ventilation inlet	325	325		EN0325K		1/1



Forced ventilation outlet "mushroom" IP23 to be placed on the roof


RAL 7035 colour, complete with self-adhesive gasket; consumption 58/78W, capacity 550/590m³/h. Operating temperature from -20 °C to + 60 °C, noise 68/71dB(A).

Description	Dimensions (mm)					Pkg/ No. pcs
	W	D	H	Type	Order code	
IP23 forced ventilation outlet 230V 50/60Hz	375	295	119	EN0480K		1/1
IP23 forced ventilation outlet 230V 50/60Hz	375	295	119	EN0482K		1/1

Forced ventilation outlet "mushroom" IP54 to be placed on the roof

Structure made up of plastic PC/ABS (PC/ABS self-extinguishing according to UL 9V-0), with the top part in aluminium, painted RAL 7035 with polyuretanic foam gasket.

Description	Dimensions (mm)					Pkg/ No. pcs
	W	D	H	Type	Order code	
IP54 forced ventilation outlet 230V 50/60Hz	324	324	94	EN0484K		1/1
IP54 forced ventilation outlet 230V 50/60Hz	324	324	94	EN0485K		1/1





IP20 Thermostat, NO - cooling

Grey RAL 7035 colour; electrical life 100,000 cycles. Dimensions (HxWxD) 68x29x45mm, can be mounted on DIN rail. Temperature scale: -10 / +80 °C. Power supply: 12-60VDC or 110-250VAC, 50/60Hz.

Description	Dimensions (mm)					Pkg/ No. pcs
	W	D	H	Type	Order code	
NO ventilation thermostat	29	45	68		EN0101K	1/1

Dedicated solution

Capacitor bank application - Order codes



Power capacitors module PMOD QCap (reassembled by the factory)

QCap power module is all-in-one pre-wired power module, which includes capacitor – QCap type, contactor, fuses and reactors (if existing). QCap power module provides all advantages of QCap dry capacitor technology in a compact case, delivering high performance within a small footprint.

Connection between PMOD has to be realized by copper bars 30*10.

U network (V) ^{(1)*}	Detuning Reactor (%) ⁽²⁾	Rated Power Qc (kvar) ⁽⁴⁾	Net Output Power Q (kvar) ⁽³⁾	Comments	Order code	Pkg/ No. pcs
50 Hz Network						
400	-	25	25	1 step	2GCA297400A0045	1/1
400	5,67	26,5	25	1 step	2GCA297405A0045	1/1
400	7	26,9	25	1 step	2GCA297406A0045	1/1
400	12,5	28,6	25	1 step	2GCA297407A0045	1/1
400	-	50	50	1 step	2GCA297401A0045	1/1
400	-	50	50	2 steps 25+25	2GCA297402A0045	1/1
400	5,67	53	50	1 step	2GCA297408A0045	1/1
400	7	53,8	50	1 step	2GCA297409A0045	1/1
400	12,5	57,2	50	1 step	2GCA297410A0045	1/1
400	-	75	75	2 steps 25+50	2GCA297403A0045	1/1
400	-	100	100	2 steps 50+50	2GCA297404A0045	1/1


QCap power module offers a number of exceptional features like: high voltage withstand capability, excellent peak current handling capacity, high capacitance stability, long life even under high electrical stress, low losses, exceptional reliability and safety. More ratings and voltages available, please contact us.

⁽¹⁾ U network is the nominal network voltage.

⁽²⁾ Value of the reactor (if existing) connected in series with the capacitor.

⁽³⁾ The net output power Q is the reactive power delivered to the network by both the capacitor and its detuning reactor (if existing) under nominal network voltage.

⁽⁴⁾ Qc is the reactive power directly at capacitor terminals under nominal voltage (note: Qc ≥ Q due to reactor impact).



Dedicated solution

Capacitor bank application - Order codes



Power Factor Controller RVC & RVT

RVC controller - Accurate control and monitoring of capacitor banks

The RVC standard range of controllers can be used to control $\cos \phi$ in industrial and commercial networks. Application examples include power factor control in buildings, mining steel industry, chemical, pulp and paper, cement, plastics, printing and food industries. The RVC operates at 100/440V - 50/60 Hz (automatic adjustment to voltage and network frequency). The RVC is available in 3, 6, 8, 10 and 12 outputs versions.back of the enclosures.

Description	Order code	Pkg/ No. pcs
RVC3 power factor controller programmable up to 3 outputs	2GCA294983A0050	1/1
RVC6 power factor controller programmable up to 6 outputs	2GCA294984A0050	1/1
RVC8 power factor controller programmable up to 8 outputs	2GCA294985A0050	1/1
RVC10 power factor controller programmable up to 10 outputs	2GCA294986A0050	1/1
RVC12 power factor controller programmable up to 12 outputs	2GCA294987A0050	1/1

Capacitor bank series is simple and easy to operate thanks to the automatic functions provided by the RVC controller:

- User-friendly interface
- Easy commissioning
- Complete automatic set-up
- Display of: $\cos \phi$, V, I, THDV, THDI
- Multiple built-in protections
- Not affected by harmonics
- Designed for hot environments (+60°C)
- Hardware and software switches
- Switching time between steps are programmable from 1s to 999s (independent of reactive load)
- Switching sequences are user defined
- Quick automatic disconnection in less than 20ms (50Hz) in case of power outage or voltage drop



RVT controller -The smart PFC for automatic capacitor bank

The RVT Touch Screen operates at 100/440V - 50/60 Hz (automatic $\cos \phi$ adjustment to voltage and network frequency). Three phase model: RVT12-3P (for both balanced and unbalanced network) with 12 outputs.

Description	Order code	Pkg/ No. pcs
RVT6 Touch Screen power factor controller	2GCA291720A0050	1/1
RVT12 Touch Screen power factor controller	2GCA291721A0050	1/1
RVT12-3P Touch Screen power factor controller 3 phases	2GCA291722A0050	1/1

For enhanced functionality, ABB recommends its advanced RVT controller with the following features:

- Complete three-phase measurements of powers and harmonics
- Communication: Ethernet, USB, Modbus and Modbus TCP, complete graphical display, touchscreen
- Multi-language support
- Programmable warning/protection threshold
- Up to 8 temperature probes connections
- Real time clock

Options only for RVT

Description	Order code	Pkg/ No. pcs
Temperature probe (up to 8 connections with daisy chain)	2GCA291864A0050	1/1
IP 54 gasket	2GCA292040A0050	1/1
OPC Server Software	2GCA286141A0050	1/1
RS485 Modbus adapter	2GCA291880A0050	1/1
PQ LINK Software	2GCA292820A0050	1/1

Dedicated solution

Capacitor bank application - Declaration on thsted configuration and overall

Declaration on tested configuration and overall technical specification

Robust type tested design

Capacitor bank is considered as low voltage switchgear and needs to be verified by type tests and routine tests. The low-voltage System pro E power factor correction banks are type tested according to IEC 61921 and IEC61439-1. Particularly, the characteristics below are checked according to IEC61439 part 1 clause 10: Design verification:

- 10.10 Verification of temperature rise;
- 10.9 Dielectric properties;
- 10.11 Short-circuit withstand strength;
- 10.4 Clearances and creepage distances;
- 10.13 Mechanical operation;
- 10.3 Degree of protection;
- 10.5 Effectiveness of the protective circuit.

The Panelbuilder shall complete only routine tests. The routine tests shall be made on every assembly and are intended to detect faults in materials and workmanship. They shall be carried out on every new assembly after its construction, or on each transport unit (see IEC 61439-1 clause 11). Another routine test at the place of installation is not required. Routine tests include:

- a) inspection of the assembly including inspection of wiring and, if necessary, an electrical operation test (see 7.3.1). See the relevant clauses of IEC 61439-1;
- b) dielectric test (see 7.3.2). See the relevant clauses of IEC 61439-1;
- c) checking of protective measures and of the electrical continuity of the protective circuit (see 7.3.3). See the relevant clauses of IEC 61439-1;
- d) verification of insulation resistance (see 7.3.4). See the relevant clauses of IEC 61439-1.

These tests may be carried out in any order.

Technical specification

Working ambient temperature	-5°C (23°F)/+40°C (104°F) according to EN 61921
Connection	Three-phase, balanced network
Protection	IP23/IP54, protected against direct and accidental contact
Execution	Indoor
Ventilation	Forced air cooling
Power factor setting	From 0.7 inductive to 0.7 capacitive
Starting current setting (C/k)	From 0.01A to 3A for the RVC controller From 0.01A to 5A for the RVT controller
Operation	During operation, RVC (RVT) controller displays: - the number of active outputs - the inductive or capacitive power factor - the alarm conditions; target cos j, over/under voltage, THDV, over temperature - the demand for switching on/off a capacitor step
Losses at 400V 50 Hz	Without reactors: less than 1.5 Watt/kvar With reactors: less than 5.5 Watt/kvar
Capacitors QCap type	Dry type self-healing according to IEC 60831-1&2 Dielectric: 2.15 Un between terminals during 10 sec at rated frequency Acceptable overvoltage: +10% max. (maximum 8h/day) as per IEC 60831-1 Acceptable overcurrent: +30% permanently Temperature range: -25°C/+55°C (class D according to IEC 60831-1&2)
Réacteurs	Dry type resin embedded according to IEC 289, IEC 76 Maximum harmonic pollution: 8% THDV with specific spectrum
Standards	IEC 61921, IEC 61439-1&2 IEC 60831-1&2 (capacitors) CE marked

Dedicated solution

Capacitor bank - Technical specification

Technical characteristics of the components

Qcap capacitor technical specification


QCap is a cylindrical type capacitor. It is based on ABB's latest technologies and developments and is a result of more than a century's knowledge on electrical engineering and over 70 years of expertise on capacitor technologies.

Network voltage range	From 220 to 690 V.
Frequency	50 and 60 Hz
Connection	Three-phase
Net output power	From 2.5 to 30 kvar
Tolerance on capacitance	2.5-12.5 kvar (dielectric only) 15-30 kvar: 0 % / + 10%
Losses	< 0.2 Watt/kvar (dielectric only) < 0.35 Watt/kvar (typical without discharge resistor) < 0.5 Watt/kvar (including discharge resistor)
Discharge resistor	Include. Discharge to 50 V in 1 minute
Maximum permissible current	1.3 x In for continuous operation
Tolerance on voltage	1.1 x Un for maximum 8 hours in every 24 hours (according to IEC 60831)
Case material	Recyclable aluminium
Color	Raw aluminium
Fixing	1 stud (M12). Recommended torque: 10 Nm
Dimensions (DxH)	90x417 mm
Weight	3 Kg
Terminals	Cage screws. Recommended torque: 2 Nm
Minimum distance above unit	20 mm
Minimum distance between capacitors	30 mm
Earth	Earth connection on the enclosure fixation
Execution	Indoor use only
Installation	Horizontal or vertical*
Temperature range	-25°C / +55°C (class D according to IEC 60831)
Altitude	Up to 2000 m without derating. For higher altitudes consult ABB.
Protection degree	IP20
Standards	CE and CSA (with US indicator complying with UL810)

*In case of horizontal mounting, it is advised to add reinforcements to support the QCap in case of shock or vibrations during use. The same advice is applicable to transport conditions.

Dimensions

Total H	Can H	D	D fixation screw H	H fixation screw
401 mm	368 mm	90 mm	M12	16 mm



Dedicated solution

Capacitor bank - Technical specification

RVC power factor controller

Measuring system	Micro-processor system for balanced three-phase networks or single-phase networks.
Operating voltage	100V to 440V.
Voltage tolerance	±10% on indicated operating voltages.
Frequency range	50 or 60 Hz ±5% (automatic adjustments to network frequency).
Measuring circuit terminals (L2, L3 and k, I)	CAT III rated.
Current Input	1A or 5A (RSM)
Current Input impedance	<0.1 Ohm (recommended CT class 1.0, 10 VA min).
Consumption of the controller	8 VA max.
Output contact rating	Max. continuous current: 1.5A; Max. peak current: 5A. Max. voltage: 440 Vac. Terminal A is rated for a continuous current of 16A.
Alarm contact	Normally open contact. Max. continuous current: 5A. Rated/max. breaking voltage: 250Vac/440Vac.
Power factor setting	From 0.7 inductive to 0.7 capacitive.
Starting current setting (C/k)	0.01 to 3A. Automatic measurement of C/k.
Number of outputs	RCV-3: programmable up to 3 outputs - RCV-6: programmable up to 6 outputs RCV-8: programmable up to 8 outputs - RCV-10: programmable up to 10 outputs RCV-12: programmable up to 12 outputs
Switching time between step	Programmable from 1s to 999s (independent of reactive load).
Switching sequences	Used defined
Mode of switching	The mode of switching for all the programmable switching sequences is integral, direct, circular or linear.
Saving-function	All programmed parameters and modes are saved in a non-volatile memory.
Power outage release	Quick automatic disconnection in less than 20ms [50Hz] in case of power outage or voltage drop.
Power outage reset delay time	40 s.
Operating temperature	-10° C to 70° C.
Storage temperature	-30° C to 85° C.
Mounting position	Vertical panel mounting.
Dimensions	144x144x43 mm (hxwxw)
Cut-out dimensions	138x138 mm(hxw)
Weight	0.4 kg (unpacked)
Connector	Spring clamp terminal block
Front plate protection	IP43
Relative humidity	Maximum 95%, non condensing
Other features	Overvoltage and undervoltage protection. Autodadaptation to the phase-rotation of the network and the CT terminals. Not affected by harmonics. working with generative and regenerative loads. LCD contrast automatically compensated with temperature.
Standards	CE marked.

Dedicated solution

Capacitor bank - Technical specification

RVT power factor controller

Measuring system	Micro-processor system for balanced three-phase/single-phase networks and unbalanced Individual phase power factor control is available.
Supply voltage	From 100Vac up to 460 Vac.
Consumption	15 VA max.
Connection type for measuring circuit and power supply	Phase-phase or phase-neutral for balanced and unbalanced network.
Voltage tolerance	±10% on indicated supply voltages.
Measurement category (according to IEC 61010-1)	CAT III.
Voltage measurement	Up to 690Vac or higher with voltage transformer.
Accuracy	±1% full scale.
Frequency range	45 to 65 Hz (automatic adjustments to network frequency).
Current input	5A or 1A (RMS) (class 1 C.T.).
Current input impedance	<0.1 Ohm.
Power outage release	Automatic disconnection of all capacitors in case of a power outage longer than 20ms.
Number of outputs	RVT6/RVT12 Base Model: programmable up to 6 or 12 outputs. RVT12-3P Three Phase Model: programmable up to 12 outputs.
Output contact rating	Max. continuous current: 1.5A (ac) – 0.3A (110V dc). Max. peak current: 5A. Max. voltage: 440 Vac. Terminal A-A are rated for a continuous current of 18A (9A/terminal).
Alarm contact rating (voltage free contact)	One normally closed contact and one normally open contact. Max. continuous current: 1.5A (ac). Rated voltage: 250Vac (max. breaking voltage: 440Vac).
Fan contact rating (voltage free contact)	Normally open contact. Max. continuous current: 1.5A (ac). Rated voltage: 250Vac (max. breaking voltage: 440Vac).
Power factor setting	From 0.7 inductive to 0.7 capacitive.
Starting current setting (C/k)	0.01 to 5A. Automatic measurement of C/k.
Switching sequences	1:1:1:1:....:1 - 1:2:2:2:....:2 - 1:2:4:4:4:....:4 1:2:4:8:8::8 - 1:1:2:2:2:....:2 - 1:1:2:4:4:....:4 1:1:2:4:8:....:8 - 1:2:3:3:3:....:3 - 1:2:3:6:6:....:6 1:1:2:3:3:....:3 - 1:1:2:3:6:....:6 and any other customer programmable sequence.
Modbus baud rate	300 - 600 - 1200 - 2400 - 4800 - 9600 - 19200 - 38400 - 57600 bps.
CAN connection	Support CAN 2.0B interface (for future use).
USB host connection	For future use.
USB device connection	Available
Temperature probe input connection	Only 2 contacts using 1-wire protocol. - Parasitic supply mode (no need of external power supply) - Connection to more nodes in a daisy chain network - 8 temperature probes connection - 8 meters maximum between RVT to temperature probe or between probes - 64 meters maximum length
Step configuration	Automatic, fixed, disabled.
Display	QVGA 320 x 240 pixels colorful touch-screen.
Adjustable display backlighting	Available
Switching time between steps	Programmable from 1s to 18h.

Dedicated solution

Capacitor bank - Technical specification

RVT power factor controller

Saving-function	All programmed parameters and modes are saved in a non-volatile memory.
Auto adaptation to the connection and phase-rotation of the network	
Auto adaptation to the CT-terminals	
Power Factor correction operation is insensitive to the presence of harmonics.	
Working with passive and regenerative loads (four-quadrant operation).	
Operating temperature	-20° C to 70° C.
Storage temperature	-30° C to 85° C.
Mounting position	Vertical panel mounting.
Dimensions	Front plate: 146 x 146 mm (h x w). Rear side: 205 x 135 mm. Overall: 146 x 211 x 67 mm (h x w x d). Cut out dimensions: 138 x 138 mm (h x w)
Weight	650 g (unpacked).
Connector	Cage clamp type (2.5mm ² single core cable).
Front plate protection	IP 43 (IP54: on request).
Relative humidity	Maximum 95%, non-condensing.
CE and UL marked	

Product line-up

Features	RV _T 6/RV _T 12	RV _T 12 - 3P
Article number	RV _T -6 RV _T -12	RV _T -12-3P
1 / 3 phase measurements	1 voltage measurement input 1 current measurement input	
Real time clock	NO	YES
Energy measurements	NO	YES
Ethernet connection	NO	YES
USB host connection	NO	YES
USB device connection	YES	YES
Digital inputs	YES	YES
Alarm / fan relays	YES	YES
Output relays	6 or 12	12
Lock switch	YES	YES
RS485 Modbus connection	YES	YES
External temperature probes	YES	YES

Dedicated solution

Capacitor bank - Technical specification



De-tuning reactors technical specification

The ABB detuning reactor is state of the art reactor with highest specification requirement in terms of:

- Superior raw materials quality
- Superior manufacturing quality and quality control
- The smallest range of tolerance about electrical parameters
- Design to operate continuously at nominal power
- The largest reactor linearity in the market (avoid saturation)

More important, ABB design is for a network pollution of 8% THDV:

Network voltage spectrum: $U_3/U_1=0.5\%$

$U_5/U_1=6\%$

$U_7/U_1=5\%$

$U_{11}/U_1=3.5\%$

$U_{13}/U_1=3\%$

But not exceeding a total THDU of 8%

Assuming the network voltage of $1.1 \times U_n$ for I_1 and the maximum harmonic voltage spectrum as per above (at $1.0 \times U_n$)

Temperatures are defined as: Operational $T_{min} = -25^\circ C$


Operational $T_{max} = 50^\circ C$

Storage $T_{min} = -40^\circ C$

Storage $T_{max} = 75^\circ C$

Voltage	Q _{net}	Detuning reactor
400 V	6.25 kVAr	-
400 V	12.5 kVAr	-
400 V	25 kVAr	-
400 V	50 kVAr	-
400 V	6.25 kVAr	5,67%
400 V	12.5 kVAr	5,67%
400 V	25 kVAr	5,67%
400 V	50 kVAr	5,67%
400 V	6.25 kVAr	7%
400 V	12.5 kVAr	7%
400 V	25 kVAr	7%
400 V	50 kVAr	7%
400 V	6.25 kVAr	12,50%
400 V	12.5 kVAr	12,50%
400 V	25 kVAr	12,50%
400 V	50 kVAr	12,50%
400 V	25 kVAr	14%
400 V	50 kVAr	14%
415 V	6.25 kVAr	-
415 V	12.5 kVAr	-
415 V	25 kVAr	-
415 V	50 kVAr	-
415 V	12.5 kVAr	7%
415 V	25 kVAr	7%
415 V	50 kVAr	7%
440 V	12.5 kVAr	-
440 V	25 kVAr	-
440 V	50 kVAr	-
440 V	75 kVAr	-
440 V	12.5 kVAr	7%
440 V	50 kVAr	7%

Note: For plain capacitor banks, while not using UA-RA type contactor, it is usual to make cable turns (around 5 turns with 10cm diameter) in order to limit the Inrush current. The contactor informed is the minimum size needed to build the step. It is possible to use higher ratings as well.



Reactor with weight >26 Kg will be provided with removable lifting eye bolt (2 pcs every set ordered)

More ratings and voltages available, please contact us.

400V, 50Hz	Height - H	Lenght - L	Depth - D
Reactor 25 kvar 7%	205 mm	228 mm	140 mm
Reactor 50 kvar 7%	235 mm	264 mm	155 mm

Dedicated solution

Capacitor bank - Technical specification

Technical aspects of the Power factor correction

Overstressing and overheating shorten the life of a capacitor, and therefore the operating conditions (that is temperature, voltage and current) should be strictly controlled. It should be noted that the introduction of a capacitance in a system might produce unsatisfactory operating conditions (for example amplification of harmonics, self-excitation of machines, overvoltage due to switching, unsatisfactory working of audio-frequency remote-control apparatus, etc.).

The choice of components of an assembly shall be carried out with careful reference to compliance between their ambient air temperature category and that of the assembly itself.

It is important to note that power factor component equipment such as fuses, capacitors, reactors, etc. generate a significant amount of heat. It is important to ensure that adequate ventilation is provided in the operating room in order to maintain good air circulation around the PFC unit.

The equipment needed for the automatic correction of power factor in an installation, including controller, fuses, switching devices, capacitors and reactors (chokes), can be installed as an integral part of the main switchboard.

The rated voltage of the PMOD capacitor unit shall be at least equal to the service voltage of the network to which the capacitor is to be connected, account being taken of the influence of the presence of the capacitor itself.

The connection of PFC (power factor correction) equipment onto a system containing harmonics may reduce the life of the PFC equipment. The damaging effects of harmonics can be mitigated by the use of a suitable detuning reactor in series with each capacitor step.

Chapter 7

Technical details and certifications

7-2 According to IEC 61439-1/2

7-11 Anti-seismic withstand

7-18 Mechanical and electrical characteristics

7-19 Declaration of conformity

7-20 Power dissipated

7-26 Handling

7-28 Electrical continuity

7-29 Conductors

7-30 IP Protection classes

7-32 Mechanical shock resistance IK

7-33 Special painting

Unifix wiring system

7-35 Connection examples - Unifix H

7-36 Connection examples - Unifix L

Configurations

7-37 Configuration examples

Technical details and certifications

According to IEC 61439-1/2

As from November 1st, 2014, the IEC 61439-1 and IEC 61439-2 Standards are to be used for the construction and specification of low voltage assemblies (e.g.: Power Centers and secondary distribution switchboards).

of low voltage assemblies (e.g.: Power Centers and secondary distribution switchboards). IEC 61439-1 includes all the rules and general prescriptions applicable to the protective and switching assemblies in low voltage (LV assemblies). This Standard deals with the definitions and establishes service conditions, construction rules, technical characteristics and verification prescriptions for LV assemblies ($U \leq 1000$ V a.c or $U \leq 1500$ V d.c.). Part 1 cannot be used alone to specify an assembly or to determine its compliance with the Standard, but it has to be used together with the specific product Standard. For System pro E power, the specific product Standard is IEC 61439-2 that deals with "Power switchgear and controlgear assemblies" and is used for the assembly designation marking. The whole of these two Standards identifies the design and testing requirements as regards the industrialization of the product and the tests to be performed to ensure its performances.

A significant change introduced by the IEC 61439 series has been the elimination of the distinction between type-tested assemblies (TTA) and partially type-tested assemblies (PTTA), replaced

with the concept of design verification. IEC 61439-1 defines as “design verification” a verification made on a sample of an assembly or on parts of assemblies to show that the design meets the requirements of the relevant assembly standard.

In particular, the Standard admits three different but equivalent methods to verify the compliance of the design with the Standard, namely:

- verification by laboratory testing (previously defined type-tests and now verification tests); or
 - verification by comparison with a tested reference design; or
 - verification by assessment (verification through design rules, appropriate safety margins, calculation etc.).

The different characteristics (e.g.: temperature-rise, short-circuit withstand strength, insulation, degree of protection, etc.) can be verified using these three methods according to Annex D of the IEC 61439-1 (see Table 1) that prescribes , for each characteristics to be verified, which of the three verification options can be used.



Table 1 – List of design verifications to be performed.

No.	Characteristic	Verification options available			Assessment
		Clauses or subclauses	Testing	Comparison with a reference design	
1	Strength of material and parts: Resistance to corrosion Properties of insulating materials Thermal stability Resistance to abnormal heat and fire due to internal electric effects Resistance to ultra-violet (UV) radiation Lifting Mechanical impact Marking	10.2 10.2.2 10.2.3 10.2.3.1 10.2.3.2 10.2.4 10.2.5 10.2.6 10.2.7	YES YES YES YES NO NO NO NO	NO NO NO NO NO NO NO NO	NO NO YES NO NO NO NO NO
2	Degree of protection of enclosures	10.3	YES	NO	YES
3	Clearances	10.4	YES	NO	NO
4	Creepage distances	10.4	YES	NO	NO
5	Protection against electric shock and integrity of protective circuits: Effective continuity between the exposed conductive parts of the assembly and protective circuit	10.5 10.5.2 10.5.3	YES YES	NO YES	NO NO
6	Incorporation of switching devices and components	10.6	NO	NO	YES
7	Internal electrical circuits and connections	10.7	NO	NO	YES
8	Terminals for external conductors	10.8	NO	NO	YES
9	Dielectric properties: Power-frequency withstand voltage Impulse withstand voltage	10.9 10.9.2 10.9.3	YES YES	NO NO	NO YES
10	Temperature-rise limits	10.10	YES	YES	YES
11	Short-circuit withstand strength	10.11	YES	YES	NO
12	Electromagnetic compatibility (EMC)	10.12	YES	NO	YES
13	Mechanical operation	10.13	YES	NO	NO

For the end user, the method used is irrelevant, provided that the assembly design has been verified according to Table 1.

Technical details and certifications

According to IEC 61439-1/2

The Standard IEC 61439-1 defines the two roles of the “Original manufacturer” and the “ASSEMBLY manufacturer”.

The “Original manufacturer” is the organization (e.g. ABB SACE) that has carried out the original design and the associated verification of an assembly, in accordance with the relevant assembly standard (IEC 61439-2 for System pro E power).

IBesides, in case mounting of the assembly is carried out by others, the Original manufacturer defines and publishes the instructions necessary to produce various assemblies.


The Original manufacturer designs and sets up a wide range of assembly configurations (the as-

sembly system¹⁾), starting from a full and pre-defined range of components.

The assembly system is verified by the Original manufacturer in the most onerous representative configurations.

The Original manufacturer shall ensure the design verifications on the assembly system and provide the instructions for the selection of the components and for the mounting of the assembly.

¹⁾ Assembly system: full range of mechanical and electrical components (enclosures, busbars, functional units, etc.), as defined by the original manufacturer, which can be assembled in accordance with the original manufacturer's instructions in order to produce various ASSEMBLIES.





The “ASSEMBLY manufacturer” is the organization taking the responsibility for the completed assembly; The ASSEMBLY manufacturer may be a different organization to the original manufacturer.

The ASSEMBLY manufacturer (e.g.: the assembler/panel builder, the partner) puts together the assembly using spare parts/components and assembly kits, and, by following the instructions of the Original manufacturer, he obtains the final assembly complying with IEC 61439-2

The ASSEMBLY manufacturer shall carry out:

- 1) selection and assembling of the components according to the instructions provided by the Original manufacturer;
- 2) design verifications, through further tests or comparisons or assessments, in case of deviations from the instructions of the Original manufacturer;
- 3) routine verifications on any assembly realized.
Hereunder the list of the routine verifications to be carried out by the “ASSEMBLY manufacturer”:

Characteristics relevant to construction:

- Degree of protection of enclosures;
- Clearances and creepage distances;
- Protection against electric shock and integrity of protective circuits;
- Installation of built-in components;
- Internal electrical circuits and connections;
- Terminals for external conductors;
- Mechanical operation.

Characteristics relevant to performance:


- Dielectric properties;
- Wiring, operational performance and function

Technical details and certifications

According to IEC 61439-1/2

The main changes introduced by the series of Standards IEC 61439 can be summarized in the following flowchart:

Table 1



1) Original manufacturer: organization that has carried out the original design and the associated verification of an ASSEMBLY in accordance with the relevant ASSEMBLY standard

2) Assembly system: full range of mechanical and electrical components (enclosures, busbars, functional units, etc.), as defined by the original manufacturer, which can be assembled in accordance with the original manufacturer's instructions in order to produce various ASSEMBLIES

3) Assembly manufacturer: organization taking the responsibility for the completed ASSEMBLY; The ASSEMBLY manufacturer may be a different organization to the original manufacturer.

4) Routine verification: verification of each ASSEMBLY performed during and/or after manufacture to confirm whether it complies with the requirements of the relevant ASSEMBLY standard

5) Assembly: combination of one or more low-voltage switching devices together with associated control, measuring, signaling, protective, regulating equipment, with all the internal electrical and mechanical interconnections and structural parts

Technical details and certifications

According to IEC 61439-1/2

System pro E power, the 100% compliant solution with IEC 61439-1/2

System pro E power assemblies are subject at ABB laboratories to the testing prescribed by the Standards IEC 61439-1/2. The results of these verifications ensure the performances of System pro E power assemblies and relieve the ASSEM-

BLY manufacturer of the burden of carrying out further design verifications when ABB SACE structures, assembly kits, enclosures, busbars and devices are used following the selection criteria and mounting instructions of the Technical Catalogue and Instruction Handbook of System pro E power. Reference can be made to such results (summarized in Table 2) when drawing up the declaration of conformity of the assembly.

Table 2

Characteristic	Section	Standard Rule/Rating	Verification method	Test report/Certificate No.
Resistance to corrosion	10.2.2	Severity test A for indoor assemblies/enclosures	Test	LBRS12753 LBRS13893 1STC860049
Thermal stability	10.2.3.1	Test for enclosures manufactured from insulating material.	Not required	Not required
Resistance to abnormal heat and fire due to internal electric effects	10.2.3.2	The Original manufacturer shall provide data on the suitability of materials from the insulating material supplier	Assessment	DATA SHEET – LET01b (Declaration by the insulating material supplier verified by ACAE/LOVAG during temperature rise tests) 1STC860049
Resistance to ultra-violet (UV) radiation	10.2.4	Only for enclosures and external parts of assemblies for outdoor installation	Not required	Not required
Lifting	10.2.5	The maximum number of sections, allowed by the Original manufacturer to be lifted together, shall be equipped with components and/or weights to achieve a weight of 1.25 times its maximum shipping weight.	Test	IT 14.136 IT 14.097 IT 14.138 IT 15.024 IT 14.095 IT 14.094 IT 14.096 IT 16.048 IT 15.069 IT 15.070 IT 15.071 IT 15.072 IT 15.073 1STC860049
Mechanical impact	10.2.6	- IK9 (glass door) - IK10 (blind door)	Test	16-0367-01 1STC860049
Marking	10.2.7	The ASSEMBLY manufacturer shall provide each ASSEMBLY with one or more labels, marked in a durable manner and located in a place such that they are visible and legible when the ASSEMBLY is installed and in operation. Compliance is checked according to the test of 10.2.7 and by inspection.	Test	ASSEMBLY manufacturer
Degree of protection of enclosures	10.3	IP30 (without doors) IP40 (with doors) IP31/41 (with roof accessories) IP65 (with IP65 doors and panels) Verification by assessment is possible when an empty enclosure in accordance with IEC 62208 is used, and no external modification has been carried out that may result in a deterioration of the degree of protection.	Test	16-0367-01 1STC860049

Technical details and certifications

According to IEC 61439-1/2

Characteristic	Section	Standard Rule/Rating	Verification method	Test report/Certificate No.
Clearances	10.4	Insulation clearances are guaranteed when the assembly instructions provided with the ABB SACE structures, busbars and devices are complied with Minimum clearances $\geq 14\text{mm}@12\text{kV}$	Test	IT 15.024 IT 15.075 1STC860049
Creepage distances	10.4	Minimum creepage distances ≥ 14 mm (pollution degree 3 and material group II)	Test	IT 15.024 IT 15.075 1STC860049
Effective continuity between the exposed conductive parts of the ASSEMBLY and the protective circuit	10.5.2	The exposed conductive parts are electrically connected with the main protective conductor; the maximum resistance value allowed for the protective circuit is $\leq 0.1 \Omega$.	Test	IT 14.095 IT 14.096 IT 14.094 IT 14.093 IT 14.097 IT 14.136 IT 14.138 IT 14.137 IT 14.139 LBRP 14175/00 1STC860049
Short-circuit withstand strength of the protective circuit	10.5.3	According to the standard (at least 60% of three-phase short circuit current): up to 72 kA (1s).	Test	IT 14.085 IT 14.086 IT 14.087 IT 14.088 IT 14.089 IT 14.096 IT 15.024 IT 14.095 IT 14.094 IT 14.093 IT 14.097 IT 14.136 IT 14.138 IT 14.137 IT 14.139 IT 15.075 IT 15.069 IT 15.070 IT 15.071 IT 15.072 IT 15.073 IT 15.074 1STC860049
Incorporation of switching devices and components	10.6	Compliance with the design requirements in section 8.5 for the incorporation of switching devices and components.	Assessment by inspection	ASSEMBLY manufacturer must observe the Original Manufacturer's instructions of the assembly system and switching devices and components.
Internal electrical circuits and connections	10.7	Compliance with the design requirements in section 8.6 for internal electrical circuits and connections	Assessment by inspection	The original parts/components must be assembled according to the original manufacturer's instructions.
Terminals for external conductors	10.8	Compliance with the design requirements in section 8.8 for terminals for external conductors.	Assessment by inspection	The original parts/components must be assembled according to the original manufacturer's instructions.

Technical details and certifications

According to IEC 61439-1/2

Characteristic	Section	Standard Rule/Rating	Verification method	Test report/Certificate No.
Power-frequency withstand voltage	10.9.2	According to Table 8/9 of IEC 61439-1: Ui up to 1000 Vac/1500 Vdc	Test	IT 14.085 IT 14.086 IT 14.087 IT 14.088 IT 14.089 IT 14.096 IT 15.024 IT 14.095 IT 14.094 IT 14.097 IT 14.136 IT 14.138 IT 15.001 IT 15.075 IT 16.048 IT 15.069 IT 15.070 IT 15.071 IT 15.072 IT 15.073 1STC860049
Impulse withstand voltage	10.9.3	According to Table 10 of IEC 61439-1: Uimp = 12 kV/8 k	Test	IT 14.085 IT 14.086 IT 14.087 IT 14.096 IT 15.024 IT 14.088 IT 14.095 IT 14.094 IT 14.097 IT 14.098 IT 14.099 IT 14.136 IT 14.138 IT 15.001 IT 15.075 IT 16.048 IT 15.069 IT 15.070 IT 15.071 IT 15.072 IT 15.073 1STC860049
Temperature-rise limits	10.10	Verification by test Rated current InA up to 6300 A InA max = 7000 A (main busbars)	Test	IT 14.085 IT 14.086 IT 14.087 IT 14.096 IT 15.024 IT 14.088 IT 14.095 IT 14.094 IT 14.097 IT 14.089 IT 14.136 IT 14.138 IT 14.137 IT 14.139 IT 15.001 IT 16.048 IT 15.069 IT 15.071 IT 15.072 IT 15.073 IT 15.074 IT 15.075 1STC860049

Technical details and certifications

According to IEC 61439-1/2

Characteristic	Section	Standard Rule/Rating	Verification method	Test report/Certificate No.
Short-circuit withstand strength	10.11	Verification by test: Icw line to line: up to 100 kA for 1s Icw line to line: up to 150 kA for 1s (main busbars) Icw line to neutral: up to 90 kA (1s) Ipk max: 330 kA Verification by comparison with the reference design: Icw line to line: 69 kA for 3s (main busbars)	Test	IT 14.085 IT 14.086 IT 14.087 IT 14.096 IT 15.024 IT 14.088 IT 14.095 IT 14.094 IT 14.093 IT 14.097 IT 14.089 IT 14.136 IT 14.138 IT 14.137 IT 14.139 IT 15.075 IT 15.069 IT 15.071 IT 15.072 IT 15.073 IT 15.074 1STC860049
Electromagnetic compatibility (EMC)	10.12	Ambient condition A and B Ambient condition A and B No EMC test if the incorporated devices and components are in compliance with the requirements for EMC as required by the relevant product Standard and the internal installation and wiring is carried out in accordance with the devices and components manufacturer's instructions.	Verification by assessment	Not required
Mechanical operation	10.13	The movable parts of System pro E power (e.g. hinges for doors and panels) have been tested through 200 operating cycles. This verification test shall not be made on such devices (e.g. withdrawable circuitbreaker) of the ASSEMBLY when they have already been type-tested according to their relevant product Standard unless their mechanical operation has been modified by their mounting.	Test	16-0367-01 1STC860049

The document and certificates can be downloaded at the following link:

<http://www.abb.com/abblibrary/downloadcenter/>

Technical details and certifications

Anti-seismic withstand

1. Introduction

Anti-seismic is an important thematic which is properly implemented in ABB by testing product solutions that meet the growing security demands and requirements from different markets. For System pro E power, ABB guarantees a seismic resistance in standard version without additional reinforcement elements up to 0.5g and with reinforcement kit up to 0.75g.

2. Reference rules

The reference rules adopted are:

- IEC 60068-3-3 Environmental testing - Part 3: Guidance. Seismic test methods for equipment;
- IEC 60068-2-6 Environmental testing - Part 2-6: Tests - Test Fc: Vibration (sinusoidal);
- IEC 60068-2-57 Environmental testing - Part 2-57: Tests - Test Ff: Vibration - Time-history method;
- IEC 60068-2-59 Environmental testing - Part 2: Tests. Test Fe: Vibration - Sine-beat method;
- IEC 60068-2-47 Environmental testing - Part 2-47: Test - Mounting of specimens for vibration, impact and similar dynamic tests;
- IEEE Std 693-2005 IEEE Recommended Practice for Seismic Design of Substations;
- Required response spectra applicable to "YATAY" and "DIKEY" sites (Turkey).

In order to meet the anti-seismic requirements, ABB offers a seismic qualification, in accordance with CEI EN 62271-207, which determine the total withstand capability of the switchgear assemblies in case of seismic stresses, combining results obtained by test, algebraically results and other service loads.


3. Seismic qualification

To determine the seismic qualification, 10 different configurations were seismic tested, using two different laboratories, CESI (Centro Elettronico Sperimentale Italiano), an Italian company founded in 1956, which deals with tests and certifications of electromechanical and electrical

systems and Virlab, an Engineering laboratory that provides seismic test in Asteasu, Spain. The data on which the certification is based are the following ones:

- Certified solutions. In particular the certified configurations are System pro E power Top Busbar System – 3200 A up to 0.5 g;
- System pro E power Top Busbar System – 3200 A with anti-seismic kit up to 0.75 g.

The front side of TBBS enclosure is represented in the picture below:



This is representative for all possible configurations: the test have been performed with an internal overall load of almost 2110 kg.

The adopted configurations are the ones that our R&D technicians identify as the most critical, due to the presence of plastic tie-rods and, due to the reduced withstand current (I_{cw}), the distance between the busbar holders is increased, which contribute to decrease the resistance in case of seismic events.

Technical details and certifications

Anti-seismic withstand

The test was performed according to the following criteria:

- Historical data on passed ArTu K and IS2 tests.
- FEM Analysis, made during design phase, by creating the structure solid, assuming loads that follow the utilization and fixing proper constraints, it was simulated the deformation on the structure. Also few comparative analysis were performed, such as System pro E power vs. ArTu K, System pro E power vs. Triline and System pro E power vs. major competitors. The purpose of the work is to perform a stress analysis in different electrical panels. The effort and displacement evaluation has to be comparable between the different geometries at the same load conditions.
- Vibration tests. These are different from a seismic event because they are predictable events in a given range, instead the antiseismic events are unavoidable, non-constant and do not have a precise range. Vibrations can last for hours or be a constant condition; seismic event is a short, impulsive event.
- Customer test data, followed by ABB as external consultants.
- Traction, compression and torsion tests.
- Lifting tests, with ACAE-LOVAG presidia. All lifting tests are performed without paneling (minus 30 % of rigidity) without the addition of the


external panels and door), with an additional load of 25% (guaranteeing the structure with an additional margin).

- In addition to seismic and vibration tests, System Pro E Power, in glass door version, has passed the internal-arc test at 65 kA @ 480 V (0.3 s) in conformity with TR61641 (criteria 1-6). In addition, the frame has the capability to resist to a short circuit up to 150 kA for 1 s in conformity to the rule CEI EN 61439-2, in both the TBS and RBBS versions. These induced accelerations are much higher of those of a seismic event (current up to 330000 A that pass through the structure) that cause mechanical stresses higher than seismic events.

4. Anti-seismic tests

It has been used the reference of IEE 693-1997 rule, by utilizing the response spectra with a 2% damping, the most critical curve.

The accelerometers were positioned in the most critical points, at the top of the structure, close to the switches and close to the bars.




Technical details and certifications


Anti-seismic withstand

It has been guaranteed in a standard configuration the resistance to a shock level up to 0.5 g, as represented in the picture below:

S2 Horizontal (5% damping)



S2 Vertical (5% damping)




The horizontal ZPA (Zero Period acceleration) 0.69 g. is higher than the corresponding to the AG5 "Ground Acceleration Reference" defined in Table 3 of point 8.2.4 of European standard EN 60068-3-3, value calculated, as it is described in point 8.2.7 of the referred standard, as follows:

Technical details and certifications


Anti-seismic withstand

In addition, by installing anti-seismic kit, it has been guaranteed the resistance to a shock level up to 0.75 g, as represented in the picture below:

S2 Horizontal (0.75 g ZPA; 5% damping)



S2 Vertical (0.6 g ZPA; 5% damping)



7

After the seismic event in the defined limits and conditions, it is guaranteed:

- No collapse of the structure.
- Operation of the switchboard after the earthquake.
- Maintaining of the mechanical characteristics, IP and IK.

The results are confirmed by looking to the resonance final and initial benchmarking, which assess that no structural failures occur during tests.

POINT NUMBER	RESONANCE (Hz) (Amplification)		
	Initial (Test Number 1)	Final (Test Number 18)	Frequency Variation
2 (Close to the center of gravity)	5.44 / (4.5) 23.81 / (2.5)	4.50 / (4.9) 24.00 / (2.5)	-17.28 % 0.80 %
3 (Close to the vertical BUS)	5.34 / (4.6)	4.50 / (4.8)	-15.73 %
4 (On the top left corner)	5.53 / (7.6)	4.59 / (8.3)	-17.00 %

POINT NUMBER	RESONANCE (Hz) (Amplification)		
	Initial (Test Number 2)	Final (Test Number 19)	Frequency Variation
2 (Close to the center of gravity)	3.94 / (5.2)	3.19 / (5.3)	-19.04 %
3 (Close to the vertical BUS)	3.84 / (3.8)	3.09 / (3.8)	-19.53 %
4 (On the top left corner)	3.94 / (8.8)	3.19 / (8.7)	-19.04 %

Technical details and certifications


Anti-seismic withstand

In order to obtain these results, ABB has performed tests with more difficult conditions. In the picture below, it is clearly visible that the test response spectrum is higher than the 0.5g thresholds.

Test Response Spectrum (TRS)

S2 Horizontal - 2%

IEEE Std. 693-2005 "High Required Spectrum", 0.5 g.



The anti-seismic tests on the structure are combined with the ones performed on the breakers. As visible on the below picture, the accelerations tested on breakers are higher than the ones tested on the SPEP. This is because, in case of an earthquake, the breaker is subject of the vibration of the building and simultaneously of the enclosure.


Technical details and certifications

Anti-seismic withstand

Specified Response Spectrum (SRS) (5%)

Envelope (points 2 to 5 and 7 of report 152322 and points 2 to 9 of report 152323)

Level S2 Horizontal Direction



By having significantly higher ZPA tested, it is possible to guarantee the operation of the switchboard during and after a seismic event.

5. Suggestions

Some suggestions are provided in order to increase the capability of the switchboard to withstand to a seismic event:

- It is better to distribute the weight at the bottom of the switchboard.
- Tighten the structure, by segregating it or by increasing the number of busbar holders.
- Fixing of floor structure with M12 class 8.8 screws.
- Avoid fixing the frame to the wall, possibly keeping a distance of 600mm to avoid the "hammer" effect during the earthquake, if


- there is no space make sure the wall is structured for fastening.
- Give maintenance instructions, for example after a seismic event of 0.5g check the tightening torques.
- Busways can compromise stability.
- If it is possible, it is better to reduce height dimension of the enclosure.
- Two structures side by side carry more than a single one.
- The lifting bar strengthens the structure.
- If you have a cable feed, expect an additional length in the cables

Technical details and certifications

Anti-seismic withstand

6. Results

The seismic zones around the World are represented in the picture below:



Below, the comparison table between the IEC 68-3-3 seismic zones, the Richter scale, the Mercalli scale, and the acceleration value.

Seismic Zone IEC 68-3-3	Scale of Richter Magnitude	Scale of Mercalli Magnitude	Phenomena	Maximum acceleration (g)	Freed energy (J)
AG5	9	XII	Exceptionally catastrophic	1.53	$>10^{17}$
	8	XI	Catastrophic	1.02	
	7	X	Very destructive	0.51-1.02	
	6	IX	Destructive	0.2-0.5	$10^{14} - 5 \times 10^{15}$
AG3	5	VIII	Damaging	0.12-0.2	
	4	VII	Very strong		
	3	VI	Strong		$10^{11} - 5 \times 10^{12}$
AG2	2	V	Fairly strong		
	1	IV	Not strong		
	0	III	Weak		$10^8 - 5 \times 10^9$
		II	Very weak		
		I	Registered by instrument		$5 \times 10^6 - 10^8$
					$<5 \times 10^6$

Technical details and certifications

Mechanical and electrical characteristics

Conformity to Standard IEC 61439-1-2

System pro E power switchboards are subjected in the ABB laboratories, to the type tests established by Standard IEC 61439-1-2.

The results of these tests guarantee the performance of System pro E power switchboards and when ABB SACE structures, air circuitbreakers, moulded-case and modular circuit-breakers are used, relieve the end manufacturer of the switchboard from having to perform further type tests so long as he/it complies with the selection criteria and assembly instructions for the various different components.

Reference can be made to these results, de-

scribed below, when drawing up the declaration of conformity of the switchboard.

Overtemperature (Ref. sect. 9.2. of the Standard)

Values from the type tests performed referring to all System pro E - Power switchboard sizes and to the type of installation are given in the tables. The dissipated power data (in Watts) depend on the allowable overtemperature inside the upper part of the switchboard and should be compared with the sum of the powers dissipated by all the components installed in the switchboard (also taking the coincidence factor into due account).

Dielectric properties (Ref. sect. 10.9. of the Standard)

Rated service voltage	up to 1000V AC / 1500V DC
Rated insulation voltage	up to 1000V AC / 1500V DC
Rated impulse withstand voltage	8kV / 12kV

Short-circuit withstand capacity (Ref. sect. 10.11. of the Standard)

Rated short-time short-circuit current:	line-to-line	120kA (1s) 50kA (3s)
	line-to-neutral	72kA (1s)
Rated max. peak short-circuit current		264kA

Protection against the circuit and short-circuit withstand (Ref. sect. 9.3. of the Standard)

Rated admissible short-time withstand current Icw for the protection circuit	72kA (1s)
--	-----------

Insulation clearances (Ref. sect. 10.4. of the Standard)

Insulation clearances are guaranteed when the assembly instructions provided with the ABB SACE structures and circuit-breakers are complied with.

Mechanical operation (Ref. sect. 10.13. of the Standard)

When the assembly instructions of the ABB SACE structures are circuit-breakers are complied with, mechanical operation can be considered as verified.

Protection class (Ref. sect. 10.3 of the Standard)

the type of panelling	Front sealing profiles	Door	Rear	Side panels	Top	Bottom	Top profile
Blind							
IP30	✓ *	-	✓ *	✓ *	✓ *	✓ *	-
IP31	✓ *	-	✓ *	✓ *	✓ *	✓ *	✓ *
IP40	-	✓ *	✓ *	✓ *	✓ *	✓ *	-
IP41	-	✓ *	✓ *	✓ *	✓ *	✓ *	✓ *
IP65	-	✓	✓	✓	✓	✓	-
Vented							
IP30	✓ *	-	✓ **	✓ **	✓ *	✓ *	-
IP31	✓ *	-	✓ **	✓ **	✓ *	✓ *	✓ *
IP40	-	✓ *	✓ ***	✓ ***	✓ *	✓ *	-
IP41	-	✓ *	✓ ***	✓ ***	✓ *	✓ *	✓ *

* Codes in the catalogue allowing IP30-IP31 protection class to be obtained for structures without doors, IP40-IP41 for structures with doors. The structures change from IP30 to IP31 if the top sealing kits are used in addition to the front sealing profiles. The structures change from IP40 to IP41 if the top sealing kits are used in addition to the doors.

** Codes in the catalogue for vented panels allowing IP30-31 protection class to be obtained for structures without doors. The structures change from IP30 to IP31 if the top sealing kits are used in addition to the front sealing profiles.

*** Codes in the catalogue for vented panels allowing IP30-31 protection class to be obtained for structures without doors. The structures change from IP30 to IP40 adding the door and the grates for vented panel. The structures change from IP30 to IP31 if the top sealing kits are used in addition to the front sealing profiles. The structures change from IP40 to IP41 if the top sealing kits are used in **addition to the doors**.

Technical details and certifications

Mechanical and electrical characteristics

Mechanical specifications

Material	
Uprights and cross-pieces	12/10mm hot-dip galvanized sheet steel 12/10mm AISI 304 stainless steel
Plinth angle pieces	25/10mm hot-dip galvanized sheet steel
Plinth flanges	15/10mm hot-dip galvanized sheet steel
External panels	pickled steel sheet thickness 8/10mm for IP30/40 and 15/10 for IP65
Doors	15/10mm thick pickled sheet steel. 4mm thick toughened glass glued from the inside
Plates	15/10mm hot-dip galvanized sheet steel
Panels	12/10mm pickled steel sheet
Partitions	plastic components: thermoplastic vulcanizate metal components: 15/10mm pickled steel sheet

Paint coating

Structure colour	RAL 7035 grey orange peel finish
Plinth colour	RAL 7012 grey orange peel finish
Standard cycle	The sheet metal is cleaned Phosphating, based on iron salts Drying in a tunnel at 100°C External and internal coating with electrostatic application of thermosetting powder coating with epoxy-polyester binders, RAL 7035 colour orange peel finish, total thickness 60/70 microns. Curing in an oven 180°C
Coating characteristics	<p>Binder: epoxy-polyester</p> <p>Specific gravity: 1.61g/cm3</p> <p>Theoretic yield: 10.4m²/kg with film an average 60 microns thick</p> <p>Melting point: 85-95 °C (Kofler bench method)</p> <p>Particle size: standard distribution between 5 and 100 microns with 30 to 40 micron average particle size. Setting: 12 min x 190 °C (temperature of object).</p> <p>Hardness: 1H - 2H</p> <p>DIN 53152 bending elasticity: unaltered on 1/4" mandrel</p> <p>DIN 53151 cross-hatch adhesion: GT O (100%)</p> <p>Erichem elasticity: SEN DIN 53156: > 6mm</p> <p>Gardner impact resistance: 25 kg x cm.</p>

Tests performed on degreased and phosphatized metal plates with 60/70 micron film thickness.

The paint coating passed the saline mist resistance tests (193 hours).

Environmental characteristics

Type of installation	indoor
Installation conditions	on floor
Climatic conditions (t°/Rh%)	constant 23°C/83% - 40°C/93% variable 23°C/98% - 40°C/98%
Ambient temperature limits	for operation -5°C +40°C Normal usage conditions (Ref. sect. 7.1 of the Standard IEC 61439-1-2) for stOrange -25°C +55°C

Technical details and certifications

ABB SACE Declaration of conformity

System pro E power switchboards with rated characteristics	
Rated service voltage Ue	up to 1000V AC / 1500V DC
Rated insulation voltage Ui	up to 1000V AC / 1500V DC
Rated current / Icw	up to 6300A / up to 150kA
IP protection class	IP30, IP31, IP40, IP41, IP65

If the components have been chosen and assembled correctly, as described in the catalogue and instruction manual, the resulting switchboards will conform to Standard IEC 61439-1-2, in accordance with the provisions established by the Low Voltage Directive adopted by the European Union 2007/95/EC (formerly Directive 73/23/EEC, Law 791/1977).

The above is valid if the switchboard has been designed and built:

- having chosen the materials on the basis of the performance values indicated in the ABB catalogues;
- having sized the conductors in accordance with the provisions established by Standards EN 61439-1 and CEI 64-8;
- having performed the individual tests established by Standard IEC 61439-1-2 and obtained positive results.

Technical details

Information about disposal at the end of the lifecycle of the products

ABB SACE has conducted research into the end of the lifecycle of the product.

The assessments were made by applying the LCA (Life Cycle Assessment) method as established by ISO 14040 - 1997 and in accordance with the re-

quirements established by SEMC in the ISO TR 14025 TYPE III Environmental declarations (MSR 1999:2 – “Guidelines Environmental Product Declarations”) document.

The research was conducted considering the disposal and recycling processes of the main materials forming a typical switchboard.

Using the bill of materials as a starting point, the researchers considered the ease with which each part can be disassembled and separated as well as the ability to recycle the materials. They found that the product is almost entirely recyclable.

After this, they limited the bill of materials to the most significant components and assessed the lifecycle of each.

The result was the flow of recyclable materials and salvaged materials (or for incineration) indicated in the Table. In theory, none of the materials should end up in a landfill.

Substance	Destination	
Aluminium scrap	Recycling	
Copper scrap	Recycling	
Polyurethane gaskets	Incineration	
Fiberglass	Recycling	
Scrapped glass	Recycling	
Paper/cardboard	Recycling	
Plastic insulators	Recycling	
Sheet metal scrap	Recycling	

Technical details and certifications

Power dissipated

System pro E power IP31

		Separate enclosure exposed on all sides				Separate enclosure for assembly on a wall				First and last enclosures exposed for assembly on wall				First and last enclosures for assembly on wall				Central enclosure exposed				Central enclosure for assembly on a wall			
W (mm)	D (mm)	Maximum power dissipated (W)				Maximum power dissipated (W)				Maximum power dissipated (W)				Maximum power dissipated (W)				Maximum power dissipated (W)				Maximum power dissipated (W)			
		25 °C	30 °C	35 °C	40 °C	25 °C	30 °C	35 °C	40 °C	25 °C	30 °C	35 °C	40 °C	25 °C	30 °C	35 °C	40 °C	25 °C	30 °C	35 °C	40 °C	25 °C	30 °C	35 °C	40 °C
Structures H = 1800mm with blind panels																									
400	200	223	280	338	400	208	258	314	371	208	262	315	374	187	234	281	332	193	246	296	350	170	215	260	310
400	300	257	322	389	460	242	301	366	433	237	298	359	425	216	270	324	383	217	276	332	393	194	245	297	353
400	500	290	364	440	520	276	344	418	494	265	333	402	476	244	305	367	434	240	305	367	435	218	274	333	395
400	700	371	461	560	668	349	440	535	622	329	410	495	588	300	377	457	539	297	370	455	536	273	343	415	491
400	900	445	553	672	802	419	528	642	746	395	492	594	706	360	452	548	647	356	444	546	643	328	412	498	589
600	200	285	357	433	511	259	324	393	464	268	336	407	481	237	297	359	424	255	320	387	457	223	279	338	400
600	300	328	412	499	589	302	378	458	541	306	383	464	549	273	342	414	489	286	359	434	513	254	319	386	456
600	500	371	466	564	666	344	432	523	617	343	430	521	616	309	387	469	553	316	397	481	568	285	358	434	512
600	700	428	537	651	769	426	535	648	765	407	511	619	731	388	486	589	695	384	481	583	688	352	442	535	632
600	900	514	644	781	923	511	642	778	918	488	613	743	877	466	583	707	834	461	577	700	826	422	530	642	758
800	200	356	446	540	638	319	400	484	572	339	425	515	608	296	371	449	530	327	410	496	586	283	355	430	508
800	300	390	489	592	699	367	461	558	659	374	469	568	671	339	425	514	607	365	458	554	654	321	403	488	577
800	500	423	531	643	759	415	521	631	745	408	512	621	733	381	478	579	684	402	505	611	722	359	451	546	645
800	700	489	614	743	877	478	599	726	857	463	581	703	830	450	564	683	807	454	570	690	815	434	544	659	778
800	900	587	737	892	1052	574	719	871	1028	556	697	844	996	540	677	820	968	545	684	828	978	521	653	791	934
1000	900	683	824	961	1098	670	812	968	1123	651	793	945	1102	632	776	927	1086	638	780	930	1089	612	757	913	1070
1250	900	799	964	1124	1285	784	950	1133	1314	762	928	1106	1289	739	908	1085	1271	746	913	1088	1274	716	886	1068	1252
Structures H = 2000mm with blind panels																									
400	200	242	304	368	435	224	268	337	399	223	280	339	399	200	251	304	359	209	260	316	377	183	230	278	329
400	300	277	349	422	498	261	314	393	465	254	318	385	454	203	289	350	413	234	291	354	422	208	262	316	374
400	500	312	393	476	561	297	360	448	530	284	356	431	508	260	327	395	467	258	322	392	466	233	293	354	419
400	700	393	495	598	705	378	475	577	680	356	444	538	636	306	386	469	550	319	397	480	565	291	365	442	525
400	900	472	594	718	846	454	570	692	816	427	533	646	763	367	463	563	660	383	476	576	678	349	438	530	630
600	200	304	382	463	546	277	347	420	496	287	360	436	514	253	317	384	454	273	342	415	489	237	298	360	426
600	300	343	431	522	616	324	406	491	580	327	410	497	586	292	384	444	524	307	384	466	549	271	340	411	486
600	500	382	479	581	685	370	464	562	663	367	460	557	658	331	451	503	594	340	426	516	609	304	381	462	545
600	700	441	554	671	792	435	546	662	781	416	522	632	746	408	512	620	732	406	509	617	728	373	468	566	669
600	900	529	665	805	950	522	655	794	937	499	626	758	895	490	614	744	878	487	611	740	874	448	562	679	803
800	200	368	462	559	660	340	427	517	610	362	454	550	650	315	395	479	565	349	437	530	625	301	378	458	541
800	300	402	504	611	721	381	479	580	684	390	489	592	700	359	450	546	644	381	433	579	684	341	428	518	612
800	500	436	546	662	781	422	530	642	758	417	524	634	749	402	505	612	722	413	519	628	742	380	477	578	682
800	700	512	643	778	919	494	620	751	887	480	602	729	861	461	578	701	827	466	585	709	837	451	566	685	809
800	900	614	772	934	1103	593	744	901	1064	576	722	875	1033	553	694	841	992	559	702	851	1004	541	679	822	971
1000	900	721	864	1022	1198	700	858	1023	1184	681	833	987	1145	659	799	947	1100	670	814	967	1123	653	792	938	1092
1250	900	844	1011	1196	1402	819	1004	1197	1385	797	975	1155	1340	771	935	1108	1287	784	952	1131	1314	764	927	1097	1278

Power dissipated inside System pro E power switchboards on the basis of the admissible overtemperature.
 Δt = difference between the temperature inside the enclosure and ambient temperature.

Example

Enclosure IP31 H=1800mm, W=400mm, D=200mm exposed on all sides

Temperature inside the enclosure (t)	°C	70 -
Ambient temperature (t)	°C	35 =
Δt	°C	35
Maximum power dissipated	(W)	338

Technical details and certifications

Power dissipated

System pro E power IP30/31

		Separate enclosure exposed on all sides				Separate enclosure for assembly on a wall				First and last enclosures exposed				First and last enclosures for assembly on wall			
W (mm)	D (mm)	25 °C	30 °C	35 °C	40 °C	25 °C	30 °C	35 °C	40 °C	25 °C	30 °C	35 °C	40 °C	25 °C	30 °C	35 °C	40 °C
Structures H = 1800mm with ventilated panels																	
600	500	571	737	914	1102	541	698	866	1044	428	552	685	826	406	524	650	784
600	700	737	951	1180	1422	712	919	1140	1374	552	713	884	1066	518	668	829	999
800	500	649	837	1038	1252	611	788	978	1179	502	648	804	969	460	593	736	887
800	700	836	1079	1339	1613	787	1016	1261	1519	625	806	1000	1205	595	768	953	1149
1000	900	1295	1606	1926	2235	1147	1444	1750	2074	914	1146	1401	1666	818	1035	1266	1516
1250	900	1450	1799	2157	2503	1273	1603	1943	2302	1024	1284	1569	1866	908	1149	1405	1683
Structures H = 2000mm with ventilated panels																	
600	500	586	756	938	1131	546	705	874	1131	434	560	695	838	407	525	651	785
600	700	741	956	1186	1429	715	923	1145	1380	560	723	897	1081	527	680	843	1016
800	500	654	844	1047	1261	623	804	997	1202	507	654	811	978	468	604	749	903
800	700	861	1112	1379	1662	792	1022	1268	1528	640	826	1024	1234	596	769	955	1151
1000	900	1333	1655	1983	2301	1154	1452	1759	2086	935	1176	1434	1706	820	1036	1263	1520
1250	900	1493	1854	2221	2577	1281	1612	1952	2315	1047	1317	1606	1911	910	1150	1402	1687

Power dissipated inside System pro E power switchboards on the basis of the admissible overtemperature.
 Δt = difference between the temperature inside the enclosure and ambient temperature.

Example

Enclosure IP31 H=2000mm, W=600mm, D=700mm exposed on all sides

Temperature inside the enclosure (t)	°C 70 -
Ambient temperature (t)	°C 35 =
Δt	°C 35
Maximum power dissipated	(W) 1186

Technical details and certifications

Power dissipated

System pro E power IP40/41

Separate enclosure exposed on all sides				Separate enclosure for assembly on a wall				First and last enclosures exposed				First and last enclosures for assembly on wall				Central enclosure exposed				Central enclosure for assembly on a wall					
W (mm)	D (mm)	Maximum power dissipated (W)				Maximum power dissipated (W)				Maximum power dissipated (W)				Maximum power dissipated (W)				Maximum power dissipated (W)				Maximum power dissipated (W)			
		25 °C	30 °C	35 °C	40 °C	25 °C	30 °C	35 °C	40 °C	25 °C	30 °C	35 °C	40 °C	25 °C	30 °C	35 °C	40 °C	25 °C	30 °C	35 °C	40 °C	25 °C	30 °C	35 °C	40 °C
Structures H = 1800mm with blind panels																									
400	200	223	280	338	400	208	258	314	371	208	262	315	374	187	234	281	332	193	246	296	350	170	215	260	310
400	300	257	322	389	460	242	301	366	433	237	298	359	425	216	270	324	383	217	276	332	393	194	245	297	353
400	500	290	364	440	520	398	514	637	768	265	333	402	476	304	392	486	586	240	305	367	435	218	274	333	395
400	700	371	461	560	668	544	703	872	1051	329	410	495	588	382	493	612	738	297	370	455	536	273	343	415	491
400	900	445	553	672	802	725	937	1163	1401	395	492	594	706	449	580	720	868	356	444	546	643	328	412	498	589
600	200	285	357	433	511	259	324	393	464	268	336	407	481	237	297	359	424	255	320	387	457	223	279	338	400
600	300	328	412	499	589	302	378	458	541	306	383	464	549	273	342	414	489	286	359	434	513	254	319	386	456
600	500	371	466	564	666	462	596	739	891	343	430	521	616	350	451	560	674	316	397	481	568	285	358	434	512
600	700	428	537	651	769	627	809	1004	1210	407	511	619	731	438	565	701	845	384	481	583	688	352	442	535	632
600	900	514	644	781	923	836	1079	1339	1613	488	613	743	877	515	665	825	994	461	577	700	826	422	530	642	758
800	200	356	446	540	638	319	400	484	572	339	425	515	608	296	371	449	530	327	410	496	586	283	355	430	508
800	300	390	489	592	699	367	461	558	659	374	469	568	671	339	425	514	607	365	458	554	654	321	403	488	577
800	500	423	531	643	759	525	678	841	1013	408	512	621	733	405	523	648	781	402	505	611	722	359	451	546	645
800	700	489	614	743	877	689	889	1103	1329	463	581	703	830	473	661	819	988	454	570	690	815	434	544	659	778
800	900	587	737	892	1052	919	1185	1471	1772	556	697	844	996	556	778	964	1162	545	684	828	978	521	653	791	934
1000	900	683	824	961	1098	1072	1338	1634	1935	651	793	945	1102	650	891	1089	1303	638	780	930	1089	612	757	913	1070
1250	900	799	964	1124	1285	1190	1485	1814	2148	762	928	1106	1289	722	989	1209	1446	746	913	1088	1274	716	886	1068	1252
Structures H = 2000mm with blind panels																									
400	200	242	304	368	435	224	268	337	399	223	280	339	399	200	251	304	359	209	260	316	377	183	230	278	329
400	300	277	349	422	498	261	314	393	465	254	318	385	454	203	289	350	413	234	291	354	422	208	262	316	374
400	500	312	393	476	561	403	519	644	777	284	356	431	508	309	398	492	591	258	322	392	466	233	293	354	419
400	700	393	495	598	705	547	706	876	1056	356	444	538	636	389	498	617	743	319	397	480	565	291	365	442	525
400	900	472	594	718	846	729	941	1168	1408	427	533	646	763	458	586	726	874	383	476	576	678	349	438	530	630
600	200	304	382	463	546	277	347	420	496	287	360	436	514	253	317	384	454	273	342	415	489	237	298	360	426
600	300	343	431	522	616	324	406	491	580	327	410	497	586	292	384	444	524	307	384	466	549	271	340	411	486
600	500	382	479	581	685	466	602	747	900	367	460	557	658	353	456	565	681	340	426	516	609	304	381	462	545
600	700	441	554	671	792	632	815	1011	1219	416	522	632	746	448	578	717	864	406	509	617	728	373	468	566	669
600	900	529	665	805	950	843	1087	1348	1625	499	626	758	895	527	680	844	1016	487	611	740	874	448	562	679	803
800	200	368	462	559	660	340	427	517	610	362	454	550	650	315	395	479	565	349	437	530	625	301	378	458	541
800	300	402	504	611	721	381	479	580	684	390	489	592	700	359	450	546	644	381	433	579	684	341	428	518	612
800	500	436	546	662	781	536	692	859	1035	417	524	634	749	410	528	656	790	413	519	628	742	380	477	578	682
800	700	512	643	778	919	701	905	1123	1353	480	602	729	861	510	658	816	983	466	585	709	837	451	566	685	809
800	900	614	772	934	1103	935	1207	1497	1804	576	722	875	1033	600	774	960	1156	559	702	851	1004	541	679	822	971
1000	900	721	864	1022	1198	1103	1391	1699	1998	681	833	987	1145	714	891	1080	1281	670	814	967	1123	653	792	938	1092
1250	900	844	1011	1196	1402	1224	1544	1886	2218	797	975	1155	1340	793	989	1199	1422	784	952	1131	1314	764	927	1097	1278

Power dissipated inside System pro E power switchboards on the basis of the admissible overtemperature.
 Δt = difference between the temperature inside the enclosure and ambient temperature.

Example

Enclosure IP31 H=1800mm, W=600mm, D=900mm exposed on all sides

Temperature inside the enclosure (t)	°C	70 -
Ambient temperature (t)	°C	35 =
Δt	°C	35
Maximum power dissipated		(W) 781

Technical details and certifications

Power dissipated

System pro E power IP40/41

Separate enclosure exposed on all sides				Separate enclosure for assembly on a wall				First and last enclosures exposed				First and last enclosures for assembly on wall					
W (mm)	D (mm)	25 °C	30 °C	35 °C	40 °C	25 °C	30 °C	35 °C	40 °C	25 °C	30 °C	35 °C	40 °C	25 °C	30 °C	35 °C	40 °C
Structures H = 1800mm with ventilated panels																	
400 500		418	539	669	806	398	514	637	768	317	409	507	611	304	392	486	586
400 700		562	725	899	1084	544	703	872	1051	395	509	632	761	382	493	612	738
400 900		749	967	1199	1445	725	937	1163	1401	494	636	790	951	449	580	720	868
600 500		489	631	783	944	462	596	739	891	376	485	602	725	350	451	560	674
600 700		651	840	1042	1256	627	809	1004	1210	471	608	754	909	438	565	701	845
600 900		868	1120	1389	1675	836	1079	1339	1613	589	760	943	1136	515	665	825	994
800 500		560	723	897	1081	525	678	841	1013	438	565	700	844	405	523	648	781
800 700		733	946	1174	1415	689	889	1103	1329	524	676	838	1010	473	661	819	988
800 900		977	1261	1565	1887	919	1185	1471	1772	655	845	1048	1263	556	778	964	1162
1000 900		1135	1408	1688	1962	1072	1338	1634	1935	766	960	1173	1397	650	891	1089	1303
1250 900		1271	1577	1891	2197	1190	1485	1814	2148	858	1075	1314	1565	722	989	1209	1446
Structures H = 2000mm with ventilated panels																	
400 500		422	543	671	809	403	519	644	777	320	413	511	615	309	398	492	591
400 700		567	732	908	1094	547	706	876	1056	398	514	635	765	389	498	617	743
400 900		756	976	1211	1459	729	941	1168	1408	498	643	794	956	458	586	726	874
600 500		503	649	805	970	466	602	747	900	379	489	607	732	353	456	565	681
600 700		657	847	1051	1267	632	815	1011	1219	477	616	764	921	448	578	717	864
600 900		876	1129	1401	1689	843	1087	1348	1625	596	770	955	1151	527	680	844	1016
800 500		566	731	907	1093	536	692	859	1035	440	568	705	850	410	528	656	790
800 700		764	985	1222	1474	701	905	1123	1353	546	705	874	1054	510	658	816	983
800 900		1019	1313	1629	1965	935	1207	1497	1804	683	881	1093	1318	600	774	960	1156
1000 900		1196	1497	1782	2134	1103	1391	1699	1998	807	1016	1232	1460	714	891	1080	1281
1250 900		1340	1677	1996	2390	1224	1544	1886	2218	904	1138	1380	1635	793	989	1199	1422

Power dissipated inside System pro E power switchboards on the basis of the admissible overtemperature.
 Δt = difference between the temperature inside the enclosure and ambient temperature.

Example

Enclosure IP31 H=2000mm, W=600mm, D=700mm exposed on all sides

Temperature inside the enclosure (t)	°C 70 -
Ambient temperature (t)	°C 35 =
Δt	°C 35
Maximum power dissipated	(W) 1051

Technical details and certifications

Power dissipated

System pro E power IP65

Separate enclosure exposed on all sides				Separate enclosure for assembly on a wall				First and last enclosures exposed				First and last enclosures for assembly on wall				Central enclosure exposed				Central enclosure for assembly on a wall					
Maximum power dissipated (W)				Maximum power dissipated (W)				Maximum power dissipated (W)				Maximum power dissipated (W)				Maximum power dissipated (W)				Maximum power dissipated (W)					
W (mm)	D (mm)	25 °C	30 °C	35 °C	40 °C	25 °C	30 °C	35 °C	40 °C	25 °C	30 °C	35 °C	40 °C	25 °C	30 °C	35 °C	40 °C	25 °C	30 °C	35 °C	40 °C	25 °C	30 °C	35 °C	40 °C
Structures H = 1800mm with blind panels																									
400	300	223	284	344	406	213	267	323	381	206	258	313	370	188	236	286	338	188	236	286	338	170	213	258	305
400	200	193	242	293	346	179	224	271	320	178	223	270	319	160	201	243	287	165	207	251	296	146	184	222	263
400	500	260	326	395	466	247	310	375	443	235	294	357	421	217	272	329	389	212	266	322	381	194	243	295	348
400	700	328	411	498	588	317	398	482	569	290	364	440	520	274	344	417	492	259	325	394	465	243	304	369	435
400	900	386	484	586	692	373	468	567	669	341	428	518	612	322	405	491	579	305	382	464	547	286	358	434	512
600	300	292	366	443	524	268	336	407	481	271	341	413	488	242	304	368	435	279	319	386	456	226	284	343	406
600	200	254	318	385	455	230	289	350	413	238	299	362	428	210	264	320	378	227	285	345	407	198	249	301	356
600	500	331	415	502	593	306	384	465	549	305	383	464	548	275	344	417	493	282	353	428	505	254	319	386	456
600	700	381	478	579	684	379	476	577	681	362	455	551	650	345	433	524	619	341	428	519	612	314	393	477	563
600	900	448	562	681	805	446	560	679	801	426	535	648	765	406	509	616	728	401	504	611	720	369	462	561	662
800	300	346	435	526	622	326	409	496	586	332	417	505	596	301	378	458	540	324	407	493	581	286	358	434	413
800	200	316	397	481	568	284	356	431	509	302	378	458	541	263	330	400	472	291	365	442	521	252	316	383	452
800	500	377	473	572	676	369	463	561	663	363	456	552	652	339	426	516	609	358	449	544	642	320	401	486	574
800	700	435	546	661	781	425	533	646	763	412	517	626	739	400	502	608	718	404	507	614	725	386	484	586	692
800	900	512	642	778	919	500	627	760	898	485	608	736	869	471	591	715	845	475	596	722	853	454	569	689	814
1000	900	596	718	838	959	583	708	844	981	568	692	832	975	551	677	808	948	556	679	811	950	533	659	795	932
1250	900	697	840	980	1122	682	828	987	1148	665	810	973	1141	645	792	945	1109	651	794	949	1112	624	771	930	1090
Structures H = 2000mm with blind panels																									
400	300	244	306	371	438	228	287	347	410	221	278	337	397	202	254	307	363	202	254	308	363	182	228	277	327
400	200	209	262	317	375	192	241	292	345	191	240	291	343	172	216	262	309	178	223	270	319	157	197	239	282
400	500	279	351	425	501	265	333	403	476	252	316	383	452	232	292	353	417	227	285	346	408	207	260	315	372
400	700	354	444	537	634	341	428	519	612	314	394	478	564	295	370	448	529	278	349	423	499	258	324	393	464
400	900	416	522	632	746	401	504	611	720	369	464	562	664	347	435	527	622	327	411	498	587	304	381	462	546
600	300	305	383	464	548	287	361	437	516	290	364	442	521	260	342	395	466	272	342	414	459	241	302	366	432
600	200	271	340	412	486	246	309	374	442	255	320	388	458	225	282	342	404	243	305	369	436	211	265	321	379
600	500	340	426	517	610	329	413	500	590	326	409	496	585	295	402	448	528	302	379	459	542	271	339	411	485
600	700	393	493	597	705	387	486	589	695	370	464	562	664	363	455	552	651	361	453	549	648	332	416	504	595
600	900	462	580	702	829	455	572	693	818	435	546	661	781	427	535	649	766	425	533	646	762	391	489	593	700
800	300	358	448	543	641	339	404	515	609	346	406	527	622	319	400	485	573	339	425	515	608	303	380	461	544
800	200	328	411	498	588	303	380	460	543	322	404	490	578	280	352	426	503	310	389	471	557	268	337	408	481
800	500	388	486	589	695	376	472	571	675	371	466	565	667	358	449	544	643	368	462	559	660	338	424	514	607
800	700	456	572	693	818	440	552	668	789	427	536	649	766	410	515	624	736	415	521	631	745	401	503	610	720
800	900	536	673	815	962	518	649	786	928	502	631	764	901	482	606	734	866	488	613	742	876	472	592	718	847
1000	900	629	753	892	1045	611	748	892	1092	593	728	862	998	574	697	826	960	585	710	843	980	569	690	819	952
1250	900	736	881	1044	1223	715	875	1044	1278	694	852	1009	1168	672	815	966	1123	684	831	986	1147	666	807	958	1114

Power dissipated inside System pro E power switchboards on the basis of the admissible overtemperature.
 Δt = difference between the temperature inside the enclosure and ambient temperature.

Example


Enclosure IP31 H=1800mm, W=600mm, D=900mm exposed on all sides

Temperature inside the enclosure (t)	°C	70 -
Ambient temperature (t)	°C	35 =
Δt	°C	35
Maximum power dissipated	(W)	681

Technical details and certifications


Handling

Handling with a transpallet




Dimensions	A (mm)
Width 300mm	198
Width 400mm	298
Width 600mm	498
Width 800mm	698
Width 1000mm	898
Width 1250mm	1098

For extra safety, it is advisable to fasten the switchboard to the lift truck when using this type of vehicle for transport.




Shallow switchboards should be handled in the following way:

Side



Check the center of gravity before handling structures measuring L=800/1000mm (with internal or external cable compartment) containing busbar systems.



Technical details and certifications

Handling


Handling with a bridge crane

Before handling switchboards with a crane or bridge crane, make sure that:

- the ropes or chains are in an excellent condition;
- the angle between the lifting ropes and the top of the switchboard must be $\geq 45^\circ$;

- up to 3 units can be carried at the same time;
- maximum weight lifted as established by Standard DIN 580 (M12).

To comply with the conditions described above, use a lifting beam with the appropriate characteristics when lifting several adjacent units.



Standard DIN 580 concerning mechanical connection components (only for eyebolts)

Eyebolts		Lifting reinforcements							
A	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	Load 1 (kg)	Load 2 (kg)	Tightening (Nm)
Eyebolts									
M12	54	12	28	10	22	30	340	240	8*
Lifting reinforcements									
M12	Ø40	37	80	25	Ø14	60	510	350	40

Technical details and certifications

Electrical continuity

Electrical continuity of the structure and fixed and movable parts

The accessible metal parts in a switchboard must be electrically connected together and with the main protection conductor. $\Omega 0.1$ is the maximum resistance value allowed for this circuit.

Electrical continuity in System pro E power switchboards is automatically guaranteed by the screws and bolts and by the way the structure assembly is engineered. In addition, the connections can be made using the earthing pins on the external covers.

The panels are earthed by means of the fastening screw, as required by standard IEC 61439-1 (part 8.4.3.2.2) "Specifications for earthing continuity to protect against the consequences of faults within switchgear": "b) For covers, doors, closing plates and similar, the ordinary connections with metal screws and metal hinges are considered sufficient for electrical continuity so long as electrical devices that exceed the low voltage limits (ELV) are not installed on them". To achieve this:

- only and exclusively use the screws and accessories supplied with the components
- comply with the assembly instructions given in the manuals

The proposed solutions have been tested and no additional earthing braid is required.

The paint reduces the electrical continuity of the assembled parts.

To assure electrical continuity, use screws with toothed washers that cut into the paint or, alternatively, earthing braid.

To assure electrical continuity, the mechanical assemblies (front plates, bottom plates, etc.) are also made with devices that cut into the painted surface:

- clips
- 1/4-turn screws
- self-threading screws
- screws + nuts with sharp-toothed washers

It is obligatory to use a braid for the earth connection in the case of movable metal parts (doors, swing frames or removable panels) that must support electrical components differing from class 2 (which, being fitted with double insulation, are not earthed).

Electrical continuity in the case of front panels, is guaranteed in the closed position by the special shape of the hinge (ABB patent), always supplied even in the absence of connection via conductor. Earthing braid is supplied on request for the electrical components installed on the door, as well as for the passage of cables from communicating or low power circuits: analog, digital and telecommunication cables. Since the internal parts and the circuit-breaker assembly kits are made of unpainted galvanized steel, continuity is guaranteed without any additional earthing braid.

The earth conductor must be properly sized in relation to the maximum operating current, as shown in the following table defined by Standard IEC 61439-1.

Technical details and certifications

Conductors

Calculation of protection conductor PE

Standard IEC 61439-1-2 contain the methods for calculating the section of the protection conductor PE, which must be sized to withstand the thermal and dynamic components of the fault currents.

The following conditions must be ascertained when choosing the position in which the bar is to be fixed:

- the bar must be connected straight to the earthed parts of the switchboard (structure);
- the bar must be connected in an easily accessible position.

—
Use the values in the table for sizing taken from Standards IEC 61439-1-2.

S (mm ²)			Sp (mm ²)
	S	≤	16
16	<	S	35
35	<	S	400
400	<	S	800
		S >	800
			S/4

Equipotentiality conductor

Conductive parts of a device, which cannot be connected to the protection circuit with their own means of connection, must be connected to the protection circuit of the apparatus through the equipotentiality of the protection.

This is done by means of a protective bonding

conductor, the section of which must be chosen in accordance with the table below.

Rated service voltage I _e (A)	I _e	≤	20	S
20	<	I _e	≤	25
25	<	I _e	≤	32
32	<	I _e	≤	63
63	<	I _e		10

S = section of the line conductor (mm²)

Conductor PEN

The section of the PEN conductors of an apparatus must be determined in the same way as the neutral conductor (N).

10mm² is the minimum section of a copper conductor.

The PEN conductor does not need to be insulated. Structure parts must not be used as a PEN conductors. However, the copper or aluminium assembly tracks can be used as PEN conductors.

For conductors that are not made of copper, equivalent conductivity sections are used instead of the sections above and may require larger terminals.

Technical details and certifications


IP protection class


1st DIGIT: protection against solid objects

0 No protection


1  Protected against solid objects larger 50mm (accidental contact with the hands)

2  Protected against solid objects larger than 12mm (fingers)

3  Protected against solid objects larger than 2.5mm (tools, wires)

4  Protected against solid objects larger than 1mm


5  Protected against dust (no harmful deposits)

6  Totally protected against dust


1st digit defined by Standards 61439-1-2 (Ref. sect. 10.3).

2nd DIGIT: Protection against liquids


0 No protection


1  Protected against vertically dripping water (condensation)


2  Protected against water dripping at an angle up to 15° from the vertical


3  Protected against rain falling at an angle up to 60° from the vertical

4  Protected against water splashing from all directions

5  Protected against jets of water sprayed from all directions

6  Protected against jets of water similar to waves

7  Protected against the effects of temporary immersion

8  Protected against the effects of continuous immersion

2nd digit defined by Standards 61439-1-2 (Ref. sect. 10.3).

Technical details and certifications

IP protection class

Protection against ingress of solid objects

1 st characteristic digit	Brief description	Full description
0	Not protected	No particular protection is envisaged
1	Protected against solid objects larger than 50mm	A large area of the human body, for example a hand (however, voluntary protection is not envisaged) or solid objects larger than 50mm in diameter must not be able to penetrate
2	Protected against solid objects measuring	The fingers or similar objects measuring 80mm or solid objects more than 12mm in diameter must not be able to penetrate
3	Protected against solid objects measuring more than 2.5mm	Tools, wires, etc., more than 2.5mm in diameter or thickness or solid objects more than 2.5mm in diameter must not be able to penetrate
4	Protected against solid objects measuring more than 1.0mm	Wires or flat cables more than 1.0mm thick or solid objects more than 1.0mm in diameter must not be able to penetrate
5	Protected against dust	Penetration of dust is not totally excluded but the quantity that may penetrate is not sufficient to impair the correct operation of the material
6	Totally protected against dust	No dust penetration is permitted

Protection against ingress of water

2 nd characteristic digit	Brief description	Full description
0	Not protected	No particular protection is envisaged
1	Protected against dripping water	Drops of water falling vertically must not produce harmful effects
2	Protected against water dripping at a maximum angle of 15°	Drops of water falling vertically must not produce harmful effects when the enclosure is tilted at any angle up to 15° from its normal position
3	Protected against rainfall	Water falling as a spray at any angle up to 60° from the vertical shall have no harmful effects
4	Protected against splashing water	Water splashing against the enclosure from any direction shall have no harmful effects
5	Protected against water jets	Water projected by a nozzle from any direction shall have no harmful effects
6	Protected against waves	Waves or powerful water jets shall not penetrate the enclosure in harmful quantities
7	Protected against the effects of temporary immersion	Ingress of water in harmful quantities shall not be possible when the enclosure is immersed in water under defined conditions of pressure and time
8	Protected against the effects of continuous immersion	The equipment is suitable for continuous immersion under conditions which shall be specified by the manufacturer

Technical details and certifications

Mechanical shock resistance IK

The IK is expressed in Joule in compliance with the requirements of IEC 62262.

IK 0	Not protected	
IK 01	Impact energy in Joule 0.140	
IK 02	Impact energy in Joule 0.200	
IK 03	Impact energy in Joule 0.350	
IK 04	Impact energy in Joule 0.500	
IK 05	Impact energy in Joule 0.700	
IK 06	Impact energy in Joule 1.00	
IK 07	Impact energy in Joule 2.00	
IK 08	Impact energy in Joule 5.00	
IK 09	System pro E power Glass door Impact energy in Joule 10.00	
IK 10	System pro E power Blind door Impact energy in Joule 20.00	

Technical details and certifications

Special painting

On request, colours other than the standard RAL 7035 orange peel are available with the same painting cycle.

Tables A, B and C indicates different raises on standard price

for the paint. For every request regarding special colours, please contact ABB.

Tables A

Tables B

RAL 1002	RAL 1004	RAL 1013	RAL 1015	RAL 1018	RAL 1019
 Smooth <input checked="" type="checkbox"/> Orange peel <input type="checkbox"/>	 Smooth <input checked="" type="checkbox"/> Orange peel <input type="checkbox"/>	 Smooth <input checked="" type="checkbox"/> Orange peel <input type="checkbox"/>	 Smooth <input checked="" type="checkbox"/> Orange peel <input type="checkbox"/>	 Smooth <input checked="" type="checkbox"/> Orange peel <input type="checkbox"/>	 Smooth <input checked="" type="checkbox"/> Orange peel <input type="checkbox"/>
RAL 1021	RAL 1023	RAL 2002	RAL 2008	RAL 2004	RAL 2009
 Smooth <input checked="" type="checkbox"/> Orange peel <input type="checkbox"/>	 Smooth <input checked="" type="checkbox"/> Orange peel <input type="checkbox"/>	 Smooth <input checked="" type="checkbox"/> Orange peel <input type="checkbox"/>	 Smooth <input checked="" type="checkbox"/> Orange peel <input type="checkbox"/>	 Smooth <input checked="" type="checkbox"/> Orange peel <input type="checkbox"/>	 Smooth <input checked="" type="checkbox"/> Orange peel <input type="checkbox"/>
RAL 3003	RAL 3004	RAL 3020	RAL 4005	RAL 5002	RAL 5003
 Smooth <input checked="" type="checkbox"/> Orange peel <input type="checkbox"/>	 Smooth <input checked="" type="checkbox"/> Orange peel <input type="checkbox"/>	 Smooth <input checked="" type="checkbox"/> Orange peel <input type="checkbox"/>	 Smooth <input checked="" type="checkbox"/> Orange peel <input type="checkbox"/>	 Smooth <input checked="" type="checkbox"/> Orange peel <input type="checkbox"/>	 Smooth <input checked="" type="checkbox"/> Orange peel <input type="checkbox"/>
RAL 5017	RAL 7004	RAL 7011	RAL 7016	RAL 7024	RAL 7031
 Smooth <input checked="" type="checkbox"/> Orange peel <input type="checkbox"/>	 Smooth <input checked="" type="checkbox"/> Orange peel <input type="checkbox"/>	 Smooth <input checked="" type="checkbox"/> Orange peel <input type="checkbox"/>	 Smooth <input checked="" type="checkbox"/> Orange peel <input type="checkbox"/>	 Smooth <input checked="" type="checkbox"/> Orange peel <input type="checkbox"/>	 Smooth <input checked="" type="checkbox"/> Orange peel <input type="checkbox"/>
RAL 7032	RAL 7035	RAL 7036	RAL 7037	RAL 7038	RAL 9001
 Smooth <input checked="" type="checkbox"/> Orange peel <input type="checkbox"/>	 Smooth <input checked="" type="checkbox"/> Orange peel <input type="checkbox"/>	 Smooth <input checked="" type="checkbox"/> Orange peel <input type="checkbox"/>	 Smooth <input checked="" type="checkbox"/> Orange peel <input type="checkbox"/>	 Smooth <input checked="" type="checkbox"/> Orange peel <input type="checkbox"/>	 Smooth <input checked="" type="checkbox"/> Orange peel <input type="checkbox"/>
RAL 9003	RAL 9007				
 Smooth <input checked="" type="checkbox"/> Orange peel <input type="checkbox"/>	 Smooth <input checked="" type="checkbox"/> Orange peel <input type="checkbox"/>				

Technical details and certifications

Special painting

Tables C

RAL 1001



RAL 1016



RAL 3002



RAL 3011



RAL 5000



RAL 5002



RAL 5009



RAL 5017



RAL 5018



RAL 6001



RAL 6002



RAL 6003



RAL 6009



RAL 6020



RAL 6024



RAL 6026



RAL 6029



RAL 7000



RAL 7001



RAL 7004



RAL 7005



RAL 7006



RAL 7012



RAL 7015




RAL 7016




RAL 7021




RAL 7022




RAL 7024




RAL 7037



RAL 7038




RAL 7040




RAL 7042




RAL 7043




RAL 7044



RAL 7045



RAL 7046




RAL 7047



RAL 9005



RAL 9016




Technical details and certifications


Connection examples - Unifix H

Unifix H frame with 400A busbars 24 and 36 DIN modules


Busbars supplied from above by means of a 4P feeder module installed laterally




Power supply by means of circuit-breaker supplied from above




Busbars supplied from below by means of a 4P feeder module installed laterally




Power supply by means of circuit-breaker supplied from below



Busbars supplied from above by means of a 4P feeder module installed centrally



Covers for IP 20 protection class




Technical details and certifications


Connection examples - Unifix L

Unifix L frame with 100A busbars
12/18/24 DIN modules


Two different single-phase circuits on a single DIN rail with 24 modules




Example of main and branched power supply




Busbars supplied by means of cable terminal under the head of the circuit-breaker's terminal and branching with parallel module




Busbars supplied by means of terminals installed centrally



Busbars supplied from above by means of terminals installed laterally



Busbars supplied directly by means of feeder module (supplied without cables) and branching by means of feeder module



Technical details and certifications

Configuration examples

2000x800x300mm (HxWxD) structure with H=100mm plinth, internal cable compartment, IP65 protection class. 1000A vertical busbar system installed at the side of the cable compartment.

T6 main circuit-breaker fixed vertically. Fixed frame. T4 circuitbreaker kit fixed horizontally, No. 3 XT1 fixed horizontally.

Quantity	Type	Description	Reference chapter
1	PUPM2000	No.4 galvanized sheet metal uprights H=2000mm	Structure
1	PUCM2000	No. 4 galvanized sheet metal cross-pieces W=800mm	Structure
1	PCFM0800	No. 4 galvanized sheet metal cross-pieces W/D=300mm	Structure
1	PCFM0300	No. 4 galvanized sheet metal plinth angle pieces H=100mm	Structure
1	PPAM0100	No. 2 front/rear plinth flanges H=100mm W=800mm	Structure
1	PPFM1080	No. 2 side plinth flanges H=100mm W/D=300mm	Structure
1	PPFM1030	Blind Top/Bottom IP65 W=800mm D=300mm	Structure
1	PTBB8036	Open Top/Bottom IP65 W=800mm D=300mm	Structure
1	PTBO8030	Incoming cable flange 800x300mm	Structure
1	PFCF8030	External cover IP65 H=2000mm W=800mm	Structure
1	PPEB2086	External cover IP65 H=2000mm W/D=300mm	Structure
2	PPEB2036	Blind door for int.cable comp. H=2000mm L=200mm	Structure
1	PDCB2020	Glass door IP65 H=2000mm W=800mm	Structure
1	PDLG2062	Upright for cable comp. in galv. sheet metal H=2000mm	Structure
1	PPPF2060	Fixed frame for panels H=2000mm L=600	Internal kits
1	PVCT6401	Kit with 3-4P T6 fixed vertical installation W=600mm	Internal kits
1	PHCT4406	Kit with 3-4P T4 fixed horizontal installation W=600mm	Internal kits
3	PHCX1401	Kit with 3-4P XT1 fixed horizontal installation W=600mm	Internal kits
1	PPFB1560	Flat blind panel H=150mm W=600mm	Internal kits
2	PPFB4060	Flat blind panel H=400mm W=600mm	Internal kits
8	PBFC4005	Flat copper bar 40x5 L=1750mm	Main distribution systems
2	PCRM0238	No. 2 galvanized sheet metal cross-pieces W=238mm	Main distribution systems
2	PBHB1125	No. 24 busbar insulating supports L=50mm	Main distribution systems
2	PTRN1951	No. 10 nylon tie rods W=195mm for In<4000A	Main distribution systems
2	PCRM0288	No. 2 galvanized sheet metal cross-pieces W=288mm	Main distribution systems
1	PBBV0008	No. 8 busbar plates vertical side	Main distribution systems

Technical details and certifications

Configuration examples

1800x600x300mm (HxWxD) structure without plinth, IP65 protection class. 630A vertical busbar system installed at the rear of the structure. T5

main circuit-breaker fixed vertically.
Kit with No.2 XT2 circuit-breakers fixed vertically.

Quantity	Type	Description	Reference chapter
1	PUPM1800	No. 4 galvanized sheet metal uprights H=1800mm	Structure
1	PCFM0600	No. 4 galvanized sheet metal cross-pieces W=600mm	Structure
1	PCFM0300	No. 4 ga lvanized sheet metal cross-pieces W/D=300mm	Structure
1	PTBB6030	Blind Top/Bottom IP40 L=600mm d=300mm	Structure
1	PBWP6030	Internal bottom IP40 L=600mm D=300mm	Structure
1	PPEB1860	External rear cover IP40 H=1800mm W=600mm	Structure
2	PPEB1830	External side cover IP40 H=1800mm W/D=300mm	Structure
1	PDLG1860	Glass door IP40 H=1800mm W=600mm	Structure
1	PFPF1860	Fixed frame for panels H=1800mm W=600	Internal kits
1	PVCT5406	Kit with 3-4P T5 fixed+vertical (400/630A)mrd W=600mm	Internal kits
2	PVCX2401	Kit with 3-4P XT2 fixed vertical installation W=600mm	Internal kits
2	PDRS0600	Standard DIN rail W=600mm	Internal kits
2	PPMF2060	Panel with 24 DIN modules H=200mm W=600mm	Internal kits
1	PPFB1560	Flat blind panel H=150mm W=600mm	Internal kits
1	PPFB3060	Flat blind panel H=300mm W=600mm	Internal kits
2	PBFC5005	Flat copper bar 50x5 L=1750mm	Main distribution systems
3	PCRM0238	No. 2 galvanized sheet metal cross-pieces W=238mm	Main distribution systems
2	PBHB1125	No. 24 busbar insulating supports L=50mm	Main distribution systems
3	PTRN1951	No. 10 nylon tie rods W=195mm for In<4000A	Main distribution systems
3	PCRM0588	No. 2 galvanized sheet metal cross-pieces W=588mm	Main distribution systems
2	PBBV0008	No. 8 busbar plates vertical side	Main distribution systems

Technical details and certifications

Configuration examples

2000x800x500mm (HxWxD) structure with H=100mm plinth, internal cable compartment, IP65 protection class. 1600A vertical busbar system installed at the side of the structure.

T7 main circuit-breaker fixed vertically.

Swing frame.

Horizontal removable T6 kit, horizontal removable T5, horizontal removable XT4.

Quantity	Type	Description	Reference chapter
1	PUPM2000	No. 4 galvanized sheet metal uprights H=2000mm	Structure
1	PCFM0800	No. 4 galvanized sheet metal cross-pieces W=800mm	Structure
1	PCFM0500	No. 4 galvanized sheet metal cross-pieces W/D=500mm	Structure
1	PPAM0100	No. 4 galvanized sheet metal plinth angle pieces H=100mm	Structure
1	PPFM1080	No. 2 front/rear plinth flanges H=100mm L=800mm	Structure
1	PPFM1050	No. 2 side plinth flanges H=100mm W/D=500mm	Structure
2	PTBB8056	Blind Top/Bottom IP65 L=800mm D=500mm	Structure
1	PPEB2086	External cover IP65 H=2000mm W=800mm	Structure
2	PPEB2056	External cover IP65 H=2000mm W=500mm	Structure
1	PDCB2020	Blind door for int.cable comp. H=2000mm W=200mm	Structure
1	PDLG2062	Glass door IP65 H=2000mm W=800mm	Structure
1	PUCM2000	Upright for cable comp. in galv. sheet metal H=2000mm	Structure
1	PCCM0500	No. 2 galvanized sheet metal cross-pieces VC D=500mm	Structure
2	PUKI2000	Swing frame for panels H=2000mm W=600	Structure
1	PFPS2060	Int. kit intermediate upright H=2000mm	Structure
1	PVCT7419	Kit with 3-4P T7 fixed vertical installation W=600mm	Internal kits
1	PHCT6410	Kit with 3-4P T6 removable horizontal installation W=600mm	Internal kits
1	PHCT5414	Kit with 3-4P T5 removable (400A) horizontal installation W=600mm	Internal kits
1	PHCX4410	Kit with 3-4P XT4 removable horizontal installation W=600mm	Internal kits
1	PPFB1560	Flat blind panel H=150mm W=600mm	Internal kits
1	PPFB2060	Flat blind panel H=200mm W=600mm	Internal kits
4	PBFC1001	Flat copper bar 100x10 W=1750mm	Main distribution systems
3	PCRM0238	No. 2 galvanized sheet metal cross-pieces W=238mm	Main distribution systems
1	PBHB1125	No. 24 busbar insulating supports W=50mm	Main distribution systems
2	PTRN1951	No. 10 nylon tie rods L=195mm for In<4000A	Main distribution systems
1	PBBV0008	No. 8 busbar plates vertical side	Main distribution systems
1	PCBS1560	Blind compartment H=150mm W=600mm	Segregations
1	PPVS2450	No.2 lateral segregation cell H=450mm	Segregations
1	PCBS2060	Blind compartment H=200mm W=600mm	Segregations
1	PPVS2500	No.2 lateral segregation cell H=500mm	Segregations
1	PPVS2350	No.2 lateral segregation cell H=350mm	Segregations
1	PPVS2250	No.2 lateral segregation cell H=250mm	Segregations
4	PSHS1906	Horizontal shelf W=600mm	Segregations

Technical details and certifications

Configuration examples

2000x600x700mm + 2000x1000x700 (HxWxD) structure with H=100mm plinth, L400mm cable compartment inside the W=1000mm structure, IP40 protection class. 2500A horizontal busbar system at any height in the unit W=600mm and

vertically on the side of the structure W=1000mm. E2.2 removable main circuit-breaker fixed vertically. Fixed frame. Kit with horizontal removable 4-pole T7, horizontal removable 4-pole T6, 2 horizontal removable XT2.

Quantity	Type	Description	Reference chapter
2	PUPM2000	No. 4 galvanized sheet metal uprights H=2000mm	Structure
1	PCFM1000	No. 4 galvanized sheet metal cross-pieces W=1000mm	Structure
1	PCFM0600	No. 4 galvanized sheet metal cross-pieces W=600mm	Structure
2	PCFM0700	No. 4 galvanized sheet metal cross-pieces D=700mm	Structure
2	PPAM0100	No. 4 galvanized sheet metal plinth angle pieces H=100mm	Structure
1	PPFM1010	No. 2 front/rear plinth flanges H=100mm W=1000mm	Structure
1	PPFM1070	No. 2 side plinth flanges H=100mm D=700mm	Structure
1	PPFM1060	No. 2 front/rear plinth flanges H=100mm W=600mm	Structure
1	PTBB6070	Blind Top/Bottom IP40 L=600mm D=700mm	Structure
1	PTBO6070	Open Top/Bottom IP65 L=600mm D=700mm	Structure
2	PTBB1070	Blind Top/Bottom IP40 L=1000mm D=700mm	Structure
1	PPEB2060	External cover IP30/40 H=2000mm W=600mm	Structure
1	PPEB2010	External cover IP30/40 H=2000mm W=1000mm	Structure
2	PPEB2070	External cover IP30/40 H=2000mm D=700mm	Structure
1	PDLG2060	Glass door IP40 H=2000mm W=600mm	Structure
1	PDLG2640	Glass door IP40 H=2000mm W=1000mm	Structure
1	PUCM2000	Galvanized sheet metal cable uprights H=2000mm	Structure
1	PCCM0700	2 galvanized sheet metal cross-pieces D=700mm	Structure
1	PDCB2040	Blind door for int.cable comp. H=2000mm W=400mm	Structure
1	PSBS0040	Kit for joining side structures IP40	Structure
5	PUKI2000	Internal kit intermediate upright H=2000mm	Structure
2	PFPF2060	Fixed frame for panels H=2000mm L=600	Structure
1	PPFB6060	Flat blind panel H=600mm W=600mm	Internal kits
1	PPFB4060	Flat blind panel H=400mm W=600mm	Internal kits
3	PPFB2060	Flat blind panel H=200mm W=600mm	Internal kits
1	PPFB3060	Flat blind panel H=300mm W=600mm	Internal kits
1	PVCE2450	Kit with vertical 3-4 pole Emax E2.2 600x600	Internal kits
1	PHCT7430	Kit with 3-4P T7 removable horizontal installation W=600mm	Internal kits
1	PHCT6410	Kit with 3-4P T6 removable horizontal installation W=600mm	Internal kits
2	PHCX2410	Kit with 3-4P XT2 removable horizontal installation W=600mm	Internal kits
1	PPMB6060	Blind mounting plate H=600mm W=600mm	Internal kits
12	PBFC1001	Flat copper bar 100x10 L=1750mm	Main distribution systems

Technical details and certifications

Configuration examples

Quantity	Type	Description	Reference chapter
3	PCRM0338	No. 2 galvanized sheet metal cross-pieces W=338mm	Main distribution systems
1	PCRM0588	No. 2 galvanized sheet metal cross-pieces W=588mm	Main distribution systems
2	PBHB2145	No. 24 busbar insulating supports L=75mm	Main distribution systems
3	PTRN1951	No. 10 nylon tie rods L=195mm for In<4000A	Main distribution systems
3	PCRM0438	No. 2 galvanized sheet metal cross-pieces W=438mm	Main distribution systems
1	PBBH0004	No. 4 busbar plates at all heights	Main distribution systems
1	PBBV0008	No. 8 busbar plates vertical side	Main distribution systems
2	PSHW5061	Segregation for Form 2a-3a T7 withdrawable H=500mm W=600mm	Segregations
2	PSVS0055	Segregations for horizontal breakers terminals H=500mm D=700mm	Segregations
2	PCVS5060	Cubicles Form 4b T7 withdrawable H=500mm W=600mm	Segregations
5	PCBS2060	Blind Compartment H=200mm W=600mm	Segregations
5	PPBS0200	Lateral segregation for blind compartment H=200mm	Segregations
1	PSVS0207	Rear segregation for blind compartment H=200mm	Segregations
1	PCBS3060	Blind compartment H=300mm W=600mm	Segregations
1	PPBS0300	Lateral segregation for blind compartment H=300mm	Segregations
1	PSVS0307	Rear segregation for blind compartment H=300mm	Segregations
2	PPVS2250	N.2 lateral cell segregations H=250mm	Segregations
2	PSVS2570	Segregation for horizontal breakers terminals H=250mm D=700mm	Segregations
2	PCVS1256	Cubicles P1 for breakers kit H=250mm W=600mm	Segregations
2	PRVS1061	Rear segregation for structure busbars side H=1000mm W=600mm	Segregations
1	PPVS2600	No.2 lateral cell segregations H=600mm	Segregations
1	PSVW6062	Segregation 2a-3a E2.2 withdrawable H=600mm W=600mm	Segregations
1	PSHW6072	Horizontal segregation 3b E2.2 withdrawable W=600mm D=700mm	Segregations
1	PRVS3060	Rear segregation H=300MM W=600MM for structure without intermediate upright	Segregations
2	PMCS3070	No.2 lateral connection modules H=300mm D=700mm	Segregations
2	PBMC0002	No.2 fixing brackets for connection modules	Segregations
2	PLVS4072	Rear lateral segregation for compartment H=400MM D=700MM for structure with rear intermediate upright	Segregations
1	PRVS7060	Segregazione verticale posteriore H=700MM W=600MM for structure without rear intermediate upright	Segregations
1	PRVS1060	Segregazione verticale posteriore H=1000MM W=600MM for structure without rear intermediate upright	Segregations
7	PSHS1906	Horizontal shelf W=600mm	Segregations

Chapter 8

Overall dimensions

8-2 Frame

8-3 Internal cable compartment

8-3 Intermediate upright

8-3 Adjacent structures

8-4 External covers

8-7 Internal kit


8-11 Main distribution systems

8-16 Segregations


Overall dimensions

Frame

Front



Side



Height measurements (mm)

A	A1
1913	1804
2113	2004


Width measurements (mm)

B	B1	B2	B3	B4	B5	B6	B7	B8
349	254	148	287	225	194	271	348	226
399	304	198	337	375	244	321	398	276
499	404	298	437	475	344	421	498	376
599	504	398	537	575	444	521	598	476
699	604	498	637	675	544	621	698	576
849	754	648	787	825	694	771	848	726
899	804	698	837	875	744	821	898	776
1099	1004	898	1037	1075	944	1021	1098	976
1349	1254	1148	1287	1325	1194	1271	1348	1226



Depth measurements (mm)

C	C1	C2	C3	C4	C5	C6	C7	C8
299	204	98	237	275	144	221	298	176
399	304	198	337	375	244	321	398	276
599	504	398	537	575	444	521	598	476
799	704	598	737	775	644	721	798	676
999	904	798	937	975	844	921	998	876
1349	1250	1148	1287	1325	1194	1271	1348	1226

Bottom



Fixing on floor




The measurements are given in millimeters

Overall dimensions

Internal cable compartment


Front



A	A1	D	D1
699	604	200	404
899	804	200	604
		400	404
1099	1004	200	804
		400	604


Intermediate upright

Side




Overall dimensions for several adjacent structures

Front



Side



Total width calculation


1- add 1mm to the width of the columns ($B+1$) + ($B+1$)....

2- add 17mm for the 2 side panels ($8.5+8.5=17$ mm)

3- subtract 1mm from the total (-1mm)

Example

$$(699+1) + (899+1) + (699+1) + 17 - 1 = 2.316$$



Total depth calculation

Add 48mm to the depth of the structure (C), corresponding to the front and rear covers.


C (depth of the structure) + 48mm (front and rear covers including handle)

The measurements are given in millimeters

Overall dimensions

External covers

Glass doors




The measurements are given in millimeters

Overall dimensions

External covers

Blind doors




The measurements are given in millimeters

Overall dimensions

External covers

Rear, side panels




The measurements are given in millimeters

Overall dimensions

Internal kit


Mounting Plates

Height 150mm



A	B	C
363	344	146
563	544	
763	744	

Height ≥ 200mm




A	B	C
381	347	196
581	547	
781	747	
981	947	
381	347	246
581	547	
781	747	
981	947	
381	347	296
581	547	
781	747	
981	947	
381	347	346
581	547	
781	747	
981	947	

A	B	C
381	347	396
581	547	
781	747	
981	947	
381	347	446
581	547	
781	747	
981	947	
381	347	496
581	547	
781	747	
981	947	
381	347	546
581	547	
781	747	
981	947	
381	347	596
581	547	
781	747	
981	947	

Overall dimensions


Internal Kit

Flat blind panels




A	B
48	343
98	543
148	743
198	943
248	
298	
398	
498	
598	

Ventilated panels



A	B
48	343
98	543
148	743
198	943
248	
298	
398	
498	
598	

Panels Modular DIN Rail




The measurements are given in millimeters

Overall dimensions

Internal kit


Panels for square measuring instruments

Panel 2 instruments



A	B	C
198	543	68
		92
198	743	68
		92

Panel 4 instruments




A	B	C	D	E	F
198	543	68	96.5	100	150
198	743	68	196.5	100	150
			92	121.5	150
				200	

Recessed blind panels



A	B	C
198	343	30
		80
398		30
598		30
198	543	30
		80
398		30
598		30
198	743	30
		80
398		30
598		30
198	943	80

Panels for ATS 022 devices mounting on DIN Rail *



A	B	C
298	58.7	123-223-323
		97
		123-223-323
		343-543-743



* Not available for sale

The measurements are given in millimeters

Overall dimensions

Internal kit

Useful space inside the switchgear



To find the useful space available for the installation of the busbars, according to depth of the structure, subtract the depth of the breaker (A or B) depending on the version shown in the following table.

Tmax T - Tmax XT - Emax 2 E1.2

Execution	F		F - I		F - I-MO		F - MO		F - RC		F - RHD	
	Front (A)	Rear (B)	Front (A)	Rear (B)	Front (A)	Rear (B)	Front (A)	Rear (B)	Front (A)	Rear (B)	Front (A)	Rear (B)
Circuit-breakers Depth circuit breaker A (mm)												
XT1-XT3	74	179	139	179	237*	277*	172	277	74	179	108	213
XT2-XT4	86	191	151	191	237*	277*	172	277	86	191	120	225
T4	107	212	172	212	287*	327*	222*	327*	107	212	140,5	245,5
T5	107	242	172	242	287*	357*	222*	357*	107	242	140,5	275,5
T6	107	180	172	180	287*	295*	222*	295*	107	180	140,5	213,5
T7	171	230	171	230	171	230	171	230	171	230	184	243
E1.2	157	216	157	216								
Execution	P (A)	(B)	P - I (A)	(B)	P - I-MO (A)	(B)	P - MO (A)	(B)	P - RC (A)	(B)	P - RHD (A)	(B)
XT1	124	204,5	189	204,5	287*	302,5*	222*	302,5*	158	238,5		
XT2	136	216,9	201*	216,9*	287*	302,9*	222*	302,9*	170	250,9		
XT3	124	206,9	189	206,9	287*	304,9*	222*	304,9*	158	240,9		
XT4	136	218,9	201*	218,9*	287*	304,9*	222*	304,9*	170	252,9		
T4												
T5 ⁽¹⁾	157	231,25	222*	231,25*	337*	346,25*	272*	346,25*	190,5	264,75		
T5 ⁽²⁾	157	231,25					272*	346,25*	190,5	264,75		
Execution	W (A)	(B)	W - I (A)	(B)	W - I-MO (A)	(B)	W - MO (A)	(B)	W - RC (A)	(B)	W - RHD (A)	(B)
XT2	170	250,9	235*	250,9*	287*	302,9	222*	302,9*	170	250,9		
XT4	170	252,9	235*	252,9*	287*	304,9	222*	304,9*	170	252,9		
T4												
T5 ⁽¹⁾	190,5	264,75	255,5*	264,75*	337*	346,25*	272*	346,25*	190,5	264,75		
T5 ⁽²⁾	190,5	264,75					272*	346,25*	190,5	264,75		
T6	190,5	271	255,5*	271*	337*	352,5*	272*	352,5*	190,5	271		
T7	251	297	251*	297*	251*	297*	251*	297*	251*	297*		
E1.2	251	300	251	300								

⁽¹⁾ Tmax T5 400A ⁽²⁾ Tmax T5 630A *Breakers with recessed mounting plate.

Emax 2

Accessorized or not accessorized, only rear terminals.

Execution	F	W
Circuit-breakers Depth circuit breaker A (mm)		
E2.2	291	405
E4.2	291	405
E6.2	291	405



Key:		
F	fixed	P - RHD plug-in with Direct Rotary Handle
F - I	fixed interlocked	W withdrawable
F - I-MO	fixed interlocked motor-operated	W - I withdrawable interlocked
F - MO	fixed motor-operated	W - I-MO withdrawable interlocked motor-operated
F - RC	fixed with residual current	W - MO withdrawable motor-operated
F - RHD	fixed with Direct Rotary Handle	W - RC withdrawable with residual current
F & F - I	fixed and fixed interlocked	W - RHD withdrawable with Direct Rotary Handle
P	plug-in	W & W - I withdrawable and withdrawable interlocked
P - I	plug-in interlocked	
P - I-MO	plug-in interlocked motor-operated	
P - MO	plug-in motor-operated	
P - RC	plug-in with residual current	

The measurements are given in millimeters

Overall dimensions

Internal kit

Blind mounting plates





Main distribution systems

Shaped profile busbars



PBSC0400

In 400A





PBSC0630

In 630A





PBSC0800

In 800A





PBSC1000

In 1000A



PBSC1250

In 1250A



The measurements are given in millimeters


Overall dimensions

Main distribution systems

Shaped profile busbars



PBSC1600

In 1600A





PBSC2500

In 2500A



PBSC2000


In 2000A



Overall dimensions

Main distribution systems

Flat busbars




Copper busbars

Code	A	B
PBFC2005	5	20
PBFC2505	5	25
PBFC4005	10	30
PBFC8005	5	40
PBFC3205	5	32

Code	A	B
PBFC1005	5	100
PBFC3010	10	30
PBFC5005	5	50
PBFC6305	5	63

Code	A	B
PBFC1001	10	100
PBFC1201	10	120
PBFC1601	10	160
PBFC2001	10	200
PBFC4010	10	40
PBFC5010	10	50
PBFC6010	10	60
PBFC8010	10	80



Cuponal busbars

Code	A	B
PBFA2005	5	20
PBFA2505	5	25
PBFA3005	5	30
PBFA4005	5	40
PBFA5005	5	50
PBFA6005	5	60
PBFA8005	5	80
PBFA4010	10	40
PBFA5010	10	50
PBFA7510	10	75
PBFA8010	10	80
PBFA1001	10	100
PBFA1201	10	120


The measurements are given in millimeters

Overall dimensions


Main distribution system

Linear busbar rails



PBHB1125




PBHB2145



PBHB3121



Distance between insulating supports



Code	L (mm)	No.	A	B	C	D
PBHB1125	50	3	0	188	354	504
		4		238	354	504
PBHB2145	75	3		438	554	704
		4		438	554	704
PBHB3121	100	3		438	554	704
		4		438	554	704
PBHB1125	50	3	12.5	238	354	504
		4		438	554	704
PBHB2145	75	3		438	554	704
		4		438	554	704
PBHB3121	100	3		438	554	704
		4		638	654	904
PBHB1125	50	3	25	238	354	504
		4		438	554	704
PBHB2145	75	3		438	554	704
		4		438	554	704
PBHB3121	100	3		438	554	704
		4		638	654	904


Code	L (mm)	No.	A	B	C	D
PBHB1125	50	3	3	37.5	438	554
		4			438	554
PBHB2145	75	3	3	438	554	704
		4			638	654
PBHB3121	100	3	3	438	554	704
		4			838	654
PBHB1125	50	3	50	438	554	704
		4			438	554
PBHB2145	75	3	3	438	554	704
		4			638	654
PBHB3121	100	3	3	438	554	704
		4			638	654

The measurements are given in millimeters

Overall dimensions


Main distribution systems

Scaled busbar rails




Tie rods


Nylon tie rods



Stainless steel tie rods



Crosspieces for insulating supports



Galvanized sheet metal	Stainless steel	A
PCRM0188		88
PCRM0238		238
PCRM0288		288
PCRM0338	PCRS0338	338
PCRM0388	PCRS0388	388
PCRM0438	PCRS0438	438
PCRM0488		488
PCRM0538		538
PCRM0588	PCRS0338	588

Galvanized sheet metal	Stainless steel	A
PCRM0638	PCRS0388	638
PCRM0688	PCRS0438	688
PCRM0738		738
PCRM0788		788
PCRM0888	PCRS0588	888
PCRM0988	PCRS0638	988
PCRM1238		1238
PCRM2013		2013

The measurements are given in millimeters


Overall dimensions

Segregations

Form 4b segregations


Segregations rear mounting positions

Assembly position P0




A	B	C
599	244	310
799	244	510
999	244	710

Assembly position P1




A	B	C
599	364	190
799	364	390
999	364	590

Assembly position P2



A	B	C
599	434	120
799	434	320
999	434	520



Screws selection for Emax anchoring plates

Screw diameter (mm)	Anchoring plates for Emax breakers (Nm)
M4	2.6÷2.9
M5	5.1÷5.7
M6	8.9÷9.9
M8	21.8÷24.2
M10	43.2÷48
M12	74.3÷82.6
M14	117÷130
M16	177.5÷197.3
M18	245.6÷272.9

Nm = Newton per meter

Chapter 9

List of codes

List of codes

Code	Page	Weight KG
06652	4-41	0,6
07241	4-42	0,57
07242	4-42	0,697
07243	4-42	0,92
07244	4-42	1,16
07245	4-42	1,694
07246	4-42	2,79
07247	4-42	3,41
07855	4-41	0,7
1SEP407792R0001	3-91	0,02
1SEP407792R0001	3-91	0,02
1SEP407792R0002	3-91	0,03
1SEP407792R0002	3-91	0,03
1SEP407792R0003	3-91	0,04
1SEP407815R0001	3-91	0,04
1SEP407815R0001	3-91	0,04
1SEP407815R0002	3-91	0,06
1SEP407951R0001	3-91	0,4
1SEP407951R0001	3-91	0,4
1SEP407951R0002	3-91	0,5
1SEP407955R0001	3-91	0,055
1SEP407955R0001	3-91	0,055
1SL9037A00	4-41	0,372
1SL9816A00	4-41	0,755
1SL9817A00	4-41	0,785
1SL9818A00	4-41	0,97
1SL9819A00	4-41	1,15
1SL9820A00	4-41	1,516
1SL9836A00	4-41	1,033
1SL9838A00	4-41	1,25
1SL9839A00	4-41	1,43
1SL9840A00	4-41	1,795
1SL9841A00	4-41	2,44
1SL9842A00	4-41	2,85
1SL9860A00	4-41	1,094
1SL9861A00	4-41	1,126
1SL9862A00	4-41	1,31
1SL9863A00	4-41	1,49
1SL9864A00	4-41	1,856
1SL9865A00	4-41	2,5
1SL9866A00	4-41	2,91
1SL9904A00	4-41	0,309
1STQ005299B0000	3-91	
1STQ005300B0000	3-91	
1STQ005301B0000	3-91	
1STQ005302B0000	3-91	
1STQ005303B0000	3-91	
1STQ005304B0000	3-91	
1STQ005305B0000	3-91	

Code	Page	Weight KG
1STQ005306B0000	3-91	
1STQ005569B0000	2-39	
1STQ005570B0000	2-39	
1STQ005571B0000	2-39	
1STQ005572B0000	2-39	
1STQ005573B0000	2-41	
1STQ005574B0000	2-41	
1STQ005575B0000	2-41	
1STQ005576B0000	2-41	
1STQ005577B0000	2-41	
1STQ005578B0000	2-41	
1STQ005579B0000	2-40	
1STQ005580B0000	2-40	
1STQ005581B0000	2-40	
1STQ005582B0000	2-40	
1STQ005583B0000	2-40	
1STQ005584B0000	2-40	
1STQ005590B0000	2-27	0,240
1STQ005590B0000	2-27	0,2350
1STQ005590B0000	2-40	
1STQ005591B0000	2-27	
1STQ005591B0000	2-27	
1STQ005591B0000	2-40	
1STQ005592B0000	2-27	
1STQ005592B0000	2-40	
1STQ005593B0000	2-27	
1STQ005593B0000	2-40	
1STQ005594B0000	2-27	
1STQ005594B0000	2-27	
1STQ005594B0000	2-40	
1STQ005595B0000	2-40	
1STQ005605B0000	2-41	
1STQ005606B0000	2-41	
1STQ005607B0000	2-41	
1STQ005608B0000	2-41	
1STQ005609B0000	2-41	
1STQ005610B0000	2-41	
1STQ005833B0000	2-39	
1STQ005834B0000	2-39	
1STQ008126A0000	2-42	0,240
1STQ008128A0000	2-42	0,2350
2GCA286141A0050	6-43	
2GCA291720A0050	6-43	
2GCA291721A0050	6-43	
2GCA291722A0050	6-43	
2GCA291864A0050	6-43	0,0780
2GCA291880A0050	6-43	0,0780

Code	Page	Weight KG
2GCA292040A0050	6-43	0,340
2GCA292820A0050	6-43	0,290
2GCA294983A0050	6-43	0,010
2GCA294984A0050	6-43	0,250
2GCA294985A0050	6-43	0,250
2GCA294986A0050	6-43	0,310
2GCA294987A0050	6-43	1,030
2GCA297400A0045	6-42	0,250
2GCA297401A0045	6-42	3,440
2GCA297402A0045	6-42	3,440
2GCA297403A0045	6-42	0,04
2GCA297404A0045	6-42	0,020
2GCA297405A0045	6-42	0,020
2GCA297406A0045	6-42	0,020
2GCA297407A0045	6-42	
2GCA297408A0045	6-42	
2GCA297409A0045	6-42	
2GCA297410A0045	6-42	
AA1560	2-42	0,020
AA1570	2-42	0,030
AA6200	2-42	0,020
AA8004	2-42	0,010
AD1009	3-97	0,0780
AD1009	3-98	0,0780
AD1037	3-97	0,340
AD1056	4-44	0,290
AD1058	2-42	0,010
AD1064	4-44	0,250
AD1071	4-44	0,250
AD1072	4-44	0,310
AD1077	4-44	1,030
AD1083	4-47	0,250
AD1086	3-98	3,440
AD1086	3-98	3,440
AD1101	3-98	0,04
AD1102	3-98	0,020
AD1103	3-98	0,020
AD1104	3-98	0,020
AD1600	3-98	0,240
AD1800	3-98	0,350
AD3301	3-99	0,150
AD3302	3-99	0,150
AD3303	3-99	0,150
AD3304	3-99	0,150
AD3305	3-99	0,150
AD3306	3-99	0,150
AD3307	3-99	0,150
AD3308	3-99	0,150
BF1602	4-45	2,650

List of codes

Code	Page	Weight KG
BF2502	4-45	4,120
BF4002	4-45	6,4
BF4012	4-45	6,370
BF6302	4-45	12,250
BF8002	4-45	18,720
BS3250	4-45	1,550
BS5050	4-45	1,750
BS6350	4-45	2,20
ED0001	4-39	0,210
ED0002	4-39	0,270
ED0003	4-39	0,280
ED0004	4-39	0,280
ED0025	4-40	1,87
ED0026	4-40	1,3
ED2183	4-38	3,040
ED2191	4-38	4,020
ED2209	4-38	1,420
ED2217	4-39	0,15
ED2225	4-39	0,16
ED2233	4-39	0,18
ED2241	4-39	0,13
ED2258	4-39	0,2
ED2266	4-39	0,22
ED2274	4-39	0,22
ED2282	4-39	0,18
ED2290	4-39	0,25
ED2308	4-39	0,26
ED2316	4-39	0,28
ED2324	4-39	0,23
ED2332	4-39	0,24
ED2340	4-39	0,22
ED2357	4-39	0,2
ED2365	4-39	0,26
ED2373	4-39	0,09
ED2373	4-39	0,09
ED2373	4-39	0,09
ED2381	4-39	0,25
ED2399	4-39	0,23
ED2407	4-39	0,25
ED2531	4-38	0,08
ED2549	4-38	0,08
ED2550	4-38	0,065
ED2551	4-38	0,125
ED2552	4-38	0,12
ED2553	4-38	0,12
ED2554	4-38	0,12
ED2556	4-38	0,08
ED2557	4-38	0,1
ED2558	4-38	0,1

Code	Page	Weight KG
ED2559	4-38	0,1
ED2560	4-38	0,1
ED2564	4-38	0,08
ED2572	4-38	0,08
ED2590	4-38	0,08
ED2598	4-38	0,09
ED2606	4-38	0,09
ED2654	4-38	0,06
ED2662	4-38	0,06
ED2670	4-38	0,08
ED2720	4-38	0,09
ED2738	4-38	0,09
ED2746	4-38	0,1
ED2753	4-38	0,09
ED2845	4-39	0,05
ED2852	4-39	0,05
ED2894	4-38	0,07
ED2902	4-38	0,06
ED2910	4-38	0,07
ED2928	4-38	0,07
ED2936	4-39	0,03
ED2944	4-40	0,35
ED2951	4-40	0,54
ED2961	4-40	0,390
ED2962	4-40	0,1
ED2969	4-40	0,74
ED2977	4-40	1,06
ED2985	4-40	0,17
ED2993	4-40	0,25
ED3009	4-40	0,38
ED3017	4-40	0,46
ED3025	4-40	0,66
ED3033	4-40	0,08
ED3041	4-40	0,07
ED3058	4-40	0,06
ED3066	4-40	0,08
ED3082	4-40	0,24
ED3090	4-40	0,55
ED3101	4-40	0,290
ED3102	4-40	0,290
ED3103	4-40	0,290
ED3104	4-40	0,290
ED3108	4-40	0,05
ED3116	4-40	0,05
ED3124	4-40	0,08
ED3132	4-40	0,32
ED3272	4-40	0,1
ED3280	4-40	0,1
ED3298	4-40	0,09

Code	Page	Weight KG
ED3355	4-40	0,06
ED3363	4-40	0,08
ED3371	4-40	0,09
ED3405	4-40	0,57
ED3413	4-40	0,78
ED3439	4-40	1,27
EN0101K	6-41	0,070
EN0325K	6-41	0,980
EN0480K	6-41	5,30
EN0482K	6-41	5,30
EN0484K	6-41	2,1
EN0485K	6-41	2,10
EV0036	3-97	0,20
EV0037	3-97	0,350
EV0042	3-98	0,250
EV0103	2-44	0,50
EV0104	2-44	0,50
EV0114	2-36	0,95
EV0116	2-36	0,95
EV0117	2-36	0,75
EV0119	2-36	0,2
EV0121	2-36	0,2
EV0123	2-36	0,2
EV0124	2-36	0,2
EV0125	2-36	0,125
EV0126	2-36	0,125
EV0127	2-36	0,125
EV1008	2-42	0,040
EV1036	2-42	0,030
EV1037	2-42	0,030
EV1039	2-42	0,030
EV1050	4-43	6,740
EV1051	4-43	0,90
EV1056	4-43	0,3080
EV1058	4-43	0,4890
EV1075K	2-42	0,20
EV1090	4-43	0,4560
EV1091	4-43	0,860
EV1092	4-43	0,540
EV1093	4-43	0,540
EV1100	2-44	1,130
EV1101	2-44	1,250
EV1110	3-97	2,690
EV1110	4-44	2,690
EV1111	3-97	0,670
EV1112	3-97	2,690
EV1113	4-44	0,1180
EV1119	4-43	3,530
EV1120	4-43	4,410

List of codes

Code	Page	Weight KG	Code	Page	Weight KG	Code	Page	Weight KG
EV1121	4-43	8,670	PBFC4010	4-30	6,50	PBSC1250	4-31	8,50
EV1122	4-43	2,40	PBFC5005	4-30	3,50	PBSC1600	4-31	11,970
EV1123	4-43	2,440	PBFC5010	4-30	8	PBSC2000	4-31	15,040
EV1124	4-43	2,710	PBFC6010	4-30	9,50	PBSC2500	4-31	19,6
EV1125	4-43	2,710	PBFC6305	4-30	4,460	PBTT4631	4-32	2,40
EV1135	3-99	0,230	PBFC8005	4-30	5,850	PBTT5631	4-32	3,60
EV1136	3-99	0,160	PBFC8010	4-30	12,50	PBTT6631	4-32	6,40
EV1137	3-99	0,230	PBGT4738	4-33	1,40	PBTT7631	4-32	12,720
EV1150	4-47	0,090	PBGT5738	4-33	2,20	PBTT7631	4-32	12,720
EV1151	4-47	0,090	PBGX1738	4-33	1	PBTX1631	4-32	1,60
EV1152	4-47	0,090	PBGX2738	4-33	0,980	PBTX2631	4-32	1,60
EV1153	4-47	0,090	PBGX3738	4-33	1,09	PBTX3631	4-32	1,780
EV1154	4-47	0,090	PBGX4738	4-33	1,090	PBTX4631	4-32	1,80
EV1155	4-47	0,010	PBHB1125	4-34	1,0050	PBUF0002	4-38	1,540
EV1156	4-47	0,060	PBHB1125	4-34	1,0050	PBUF0002	4-40	1,540
EV2110	3-97	0,5480	PBHB2145	4-34	1,50	PBWF0002	2-44	0,0910
EV2112	3-97	0,5480	PBHB3121	4-34	2	PBWP1030	2-27	4,80
PBBE0062	3-90	1,7	PBHS1125	4-34	0,250	PBWP1030	6-14	4,80
PBBE0712	3-90	4,35	PBK0002	2-43	1,66	PBWP1050	2-27	7,30
PBBE2242	3-90	8,7	PBMC0001	6-8	0,25	PBWP1050	6-14	7,30
PBBT0008	4-35	0,790	PBMC0002	4-45	0,250	PBWP1050	6-31	7,30
PBBU0008	4-34	0,8	PBMC0002	5-51	0,250	PBWP1070	2-27	9,60
PBBV0008	4-35	0,870	PBPT4631	4-32	2,080	PBWP1070	6-14	9,60
PBCB0002	4-34	0,40	PBPT4738	4-33	1,70	PBWP1070	6-31	9,60
PBCM0004	6-8	0,648	PBPT5631	4-32	3,160	PBWP1090	2-27	12,120
PBFA1001	4-31	6,470	PBPT5738	4-33	2,60	PBWP1090	6-14	12,120
PBFA1201	4-31	7,660	PBPT6738	4-33	4,340	PBWP1090	6-31	12,120
PBFA2005	4-31	0,740	PBPX1631	4-32	1,320	PBWP1230	6-14	3,505
PBFA2505	4-31	0,850	PBPX1738	4-33	1,150	PBWP1250	6-14	9,6
PBFA3005	4-31	1,020	PBPX2631	4-32	14,80	PBWP1270	6-14	13
PBFA4005	4-31	1,330	PBPX2738	4-33	1,180	PBWP1290	2-27	9,030
PBFA4010	4-31	2,520	PBPX3631	4-32	1,60	PBWP1290	6-14	9,030
PBFA5005	4-31	1,740	PBPX3738	4-33	1,370	PBWP2520	6-14	1,2
PBFA5010	4-31	3,20	PBPX4631	4-32	1,560	PBWP2530	6-14	1,4
PBFA6005	4-31	2,130	PBPX4738	4-33	1,30	PBWP2550	6-14	2,18
PBFA7510	4-31	4,880	PBRB0004	2-18	0,560	PBWP2570	6-14	2,96
PBFA8005	4-31	2,730	PBRF3453	4-27	0,320	PBWP2590	6-14	8,8
PBFA8010	4-31	5,080	PBRL0002	2-43	1,490	PBWP3020	2-27	1,310
PBFC0160	4-45	2,660	PBRN0002	4-35	0,4	PBWP3030	2-27	1,790
PBFC1001	4-30	15,50	PBRP0002	4-35	0,5	PBWP3050	2-27	2,660
PBFC1005	4-30	7,260	PBRP1040	3-96	0,590	PBWP3050	6-14	2,660
PBFC1201	4-30	19	PBRP2040	3-96	1,060	PBWP3070	2-27	3,430
PBFC1601	4-30	25	PBRP3040	3-96	1,480	PBWP3090	2-27	4,440
PBFC2001	4-30	31,50	PBRP6040	3-96	2,780	PBWP4020	2-27	1,640
PBFC2005	4-30	1,50	PBRR6040	3-96	9,15	PBWP4030	2-27	2,150
PBFC2505	4-30	1,860	PBSC0400	4-31	2,590	PBWP4050	2-27	3,270
PBFC3010	4-30	4,50	PBSC0630	4-31	3,280	PBWP4070	2-27	4,570
PBFC3205	4-30	2,380	PBSC0800	4-31	4,810	PBWP4090	2-27	5,360
PBFC4005	4-30	3	PBSC1000	4-31	7,80	PBWP5020	6-14	1,9

List of codes

Code	Page	Weight KG	Code	Page	Weight KG	Code	Page	Weight KG
PBWP5050	6-14	3,79	PCCM0200	2-16	1	PCFM1000	2-39	7,070
PBWP5070	6-14	5,06	PCCM0200	3-93	1	PCFM1000	6-9	7,070
PBWP5090	6-14	3,2	PCCM0300	2-16	1,3	PCFM1000	6-27	7,070
PBWP6020	2-27	2,260	PCCM0300	2-16	1,3	PCFM1250	2-14	9,50
PBWP6030	2-27	2,990	PCCM0300	3-93	1,3	PCFM1250	2-14	9,50
PBWP6050	2-27	4,650	PCCM0400	2-16	1,60	PCFM1250	2-39	9,50
PBWP6050	6-31	4,650	PCCM0500	2-16	1,9	PCFM1250	2-39	9,50
PBWP6070	2-27	3,36	PCCM0500	3-93	1,9	PCFM1250	6-9	9,50
PBWP6070	6-31	3,36	PCCM0600	2-16	2,20	PCFS0200	2-14	1,7
PBWP6090	2-27	8,120	PCCM0700	2-16	2,540	PCFS0300	2-14	2,50
PBWP6090	6-31	8,120	PCCM0700	3-93	2,540	PCFS0300	2-39	2,50
PBWP7520	6-14	2,66	PCCM0800	2-16	2,60	PCFS0400	2-14	3
PBWP7530	6-14	3,71	PCCM0900	2-16	3,080	PCFS0400	2-39	3
PBWP7550	6-14	5,36	PCCM0900	3-93	3,080	PCFS0600	2-14	4
PBWP7570	6-14	7,53	PCCM1000	2-16	3,420	PCFS0600	2-39	4
PBWP7590	6-14	9,6	PCCM2010	6-8	1,4	PCFS0700	2-14	5
PBWP8020	2-27	2,980	PCCM2012	6-8	1,6	PCFS0800	2-14	5,40
PBWP8030	2-27	3,860	PCCM2025	6-8	0,96	PCFS0800	2-39	5,40
PBWP8050	2-27	6	PCCM2050	6-8	1,38	PCFS0900	2-14	6
PBWP8050	6-31	6	PCCM2075	6-8	1,07	PCFS1000	2-14	7
PBWP8070	2-27	8,310	PCCS0700	2-16	2,410	PCFS1000	2-39	7
PBWP8070	6-31	8,310	PCCS0900	2-16	3,290	PCFS1250	2-14	8
PBWP8090	2-27	10,250	PCFM0200	2-14	1,80	PCFS1250	2-14	8
PBWP8090	6-31	10,250	PCFM0200	6-9	1,80	PCFS1250	2-39	8
PCBS1010	5-26	2,5250	PCFM0250	6-9	2,08	PCFS1250	2-39	8
PCBS1012	5-26	3,395	PCFM0300	2-14	2,3310	PCIS0500	5-34	0,880
PCBS1040	5-26	1,120	PCFM0300	2-14	2,3310	PCIS0500	6-20	0,880
PCBS1060	5-26	1,50	PCFM0300	2-39	2,3310	PCIS0700	5-34	1,260
PCBS1080	5-26	2,0750	PCFM0300	6-9	2,3310	PCIS0900	5-34	1,490
PCBS1510	5-26	3,170	PCFM0400	2-14	3,150	PCKI0250	6-20	0,25
PCBS1540	5-26	1,440	PCFM0400	2-39	3,150	PCKI0300	4-35	1,350
PCBS1560	5-26	1,990	PCFM0500	2-14	3,6150	PCKI0400	4-35	1,530
PCBS1580	5-26	2,620	PCFM0500	6-9	3,6150	PCKI0600	4-35	2,040
PCBS2010	5-26	3,840	PCFM0500	6-9	3,6150	PCKI0750	6-20	0,6
PCBS2040	5-26	1,1650	PCFM0500	6-27	3,6150	PCKI0800	4-35	2,820
PCBS2060	5-26	2,410	PCFM0600	2-14	4,290	PCKI1000	4-35	3,320
PCBS2080	5-26	3,2250	PCFM0600	2-39	4,290	PCKI1000	6-20	3,320
PCBS2510	5-26	4,5550	PCFM0600	6-27	4,290	PCKI1250	4-35	4,050
PCBS2540	5-26	2,1650	PCFM0700	2-14	4,9530	PCKI1250	6-20	4,050
PCBS2560	5-26	2,860	PCFM0700	6-9	4,9530	PCNL0050	6-26	2,23
PCBS2580	5-26	3,7150	PCFM0700	6-27	4,9530	PCNL0100	6-26	3,17
PCBS3010	5-26	5,1550	PCFM0750	6-9	5,11	PCPA0004	2-17	1
PCBS3040	5-26	2,4950	PCFM0800	2-14	5,580	PCPT6738	4-33	8
PCBS3060	5-26	3,220	PCFM0800	2-39	5,580	PCRM0188	4-29	0,4440
PCBS3080	5-26	4,2950	PCFM0800	6-27	5,580	PCRM0238	4-29	0,570
PCBS5010	5-26	1,8750	PCFM0900	2-14	6,3350	PCRM0288	4-29	0,6880
PCBS5040	5-26	0,760	PCFM0900	6-9	6,3350	PCRM0288	4-29	0,6880
PCBS5060	5-26	1,080	PCFM0900	6-27	6,3350	PCRM0338	4-29	0,8050
PCBS5080	5-26	1,50	PCFM1000	2-14	7,070	PCRM0388	4-29	0,920

List of codes

Code	Page	Weight KG
PCRM0438	4-29	1,0380
PCRM0488	4-29	1,1660
PCRM0538	4-29	1,30
PCRM0588	4-29	1,40
PCRM0638	4-29	1,5540
PCRM0688	4-29	1,6340
PCRM0738	4-29	1,7530
PCRM0788	4-29	1,880
PCRM0888	4-29	2,1380
PCRM0988	4-29	2,350
PCRM1238	4-29	2,9940
PCRM1788	4-29	4,322
PCRM1988	4-29	4,805
PCRM2013	4-29	5
PCRS0338	4-30	0,9650
PCRS0388	4-30	1,1350
PCRS0438	4-30	1,2780
PCRS0438	4-30	1,2780
PCRS0588	4-30	1,7020
PCRS0638	4-30	1,850
PCRS0788	4-30	2,3170
PCRS0888	4-30	2,5680
PCRS0988	4-30	2,930
PCRS1238	4-30	3,5950
PCRS2013	4-30	5,8260
PCSS0024	2-44	0,1530
PCTG1810	6-8	3,82
PCTG1812	6-8	5,06
PCTG1825	6-8	3,65
PCTG1850	6-8	3,25
PCTG1875	6-8	4,05
PCTG2010	6-8	4,04
PCTG2012	6-8	5,08
PCTG2025	6-8	3,86
PCTG2050	6-8	3,47
PCTG2075	6-8	3,70
PCTT6631	4-32	11
PCTT7631	4-32	20
PCTT7631	4-32	20
PCVS0204	5-49	0,320
PCVS0206	5-49	0,420
PCVS0208	5-49	0,480
PCVS0254	5-49	0,40
PCVS0256	5-49	0,510
PCVS0258	5-49	6,610
PCVS0304	5-49	0,490
PCVS0306	5-49	0,620
PCVS0308	5-49	0,840
PCVS0354	5-49	0,560

Code	Page	Weight KG
PCVS0356	5-49	0,710
PCVS0358	5-49	0,840
PCVS0404	5-49	0,650
PCVS0406	5-49	0,80
PCVS0408	5-49	0,970
PCVS0504	5-49	0,80
PCVS0506	5-49	0,990
PCVS0508	5-49	1,190
PCVS0604	5-49	0,9450
PCVS0606	5-49	1,120
PCVS0608	5-49	1,4250
PCVS1204	5-49	1,120
PCVS1206	5-49	1,20
PCVS1208	5-49	1,460
PCVS1254	5-49	1,060
PCVS1256	5-49	1,4150
PCVS1258	5-49	1,680
PCVS1304	5-49	1,320
PCVS1306	5-49	1,570
PCVS1308	5-49	1,940
PCVS1354	5-49	1,510
PCVS1356	5-49	1,780
PCVS1358	5-49	2,110
PCVS1404	5-49	1,640
PCVS1406	5-49	1,940
PCVS1408	5-49	2,290
PCVS1504	5-49	1,950
PCVS1506	5-49	2,30
PCVS1508	5-49	2,680
PCVS1604	5-49	2,270
PCVS1606	5-49	2,6350
PCVS1608	5-49	3,070
PCVS2204	5-50	1,270
PCVS2206	5-50	1,5850
PCVS2208	5-50	1,870
PCVS2254	5-50	1,490
PCVS2256	5-50	1,80
PCVS2258	5-50	2,110
PCVS2304	5-50	1,690
PCVS2306	5-50	2,020
PCVS2308	5-50	2,350
PCVS2354	5-50	1,90
PCVS2356	5-50	2,250
PCVS2358	5-50	2,60
PCVS2404	5-50	2,050
PCVS2406	5-50	2,450
PCVS2408	5-50	2,820
PCVS2504	5-50	2,410
PCVS2506	5-50	2,850

Code	Page	Weight KG
PCVS2508	5-50	3,260
PCVS2604	5-50	2,850
PCVS2606	5-50	3,310
PCVS2608	5-50	3,790
PDCB1820	2-35	5
PDCB1820	5-45	5
PDCB1830	2-35	8
PDCB1830	5-46	8
PDCB1840	2-35	9
PDCB1840	5-45	9
PDCB1844	2-35	10,50
PDCB1844	5-46	10,50
PDCB2020	2-35	5,6350
PDCB2020	5-45	5,6350
PDCB2030	2-35	9
PDCB2030	5-46	9
PDCB2040	2-35	10
PDCB2040	5-45	10
PDCB2044	2-35	11,50
PDCB2044	5-46	11,50
PDFO200	6-8	0,553
PDFO300	6-8	0,83
PDFO500	6-8	1,2
PDFO700	6-8	1,811
PDFO900	6-8	2,8
PDGT4738	4-33	1,60
PDGT5738	4-33	3,80
PDGX1738	4-33	3,60
PDGX2738	4-33	1,170
PDGX3738	4-33	1,360
PDGX4738	4-33	1,40
PDLB1810	2-34	34
PDLB1810	6-19	34
PDLB1810	6-36	34
PDLB1816	2-33	34,50
PDLB1816	6-19	34,50
PDLB1816	6-35	34,50
PDLB1825	6-19	12,86
PDLB1826	6-19	13
PDLB1830	2-34	14
PDLB1836	2-33	14,50
PDLB1840	2-34	16,50
PDLB1846	2-33	17
PDLB1850	6-19	22
PDLB1852	6-40	
PDLB1856	6-19	21,5
PDLB1860	2-34	24
PDLB1860	6-36	24
PDLB1866	2-33	24,50

List of codes

Code	Page	Weight KG
PDLB1866	6-35	24,50
PDLB1875	6-19	29
PDLB1876	6-19	29
PDLB1880	2-34	29
PDLB1880	6-36	29
PDLB1886	2-33	29,50
PDLB1886	6-35	29,50
PDLB2010	2-34	38
PDLB2010	6-19	38
PDLB2010	6-36	38
PDLB2016	2-33	38,50
PDLB2016	6-19	38,50
PDLB2016	6-35	38,50
PDLB2025	6-19	14
PDLB2026	6-19	14
PDLB2030	2-34	15,50
PDLB2036	2-33	15,50
PDLB2040	2-34	18
PDLB2046	2-33	18,50
PDLB2050	6-19	24
PDLB2052	6-40	
PDLB2056	6-19	24
PDLB2060	2-34	26,50
PDLB2060	6-36	26,50
PDLB2066	2-33	25
PDLB2066	6-35	25
PDLB2075	6-19	31
PDLB2076	6-19	31,5
PDLB2080	2-34	32,50
PDLB2080	6-36	32,50
PDLB2086	2-33	32,50
PDLB2086	6-35	32,50
PDLB2120	2-34	13
PDLB2500	2-34	38
PDLB8120	2-34	10,60
PDLB8500	2-34	34
PDLG1810	2-33	32
PDLG1810	6-18	32
PDLG1810	6-35	32
PDLG1816	2-32	32
PDLG1816	6-18	32
PDLG1816	6-34	32
PDLG1840	2-33	18
PDLG1842	2-32	23
PDLG1844	2-32	27,50
PDLG1846	2-32	18
PDLG1850	6-18	20
PDLG1856	6-18	20
PDLG1860	2-33	23

Code	Page	Weight KG
PDLG1860	6-35	23
PDLG1862	2-32	27,50
PDLG1864	2-32	32
PDLG1866	2-32	23
PDLG1866	6-34	23
PDLG1870	6-18	26
PDLG1876	6-18	26,5
PDLG1880	2-33	27,50
PDLG1880	6-35	27,50
PDLG1882	2-32	32
PDLG1886	2-32	27,50
PDLG1886	6-34	27,50
PDLG2010	2-33	35
PDLG2010	6-18	35
PDLG2010	6-35	35
PDLG2016	2-32	38,50
PDLG2016	6-34	38,50
PDLG2040	2-33	19,50
PDLG2042	2-32	25
PDLG2044	2-32	30
PDLG2046	2-32	20
PDLG2050	6-18	22
PDLG2056	6-18	22,5
PDLG2060	2-33	25
PDLG2060	6-35	25
PDLG2062	2-32	30
PDLG2064	2-32	35
PDLG2066	2-32	25
PDLG2066	6-18	25
PDLG2066	6-34	25
PDLG2070	6-18	28,5
PDLG2076	6-18	28,5
PDLG2080	2-33	30
PDLG2080	6-35	30
PDLG2082	2-32	35
PDLG2086	2-32	30
PDLG2086	6-34	30
PDLG2420	2-33	25
PDLG2440	2-33	30
PDLG2500	2-34	35
PDLG2620	2-33	30
PDLG2640	2-33	36
PDLG2820	2-33	35
PDLG8420	2-33	23
PDLG8440	2-33	27,50
PDLG8500	2-34	32
PDLG8620	2-33	27
PDLG8640	2-33	31,50
PDLG8820	2-33	32

Code	Page	Weight KG
PDPT4631	4-32	2,530
PDPT4738	4-33	2,150
PDPT5631	4-32	4
PDPT5738	4-33	4,40
PDPT6738	4-33	1,140
PDPX1631	4-32	1,60
PDPX1738	4-33	1,410
PDPX2631	4-32	1,60
PDPX2738	4-33	1,410
PDPX3631	4-32	1,930
PDPX3738	4-33	1,40
PDPX4631	4-32	1,60
PDPX4738	4-33	1,60
PDRM0400	3-70	4
PDRM0600	3-70	1,8
PDRM0800	3-70	1,88
PDRP0300	3-93	1
PDRP0500	3-93	1,8
PDRP0700	3-93	2,506
PDRP0900	3-93	3
PDRS0400	3-70	1,1250
PDRS0400	3-96	1,1250
PDRS0600	3-70	1,40
PDRS0800	3-70	1,4450
PDTT4631	4-32	2,940
PDTT5631	4-32	4,530
PDTT6631	4-32	7,840
PDTT7631	4-32	16
PDTT7631	4-32	16
PDTX1631	4-32	2
PDTX2631	4-32	1,80
PDTX3631	4-32	2,20
PDTX4631	4-32	2,20
PEBL0004	2-43	0,670
PFBS1020	5-45	3,80
PFBS1021	5-45	4,6
PFBS1040	5-45	8,083
PFBS1041	5-45	8,256
PFBS8020	5-45	3,8
PFBS8021	5-45	4,6
PFBS8040	5-45	7,60
PFBS8041	5-45	8,256
PFCB1016	4-35	0,660
PFCB2025	4-35	0,890
PFCB4080	4-35	0,340
PFCC0023	4-35	0,840
PFCF1030	2-25	3,80
PFCF1030	6-14	3,80
PFCF1050	2-25	6,920

List of codes

Code	Page	Weight KG
PFCF1050	6-14	6,920
PFCF1050	6-31	6,920
PFCF1070	2-25	9,370
PFCF1070	6-14	9,370
PFCF1070	6-31	9,370
PFCF1090	2-25	12,60
PFCF1090	6-14	12,60
PFCF1090	6-31	12,60
PFCF2031	2-20	0,4
PFCF2051	2-20	1,2
PFCF2071	2-20	0,6
PFCF2091	2-20	2
PFCF2520	6-14	0,47
PFCF2530	6-14	0,78
PFCF2550	6-14	1,41
PFCF2570	6-14	2,02
PFCF2590	6-14	2,61
PFCF3020	2-25	0,560
PFCF3030	2-25	1
PFCF3050	2-25	1,50
PFCF3050	6-14	1,50
PFCF3070	2-25	2,50
PFCF3090	2-25	3
PFCF4020	2-25	0,80
PFCF4030	2-25	1,310
PFCF4031	2-20	1,309
PFCF4050	2-25	2,50
PFCF4051	2-20	2,4
PFCF4070	2-25	3,50
PFCF4071	2-20	3,5
PFCF4090	2-25	5
PFCF4091	2-20	4
PFCF5020	6-14	1
PFCF5050	6-14	3,13
PFCF5070	6-14	4,72
PFCF5090	6-14	5,93
PFCF6020	2-25	1,280
PFCF6030	2-25	2
PFCF6050	2-25	3,50
PFCF6050	6-31	3,50
PFCF6070	2-25	5,50
PFCF6070	6-31	5,50
PFCF6090	2-25	7,50
PFCF6090	6-14	7,50
PFCF6090	6-31	7,50
PFCF7520	6-14	1,6
PFCF7530	6-14	1,67
PFCF7550	6-14	4,96
PFCF7570	6-14	7,13
PFCF7590	6-14	9

Code	Page	Weight KG
PFCF8020	2-25	1,50
PFCF8030	2-25	3
PFCF8050	2-25	5
PFCF8050	6-31	5
PFCF8070	2-25	7,50
PFCF8070	6-31	7,50
PFCF8090	2-25	10
PFCF8090	6-31	10
PFCS1050	2-26	4,740
PFCS1050	6-15	4,740
PFCS1050	6-32	4,740
PFCS1070	2-26	6,830
PFCS1070	6-15	6,830
PFCS1070	6-32	6,830
PFCS1090	2-26	9,370
PFCS1090	6-15	9,370
PFCS1090	6-32	9,370
PFCS4050	2-26	1,670
PFCS4070	2-26	2,40
PFCS4090	2-26	3,140
PFCS5050	6-15	3,6
PFCS5070	6-15	3,4
PFCS5090	6-15	4,4
PFCS6050	2-26	2,710
PFCS6050	6-32	2,710
PFCS6070	2-26	3,850
PFCS6070	6-32	3,850
PFCS6090	2-26	5,090
PFCS6090	6-15	5,090
PFCS6090	6-32	5,090
PFCS7550	6-15	3,6
PFCS7570	6-15	5,1
PFCS7590	6-15	6,9
PFCS8050	2-26	3,640
PFCS8050	6-32	3,640
PFCS8070	2-26	6,010
PFCS8070	6-32	6,010
PFCS8090	2-26	7,280
PFCS8090	6-32	7,280
PFFA1810	3-68	13
PFFA1825	3-68	13
PFFA1840	3-68	10,20
PFFA1860	3-68	10
PFFA1880	3-68	11,80
PFFA2010	3-68	12,20
PFFA2025	3-68	13
PFFA2040	3-68	12
PFFA2060	3-68	11,20
PFFA2080	3-68	13
PFFN1810	6-26	7,4

Code	Page	Weight KG
PFNL1860	6-26	7,8
PFNL1880	6-26	7,2
PFNL2010	6-26	8,2
PFNL2060	6-26	7
PFNL2080	6-26	7,4
PFPPF1810	3-68	8
PFPPF1812	3-68	9,240
PFPPF1840	3-68	7,030
PFPPF1860	3-68	7,470
PFPPF1880	3-68	8,040
PFPPF2010	3-68	9,230
PFPPF2012	3-68	9,80
PFPPF2040	3-68	7,70
PFPPF2060	3-68	7,80
PFPPF2080	3-68	8,680
PFPS1840	3-68	15
PFPS1860	3-68	17
PFPS1880	3-68	18
PFPS2040	3-68	16,020
PFPS2060	3-68	18
PFPS2080	3-68	20
PFPT6738	4-33	11,80
PFRF1840	3-96	5,40
PFRF2040	3-96	5,920
PRFS2062	5-30	
PRFS2130	5-30	
PFTT6631	4-32	12,20
PFTT7631	4-32	26,80
PFTT7631	4-32	26,80
PFVS1030	5-46	6,675
PFVS1032	5-46	4,753
PFVS1040	5-46	9,131
PFVS1042	5-46	5,952
PFVS2012	5-31	2,710
PFVS2040	5-29	1,220
PFVS2042	5-24	1,10
PFVS2042	5-31	1,10
PFVS2042	5-32	1,10
PFVS2060	5-29	1,680
PFVS2062	5-24	1,540
PFVS2062	5-31	1,540
PFVS2080	5-29	2,170
PFVS2082	5-24	2,630
PFVS2082	5-31	2,630
PFVS2122	5-31	3,280
PFVS2130	5-30	1,070
PFVS2132	5-32	0,970
PFVS2140	5-30	1,320
PFVS2220	5-30	0,460
PFVS2222	5-32	0,940
PFVS2223	5-32	0,7050

List of codes

Code	Page	Weight KG
PFVS2240	5-30	1,020
PFVS2242	5-32	1,360
PFVS2243	5-32	1,190
PFVS3012	5-31	3,780
PFVS3042	5-31	1,610
PFVS3042	5-32	1,610
PFVS3062	5-31	2,3050
PFVS3082	5-31	3,020
PFVS3122	5-31	4,680
PFVS3132	5-32	1,260
PFVS3222	5-32	0,70
PFVS3223	5-32	1
PFVS3242	5-32	1,810
PFVS3243	5-32	1,740
PFVS8030	5-46	6,184
PFVS8032	5-46	4,865
PFVS8040	5-46	8,156
PFVS8042	5-46	6,15
PGPP0040	2-31	0,190
PGPP0040	6-17	0,190
PGPP0040	6-34	0,190
PHBT4301	3-73	1,930
PHBT4402	3-73	5,620
PHBT4404	3-73	3,630
PHBT4406	3-73	3,120
PHBT4406	3-73	3,120
PHBT5304	3-73	3,480
PHBT5306	3-73	3,110
PHBT5306	3-74	3,110
PHBT5309	3-74	6,950
PHBT5312	3-74	5,320
PHBT5314	3-74	4,010
PHBT5314	3-74	4,010
PHBT5326	3-74	3,10
PHBT5326	3-74	3,10
PHBT5404	3-74	3,980
PHBT5406	3-74	3,550
PHBT5406	3-74	3,550
PHBT5409	3-74	4,740
PHBT5412	3-74	5,840
PHBT5414	3-74	4,460
PHBT5414	3-74	4,460
PHBT5426	3-74	6,640
PHBT5426	3-74	6,640
PHBX1101	3-72	3,190
PHBX1105	3-72	3,180
PHBX1323	3-72	3,280
PHBX1401	3-72	1,920
PHBX1404	3-72	3,230
PHBX1405	3-72	2,010
PHBX1407	3-72	3,30

Code	Page	Weight KG
PHBX1409	3-72	3,510
PHBX1422	3-72	4,930
PHBX1422	3-72	4,930
PHBX1423	3-72	3,30
PHBX1424	3-72	6,290
PHBX1424	3-72	6,290
PHBX1427	3-72	3,290
PHBX2300	3-72	3,170
PHBX2301	3-72	2,020
PHBX2310	3-72	3,170
PHBX2312	3-72	3,490
PHBX2400	3-72	3,610
PHBX2401	3-72	3,1950
PHBX2402	3-73	4,970
PHBX2404	3-72	4,230
PHBX2405	3-72	3,090
PHBX2407	3-72	3,140
PHBX2409	3-72	3,460
PHBX2410	3-72	3,620
PHBX2412	3-72	3,950
PHBX2423	3-73	3,180
PHBX2424	3-73	6,350
PHBX2424	3-73	6,350
PHBX2425	3-73	6,290
PHBX2427	3-72	3,190
PHBX2428	3-72	3,440
PHBX2431	3-73	5,680
PHBX3301	3-73	2,020
PHBX3305	3-73	2,040
PHBX3401	3-73	3,180
PHBX3404	3-73	3,180
PHBX3405	3-73	3,20
PHBX3407	3-73	3,160
PHBX3409	3-73	3,440
PHBX3422	3-73	5,010
PHBX3422	3-73	5,010
PHBX3423	3-73	3,750
PHBX3424	3-73	6,310
PHBX3424	3-73	6,310
PHBX3427	3-73	3,190
PHBX4301	3-73	2,8150
PHBX4400	3-73	3,580
PHBX4401	3-73	3,0550
PHBX4402	3-73	4,930
PHBX4404	3-73	3,1150
PHBX4405	3-73	3,190
PHBX4407	3-73	3,050
PHBX4409	3-73	3,470
PHBX4410	3-73	3,490
PHBX4412	3-73	3,940

Code	Page	Weight KG
PHBX4423	3-73	3,010
PHBX4424	3-73	6,280
PHBX4424	3-73	6,280
PHBX4425	3-73	6,380
PHBX4425	3-73	6,380
PHBX4427	3-73	3,110
PHBX4428	3-73	3,30
PHBX4431	3-73	5,440
PHCE1240	3-81	10,60
PHCE1240	3-81	10,60
PHCE1241	3-81	6,270
PHCE1241	3-81	6,270
PHCT4301	3-76	2,7450
PHCT4402	3-76	8,610
PHCT4403	3-76	10,260
PHCT4404	3-76	4,590
PHCT4406	3-76	4,280
PHCT4406	3-76	4,280
PHCT4423	3-76	4,130
PHCT5304	3-76	4,620
PHCT5306	3-76	4,160
PHCT5306	3-76	4,160
PHCT5307	3-85	4
PHCT5309	3-76	5,610
PHCT5310	3-85	5,4
PHCT5312	3-76	7,220
PHCT5314	3-76	5,510
PHCT5314	3-76	5,510
PHCT5326	3-76	4,210
PHCT5326	3-76	4,210
PHCT5402	3-76	8,7850
PHCT5402	3-77	8,7850
PHCT5403	3-76	10,370
PHCT5404	3-76	3,310
PHCT5406	3-76	4,690
PHCT5406	3-76	4,690
PHCT5407	3-76	4,6
PHCT5409	3-76	6,330
PHCT5411	3-77	11,460
PHCT5412	3-76	7,90
PHCT5414	3-76	6,10
PHCT5414	3-76	6,10
PHCT5423	3-77	4,90
PHCT5425	3-77	11,50
PHCT5426	3-76	4,790
PHCT5426	3-76	4,790
PHCT5427	3-76	6,2
PHCT5431	3-76	9,370
PHCT5432	3-76	12,420
PHCT6301	3-77	5,460
PHCT6304	3-77	5,890

List of codes

Code	Page	Weight KG
PHCT6305	3-77	5,40
PHCT6312	3-77	7,580
PHCT6314	3-77	5,810
PHCT6314	3-77	5,810
PHCT6401	3-77	6,070
PHCT6402	3-77	9,24
PHCT6403	3-77	11,230
PHCT6404	3-77	6,440
PHCT6405	3-77	6,070
PHCT6410	3-77	7,960
PHCT6410	3-77	7,960
PHCT6411	3-77	12,440
PHCT6412	3-77	10,140
PHCT6425	3-77	11,6
PHCT7329	3-77	5,420
PHCT7418	3-77	6,790
PHCT7418	3-78	6,790
PHCT7420	3-77	5,990
PHCT7420	3-77	5,990
PHCT7430	3-78	11,1850
PHCX1101	3-74	4,320
PHCX1105	3-74	4,30
PHCX1323	3-74	4,390
PHCX1401	3-74	2,850
PHCX1404	3-74	4,310
PHCX1405	3-74	2,840
PHCX1407	3-74	4,280
PHCX1409	3-74	4,60
PHCX1422	3-74	7,430
PHCX1422	3-74	7,430
PHCX1423	3-74	4,280
PHCX1424	3-74	9,250
PHCX1424	3-74	9,250
PHCX1427	3-74	4,230
PHCX2300	3-74	4,390
PHCX2301	3-74	2,820
PHCX2310	3-74	4,260
PHCX2312	3-74	4,670
PHCX2400	3-75	4,90
PHCX2401	3-74	3,880

Code	Page	Weight KG
PHCX2402	3-75	7,360
PHCX2404	3-74	4,260
PHCX2405	3-74	4,340
PHCX2407	3-74	4,230
PHCX2409	3-74	3,890
PHCX2410	3-75	4,980
PHCX2412	3-75	5,330
PHCX2417	3-75	4,80
PHCX2423	3-75	3,740
PHCX2424	3-75	9,060
PHCX2424	3-75	9,060
PHCX2425	3-75	8,950
PHCX2425	3-75	8,950
PHCX2427	3-75	4,30
PHCX2431	3-75	8,340
PHCX3301	3-75	2,860
PHCX3305	3-75	2,840
PHCX3401	3-75	4,240
PHCX3404	3-75	4,190
PHCX3405	3-75	4,220
PHCX3407	3-75	4,30
PHCX3409	3-75	4,580
PHCX3422	3-75	7,610
PHCX3422	3-75	7,610
PHCX3423	3-75	4,90
PHCX3424	3-75	9,040
PHCX3424	3-75	9,040
PHCX3427	3-75	4,250
PHCX4301	3-75	2,790
PHCX4400	3-76	4,790
PHCX4401	3-75	4,080
PHCX4402	3-76	7,330
PHCX4404	3-75	4,240
PHCX4405	3-75	4,310
PHCX4407	3-75	4,140
PHCX4409	3-75	4,620
PHCX4410	3-76	4,870
PHCX4412	3-76	5,40
PHCX4417	3-76	4,650
PHCX4423	3-76	4,160
PHCX4424	3-76	9,120
PHCX4424	3-76	9,120
PHCX4425	3-76	8,970
PHCX4425	3-76	8,970
PHCX4427	3-76	4,250
PHCX4431	3-76	7,970
PHDE1240	3-81	12,470
PHDE1240	3-81	12,470
PHDE1241	3-81	8,470

Code	Page	Weight KG
PHDE1241	3-81	8,470
PHDR0004	2-44	0,180
PHDT4402	3-79	11,480
PHDT4403	3-79	11,680
PHDT5304	3-79	5,820
PHDT5306	3-79	5,30
PHDT5306	3-79	5,30
PHDT5309	3-79	6,920
PHDT5309	3-79	6,920
PHDT5312	3-79	9,110
PHDT5314	3-79	7,040
PHDT5314	3-79	7,040
PHDT5326	3-79	5,350
PHDT5326	3-79	5,350
PHDT5404	3-79	6,740
PHDT5406	3-79	6,270
PHDT5406	3-80	6,270
PHDT5407	3-80	6,2
PHDT5409	3-80	8,150
PHDT5411	3-80	15,60
PHDT5412	3-80	10,080
PHDT5414	3-80	7,910
PHDT5414	3-80	7,910
PHDT5423	3-80	6,210
PHDT5423	3-80	6,210
PHDT5425	3-80	14,760
PHDT5426	3-80	6,080
PHDT5426	3-80	6,080
PHDT5428	3-80	5,3
PHDT5431	3-80	15,2
PHDT5432	3-80	15,2
PHDT6301	3-80	7,640
PHDT6304	3-80	7,550
PHDT6305	3-80	7,520
PHDT6312	3-80	9,770
PHDT6314	3-80	7,640
PHDT6314	3-80	7,640
PHDT6401	3-80	7,70
PHDT6402	3-80	9,45
PHDT6403	3-80	9,45
PHDT6404	3-80	8,310
PHDT6405	3-80	7,530
PHDT6412	3-80	12,580
PHDT6414	3-80	9,460
PHDT6414	3-80	9,460
PHDT7329	3-80	7,040

List of codes

Code	Page	Weight KG
PHDT7329	3-80	7,040
PHDT7418	3-80	8,870
PHDT7418	3-80	8,870
PHDT7420	3-80	7,510
PHDT7420	3-80	7,510
PHDT7420	3-80	7,510
PHDT7430	3-80	14,40
PHDX1105	3-78	3,54
PHDX1301	3-78	3,8
PHDX1401	3-78	5,4
PHDX1402	3-78	9,87
PHDX1403	3-78	9,87
PHDX1404	3-78	3,54
PHDX1407	3-78	3,54
PHDX1409	3-78	3,54
PHDX1422	3-78	9,87
PHDX1423	3-78	6,8
PHDX1424	3-78	9,87
PHDX1427	3-78	3,54
PHDX2400	3-78	3,54
PHDX2401	3-78	5,380
PHDX2402	3-78	9,87
PHDX2403	3-78	9,87
PHDX2404	3-78	5,310
PHDX2405	3-78	5,4
PHDX2407	3-78	5,2
PHDX2409	3-78	6
PHDX2410	3-78	6
PHDX2412	3-78	4,58
PHDX2417	3-78	3,54
PHDX2423	3-78	5,260
PHDX2425	3-78	9,87
PHDX2427	3-78	4,2
PHDX2428	3-78	5,920
PHDX2432	3-78	9,87
PHDX3401	3-78	5,4
PHDX3402	3-79	9,87
PHDX3403	3-79	9,87
PHDX3404	3-78	3,54
PHDX3405	3-78	3,54
PHDX3407	3-78	5,2
PHDX3409	3-79	3,54
PHDX3423	3-78	6,2
PHDX3427	3-79	3,54
PHDX4400	3-79	4,58

Code	Page	Weight KG
PHDX4401	3-79	5,290
PHDX4402	3-79	9,87
PHDX4403	3-79	9,87
PHDX4404	3-79	5,290
PHDX4405	3-79	5,2
PHDX4407	3-79	5,2
PHDX4410	3-79	4,58
PHDX4412	3-79	4,58
PHDX4417	3-79	4,58
PHDX4422	3-79	9,87
PHDX4423	3-79	5,190
PHDX4425	3-79	9,87
PHDX4427	3-79	3,54
PHDX4428	3-79	7
PHFP0020	3-99	0,80
PHFR4180	2-44	0,770
PIDH0010	2-42	0,30
PIEH0008	2-42	0,020
PIFH0020	2-42	0,020
PIRH0405	2-42	0,20
PIRH0455	2-42	0,20
PIRH1242	2-42	0,20
PIRH2432	2-42	0,2
PIRP2040	3-96	0,940
PISH0007	2-42	0,020
PITE7120	4-33	0,50
PITH0064	2-42	0,020
PITH1234	4-33	0,230
PITH5000	4-33	0,30
PITH6000	4-33	0,440
PITV6000	4-33	0,60
PKAT5050	2-23	2,7
PKAT5050	6-12	2,7
PKAT5050	6-30	2,7
PKAT7070	2-23	3,55
PKAT7070	6-12	3,55
PKAT7070	6-30	3,55
PKAT9090	2-23	4,8
PKAT9090	6-12	4,8
PKAT9090	6-30	4,8
PKDT0200	2-23	0,4
PKDT0200	6-12	0,4
PKDT0200	6-30	0,4
PKDT0250	2-23	0,443
PKDT0250	6-12	0,443
PKDT0250	6-30	0,443
PKDT0300	2-23	0,512
PKDT0300	6-12	0,512
PKDT0300	6-30	0,512

Code	Page	Weight KG
PKDT0301	2-23	0,47
PKDT0301	6-12	0,47
PKDT0301	6-30	0,47
PKDT0400	2-23	0,648
PKDT0400	6-12	0,648
PKDT0400	6-30	0,648
PKDT0500	2-23	0,785
PKDT0500	6-12	0,785
PKDT0500	6-30	0,785
PKDT0501	2-23	0,53
PKDT0501	6-12	0,53
PKDT0501	6-30	0,53
PKDT0600	2-23	0,921
PKDT0600	6-12	0,921
PKDT0600	6-30	0,921
PKDT0700	2-23	0,8
PKDT0700	6-12	0,8
PKDT0700	6-30	0,8
PKDT0750	2-23	1,126
PKDT0750	6-12	1,126
PKDT0750	6-30	1,126
PKDT0800	2-23	1,4
PKDT0800	6-12	1,4
PKDT0800	6-30	1,4
PKDT0900	2-23	1,2
PKDT0900	6-12	1,2
PKDT0900	6-30	1,2
PKDT1000	2-23	1,468
PKDT1000	6-12	1,468
PKDT1000	6-30	1,468
PKDT1250	2-23	1,809
PKDT1250	6-12	1,809
PKDT1250	6-30	1,809
PKEK0004	3-69	0,440
PKMI0002	2-43	0,06
PKNL1210	6-26	13,6
PKNL1260	6-26	9
PKNL1280	6-26	10,4
PKOH1060	3-90	11,850
PKOH1080	3-90	13,620
PKOH1660	3-90	5
PKOH1680	3-90	6,310
PKOH3160	3-90	5,640
PKOH3180	3-90	7,170
PKOH6360	3-90	8,380
PKOH6380	3-90	10,710
PKOV1060	3-90	12,010
PKOV1080	3-90	13,890
PKOV1660	3-90	6,310

List of codes

Code	Page	Weight KG
PKOV1680	3-90	8,240
PKOV3160	3-90	7,680
PKOV3180	3-90	9,940
PKOV6360	3-90	8,320
PKOV6380	3-90	10,760
PKST0200	2-23	0,601
PKST0200	6-12	0,601
PKST0200	6-30	0,601
PKST0250	2-23	0,705
PKST0250	6-12	0,705
PKST0250	6-30	0,705
PKST0300	2-23	0,8
PKST0300	6-12	0,8
PKST0300	6-30	0,8
PKST0301	2-23	0,78
PKST0301	6-12	0,78
PKST0301	6-30	0,78
PKST0400	2-23	1
PKST0400	6-12	1
PKST0400	6-30	1
PKST0500	2-23	1,09
PKST0500	6-12	1,09
PKST0500	6-30	1,09
PKST0501	2-23	1
PKST0501	6-12	1
PKST0501	6-30	1
PKST0600	2-23	1,2
PKST0600	6-12	1,2
PKST0600	6-30	1,2
PKST0700	2-23	1,2
PKST0700	6-12	1,2
PKST0700	6-30	1,2
PKST0750	2-23	1,657
PKST0750	6-12	1,657
PKST0750	6-30	1,657
PKST0800	2-23	1,6
PKST0800	6-12	1,6
PKST0800	6-30	1,6
PKST0900	2-23	1,8
PKST0900	6-12	1,8
PKST0900	6-30	1,8
PKST1000	2-23	2
PKST1000	6-12	2
PKST1000	6-30	2
PKST1250	2-23	2,609
PKST1250	6-12	2,609
PKST1250	6-30	2,609
PLLS2050	5-33	0,2
PLLS2070	5-33	0,66

Code	Page	Weight KG
PLLS2090	5-33	0,6
PLLS3050	5-33	4
PLLS3070	5-33	0,8
PLLS3090	5-33	1,17
PLSU0300	5-24	1,7
PLVS0552	5-41	0,175
PLVS0572	5-41	0,279
PLVS0592	5-41	0,413
PLVS1052	5-41	0,328
PLVS1072	5-41	0,564
PLVS1092	5-41	0,825
PLVS1552	5-41	0,525
PLVS1572	5-41	0,852
PLVS1592	5-41	1,238
PLVS1752	5-43	0,580
PLVS1772	5-43	0,970
PLVS1792	5-43	1,40
PLVS2052	5-37	0,6550
PLVS2052	5-43	0,6550
PLVS2072	5-37	1,110
PLVS2072	5-43	1,110
PLVS2092	5-37	1,640
PLVS2092	5-43	1,640
PLVS2252	5-43	0,740
PLVS2272	5-43	1,240
PLVS2292	5-43	1,760
PLVS2552	5-37	0,830
PLVS2552	5-43	0,830
PLVS2552	5-43	0,830
PLVS2572	5-37	1,40
PLVS2572	5-43	1,40
PLVS2572	5-43	1,40
PLVS2592	5-37	2,110
PLVS2592	5-43	2,110
PLVS2592	5-43	2,110
PLVS3052	5-37	0,9950
PLVS3052	5-43	0,9950
PLVS3072	5-37	1,680
PLVS3072	5-43	1,680
PLVS3092	5-37	2,480
PLVS3092	5-43	2,480
PLVS3552	5-37	1,180
PLVS3552	5-43	1,180
PLVS3572	5-37	1,950
PLVS3572	5-43	1,950
PLVS3592	5-37	2,780
PLVS3592	5-43	2,780
PLVS4052	5-37	1,350
PLVS4072	5-37	2,250

Code	Page	Weight KG
PLVS4092	5-37	3,330
PLVS5052	5-37	1,750
PLVS5072	5-37	2,840
PLVS5092	5-37	4,130
PLVS6052	5-37	2,10
PLVS6072	5-37	3,440
PLVS6092	5-37	4,940
PLVS7052	5-28	2,430
PLVS7052	5-44	2,430
PLVS7052	5-47	2,430
PLVS7072	5-28	4,120
PLVS7072	5-44	4,120
PLVS7072	5-47	4,120
PLVS7092	5-28	5,7750
PLVS7092	5-44	5,7750
PLVS7092	5-47	5,7750
PMCC2060	3-93	
PMCC3060	3-93	
PMCC4060	3-93	
PMCC6060	3-93	
PMCC8060	3-93	
PMCS1755	4-45	1,360
PMCS1755	5-51	1,360
PMCS1757	4-45	2,10
PMCS1757	5-51	2,10
PMCS1759	4-45	3,290
PMCS1759	5-51	3,290
PMCS2050	4-45	1,530
PMCS2050	5-51	1,530
PMCS2070	4-45	2,550
PMCS2070	5-51	2,550
PMCS2090	4-45	3,620
PMCS2090	5-51	3,620
PMCS2255	4-45	1,60
PMCS2255	5-51	1,60
PMCS2257	4-45	2,70
PMCS2257	5-51	2,70
PMCS2259	4-45	3,950
PMCS2259	5-51	3,950
PMCS2550	4-45	1,890
PMCS2550	5-51	1,890
PMCS2570	4-45	3,10
PMCS2570	5-51	3,10
PMCS2590	4-45	4,340
PMCS2590	5-51	4,340
PMCS3050	4-45	2,260
PMCS3050	5-51	2,260
PMCS3070	4-45	3,710

List of codes

Code	Page	Weight KG
PMCS3070	5-51	3,710
PMCS3090	4-45	4,90
PMCS3090	5-51	4,90
PMRP2040	3-96	0,860
PPAM0100	2-17	3,70
PPAM0100	6-9	3,70
PPAM0100	6-28	3,70
PPAM0200	2-17	7,350
PPAM0200	6-9	7,350
PPAM0200	6-28	7,350
PPBR2040	3-95	1,110
PPBR2060	3-95	1,610
PPBR2068	3-95	2,2
PPBR2080	3-95	2,140
PPBR2088	3-95	3
PPBR4040	3-95	1,950
PPBR4060	3-95	2,880
PPBR4080	3-95	3,980
PPBR6040	3-95	2,810
PPBR6060	3-95	4,190
PPBR6080	3-95	5,250
PPBS0050	5-34	0,090
PPBS0100	5-34	0,190
PPBS0150	5-34	0,280
PPBS0200	5-34	0,370
PPBS0250	5-34	0,490
PPBS0300	5-34	0,550
PPCV1800	2-35	1,880
PPCV1800	6-20	1,880
PPCV1800	6-36	1,880
PPCV2000	2-35	1,940
PPCV2000	6-20	1,940
PPCV2000	6-36	1,940
PPDS0200	5-24	0,7350
PPEA1810	2-29	15,50
PPEA1810	6-33	15,50
PPEA1830	2-29	6,50
PPEA1830	2-31	6,50
PPEA1830	6-17	6,50
PPEA1840	2-29	8
PPEA1850	2-31	10
PPEA1850	6-17	10
PPEA1850	6-34	10
PPEA1860	2-29	11
PPEA1860	6-33	11
PPEA1870	2-31	12,50
PPEA1870	6-17	12,50
PPEA1870	6-34	12,50
PPEA1875	6-16	13,5

Code	Page	Weight KG
PPEA1880	2-29	13
PPEA1880	6-33	13
PPEA1890	2-31	15
PPEA1890	6-17	15
PPEA1890	6-34	15
PPEA2010	2-29	17,50
PPEA2010	6-33	17,50
PPEA2030	2-29	7
PPEA2030	2-31	7
PPEA2030	6-17	7
PPEA2040	2-29	9
PPEA2050	2-31	11
PPEA2050	6-17	11
PPEA2050	6-34	11
PPEA2060	2-29	12
PPEA2060	6-33	12
PPEA2070	2-31	14
PPEA2070	6-17	14
PPEA2070	6-34	14
PPEA2075	6-16	14,5
PPEA2080	2-29	15
PPEA2080	6-33	15
PPEA2090	2-31	16,50
PPEA2090	6-17	16,50
PPEA2090	6-34	16,50
PPEB1810	2-28	18
PPEB1810	6-15	18
PPEB1810	6-32	18
PPEB1816	2-28	30
PPEB1816	6-15	30
PPEB1816	6-32	30
PPEB1820	2-30	5,50
PPEB1820	6-16	5,50
PPEB1825	6-15	9,5
PPEB1826	2-29	8,50
PPEB1826	6-16	8,50
PPEB1827	6-15	6,5
PPEB1830	2-28	7
PPEB1830	2-30	7
PPEB1830	6-16	7
PPEB1836	2-28	11
PPEB1836	2-29	11
PPEB1836	6-16	11
PPEB1840	2-28	8,50
PPEB1846	2-28	14
PPEB1850	2-30	10
PPEB1850	6-15	10
PPEB1850	6-16	10
PPEB1850	6-33	10

Code	Page	Weight KG
PPEB1856	2-29	16
PPEB1856	6-15	16
PPEB1856	6-16	16
PPEB1856	6-33	16
PPEB1860	2-28	12
PPEB1860	6-32	12
PPEB1866	2-28	19
PPEB1866	6-32	19
PPEB1870	2-30	13,50
PPEB1870	6-16	13,50
PPEB1870	6-33	13,50
PPEB1875	6-15	22,5
PPEB1876	2-29	21,50
PPEB1876	6-16	21,50
PPEB1876	6-33	21,50
PPEB1877	6-15	14
PPEB1880	2-28	15
PPEB1880	6-32	15
PPEB1886	2-28	24,50
PPEB1886	6-32	24,50
PPEB1890	2-30	16,50
PPEB1890	6-16	16,50
PPEB1890	6-33	16,50
PPEB1896	2-29	26,50
PPEB1896	6-16	26,50
PPEB1896	6-33	26,50
PPEB1906	2-28	20
PPEB2010	6-15	20
PPEB2010	6-32	20
PPEB2016	2-28	32
PPEB2016	6-15	32
PPEB2016	6-32	32
PPEB2020	2-30	6
PPEB2020	6-16	6
PPEB2025	6-15	10,5
PPEB2026	2-29	9,50
PPEB2026	6-16	9,50
PPEB2027	6-15	8,04
PPEB2030	2-28	8
PPEB2030	2-30	8
PPEB2030	6-16	8
PPEB2036	2-28	11,60
PPEB2036	2-29	11,60
PPEB2036	6-16	11,60
PPEB2040	2-28	9,50
PPEB2046	2-28	15
PPEB2050	2-30	11,50
PPEB2050	6-15	11,50
PPEB2050	6-16	11,50

List of codes

Code	Page	Weight KG
PPEB2050	6-33	11,50
PPEB2056	2-29	18
PPEB2056	6-15	18
PPEB2056	6-16	18
PPEB2056	6-33	18
PPEB2060	2-28	13
PPEB2060	6-32	13
PPEB2066	2-28	20,20
PPEB2066	6-32	20,20
PPEB2070	2-30	15
PPEB2070	6-16	15
PPEB2070	6-33	15
PPEB2075	6-15	25
PPEB2076	2-29	23,50
PPEB2076	6-16	23,50
PPEB2076	6-33	23,50
PPEB2077	6-15	15,5
PPEB2080	2-28	16,50
PPEB2080	6-32	16,50
PPEB2086	2-28	25,40
PPEB2086	6-32	25,40
PPEB2090	2-30	18
PPEB2090	6-16	18
PPEB2090	6-33	18
PPEB2096	2-29	28
PPEB2096	6-16	28
PPEB2096	6-33	28
PPFA1010	3-95	1,160
PPFA1040	3-95	0,460
PPFA1060	3-95	0,690
PPFA1080	3-95	0,880
PPFA2010	3-95	2,020
PPFA2040	3-95	0,870
PPFA2060	3-95	1,220
PPFA2080	3-95	1,610
PPFB1010	3-94	1,240
PPFB1013	3-94	1,579
PPFB1040	3-94	0,50
PPFB1060	3-94	0,720
PPFB1080	3-94	0,980
PPFB1510	3-94	1,89
PPFB1540	3-94	0,760
PPFB1560	3-94	1,060
PPFB1580	3-94	1,410
PPFB1840	3-94	7
PPFB1860	3-94	10
PPFB1880	3-94	14
PPFB2004	3-94	7,50
PPFB2006	3-94	12

Code	Page	Weight KG
PPFB2008	3-94	16
PPFB2010	3-94	2,30
PPFB2012	3-94	2,870
PPFB2040	3-94	0,920
PPFB2060	3-94	1,370
PPFB2080	3-94	1,80
PPFB2512	3-94	3,60
PPFB2540	3-94	1,190
PPFB2560	3-94	1,640
PPFB2580	3-94	2,20
PPFB3010	3-94	3,510
PPFB3012	3-94	4
PPFB3040	3-94	1,30
PPFB3060	3-94	1,940
PPFB3080	3-94	2,60
PPFB3512	3-94	4,80
PPFB3540	3-94	1,8
PPFB3560	3-94	2,24
PPFB3580	3-94	3,02
PPFB4010	3-94	4,480
PPFB4040	3-94	1,720
PPFB4060	3-94	2,520
PPFB4080	3-94	3,50
PPFB4540	3-94	2
PPFB4560	3-94	2,8
PPFB4580	3-94	3,77
PPFB5001	3-94	5,490
PPFB5004	3-94	2,130
PPFB5006	3-94	3,170
PPFB5008	3-94	4,230
PPFB5040	3-94	0,30
PPFB5060	3-94	0,440
PPFB5080	3-94	0,610
PPFB6010	3-94	6,620
PPFB6040	3-94	2,510
PPFB6060	3-94	3,630
PPFB6080	3-94	5
PPFB8010	3-94	8,930
PPFB8040	3-94	3,310
PPFB8060	3-94	4,980
PPFB8080	3-94	6,370
PPFH0250	6-20	1,2
PPFH0300	2-35	1,370
PPFH0400	2-35	1,580
PPFH0500	6-20	1,68
PPFH0600	2-35	1,990
PPFH0600	6-36	1,990
PPFH0750	6-20	2,19
PPFH0800	2-35	2,40

Code	Page	Weight KG
PPFH0800	6-36	2,40
PPFH1000	2-35	2,780
PPFH1000	6-20	2,780
PPFH1000	6-36	2,780
PPFH1250	2-35	3,320
PPFH1250	6-20	3,320
PPFI2726	3-95	1,340
PPFI2728	3-95	1,780
PPFI2966	3-95	1,260
PPFI2968	3-95	1,70
PPFI4726	3-95	1,230
PPFI4728	3-95	1,670
PPFI4968	3-95	1,530
PPFM1010	2-18	3,6880
PPFM1010	6-9	3,6880
PPFM1020	2-18	0,9540
PPFM1020	6-9	0,9540
PPFM1025	6-9	1,142
PPFM1030	2-18	1,3160
PPFM1030	6-9	1,3160
PPFM1040	2-18	1,6940
PPFM1050	2-18	1,980
PPFM1050	6-9	1,980
PPFM1050	6-9	1,980
PPFM1060	2-18	2,3820
PPFM1070	2-18	2,6960
PPFM1070	6-9	2,6960
PPFM1075	6-9	2,82
PPFM1080	2-18	3,0670
PPFM1090	2-18	3,4170
PPFM1090	6-9	3,4170
PPFM1250	2-18	2,270
PPFM1250	6-9	2,270
PPFV1800	2-35	4,50
PPFV1800	6-20	4,50
PPFV1800	6-36	4,50
PPFV2000	2-35	4,420
PPFV2000	6-20	4,420
PPFV2000	6-36	4,420
PPIM0100	2-17	3,0850
PPIM0200	2-17	6,240
PPLA1820	2-29	10,50
PPLA1820	6-16	10,50
PPLA2020	2-29	12
PPLA2020	6-16	12
PPLB1820	2-28	11,50
PPLB1820	6-15	11,50
PPLB2020	2-28	13

List of codes

Code	Page	Weight KG
PPLB2020	6-15	13
PPMB1510	3-92	2,99
PPMB1540	3-92	0,6250
PPMB1560	3-92	1,810
PPMB1580	3-92	2,260
PPMB2010	3-92	4,320
PPMB2012	3-92	5,020
PPMB2040	3-92	2,560
PPMB2060	3-92	3,060
PPMB2080	3-92	3,830
PPMB2512	3-92	6
PPMB2540	3-92	2,770
PPMB2560	3-92	3,430
PPMB2580	3-92	4,80
PPMB3010	3-92	5,530
PPMB3012	3-92	5,60
PPMB3040	3-92	3,090
PPMB3060	3-92	3,910
PPMB3080	3-92	4,680
PPMB3512	3-92	7,80
PPMB3540	3-92	3,43
PPMB3560	3-92	4,39
PPMB3580	3-92	5,38
PPMB4010	3-92	6,850
PPMB4040	3-92	3,480
PPMB4060	3-92	4,570
PPMB4080	3-92	5,560
PPMB4540	3-92	3,97
PPMB4560	3-92	5,18
PPMB4580	3-92	6,45
PPMB5001	3-92	5,710
PPMB5004	3-92	4,040
PPMB5006	3-92	5,350
PPMB5008	3-92	6,640
PPMB6010	3-92	9,660
PPMB6040	3-92	4,560
PPMB6060	3-92	5,980
PPMB6080	3-92	7,710
PPMD3040	3-71	1,14
PPMD3060	3-71	1,71
PPMD3080	3-71	2,4
PPMF1540	3-71	0,630
PPMF1560	3-71	0,860
PPMF1580	3-71	1,140
PPMF2040	3-71	0,810
PPMF2060	3-71	1,20
PPMF2080	3-71	1,550
PPMF3040	3-71	1,050
PPMF3060	3-71	1,620

Code	Page	Weight KG
PPMF3080	3-71	2,10
PPMU3060	3-71	1,890
PPMU3060	4-39	1,890
PPMU3080	3-71	2,430
PPMU3080	4-39	2,430
PPNL3010	6-26	3,4
PPNL3060	6-26	2,14
PPNL3080	6-26	3
PPNL4010	6-26	4,6
PPNL4060	6-26	2,6
PPNL4080	6-26	3,8
PPRA1820	2-29	140
PPRA1820	6-16	140
PPRA2020	2-29	160
PPRA2020	6-16	160
PPRB1820	2-28	15,50
PPRB1820	6-15	15,50
PPRB2020	2-28	170
PPRB2020	6-15	170
PPRR6040	3-96	4,379
PPRS0150	5-24	0,090
PPRS0200	5-24	0,050
PPRS0250	5-24	0,080
PPRS0250	5-29	0,080
PPRS0300	5-24	0,10
PPRS0300	5-29	0,10
PPRS0350	5-24	0,150
PPRS0350	5-29	0,150
PPRS0400	5-24	0,130
PPRS0400	5-29	0,130
PPRS0450	5-24	0,150
PPRS0450	5-29	0,150
PPRS0500	5-24	0,180
PPRS0500	5-29	0,180
PPRS0600	5-24	0,210
PPRS0600	5-29	0,210
PPUN0100	2-37	30
PPVS2200	5-23	0,360
PPVS2250	5-23	0,450
PPVS2300	5-23	1
PPVS2350	5-23	0,620
PPVS2400	5-23	1,430
PPVS2450	5-23	1,610
PPVS2500	5-23	0,870
PPVS2600	5-23	2,070
PPVS2700	5-23	2,450
PRAS0012	2-37	8,351
PRBE1243	3-96	5,810

Code	Page	Weight KG
PRBE2232	3-96	5,420
PRBE2233	3-96	5,350
PRBS1220	5-47	2,620
PRBS1240	5-47	5,090
PRBS8220	5-47	2,10
PRBS8240	5-47	4
PRVS0141	5-41	0,193
PRVS0161	5-41	0,314
PRVS0162	5-41	0,421
PRVS0181	5-36	0,43
PRVS0181	5-41	0,43
PRVS0182	5-41	0,646
PRVS0182	5-41	0,646
PRVS0541	5-41	0,097
PRVS0560	5-41	0,413
PRVS0561	5-41	0,157
PRVS0562	5-41	0,211
PRVS0580	5-41	0,554
PRVS0581	5-36	0,215
PRVS0581	5-41	0,215
PRVS0582	5-41	0,323
PRVS0582	5-41	0,323
PRVS1006	5-41	0,828
PRVS1008	5-41	1,104
PRVS1010	5-45	13,250
PRVS1040	5-45	5,3450
PRVS1040	5-47	5,3450
PRVS1041	5-44	3,1950
PRVS1060	5-45	8,0350
PRVS1061	5-44	2,0450
PRVS1062	5-44	4,2050
PRVS1062	5-47	4,2050
PRVS1080	5-45	10,330
PRVS1081	5-44	5,250
PRVS1082	5-44	5,230
PRVS1541	5-41	0,289
PRVS1560	5-41	1,238
PRVS1561	5-41	0,47
PRVS1562	5-41	0,632
PRVS1580	5-41	1,7
PRVS1581	5-41	0,645
PRVS1582	5-41	0,789
PRVS1582	5-41	0,789
PRVS1710	5-42	2,5050
PRVS1740	5-42	1,030
PRVS1741	5-39	0,330
PRVS1760	5-42	1,420
PRVS1761	5-39	0,540
PRVS1762	5-40	0,70

List of codes

Code	Page	Weight KG
PRVS1780	5-42	2,040
PRVS1781	5-39	0,7350
PRVS1782	5-40	0,9650
PRVS2010	5-31	2,8050
PRVS2010	5-42	2,8050
PRVS2040	5-29	1,80
PRVS2040	5-31	1,80
PRVS2040	5-32	1,80
PRVS2040	5-42	1,80
PRVS2041	5-36	0,3850
PRVS2041	5-39	0,3850
PRVS2060	5-29	1,650
PRVS2060	5-31	1,650
PRVS2060	5-42	1,650
PRVS2061	5-36	0,60
PRVS2061	5-39	0,60
PRVS2062	5-40	0,810
PRVS2080	5-29	2,280
PRVS2080	5-31	2,280
PRVS2080	5-42	2,280
PRVS2081	5-39	0,8750
PRVS2082	5-40	1,0950
PRVS2125	5-31	3,570
PRVS2125	5-42	3,570
PRVS2210	5-42	3,230
PRVS2240	5-42	1,290
PRVS2241	5-39	1,30
PRVS2251	5-39	0,9650
PRVS2260	5-42	1,840
PRVS2261	5-39	0,70
PRVS2262	5-40	0,90
PRVS2280	5-42	2,550
PRVS2282	5-40	1,210
PRVS2510	5-42	3,5350
PRVS2510	5-42	3,5350
PRVS2512	5-42	4,1050
PRVS2512	5-42	4,1050
PRVS2541	5-36	0,50
PRVS2560	5-42	2,040
PRVS2560	5-42	2,040
PRVS2561	5-36	0,770
PRVS2561	5-39	0,770
PRVS2561	5-39	0,770
PRVS2562	5-40	0,980
PRVS2562	5-40	0,980
PRVS2580	5-42	2,7750
PRVS2580	5-42	2,7750
PRVS2581	5-39	1,0550
PRVS2581	5-39	1,0550

Code	Page	Weight KG
PRVS2582	5-40	1,3250
PRVS2582	5-40	1,3250
PRVS3010	5-31	4,150
PRVS3010	5-42	4,150
PRVS3041	5-36	0,570
PRVS3041	5-39	0,570
PRVS3041	5-39	0,570
PRVS3060	5-42	2,40
PRVS3060	5-42	2,40
PRVS3061	5-36	0,960
PRVS3061	5-39	0,960
PRVS3061	5-39	0,960
PRVS3062	5-40	1,180
PRVS3060	5-31	
PRVS3080	5-31	3,20
PRVS3080	5-42	3,20
PRVS3080	5-42	3,20
PRVS3081	5-36	1,290
PRVS3081	5-39	1,290
PRVS3082	5-40	1,5750
PRVS3125	5-31	5,090
PRVS3125	5-42	5,090
PRVS3501	5-42	5,90
PRVS3510	5-42	4,480
PRVS3510	5-42	4,480
PRVS3541	5-36	0,6750
PRVS3561	5-36	1,0850
PRVS3581	5-36	1,480
PRVS4041	5-36	0,7850
PRVS4061	5-36	1,230
PRVS4081	5-36	1,780
PRVS5041	5-36	0,970
PRVS5061	5-36	1,520
PRVS5081	5-36	2,1250
PRVS6041	5-36	1,160
PRVS6061	5-36	1,860
PRVS6081	5-36	2,5650
PRVS7010	5-45	9,110
PRVS7040	5-45	3,930
PRVS7041	5-36	1,370
PRVS7041	5-44	1,370
PRVS7060	5-45	5,4250
PRVS7061	5-36	2,2650
PRVS7061	5-44	2,2650
PRVS7062	5-44	2,9450
PRVS7080	5-45	7,260
PRVS7081	5-36	3,0950
PRVS7081	5-44	3,0950

Code	Page	Weight KG
PRVS7082	5-44	3,20
PRVS8010	5-45	10,4050
PRVS8040	5-45	4,290
PRVS8040	5-47	4,290
PRVS8041	5-44	1,6350
PRVS8060	5-45	6,4350
PRVS8061	5-44	2,560
PRVS8062	5-44	3,6850
PRVS8062	5-47	3,6850
PRVS8080	5-45	8,40
PRVS8081	5-44	3,470
PRVS8082	5-44	4,160
PSAF0016	2-44	0,660
PSBS0065	2-43	0,390
PSCP0024	2-44	0,280
PSCS0579	2-43	0,520
PSHF1096	5-38	2,560
PSHF1296	5-38	3,140
PSHF4072	3-96	0,82
PSHF4072	5-38	0,82
PSHF4092	3-96	1,11
PSHF4092	5-38	1,11
PSHF6072	5-38	1,10
PSHF6072	5-38	1,10
PSHF6092	5-38	1,60
PSHF6092	5-38	1,60
PSHF8072	5-38	1,510
PSHF8072	5-38	1,510
PSHF8092	5-38	2,160
PSHF8092	5-38	2,160
PSHS1400	5-50	0,370
PSHS1600	5-50	0,530
PSHS1800	5-50	0,70
PSHS1901	5-23	2,460
PSHS1904	5-23	0,990
PSHS1906	5-23	1,420
PSHS1908	5-23	1,9350
PSHS1912	5-23	
PSHS2400	5-50	0,490
PSHS2600	5-50	0,730
PSHS2800	5-50	0,940
PSHS4050	5-37	2,840
PSHS4070	5-37	3,850
PSHS4090	5-37	5,020
PSHS6050	5-37	3,790
PSHS6070	5-37	5,450
PSHS6090	5-37	7
PSHS8050	5-37	4,980
PSHS8070	5-37	7

List of codes

Code	Page	Weight KG
PSHS8090	5-37	8,960
PSHW1096	5-38	2,090
PSHW1292	5-38	2,599
PSHW1296	5-38	2,590
PSHW4051	3-96	0,46
PSHW4051	5-38	0,46
PSHW4071	3-96	0,79
PSHW4071	5-38	0,79
PSHW4072	3-96	0,62
PSHW4072	5-38	0,62
PSHW4091	3-96	1,09
PSHW4091	5-38	1,09
PSHW4092	3-96	0,91
PSHW4092	5-38	0,91
PSHW5061	5-25	3,70
PSHW5081	5-25	4,470
PSHW6051	5-38	0,640
PSHW6071	5-38	1,110
PSHW6072	5-38	0,940
PSHW6074	5-38	0,920
PSHW6091	5-38	1,570
PSHW6092	5-38	1,360
PSHW6094	5-38	1,450
PSHW8051	5-38	0,870
PSHW8071	5-38	1,470
PSHW8072	5-38	1,20
PSHW8074	5-38	1,20
PSHW8091	5-38	2,20
PSHW8092	5-38	1,760
PSHW8094	5-38	1,770
PSRM1515	3-97	0,130
PSVF6042	3-96	4
PSVF6042	5-25	4
PSVF6062	5-25	8,110
PSVF6064	5-25	9,80
PSVF6082	5-25	12,960
PSVF6084	5-25	12,520
PSVF7016	5-25	14,920
PSVF7126	5-25	16,760
PSVS0055	5-34	4
PSVS0057	5-34	5,910
PSVS0105	5-36	0,730
PSVS0107	5-36	1,070
PSVS0109	5-36	1,370
PSVS0155	5-36	1,620
PSVS0157	5-36	1,460
PSVS0159	5-36	1,960
PSVS0205	5-36	1,290
PSVS0207	5-36	1,860

Code	Page	Weight KG
PSVS0209	5-36	2,550
PSVS0255	5-36	1,040
PSVS0257	5-36	2,330
PSVS0259	5-36	3,090
PSVS0305	5-36	1,90
PSVS0307	5-36	2,690
PSVS0309	5-36	3,680
PSVS0505	5-36	0,460
PSVS0507	5-36	0,660
PSVS0509	5-36	0,850
PSVS2050	5-34	1,220
PSVS2051	5-35	0,79
PSVS2070	5-34	1,740
PSVS2071	5-35	1,39
PSVS2090	5-34	2,290
PSVS2091	5-35	1,93
PSVS2550	5-34	1,510
PSVS2551	5-35	0,93
PSVS2553	5-35	0,79
PSVS2570	5-34	2,140
PSVS2571	5-35	1,7
PSVS2573	5-35	1,51
PSVS2590	5-34	2,820
PSVS2591	5-35	2,44
PSVS2593	5-35	2,2
PSVS3050	5-34	1,810
PSVS3051	5-35	1,53
PSVS3070	5-34	2,550
PSVS3071	5-35	1,78
PSVS3090	5-34	3,380
PSVS3091	5-35	2,62
PSVS3550	5-34	2,030
PSVS3551	5-35	1,06
PSVS3553	5-35	1,34
PSVS3570	5-34	2,970
PSVS3571	5-35	2
PSVS3573	5-35	2,25
PSVS3590	5-34	3,860
PSVS3591	5-35	2,96
PSVS3593	5-35	3,17
PSVS4050	5-34	2,330
PSVS4070	5-34	3,350
PSVS4090	5-34	4,410
PSVS5050	5-34	2,830
PSVS5052	5-35	1,52
PSVS5053	5-35	1,13
PSVS5070	5-34	4,130
PSVS5072	5-35	2,79
PSVS5073	5-35	1,98

Code	Page	Weight KG
PSVS5090	5-34	5,320
PSVS5092	5-35	4,07
PSVS5093	5-35	2,79
PSVS6050	5-34	3,610
PSVS6070	5-34	5,130
PSVS6090	5-34	6,730
PSVW5061	5-25	6,380
PSVW5081	5-25	12,390
PSVW6041	3-96	9,13
PSVW6041	5-25	9,13
PSVW6042	3-96	11,04
PSVW6042	5-25	11,04
PSVW6062	5-25	12,260
PSVW6064	5-25	11,5150
PSVW6082	5-25	15,340
PSVW6084	5-25	14,7950
PSVW6126	5-25	19,245
PSVW7016	5-25	16,730
PSVW7126	5-25	20,040
PTAB1076	2-26	12
PTAB1096	2-26	15
PTAB3070	2-26	6,301
PTAB3090	2-26	9,822
PTAB4070	2-26	6,301
PTAB4090	2-26	9,822
PTAB6076	2-26	5,373
PTAB6096	2-26	6,725
PTAB8076	2-26	6,918
PTAB8096	2-26	8,659
PTBB1012	2-22	
PTBB1020	2-22	4,50
PTBB1020	6-11	4,50
PTBB1026	2-19	4,690
PTBB1026	6-10	4,690
PTBB1026	6-29	4,690
PTBB1030	2-22	6
PTBB1030	6-11	6
PTBB1036	2-19	6,080
PTBB1036	6-10	6,080
PTBB1036	6-29	6,080
PTBB1050	2-22	9
PTBB1050	6-11	9
PTBB1050	6-29	9
PTBB1056	2-19	9,20
PTBB1056	6-10	9,20
PTBB1056	6-28	9,20
PTBB1056	6-29	9,20
PTBB1070	2-22	12
PTBB1070	6-11	12

List of codes

Code	Page	Weight KG
PTBB1070	6-29	12
PTBB1076	2-19	11,90
PTBB1076	6-10	11,90
PTBB1076	6-28	11,90
PTBB1076	6-29	11,90
PTBB1090	2-22	14,50
PTBB1090	6-11	14,50
PTBB1090	6-29	14,50
PTBB1096	2-19	14,850
PTBB1096	6-10	14,850
PTBB1096	6-28	14,850
PTBB1096	6-29	14,850
PTBB1212	2-22	
PTBB1220	2-22	5,50
PTBB1220	6-11	5,50
PTBB1230	2-19	5,8
PTBB1230	6-11	5,8
PTBB1250	6-11	11
PTBB1270	6-11	14,08
PTBB1290	2-22	18
PTBB1290	6-11	18
PTBB2520	6-11	1,56
PTBB2526	6-10	1,5
PTBB2526	6-29	1,5
PTBB2530	6-11	1,98
PTBB2536	6-10	2,02
PTBB2536	6-29	2,02
PTBB2550	6-11	3
PTBB2556	6-10	3,068
PTBB2556	6-29	3,068
PTBB2570	6-11	4
PTBB2576	6-10	4,08
PTBB2576	6-29	4,08
PTBB2590	6-11	4,6
PTBB2596	6-10	5
PTBB2596	6-29	5
PTBB3012	2-22	
PTBB3020	2-22	1,750
PTBB3026	2-19	1,790
PTBB3030	2-22	2,330
PTBB3036	2-19	2,360
PTBB3050	2-22	3,450
PTBB3050	6-11	3,450
PTBB3056	2-19	3,460
PTBB3056	6-10	3,460
PTBB3056	6-29	3,460
PTBB3070	2-22	4,50
PTBB3076	2-19	4,180

Code	Page	Weight KG
PTBB3090	2-22	5,540
PTBB3096	2-19	5,5350
PTBB4012	2-22	
PTBB4020	2-22	2,10
PTBB4026	2-19	2,20
PTBB4030	2-22	2,870
PTBB4036	2-19	2,90
PTBB4050	2-22	4,20
PTBB4056	2-19	3,90
PTBB4070	2-22	5,4250
PTBB4076	2-19	5,20
PTBB4090	2-22	6,850
PTBB4096	2-19	7,0580
PTBB5020	6-11	2,4
PTBB5026	6-10	2,56
PTBB5026	6-29	2,56
PTBB5050	2-21	5,050
PTBB5050	6-10	5,050
PTBB5050	6-29	5,050
PTBB5057	6-11	5
PTBB5070	6-11	6,5
PTBB5076	6-10	6,73
PTBB5076	6-29	6,73
PTBB5090	6-11	8
PTBB5096	6-10	8,21
PTBB5096	6-29	8,21
PTBB6012	2-22	
PTBB6020	2-22	2,980
PTBB6026	2-19	3,0320
PTBB6030	2-22	3,9250
PTBB6036	2-19	3,5270
PTBB6050	2-22	5,80
PTBB6050	6-29	5,80
PTBB6056	2-19	5,2150
PTBB6056	6-28	5,2150
PTBB6070	2-22	7,60
PTBB6070	6-29	7,60
PTBB6076	2-19	7,660
PTBB6076	6-28	7,660
PTBB6090	2-22	9,50
PTBB6090	6-29	9,50
PTBB6096	2-19	9,250
PTBB6096	6-28	9,250
PTBB7070	2-21	9
PTBB7520	6-11	3,48
PTBB7526	6-10	3,56
PTBB7526	6-29	3,56
PTBB7530	6-11	4,64
PTBB7536	6-10	5

Code	Page	Weight KG
PTBB7536	6-29	5
PTBB7550	6-11	7
PTBB7556	6-10	7,165
PTBB7556	6-29	7,165
PTBB7570	6-11	9,5
PTBB7576	6-10	9,5
PTBB7576	6-29	9,5
PTBB7590	6-11	11,6
PTBB7596	6-10	12,04
PTBB7596	6-29	12,04
PTBB8012	2-22	
PTBB8020	2-22	3,730
PTBB8026	2-19	3,480
PTBB8030	2-22	5
PTBB8036	2-19	4,4740
PTBB8050	2-22	7,40
PTBB8050	6-29	7,40
PTBB8056	2-19	7,430
PTBB8056	6-28	7,430
PTBB8070	2-22	9,850
PTBB8070	6-29	9,850
PTBB8076	2-19	9,760
PTBB8076	6-28	9,760
PTBB8090	2-22	12,50
PTBB8090	6-29	12,50
PTBB8096	2-19	12,490
PTBB8096	6-28	12,490
PTBB9090	2-21	13,50
PTBO1030	2-24	4,080
PTBO1030	6-13	4,080
PTBO1050	2-24	5,060
PTBO1050	6-13	5,060
PTBO1050	6-31	5,060
PTBO1070	2-24	5,770
PTBO1070	6-13	5,770
PTBO1070	6-31	5,770
PTBO1090	2-24	6,860
PTBO1090	6-13	6,860
PTBO1090	6-31	6,860
PTBO1230	6-13	6
PTBO1231	2-20	4,637
PTBO1250	6-13	7,2
PTBO1251	2-20	6,806
PTBO1270	6-13	8,6
PTBO1271	2-20	9,074
PTBO1290	2-24	12,060
PTBO1290	6-13	12,060
PTBO1291	2-20	11,343
PTBO1431	2-20	4,8

List of codes

Code	Page	Weight KG
PTBO1451	2-20	5,8
PTBO1471	2-20	7
PTBO1491	2-20	8
PTBO2520	6-13	1,406
PTBO2530	6-13	1,83
PTBO2550	6-13	2,6
PTBO2570	6-13	3,3
PTBO2590	6-13	4
PTBO3020	2-24	1,290
PTBO3030	2-24	2,060
PTBO3050	2-24	2,780
PTBO3050	6-13	2,780
PTBO3070	2-24	3,080
PTBO3090	2-24	3,710
PTBO4020	2-24	1,630
PTBO4030	2-24	2,460
PTBO4050	2-24	2,80
PTBO4070	2-24	3,470
PTBO4090	2-24	4,2450
PTBO5020	6-13	2,4
PTBO5050	6-13	3,55
PTBO5052	6-40	
PTBO5055	6-40	
PTBO5070	6-13	4,29
PTBO5072	6-40	
PTBO5075	6-40	
PTBO5090	6-13	5
PTBO5092	6-40	
PTBO5095	6-40	
PTBO6020	2-24	2,30
PTBO6030	2-24	2,6420
PTBO6050	2-24	3,2630
PTBO6050	6-31	3,2630
PTBO6070	2-24	4,250
PTBO6070	6-31	4,250
PTBO6090	2-24	5,0070
PTBO6090	6-31	5,0070
PTBO7520	6-13	3,14
PTBO7530	6-13	3,57
PTBO7550	6-13	4,47
PTBO7570	6-13	5,29
PTBO7590	6-13	6,2
PTBO8020	2-24	3
PTBO8030	2-24	3,2380
PTBO8050	2-24	4,650
PTBO8050	6-31	4,650
PTBO8070	2-24	5,030
PTBO8070	6-31	5,030
PTBO8090	2-24	5,930

Code	Page	Weight KG
PTBO8090	6-31	5,930
PTBO8231	2-20	4
PTBO8251	2-20	5,6
PTBO8271	2-20	6,2
PTBO8291	2-20	7,2
PTBS1001	5-28	2,650
PTBS1020	5-27	2,820
PTBS1030	5-27	3,860
PTBS1050	5-27	6,530
PTBS1052	5-28	3,430
PTBS1052	5-44	3,430
PTBS1052	5-47	3,430
PTBS1070	5-27	8,920
PTBS1072	5-28	5,750
PTBS1072	5-44	5,750
PTBS1072	5-47	5,750
PTBS1090	5-27	11,079
PTBS8001	5-28	2,110
PTBS8020	5-27	2,240
PTBS8030	5-27	3,10
PTBS8050	5-27	5,050
PTBS8052	5-28	2,30
PTBS8052	5-44	2,30
PTBS8052	5-47	2,30
PTBS8070	5-27	6,930
PTBS8072	5-28	4,560
PTBS8072	5-44	4,560
PTBS8072	5-47	4,560
PTBS8090	5-27	9,07
PTBS8091	5-28	6,640
PTBS8091	5-44	6,640
PTBS8091	5-47	6,640
PTHS1052	5-31	3,840
PTHS1072	5-31	6,240
PTHS1092	5-31	8,570
PTHS1292	5-31	10,570
PTHS2030	5-30	0,850
PTHS2050	5-30	1,320
PTHS2052	5-32	0,750
PTHS2070	5-30	1,80
PTHS2072	5-32	1,250
PTHS2090	5-30	2,350
PTHS2092	5-32	1,720
PTHS3030	5-30	1,460
PTHS3050	5-30	2,280
PTHS3052	5-32	1,360
PTHS3070	5-30	3,340
PTHS3072	5-32	2,270
PTHS3090	5-30	4,240

Code	Page	Weight KG
PTHS3092	5-32	3,2750
PTHS4030	5-29	1,80
PTHS4030	5-30	1,80
PTHS4050	5-29	2,80
PTHS4050	5-30	2,80
PTHS4052	5-31	1,460
PTHS4070	5-29	4
PTHS4070	5-30	4
PTHS4072	5-31	2,930
PTHS4092	5-31	4,090
PTHS4152	5-32	1,740
PTHS4172	5-32	2,870
PTHS4190	5-30	5,120
PTHS4192	5-32	4,080
PTHS4230	5-30	1,560
PTHS4250	5-30	2,880
PTHS4252	5-32	1,420
PTHS4270	5-30	3,40
PTHS4272	5-32	2,370
PTHS4290	5-30	4,390
PTHS4292	5-32	3,350
PTHS6030	5-29	2,420
PTHS6050	5-29	3,990
PTHS6052	5-31	2,410
PTHS6070	5-29	5,710
PTHS6072	5-31	4,050
PTHS6092	5-31	5,650
PTHS8030	5-29	3,160
PTHS8050	5-29	5,070
PTHS8052	5-31	3,120
PTHS8070	5-29	7,080
PTHS8072	5-31	5,110
PTHS8092	5-31	7,150
PTRN1951	4-34	0,3530
PTRS1201	4-34	1,3450
PTRS1601	4-34	1,5450
PTRS2001	4-34	1,740
PTVB1091	5-28	8,310
PTVB1091	5-44	8,310
PTVB1091	5-47	8,310
PTVS1001	5-28	2,060
PTVS1020	5-27	2,510
PTVS1030	5-27	3,270
PTVS1050	5-27	5,3650
PTVS1052	5-28	2,950
PTVS1070	5-27	7,440
PTVS1072	5-28	7,890
PTVS1091	5-28	7,260
PTVS8001	5-28	1,6650

List of codes

Code	Page	Weight KG
PTVS8020	5-27	2
PTVS8030	5-27	2,830
PTVS8050	5-27	4,290
PTVS8052	5-28	2,30
PTVS8070	5-27	5,950
PTVS8072	5-28	4,060
PTVS8091	5-28	5,710
PUCM1800	2-14	3
PUCM1800	6-40	3
PUCM2000	2-14	3,50
PUCM2000	6-40	3,50
PUCS1800	2-15	2,830
PUCS2000	2-15	3,20
PUKI1800	3-69	2,870
PUKI1800	5-23	2,870
PUKI1800	5-27	2,870
PUKI1800	5-33	2,870
PUKI1800	5-48	2,870
PUKI1800	6-27	2,870
PUKI2000	3-69	3,30
PUKI2000	5-23	3,30
PUKI2000	5-27	3,30
PUKI2000	5-33	3,30
PUKI2000	5-48	3,30
PUKI2000	6-27	3,30
PUPM1800	2-13	15,380
PUPM1800	2-39	15,380
PUPM1800	6-8	15,380
PUPM1800	6-27	15,380
PUPM1802	2-13	16,80
PUPM2000	2-13	16,50
PUPM2000	2-39	16,50
PUPM2000	6-8	16,50
PUPM2000	6-27	16,50
PUPM2002	2-13	19,80
PVBE1241	3-88	4,790
PVBE1241	3-88	4,790
PVBT4404	3-83	5,010
PVBT4406	3-83	4,550
PVBT4406	3-83	4,550
PVBT4423	3-83	5,40
PVBT5319	3-83	5,1
PVBT5404	3-83	4,910
PVBT5406	3-83	4,50
PVBT5406	3-83	4,50
PVBT5409	3-83	4,5
PVBT5412	3-83	5,860
PVBT5414	3-83	4,470
PVBT5414	3-83	4,470

Code	Page	Weight KG
PVBT5423	3-83	5,40
PVBT5426	3-83	4,440
PVBT5426	3-83	4,440
PVBT5428	3-83	5,250
PVBT6312	3-83	6,690
PVBT6314	3-83	5,010
PVBT6314	3-83	5,010
PVBT6401	3-83	5,210
PVBT6404	3-83	4,980
PVBT6405	3-83	5,140
PVBX1401	3-82	4,1250
PVBX1404	3-82	4,090
PVBX1405	3-82	4,1250
PVBX1407	3-82	4,180
PVBX1409	3-82	4,510
PVBX1423	3-82	4,20
PVBX1427	3-82	4,090
PVBX2400	3-82	4,070
PVBX2401	3-82	4,040
PVBX2404	3-82	4,110
PVBX2405	3-82	4,10
PVBX2407	3-82	4,080
PVBX2409	3-82	4,420
PVBX2410	3-82	4,10
PVBX2412	3-82	4,510
PVBX2417	3-82	4,350
PVBX2423	3-82	4,570
PVBX2427	3-82	4,080
PVBX3401	3-82	4,060
PVBX3404	3-82	3,980
PVBX3405	3-82	4,040
PVBX3407	3-82	4,030
PVBX3409	3-82	34,90
PVBX3423	3-82	5,030
PVBX3427	3-82	4,110
PVBX4400	3-83	4,80
PVBX4401	3-82	4,060
PVBX4404	3-83	4,130
PVBX4405	3-83	4,160
PVBX4407	3-83	6,130
PVBX4409	3-83	4,570
PVBX4410	3-83	4,470
PVBX4412	3-83	4,50
PVBX4417	3-83	4,80
PVBX4423	3-83	3,870
PVBX4427	3-83	4,410
PVCE1240	3-88	6,820
PVCE1240	3-88	6,820

Code	Page	Weight KG
PVCE1241	3-88	6,920
PVCE1241	3-88	6,920
PVCE2441	3-89	6,880
PVCE2441	3-89	6,880
PVCE2442	3-89	7,160
PVCE2450	3-89	6,880
PVCE2450	3-89	6,880
PVCE4350	3-89	7
PVCE4350	3-89	7
PVCT4404	3-85	6,770
PVCT4406	3-85	6,250
PVCT4406	3-85	6,250
PVCT4423	3-85	7,460
PVCT5307	3-85	7
PVCT5404	3-85	6,710
PVCT5406	3-85	6,240
PVCT5406	3-85	6,240
PVCT5407	3-85	3,9
PVCT5409	3-85	5,2
PVCT5412	3-85	7,820
PVCT5414	3-85	6,070
PVCT5414	3-85	6,070
PVCT5423	3-85	7,450
PVCT5426	3-85	6,20
PVCT5426	3-85	6,20
PVCT5428	3-85	7,490
PVCT5430	3-85	5,2
PVCT5601	3-85	6,8
PVCT5710	3-85	7,4
PVCT5712	3-85	
PVCT5712	3-85	
PVCT6401	3-85	8,860
PVCT6404	3-85	7,370
PVCT6405	3-85	6,90
PVCT6412	3-85	9,380
PVCT6414	3-85	7,320
PVCT6414	3-85	7,320
PVCT7413	3-85	6,880
PVCT7413	3-86	6,880
PVCT7413	3-86	6,880
PVCT7419	3-85	7,440
PVCX1301	3-83	5,4
PVCX1401	3-83	5,670
PVCX1404	3-83	5,650
PVCX1405	3-83	5,6950

List of codes

Code	Page	Weight KG
PVCX1407	3-83	5,690
PVCX1409	3-83	6,080
PVCX1423	3-84	5,780
PVCX1427	3-84	5,620
PVCX1707	3-83	5,760
PVCX2400	3-84	5,560
PVCX2401	3-84	5,650
PVCX2404	3-84	4,890
PVCX2405	3-84	5,670
PVCX2407	3-84	5,560
PVCX2409	3-84	6,760
PVCX2410	3-84	5,640
PVCX2412	3-84	6,090
PVCX2417	3-84	6,220
PVCX2423	3-84	6,250
PVCX2427	3-84	5,630
PVCX2701	3-84	5,650
PVCX2707	3-84	6,210
PVCX3301	3-84	5,6
PVCX3401	3-84	5,510
PVCX3404	3-84	5,590
PVCX3405	3-84	5,610
PVCX3407	3-84	5,580
PVCX3409	3-84	5,950
PVCX3423	3-84	7
PVCX3427	3-84	5,560
PVCX3607	3-84	5,650
PVCX3707	3-84	5,430
PVCX4400	3-85	6,270
PVCX4401	3-84	5,550
PVCX4404	3-84	5,540
PVCX4405	3-84	5,610
PVCX4407	3-84	6,120
PVCX4409	3-85	6,670
PVCX4410	3-85	6,240
PVCX4412	3-85	6,770
PVCX4417	3-85	6,60
PVCX4423	3-85	6,860
PVCX4427	3-85	6,120
PVCX4601	3-84	5,660
PVCX4607	3-84	5,90
PVCX4701	3-84	5,530
PVCX4707	3-84	5,70
PVDE1240	3-88	9,1450
PVDE1240	3-88	9,1450
PVDE1241	3-88	8,970
PVDE1241	3-88	8,970
PVDE1262	3-88	8,140
PVDE2440	3-89	9,150

Code	Page	Weight KG
PVDE2440	3-89	9,150
PVDE2440	3-89	9,150
PVDE2441	3-89	10,810
PVDE2441	3-89	10,810
PVDT5404	3-86	8,510
PVDT5406	3-86	8,110
PVDT5406	3-86	8,110
PVDT5407	3-86	4,8
PVDT5409	3-86	6,5
PVDT5412	3-86	9,980
PVDT5414	3-86	7,840
PVDT5414	3-86	7,840
PVDT5423	3-87	9,790
PVDT5426	3-86	7,980
PVDT5426	3-86	7,980
PVDT5428	3-87	9,560
PVDT5430	3-86	6,5
PVDT5601	3-86	9,85
PVDT5610	3-86	7,530
PVDT5612	3-86	9,580
PVDT5701	3-87	9,5
PVDT5810	3-87	10
PVDT5813	3-86	
PVDT6401	3-87	8,8250
PVDT6404	3-87	9,320
PVDT6405	3-87	5,570
PVDT6412	3-87	11,780
PVDT6414	3-87	9,640
PVDT6414	3-87	9,640
PVDT7413	3-87	7,880
PVDT7413	3-87	7,880
PVDT7413	3-87	7,880
PVDT7419	3-87	8,90
PVDX1807	3-86	6,690
PVDX2801	3-86	6,960
PVDX2807	3-86	6,520
PVDX3707	3-86	7,040
PVDX3807	3-86	6,50
PVDX4701	3-86	6,870
PVDX4707	3-86	7,160
PVDX4801	3-86	6,850
PVDX4807	3-86	7,170

Code	Page	Weight KG
PVFE1263	3-88	10,610
PVFE6230	3-89	24,060
PVFE6230	3-89	24,060
PVFE6231	3-89	25,630
PVFE6231	3-89	25,630
PVFT5710	3-87	9,10
PVFT5712	3-87	11,40
PVFT5810	3-87	8,890
PVFT5812	3-87	11,280
PVFT6610	3-87	11,480
PVFT6610	3-87	11,480
PVFT6612	3-87	13,920
PVFT7633	3-87	10,880
PVFT7633	3-87	10,880
PVGE2440	3-89	15
PVGE6230	3-89	26,860
PVGE6230	3-89	26,860
PVGE6231	3-89	30,60
PVGE6231	3-89	30,60
PWRP1640	3-93	16,2
PWRP1660	3-93	22,6
PWRP1680	3-93	30,6
PWRP1840	3-93	20,2
PWRP1860	3-93	26,4
PWRP1880	3-93	34,5
PWRP2040	3-93	21
PWRP2060	3-93	30
PWRP2080	3-93	37,2
PXLPO040	3-91	
PXLPO060	3-91	
PXLPO140	3-91	
PXLPO160	3-91	
PXLPO240	3-91	
PXLPO260	3-91	
PXLPO340	3-91	
PXLPO360	3-91	
TS4011	4-44	2
TS4012	4-44	2
TS4013	4-44	1,960
ZN1041	2-17	1,3670

Contact**ABB SACE****A division of ABB S.p.A.****Automation and Distribution Boards**

Via Italia, 58

23846 Garbagnate Monastero (LC) - Italy

Tel: +39 031 3570.111

Fax: +39 031 3570.228

www.abb.com

Due to possible developments of standards as well as of materials, the characteristics and dimensions specified in this document may only be considered binding after confirmation by ABB SACE.

