


FurseWELD

Cable to reinforcing bar CRE6 & CRE17

Cable to reinforcing bar CRE6 - FurseWELD

Reinforcing bar size A \varnothing (mm)	Stranded/solid circular conductor size B (mm ²)	Mould part no.	Order code	Powder cartridge part no.	Handle clamp part no.	Packing part no.
10-40	16 *	CRE6-3-16	7TCA083910R1973	45P10	HCPK3-A	PACK-A
10-40	25	CRE6-3-25	7TCA083910R1974	45P10	HCPK3-A	PACK-A
10-40	35	CRE6-3-35	7TCA083910R1975	45P10	HCPK3-A	PACK-A
10-40	\varnothing 8	CRE6-3-8SC	7TCA083910R1978	65P10	HCPK3-A	PACK-A
10-40	50	CRE6-3-50	7TCA083910R1976	65P10	HCPK3-A	PACK-A
10-40	70	CRE6-3-70	7TCA083910R1977	90P10	HCPK3-A	PACK-A
10-40	95	CRE6-4-95	7TCA083910R1979	90P10	HCPK3-A	PACK-A
10-40	120	CRE6-4-120	7TCA083910R1980	115P10	HCPK3-A	PACK-A



Special moulds for all FurseWELD products can be manufactured to meet specific customer applications on request

*1 x S103 Sleeve required when joining conductors 16 mm² or smaller

For order codes of powder cartridges, handle clamps and packing, see pages 49-50


FurseWELD moulds should only be used with FurseWELD powders, handle clamps and accessories. If moulds, powders, handle clamps and accessories from other manufacturers are utilized, we cannot guarantee the safe use or the integrity of the completed joint

FurseWELD moulds for use with stranded conductor are designed for use with non-compacted conductor to BS EN 60228. If a mould for compacted conductor is required, please contact your local representative

Conductors must be installed in the orientation shown to achieve the correct connection

Cable to reinforcing bar CRE17 - FurseWELD

Reinforcing bar size A \varnothing (mm)	Stranded/solid circular conductor size B (mm ²)	Mould part no.	Order code	Powder cartridge part no.	Handle clamp part no.	Packing part no.
10-40	16 *	CRE17-3-16	7TCA083910R1848	45P10	HCPK3-B	PACK-A
10-40	25	CRE17-3-25	7TCA083910R1850	45P10	HCPK3-B	PACK-A
10-40	35	CRE17-3-35	7TCA083910R1852	45P10	HCPK3-B	PACK-A
10-40	\varnothing 8	CRE17-3-8SC	7TCA083910R3004	90P10	HCPK3-B	PACK-A
10-40	50	CRE17-3-50	7TCA083910R1853	90P10	HCPK3-B	PACK-A
10-40	70	CRE17-3-70	7TCA083910R1854	90P10	HCPK3-B	PACK-A
10-40	95	CRE17-3-95	7TCA083910R1855	90P10	HCPK3-B	PACK-A
10-40	120	CRE17-3-120	7TCA083910R1846	90P10	HCPK3-B	PACK-A



Special moulds for all FurseWELD products can be manufactured to meet specific customer applications on request

*1 x S103 Sleeve required when joining conductors 16 mm² or smaller

For order codes of powder cartridges, handle clamps and packing, see pages 49-50

FurseWELD moulds should only be used with FurseWELD powders, handle clamps and accessories. If moulds, powders, handle clamps and accessories from other manufacturers are utilized, we cannot guarantee the safe use or the integrity of the completed joint

FurseWELD moulds for use with stranded conductor are designed for use with non-compacted conductor to BS EN 60228. If a mould for compacted conductor is required, please contact your local representative

Conductors must be installed in the orientation shown to achieve the correct connection