

# CERTIFICATE OF COMPLIANCE

**Certificate Number** E48139  
**Report Reference** E48139-19970507  
**Issue Date** 2020-MARCH-25

**Issued to:** ABB Stotz-Kontakt GmbH  
Eppelheimer Str 82  
69123 Heidelberg GERMANY

**This certificate confirms that representative samples of** AUXILIARY DEVICES  
See next page for models.

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

**Standard(s) for Safety:** UL 60947-1 and CSA C22.2 No. 60947-1-13, Low Voltage Switchgear and Controlgear, Part 1: General Rules  
UL 60947-4-1 and CSA C22.2 No. 60947-4-1-14, Low Voltage Switchgear and Controlgear, Part 4-1: Contactors and Motor Starters, Electromechanical Contactors and Motor-Starters.

**Additional Information:** See the UL Online Certifications Directory at Fehler! Linkreferenz ungültig. for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>




# CERTIFICATE OF COMPLIANCE

**Certificate Number** E48139  
**Report Reference** E48139-19970507  
**Issue Date** 2020-MARCH-25

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

**Models:**

Overload relay, open type Class 10 device Cat. No. TA25DU, followed by .16, .25, .4, .63, 1.0, 1.4, 1.8, 2.4, 3.1, 4.0, 5.0, 6.5, 8.5, 11, 14, 19, 25 or 32, may be followed by M, may be followed by -V1000;  
Class 20 device Cat. No. TA25DU, followed by 1.8, 2.4, 3.1, 4.0, 5.0, 6.5, 8.5, 11, 14, 19, 25 or 32;  
Terminal block adapters, DB25/25A, DB25/32A and DX25 may be followed by -M



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

