

# CERTIFICATE OF COMPLIANCE

**Certificate Number** E76126  
**Report Reference** E76126-20211227  
**Date** 2022-March-02

**Issued to:** ABB STOTZ-KONTAKT GmbH  
ABB  
Eppelheimer Str. 82  
Heidelberg 69123 DE

**This is to certify that  
representative samples of**

PROTECTORS, SUPPLEMENTARY - COMPONENT  
See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

**Standard(s) for Safety:**

UL 1077 - Supplementary Protectors for Use in Electrical Equipment

CSA C22.2 No. 235-04 - Supplementary Protectors

**Additional Information:**

See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information

This *Certificate of Compliance* does not provide authorization to apply the UL Recognized Component Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/locations/>

# CERTIFICATE OF COMPLIANCE

**Certificate Number** E76126  
**Report Reference** E76126-20211227  
**Date** 2022-March-02

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Cat. Nos. S301P, S302P, S303P and S304P followed by K followed by 0.2,0.3 or 0.75

Cat. Nos. S301P, S302P, S303P and S304P may be followed by C, D, Z or K followed by 0.5, 0.75, 1, 1.6, 2, 2.5, 3, 4 or 5

Cat. Nos. S301P, S302P, S303P and S304P followed by B, C, D, K followed by 6,7,8,10,13,15,16,20,25,30,32,35,40,50,60 or 63.

Cat. Nos. S301P, S302P, S303P and S304P followed by B, C, D, K or Z followed by 6,7,8,10,15,16,20,25,30,32,35,40,50,60 or 63.



Bruce Mahrenholz, Director North American Certification Program

UL LLC



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/locations/>