


保密文件，经手人赋有保密义务；未经授权而披露，权利人享有追偿权利

MS132-20T (16...20A)

Transformatorschutzschalter / Circuit breaker for transformer protection



We reserve all rights in this document and in the information contained therein. Reproduction, use or disclosure to third parties without express authority is strictly forbidden. ©Copyright 2014 ABB.

Für dieses Dokument und den darin dargestellten Gegenstand behalten wir uns alle Rechte vor. Vervielfältigung, Bekanntheit an Dritte oder Verwertung seines Inhalts sind ohne unsere ausdrückliche Zustimmung verboten. ©Copyright 2014 ABB.

Auslösekennlinie (aus kaltem Zustand)
 Die Ansprechwerte der elektromagnet. Auslöser beziehen sich auf Skala Maximum I_{e,max}
 Für Nennströme (3-polig) zwischen dem 3- und 8-fachen des Einstellwertes beträgt die Toleranz der Auslösezeit ±20%
 Tripping characteristic (from cold state)
 The values of the electromagn. release refer to scale maximum
 For currents (3-pole) between 3 and 8 times the current setting the tolerance of the tripping time is ±20%

F13

| | | | | | | |
|------------------------------------|----------------|----------------|------------|----------------------------|---------------------|---|
| Proprietary and Secret Information | Created by | Frank Hustert | Checked by | Michael Konrad | Approved by | Richard Kommer |
| | Created on | 2014-07-07 | Checked on | 2014-07-10 | Approved on | 2014-07-11 |
| | ECN number | ECN000006524 | ECN date | 17-07-14 | Department | CLD |
| | Revision index | B 1 | PRU | DESTO | Scale | % |
| | Partname | MODEL NAME B.2 | | Drawing | 1SAM300535_F013 B.2 | |
| | | Title (de) | | Auslösekennlinie MS132-20T | | Format A4 Language DE/EN Sheet No. 13 No. Sheets 17 (B) |
| | | Title (en) | | Tripping characteristic | | 1SAM300535 |