Automation Products AC500-eCo Product News AC500-eCo CPUs

New AC500-eCo CPUs for use with pluggable terminal blocks New compatible CPUs Identical terminal blocks for CPUs and S500-eCo I/O modules



Features of new CPUs

New AC500-eCo CPUs for use with pluggable terminal blocks are available.

In the fixed terminal CPUs, one pair of screw type terminal blocks is mounted to the CPU and cannot be removed. In the new CPUs, the terminal blocks can be removed.

- The new CPUs have the same mechanical dimensions, compatible hardware and can be used with the same options and accessories as the fixed terminal CPU assortment.
- The new CPUs offer the same specifications and features and can be used as replacement for the fixed terminal CPU assortment.
- You can choose between three types of terminal blocks for the CPU. The terminal blocks have to be ordered separately.

- Pluggable terminal blocks are used for the onboard I/O channels – the position of all signals on the CPU and the terminal blocks remains unchanged.
- All types of terminal blocks used for the S500eCo I/O modules can also be used with the new AC500-eCo CPUs.

Advantages

- The deliveries of the new CPUs start with Firmware version V2.3.x which is supported by the released Automation Builder 1.0 and later versions.
- Three types of terminal blocks are available and can be ordered separately.
- Pre-wiring of panels without CPU is now possible.
- The CPU can be replaced easily.
- The CPU can be installed later during commissioning.

Power and productivity for a better world™



Automation Products AC500-eCo Product News AC500-eCo CPUs

Change in ordering procedure

The new CPUs have

- a different type identifier (Product Designation/Product Type) and a different order code.
- They are delivered without terminal blocks for the onboard I/O channels.
- The terminal blocks have to be ordered separately. Each CPU requires one nine pole and one eleven pole terminal block.

New order codes and new type designators

The letter **P** is the differentiator in the new product designation. P stands for "pluggable":

Fixed terminal CPUs Product Designation	Order code (with terminal blocks)		New Product Designation	Order code (without terminal blocks)
PM554-R	1TNE968900R0200	\rightarrow	PM554-R P	1SAP120700R0001
PM554-R-AC	1TNE968900R0220	\rightarrow	PM554-R P -AC	1SAP120800R0001
PM554-T	1TNE968900R0100	\rightarrow	PM554-T P	1SAP120600R0001
PM554-T-ETH	1TNE968900R0110	\rightarrow	PM554-T P -ETH	1SAP120600R0071
PM564-R	1TNE968900R1200	\rightarrow	PM564-R P	1SAP121000R0001
PM564-R-AC	1TNE968900R1220	\rightarrow	PM564-R P -AC	1SAP121100R0001
PM564-R-ETH	1TNE968900R1210	\rightarrow	PM564-R P -ETH	1SAP121000R0071
PM564-R-ETH-AC	1TNE968900R1211	\rightarrow	PM564-R P -ETH-AC	1SAP121100R0071
PM564-T	1TNE968900R1100	\rightarrow	PM564-T P	1SAP120900R0001
PM564-T-ETH	1TNE968900R1110	\rightarrow	PM564-T P -ETH	1SAP120900R0071



20.12.2013

Automation Products AC500-eCo Product News AC500-eCo CPUs

Terminal blocks suitable for the new CPU modules

For each new CPU one nine pole and one eleven pole terminal block is required. The terminal blocks for AC500-eCo CPUs and S500-eCo I/O modules are identical. You can now also choose between three types of terminal blocks for the CPU.

Description Product		Order code for 9	Product	Order code for 11
	Designation for	pole terminal blocks	Designation for	pole terminal blocks
	9 pole terminal	(Quantity:	11 pole terminal	(Quantity:
	block	6 pieces)	block	6 pieces)
Screw type terminal block with cable insertion from the side	TA563-9	1TNE968901R3101	TA563-11	1TNE968901R3102
Screw type terminal block with cable insertion from the front	TA564-9	1TNE968901R3103	TA564-11	1TNE968901R3104
Spring type terminal block with cable insertion from the front	TA565-9	1TNE968901R3105	TA565-11	1TNE968901R3106



Product News ACM-34/2013

Automation Products AC500-eCo Product News AC500-eCo CPUs

ABB Automation Products GmbH

Wallstadter Str. 59 68526 Ladenburg Germany Phone: +49 (0) 6221 701-1444 Fax: +49 (0) 6221 701-1382 Email: plc.sales@de.abb.com

www.abb.com/plc

www.abb.com/drives

Note:

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB AG does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its contents – in whole or in parts – is forbidden without prior written consent of ABB AG.

Copyright© 2013 ABB - All rights reserved

20.12.2013